

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: January 20, 2018

H. Hong
J. Jeong
J. Kim
Sungkyunkwan University
S. Hares
L. Xia
Huawei
July 19, 2017

I2NSF Network Security Function Monitoring YANG Data Model
draft-hong-i2nsf-nsf-monitoring-data-model-00

Abstract

This document proposes a YANG data model for monitoring Network Security Functions (NSFs) in the Interface to Network Security Functions (I2NSF) system. If the monitoring of NSFs is performed in a timely and comprehensive way, it is possible to detect the indication of malicious activity, anomalous behavior or the potential sign of denial of service attacks. This monitoring functionality is based on the monitoring information that is generated by NSFs. Thus, this document describes not only a data tree to specify monitoring information model but also a YANG data model for monitoring NSFs.

Status of This Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on January 20, 2018.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Requirements Language	3
3.	Terminology	3
3.1.	Tree Diagrams	3
4.	Information Model Structure	4
5.	YANG Data Model	12
6.	Acknowledgments	45
7.	References	45
7.1.	Normative References	45
7.2.	Informative References	45

1. Introduction

This document defines a YANG [[RFC6020](#)] data model for monitoring Network Security Functions (NSFs). This monitoring means the acquisition of vital information about NSFs via notifications, events, records or counters. The data model for the monitoring presented in this document is derived from the information model for the security policy provisioning of the NSF-Facing Interface specified in [[i2nsf-monitoring-im](#)].

2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

3. Terminology

This document uses the terminology described in [[i2nsf-terminology](#)][i2nsf-framework]. Especially, the following terms are from [[i2nsf-monitoring-im](#)].

- o Information Model: An information model is a representation of concepts of interest to an environment in a form that is independent of data repository, data definition language, query language, implementation language, and protocol.
- o Data Model: A data model is a representation of concepts of interest to an environment in a form that is dependent on data repository, data definition language, query language, implementation language, and protocol.

3.1. Tree Diagrams

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in these diagrams [[i2rs-rib-data-model](#)] is as follows:

- o Brackets "[" and "]" enclose list keys.
- o Abbreviations before data node names: "rw" means configuration (read-write) and "ro" state data (read-only).
- o Symbols after data node names: "?" means an optional node and "*" denotes a "list" and "leaf-list".
- o Parentheses enclose choice and case nodes, and case nodes are also marked with a colon (":").

Hong, et al.

Expires January 20, 2018

[Page 3]

- o Ellipsis ("...") stands for contents of subtrees that are not shown.

4. Information Model Structure

Figure 1 shows the overview of a structure tree of monitoring information based on the [[i2nsf-monitoring-im](#)].

```
module: ietf-i2nsf-monitoring-information
  +-+rw monitoring-message
    +-+rw monitoring-messages* [message-id]
      +-+rw message-id                                uint8
      +-+rw message-version                           uint8
      +-+rw (message-type)?
        |  +-+:(alarm)
        |  |  +-+rw (alarm-type)?
        |  |  |  +-+:(system-alarm)
        |  |  |  |  +-+rw memory-alarm
        |  |  |  |  |  +-+rw event-name                string
        |  |  |  |  |  +-+rw usage?                   uint8
        |  |  |  |  |  +-+rw threshold?              uint8
        |  |  |  |  |  +-+rw message                  string
        |  |  |  |  |  +-+rw module-name             string
        |  |  |  |  +-+rw cpu-alarm
        |  |  |  |  |  +-+rw event-name                string
        |  |  |  |  |  +-+rw usage?                   uint8
        |  |  |  |  |  +-+rw threshold?              uint8
        |  |  |  |  |  +-+rw message                  string
        |  |  |  |  +-+rw disk-alarm
        |  |  |  |  |  +-+rw event-name                string
        |  |  |  |  |  +-+rw usage?                   uint8
        |  |  |  |  |  +-+rw threshold?              uint8
        |  |  |  |  |  +-+rw message                  string
        |  |  |  |  +-+rw hardware-alarm
        |  |  |  |  |  +-+rw event-name               string
        |  |  |  |  |  +-+rw usage?                 uint8
        |  |  |  |  |  +-+rw threshold?            uint8
        |  |  |  |  |  +-+rw message                 string
        |  |  |  |  |  +-+rw component-name?       string
        |  |  |  |  +-+rw interface-alarm
        |  |  |  |  |  +-+rw event-name              string
        |  |  |  |  |  +-+rw usage?                 uint8
        |  |  |  |  |  +-+rw threshold?            uint8
        |  |  |  |  |  +-+rw message                string
        |  |  |  |  |  +-+rw interface-name?       string
        |  |  |  |  +-+rw interface-state
          |  |  |  |  |  +-+rw up                   boolean
          |  |  |  |  |  +-+rw down                 boolean
```

Hong, et al.

Expires January 20, 2018

[Page 4]

	+--rw congested	boolean
+--:(event)		
+--rw (event-type)?		
+--:(system-event)		
+--rw access-violation		
+--rw event-name	string	
+--rw user-name	string	
+--rw group	string	
+--rw login-ip	inet:ipv4-address	
+--rw authentication-mode		
+--rw local-auth	boolean	
+--rw third-part-auth	boolean	
+--rw exemption-auth	boolean	
+--rw sso-auth	boolean	
+--rw message	string	
+--rw config-change		
+--rw event-name	string	
+--rw user-name	string	
+--rw group	string	
+--rw login-ip	inet:ipv4-address	
+--rw authentication-mode		
+--rw local-auth	boolean	
+--rw third-part-auth	boolean	
+--rw exemption-auth	boolean	
+--rw sso-auth	boolean	
+--rw message	string	
+--:(nsf-event)		
+--rw ddos-event		
+--rw event-name	string	
+--rw user-name?	string	
+--rw message?	string	
+--rw src-ip?	inet:ipv4-address	
+--rw dst-ip?	inet:ipv4-address	
+--rw src-port?	inet:port-number	
+--rw dst-port?	inet:port-number	
+--rw src-zone?	string	
+--rw dst-zone?	string	
+--rw rule-id	uint8	
+--rw rule-name	string	
+--rw profile?	string	
+--rw raw-info?	string	
+--rw ddos-attack-type		
+--rw syn-flood?	boolean	
+--rw ack-flood?	boolean	
+--rw syn-ack-flood?	boolean	
+--rw finrst-flood?	boolean	
+--rw tcp-con-flood?	boolean	
+--rw udp-flood?	boolean	

Hong, et al.

Expires January 20, 2018

[Page 5]

			++-rw icmp-flood?	boolean
			++-rw https-flood?	boolean
			++-rw http-flood?	boolean
			++-rw dns-reply-flood?	boolean
			++-rw dns-query-flood?	boolean
			++-rw sip-flood?	boolean
			++-rw start-time	yang:date-and-time
			++-rw end-time	yang:date-and-time
			++-rw attack-rate?	uint32
			++-rw attack-speed?	uint32
			++-rw session-table-event	
			++-rw event-name?	string
			++-rw current-session?	uint8
			++-rw maximum-session?	uint8
			++-rw threshold?	uint8
			++-rw message?	string
			++-rw virus-event	
			++-rw event-name	string
			++-rw user-name?	string
			++-rw message?	string
			++-rw src-ip?	inet:ipv4-address
			++-rw dst-ip?	inet:ipv4-address
			++-rw src-port?	inet:port-number
			++-rw dst-port?	inet:port-number
			++-rw src-zone?	string
			++-rw dst-zone?	string
			++-rw rule-id	uint8
			++-rw rule-name	string
			++-rw profile?	string
			++-rw raw-info?	string
			++-rw virus-type	
			++-rw trajan?	boolean
			++-rw worm?	boolean
			++-rw macro?	boolean
			++-rw virus-name?	string
			++-rw file-type?	string
			++-rw file-name?	string
			++-rw intrusion-event	
			++-rw event-name	string
			++-rw user-name?	string
			++-rw message?	string
			++-rw src-ip?	inet:ipv4-address
			++-rw dst-ip?	inet:ipv4-address
			++-rw src-port?	inet:port-number
			++-rw dst-port?	inet:port-number
			++-rw src-zone?	string
			++-rw dst-zone?	string
			++-rw rule-id	uint8

Hong, et al.

Expires January 20, 2018

[Page 6]

		++-rw rule-name	string
		++-rw profile?	string
		++-rw raw-info?	string
		++-rw protocol	
		++-rw tcp?	boolean
		++-rw udp?	boolean
		++-rw icmp?	boolean
		++-rw icmpv6?	boolean
		++-rw ip?	boolean
		++-rw http?	boolean
		++-rw ftp?	boolean
		++-rw intrusion-attack-type	
		++-rw brutal-force?	boolean
		++-rw buffer-overflow?	boolean
		++-rw botnet-event	
		++-rw event-name	string
		++-rw user-name?	string
		++-rw message?	string
		++-rw src-ip?	inet:ipv4-address
		++-rw dst-ip?	inet:ipv4-address
		++-rw src-port?	inet:port-number
		++-rw dst-port?	inet:port-number
		++-rw src-zone?	string
		++-rw dst-zone?	string
		++-rw rule-id	uint8
		++-rw rule-name	string
		++-rw profile?	string
		++-rw raw-info?	string
		++-rw protocol	
		++-rw tcp?	boolean
		++-rw udp?	boolean
		++-rw icmp?	boolean
		++-rw icmpv6?	boolean
		++-rw ip?	boolean
		++-rw http?	boolean
		++-rw ftp?	boolean
		++-rw botnet-name?	string
		++-rw role?	string
		++-rw web-attack-event	
		++-rw event-name	string
		++-rw user-name?	string
		++-rw message?	string
		++-rw src-ip?	inet:ipv4-address
		++-rw dst-ip?	inet:ipv4-address
		++-rw src-port?	inet:port-number
		++-rw dst-port?	inet:port-number
		++-rw src-zone?	string
		++-rw dst-zone?	string

Hong, et al.

Expires January 20, 2018

[Page 7]

```
| |     +-rw rule-id          uint8
| |     +-rw rule-name        string
| |     +-rw profile?         string
| |     +-rw raw-info?         string
| |     +-rw web-attack-type
| |     | +-rw sql-injection? boolean
| |     | +-rw command-injection? boolean
| |     | +-rw xss?            boolean
| |     | +-rw csrf?           boolean
| |     +-rw req-method
| |     | +-rw put?            boolean
| |     | +-rw get?            boolean
| |     +-rw req-url?         string
| |     +-rw url-category?    string
| |     +-rw filtering-type
| |     | +-rw blacklist?      boolean
| |     | +-rw whitelist?      boolean
| |     | +-rw user-defined?   boolean
| |     | +-rw balicious-category? boolean
| |     | +-rw unknown?         boolean
+---:(log)
| +-rw (log-type)?
|   +-:(system-log)
|   | +-rw access-logs
|   | | +-rw login-ip          inet:ipv4-address
|   | | +-rw administorator?   string
|   | | +-rw login-mode?       login-mode
|   | | +-rw operation-type?   operation-type
|   | | +-rw result?           string
|   | | +-rw content?          string
|   | +-rw resource-utiliz-logs
|   | | +-rw system-status?    string
|   | | +-rw cpu-usage?        uint8
|   | | +-rw memory-usage?     uint8
|   | | +-rw disk-usage?       uint8
|   | | +-rw disk-left?        uint8
|   | | +-rw session-num?      uint8
|   | | +-rw process-num?      uint8
|   | | +-rw in-traffic-rate?  uint32
|   | | +-rw out-traffic-rate? uint32
|   | | +-rw in-traffic-speed? uint32
|   | | +-rw out-traffic-speed? uint32
|   | +-rw user-activity-logs
|   | | +-rw user              string
|   | | +-rw group             string
|   | | +-rw login-ip          inet:ipv4-address
|   | | | +-rw authentication-mode
|   | | | | +-rw local-auth     boolean
```

Hong, et al.

Expires January 20, 2018

[Page 8]

```

| | | | +--rw third-part-auth      boolean
| | | | +--rw exemption-auth     boolean
| | | | +--rw sso-auth          boolean
| | | +--rw access-mode
| | | | +--rw ppp?             boolean
| | | | +--rw svn?             boolean
| | | | +--rw local?            boolean
| | | | +--rw online-duration? string
| | | | +--rw logout-duration? string
| | | | +--rw additional-info? string
| | +---:(nsf-log)
| | | +--rw ddos-logs
| | | | +--rw attack-type?      string
| | | | +--rw attack-ave-rate?   uint32
| | | | +--rw attack-ave-speed?  uint32
| | | | +--rw attack-pkt-num?    uint32
| | | | +--rw attack-src-ip?    inet:ipv4-address
| | | | +--rw action?           all-action
| | | | +--rw os?               string
| | | +--rw virus-logs
| | | | +--rw protocol
| | | | | +--rw tcp?            boolean
| | | | | +--rw udp?            boolean
| | | | | +--rw icmp?           boolean
| | | | | +--rw icmpv6?         boolean
| | | | | +--rw ip?              boolean
| | | | | +--rw http?            boolean
| | | | | +--rw ftp?             boolean
| | | | | +--rw attack-type?    string
| | | | | +--rw action?          all-action
| | | | | +--rw os?              string
| | | | +--rw time              yang:date-and-time
| | | +--rw intrusion-logs
| | | | +--rw attack-type?      string
| | | | +--rw action?           all-action
| | | | +--rw time              yang:date-and-time
| | | | +--rw attack-rate?      uint32
| | | | +--rw attack-speed?     uint32
| | | +--rw botnet-logs
| | | | +--rw attack-type?      string
| | | | +--rw botnet-pkt-num?    uint8
| | | | +--rw action?           all-action
| | | | +--rw os?               string
| | | +--rw dpi-logs
| | | | +--rw dpi-type?         dpi-type
| | | | +--rw src-ip?           inet:ipv4-address
| | | | +--rw dst-ip?           inet:ipv4-address
| | | | +--rw src-port?         inet:port-number

```

Hong, et al.

Expires January 20, 2018

[Page 9]

```
| | | +--rw dst-port?          inet:port-number
| | | +--rw src-zone?        string
| | | +--rw dst-zone?        string
| | | +--rw src-region?      string
| | | +--rw dst-region?      string
| | | +--rw policy-id       uint8
| | | +--rw policy-name      string
| | | +--rw src-user?        string
| | | +--rw protocol
| | | | +--rw tcp?           boolean
| | | | +--rw udp?           boolean
| | | | +--rw icmp?          boolean
| | | | +--rw icmpv6?        boolean
| | | | +--rw ip?            boolean
| | | | +--rw http?          boolean
| | | | +--rw ftp?           boolean
| | | +--rw file-type?       string
| | | +--rw file-name?       string
+--rw vul-scan-logs* [vulnerability-id]
| | +--rw vul-id             uint8
| | +--rw victim-ip?         inet:ipv4-address
| | +--rw protocol
| | | +--rw tcp?             boolean
| | | +--rw udp?             boolean
| | | +--rw icmp?            boolean
| | | +--rw icmpv6?          boolean
| | | +--rw ip?              boolean
| | | +--rw http?            boolean
| | | +--rw ftp?             boolean
| | +--rw port-num?          inet:port-number
| | +--rw level?             severity
| | +--rw os?                string
| | +--rw additional-info?   string
+--rw web-attack-logs
| | +--rw attack-type?       string
| | +--rw rsp-code?          string
| | +--rw req-clientapp?     string
| | +--rw req-cookies?       string
| | +--rw req-host?          string
| | +--rw raw-info?          string
+--:(counters)
| | +--rw (counter-type)?
| | +--:(system-counter)
| | | +--rw interface-counters
| | | | +--rw interface-name?   string
| | | | +--rw in-total-traffic-pkts? uint32
| | | | +--rw out-total-traffic-pkts? uint32
| | | | +--rw in-total-traffic-bytes? uint32
```

Hong, et al.

Expires January 20, 2018

[Page 10]

```
|   |   +-rw out-total-traffic-bytes? uint32
|   |   +-rw in-drop-traffic-pkts?      uint32
|   |   +-rw out-drop-traffic-pkts?      uint32
|   |   +-rw in-drop-traffic-bytes?      uint32
|   |   +-rw out-drop-traffic-bytes?      uint32
|   |   +-rw total-traffic?              uint32
|   |   +-rw in-traffic-ave-rate?       uint32
|   |   +-rw in-traffic-peak-rate?      uint32
|   |   +-rw in-traffic-ave-speed?      uint32
|   |   +-rw in-traffic-peak-speed?      uint32
|   |   +-rw out-traffic-ave-rate?      uint32
|   |   +-rw out-traffic-peak-rate?      uint32
|   |   +-rw out-traffic-ave-speed?      uint32
|   |   +-rw out-traffic-peak-speed?      uint32
+--:(nsf-counter)
    +-rw firewall-counters
        |   +-rw src-ip?                  inet:ipv4-address
        |   +-rw dst-ip?                  inet:ipv4-address
        |   +-rw src-port?                inet:port-number
        |   +-rw dst-port?                inet:port-number
        |   +-rw src-zone?                string
        |   +-rw dst-zone?                string
        |   +-rw src-region?              string
        |   +-rw dst-region?              string
        |   +-rw policy-id?              uint8
        |   +-rw policy-name?            string
        |   +-rw src-user?                string
        |   +-rw protocol
            |       +-rw tcp?             boolean
            |       +-rw udp?             boolean
            |       +-rw icmp?            boolean
            |       +-rw icmpv6?          boolean
            |       +-rw ip?              boolean
            |       +-rw http?            boolean
            |       +-rw ftp?              boolean
        |   +-rw total-traffic?          uint32
        |   +-rw in-traffic-ave-rate?    uint32
        |   +-rw in-traffic-peak-rate?  uint32
        |   +-rw in-traffic-ave-speed?  uint32
        |   +-rw in-traffic-peak-speed? uint32
        |   +-rw out-traffic-ave-rate?  uint32
        |   +-rw out-traffic-peak-rate? uint32
        |   +-rw out-traffic-ave-speed? uint32
        |   +-rw out-traffic-peak-speed? uint32
        +-rw bound
            +-rw in-interface?          boolean
            +-rw out-interface?         boolean
+-rw policy-hit-counters
```

Hong, et al.

Expires January 20, 2018

[Page 11]

```

|      +-rw src-ip?          inet:ipv4-address
|      +-rw dst-ip?          inet:ipv4-address
|      +-rw src-port?        inet:port-number
|      +-rw dst-port?        inet:port-number
|      +-rw src-zone?        string
|      +-rw dst-zone?        string
|      +-rw src-region?      string
|      +-rw dst-region?      string
|      +-rw policy-id        uint8
|      +-rw policy-name       string
|      +-rw src-user?         string
|      +-rw protocol
|      |  +-rw tcp?            boolean
|      |  +-rw udp?            boolean
|      |  +-rw icmp?           boolean
|      |  +-rw icmpv6?         boolean
|      |  +-rw ip?             boolean
|      |  +-rw http?           boolean
|      |  +-rw ftp?            boolean
|      +-rw total-traffic?    uint32
|      +-rw in-traffic-ave-rate?  uint32
|      +-rw in-traffic-peak-rate? uint32
|      +-rw in-traffic-ave-speed? uint32
|      +-rw in-traffic-peak-speed? uint32
|      +-rw out-traffic-ave-rate? uint32
|      +-rw out-traffic-peak-rate? uint32
|      +-rw out-traffic-ave-speed? uint32
|      +-rw out-traffic-peak-speed? uint32
|      +-rw hit-times?         uint32
+-rw time-stamp                  yang:date-and-time
+-rw severity                    severity
+-rw vendor-name?                string

```

Figure 1: Information Model for NSF Monitoring

5. YANG Data Model

This section introduces a YANG data model for the information model of monitoring inforamtion based on [[i2nsf-monitoring-im](#)].

```
<CODE BEGINS> file "ietf-i2nsf-nsf-monitoring-data-model@20170719.yang"

module ietf-i2nsf-monitoring-information {
namespace
  "urn:ietf:params:xml:ns:yang:ietf-i2nsf-nsf-monitoring-data-model";
prefix
  monitoring-information;
import ietf-inet-types{
```

Hong, et al.

Expires January 20, 2018

[Page 12]

```
prefix inet;
}

import ietf-yang-types {
    prefix yang;
}

organization
    "IETF I2NSF (Interface to Network Security Functions)
     Working Group";

contact
    "WG Web: <http://tools.ietf.org/wg/i2nsf>
     WG List: <mailto:i2nsf@ietf.org>

     WG Chair: Linda Dunbar
     <mailto:Linda.duhbar@huawei.com>

     Editor: Dongjin Hong
     <mailto:dong.jin@skku.edu>

     Editor: Jaehoon Paul Jeong
     <mailto:pauljeong@skku.edu>";

description
    "This module defines a YANG data module for monitoring NSFs.';

revision "2017-07-19" {
    description "Initial revision";
    reference
        "draft-zhang-i2nsf-info-model-monitoring-04";
}

typedef severity {
    type enumeration {
        enum high {
            description
                "high-level";
        }
        enum middle {
            description
                "middle-level";
        }
        enum low {
            description
                "low-level";
        }
    }
    description
        "This is used for indicating the severity";
}
```

Hong, et al.

Expires January 20, 2018

[Page 13]

```
}
```

```
typedef all-action {
```

```
    type enumeration {
```

```
        enum allow {
```

```
            description
```

```
                "TBD";
```

```
        }
```

```
        enum alert {
```

```
            description
```

```
                "TBD";
```

```
        }
```

```
        enum block {
```

```
            description
```

```
                "TBD";
```

```
        }
```

```
        enum discard {
```

```
            description
```

```
                "TBD";
```

```
        }
```

```
        enum declare {
```

```
            description
```

```
                "TBD";
```

```
        }
```

```
        enum block-ip {
```

```
            description
```

```
                "TBD";
```

```
        }
```

```
        enum block-service{
```

```
            description
```

```
                "TBD";
```

```
        }
```

```
    }
```

```
    description
```

```
        "This is used for protocol";
```

```
}
```

```
typedef dpi-type{
```

```
    type enumeration {
```

```
        enum file-blocking{
```

```
            description
```

```
                "TBD";
```

```
        }
```

```
        enum data-filtering{
```

```
            description
```

```
                "TBD";
```

```
        }
```

```
        enum application-behavior-control{
```

```
            description
```

```
                "TBD";
```

Hong, et al.

Expires January 20, 2018

[Page 14]

```
        }
    }
    description
      "This is used for dpi type";
}
typedef operation-type{
  type enumeration {
    enum login{
      description
        "TBD";
    }
    enum logout{
      description
        "TBD";
    }
    enum configuration{
      description
        "TBD";
    }
  }
  description
    "This is used for operation type";
}
typedef login-mode{
  type enumeration {
    enum root{
      description
        "TBD";
    }
    enum user{
      description
        "TBD";
    }
    enum guest{
      description
        "TBD";
    }
  }
  description
    "This is used for login mode";
}
grouping protocol {
  description
    "A set of protocols";
  container protocol {
    description
      "Protocol types:
TCP, UDP, ICMP, ICMPv6, IP, HTTP, FTP and etc.";
```

Hong, et al.

Expires January 20, 2018

[Page 15]

```
leaf tcp {
    type boolean;
    description
        "TCP protocol type.";
}
leaf udp {
    type boolean;
    description
        "UDP protocol type.";
}
leaf icmp {
    type boolean;
    description
        "ICMP protocol type.";
}
leaf icmpv6 {
    type boolean;
    description
        "ICMPv6 protocol type.";
}
leaf ip {
    type boolean;
    description
        "IP protocol type.";
}
leaf http {
    type boolean;
    description
        "HTTP protocol type.";
}
leaf ftp {
    type boolean;
    description
        "ftp protocol type.";
}
}
}
grouping traffic-rates {
    description
        "A set of traffic rates
        for statistics data";
leaf total-traffic {
    type uint32;
    description
        "Total traffic";
}
leaf in-traffic-ave-rate {
    type uint32;
```

Hong, et al.

Expires January 20, 2018

[Page 16]

```
    description
      "Inbound traffic average rate in pps";
}
leaf in-traffic-peak-rate {
  type uint32;
  description
    "Inbound traffic peak rate in pps";
}
leaf in-traffic-ave-speed {
  type uint32;
  description
    "Inbound traffic average speed in bps";
}
leaf in-traffic-peak-speed {
  type uint32;
  description
    "Inbound traffic peak speed in bps";
}
leaf out-traffic-ave-rate {
  type uint32;
  description
    "Outbound traffic average rate in pps";
}
leaf out-traffic-peak-rate {
  type uint32;
  description
    "Outbound traffic peak rate in pps";
}
leaf out-traffic-ave-speed {
  type uint32;
  description
    "Outbound traffic average speed in bps";
}
leaf out-traffic-peak-speed {
  type uint32;
  description
    "Outbound traffic peak speed in bps";
}
}
grouping i2nsf-system-alarm-type-content {
  description
    "A set of system alarm type contents";
  leaf event-name {
    type string;
    mandatory true;
    description
      "This is used to distinguish event type";
  }
}
```

Hong, et al.

Expires January 20, 2018

[Page 17]

```
leaf usage {
    type uint8;
    description
        "specifies the amount of usage";
}
leaf threshold {
    type uint8;
    description
        "The threshold triggering the alarm or the event";
}
leaf message {
    type string;
    mandatory true;
    description
        "The usage exceeded the threshold";
}
}
grouping i2nsf-system-event-type-content {
    description
        "A set of system event type contents";
    leaf event-name {
        type string;
        mandatory true;
        description
            "ACCESS_DENIED, CONFIG_CHANGE and so on.";
    }
    leaf user-name {
        type string;
        mandatory true;
        description
            "Name of a user";
    }
    leaf group {
        type string;
        mandatory true;
        description
            "Group to which a user belongs.";
    }
    leaf login-ip {
        type inet:ipv4-address;
        mandatory true;
        description
            "Login IP address of a user.";
    }
    container authentication-mode {
        description
            "User authentication mode. e.g., Local Authentication,
            Third-Party Server Authentication,
```

Hong, et al.

Expires January 20, 2018

[Page 18]

```
    Authentication Exemption, SSO Authentication.";  
leaf local-authentication {  
    type boolean;  
    mandatory true;  
    description  
        "Authentication-mode : local authentication.";  
}  
leaf third-part-server-authentication {  
    type boolean;  
    mandatory true;  
    description  
        "TBD";  
}  
leaf exemption-authentication {  
    type boolean;  
    mandatory true;  
    description  
        "TBD";  
}  
leaf sso-authentication {  
    type boolean;  
    mandatory true;  
    description  
        "TBD";  
}  
leaf message {  
    type string;  
    mandatory true;  
    description  
        "The message for system events";  
}  
}  
grouping i2nsf-nsf-event-type-content {  
    description  
        "A set of nsf event type contents";  
leaf event-name {  
    type string;  
    mandatory true;  
    description  
        "This is used to distinguish event type";  
}  
leaf user-name {  
    type string;  
    description  
        "User name who generates traffic";  
}  
leaf message {
```

Hong, et al.

Expires January 20, 2018

[Page 19]

```
type string;
description
  "The message for nsf events";
}
leaf src-ip {
  type inet:ipv4-address;
  description
    "The source IP address of the packet";
}
leaf dst-ip {
  type inet:ipv4-address;
  description
    "The destination IP address of the packet";
}
leaf src-port {
  type inet:port-number;
  description
    "The source port of the packet";
}
leaf dst-port {
  type inet:port-number;
  description
    "The destination port of the packet";
}
leaf src-zone {
  type string;
  description
    "The source security zone of the packet";
}
leaf dst-zone {
  type string;
  description
    "The destination security zone of the packet";
}
leaf rule-id {
  type uint8;
  mandatory true;
  description
    "The ID of the rule being triggered";
}
leaf rule-name {
  type string;
  mandatory true;
  description
    "The name of the rule being triggered";
}
leaf profile {
  type string;
```

Hong, et al.

Expires January 20, 2018

[Page 20]

```
description
  "Security profile that traffic matches.";
}
leaf raw-info {
  type string;
  description
    "The information describing the packet
     triggering the event.";
}
}
grouping i2nsf-system-counter-type-content{
  description
    "A set of system counter type contents";
leaf interface-name {
  type string;
  description
    "Network interface name configured in NSF";
}
leaf in-total-traffic-pkts {
  type uint32;
  description
    "Total inbound packets";
}
leaf out-total-traffic-pkts {
  type uint32;
  description
    "Total outbound packets";
}
leaf in-total-traffic-bytes {
  type uint32;
  description
    "Total inbound bytes";
}
leaf out-total-traffic-bytes {
  type uint32;
  description
    "Total outbound bytes";
}
leaf in-drop-traffic-pkts {
  type uint32;
  description
    "Total inbound drop packets";
}
leaf out-drop-traffic-pkts {
  type uint32;
  description
    "Total outbound drop packets";
}
```

Hong, et al.

Expires January 20, 2018

[Page 21]

```
leaf in-drop-traffic-bytes {
    type uint32;
    description
        "Total inbound drop bytes";
}
leaf out-drop-traffic-bytes {
    type uint32;
    description
        "Total outbound drop bytes";
}
uses traffic-rates;
}
grouping i2nsf-nsf-counters-type-content{
    description
        "A set of nsf counters type contents";
    leaf src-ip {
        type inet:ipv4-address;
        description
            "The source IP address of the packet";
    }
    leaf dst-ip {
        type inet:ipv4-address;
        description
            "The destination IP address of the packet";
    }
    leaf src-port {
        type inet:port-number;
        description
            "The source port of the packet";
    }
    leaf dst-port {
        type inet:port-number;
        description
            "The destination port of the packet";
    }
    leaf src-zone {
        type string;
        description
            "The source security zone of the packet";
    }
    leaf dst-zone {
        type string;
        description
            "The destination security zone of the packet";
    }
    leaf src-region {
        type string;
        description
```

Hong, et al.

Expires January 20, 2018

[Page 22]

```
        "Source region of the traffic";
    }
leaf dst-region{
    type string;
    description
        "Destination region of the traffic";
}
leaf policy-id {
    type uint8;
    mandatory true;
    description
        "The ID of the policy being triggered";
}
leaf policy-name {
    type string;
    mandatory true;
    description
        "The name of the policy being triggered";
}
leaf src-user{
    type string;
    description
        "User who generates traffic";
}
uses protocol;
uses traffic-rates;
}

container monitoring-message {
    description
        "The message for monitoring information";
list monitoring-messages {
    key message-id;
    description
        "The messages according to monitoring information";
leaf message-id {
    type uint8;
    mandatory true;
    description
        "This is message ID
        This is key for monitoring messages";
}
leaf message-version {
    type uint8;
    mandatory true;
    description
        "The version of message";
}
```

Hong, et al.

Expires January 20, 2018

[Page 23]

```
choice message-type {
    description
        "The type of message";
    case alarm {
        description
            "If the message type is alarm";
        choice alarm-type {
            description
                "This is alarm type such as system alarm";
            case system-alarm{
                description
                    "If the alarm type is system alarm";
                container memory-alarm {
                    description
                        "This is memory alarm in
                        system alarm";
                    uses i2nsf-system-alarm-type-content;
                    leaf module-name {
                        type string;
                        mandatory true;
                        description
                            "Indicate the NSF module
                            responsible for generating
                            this alarm";
                    }
                }
                container cpu-alarm {
                    description
                        "This is cpu alarm in system alarm";
                    uses i2nsf-system-alarm-type-content;
                }
                container disk-alarm {
                    description
                        "This is disk alarm in system alarm";
                    uses i2nsf-system-alarm-type-content;
                }
                container hardware-alarm {
                    description
                        "This is hardware alarm
                        in system alarm";
                    uses i2nsf-system-alarm-type-content;
                    leaf component-name {
                        type string;
                        description
                            "Indicate the HW component
                            responsible for generating
                            this alarm.";
                    }
                }
            }
        }
    }
}
```

Hong, et al.

Expires January 20, 2018

[Page 24]

```
    }
  container interface-alarm {
    description
      "This is interface alarm
       in system alarm";
    uses i2nsf-system-alarm-type-content;
    leaf interface-name {
      type string;
      description
        "The name of interface.";
    }
  container interface-state {
    description
      "This is interface state
       in interface-alarm";
    leaf up {
      type boolean;
      mandatory true;
      description
        "The state of interface is up";
    }
    leaf down {
      type boolean;
      mandatory true;
      description
        "The state of interface is down";
    }
    leaf congested {
      type boolean;
      mandatory true;
      description
        "The state of interface is
         congested";
    }
  }
}
case event {
  description
    "If the message type is event";
  choice event-type {
    description
      "This is event type such as system event
       and nsf event.";
    case system-event {
      description
```

Hong, et al.

Expires January 20, 2018

[Page 25]

```
    "If the event type is system event";
container access-violation {
    description
        "If the system event is
        access violation";
    uses i2nsf-system-event-type-content;
}
container config-change {
    description
        "If the system event is
        config change violation";
    uses i2nsf-system-event-type-content;
}
case nsf-event {
    description
        "If the event type is nsf event";
    container ddos-event {
        description
            "If the event type is DDoS event";
        uses i2nsf-nsf-event-type-content;
        container ddos-attack-type{
            description
                "Type of DDoS attack";
            leaf syn-flood{
                type boolean;
                description
                    "If the DDoS attack is
                    syn flood";
            }
            leaf ack-flood{
                type boolean;
                description
                    "If the DDoS attack is
                    ack flood";
            }
            leaf syn-ack-flood{
                type boolean;
                description
                    "If the DDoS attack is
                    syn ack flood";
            }
            leaf finrst-flood{
                type boolean;
                description
                    "If the DDoS attack is
                    fin rst flood";
            }
        }
```

Hong, et al.

Expires January 20, 2018

[Page 26]

```
leaf tcp-connection-flood{
    type boolean;
    description
        "If the DDoS attack is
        tcp connection flood";
}
leaf udp-flood{
    type boolean;
    description
        "If the DDoS attack is
        udp flood";
}
leaf icmp-flood{
    type boolean;
    description
        "If the DDoS attack is
        icmp flood";
}
leaf https-flood{
    type boolean;
    description
        "If the DDoS attack is
        https flood";
}
leaf http-flood{
    type boolean;
    description
        "If the DDoS attack is
        http flood";
}
leaf dns-reply-flood{
    type boolean;
    description
        "If the DDoS attack is
        dns reply flood";
}
leaf dns-query-flood{
    type boolean;
    description
        "If the DDoS attack is
        dns query flood";
}
leaf sip-flood{
    type boolean;
    description
        "If the DDoS attack is
        sip flood";
}
```

Hong, et al.

Expires January 20, 2018

[Page 27]

```
    }
    leaf start-time {
        type yang:date-and-time;
        mandatory true;
        description
            "The time stamp indicating
            when the attack started";
    }
    leaf end-time {
        type yang:date-and-time;
        mandatory true;
        description
            "The time stamp indicating
            when the attack ended";
    }
    leaf attack-rate {
        type uint32;
        description
            "The PPS of attack traffic";
    }
    leaf attack-speed {
        type uint32;
        description
            "the bps of attack traffic";
    }
}
container session-table-event {
    description
        "If the event type is session
        table event";
    leaf event-name {
        type string;
        description
            "The event name for
            session table event";
    }
    leaf current-session {
        type uint8;
        description
            "The number of concurrent
            sessions";
    }
    leaf maximum-session {
        type uint8;
        description
            "The maximum number of sessions
            that the session table can
            support";
```

Hong, et al.

Expires January 20, 2018

[Page 28]

```
        }
leaf threshold {
    type uint8;
description
    "The threshold triggering
the event";
}
leaf message {
    type string;
description
    "The number of session table
exceeded the threshold";
}
}
container virus-event {
description
    "If the event type is virus event";
uses i2nsf-nsf-event-type-content;
container virus-type {
    description
        "The type of virus";
leaf trajan {
    type boolean;
description
    "If the virus type is trajan";
}
leaf worm {
    type boolean;
description
    "If the virus type is worm";
}
leaf macro {
    type boolean;
description
    "If the virus type is macro";
}
}
leaf virus-name {
    type string;
description
    "The name of virus";
}
leaf file-type {
    type string;
description
    "The type of file";
}
leaf file-name {
```

Hong, et al.

Expires January 20, 2018

[Page 29]

```
    type string;
    description
      "The name of file";
  }
}

container intrusion-event {
  description
    "If the event type is intrusion event";
  uses i2nsf-nsf-event-type-content;
  uses protocol;
  container intrusion-attack-type {
    description
      "The attack type of intrusion";
    leaf brutal-force {
      type boolean;
      description
        "The intrusion type is
        brutal force";
    }
    leaf buffer-overflow {
      type boolean;
      description
        "The intrusion type is
        buffer overflow";
    }
  }
}
container botnet-event {
  description
    "If the event type is botnet event";
  uses i2nsf-nsf-event-type-content;
  uses protocol;
  leaf botnet-name {
    type string;
    description
      "The name of the detected botnet";
  }
  leaf role {
    type string;
    description
      "The role of the communicating
      parties within the botnet";
  }
}
container web-attack-event {
  description
    "If the event type is web
    attack event";
```

Hong, et al.

Expires January 20, 2018

[Page 30]

```
uses i2nsf-nsf-event-type-content;
container web-attack-type {
    description
        "To determine the attack
        type";
    leaf sql-injection {
        type boolean;
        description
            "If the web attack type is
            sql injection";
    }
    leaf command-injection {
        type boolean;
        description
            "If the web attack type is
            command injection";
    }
    leaf xss {
        type boolean;
        description
            "If the web attack type is
            xss injection";
    }
    leaf csrf {
        type boolean;
        description
            "If the web attack type is
            csrf injection";
    }
}
container req-method {
    description
        "The method of requirement.
        For instance, PUT or GET
        in HTTP";
    leaf put{
        type boolean;
        description
            "If req method is PUT";
    }
    leaf get {
        type boolean;
        description
            "If req method is GET";
    }
}
leaf req-url {
    type string;
```

Hong, et al.

Expires January 20, 2018

[Page 31]

```
        description
          "Requested URL";
    }
leaf url-category {
    type string;
    description
      "Matched URL category";
}
container filtering-type {
    description
      "URL filtering type,
       e.g., Blacklist, Whitelist,
       User-Defined, Predefined,
       Malicious Category, Unknown";
    leaf blacklist {
        type boolean;
        description
          "The filtering type is
           blacklist";
    }
    leaf whitelist {
        type boolean;
        description
          "The filtering type is
           whitelist";
    }
    leaf user-defined {
        type boolean;
        description
          "The filtering type is
           user defined";
    }
    leaf balicious-category{
        type boolean;
        description
          "The filtering type is
           balicious category";
    }
    leaf unknown {
        type boolean;
        description
          "The filtering type is
           unknown";
    }
}
}
```

Hong, et al.

Expires January 20, 2018

[Page 32]

```
}

case log {
    description
        "If the message type is log";
    choice log-type {
        description
            "The type of log";
    case system-log{
        description
            "If the log type is system log";
        container access-logs {
            description
                "If the log is access logs
                 in system log";
            leaf login-ip {
                type inet:ipv4-address;
                mandatory true;
                description
                    "Login IP address of a user.";
            }
            leaf administartor {
                type string;
                description
                    "Administrator that
                     operates on the device";
            }
            leaf login-mode {
                type login-mode;
                description
                    "Specifies the
                     administrator logs in mode";
            }
            leaf operation-type {
                type operation-type;
                description
                    "The operation type that
                     the administrator execute";
            }
            leaf result {
                type string;
                description
                    "Command execution result";
            }
            leaf content {
                type string;
                description
                    "Operation performed by
                     an administrator after login.";
            }
        }
    }
}
```

Hong, et al.

Expires January 20, 2018

[Page 33]

```
        }
    }
container resource-utiliz-logs {
    description
        "If the log is resource utilize
        logs in system log";
    leaf system-status {
        type string;
        description
            "TBD";
    }
    leaf cpu-usage {
        type uint8;
        description
            "specifies the amount of
            cpu usage";
    }
    leaf memory-usage {
        type uint8;
        description
            "specifies the amount of
            memory usage";
    }
    leaf disk-usage {
        type uint8;
        description
            "specifies the amount of
            disk usage";
    }
    leaf disk-left {
        type uint8;
        description
            "specifies the amount of
            disk left";
    }
    leaf session-num {
        type uint8;
        description
            "The total number of
            sessions";
    }
    leaf process-num {
        type uint8;
        description
            "The total number of
            process";
    }
    leaf in-traffic-rate {
```

Hong, et al.

Expires January 20, 2018

[Page 34]

```
    type uint32;
    description
        "The total inbound
         traffic rate in pps";
}
leaf out-traffic-rate {
    type uint32;
    description
        "The total outbound
         traffic rate in pps";
}
leaf in-traffic-speed {
    type uint32;
    description
        "The total inbound
         traffic speed in bps";
}
leaf out-traffic-speed {
    type uint32;
    description
        "The total outbound
         traffic speed in bps";
}
}
container user-activity-logs {
    description
        "If the log is user activity
         logs in system log";
    leaf user {
        type string;
        mandatory true;
        description
            "Name of a user";
    }
    leaf group {
        type string;
        mandatory true;
        description
            "Group to which a user belongs.";
    }
    leaf login-ip {
        type inet:ipv4-address;
        mandatory true;
        description
            "Login IP address of a user.";
    }
}
container authentication-mode {
    description
```

Hong, et al.

Expires January 20, 2018

[Page 35]

```
    "User authentication mode. e.g.,
    Local Authentication,
    Third-Party Server Authentication,
    Authentication Exemption, SSO Authentication.";
leaf local-authentication {
    type boolean;
    mandatory true;
    description
        "Authentication-mode : local authentication.";
}
leaf third-part-server-authentication {
    type boolean;
    mandatory true;
    description
        "TBD";
}
leaf exemption-authentication {
    type boolean;
    mandatory true;
    description
        "TBD";
}
leaf sso-authentication {
    type boolean;
    mandatory true;
    description
        "TBD";
}
}
container access-mode {
    description
        "TBD";
leaf ppp{
    type boolean;
    description
        "TBD";
}
leaf svn{
    type boolean;
    description
        "TBD";
}
leaf local{
    type boolean;
    description
        "TBD";
}
}
```

Hong, et al.

Expires January 20, 2018

[Page 36]

```
leaf online-duration {
    type string;
    description
        "TBD";
}
leaf logout-duration {
    type string;
    description
        "TBD";
}
leaf addtional-info {
    type string;
    description
        "TBD";
}
}
case nsf-log{
    description
        "If the log type is nsf log";
    container ddos-logs {
        description
            "If the log is DDoS logs
            in nsf log";
        leaf attack-type{
            type string;
            description
                "DDoS";
        }
        leaf attack-ave-rate {
            type uint32;
            description
                "The ave PPS of
                attack traffic";
        }
        leaf attack-ave-speed {
            type uint32;
            description
                "the ave bps of
                attack traffic";
        }
        leaf attack-pkt-num{
            type uint32;
            description
                "the number of
                attack packets";
        }
        leaf attack-src-ip {
```

Hong, et al.

Expires January 20, 2018

[Page 37]

```
    type inet:ipv4-address;
    description
        "TBD";
}
leaf action {
    type all-action;
    description
        "TBD";
}
leaf os {
    type string;
    description
        "simple os information";
}
}
container virus-logs {
    description
        "If the log is virus logs
         in nsf log";
    uses protocol;
    leaf attack-type{
        type string;
        description
            "Virus";
    }
    leaf action{
        type all-action;
        description
            "TBD";
    }
    leaf os{
        type string;
        description
            "simple os information";
    }
    leaf time {
        type yang:date-and-time;
        mandatory true;
        description
            "Indicate the time when the
             message is generated";
    }
}
container intrusion-logs {
    description
        "If the log is intrusion logs
         in nsf log";
    leaf attack-type{
```

Hong, et al.

Expires January 20, 2018

[Page 38]

```
    type string;
    description
      "Intrusion";
}
leaf action{
  type all-action;
  description
    "TBD";
}
leaf time {
  type yang:date-and-time;
  mandatory true;
  description
    "Indicate the time when the
     message is generated";
}
leaf attack-rate {
  type uint32;
  description
    "The PPS of attack traffic";
}
leaf attack-speed {
  type uint32;
  description
    "the bps of attack traffic";
}
}
container botnet-logs {
  description
    "If the log is botnet logs
     in nsf log";
  leaf attack-type{
    type string;
    description
      "Botnet";
}
  leaf botnet-pkt-num{
    type uint8;
    description
      "The number of the packets
       sent to or from the
       detected botnet";
}
  leaf action{
    type all-action;
    description
      "TBD";
}
```

Hong, et al.

Expires January 20, 2018

[Page 39]

```
leaf os{
    type string;
    description
        "simple os information";
}
}
container dpi-logs {
    description
        "If the log is dpi logs
        in nsf log";
    leaf dpi-type{
        type dpi-type;
        description
            "The type of dpi";
    }
    leaf src-ip {
        type inet:ipv4-address;
        description
            "The source IP address of the packet";
    }
    leaf dst-ip {
        type inet:ipv4-address;
        description
            "The destination IP address of the packet";
    }
    leaf src-port {
        type inet:port-number;
        description
            "The source port of the packet";
    }
    leaf dst-port {
        type inet:port-number;
        description
            "The destination port of the packet";
    }
    leaf src-zone {
        type string;
        description
            "The source security zone of the packet";
    }
    leaf dst-zone {
        type string;
        description
            "The destination security zone of the packet";
    }
    leaf src-region {
        type string;
        description
            "The source region of the packet";
    }
}
```

Hong, et al.

Expires January 20, 2018

[Page 40]

```
        "Source region of the traffic";
    }
    leaf dst-region{
        type string;
        description
            "Destination region of the traffic";
    }
    leaf policy-id {
        type uint8;
        mandatory true;
        description
            "The ID of the policy being triggered";
    }
    leaf policy-name {
        type string;
        mandatory true;
        description
            "The name of the policy being triggered";
    }
    leaf src-user{
        type string;
        description
            "User who generates traffic";
    }
    uses protocol;
    leaf file-type {
        type string;
        description
            "The type of file";
    }
    leaf file-name {
        type string;
        description
            "The name of file";
    }
}
list vulnerability-scanning-logs {
    key vulnerability-id;
    description
        "If the log is vulnerability
        scanning logs in nsf log";
    leaf vulnerability-id{
        type uint8;
        description
            "The vulnerability id";
    }
    leaf victim-ip {
        type inet:ipv4-address;
```

Hong, et al.

Expires January 20, 2018

[Page 41]

```
    description
      "IP address of the victim
       host which has vulnerabilities";
  }
  uses protocol;
  leaf port-num{
    type inet:port-number;
    description
      "The port number";
  }
  leaf level{
    type severity;
    description
      "The vulnerability severity";
  }
  leaf os{
    type string;
    description
      "simple os information";
  }
  leaf addtional-info{
    type string;
    description
      "TBD";
  }
}
container web-attack-logs {
  description
    "If the log is web attack
     logs in nsf log";
  leaf attack-type{
    type string;
    description
      "Web Attack";
  }
  leaf rsp-code{
    type string;
    description
      "Response code";
  }
  leaf req-clientapp{
    type string;
    description
      "The client application";
  }
  leaf req-cookies{
    type string;
    description
```

Hong, et al.

Expires January 20, 2018

[Page 42]

```
        "Cookies";
    }
    leaf req-host{
        type string;
        description
            "The domain name of the
            requested host";
    }
    leaf raw-info{
        type string;
        description
            "The information describing
            the packet triggering the
            event.";
    }
}
}
}
}

case counters {
    description
        "If the message type is counters";
    choice counter-type {
        description
            "The type of counter";
        case system-counter {
            container interface-counters {
                description
                    "The system counter type is
                    interface counter";
                uses i2nsf-system-counter-type-content;
            }
        }
        case nsf-counter{
            container firewall-counters {
                description
                    "The nsf counter type is
                    firewall counter";
                uses i2nsf-nsf-counters-type-content;
                container bound{
                    description
                    "Inbound or Outbound";
                    leaf in-interface {
                        type boolean;
                        description
                            "If the bound is inbound";
                    }
                    leaf out-interface {
```

Hong, et al.

Expires January 20, 2018

[Page 43]

```
        type boolean;
        description
          "If the bound is outbound";
      }
    }
  }
  container policy-hit-counters {
    description
      "The counters of policy hit";
    uses i2nsf-nsf-counters-type-content;
    leaf hit-times{
      type uint32;
      description
        "The hit times for policy";
    }
  }
}
leaf time-stamp {
  type yang:date-and-time;
  mandatory true;
  description
    "Indicate the time when the message is generated";
}
leaf severity {
  type severity;
  mandatory true;
  description
    "The severity of the alarm such as
     critical, high, middle, low.";
}
leaf vendor-name {
  type string;
  description
    "The name of the NSF vendor";
}
}
}
}
<CODE ENDS>
```

Figure 2: Data Model of Monitoring

Hong, et al.

Expires January 20, 2018

[Page 44]

6. Acknowledgments

This work was supported by Institute for Information & Communications Technology Promotion (IITP) grant funded by the Korea government (MSIP) (R-20160222-002755, Cloud based Security Intelligence Technology Development for the Customized Security Service Provisioning).

This document has greatly benefited from inputs by Daeyoung Hyun.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.

7.2. Informative References

- [i2rs-rib-data-model] Wang, L., Ananthakrishnan, H., Chen, M., Dass, A., Kini, S., and N. Bahadur, "A YANG Data Model for Routing Information Base (RIB)", [draft-ietf-i2rs-rib-data-model-07](#) (work in progress), January 2017.
- [i2nsf-terminology] Hares,, S., Strassner,, J., Lopez,, D., Xia,,, L., and H. Birkholz,, "Interface to Network Security Functions (I2NSF) Terminology", [draft-ietf-i2nsf-terminology-04](#) (work in progress), July 2017.
- [i2nsf-framework] Hares,, S., Lopez,, J., Dunbar, L., Strassner, J., and R. Kumar, "Framework for Interface to Network Security Functions", [draft-ietf-i2nsf-framework-05](#) (work in progress), May 2017.
- [i2nsf-monitoring-im] Xia,, L., Zhang,, D., Wu, Y., Kumar, R., Lohiya, A., and H. Birkholz, "An Information Model for the Monitoring of Network Security Functions (NSF)", [draft-zhang-i2nsf-info-model-monitoring-04](#) (work in progress), July 2017.

Hong, et al.

Expires January 20, 2018

[Page 45]

Authors' Addresses

Dongjin Hong
Department of Computer Engineering
Sungkyunkwan University
2066 Seobu-Ro, Jangan-Gu
Suwon, Gyeonggi-Do 16419
Republic of Korea

Phone: +82 10 7630 5473
EMail: dong.jin@skku.edu

Jaehoon Paul Jeong
Department of Software
Sungkyunkwan University
2066 Seobu-Ro, Jangan-Gu
Suwon, Gyeonggi-Do 16419
Republic of Korea

Phone: +82 31 299 4957
Fax: +82 31 290 7996
EMail: pauljeong@skku.edu
URI: <http://iotlab.skku.edu/people-jaehoon-jeong.php>

Jinyong Tim Kim
Department of Computer Engineering
Sungkyunkwan University
2066 Seobu-Ro, Jangan-Gu
Suwon, Gyeonggi-Do 16419
Republic of Korea

Phone: +82 10 8273 0930
EMail: timkim@skku.edu

Susan Hares
Huawei
7453 Hickory Hill
Saline, MI 48176
USA

Phone: +1-734-604-0332
EMail: shares@ndzh.com

Hong, et al.

Expires January 20, 2018

[Page 46]

Liang Xia (Frank)
Huawei
101 Software Avenue, Yuhuatai District
Nanjing, Jiangsu
China

Phone:
EMail: Frank.xialiang@huawei.com