

Software WG
Internet-Draft
Intended status: Standards Track
Expires: August 29, 2013

Q. Wang
China Telecom
W. Meng
C. Wang
ZTE Corporation
M. Boucadair
France Telecom
February 25, 2013

RADIUS Extensions for IPv4-Embedded Multicast and Unicast IPv6 Prefixes
[draft-hu-software-multicast-radius-ext-03](#)

Abstract

This document specifies a new Remote Authentication Dial-In User Service (RADIUS) attribute to carry the Multicast-Prefixes-64 information, aiming to delivery the Multicast and Unicast IPv6 Prefixes to be used to build multicast and unicast IPv4-Embedded IPv6 addresses. this RADIUS attribute is defined based on the equivalent DHCPv6 OPTION_PREFIX64 option.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 29, 2013.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Convention and Terminology	4
3.	Multicast-Prefixes-64 Configuration with RADIUS and DHCPv6 . .	5
4.	RADIUS Attribute	8
4.1.	Multicast-Prefixes-64	8
5.	Table of Attributes	11
6.	Security Considerations	12
7.	IANA Considerations	13
8.	Normative References	14
	Authors' Addresses	15

1. Introduction

The solution specified in [[I-D.ietf-softwire-dslite-multicast](#)] relies on stateless functions to graft part of the IPv6 multicast distribution tree and IPv4 multicast distribution tree, also uses IPv4-in-IPv6 encapsulation scheme to deliver IPv4 multicast traffic over an IPv6 multicast-enabled network to IPv4 receivers. DS-Lite Multicast [[I-D.ietf-softwire-dslite-multicast](#)] is a solution in particular to offer multicast service to DS-Lite serviced customers.

[I-D.ietf-softwire-multicast-prefix-option] defines a DHCPv6 option that is meant to be used by a mB4 element to convey the IPv6 prefixes to be used for constructing IPv4-embedded IPv6 addresses and extracting the IPv4 address when needed. In order to be able to populate such an option, the DHCPv6 server must be pre-provisioned with the required Multicast Prefixes.

In broadband environments, a customer profile may be managed by Authentication, Authorization, and Accounting (AAA) servers, together with AAA for users. The Remote Authentication Dial-In User Service (RADIUS) protocol [[RFC2865](#)] is usually used by AAA servers to communicate with network elements. Since the Multicast-Prefixes-64 information can be stored in AAA servers and the client configuration is mainly provided through DHCP running between the NAS and the requesting clients, a new RADIUS attribute is needed to send Multicast-Prefixes-64 information from the AAA server to the NAS.

This document defines a new RADIUS attribute to be used for carrying the Multicast-Prefixes-64, based on the equivalent DHCPv6 option already specified in [[I-D.ietf-softwire-multicast-prefix-option](#)].

This document makes use of the same terminology defined in [[I-D.ietf-softwire-dslite-multicast](#)] and [[I-D.ietf-mboned-64-multicast-address-format](#)]

This attribute can be in particular used in the context of DS-Lite Multicast, MAP-E Multicast and other IPv4-IPv6 Multicast techniques. This attribute is however not limited to DS-Lite Multicast.

DS-Lite unicast RADIUS extensions are defined in [[RFC6519](#)] .

2. Convention and Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

The terms DS-Lite multicast Basic Bridging BroadBand element (mB4) and the DS-Lite multicast Address Family Transition Router element (mAFTR) are defined in [[I-D.ietf-softwire-dslite-multicast](#)]

3. Multicast-Prefixes-64 Configuration with RADIUS and DHCPv6

Figure 1 illustrates in DS-Lite scenario how the RADIUS protocol and DHCPv6 work together to accomplish Multicast-Prefixes-64 configuration on the mB4 element for multicast service when an IP session is used to provide connectivity to the user.




Figure 1: RADIUS and DHCPv6 Multicast-Prefixes-64 attribute Message Flow for a IP Session

The NAS operates as a client of RADIUS and as a DHCP Server/Relay for mB4. When the mB4 sends a DHCPv6 Solicit message to NAS (DHCP Server/Relay). The NAS sends a RADIUS Access-Request message to the RADIUS server, requesting authentication. Once the RADIUS server receives the request, it validates it based on the sending client, and if the request is approved, the AAA server replies with an Access-Accept message including a list of attribute-value pairs that describe the parameters to be used for this session. This list MAY contain the Multicast-Prefixes-64 attribute (asm-length, ASM_PREFIX64, ssm-length, SSM_PREFIX64, unicast-length, U_PREFIX64). Then, when the NAS receives the DHCPv6 Request message containing the OPTION_PREFIX64 option, the NAS SHALL use the prefixes returned in the RADIUS Multicast-Prefixes-64 attribute to populate the DHCPv6 OPTION_PREFIX64 option in the DHCPv6 reply message.

If the NAS does not receive the Multicast-Prefixes-64 attribute in

the Access-Accept message, it MAY fall back to a pre-configured

default Multicast-Prefixes-64, if any. If the NAS does not have any pre-configured, the delivery of multicast traffic is not supported.

NAS MAY be configured to return the configured Multicast-Prefixes-64 by the AAA Server to any requesting client without relaying each received request to the AAA Server.

Figure 2 describes another scenario, which accomplish DS-Lite Multicast-Prefixes-64 configuration on the mB4 element for multicast service when a PPP session is used to provide connectivity to the user. Once the NAS obtains the Multicast-Prefixes-64 attribute from the AAA server through the RADIUS protocol, the NAS MUST store the received Multicast-Prefixes-64 locally. When a user is online and sends a DHCPv6 Request message , the NAS retrieves the previously stored Multicast-Prefixes-64 and uses it as OPTION_PREFIX64 option in DHCPv6 Reply message.




Figure 2: RADIUS and DHCPv6 Multicast-Prefixes-64 attribute Message

Flow for a PPP Session

According to [[RFC3315](#)], if the DHCPv6 server to which the DHCPv6 Renew message was sent at time T1 has not responded, the DHCPv6 client initiates a Rebind/Reply message exchange with any available server. In this scenario, the NAS receiving the DHCPv6 Rebind message MUST initiate a new Access-Request message towards the AAA server. The NAS MAY include the Multicast-Prefixes-64 attribute in its Access-Request message.

4. RADIUS Attribute

This section specifies the format of the new RADIUS attribute.

4.1. Multicast-Prefixes-64

The Multicast-Prefixes-64 attribute conveys the IPv6 prefixes to be used in [[I-D.ietf-softwire-dslite-multicast](#)] to synthesize IPv4-embedded IPv6 addresses. The NAS SHALL use the IPv6 prefixes returned in the RADIUS Multicast-Prefixes-64 attribute to populate the DHCPv6 PREFIX64 Option [[I-D.ietf-softwire-multicast-prefix-option](#)] .

This attribute MAY be used in Access-Request packets as a hint to the RADIUS server, for example, if the NAS is pre-configured with Multicast-Prefixes-64, these prefixes MAY be inserted in the attribute. The RADIUS server MAY ignore the hint sent by the NAS, and it MAY assign a different Multicast-Prefixes-64 attribute.

If the NAS includes the Multicast-Prefixes-64 attribute, but the AAA server does not recognize it, this attribute MUST be ignored by the AAA server.

NAS MAY be configured with both ASM and SSM prefixes or only one of them. Concretely, AAA server MAY return ASM or SSM prefix based on the user profile and service policies. AAA MAY return both ASM and SSM prefixes. When SSM prefix is returned by the AAA server, unicast IPv4-Embedded IPv6 prefix MUST also be returned by the AAA server.

If the NAS does not receive the Multicast-Prefixes-64 attribute in the Access-Accept message, it MAY fall back to a pre-configured default Multicast-Prefixes-64, if any. If the NAS does not have any pre-configured, the delivery of multicast traffic is not supported.

If the NAS is pre-provisioned with a default Multicast-Prefixes-64 and the Multicast-Prefixes-64 received in the Access-Accept message are different from the configured default, then the Multicast-Prefixes-64 attribute received in the Access-Accept message MUST be used for the session.

A summary of the Multicast-Prefixes-64 RADIUS attribute format is shown Figure 3. The fields are transmitted from left to right.


```

0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5
+-+--+--+--+--+--+--+--+--+--+
|      Type      |      Length   |
+-+--+--+--+--+--+--+--+--+--+
|  asm-length    |                |
+-+--+--+--+--+--+--+--+--+--+
:                :
:  ASM_PREFIX64 (12 octets) :
+-+--+--+--+--+--+--+--+--+--+
|  ssm-length    |                |
+-+--+--+--+--+--+--+--+--+--+
:                :
:  SSM_PREFIX64 (12 octets) :
+-+--+--+--+--+--+--+--+--+--+
| unicast-length|                |
+-+--+--+--+--+--+--+--+--+--+
:                :
:  U_PREFIX64 (12 octets)   :
+-+--+--+--+--+--+--+--+--+--+

```

Figure 3: RADIUS attribute format for Multicast-Prefixes-64

Type:

145 for Multicast-Prefixes-64

Length:

This field indicates the total length in octets of this attribute including the Type and Length fields, and the length in octets of the PREFIX field. Equals to 41 octets.

asm-length:

The length for the ASM IPv4-embdded IPv6 prefix in bits. If the field is set to 0, all bits of ASM_PREFIX64 field MUST be set to zeros.

ASM_PREFIX64:

This field identifies the IPv6 multicast prefix to be used to synthesize the IPv4-embedded IPv6 addresses [[I-D.ietf-mboned-64-multicast-address-format](#)] of the multicast groups for the ASM mode.

ssm-length:

The length for the SSM IPv4-embdded IPv6 prefix in bits. If the field is set to 0, all bits of SSM_PREFIX64 field MUST be set to zeros.

SSM_PREFIX64:

This field identifies the IPv6 multicast prefix to be used to synthesize the IPv4-embedded IPv6 addresses [[I-D.ietf-mboned-64-multicast-address-format](#)] of the multicast groups for the SSM mode.

unicast-length:

The length for the unicast IPv4-embedded IPv6 prefix in bits. If the field is set to 0, all bits of U_PREFIX64 field MUST be set to zeros.

U_PREFIX64:

This field identifies the IPv6 unicast prefix [[RFC6052](#)] to be used in SSM mode for constructing the IPv4-embedded IPv6 addresses of the multicast sources. It MAY also be used to extract the IPv4 address from the received multicast data flows.

5. Table of Attributes

The following tables provide a guide to which attributes may be found in which kinds of packets, and in what quantity.

The following table defines the meaning of the above table entries.

Access-Request	Access-Accept	Access-Reject	Challenge	Accounting-Request	#	Attribute
0-1	0-1	0	0	0-1	145	Multicast-Prefixes-64

CoA-Request	CoA-ACK	CoA-NACK	#	Attribute
0-1	0	0	145	Multicast-Prefixes-64

0 This attribute MUST NOT be present in the packet.

0+ Zero or more instances of this attribute MAY be present in the packet.

0-1 Zero or one instances of this attribute MAY be present in the packet.

1 Exactly one instances of this attribute MAY be present in the packet.

6. Security Considerations

This document has no additional security considerations beyond those already identified in [[RFC2865](#)] for the RADIUS protocol and in [[RFC5176](#)] for CoA messages.

The security considerations documented in [[RFC3315](#)] and [[RFC6052](#)] are to be considered.

7. IANA Considerations

Per this document, IANA has allocated a new RADIUS attribute type from the IANA registry "Radius Attribute Types" located at <http://www.iana.org/assignments/radius-types>.

Multicast-Prefixes-64 - 145

8. Normative References

- [I-D.ietf-mboned-64-multicast-address-format]
Boucadair, M., Qin, J., Lee, Y., Venaas, S., Li, X., and M. Xu, "IPv6 Multicast Address With Embedded IPv4 Multicast Address", [draft-ietf-mboned-64-multicast-address-format-04](#) (work in progress), August 2012.
- [I-D.ietf-softwire-dslite-multicast]
Qin, J., Boucadair, M., Jacquenet, C., Lee, Y., and Q. Wang, "Delivery of IPv4 Multicast Services to IPv4 Clients over an IPv6 Multicast Network", [draft-ietf-softwire-dslite-multicast-04](#) (work in progress), October 2012.
- [I-D.ietf-softwire-multicast-prefix-option]
Boucadair, M., Qin, J., Tsou, T., and X. Deng, "DHCPv6 Option for IPv4-Embedded Multicast and Unicast IPv6 Prefixes", [draft-ietf-softwire-multicast-prefix-option-03](#) (work in progress), October 2012.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2865] Rigney, C., Willens, S., Rubens, A., and W. Simpson, "Remote Authentication Dial In User Service (RADIUS)", [RFC 2865](#), June 2000.
- [RFC3315] Droms, R., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", [RFC 3315](#), July 2003.
- [RFC5176] Chiba, M., Dommety, G., Eklund, M., Mitton, D., and B. Aboba, "Dynamic Authorization Extensions to Remote Authentication Dial In User Service (RADIUS)", [RFC 5176](#), January 2008.
- [RFC6052] Bao, C., Huitema, C., Bagnulo, M., Boucadair, M., and X. Li, "IPv6 Addressing of IPv4/IPv6 Translators", [RFC 6052](#), October 2010.
- [RFC6519] Maglione, R. and A. Durand, "RADIUS Extensions for Dual-Stack Lite", [RFC 6519](#), February 2012.

Authors' Addresses

Qian Wang
China Telecom
No.118, Xizhimennei
Beijing 100035
China

Email: wangqian@ctbri.com.cn

Wei Meng
ZTE Corporation
No.50 Software Avenue, Yuhuatai District
Nanjing
China

Email: meng.wei2@zte.com.cn, vally.meng@gmail.com

Cui Wang
ZTE Corporation
No.50 Software Avenue, Yuhuatai District
Nanjing
China

Email: wang.cui1@zte.com.cn

Mohamed Boucadair
France Telecom
Rennes, 35000
France

Email: mohamed.boucadair@orange.com

