

BMWG
Internet-Draft
Intended status: Informational
Expires: January 18, 2018

L. Huang, Ed.
R. Gu, Ed.
China Mobile
Bob. Mandeville
Iometrix
Brooks. Hickman
Spirent Communications
July 17, 2017

Benchmarking Methodology for Virtualization Network Performance
draft-huang-bmwg-virtual-network-performance-03

Abstract

As the virtual network has been widely established in IDC, the performance of virtual network has become a valuable consideration to the IDC managers. This draft introduces a benchmarking methodology for virtualization network performance based on virtual switch.

Status of This Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 18, 2018.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

Table of Contents

1.	Introduction	2
2.	Terminology	3
3.	Test Considerations	3
4.	Key Performance Indicators	5
5.	Test Setup	6
6.	Benchmarking Tests	7
6.1.	Throughput	7
6.1.1.	Objectives	7
6.1.2.	Configuration parameters	7
6.1.3.	Test parameters	8
6.1.4.	Test process	8
6.1.5.	Test result format	8
6.2.	Frame loss rate	8
6.2.1.	Objectives	9
6.2.2.	Configuration parameters	9
6.2.3.	Test parameters	9
6.2.4.	Test process	9
6.2.5.	Test result format	10
6.3.	CPU consumption	10
6.3.1.	Objectives	10
6.3.2.	Configuration parameters	10
6.3.3.	Test parameters	11
6.3.4.	Test process	11
6.3.5.	Test result format	11
6.4.	MEM consumption	12
6.4.1.	Objectives	12
6.4.2.	Configuration parameters	12
6.4.3.	Test parameters	13
6.4.4.	Test process	13
6.4.5.	Test result format	13
6.5.	Latency	14
6.5.1.	Objectives	15
6.5.2.	Configuration parameters	15
6.5.3.	Test parameters	15
6.5.4.	Test process	15
6.5.5.	Test result format	15
7.	Security Considerations	16
8.	IANA Considerations	16
9.	Normative References	16
	Authors' Addresses	17

[1.](#) Introduction

As the virtual network has been widely established in IDC, the performance of virtual network has become a valuable consideration to the IDC managers. This draft introduces a benchmarking methodology

for virtualization network performance based on virtual switch as the DUT.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

3. Test Considerations

In a conventional test setup with Non-Virtual test ports, it is quite legitimate to assume that test ports provide the golden standard in measuring the performance metrics. If test results are sub optimal, it is automatically assumed that the Device-Under-Test (DUT) is at fault. For example, when testing throughput at a given frame size, if the test result shows less than 100% throughput, we can safely conclude that it's the DUT that can not deliver line rate forwarding at that frame size(s). We never doubt that the tester can be an issue.

While in a virtual test environment where both the DUT as well as the test tool itself are software based, it's quite a different story. Just like the DUT, tester running as software will have its own performance peak under various conditions.

There are two types of vSwitch according to different installation location. One is VM based vSwitch which is installed on a virtual machine, another is vSwitch directly installed on the host OS (similar to hypervisor).The latter is much more popular currently.

Tester's calibration is essential in benchmarking testing in a virtual environment. Furthermore, to reduce the enormous combination of various conditions, tester must be calibrated with the exact same combination and parameter settings the user wants to measure against the DUT. A slight variation of conditions and parameter values will cause inaccurate measurements of the DUT.

While it is difficult to list the exact combination and parameter settings, the following table attempts to give the most common example how to calibrate a tester before testing a DUT (VSWITCH).

Sample calibration permutation:

Hypervisor	VM VNIC	VM Memory	Frame	
Type	Speed	CPU Allocation	Size	Throughput
ESXi	1G/10G	512M/1Core	64	
			128	
			256	
			512	
			1024	
			1518	

Figure 1: Sample Calibration Permutation

Key points are as following:

a) The hypervisor type is of ultimate importance to the test results. VM tester(s) MUST be installed on the same hypervisor type as the DUT (VSWITCH). Different hypervisor type has an influence on the test result.

b) The VNIC speed will have an impact on testing results. Testers MUST calibrate against all VNIC speeds.

c) VM allocations of CPU resources and memory have an influence on test results.

d) Frame sizes will affect the test results dramatically due to the nature of virtual machines.

e) Other possible extensions of above table: The number of VMs to be created, latency reading, one VNIC per VM vs. multiple VM sharing one VNIC, and uni-directional traffic vs. bi-directional traffic.

Besides, the compute environment including the hardware should be also recorded.

Compute environment componenets	Model
CPU	
Memory	
Hard Disk	
10G Adaptors	
Blade/Motherboard	

Figure 2: Compute Environment

It's important to confirm test environment for tester's calibration as close to the environment a virtual DUT (VSWITCH) involved in for the benchmark test. Key points which SHOULD be noticed in test setup are listed as follows.

1. One or more VM tester(s) need to be created for both traffic generation and analysis.
2. vSwitch has an influence on performance penalty due to extra resource occupation.
3. VNIC and its type is needed in the test setup to once again accommodate performance penalty when DUT (VSWITCH) is created.

In summary, calibration should be done in such an environment that all possible factors which may negatively impact test results should be taken into consideration.

4. Key Performance Indicators

We listed numbers of key performance indicators for virtual network below:

- a) Throughput under various frame sizes: forwarding performance under various frame sizes is a key performance indicator of interest.
- b) DUT consumption of CPU: when adding one or more VM(s), DUT (VSWITCH) will consume more CPU. Vendors can allocate appropriate CPU to reach the line rate performance.

This test setup is also available in the VxLAN measurement.

6. Benchmarking Tests

6.1. Throughput

Unlike traditional test cases where the DUT and the tester are separated, virtual network test has been brought in unparalleled challenges. In virtual network test, the virtual tester and the DUT (VSWITCH) are in one server which means they are physically converged, so the test and DUT (VSWITCH) are sharing the same CPU and MEM resources of one server. Theoretically, the virtual tester's operation may have influence on the DUT (VSWITCH)'s performance. However, for the specialty of virtualization, this method is the only way to test the performance of a virtual DUT.

Under the background of existing technology, when we test the virtual switch's throughput, the concept of traditional physical switch CANNOT be applicable. The traditional throughput indicates the switches' largest forwarding capability, for certain bytes selected and under zero-packet-lose conditions. But in virtual environments, virtual variations on virtual network will be much greater than that of dedicated physical devices. As the DUT and the tester cannot be separated, it proves that the DUT (VSWITCH) realize such network performances under certain circumstances.

Therefore, we change the bytes in virtual environment to test the maximum value which we think of the indicator of throughput. It's conceivable that the throughput should be tested on both the test model A and B. The tested throughput has certain referential meanings to value the performance of the virtual DUT.

6.1.1. Objectives

The objective of the test is to determine the throughput of the DUT (VSWITCH), which the DUT can support.

6.1.2. Configuration parameters

Network parameters should be defined as follows:

- a) the number of virtual tester (VMs)
- b) the number of vNIC of virtual tester
- c) the CPU type of the server
- d) vCPU allocated for virtual tester (VMs)

- e) memory allocated for virtual tester (VMs)
- f) the number and rate of server NIC

6.1.3. Test parameters

- a) test repeated times
- b) test frame length

6.1.4. Test process

1. Configure the VM tester to offer traffic to the V-Switch.
2. Increase the traffic rate of tester until packet loss happens.
3. Record the max traffic rate without packet loss on VSwitch.
4. Change the frame length and repeat from step1 to step4.

6.1.5. Test result format

Byte	Throughput (Gbps)
64	
128	
256	
512	
1024	
1518	

Figure 5: test result format

6.2. Frame loss rate

Frame loss rate is also an important indicator in evaluating the performance of virtual switch. As is defined in [RFC 1242](#), percentage of frames that should have been forwarded which actually fails to be forwarded due to lack of resources needs to be tested. Both model A

and model B are tested. Frame loss rate is an important indicator in evaluating the performance of virtual switches.

6.2.1. Objectives

The objective of the test is to determine the frame loss rate under different data rates and frame sizes..

6.2.2. Configuration parameters

Network parameters should be defined as follows:

- a) the number of virtual tester (VMs)
- b) the number of vNIC of virtual tester
- c) the CPU type of the server
- d) vCPU allocated for virtual tester (VMs)
- e) memory allocated for virtual tester (VMs)
- f) the number and rate of server NIC

6.2.3. Test parameters

- a) test repeated times
- b) test frame length
- c) test frame rate

6.2.4. Test process

1. Configure the VM tester to offer traffic to the V-Switch with the input frame changing from the maximum rate to the rate with no frame loss at reducing 10% intervals according to [RFC 2544](#).
2. Record the input frame count and output count on VSwitch.
3. Calculate the frame loss percentage under different frame rate.
4. Change the frame length and repeat from step1 to step4.

6.2.5. Test result format

Byte	Maximum rate	90% Maximum	80% Maximum	...	rate with
	(Gbps)	rate (Gbps)	rate (Gbps)		no loss (Gbps)
64					
128					
256					
512					
1024					
1518					

Figure 6: test result format

6.3. CPU consumption

The objective of the test is to determine the CPU load of DUT(VSWITCH). The operation of DUT (VSWITCH) can increase the CPU load of host server. Different V-Switches have different CPU occupation. This can be an important indicator in benchmarking the virtual network performance.

6.3.1. Objectives

The objective of this test is to verify the CPU consumption caused by the DUT (VSWITCH).

6.3.2. Configuration parameters

Network parameters should be defined as follows:

- the number of virtual tester (VMs)
- the number of vNIC of virtual tester
- the CPU type of the server
- vCPU allocated for virtual tester (VMs)
- memory allocated for virtual tester (VMs)

- f) the number and rate of server NIC

6.3.3. Test parameters

- a) test repeated times
- b) test frame length
- c) traffic rate

6.3.4. Test process

1. Configure the VM tester to offer traffic to the V-Switch with certain traffic rate. The traffic rate could be different ratio of NIC's speed.
2. Record vSwitch's CPU usage on the host OS if no packets loss happens.
3. Change the traffic rate and repeat from step1 to step2.
4. Change the frame length and repeat from step1 to step3.

6.3.5. Test result format

Byte	Traffic Rate(Gbps)	CPU usage of vSwitch

	50% of NIC speed	

64	75%	

	90%	

	50% of NIC speed	

128	75%	

	90%	

~	~	~

	50% of NIC speed	

1500	75%	

	90%	

Figure 7: test result format

6.4. MEM consumption

The objective of the test is to determine the Memory load of DUT(VSWITCH). The operation of DUT (VSWITCH) can increase the Memory load of host server. Different V-Switches have different memory occupation. This can be an important indicator in benchmarking the virtual network performance.

6.4.1. Objectives

The objective of this test is to verify the memory consumption by the DUT (VSWITCH) on the Host server.

6.4.2. Configuration parameters

Network parameters should be defined as follows:

- a) the number of virtual tester (VMs)
- b) the number of vNIC of virtual tester
- c) the CPU type of the server

- d) vCPU allocated for virtual tester (VMs)
- e) memory allocated for virtual tester (VMs)
- f) the number and rate of server NIC

6.4.3. Test parameters

- a) test repeated times
- b) test frame length

6.4.4. Test process

1. Configure the VM tester to offer traffic to the V-Switch with certain traffic rate. The traffic rate could be different ratio of NIC's speed.
2. Record vSwitch's MEM usage on the host OS if no packets loss happens.
3. Change the traffic rate and repeat from step1 to step2.
4. Change the frame length and repeat from step1 to step3.

6.4.5. Test result format

Byte	Traffic Rate(Gbps)	MEM usage of vSwitch
	50% of NIC speed	
64	75%	
	90%	
	50% of NIC speed	
128	75%	
	90%	
~	~	~
	50% of NIC speed	
1500	75%	
	90%	

Figure 8: test result format

6.5. Latency

Physical tester's time refers from its own clock or other time source, such as GPS, which can achieve the accuracy of 10ns. While in virtual network circumstances, the virtual tester gets its reference time from the clock of Linux systems and it's hard to make the physical and virtual tester keep precisely synchronized. So We use the traffic model B as the latency test model.




Figure 9: time delay test model

6.5.1. Objectives

The objective of this test is to verify the DUT (VSWITCH) for latency of the flow. This can be an important indicator in benchmarking the virtual network performance.

6.5.2. Configuration parameters

Network parameters should be defined as follows:

- a) the number of virtual tester (VMs)
- b) the number of vNIC of virtual tester
- c) the CPU type of the server
- d) vCPU allocated for virtual tester (VMs)
- e) memory allocated for virtual tester (VMs)
- f) the number and rate of server NIC

6.5.3. Test parameters

- a) test repeated times
- b) test frame length

6.5.4. Test process

1. Configure the virtual tester to offer traffic to the V-Switch with the traffic value of throughput tested in 6.1.
2. Keep the traffic for a while and then stop it, record the minimum, maximum and average latency.
3. Change the frame length and repeat from step1 to step4.

6.5.5. Test result format

Byte	Min Latency	Max Latency	Average Latency
64			
128			
256			
512			
1024			
1518			

Figure 10: test result format

7. Security Considerations

None.

8. IANA Considerations

None.

9. Normative References

- [RFC1242] Bradner, S., "Benchmarking Terminology for Network Interconnection Devices", [RFC 1242](#), DOI 10.17487/RFC1242, July 1991, <<http://www.rfc-editor.org/info/rfc1242>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", [RFC 2234](#), DOI 10.17487/RFC2234, November 1997, <<http://www.rfc-editor.org/info/rfc2234>>.
- [RFC2544] Bradner, S. and J. McQuaid, "Benchmarking Methodology for Network Interconnect Devices", [RFC 2544](#), DOI 10.17487/RFC2544, March 1999, <<http://www.rfc-editor.org/info/rfc2544>>.

Authors' Addresses

Lu Huang (editor)
China Mobile
32 Xuanwumen West Ave, Xicheng District
Beijing 100053
China

Email: hlisname@yahoo.com

Rong Gu (editor)
China Mobile
32 Xuanwumen West Ave, Xicheng District
Beijing 100053
China

Email: gurong@chinamobile.com

Bob Mandeville
Iometrix
3600 Fillmore Street Suite 409
San Francisco, CA 94123
USA

Email: bob@iometrix.com

Brooks Hickman
Spirent Communications
1325 Borregas Ave
Sunnyvale, CA 94089
USA

Email: Brooks.Hickman@spirent.com

