

Internet Draft  
Document: [draft-iab-e2e-futures-05.txt](#)  
Expires: August 2004

James Kempf  
Rob Austein  
IAB  
February 2004

## **The Rise of the Middle and the Future of End to End: Reflections on the Evolution of the Internet Architecture**

### Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force

(IETF), its areas, and its working groups. Note that other groups may also

distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at

<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at

<http://www.ietf.org/shadow.html>.

### Abstract

The end to end principle is the core architectural guideline of the Internet. In this document, we briefly examine the development of the end to end principle as it has been applied to the Internet architecture over the years. We discuss current trends in the evolution of the Internet architecture in relation to the end to end principle, and try to draw some conclusion about the

evolution of the end to end principle, and thus for the Internet architecture which it supports, in light of these current trends.

### Table of Contents

<a href="#">1.0</a>	
Introduction.....	<a href="#">2</a>
<a href="#">2.0</a> A Brief History of the End to End	
Principle.....	<a href="#">2</a>
<a href="#">3.0</a> Trends Opposed to the End to End	
Principle.....	<a href="#">4</a>

<a href="#">4.0</a>	Whither the End to End	
	Principle?.....	<a href="#">7</a>
<a href="#">5.0</a>	Internet Standards as an Arena for	
	Conflict.....	<a href="#">8</a>
<a href="#">6.0</a>		
	Conclusions.....	<a href="#">9</a>
<a href="#">7.0</a>		
	Acknowledgements.....	<a href="#">9</a>
<a href="#">8.0</a>		
	References.....	<a href="#">9</a>
<a href="#">9.0</a>	Security Considerations.....	
<a href="#">10</a>		
<a href="#">10.0</a>	IANA Considerations.....	
<a href="#">10</a>		

<a href="#">11.0</a>	<a href="#">Author Information.....</a>	
<a href="#">10</a>		
<a href="#">12.0</a>	<a href="#">Full Copyright Statement.....</a>	
<a href="#">11</a>		

## 1.0 Introduction

One of the key architectural guidelines of the Internet is the end to end principle in the papers by Saltzer, Reed, and Clark [[1](#)][2]. The end to end principle was originally articulated as a question of where best not to put functions in a communication system. Yet, in the ensuing years, it has evolved

to address concerns of maintaining openness, increasing reliability and

robustness, and preserving the properties of user choice and ease of new service development as discussed by Blumenthal and Clark in [3]; concerns that

were not part of the original articulation of the end to end principle.

In this document, we examine how the interpretation of the end to end principle

has evolved over the years, and where it stands currently. We examine trends in

the development of the Internet that have led to pressure to define services in

the network, a topic that has already received some amount of attention from the IAB in [RFC 3238](#) [5]. We describe some considerations about how the end to end principle might evolve in light of these trends.

## 2.0 A Brief History of the End to End Principle

### [2.1](#) In the Beginning...

The end to end principle was originally articulated as a question of where best

to put functions in a communication system:

The function in question can completely and correctly be implemented only with the knowledge and help of the application standing at the end points of

the communication system. Therefore, providing that questioned function as a

feature of the communication system itself is not possible. (Sometimes an incomplete version of the function provided by the communication system may

be useful as a performance enhancement.) [[1](#)].

A specific example of such a function is delivery guarantees [[1](#)]. The original

ARPANET returned a message "Request for Next Message" whenever it delivered a packet. Although this message was found to be useful within the network as a form of congestion control, since the ARPANET refused to accept another message

to the same destination until the previous acknowledgment was returned, it was

never particularly useful as an indication of guaranteed delivery. The problem

was that the host stack on the sending host typically doesn't want to know just

that the network delivered a packet, but rather the stack layer on the sending

host wants to know that the stack layer on the receiving host properly processed the packet. In terms of modern IP stack structure, a reliable transport layer requires an indication that transport processing has successfully completed, such as given by TCP's ACK message [4], and not simply

an indication from the IP layer that packet arrived. Similarly, an application

layer protocol may require an application-specific acknowledgement that

contains, among other things, a status code indicating the disposition of the request.

The specific examples given in [1] and other references at the time [2] primarily involve transmission of data packets: data integrity, delivery guarantees, duplicate message suppression, per packet encryption, and transaction management. From the viewpoint of today's Internet architecture, we would view most of these as transport layer functions (data integrity, delivery guarantees, duplicate message suppression, and perhaps transaction management), others as network layer functions with support at other layers where necessary (for example, packet encryption), and not application layer functions.

## **2.2 ...In the Middle...**

As the Internet developed, the end to end principle gradually widened to concerns about where best to put the state associated with applications in the Internet: in the network or at end nodes. The best example is the description in [RFC 1958](#) [6]:

This principle has important consequences if we require applications to survive partial network failures. An end-to-end protocol design should not rely on the maintenance of state (i.e. information about the state of the end-to-end communication) inside the network. Such state should be maintained only in the endpoints, in such a way that the state can only be destroyed when the endpoint itself breaks (known as fate-sharing). An immediate consequence of this is that datagrams are better than classical virtual circuits. The network's job is to transmit datagrams as efficiently and flexibly as possible. Everything else should be done at the fringes.

The original articulation of the end to end principle - that knowledge and assistance of the end point is essential and that omitting such knowledge and implementing a function in the network without such knowledge and assistance is not possible - took a while to percolate through the engineering community, and had evolved by this point to a broad architectural statement about what belongs in the network and what doesn't. [RFC 1958](#) uses the term "application" to mean the entire network stack on the end node, including network, transport, and application layers, in contrast to the earlier articulation of the end to end principle as being about the communication system itself. "Fate-sharing" describes this quite clearly: the fate of a conversation between two applications is only shared between the two applications; the fate does not depend on anything in the network, except for the network's ability to get

packets from one application to the other.

The end to end principle in this formulation is specifically about what kind of state is maintained where:

To perform its services, the network maintains some state information: routes, QoS guarantees that it makes, session information where that is used in header compression, compression histories for data compression, and the like. This state must be self-healing; adaptive procedures or protocols must exist to derive and maintain that state, and change it when the topology or activity of the network changes. The volume of this state must be minimized, and the loss of the state must not result in more than a temporary denial of service given that connectivity exists. Manually configured state must be kept to an absolute minimum.[6]

In this formulation of the end to end principle, state involved in getting packets from one end of the network to the other is maintained in the network.

The state is "soft state," in the sense that it can be quickly dropped and reconstructed (or even required to be periodically renewed) as the network topology changes due to routers and switches going on and off line. "Hard state", state upon which the proper functioning of the application depends, is

only maintained in the end nodes. This formulation of the principle is a definite change from the original formulation of the principle, about end node

participation being required for proper implementation of most functions.

In summary, the general awareness both of the principle itself and of its implications for how unavoidable state should be handled grew over time to become a (if not the) foundation principle of the Internet architecture.

### [2.3](#) ...And Now.

An interesting example of how the end to end principle continues to influence the technical debate in the Internet community is IP mobility. The existing Internet routing architecture severely constrains how closely IP mobility can match the end to end principle without making fundamental changes. Mobile IPv6,

described in the Mobile IPv6 specification by Johnson, Perkins, and Arkko [7],

requires a routing proxy in the mobile node's home network (the Home Agent) for

maintaining the mapping between the mobile node's routing locator, the care of

address, and the mobile node's node identifier, the home address. But the local

subnet routing proxy (the Foreign Agent), which was a feature of the older Mobile IPv4 design that compromised end to end routing, has been eliminated. The end node now handles its own care of address. In addition, Mobile IPv6 includes secure mechanisms for optimizing routing to allow end to end routing between the mobile end node and the correspondent node, removing the need to route through the global routing proxy at the home agent. These features are all based on end to end considerations. However, the need for the global routing proxy in the Home Agent in Mobile IPv6 is determined by the aliasing of

the global node identifier with the routing identifier in the Internet routing

architecture, a topic that was discussed in an IAB workshop and reported in RFC

[2956](#) [9], and that hasn't changed in IPv6.

Despite this constraint, the vision emerging out of the IETF working groups developing standards for mobile networking is of a largely autonomous mobile

node with multiple wireless link options, among which the mobile node picks and chooses. The end node is therefore responsible for maintaining the integrity of the communication, as the end to end principle implies. This kind of innovative application of the end to end principle derives from the same basic considerations of reliability and robustness (wireless link integrity, changes in connectivity and service availability with movement, etc.) that motivated the original development of the end to end principle. While the basic reliability of wired links and routing and switching equipment has improved considerably since the end to end principle was formalized 15 years ago, the reliability or unreliability of wireless links is governed more strongly by the basic physics of the medium and the instantaneous radio propagation conditions.

### 3.0 Trends Opposed to the End to End Principle

While the end to end principle continues to provide a solid foundation for much IETF design work, the specific application of the end to end principle



described in RFC 1958 has increasingly come into question from various directions. The IAB has been concerned about trends opposing the end to end principle for some time, for example [RFC 2956](#) [9] and [RFC 2775](#) [12]. The primary focus of concern in these documents is the reduction in transparency due to the introduction of NATs and other address translation mechanisms in the Internet, and the consequences to the end to end principle of various scenarios involving full, partial, or no deployment of IPv6. More recently, the topic of concern has shifted to the consequences of service deployment in the network. The IAB opinion on Open Pluggable Edge Services (OPES) in [RFC 3238](#) [5] is intended to assess the architectural desirability of defining services in the network and to raise questions about how such services might result in compromises of privacy, security, and end-to-end data integrity. Clark, et al. in [10] and Carpenter in [RFC 3234](#) [11] also take up the topic of service definition in the network.

Perhaps the best review of the forces militating against the end to end principle is by Blumenthal and Clark in [3]. The authors make the point that the Internet originally developed among a community of like-minded technical professionals who trusted each other, and was administered by academic and government institutions who enforced a policy of no commercial use. The major stakeholders in the Internet are quite different today. As a consequence, new requirements have evolved over the last decade. Examples of these requirements are discussed in the following subsections. Other discussions about pressures on the end to end principle in today's Internet can be found in the discussion by Reed [13] and Moors' paper in the 2002 IEEE International Communications Conference [14].

### **[3.1](#) Need for Authentication**

Perhaps the single most important change from the Internet of 15 years ago is the lack of trust between users. Because the end users in the Internet of 15 years ago were few, and were largely dedicated to using the Internet as a tool for academic research and communicating research results (explicit commercial use of the Internet was forbidden when it was run by the US government), trust between end users (and thus authentication of end nodes that they use) and between network operators and their users was simply not an issue in general. Today, the motivations of some individuals using the Internet are not always entirely ethical, and, even if they are, the assumption that end nodes will always co-operate to achieve some mutually beneficial action, as implied by the

end to end principle, is not always accurate. In addition, the growth in users who are either not technologically sophisticated enough or simply uninterested in maintaining their own security has required network operators to become more proactive in deploying measures to prevent naive or uninterested users from inadvertently or intentionally generating security problems.

While the end to end principle does not require that users implicitly trust each other, the lack of trust in the Internet today requires that application and system designers make a choice about how to handle authentication, whereas that choice was rarely apparent 15 years ago. One of the most common examples of network elements interposing between end hosts are those dedicated to security: firewalls, VPN tunnel endpoints, certificate servers, etc. These intermediaries are designed to protect the network from unimpeded attack or to allow two end nodes whose users may have no inherent reason to trust each other to achieve some level of authentication. At the same time, these measures act

as impediments for end to end communications. Third party trust intermediaries

are not a requirement for security, as end to end security mechanisms, such as

S/MIME [15], can be used instead, and where third party measures such as PKI infrastructure or keys in DNS are utilized to exchange keying material, they don't necessarily impinge on end to end traffic after authentication has been achieved. Even if third parties are involved, ultimately it is up to the endpoints and their users in particular, to determine which third parties they trust.

### **3.2 New Service Models**

New service models inspired by new applications require achieving the proper performance level as a fundamental part of the delivered service. These service

models are a significant change from the original best effort service model. Email, file transfer, and even Web access aren't perceived as failing if performance degrades, though the user may become frustrated at the time required to complete the transaction. However, for streaming audio and video, to say nothing of real time bidirectional voice and video, achieving the proper

performance level, whatever that might mean for an acceptable user experience of the service, is part of delivering the service, and a customer contracting for the service has a right to expect the level of performance for which they have contracted. For example, content distributors sometimes release content via content distribution servers that are spread around the Internet at various

locations to avoid delays in delivery if the server is topologically far away from the client. Retail broadband and multimedia services are a new service model for many service providers.

### **3.3 Rise of the Third Party**

Academic and government institutions ran the Internet of 15 years ago. These institutions did not expect to make a profit from their investment in

networking technology. In contrast, the network operator with which most Internet users deal today is the commercial ISP. Commercial ISPs run their networks as a business, and their investors rightly expect the business to turn

a profit. This change in business model has led to a certain amount of pressure on ISPs to increase business prospects by deploying new services.

In particular, the standard retail dialup bit pipe account with email and shell

access has become a commodity service, resulting in low profit margins. While

many ISPs are happy with this business model and are able to survive on it, others would like to deploy different service models that have a higher profit

potential and provide the customer with more or different services. An example

is retail broadband bit pipe access via cable or DSL coupled with streaming multimedia. Some ISPs that offer broadband access also deploy content

distribution networks to increase the performance of streaming media. These services are typically deployed so that they are only accessible within the ISP's network, and as a result, they do not contribute to open, end to end service. From an ISP's standpoint, however, offering such service is an incentive for customers to buy the ISP's service.

ISPs are not the only third party intermediary that has appeared within the last 10 years. Unlike the previous involvement of corporations and governments

in running the Internet, corporate network administrators, and governmental officials have become increasingly demanding of opportunities to interpose

between two parties in an end to end conversation. A benign motivation for this

involvement is to mitigate the lack of trust, so the third party acts as a trust anchor or enforcer of good behavior between the two ends. A less benign motivation is for the third parties to insert policy for their own reasons, perhaps taxation or even censorship. The requirements of third parties often have little or nothing to do with technical concerns, but rather derive from particular social and legal considerations.

#### 4.0 Whither the End to End Principle?

Given the pressures on the end to end principle discussed in the previous section, a question arises about the future of the end to end principle. Does the end to end principle have a future in the Internet architecture or not?

If

it does have a future, how should it be applied? Clearly, an unproductive approach to answering this question is to insist upon the end to end principle

as a fundamentalist principle that allows no compromise. The pressures

described above are real and powerful, and if the current Internet technical community chooses to ignore these pressures, the likely result is that a market

opportunity will be created for a new technical community that does not ignore

these pressures but which may not understand the implications of their design choices. A more productive approach is to return to first principles and re-examine what the end to end principle is trying to accomplish, and then

update

our definition and exposition of the end to end principle given the

complexities of the Internet today.

#### [4.1](#) Consequences of the End to End Principle

In this section, we consider the two primary desirable consequences of the end

to end principle: protection of innovation and provision of reliability and robustness.

##### [4.1.1](#) Protection of Innovation

One desirable consequence of the end to end principle is protection of innovation. Requiring modification in the network in order to deploy new services is still typically more difficult than modifying end nodes. The counterargument - that many end nodes are now essentially closed boxes which are not updatable and that most users don't want to update them anyway - does not apply to all nodes and all users. Many end nodes are still user

configurable and a sizable percentage of users are "early adopters," who are willing to put up with a certain amount of technological grief in order to try out a new idea. And, even for the closed boxes and uninvolved users, downloadable code that abides by the end to end principle can provide fast service innovation. Requiring someone with a new idea for a service to convince a bunch of ISPs or corporate network administrators to modify their networks is much more difficult than simply putting up a Web page with some downloadable software implementing the service.

#### [4.1.2](#) **Reliability and Trust**

Of increasing concern today, however, is the decrease in reliability and robustness that results from deliberate, active attacks on the network infrastructure and end nodes. While the original developers of the Internet were concerned by large-scale system failures, attacks of the subtlety and

variety that the Internet experiences today were not a problem during the original development of the Internet. By and large, the end to end principle was not addressed to the decrease in reliability resulting from attacks deliberately engineered to take advantage of subtle flaws in software. These attacks are part of the larger issue of the trust breakdown discussed in [Section 3.1](#). Thus, the issue of the trust breakdown can be considered another forcing function on the Internet architecture.

The immediate reaction to this trust breakdown has been to try to back fit security into existing protocols. While this effort is necessary, it is not sufficient. The issue of trust must become as firm an architectural principle in protocol design for the future as the end to end principle is today. Trust isn't simply a matter of adding some cryptographic protection to a protocol after it is designed. Rather, prior to designing the protocol, the trust relationships between the network elements involved in the protocol must be defined, and boundaries must be drawn between those network elements that share

a trust relationship. The trust boundaries should be used to determine what type of communication occurs between the network elements involved in the protocol and which network elements signal each other. When communication occurs across a trust boundary, cryptographic or other security protection of some sort may be necessary. Additional measures may be necessary to secure the

protocol when communicating network elements do not share a trust relationship.

For example, a protocol might need to minimize state in the recipient prior to

establishing the validity of the credentials from the sender in order to avoid

a memory depletion DoS attack.

#### [4.2](#) The End to End Principle in Applications Design

The concern expressed by the end to end principle is applicable to applications

design too. Two key points in designing application protocols are to ensure they don't have any dependencies that would break the end to end principle and

to ensure that they can identify end points in a consistent fashion. An example

of the former is layer violations - creating dependencies that would make it impossible for the transport layer, for example, to do its work appropriately.

Another issue is the desire to insert more applications infrastructure into the

network. Architectural considerations around this issue are discussed in RFC [3238](#) [5]. **This desire need not result in a violation the end to end principle** if the partitioning of functioning is done so that services provided in the network operate with the explicit knowledge and involvement of endpoints,

when

such knowledge and involvement is necessary for the proper functioning of the service. The result becomes a distributed application, in which the end to end

principle applies to each connection involved in implementing the application.

## 5.0 Internet Standards as an Arena for Conflict

Internet standards have increasingly become an arena for conflict [10]. ISPs have certain concerns, businesses and government have others, and vendors of networking hardware and software still others. Often, these concerns conflict,

and sometimes they conflict with the concerns of the end users. For example, ISPs are reluctant to deploy interdomain QoS services because, among other reasons, every known instance creates a significant and easily exploited DoS/DDoS vulnerability. However, some end users would like to have end-to-end,

Diffserv or Intserv-style QoS available to improve support for voice and video

multimedia applications between end nodes in different domains, as discussed by



Huston in [RFC 2990](#) [16]. In this case, the security, robustness and reliability concerns of the ISP conflict with the desire of users for a different type of service.

These conflicts will inevitably be reflected in the Internet architecture going forward. Some of these conflicts are impossible to resolve on a technical level, nor would it even be desirable, because they involve social and legal choices that the IETF is not empowered to make (for a counter argument in the area of privacy, see Goldberg, et al. [17]). But for those conflicts that do involve technical choices, the important properties of user choice and empowerment, reliability and integrity of end to end service, supporting trust and "good network citizen behavior," and fostering innovation in services should be the basis upon which resolution is made. The conflict will then play out on the field of the resulting architecture.

## 6.0 Conclusions

The end to end principle continues to guide technical development of Internet standards, and remains as important today for the Internet architecture as in the past. In many cases, unbundling of the end to end principle into its consequences leads to a distributed approach in which the end to end principle applies to interactions between the individual pieces of the application, while the unbundled consequences, protection of innovation and reliability and robustness, apply to the entire application. While the end to end principle originated as a focused argument about the need for the knowledge and assistance of end nodes to properly implement functions in a communication system, particular second order properties developed by the Internet as a result of the end to end principle have come to be recognized as being as important, if not more so, than the principle itself. End user choice and empowerment, integrity of service, support for trust, and "good network citizen behavior" are all properties that have developed as a consequence of the end to end principle. Recognizing these properties in a particular proposal for modifications to the Internet has become more important than before as the pressures to incorporate services into the network have increased. Any proposal to incorporate services in the network should be weighed against these

properties before proceeding.

## 7.0 Acknowledgements

Many of the ideas presented here originally appeared in the works of Dave Clark, John Wroclawski, Bob Braden, Karen Sollins, Marjory Blumenthal, and Dave

Reed on forces currently influencing the evolution of the Internet. The authors

would particularly like to single out the work of Dave Clark, who was the original articulator of the end to end principle and who continues to inspire and guide the evolution of the Internet architecture, and John Wroclawski, with

whom conversations during the development of this paper helped to clarify issues involving tussle and the Internet.

## 8.0 References

[1] Saltzer, J.H., Reed, D.P., and Clark, D.D., "End to End Arguments in System Design," ACM TOCS, Vol 2, Number 4, November 1984, pp 277-288.

- [2] Clark, D., "The Design Philosophy of the DARPA Internet Protocols," Proc SIGCOMM 88, ACM CCR Vol 18, Number 4, August 1988, pp. 106-114.
- [3] Blumenthal, M., Clark, D.D., "Rethinking the design of the Internet: The end to end arguments vs. the brave new world", ACM Transactions on Internet Technology, Vol. 1, No. 1, August 2001, pp 70-109.
- [4] Postel, J., "Transmission Control Protocol," [RFC 793](#), September, 1981.
- [5] Floyd, S., and Daigle, L., "IAB Architectural and Policy Considerations for Open Pluggable Edge Services", [RFC 3238](#), January 2002.
- [6] Carpenter, B. (editor), "Architectural Principles of the Internet," [RFC 1958](#), June, 1996.
- [7] Johnson, D., Perkins, C., and Arkko, J., "Mobility Support in IPv6," [draft-ietf-mobileip-ipv6-20.txt](#), a work in progress.
- [8] Perkins, C., editor, "Mobility Support in IPv4", [RFC 3220](#), August, 2002.
- [9] Kaat, M., "Overview of 1999 IAB Network Layer Workshop," [RFC 2956](#), October, 2000.
- [10] Clark, D.D., Wroclawski, J., Sollins, K., and Braden, B., "Tussle in Cyberspace: Defining Tomorrow's Internet", Proceedings of Sigcomm 2002.
- [11] Carpenter, B., and Brim, S., "Middleboxes: Taxonomy and Issues," [RFC 3234](#), February, 2002.
- [12] Carpenter, B., "Internet Transparency," [RFC 2775](#), February, 2000.
- [13] Reed, D., "The End of the End-to-End Argument?", <http://www.reed.com/dprframeweb/dprframe.asp?section=paper&fn=endofendtoend.html>, April, 2000.
- [14] Moors, T., "A Critical Review of End-to-end Arguments in System Design," Proc. 2000 IEEE International Conference on Communications, pp. 1214-1219, April, 2002.
- [15] Ramsdell, B. (editor), "S/MIME Version 3 Message Specification", [RFC 2633](#), June, 1999.
- [16] Huston, G., "Next Steps for the IP QoS Architecture", [RFC 2990](#), November, 2000.
- [17] Goldberg, I., Wagner, D., and Brewer, E., "Privacy-enhancing technologies for the Internet," Proceedings of IEEE COMPCON 97, pp. 103-109, 1997.

## 9.0 Security Considerations

This document does not propose any new protocols, and therefore does not involve any security considerations in that sense. However, throughout this document there are discussions of the privacy and integrity issues and the architectural requirements created by those issues.

## 10.0 IANA Considerations

There are no IANA considerations regarding this document.

## 11.0 Author Information

Internet Architecture Board

E-Mail: [iab@iab.org](mailto:iab@iab.org)

IAB Membership at time this document was completed:

Kempf and Austein Expires August 2004

[Page

Bernard Aboba  
Harald Alvestrand  
Rob Austein  
Leslie Daigle  
Patrik F. Faltstrom  
Sally Floyd  
Jun-ichiro Ito  
Jun Hagino  
Mark Handley  
Geoff Huston  
Charlie Kaufman  
James Kempf  
Eric Rescorla  
Mike St. Johns

This draft was created in February 2004.

## 12.0 Full Copyright Statement

Copyright (C) The Internet Society (2004). All Rights Reserved. This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English. The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns. This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

