

Network Working Group
Internet-Draft
Obsoletes: [7991](#) (if approved)
Intended status: Informational
Expires: April 22, 2019

P. Hoffman
ICANN
October 19, 2018

**The "xml2rfc" version 3 Vocabulary
draft-iab-rfc7991bis-01**

Abstract

This document defines the "xml2rfc" version 3 vocabulary: an XML-based language used for writing RFCs and Internet-Drafts. It is heavily derived from the version 2 vocabulary that is also under discussion. This document obsoletes the earlier v3 grammar described in [RFC 7991](#), which in turn obsoleted the v2 grammar in [RFC 7749](#).

Editorial Note (To be removed by RFC Editor)

Discussion of this draft takes place on the xml2rfc-dev@ietf.org mailing list, which has its home page at [<https://www.ietf.org/mailman/listinfo/xml2rfc-dev>](https://www.ietf.org/mailman/listinfo/xml2rfc-dev).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 22, 2019.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

| | | |
|------------------------|--|--------------------|
| 1. | Introduction | 5 |
| 1.1. | Expected Updates to the Specification | 5 |
| 1.2. | Design Criteria for the Changes in v3 | 5 |
| 1.3. | Differences from RFC 7991 in This Document | 6 |
| 1.4. | Differences from v2 to v3 | 6 |
| 1.4.1. | New Elements in v3 | 6 |
| 1.4.2. | New Attributes for Existing Elements | 8 |
| 1.4.3. | Elements and Attributes Deprecated from v2 | 8 |
| 1.4.4. | Additional Changes from v2 | 9 |
| 1.5. | Syntax Notation | 10 |
| 2. | Elements | 10 |
| 2.1. | <abstract> | 11 |
| 2.2. | <address> | 12 |
| 2.3. | <annotation> | 12 |
| 2.4. | <area> | 13 |
| 2.5. | <artwork> | 13 |
| 2.6. | <aside> | 17 |
| 2.7. | <author> | 17 |
| 2.8. | <back> | 19 |
| 2.9. | <bcp14> | 19 |
| 2.10. | <blockquote> | 20 |
| 2.11. | <boilerplate> | 21 |
| 2.12. | <city> | 22 |
| 2.13. | <code> | 22 |
| 2.14. | <country> | 22 |
| 2.15. | <cref> | 22 |
| 2.16. | <date> | 24 |
| 2.17. | <dd> | 25 |
| 2.18. | <displayreference> | 26 |
| 2.19. | <dl> | 27 |
| 2.20. | <dt> | 28 |
| 2.21. | | 29 |
| 2.22. | <email> | 30 |
| 2.23. | <eref> | 30 |
| 2.24. | <figure> | 31 |
| 2.25. | <front> | 33 |
| 2.26. | <ieref> | 34 |
| 2.27. | <keyword> | 35 |

Hoffman

Expires April 22, 2019

[Page 2]

| | | |
|-----------------------|--|--------------------|
| 2.28. | | 35 |
| 2.29. | <link> | 36 |
| 2.30. | <middle> | 37 |
| 2.31. | <name> | 37 |
| 2.32. | <note> | 38 |
| 2.33. | | 39 |
| 2.34. | <organization> | 41 |
| 2.35. | <phone> | 41 |
| 2.36. | <postal> | 42 |
| 2.37. | <postalLine> | 42 |
| 2.38. | <refcontent> | 43 |
| 2.39. | <reference> | 43 |
| 2.40. | <referencegroup> | 44 |
| 2.41. | <references> | 45 |
| 2.42. | <region> | 46 |
| 2.43. | <relref> | 46 |
| 2.44. | <rfc> | 49 |
| 2.45. | <section> | 53 |
| 2.46. | <seriesInfo> | 55 |
| 2.47. | <sourcecode> | 57 |
| 2.48. | <street> | 59 |
| 2.49. | | 59 |
| 2.50. | <sub> | 60 |
| 2.51. | <sup> | 61 |
| 2.52. | <t> | 62 |
| 2.53. | <table> | 64 |
| 2.54. | <tbody> | 65 |
| 2.55. | <td> | 65 |
| 2.56. | <tfoot> | 67 |
| 2.57. | <th> | 67 |
| 2.58. | <thead> | 69 |
| 2.59. | <title> | 69 |
| 2.60. | <tr> | 70 |
| 2.61. | <tt> | 70 |
| 2.62. | | 71 |
| 2.63. | <uri> | 72 |
| 2.64. | <workgroup> | 72 |
| 2.65. | <xref> | 72 |
| 3. | Elements from v2 That Have Been Deprecated | 75 |
| 3.1. | <c> | 75 |
| 3.2. | <facsimile> | 76 |
| 3.3. | <format> | 76 |
| 3.4. | <list> | 76 |
| 3.5. | <postamble> | 77 |
| 3.6. | <preamble> | 78 |
| 3.7. | <spanx> | 78 |
| 3.8. | <texttable> | 79 |
| 3.9. | <ttable> | 80 |

| | | |
|-----------------------------|--|---------------------|
| 3.10. | <vspace> | 81 |
| 4. | SVG | 81 |
| 5. | Use of CDATA Structures and Escaping | 81 |
| 6. | Internationalization Considerations | 82 |
| 7. | Security Considerations | 82 |
| 8. | IANA Considerations | 83 |
| 8.1. | Internet Media Type Registration | 83 |
| 8.2. | Link Relation Registration | 84 |
| 9. | References | 85 |
| 9.1. | Normative References | 85 |
| 9.2. | Informative References | 85 |
| Appendix A. | Front-Page ("Boilerplate") Generation | 89 |
| A.1. | The "ipr" Attribute | 89 |
| A.1.1. | Current Values: "*trust200902" | 89 |
| A.1.2. | Historic Values | 91 |
| A.2. | The "submissionType" Attribute | 92 |
| A.3. | The "consensus" Attribute | 92 |
| Appendix B. | The v3 Format and Processing Tools | 93 |
| B.1. | Including External Text with XInclude | 94 |
| B.2. | Anchors and IDs | 95 |
| B.2.1. | Overlapping Values | 96 |
| B.3. | Attributes Controlled by the Prep Tool | 97 |
| Appendix C. | RELAX NG Schema | 98 |
| Appendix D. | Schema Differences from v2 | 118 |
| Appendix E. | IAB Members at the Time of Approval | 138 |
| Appendix F. | Acknowledgments | 138 |
| | Index | 138 |

1. Introduction

This document describes version 3 ("v3") of the "xml2rfc" vocabulary: an XML-based language ("Extensible Markup Language" [[XML](#)]) used for writing RFCs [[RFC7322](#)] and Internet-Drafts [[IDGUIDE](#)].

This document obsoletes [[RFC7991](#)], [[RFC7991](#)] obsoleted the version 2 vocabulary ("v2") [[RFC7749](#)], which contains the extended language definition. [[RFC7749](#)] obsoleted the original version ("v1") [[RFC2629](#)]. This document directly copies the material from [[RFC7749](#)] where possible.

The v3 format will be used as part of the new RFC Series format described in [[RFC6949](#)]. The new format will be handled by one or more new tools for preparing the XML and converting it to other representations. Features of the expected tools are described in [Appendix B](#). That section defines some terms used throughout this document, such as "prep tool" and "formatter".

Note that the vocabulary contains certain constructs that might not be used when generating the final text; however, they can provide useful data for other uses (such as index generation, populating a keyword database, or syntax checks).

In this document, the term "format" is used when describing types of documents, primarily XML and HTML. The term "representation" is used when talking about a specific instantiation of a format, such as an XML document or an HTML document that was created by an XML document.

1.1. Expected Updates to the Specification

Non-interoperable changes in later versions of this specification are likely based on experience gained in implementing the new publication toolsets. Revised documents will be published capturing those changes as the toolsets are completed. Other implementers must not expect those changes to remain backwards-compatible with the details described in this document.

1.2. Design Criteria for the Changes in v3

The design criteria of the changes from v2 to v3 are as follows:

- o The intention is that starting and editing a v3 document will be easier than for a v2 document.
- o There will be good v2-to-v3 conversion tools for when an author wants to change versions.

- o There are no current plans to make v3 XML the required submission format for drafts or RFCs. That might happen eventually, but it is likely to be years away.

There is a desire to keep as much of the v2 grammar as makes sense within the above design criteria and not to make gratuitous changes to the v2 grammar. Another way to say this is "we would rather encourage backwards compatibility but not be constrained by it." Still, the goal of starting and editing a v3 document being easier than for a v2 document is more important than backwards compatibility with v2, given the latter two design criteria.

v3 is upwards compatible with v2, meaning that a v2 document is meant to be a valid v3 document as well. However, some features of v2 are deprecated in v3 in favor of new elements. Deprecated features are listed in [Section 1.4.3](#) and are described in [\[RFC7749\]](#).

[1.3.](#) Differences from [RFC 7991](#) in This Document

This is a (hopefully) complete list of all the technical changes between [\[RFC7991\]](#) and this document.

- o Changed the text about what this draft obsoletes and updates.
- o Allow `<blockquote>` as a child of ``.
- o Removed "It is an error to have both a "src" attribute and content in the `<artwork>` element." from [Section 2.5.6](#).
- o Removed `
` from the vocabulary.
- o Changed the "hanging" attribute of `<dl>` to "newline".
- o Added the "indent" attribute to `<dl>`.
- o Added the "align" attribute to `<table>`.

[1.4.](#) Differences from v2 to v3

This is a (hopefully) complete list of all the technical changes between [\[RFC7749\]](#) and this document.

[1.4.1.](#) New Elements in v3

- o Add `<dl>`, ``, and `` as new ways to make lists. This is a significant change from v2 in that the child under these elements is ``, not `<t>`. `` has a model of either containing one or more `<t>` elements, or containing the flowing text normally found

in `<t>`. These lists are children of `<section>`s and other lists instead of `<t>`.

- o Add ``, ``, `<tt>`, `<sub>`, and `<sup>` for character formatting.
- o Add `<aside>` for incidental text that will be indented when displayed.
- o Add `<sourcecode>` to differentiate from `<artwork>`.
- o Add `<table>`, `<thead>`, `<tbody>`, `<tfoot>`, `<tr>`, `<td>`, and `<th>` to give table functionality like that in HTML.
- o Add `<boilerplate>` to hold the automatically generated boilerplate text.
- o Add `<blockquote>` to indicate a quotation as in a paragraph-like format.
- o Add `<name>` to sections, notes, figures, and texttables to allow character formatting (fixed-width font) in their titles and to allow references in the names.
- o Add `<postalLine>`, free text that represents one line of the address.
- o Add `<displayreference>` to allow display of more mnemonic anchor names for automatically included references.
- o Add `<refcontent>` to allow better control of text in a reference.
- o Add `<referencegroup>` to allow referencing multi-RFC documents such as STDs and BCPS.
- o Add `<relref>` to allow referencing specific sections or anchors in references.
- o Add `<link>` to point to a resource related to the RFC.
- o Add `
` to allow line breaks (but not blank lines) in the generated output for table cells.
- o Add `<svg>` to allow easy inclusion of SVG drawings in `<artwork>`.

1.4.2. New Attributes for Existing Elements

- o Add "sortRefs", "symRefs", "tocDepth", and "tocInclude" attributes to <rfc> to cover Processing Instructions (PIs) that were in v2 that are still needed in the grammar. Add "prepTime" to indicate the time that the XML went through a preparation step. Add "version" to indicate the version of xml2rfc vocabulary used in the document. Add "scripts" to indicate which scripts are needed to render the document. Add "expiresDate" when an Internet-Draft expires.
- o Add "ascii" attributes to <email>, <organization>, <street>, <city>, <region>, <country>, and <code>. Also add "asciiFullname", "asciiInitials", and "asciiSurname" to <author>. This allows an author to specify their information in their native scripts as the primary entry and still allow the ASCII-equivalent values to appear in the processed documents.
- o Add "anchor" attributes to many block elements to allow them to be linked with <relref> and <xref>.
- o Add the "section", "relative", and "sectionFormat" attributes to <xref>.
- o Add the "numbered" and "removeInRFC" attributes to <section>.
- o Add the "removeInRFC" attribute to <note>.
- o Add "pn" to <artwork>, <aside>, <blockquote>, <boilerplate>, <dt>, <figure>, <iref>, , <references>, <section>, <sourcecode>, <t>, and <table> to hold automatically generated numbers for items in a section that don't have their own numbering (namely figures and tables).
- o Add "display" to <cref> to indicate to tools whether or not to display the comment.
- o Add "keepWithNext" and "keepWithPrevious" to <t> as a hint to tools that do pagination that they should try to keep the paragraph with the next/previous element.

1.4.3. Elements and Attributes Deprecated from v2

Deprecated elements and attributes are legacy vocabulary from v2 that are supported for input to v3 tools. They are likely to be removed from those tools in the future. Deprecated attributes are still listed in [Section 2](#), and deprecated elements are listed in [Section 3](#). See [Appendix B](#) for more information on tools and how they will handle

deprecated features.

- o Deprecate `<list>` in favor of `<dl>`, ``, and ``.
- o Deprecate `<spanx>`; replace it with ``, ``, and `<tt>`.
- o Deprecate `<vspace>` because the major use for it, creating pseudo-paragraph-breaks in lists, is now handled properly.
- o Deprecate `<texttable>`, `<ttable>`, and `<c>`; replace them with the new table elements (`<table>` and the elements that can be contained within it).
- o Deprecate `<facsimile>` because it is rarely used.
- o Deprecate `<format>` because it is not useful and has caused surprise for authors in the past. If the goal is to provide a single URI (Uniform Resource Identifier) for a reference, use the "target" attribute in `<reference>` instead.
- o Deprecate `<preamble>` and `<postamble>` in favor of simply using `<t>` before or after the figure. This also deprecates the "align" attribute in `<figure>`.
- o Deprecate the "title" attribute in `<section>`, `<note>`, `<figure>`, `<references>`, and `<texttable>` in favor of the new `<name>`.
- o Deprecate the "alt" and "src" attributes in `<figure>` because they overlap with the attributes in `<artwork>`.
- o Deprecate the "xml:space" attribute in `<artwork>` because there was only one useful value. Deprecate the "height" and "width" attributes in both `<artwork>` and `<figure>` because they are not needed for the new output formats.
- o Deprecate the "pageno" attribute in `<xref>` because it was unused in v2. Deprecate the "none" values for the "format" attribute in `<xref>` because it makes no sense semantically.

1.4.4. Additional Changes from v2

- o Allow non-ASCII characters in the format; the characters that are actually allowed will be determined by the RFC Series Editor.
- o Allow `<artwork>` and `<sourcecode>` to be used on their own in `<section>` (no longer confine them to a figure).

- o Give more specifics of handling the "type" attribute in <artwork>.
- o Allow , , <tt>, <eref>, and <xref> in <cref>.
- o Allow the sub-elements inside a <reference> to be in any order.
- o Turn off the autogeneration of anchors in <cref> because there is no use case for them that cannot be achieved in other ways.
- o Allow more than one <artwork>, or more than one <sourcecode>, in <figure>.
- o In <front>, make <date> optional.
- o In <date>, add restrictions to the "date" and "year" attributes when used in the <front> for the document's boilerplate text.
- o In <postal>, allow the sub-elements to be in any order. Also allow the inclusion of the new <postalLine> instead of the older elements.
- o In <section>, restrict the names of the anchors that can be used on some types of sections.
- o Make <seriesInfo> a child of <front>, and deprecated it as a child of <reference>. This also deprecates some of the attributes from <rfc> and moves them into <seriesInfo>.
- o <t> now only contains non-block elements, so it no longer contains <figure> elements.
- o Do not generate the grammar from a DTD, but instead get it directly from the RELAX Next Generation (RNG) grammar [[RNG](#)].

[1.5.](#) Syntax Notation

The XML vocabulary here is defined in prose, based on the RELAX NG schema [[RNC](#)] contained in [Appendix C](#) (specified in RELAX NG Compact Notation (RNC)).

Note that the schema can be used for automated validity checks, but certain constraints are only described in prose (example: the conditionally required presence of the "abbrev" attribute).

[2.](#) Elements

The sections below describe all elements and their attributes.

Note that attributes not labeled "mandatory" are optional.

Many elements have an optional "anchor" attribute. In all cases, the value of the "anchor" attribute needs to be a valid XML "Name" (Section 2.3 of [\[XML\]](#)), additionally constrained to US-ASCII characters [\[USASCII\]](#). Thus, the character repertoire consists of "A-Z", "a-z", "0-9", "_", "-", ".", and ":", where "0-9", ".", and "-" are disallowed as start characters. Anchors are described in more detail in [Appendix B.2](#).

Tools interpreting the XML described here will collapse horizontal whitespace and line breaks to a single whitespace (except inside `<artwork>` and `<sourcecode>`) and will trim leading and trailing whitespace. Tab characters (U+0009) inside `<artwork>` and `<sourcecode>` are prohibited.

Some of the elements have attributes that are not described in this section because those attributes are specific to the prep tool. People writing tools to process this format should read all of the appendices for a complete description of these attributes.

Every element in the v3 vocabulary can have an "xml:lang" attribute, an "xml:base" attribute, or both. The xml:lang attribute specifies the language used in the element. This is sometimes useful for renderers that display different fonts for ideographic characters used in China and Japan. The xml:base attribute is sometimes added to an XML file when doing XML-to-XML conversion where the base file has XInclude attributes (see [Appendix B.1](#)).

[2.1.](#) <abstract>

Contains the Abstract of the document. See [\[RFC7322\]](#) for more information on restrictions for the Abstract.

This element appears as a child element of `<front>` ([Section 2.25](#)).

Content model:

In any order, but at least one of:

- o `<dl>` elements ([Section 2.19](#))
- o `` elements ([Section 2.33](#))
- o `<t>` elements ([Section 2.52](#))
- o `` elements ([Section 2.62](#))

2.1.1. "anchor" Attribute

Document-wide unique identifier for the Abstract.

2.2. <address>

Provides address information for the author.

This element appears as a child element of <author> ([Section 2.7](#)).

Content model:

In this order:

1. One optional <postal> element ([Section 2.36](#))
2. One optional <phone> element ([Section 2.35](#))
3. One optional <facsimile> element ([Section 3.2](#))
4. One optional <email> element ([Section 2.22](#))
5. One optional <uri> element ([Section 2.63](#))

2.3. <annotation>

Provides additional prose augmenting a bibliographic reference. This text is intended to be shown after the rest of the generated reference text.

This element appears as a child element of <reference> ([Section 2.39](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.9](#))
- o <cref> elements ([Section 2.15](#))
- o elements ([Section 2.21](#))
- o <eref> elements ([Section 2.23](#))

- o `<iref>` elements ([Section 2.26](#))
- o `<relref>` elements ([Section 2.43](#))
- o `<spanx>` elements ([Section 3.7](#))
- o `` elements ([Section 2.49](#))
- o `<sub>` elements ([Section 2.50](#))
- o `<sup>` elements ([Section 2.51](#))
- o `<tt>` elements ([Section 2.61](#))
- o `<xref>` elements ([Section 2.65](#))

[2.4.](#) `<area>`

Provides information about the IETF area to which this document relates (currently not used when generating documents).

The value ought to be either the full name or the abbreviation of one of the IETF areas as listed on <http://www.ietf.org/iesg/area.html>. A list of full names and abbreviations will be kept by the RFC Series Editor.

This element appears as a child element of `<front>` ([Section 2.25](#)).

Content model: only text content.

[2.5.](#) `<artwork>`

This element allows the inclusion of "artwork" in the document. `<artwork>` provides full control of horizontal whitespace and line breaks; thus, it is used for a variety of things, such as diagrams ("line art") and protocol unit diagrams. Tab characters (U+0009) inside of this element are prohibited.

Alternatively, the "src" attribute allows referencing an external graphics file, such as a vector drawing in SVG or a bitmap graphic file, using a URI. In this case, the textual content acts as a fallback for output representations that do not support graphics; thus, it ought to contain either (1) a "line art" variant of the graphics or (2) prose that describes the included image in sufficient detail.

In [[RFC7749](#)], the `<artwork>` element was also used for source code and formal languages; in v3, this is now done with `<sourcecode>`.

There are at least five ways to include SVG in artwork in Internet-Drafts:

- o Inline, by including all of the SVG in the content of the element, such as: `<artwork type="svg"><svg xmlns="http://www.w3.org/2000/svg...">`
- o Inline, but using XInclude (see [Appendix B.1](#)), such as: `<artwork type="svg"><xi:include href=...>`
- o As a data: URI, such as: `<artwork type="svg" src="data:image/svg+xml,%3Csvg%20xmlns%3D%22http%3A%2F%2Fwww.w3...">`
- o As a URI to an external entity, such as: `<artwork type="svg" src="http://www.example.com/...">`
- o As a local file, such as: `<artwork type="svg" src="diagram12.svg">`

The use of SVG in Internet-Drafts and RFCs is covered in much more detail in [[RFC7996](#)].

The above methods for inclusion of SVG art can also be used for including text artwork, but using a data: URI is probably confusing for text artwork.

Formatters that do pagination should attempt to keep artwork on a single page. This is to prevent artwork that is split across pages from looking like two separate pieces of artwork.

See [Section 5](#) for a description of how to deal with issues of using "&" and "<" characters in artwork.

This element appears as a child element of `<aside>` ([Section 2.6](#)), `<blockquote>` ([Section 2.10](#)), `<dd>` ([Section 2.17](#)), `<figure>` ([Section 2.24](#)), `` ([Section 2.28](#)), `<section>` ([Section 2.45](#)), `<td>` ([Section 2.55](#)), and `<th>` ([Section 2.57](#)).

Content model:

Either:

Text

Or:

`<svg>` elements ([Section 4](#))

[2.5.1.](#) "align" Attribute

Controls whether the artwork appears left justified (default), centered, or right justified. Artwork is aligned relative to the left margin of the document.

Allowed values:

- o "left" (default)
- o "center"
- o "right"

[2.5.2.](#) "alt" Attribute

Alternative text description of the artwork (which is more than just a summary or caption). When the art comes from the "src" attribute and the format of that artwork supports alternate text, the alternative text comes from the text of the artwork itself, not from this attribute. The contents of this attribute are important to readers who are visually impaired, as well as those reading on devices that cannot show the artwork well, or at all.

[2.5.3.](#) "anchor" Attribute

Document-wide unique identifier for this artwork.

[2.5.4.](#) "height" Attribute

Deprecated.

[2.5.5.](#) "name" Attribute

A filename suitable for the contents (such as for extraction to a local file). This attribute can be helpful for other kinds of tools (such as automated syntax checkers, which work by extracting the artwork). Note that the "name" attribute does not need to be unique for <artwork> elements in a document. If multiple <artwork> elements have the same "name" attribute, a processing tool might assume that the elements are all fragments of a single file, and the tool can collect those fragments for later processing. See [Section 7](#) for a discussion of possible problems with the value of this attribute.

[2.5.6.](#) "src" Attribute

The URI reference of a graphics file [[RFC3986](#)], or the name of a file on the local disk. This can be a "data" URI [[RFC2397](#)] that contains

the contents of the graphics file. Note that the inclusion of art with the "src" attribute depends on the capabilities of the processing tool reading the XML document. Tools need to be able to handle the file: URI, and they should be able to handle http: and https: URIs as well. The prep tool will be able to handle reading the "src" attribute.

If no URI scheme is given in the attribute, the attribute is considered to be a local filename relative to the current directory. Processing tools must be careful to not accept dangerous values for the filename, particularly those that contain absolute references outside the current directory. Document creators should think hard before using relative URIs due to possible later problems if files move around on the disk. Also, documents should most likely use explicit URI schemes wherever possible.

In some cases, the prep tool may remove the "src" attribute after processing its value. See [[RFC7998](#)] for a description of this.

2.5.7. "type" Attribute

Specifies the type of the artwork. The value of this attribute is free text with certain values designated as preferred.

The preferred values for <artwork> types are:

- o ascii-art
- o binary-art
- o call-flow
- o hex-dump
- o svg

The RFC Series Editor will maintain a complete list of the preferred values on the RFC Editor web site, and that list is expected to be updated over time. Thus, a consumer of v3 XML should not cause a failure when it encounters an unexpected type or no type is specified. The table will also indicate which type of art can appear in plain-text output (for example, type="svg" cannot).

2.5.8. "width" Attribute

Deprecated.

[2.5.9.](#) "xml:space" Attribute

Deprecated.

[2.6.](#) <aside>

This element is a container for content that is semantically less important or tangential to the content that surrounds it.

This element appears as a child element of <section> ([Section 2.45](#)).

Content model:

In any order:

- o <artwork> elements ([Section 2.5](#))
- o <dl> elements ([Section 2.19](#))
- o <figure> elements ([Section 2.24](#))
- o <iref> elements ([Section 2.26](#))
- o <list> elements ([Section 3.4](#))
- o elements ([Section 2.33](#))
- o <t> elements ([Section 2.52](#))
- o <table> elements ([Section 2.53](#))
- o elements ([Section 2.62](#))

[2.6.1.](#) "anchor" Attribute

Document-wide unique identifier for this aside.

[2.7.](#) <author>

Provides information about a document's author. This is used both for the document itself (at the beginning of the document) and for referenced documents.

The <author> elements contained within the document's <front> element are used to fill the boilerplate and also to generate the "Author's Address" section (see [[RFC7322](#)]).

Note that an "author" can also be just an organization (by not

specifying any of the "name" attributes, but adding the <organization> child element).

Furthermore, the "role" attribute can be used to mark an author as "editor". This is reflected both on the front page and in the "Author's Address" section, as well as in bibliographic references. Note that this specification does not define a precise meaning for the term "editor".

This element appears as a child element of <front> ([Section 2.25](#)).

Content model:

In this order:

1. One optional <organization> element ([Section 2.34](#))
2. One optional <address> element ([Section 2.2](#))

[2.7.1.](#) "asciiFullname" Attribute

The ASCII equivalent of the author's full name.

[2.7.2.](#) "asciiInitials" Attribute

The ASCII equivalent of the author's initials, to be used in conjunction with the separately specified asciiSurname.

[2.7.3.](#) "asciiSurname" Attribute

The ASCII equivalent of the author's surname, to be used in conjunction with the separately specified asciiInitials.

[2.7.4.](#) "fullname" Attribute

The full name (used in the automatically generated "Author's Address" section). Although this attribute is optional, if one or more of the "asciiFullname", "asciiInitials", or "asciiSurname" attributes have values, the "fullname" attribute is required.

[2.7.5.](#) "initials" Attribute

An abbreviated variant of the given name(s), to be used in conjunction with the separately specified surname. It usually appears on the front page, in footers, and in references.

Some processors will post-process the value -- for instance, when it only contains a single letter (in which case they might add a

trailing dot). Relying on this kind of post-processing can lead to results varying across formatters and thus ought to be avoided.

[2.7.6.](#) "role" Attribute

Specifies the role the author had in creating the document.

Allowed values:

- o "editor"

[2.7.7.](#) "surname" Attribute

The author's surname, to be used in conjunction with the separately specified initials. It usually appears on the front page, in footers, and in references.

[2.8.](#) <back>

Contains the "back" part of the document: the references and appendices. In <back>, <section> elements indicate appendices.

This element appears as a child element of <rfc> ([Section 2.44](#)).

Content model:

In this order:

1. Optional <displayreference> elements ([Section 2.18](#))
2. Optional <references> elements ([Section 2.41](#))
3. Optional <section> elements ([Section 2.45](#))

[2.9.](#) <bcp14>

Marks text that are phrases defined in [\[BCP14\]](#) such as "MUST", "SHOULD NOT", and so on. When shown in some of the output representations, the text in this element might be highlighted. The use of this element is optional.

This element is only to be used around the actual phrase from [BCP 14](#), not the full definition of a requirement. For example, it is correct to say "The packet <bcp14>MUST</bcp14> be dropped.", but it is not correct to say "<bcp14>The packet MUST be dropped.</bcp14>".

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.10](#)), <dd> ([Section 2.17](#)), <dt>

([Section 2.20](#)), `` ([Section 2.21](#)), `` ([Section 2.28](#)), `<preamble>` ([Section 3.6](#)), `<refcontent>` ([Section 2.38](#)), `` ([Section 2.49](#)), `<sub>` ([Section 2.50](#)), `<sup>` ([Section 2.51](#)), `<t>` ([Section 2.52](#)), `<td>` ([Section 2.55](#)), `<th>` ([Section 2.57](#)), and `<tt>` ([Section 2.61](#)).

Content model: only text content.

[2.10.](#) `<blockquote>`

Specifies that a block of text is a quotation.

This element appears as a child element of `` ([Section 2.28](#)) and `<section>` ([Section 2.45](#)).

Content model:

Either:

In any order, but at least one of:

- * `<artwork>` elements ([Section 2.5](#))
- * `<dl>` elements ([Section 2.19](#))
- * `<figure>` elements ([Section 2.24](#))
- * `` elements ([Section 2.33](#))
- * `<sourcecode>` elements ([Section 2.47](#))
- * `<t>` elements ([Section 2.52](#))
- * `` elements ([Section 2.62](#))

Or:

In any order, but at least one of:

- * Text
- * `<bcp14>` elements ([Section 2.9](#))
- * `<cref>` elements ([Section 2.15](#))

- * `` elements ([Section 2.21](#))
- * `<eref>` elements ([Section 2.23](#))
- * `<iref>` elements ([Section 2.26](#))
- * `<relref>` elements ([Section 2.43](#))
- * `` elements ([Section 2.49](#))
- * `<sub>` elements ([Section 2.50](#))
- * `<sup>` elements ([Section 2.51](#))
- * `<tt>` elements ([Section 2.61](#))
- * `<xref>` elements ([Section 2.65](#))

[2.10.1.](#) **"anchor" Attribute**

Document-wide unique identifier for this quotation.

[2.10.2.](#) **"cite" Attribute**

The source of the citation. This must be a URI. If the "quotedFrom" attribute is given, this URI will be used by processing tools as the link for the text of that attribute.

[2.10.3.](#) **"quotedFrom" Attribute**

Name of person or document the text in this element is quoted from. A formatter should render this as visible text at the end of the quotation.

[2.11.](#) **`<boilerplate>`**

Holds the boilerplate text for the document. This element is filled in by the prep tool.

This element contains `<section>` elements. Every `<section>` element in this element must have the "numbered" attribute set to "false".

This element appears as a child element of `<front>` ([Section 2.25](#)).

Content model:

One or more `<section>` elements ([Section 2.45](#))

[2.12.](#) `<city>`

Gives the city name in a postal address.

This element appears as a child element of `<postal>` ([Section 2.36](#)).

Content model: only text content.

[2.12.1.](#) "ascii" Attribute

The ASCII equivalent of the city name.

[2.13.](#) `<code>`

Gives the postal region code.

This element appears as a child element of `<postal>` ([Section 2.36](#)).

Content model: only text content.

[2.13.1.](#) "ascii" Attribute

The ASCII equivalent of the postal code.

[2.14.](#) `<country>`

Gives the country name or code in a postal address.

This element appears as a child element of `<postal>` ([Section 2.36](#)).

Content model: only text content.

[2.14.1.](#) "ascii" Attribute

The ASCII equivalent of the country name.

[2.15.](#) `<cref>`

Represents a comment.

Comments can be used in a document while it is work in progress. They might appear either inline and visually highlighted, at the end of the document, or not at all, depending on the formatting tool.

This element appears as a child element of `<annotation>` ([Section 2.3](#)), `<blockquote>` ([Section 2.10](#)), `<c>` ([Section 3.1](#)), `<dd>` ([Section 2.17](#)), `<dt>` ([Section 2.20](#)), `` ([Section 2.21](#)), `` ([Section 2.28](#)), `<name>` ([Section 2.31](#)), `<postamble>` ([Section 3.5](#)),

<preamble> ([Section 3.6](#)), ([Section 2.49](#)), <sub> ([Section 2.50](#)), <sup> ([Section 2.51](#)), <t> ([Section 2.52](#)), <td> ([Section 2.55](#)), <th> ([Section 2.57](#)), <tt> ([Section 2.61](#)), and <ttcol> ([Section 3.9](#)).

Content model:

In any order:

- o Text
- o elements ([Section 2.21](#))
- o <eref> elements ([Section 2.23](#))
- o <relref> elements ([Section 2.43](#))
- o elements ([Section 2.49](#))
- o <sub> elements ([Section 2.50](#))
- o <sup> elements ([Section 2.51](#))
- o <tt> elements ([Section 2.61](#))
- o <xref> elements ([Section 2.65](#))

[2.15.1.](#) "anchor" Attribute

Document-wide unique identifier for this comment.

[2.15.2.](#) "display" Attribute

Suggests whether or not the comment should be displayed by formatting tools. This might be set to "false" if you want to keep a comment in a document after the contents of the comment have already been dealt with.

Allowed values:

- o "true" (default)
- o "false"

[2.15.3.](#) "source" Attribute

Holds the "source" of a comment, such as the name or the initials of the person who made the comment.

[2.16.](#) <date>

Provides information about the publication date. This element is used for two cases: the boilerplate of the document being produced, and inside bibliographic references that use the <front> element.

Boilerplate for Internet-Drafts and RFCs: This element defines the date of publication for the current document (Internet-Draft or RFC). When producing Internet-Drafts, the prep tool uses this date to compute the expiration date (see [[IDGUIDE](#)]). When one or more of "year", "month", or "day" are left out, the prep tool will attempt to use the current system date if the attributes that are present are consistent with that date.

In dates in <rfc> elements, the month must be a number or a month in English. The prep tool will silently change text month names to numbers. Similarly, the year must be a four-digit number.

When the prep tool is used to create Internet-Drafts, it will reject a submitted Internet-Draft that has a <date> element in the boilerplate for itself that is anything other than today. That is, the tool will not allow a submitter to specify a date other than the day of submission. To avoid this problem, authors might simply not include a <date> element in the boilerplate.

Bibliographic references: In dates in <reference> elements, the date information can have prose text for the month or year. For example, vague dates (year="ca. 2000"), date ranges (year="2012-2013"), non-specific months (month="Second quarter"), and so on are allowed.

This element appears as a child element of <front> ([Section 2.25](#)).

Content model: this element does not have any contents.

[2.16.1.](#) "day" Attribute

The day of publication.

[2.16.2.](#) "month" Attribute

The month or months of publication.

[2.16.3.](#) "year" Attribute

The year or years of publication.

[2.17.](#) <dd>

The definition part of an entry in a definition list.

This element appears as a child element of <dl> ([Section 2.19](#)).

Content model:

Either:

In any order, but at least one of:

- * <artwork> elements ([Section 2.5](#))
- * <dl> elements ([Section 2.19](#))
- * <figure> elements ([Section 2.24](#))
- * elements ([Section 2.33](#))
- * <sourcecode> elements ([Section 2.47](#))
- * <t> elements ([Section 2.52](#))
- * elements ([Section 2.62](#))

Or:

In any order, but at least one of:

- * Text
- * <bcp14> elements ([Section 2.9](#))
- * <cref> elements ([Section 2.15](#))
- * elements ([Section 2.21](#))
- * <eref> elements ([Section 2.23](#))

- * `<iref>` elements ([Section 2.26](#))
- * `<relref>` elements ([Section 2.43](#))
- * `` elements ([Section 2.49](#))
- * `<sub>` elements ([Section 2.50](#))
- * `<sup>` elements ([Section 2.51](#))
- * `<tt>` elements ([Section 2.61](#))
- * `<xref>` elements ([Section 2.65](#))

[2.17.1.](#) "anchor" Attribute

Document-wide unique identifier for this definition.

[2.18.](#) `<displayreference>`

This element gives a mapping between the anchor of a reference and a name that will be displayed instead. This allows authors to display more mnemonic anchor names for automatically included references. The mapping in this element only applies to `<xref>` elements whose format is "default". For example, if the reference uses the anchor "[RFC6949](#)", the following would cause that anchor in the body of displayed documents to be "RFC-dev":

```
<displayreference target="RFC6949" to="RFC-dev"/>
```

If a reference section is sorted, this element changes the sort order.

It is expected that this element will only be valid in input documents. It will likely be removed by prep tools when preparing a final version after those tools have replaced all of the associated anchors, targets, and "derivedContent" attributes.

This element appears as a child element of `<back>` ([Section 2.8](#)).

Content model: this element does not have any contents.

[2.18.1.](#) "target" Attribute (Mandatory)

This attribute must be the name of an anchor in a `<reference>` or `<referencegroup>` element.

[2.18.2.](#) "to" Attribute (Mandatory)

This attribute is a name that will be displayed as the anchor instead of the anchor that is given in the <reference> element. The string given must start with one of the following characters: 0-9, a-z, or A-Z. The other characters in the string must be 0-9, a-z, A-Z, "-", ".", or "_".

[2.19.](#) <dl>

A definition list. Each entry has a pair of elements: a term (<dt>) and a definition (<dd>). (This is slightly different and simpler than the model used in HTML, which allows for multiple terms for a single definition.)

This element appears as a child element of <abstract> ([Section 2.1](#)), <aside> ([Section 2.6](#)), <blockquote> ([Section 2.10](#)), <dd> ([Section 2.17](#)), ([Section 2.28](#)), <note> ([Section 2.32](#)), <section> ([Section 2.45](#)), <td> ([Section 2.55](#)), and <th> ([Section 2.57](#)).

Content model:

One or more sequences of:

1. One <dt> element
2. One <dd> element

[2.19.1.](#) "anchor" Attribute

Document-wide unique identifier for the list.

[2.19.2.](#) "indent" Attribute

Indicates the indentation to be used for the rendering of the second and following lines of the item (the first line starts with the term, and is not indented). The indentation amount is interpreted as characters when rendering plain-text documents, and en-space units when rendering in formats that have richer typographic support such as HTML or PDF. One en-space is assumed to be the length of 0.5 em-space in CSS units.

[2.19.3.](#) "newline" Attribute

The "newline" attribute defines whether or not the term appears on the same line as the definition. newline="true" indicates that the term is to the left of the definition, while newline="false" indicates that the term will be on a separate line.

Allowed values:

- o "false"
- o "true" (default)

2.19.4. "spacing" Attribute

Defines whether or not there is a blank line between entries. spacing="normal" indicates a single blank line, while spacing="compact" indicates no space between.

Allowed values:

- o "normal" (default)
- o "compact"

2.20. <dt>

The term being defined in a definition list.

This element appears as a child element of <dl> ([Section 2.19](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.9](#))
- o <cref> elements ([Section 2.15](#))
- o elements ([Section 2.21](#))
- o <eref> elements ([Section 2.23](#))
- o <iref> elements ([Section 2.26](#))
- o <relref> elements ([Section 2.43](#))
- o elements ([Section 2.49](#))
- o <sub> elements ([Section 2.50](#))
- o <sup> elements ([Section 2.51](#))

- o `<tt>` elements ([Section 2.61](#))
- o `<xref>` elements ([Section 2.65](#))

[2.20.1.](#) "anchor" Attribute

Document-wide unique identifier for this term.

[2.21.](#) ``

Indicates text that is semantically emphasized. Text enclosed within this element will be displayed as italic after processing. This element can be combined with other character formatting elements, and the formatting will be additive.

This element appears as a child element of `<annotation>` ([Section 2.3](#)), `<blockquote>` ([Section 2.10](#)), `<cref>` ([Section 2.15](#)), `<dd>` ([Section 2.17](#)), `<dt>` ([Section 2.20](#)), `` ([Section 2.28](#)), `<preamble>` ([Section 3.6](#)), `<refcontent>` ([Section 2.38](#)), `` ([Section 2.49](#)), `<sub>` ([Section 2.50](#)), `<sup>` ([Section 2.51](#)), `<t>` ([Section 2.52](#)), `<td>` ([Section 2.55](#)), `<th>` ([Section 2.57](#)), and `<tt>` ([Section 2.61](#)).

Content model:

In any order:

- o Text
- o `<bcp14>` elements ([Section 2.9](#))
- o `<cref>` elements ([Section 2.15](#))
- o `<eref>` elements ([Section 2.23](#))
- o `<iref>` elements ([Section 2.26](#))
- o `<relref>` elements ([Section 2.43](#))
- o `` elements ([Section 2.49](#))
- o `<sub>` elements ([Section 2.50](#))
- o `<sup>` elements ([Section 2.51](#))
- o `<tt>` elements ([Section 2.61](#))

- o `<xref>` elements ([Section 2.65](#))

2.22. `<email>`

Provides an email address.

The value is expected to be the `addr-spec` defined in [Section 2 of \[RFC6068\]](#).

This element appears as a child element of `<address>` ([Section 2.2](#)).

Content model: only text content.

2.22.1. "ascii" Attribute

The ASCII equivalent of the author's email address. This is only used if the email address has any internationalized components.

2.23. `<eref>`

Represents an "external" link (as specified in the "target" attribute). This is useful for embedding URIs in the body of a document.

If the `<eref>` element has non-empty text content, formatters should use the content as the displayed text that is linked. Otherwise, the formatter should use the value of the "target" attribute as the displayed text. Formatters will link the displayed text to the value of the "target" attribute in a manner appropriate for the output format.

For example, with an input of:

```
This is described at
<eref target="http://www.example.com/reports/r12.html"/>.
```

An HTML formatter might generate:

```
This is described at
<a href="http://www.example.com/reports/r12.html">
http://www.example.com/reports/r12.html</a>.
```

With an input of:

```
This is described
<eref target="http://www.example.com/reports/r12.html">
in this interesting report</eref>.
```


An HTML formatter might generate:

```
This is described
<a href="http://www.example.com/reports/r12.html">
in this interesting report</a>.
```

This element appears as a child element of `<annotation>` ([Section 2.3](#)), `<blockquote>` ([Section 2.10](#)), `<c>` ([Section 3.1](#)), `<cref>` ([Section 2.15](#)), `<dd>` ([Section 2.17](#)), `<dt>` ([Section 2.20](#)), `` ([Section 2.21](#)), `` ([Section 2.28](#)), `<name>` ([Section 2.31](#)), `<postamble>` ([Section 3.5](#)), `<preamble>` ([Section 3.6](#)), `` ([Section 2.49](#)), `<sub>` ([Section 2.50](#)), `<sup>` ([Section 2.51](#)), `<t>` ([Section 2.52](#)), `<td>` ([Section 2.55](#)), `<th>` ([Section 2.57](#)), `<tt>` ([Section 2.61](#)), and `<ttcol>` ([Section 3.9](#)).

Content model: only text content.

2.23.1. "target" Attribute (Mandatory)

URI of the link target [[RFC3986](#)]. This must begin with a scheme name (such as "https://") and thus not be relative to the URL of the current document.

2.24. <figure>

Contains a figure with a caption with the figure number. If the element contains a `<name>` element, the caption will also show that name.

This element appears as a child element of `<aside>` ([Section 2.6](#)), `<blockquote>` ([Section 2.10](#)), `<dd>` ([Section 2.17](#)), `` ([Section 2.28](#)), `<section>` ([Section 2.45](#)), `<td>` ([Section 2.55](#)), and `<th>` ([Section 2.57](#)).

Content model:

In this order:

1. One optional `<name>` element ([Section 2.31](#))
2. Optional `<iref>` elements ([Section 2.26](#))
3. One optional `<preamble>` element ([Section 3.6](#))
4. In any order, but at least one of:

- * <artwork> elements ([Section 2.5](#))
- * <sourcecode> elements ([Section 2.47](#))

5. One optional <postamble> element ([Section 3.5](#))

[2.24.1.](#) "align" Attribute

Deprecated.

Note: does not affect title or <artwork> alignment.

Allowed values:

- o "left" (default)
- o "center"
- o "right"

[2.24.2.](#) "alt" Attribute

Deprecated. If the goal is to provide a single URI for a reference, use the "target" attribute in <reference> instead.

[2.24.3.](#) "anchor" Attribute

Document-wide unique identifier for this figure.

[2.24.4.](#) "height" Attribute

Deprecated.

[2.24.5.](#) "src" Attribute

Deprecated.

[2.24.6.](#) "suppress-title" Attribute

Deprecated.

Allowed values:

- o "true"
- o "false" (default)

[2.24.7.](#) "title" Attribute

Deprecated. Use <name> instead.

[2.24.8.](#) "width" Attribute

Deprecated.

[2.25.](#) <front>

Represents the "front matter": metadata (such as author information), the Abstract, and additional notes.

A <front> element may have more than one <seriesInfo> element. A <seriesInfo> element determines the document number (for RFCs) or name (for Internet-Drafts). Another <seriesInfo> element determines the "maturity level" (defined in [\[RFC2026\]](#)), using values of "std" for "Standards Track", "bcp" for "BCP", "info" for "Informational", "exp" for "Experimental", and "historic" for "Historic". The "name" attributes of those multiple <seriesInfo> elements interact as described in [Section 2.46](#).

This element appears as a child element of <reference> ([Section 2.39](#)) and <rfc> ([Section 2.44](#)).

Content model:

In this order:

1. One <title> element ([Section 2.59](#))
2. Optional <seriesInfo> elements ([Section 2.46](#))
3. One or more <author> elements ([Section 2.7](#))
4. One optional <date> element ([Section 2.16](#))
5. Optional <area> elements ([Section 2.4](#))
6. Optional <workgroup> elements ([Section 2.64](#))
7. Optional <keyword> elements ([Section 2.27](#))
8. One optional <abstract> element ([Section 2.1](#))
9. Optional <note> elements ([Section 2.32](#))

10. One optional <boilerplate> element ([Section 2.11](#))

2.26. <ieref>

Provides terms for the document's index.

Index entries can be either regular entries (when just the "item" attribute is given) or nested entries (by specifying "subitem" as well), grouped under a regular entry.

Index entries generally refer to the exact place where the <ieref> element occurred. An exception is the occurrence as a child element of <section>, in which case the whole section is considered to be relevant for that index entry. In some formats, index entries of this type might be displayed as ranges.

When the prep tool is creating index content, it collects the items in a case-sensitive fashion for both the item and subitem level.

This element appears as a child element of <annotation> ([Section 2.3](#)), <aside> ([Section 2.6](#)), <blockquote> ([Section 2.10](#)), <c> ([Section 3.1](#)), <dd> ([Section 2.17](#)), <dt> ([Section 2.20](#)), ([Section 2.21](#)), <figure> ([Section 2.24](#)), ([Section 2.28](#)), <postamble> ([Section 3.5](#)), <preamble> ([Section 3.6](#)), <section> ([Section 2.45](#)), ([Section 2.49](#)), <sub> ([Section 2.50](#)), <sup> ([Section 2.51](#)), <t> ([Section 2.52](#)), <table> ([Section 2.53](#)), <td> ([Section 2.55](#)), <th> ([Section 2.57](#)), <tt> ([Section 2.61](#)), and <ttcol> ([Section 3.9](#)).

Content model: this element does not have any contents.

2.26.1. "item" Attribute (Mandatory)

The item to include.

2.26.2. "primary" Attribute

Setting this to "true" declares the occurrence as "primary", which might cause it to be highlighted in the index. There is no restriction on the number of occurrences that can be "primary".

Allowed values:

- o "true"
- o "false" (default)

[2.26.3.](#) "subitem" Attribute

The subitem to include.

[2.27.](#) <keyword>

Specifies a keyword applicable to the document.

Note that each element should only contain a single keyword; for multiple keywords, the element can simply be repeated.

Keywords are used both in the RFC Index and in the metadata of generated document representations.

This element appears as a child element of <front> ([Section 2.25](#)).

Content model: only text content.

**[2.28.](#) **

A list element, used in and .

This element appears as a child element of ([Section 2.33](#)) and ([Section 2.62](#)).

Content model:

Either:

In any order, but at least one of:

- * <artwork> elements ([Section 2.5](#))
- * <blockquote> elements ([Section 2.10](#))
- * <dl> elements ([Section 2.19](#))
- * <figure> elements ([Section 2.24](#))
- * elements ([Section 2.33](#))
- * <sourcecode> elements ([Section 2.47](#))
- * <t> elements ([Section 2.52](#))
- * elements ([Section 2.62](#))

Or:

In any order, but at least one of:

- * Text
- * `<bcp14>` elements ([Section 2.9](#))
- * `<cref>` elements ([Section 2.15](#))
- * `` elements ([Section 2.21](#))
- * `<eref>` elements ([Section 2.23](#))
- * `<iref>` elements ([Section 2.26](#))
- * `<relref>` elements ([Section 2.43](#))
- * `` elements ([Section 2.49](#))
- * `<sub>` elements ([Section 2.50](#))
- * `<sup>` elements ([Section 2.51](#))
- * `<tt>` elements ([Section 2.61](#))
- * `<xref>` elements ([Section 2.65](#))

[2.28.1](#). "anchor" Attribute

Document-wide unique identifier for this list item.

[2.29](#). `<link>`

A link to an external document that is related to the RFC.

The following are the supported types of external documents that can be pointed to in a `<link>` element:

- o The current International Standard Serial Number (ISSN) for the RFC Series. The value for the "rel" attribute is "item". The link should use the form "urn:issn:".
- o The Digital Object Identifier (DOI) for this document. The value for the "rel" attribute is "describedBy". The link should use the form specified in [[RFC7669](#)]; this is expected to change in the

future.

- o The Internet-Draft that was submitted to the RFC Editor to become the published RFC. The value for the "rel" attribute is "convertedFrom". The link should be to an IETF-controlled web site that retains copies of Internet-Drafts.
- o A representation of the document offered by the document author. The value for the "rel" attribute is "alternate". The link can be to a personally run web site.

In RFC production mode, the prep tool needs to check the values for <link> before an RFC is published. In draft production mode, the prep tool might remove some <link> elements during the draft submission process.

This element appears as a child element of <rfc> ([Section 2.44](#)).

Content model: this element does not have any contents.

[2.29.1.](#) "href" Attribute (Mandatory)

The URI of the external document.

[2.29.2.](#) "rel" Attribute

The relationship of the external document to this one. The relationships are taken from the "Link Relations" registry maintained by IANA [[LINKRELATIONS](#)].

[2.30.](#) <middle>

Represents the main content of the document.

This element appears as a child element of <rfc> ([Section 2.44](#)).

Content model:

One or more <section> elements ([Section 2.45](#))

[2.31.](#) <name>

The name of the section, note, figure, or texttable. This name can indicate markup of flowing text (for example, including references or making some characters use a fixed-width font).

This element appears as a child element of <figure> ([Section 2.24](#)), <note> ([Section 2.32](#)), <references> ([Section 2.41](#)), <section>

([Section 2.45](#)), <table> ([Section 2.53](#)), and <texttable> ([Section 3.8](#)).

Content model:

In any order:

- o Text
- o <cref> elements ([Section 2.15](#))
- o <eref> elements ([Section 2.23](#))
- o <relref> elements ([Section 2.43](#))
- o <tt> elements ([Section 2.61](#))
- o <xref> elements ([Section 2.65](#))

[2.32.](#) <note>

Creates an unnumbered, titled block of text that appears after the Abstract.

It is usually used for additional information to reviewers (Working Group information, mailing list, ...) or for additional publication information such as "IESG Notes".

This element appears as a child element of <front> ([Section 2.25](#)).

Content model:

In this order:

1. One optional <name> element ([Section 2.31](#))
2. In any order, but at least one of:
 - * <dl> elements ([Section 2.19](#))
 - * elements ([Section 2.33](#))
 - * <t> elements ([Section 2.52](#))
 - * elements ([Section 2.62](#))

[2.32.1.](#) "removeInRFC" Attribute

If set to "true", this note is marked in the prep tool with text indicating that it should be removed before the document is published as an RFC. That text will be "This note is to be removed before publishing as an RFC."

Allowed values:

- o "true"
- o "false" (default)

[2.32.2.](#) "title" Attribute

Deprecated. Use <name> instead.

[2.33.](#)

An ordered list. The labels on the items will be either a number or a letter, depending on the value of the style attribute.

This element appears as a child element of <abstract> ([Section 2.1](#)), <aside> ([Section 2.6](#)), <blockquote> ([Section 2.10](#)), <dd> ([Section 2.17](#)), ([Section 2.28](#)), <note> ([Section 2.32](#)), <section> ([Section 2.45](#)), <td> ([Section 2.55](#)), and <th> ([Section 2.57](#)).

Content model:

One or more elements ([Section 2.28](#))

[2.33.1.](#) "anchor" Attribute

Document-wide unique identifier for the list.

[2.33.2.](#) "group" Attribute

When the prep tool sees an element with a "group" attribute that has already been seen, it continues the numbering of the list from where the previous list with the same group name left off. If an element has both a "group" attribute and a "start" attribute, the group's numbering is reset to the given start value.

[2.33.3.](#) "spacing" Attribute

Defines whether or not there is a blank line between entries. spacing="normal" indicates a single blank line, while spacing="compact" indicates no space between.

Allowed values:

- o "normal" (default)
- o "compact"

2.33.4. "start" Attribute

The ordinal value at which to start the list. This defaults to "1" and must be an integer of 0 or greater.

2.33.5. "type" Attribute

The type of the labels on list items. If the length of the type value is 1, the meaning is the same as it is for HTML:

- a Lowercase letters (a, b, c, ...)
- A Uppercase letters (A, B, C, ...)
- 1 Decimal numbers (1, 2, 3, ...)
- i Lowercase Roman numerals (i, ii, iii, ...)
- I Uppercase Roman numerals (I, II, III, ...)

For types "a" and "A", after the 26th entry, the numbering starts at "aa"/"AA", then "ab"/"AB", and so on.

If the length of the type value is greater than 1, the value must contain a percent-encoded indicator and other text. The value is a free-form text that allows counter values to be inserted using a "percent-letter" format. For instance, "[REQ%d]" generates labels of the form "[REQ1]", where "%d" inserts the item number as a decimal number.

The following formats are supported:

- %c Lowercase letters (a, b, c, ...)
- %C Uppercase letters (A, B, C, ...)
- %d Decimal numbers (1, 2, 3, ...)
- %i Lowercase Roman numerals (i, ii, iii, ...)

%I Uppercase Roman numerals (I, II, III, ...)

%% Represents a percent sign

Other formats are reserved for future use. Only one percent encoding other than "%" is allowed in a type string.

It is an error for the type string to be empty. For bulleted lists, use the element. For lists that have neither bullets nor numbers, use the element with the 'empty="true"' attribute.

If no type attribute is given, the default type is the same as "type='%d.'".

2.34. <organization>

Specifies the affiliation [[RFC7322](#)] of an author.

This information appears both in the "Author's Address" section and on the front page (see [[RFC7322](#)] for more information). If the value is long, an abbreviated variant can be specified in the "abbrev" attribute.

This element appears as a child element of <author> ([Section 2.7](#)).

Content model: only text content.

2.34.1. "abbrev" Attribute

Abbreviated variant.

2.34.2. "ascii" Attribute

The ASCII equivalent of the organization's name.

2.35. <phone>

Represents a phone number.

The value is expected to be the scheme-specific part of a "tel" URI (and so does not include the prefix "tel:"), using the "global-number-digits" syntax. See [Section 3 of \[RFC3966\]](#) for details.

This element appears as a child element of <address> ([Section 2.2](#)).

Content model: only text content.

[2.36.](#) <postal>

Contains optional child elements providing postal information. These elements will be displayed in an order that is specific to formatters. A postal address can contain only a set of <street>, <city>, <region>, <code>, and <country> elements, or only an ordered set of <postalLine> elements, but not both.

This element appears as a child element of <address> ([Section 2.2](#)).

Content model:

Either:

In any order:

- * <city> elements ([Section 2.12](#))
- * <code> elements ([Section 2.13](#))
- * <country> elements ([Section 2.14](#))
- * <region> elements ([Section 2.42](#))
- * <street> elements ([Section 2.48](#))

Or:

One or more <postalLine> elements ([Section 2.37](#))

[2.37.](#) <postalLine>

Represents one line of a postal address. When more than one <postalLine> is given, the prep tool emits them in the order given.

This element appears as a child element of <postal> ([Section 2.36](#)).

Content model: only text content.

[2.37.1.](#) "ascii" Attribute

The ASCII equivalent of the text in the address line.

[2.38.](#) <refcontent>

Text that should appear between the title and the date of a reference. The purpose of this element is to prevent the need to abuse <seriesInfo> to get such text in a reference.

For example:

```
<reference anchor="April1">
  <front>
    <title>On Being A Fool</title>
    <author initials="K." surname="Phunny" fullname="Knot Phunny"/>
    <date year="2000" month="April"/>
  </front>
  <refcontent>Self-published pamphlet</refcontent>
</reference>
```

would render as:

```
[April1]    Phunny, K., "On Being A Fool", Self-published
            pamphlet, April 2000.
```

This element appears as a child element of <reference> ([Section 2.39](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.9](#))
- o elements ([Section 2.21](#))
- o elements ([Section 2.49](#))
- o <sub> elements ([Section 2.50](#))
- o <sup> elements ([Section 2.51](#))
- o <tt> elements ([Section 2.61](#))

[2.39.](#) <reference>

Represents a bibliographic reference.

This element appears as a child element of <referencegroup>

([Section 2.40](#)) and <references> ([Section 2.41](#)).

Content model:

In this order:

1. One <front> element ([Section 2.25](#))
2. In any order:
 - * <annotation> elements ([Section 2.3](#))
 - * <format> elements ([Section 3.3](#))
 - * <refcontent> elements ([Section 2.38](#))
 - * <seriesInfo> elements ([Section 2.46](#); deprecated in this context)

[2.39.1.](#) "anchor" Attribute (Mandatory)

Document-wide unique identifier for this reference. Usually, this will be used both to "label" the reference in the "References" section and as an identifier in links to this reference entry.

[2.39.2.](#) "quoteTitle" Attribute

Specifies whether or not the title in the reference should be quoted. This can be used to prevent quoting, such as on errata.

Allowed values:

- o "true" (default)
- o "false"

[2.39.3.](#) "target" Attribute

Holds the URI for the reference.

[2.40.](#) <referencegroup>

Represents a list of bibliographic references that will be represented as a single reference. This is most often used to reference STDs and BCPs, where a single reference (such as "[BCP 9](#)") may encompass more than one RFC.

This element appears as a child element of <references> ([Section 2.41](#)).

Content model:

One or more <reference> elements ([Section 2.39](#))

[2.40.1.](#) "anchor" Attribute (Mandatory)

Document-wide unique identifier for this reference group. Usually, this will be used both to "label" the reference group in the "References" section and as an identifier in links to this reference entry.

[2.41.](#) <references>

Contains a set of bibliographic references.

In the early days of the RFC Series, there was only one "References" section per RFC. This convention was later changed to group references into two sets, "Normative" and "Informative", as described in [[RFC7322](#)]. This vocabulary supports the split with the <name> child element. In general, the title should be either "Normative References" or "Informative References".

This element appears as a child element of <back> ([Section 2.8](#)).

Content model:

In this order:

1. One optional <name> element ([Section 2.31](#))
2. In any order:
 - * <reference> elements ([Section 2.39](#))
 - * <referencegroup> elements ([Section 2.40](#))

[2.41.1.](#) "anchor" Attribute

An optional user-supplied identifier for this set of references.

[2.41.2.](#) "title" Attribute

Deprecated. Use <name> instead.

[2.42.](#) <region>

Provides the region name in a postal address.

This element appears as a child element of <postal> ([Section 2.36](#)).

Content model: only text content.

[2.42.1.](#) "ascii" Attribute

The ASCII equivalent of the region name.

[2.43.](#) <relref>

Represents a link to a specific part of a document that appears in a <reference> element. Formatters that have links (such as HTML and PDF) render <relref> elements as external hyperlinks to the specified part of the reference, creating the link target by combining the base URI from the <reference> element with the "relative" attribute from this element. The "target" attribute is required, and it must be the anchor of a <reference> element.

The "section" attribute is required, and the "relative" attribute is optional. If the reference is not an RFC or Internet-Draft that is in the v3 format, the element needs to have a "relative" attribute; in this case, the value of the "section" attribute is ignored.

An example of the <relref> element with text content might be:

```
See
  <relref section="2.3" target="RFC9999" displayFormat="bare">
    the protocol overview</relref>
  for more information.
```

An HTML formatter might generate:

```
See
  <a href="http://www.rfc-editor.org/rfc/rfc9999.html#s-2.3">
    the protocol overview</a>
  for more information.
```

Note that the URL in the above example might be different when the RFC Editor deploys the v3 format.

This element appears as a child element of `<annotation>` ([Section 2.3](#)), `<blockquote>` ([Section 2.10](#)), `<cref>` ([Section 2.15](#)), `<dd>` ([Section 2.17](#)), `<dt>` ([Section 2.20](#)), `` ([Section 2.21](#)), `` ([Section 2.28](#)), `<name>` ([Section 2.31](#)), `<preamble>` ([Section 3.6](#)), `` ([Section 2.49](#)), `<sub>` ([Section 2.50](#)), `<sup>` ([Section 2.51](#)), `<t>` ([Section 2.52](#)), `<td>` ([Section 2.55](#)), `<th>` ([Section 2.57](#)), and `<tt>` ([Section 2.61](#)).

Content model: only text content.

[2.43.1](#). "displayFormat" Attribute

This attribute is used to signal formatters what the desired format of the relative reference should be. Formatters for document types that have linking capability should wrap each part of the displayed text in hyperlinks. If there is content in the `<relref>` element, formatters will ignore the value of this attribute.

"of"

A formatter should display the relative reference as the word "Section" followed by a space, the contents of the "section" attribute followed by a space, the word "of", another space, and the value from the "target" attribute enclosed in square brackets.

For example, with an input of:

```
See
<relref section="2.3" target="RFC9999" displayFormat="of"/>
for an overview.
```

An HTML formatter might generate:

```
See
<a href="http://www.rfc-editor.org/info/rfc9999#s-2.3">
  Section 2.3</a> of
  [
```

Note that `displayFormat='of'` is the default for `<relref>`, so it does not need to be given in a `<relref>` element if that format is desired.

"comma"

A formatter should display the relative reference as the value from the "target" attribute enclosed in square brackets, a comma, a space, the word "Section" followed by a space, and the "section"

attribute.

For example, with an input of:

```
See
<relref section="2.3" target="RFC9999" displayFormat="comma"/>,
for an overview.
```

An HTML formatter might generate:

```
See
[<a href="#RFC9999">RFC9999</a>],
<a href="http://www.rfc-editor.org/info/rfc9999#s-2.3">
  Section 2.3</a>, for an overview.
```

"parens"

A formatter should display the relative reference as the value from the "target" attribute enclosed in square brackets, a space, a left parenthesis, the word "Section" followed by a space, the "section" attribute, and a right parenthesis.

For example, with an input of:

```
See
<relref section="2.3" target="RFC9999" displayFormat="parens"/>
for an overview.
```

An HTML formatter might generate:

```
See
[<a href="#RFC9999">RFC9999</a>]
(<a href="http://www.rfc-editor.org/info/rfc9999#s-2.3">
  Section 2.3</a>)
for an overview.
```

"bare"

A formatter should display the relative reference as the contents of the "section" attribute and nothing else. This is useful when there are multiple relative references to a single base reference.

For example:

```
See Sections
<relref section="2.3" target="RFC9999" displayFormat="bare"/>
and
<relref section="2.4" target="RFC9999" displayFormat="of"/>
```


for an overview.

An HTML formatter might generate:

See Sections

[2.3](http://www.rfc-editor.org/info/rfc9999#s-2.3)

and

[Section 2.4](http://www.rfc-editor.org/info/rfc9999#s-2.4) of

[[RFC9999](#)]

for an overview.

Allowed values:

- o "of" (default)
- o "comma"
- o "parens"
- o "bare"

2.43.2. "relative" Attribute

Specifies a relative reference from the URI in the target reference. This value must include whatever leading character is needed to create the relative reference; typically, this is "#" for HTML documents.

2.43.3. "section" Attribute (Mandatory)

Specifies a section of the target reference. If the reference is not an RFC or Internet-Draft in the v3 format, it is an error.

2.43.4. "target" Attribute (Mandatory)

The anchor of the reference for this element. If this value is not an anchor to a <reference> or <referencegroup> element, it is an error. If the reference at the target has no URI, it is an error.

2.44. <rfc>

This is the root element of the xml2rfc vocabulary.

Content model:

In this order:

1. Optional <link> elements ([Section 2.29](#))
2. One <front> element ([Section 2.25](#))
3. One <middle> element ([Section 2.30](#))
4. One optional <back> element ([Section 2.8](#))

[2.44.1.](#) "category" Attribute

Deprecated; instead, use the "name" attribute in <seriesInfo>.

[2.44.2.](#) "consensus" Attribute

Affects the generated boilerplate. Note that the values of "no" and "yes" are deprecated and are replaced by "false" (the default) and "true".

See [[RFC7841](#)] for more information.

Allowed values:

- o "no"
- o "yes"
- o "false" (default)
- o "true"

[2.44.3.](#) "docName" Attribute

Deprecated; instead, use the "value" attribute in <seriesInfo>.

[2.44.4.](#) "indexInclude" Attribute

Specifies whether or not a formatter is requested to include an index in generated files. If the source file has no <iref> elements, an index is never generated. This option is useful for generating documents where the source document has <iref> elements but the author no longer wants an index.

Allowed values:

- o "true" (default)
- o "false"

[2.44.5.](#) "ipr" Attribute

Represents the Intellectual Property status of the document. See [Appendix A.1](#) for details.

[2.44.6.](#) "iprExtract" Attribute

Identifies a single section within the document for which extraction "as is" is explicitly allowed (only relevant for historic values of the "ipr" attribute).

[2.44.7.](#) "number" Attribute

Deprecated; instead, use the "value" attribute in <seriesInfo>.

[2.44.8.](#) "obsoletes" Attribute

A comma-separated list of RFC numbers or Internet-Draft names.

The prep tool will parse the attribute value so that incorrect references can be detected.

[2.44.9.](#) "prepTime" Attribute

The date that the XML was processed by a prep tool. This is included in the XML file just before it is saved to disk. The value is formatted using the "date-time" format defined in [Section 5.6 of \[RFC3339\]](#). The "time-offset" should be "Z".

[2.44.10.](#) "seriesNo" Attribute

Deprecated; instead, use the "value" attribute in <seriesInfo>.

[2.44.11.](#) "sortRefs" Attribute

Specifies whether or not the prep tool will sort the references in each reference section.

Allowed values:

- o "true"
- o "false" (default)

2.44.12. "submissionType" Attribute

The document stream, as described in [[RFC7841](#)]. (The RFC Series Editor may change the list of allowed values in the future.)

Allowed values:

- o "IETF" (default)
- o "IAB"
- o "IRTF"
- o "independent"

2.44.13. "symRefs" Attribute

Specifies whether or not a formatter is requested to use symbolic references (such as "[\[RFC2119\]](#)"). If the value for this is "false", the references come out as numbers (such as "[3]").

Allowed values:

- o "true" (default)
- o "false"

2.44.14. "tocDepth" Attribute

Specifies the number of levels of headings that a formatter is requested to include in the table of contents; the default is "3".

2.44.15. "tocInclude" Attribute

Specifies whether or not a formatter is requested to include a table of contents in generated files.

Allowed values:

- o "true" (default)
- o "false"

2.44.16. "updates" Attribute

A comma-separated list of RFC numbers or Internet-Draft names.

The prep tool will parse the attribute value so that incorrect

references can be detected.

2.44.17. "version" Attribute

Specifies the version of xml2rfc syntax used in this document. The only expected value (for now) is "3".

2.45. <section>

Represents a section (when inside a <middle> element) or an appendix (when inside a <back> element).

Subsections are created by nesting <section> elements inside <section> elements. Sections are allowed to be empty.

This element appears as a child element of <back> ([Section 2.8](#)), <boilerplate> ([Section 2.11](#)), <middle> ([Section 2.30](#)), and <section> ([Section 2.45](#)).

Content model:

In this order:

1. One optional <name> element ([Section 2.31](#))
2. In any order:
 - * <artwork> elements ([Section 2.5](#))
 - * <aside> elements ([Section 2.6](#))
 - * <blockquote> elements ([Section 2.10](#))
 - * <dl> elements ([Section 2.19](#))
 - * <figure> elements ([Section 2.24](#))
 - * <iref> elements ([Section 2.26](#))
 - * elements ([Section 2.33](#))
 - * <sourcecode> elements ([Section 2.47](#))
 - * <t> elements ([Section 2.52](#))
 - * <table> elements ([Section 2.53](#))

- * `<texttable>` elements ([Section 3.8](#))
- * `` elements ([Section 2.62](#))

3. Optional `<section>` elements ([Section 2.45](#))

[2.45.1.](#) "anchor" Attribute

Document-wide unique identifier for this section.

[2.45.2.](#) "numbered" Attribute

If set to "false", the formatter is requested to not display a section number. The prep tool will verify that such a section is not followed by a numbered section in this part of the document and will verify that the section is a top-level section.

Allowed values:

- o "true" (default)
- o "false"

[2.45.3.](#) "removeInRFC" Attribute

If set to "true", this note is marked in the prep tool with text indicating that it should be removed before the document is published as an RFC. That text will be "This note is to be removed before publishing as an RFC."

Allowed values:

- o "true"
- o "false" (default)

[2.45.4.](#) "title" Attribute

Deprecated. Use `<name>` instead.

[2.45.5.](#) "toc" Attribute

Indicates to a formatter whether or not the section is to be included in a table of contents, if such a table of contents is produced. This only takes effect if the level of the section would have appeared in the table of contents based on the "tocDepth" attribute of the `<rfc>` element, and of course only if the table of contents is

being created based on the "tocInclude" attribute of the <rfc> element. If this is set to "exclude", any section below this one will be excluded as well. The "default" value indicates inclusion of the section if it would be included by the tocDepth attribute of the <rfc> element.

Allowed values:

- o "include"
- o "exclude"
- o "default" (default)

[2.46.](#) <seriesInfo>

Specifies the document series in which this document appears, and also specifies an identifier within that series.

A processing tool determines whether it is working on an RFC or an Internet-Draft by inspecting the "name" attribute of a <seriesInfo> element inside the <front> element inside the <rfc> element, looking for "RFC" or "Internet-Draft". (Specifying neither value in any of the <seriesInfo> elements can be useful for producing other types of documents but is out of scope for this specification.)

It is invalid to have multiple <seriesInfo> elements inside the same <front> element containing the same "name" value. Some combinations of <seriesInfo> "name" attribute values make no sense, such as having both <seriesInfo name="rfc"/> and <seriesInfo name="Internet-Draft"/> in the same <front> element.

This element appears as a child element of <front> ([Section 2.25](#)) and <reference> ([Section 2.39](#); deprecated in this context).

Content model: this element does not have any contents.

[2.46.1.](#) "asciiName" Attribute

The ASCII equivalent of the name field.

[2.46.2.](#) "asciiValue" Attribute

The ASCII equivalent of the value field.

2.46.3. "name" Attribute (Mandatory)

The name of the series. The currently known values are "RFC", "Internet-Draft", and "DOI". The RFC Series Editor may change this list in the future.

Some of the values for "name" interact as follows:

- o If a <front> element contains a <seriesInfo> element with a name of "Internet-Draft", it can also have at most one additional <seriesInfo> element with a "status" attribute whose value is of "standard", "full-standard", "bcp", "fyi", "informational", "experimental", or "historic" to indicate the intended status of this Internet-Draft, if it were to be later published as an RFC. If such an additional <seriesInfo> element has one of those statuses, the name needs to be "".
- o If a <front> element contains a <seriesInfo> element with a name of "RFC", it can also have at most one additional <seriesInfo> element with a "status" attribute whose value is of "full-standard", "bcp", or "fyi" to indicate the current status of this RFC. If such an additional <seriesInfo> element has one of those statuses, the "value" attribute for that name needs to be the number within that series. That <front> element might also contain an additional <seriesInfo> element with the status of "info", "exp", or "historic" and a name of "" to indicate the status of the RFC.
- o A <front> element that has a <seriesInfo> element that has the name "Internet-Draft" cannot also have a <seriesInfo> element that has the name "RFC".
- o The <seriesInfo> element can contain the DOI for the referenced document. This cannot be used when the <seriesInfo> element is an eventual child element of an <rfc> element -- only as an eventual child of a <reference> element. The "value" attribute should use the form specified in [[RFC7669](#)].

2.46.4. "status" Attribute

The status of this document. The currently known values are "standard", "informational", "experimental", "bcp", "fyi", and "full-standard". The RFC Series Editor may change this list in the future.

2.46.5. "stream" Attribute

The stream (as described in [[RFC7841](#)]) that originated the document. (The RFC Series Editor may change this list in the future.)

Allowed values:

- o "IETF" (default)
- o "IAB"
- o "IRTF"
- o "independent"

2.46.6. "value" Attribute (Mandatory)

The identifier within the series specified by the "name" attribute.

For BCPs, FYIs, RFCs, and STDs, this is the number within the series. For Internet-Drafts, it is the full draft name (ending with the two-digit version number). For DOIs, the value is given, such as "10.17487/rfc1149", as described in [[RFC7669](#)].

The name in the value should be the document name without any file extension. For Internet-Drafts, the value for this attribute should be "[draft-ietf-somewg-someprotocol-07](#)", not "[draft-ietf-somewg-someprotocol-07.txt](#)".

2.47. <sourcecode>

This element allows the inclusion of source code into the document.

When rendered, source code is always shown in a monospace font. When <sourcecode> is a child of <figure> or <section>, it provides full control of horizontal whitespace and line breaks. When formatted, it is indented relative to the left margin of the enclosing element. It is thus useful for source code and formal languages (such as ABNF [[RFC5234](#)] or the RNC notation used in this document). (When <sourcecode> is a child of other elements, it flows with the text that surrounds it.) Tab characters (U+0009) inside of this element are prohibited.

For artwork such as character-based art, diagrams of message layouts, and so on, use the <artwork> element instead.

Output formatters that do pagination should attempt to keep source code on a single page. This is to prevent source code that is split across pages from looking like two separate pieces of code.

See [Section 5](#) for a description of how to deal with issues of using "&" and "<" characters in source code.

This element appears as a child element of `<blockquote>` ([Section 2.10](#)), `<dd>` ([Section 2.17](#)), `<figure>` ([Section 2.24](#)), `` ([Section 2.28](#)), `<section>` ([Section 2.45](#)), `<td>` ([Section 2.55](#)), and `<th>` ([Section 2.57](#)).

Content model: only text content.

[2.47.1.](#) "anchor" Attribute

Document-wide unique identifier for this source code.

[2.47.2.](#) "name" Attribute

A filename suitable for the contents (such as for extraction to a local file). This attribute can be helpful for other kinds of tools (such as automated syntax checkers, which work by extracting the source code). Note that the "name" attribute does not need to be unique for `<artwork>` elements in a document. If multiple `<sourcecode>` elements have the same "name" attribute, a formatter might assume that the elements are all fragments of a single file, and such a formatter can collect those fragments for later processing.

[2.47.3.](#) "src" Attribute

The URI reference of a source file [[RFC3986](#)].

It is an error to have both a "src" attribute and content in the `<sourcecode>` element.

[2.47.4.](#) "type" Attribute

Specifies the type of the source code. The value of this attribute is free text with certain values designated as preferred.

The preferred values for `<sourcecode>` types are:

- o abnf
- o asn.1
- o bash
- o c++
- o c

- o cbor
- o dtd
- o java
- o javascript
- o json
- o mib
- o perl
- o pseudocode
- o python
- o rnc
- o xml
- o yang

The RFC Series Editor will maintain a complete list of the preferred values on the RFC Editor web site, and that list is expected to be updated over time. Thus, a consumer of v3 XML should not cause a failure when it encounters an unexpected type or no type is specified.

2.48. <street>

Provides a street address.

This element appears as a child element of <postal> ([Section 2.36](#)).

Content model: only text content.

2.48.1. "ascii" Attribute

The ASCII equivalent of the street address.

**2.49. **

Indicates text that is semantically strong. Text enclosed within this element will be displayed as bold after processing. This element can be combined with other character formatting elements, and the formatting will be additive.

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.10](#)), <cref> ([Section 2.15](#)), <dd> ([Section 2.17](#)), <dt> ([Section 2.20](#)), ([Section 2.21](#)), ([Section 2.28](#)), <preamble> ([Section 3.6](#)), <refcontent> ([Section 2.38](#)), <sub> ([Section 2.50](#)), <sup> ([Section 2.51](#)), <t> ([Section 2.52](#)), <td> ([Section 2.55](#)), <th> ([Section 2.57](#)), and <tt> ([Section 2.61](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.9](#))
- o <cref> elements ([Section 2.15](#))
- o elements ([Section 2.21](#))
- o <eref> elements ([Section 2.23](#))
- o <iref> elements ([Section 2.26](#))
- o <relref> elements ([Section 2.43](#))
- o <sub> elements ([Section 2.50](#))
- o <sup> elements ([Section 2.51](#))
- o <tt> elements ([Section 2.61](#))
- o <xref> elements ([Section 2.65](#))

[2.50](#). <sub>

Causes the text to be displayed as subscript, approximately half a letter-height lower than normal text. This element can be combined with other character formatting elements, and the formatting will be additive.

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.10](#)), <cref> ([Section 2.15](#)), <dd> ([Section 2.17](#)), <dt> ([Section 2.20](#)), ([Section 2.21](#)), ([Section 2.28](#)), <preamble> ([Section 3.6](#)), <refcontent> ([Section 2.38](#)), ([Section 2.49](#)), <t> ([Section 2.52](#)), <td> ([Section 2.55](#)), <th> ([Section 2.57](#)), and <tt> ([Section 2.61](#)).

Content model:

In any order:

- o Text
- o `<bcp14>` elements ([Section 2.9](#))
- o `<cref>` elements ([Section 2.15](#))
- o `` elements ([Section 2.21](#))
- o `<eref>` elements ([Section 2.23](#))
- o `<iref>` elements ([Section 2.26](#))
- o `<relref>` elements ([Section 2.43](#))
- o `` elements ([Section 2.49](#))
- o `<tt>` elements ([Section 2.61](#))
- o `<xref>` elements ([Section 2.65](#))

[2.51.](#) `<sup>`

Causes the text to be displayed as superscript, approximately half a letter-height higher than normal text. This element can be combined with other character formatting elements, and the formatting will be additive.

This element appears as a child element of `<annotation>` ([Section 2.3](#)), `<blockquote>` ([Section 2.10](#)), `<cref>` ([Section 2.15](#)), `<dd>` ([Section 2.17](#)), `<dt>` ([Section 2.20](#)), `` ([Section 2.21](#)), `` ([Section 2.28](#)), `<preamble>` ([Section 3.6](#)), `<refcontent>` ([Section 2.38](#)), `` ([Section 2.49](#)), `<t>` ([Section 2.52](#)), `<td>` ([Section 2.55](#)), `<th>` ([Section 2.57](#)), and `<tt>` ([Section 2.61](#)).

Content model:

In any order:

- o Text
- o `<bcp14>` elements ([Section 2.9](#))
- o `<cref>` elements ([Section 2.15](#))

- o `` elements ([Section 2.21](#))
- o `<eref>` elements ([Section 2.23](#))
- o `<iref>` elements ([Section 2.26](#))
- o `<relref>` elements ([Section 2.43](#))
- o `` elements ([Section 2.49](#))
- o `<tt>` elements ([Section 2.61](#))
- o `<xref>` elements ([Section 2.65](#))

[2.52.](#) `<t>`

Contains a paragraph of text.

This element appears as a child element of `<abstract>` ([Section 2.1](#)), `<aside>` ([Section 2.6](#)), `<blockquote>` ([Section 2.10](#)), `<dd>` ([Section 2.17](#)), `` ([Section 2.28](#)), `<list>` ([Section 3.4](#)), `<note>` ([Section 2.32](#)), `<section>` ([Section 2.45](#)), `<td>` ([Section 2.55](#)), and `<th>` ([Section 2.57](#)).

Content model:

In any order:

- o Text
- o `<bcp14>` elements ([Section 2.9](#))
- o `<cref>` elements ([Section 2.15](#))
- o `` elements ([Section 2.21](#))
- o `<eref>` elements ([Section 2.23](#))
- o `<iref>` elements ([Section 2.26](#))
- o `<list>` elements ([Section 3.4](#))
- o `<relref>` elements ([Section 2.43](#))
- o `<spanx>` elements ([Section 3.7](#))
- o `` elements ([Section 2.49](#))

- o <sub> elements ([Section 2.50](#))
- o <sup> elements ([Section 2.51](#))
- o <tt> elements ([Section 2.61](#))
- o <vspace> elements ([Section 3.10](#))
- o <xref> elements ([Section 2.65](#))

[2.52.1.](#) "anchor" Attribute

Document-wide unique identifier for this paragraph.

[2.52.2.](#) "hangText" Attribute

Deprecated. Instead, use <dd> inside of a definition list (<dl>).

[2.52.3.](#) "keepWithNext" Attribute

Acts as a hint to the output formatters that do pagination to do a best-effort attempt to keep the paragraph with the next element, whatever that happens to be. For example, the HTML output @media print CSS ("CSS" refers to Cascading Style Sheets) might translate this to page-break-after: avoid. For PDF, the paginator could attempt to keep the paragraph with the next element. Note: this attribute is strictly a hint and not always actionable.

Allowed values:

- o "false" (default)
- o "true"

[2.52.4.](#) "keepWithPrevious" Attribute

Acts as a hint to the output formatters that do pagination to do a best-effort attempt to keep the paragraph with the previous element, whatever that happens to be. For example, the HTML output @media print CSS might translate this to page-break-before: avoid. For PDF, the paginator could attempt to keep the paragraph with the previous element. Note: this attribute is strictly a hint and not always actionable.

Allowed values:

- o "false" (default)
- o "true"

2.53. <table>

Contains a table with a caption with the table number. If the element contains a <name> element, the caption will also show that name.

Inside the <table> element is, optionally, a <thead> element to contain the rows that will be the table's heading and, optionally, a <tfoot> element to contain the rows of the table's footer. If the XML is converted to a representation that has page breaks (such as PDFs or printed HTML), the header and footer are meant to appear on each page.

This element appears as a child element of <aside> ([Section 2.6](#)) and <section> ([Section 2.45](#)).

Content model:

In this order:

1. One optional <name> element ([Section 2.31](#))
2. Optional <iref> elements ([Section 2.26](#))
3. One optional <thead> element ([Section 2.58](#))
4. One or more <tbody> elements ([Section 2.54](#))
5. One optional <tfoot> element ([Section 2.56](#))

2.53.1. "align" Attribute

Controls whether the table appears left justified, centered (default), or right justified. Tables are aligned relative to the left margin of the document.

Allowed values:

- o "left"
- o "center" (default)
- o "right"

[2.53.2.](#) "anchor" Attribute

Document-wide unique identifier for this table.

[2.54.](#) <tbody>

A container for a set of body rows for a table.

This element appears as a child element of <table> ([Section 2.53](#)).

Content model:

One or more <tr> elements ([Section 2.60](#))

[2.54.1.](#) "anchor" Attribute

Document-wide unique identifier for the tbody.

[2.55.](#) <td>

A cell in a table row.

This element appears as a child element of <tr> ([Section 2.60](#)).

Content model:

Either:

In any order, but at least one of:

- * <artwork> elements ([Section 2.5](#))
- * <dl> elements ([Section 2.19](#))
- * <figure> elements ([Section 2.24](#))
- * elements ([Section 2.33](#))
- * <sourcecode> elements ([Section 2.47](#))
- * <t> elements ([Section 2.52](#))
- * elements ([Section 2.62](#))

Or:

In any order:

- * Text
- * `<bcp14>` elements ([Section 2.9](#))
- * `<cref>` elements ([Section 2.15](#))
- * `` elements ([Section 2.21](#))
- * `<eref>` elements ([Section 2.23](#))
- * `<iref>` elements ([Section 2.26](#))
- * `<relref>` elements ([Section 2.43](#))
- * `` elements ([Section 2.49](#))
- * `<sub>` elements ([Section 2.50](#))
- * `<sup>` elements ([Section 2.51](#))
- * `<tt>` elements ([Section 2.61](#))
- * `<xref>` elements ([Section 2.65](#))

[2.55.1](#). "align" Attribute

Controls whether the content of the cell appears left justified (default), centered, or right justified. Note that "center" or "right" will probably only work well in cells with plain text; any other elements might make the contents render badly.

Allowed values:

- o "left" (default)
- o "center"
- o "right"

[2.55.2](#). "anchor" Attribute

Document-wide unique identifier for the cell.

[2.55.3.](#) "colspan" Attribute

The number of columns that the cell is to span. For example, setting "colspan='3'" indicates that the cell occupies the same horizontal space as three cells of a row without any "colspan" attributes.

[2.55.4.](#) "rowspan" Attribute

The number of rows that the cell is to span. For example, setting "rowspan='3'" indicates that the cell occupies the same vertical space as three rows.

[2.56.](#) <tfoot>

A container for a set of footer rows for a table.

This element appears as a child element of <table> ([Section 2.53](#)).

Content model:

One or more <tr> elements ([Section 2.60](#))

[2.56.1.](#) "anchor" Attribute

Document-wide unique identifier for the tfoot.

[2.57.](#) <th>

A cell in a table row. When rendered, this will normally come out in boldface; other than that, there is no difference between this and the <td> element.

This element appears as a child element of <tr> ([Section 2.60](#)).

Content model:

Either:

In any order, but at least one of:

- * <artwork> elements ([Section 2.5](#))
- * <dl> elements ([Section 2.19](#))
- * <figure> elements ([Section 2.24](#))

- * `` elements ([Section 2.33](#))
- * `<sourcecode>` elements ([Section 2.47](#))
- * `<t>` elements ([Section 2.52](#))
- * `` elements ([Section 2.62](#))

Or:

In any order:

- * Text
- * `<bc14>` elements ([Section 2.9](#))
- * `<cref>` elements ([Section 2.15](#))
- * `` elements ([Section 2.21](#))
- * `<eref>` elements ([Section 2.23](#))
- * `<iref>` elements ([Section 2.26](#))
- * `<relref>` elements ([Section 2.43](#))
- * `` elements ([Section 2.49](#))
- * `<sub>` elements ([Section 2.50](#))
- * `<sup>` elements ([Section 2.51](#))
- * `<tt>` elements ([Section 2.61](#))
- * `<xref>` elements ([Section 2.65](#))

2.57.1. "align" Attribute

Controls whether the content of the cell appears left justified (default), centered, or right justified. Note that "center" or "right" will probably only work well in cells with plain text; any other elements might make the contents render badly.

Allowed values:

- o "left" (default)
- o "center"
- o "right"

[2.57.2.](#) "anchor" Attribute

Document-wide unique identifier for the row.

[2.57.3.](#) "colspan" Attribute

The number of columns that the cell is to span. For example, setting "colspan='3'" indicates that the cell occupies the same horizontal space as three cells of a row without any "colspan" attributes.

[2.57.4.](#) "rowspan" Attribute

The number of rows that the cell is to span. For example, setting "rowspan='3'" indicates that the cell occupies the same vertical space as three rows.

[2.58.](#) <thead>

A container for a set of header rows for a table.

This element appears as a child element of <table> ([Section 2.53](#)).

Content model:

One or more <tr> elements ([Section 2.60](#))

[2.58.1.](#) "anchor" Attribute

Document-wide unique identifier for the thead.

[2.59.](#) <title>

Represents the document title.

When this element appears in the <front> element of the current document, the title might also appear in page headers or footers. If it is long (~40 characters), the "abbrev" attribute can be used to specify an abbreviated variant.

This element appears as a child element of <front> ([Section 2.25](#)).

Content model: only text content.

[2.59.1.](#) "abbrev" Attribute

Specifies an abbreviated variant of the document title.

[2.59.2.](#) "ascii" Attribute

The ASCII equivalent of the title.

[2.60.](#) <tr>

A row of a table.

This element appears as a child element of <tbody> ([Section 2.54](#)), <tfoot> ([Section 2.56](#)), and <thead> ([Section 2.58](#)).

Content model:

In any order, but at least one of:

- o <td> elements ([Section 2.55](#))
- o <th> elements ([Section 2.57](#))

[2.60.1.](#) "anchor" Attribute

Document-wide unique identifier for the row.

[2.61.](#) <tt>

Causes the text to be displayed in a constant-width font. This element can be combined with other character formatting elements, and the formatting will be additive.

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.10](#)), <cref> ([Section 2.15](#)), <dd> ([Section 2.17](#)), <dt> ([Section 2.20](#)), ([Section 2.21](#)), ([Section 2.28](#)), <name> ([Section 2.31](#)), <preamble> ([Section 3.6](#)), <refcontent> ([Section 2.38](#)), ([Section 2.49](#)), <sub> ([Section 2.50](#)), <sup> ([Section 2.51](#)), <t> ([Section 2.52](#)), <td> ([Section 2.55](#)), and <th> ([Section 2.57](#)).

Content model:

In any order:

- o Text

- o `<bcp14>` elements ([Section 2.9](#))
- o `<cref>` elements ([Section 2.15](#))
- o `` elements ([Section 2.21](#))
- o `<eref>` elements ([Section 2.23](#))
- o `<iref>` elements ([Section 2.26](#))
- o `<relref>` elements ([Section 2.43](#))
- o `` elements ([Section 2.49](#))
- o `<sub>` elements ([Section 2.50](#))
- o `<sup>` elements ([Section 2.51](#))
- o `<xref>` elements ([Section 2.65](#))

[2.62.](#) ``

An unordered list. The labels on the items will be symbols picked by the formatter.

This element appears as a child element of `<abstract>` ([Section 2.1](#)), `<aside>` ([Section 2.6](#)), `<blockquote>` ([Section 2.10](#)), `<dd>` ([Section 2.17](#)), `` ([Section 2.28](#)), `<note>` ([Section 2.32](#)), `<section>` ([Section 2.45](#)), `<td>` ([Section 2.55](#)), and `<th>` ([Section 2.57](#)).

Content model:

One or more `` elements ([Section 2.28](#))

[2.62.1.](#) "anchor" Attribute

Document-wide unique identifier for the list.

[2.62.2.](#) "empty" Attribute

Defines whether or not the label is empty. `empty="true"` indicates that no label will be shown.

Allowed values:

- o "false" (default)

- o "true"

2.62.3. "spacing" Attribute

Defines whether or not there is a blank line between entries. spacing="normal" indicates a single blank line, while spacing="compact" indicates no space between.

Allowed values:

- o "normal" (default)
- o "compact"

2.63. <uri>

Contains a web address associated with the author.

The contents should be a valid URI; this most likely will be an "http:" or "https:" URI.

This element appears as a child element of <address> ([Section 2.2](#)).

Content model: only text content.

2.64. <workgroup>

This element is used to specify the Working Group (IETF) or Research Group (IRTF) from which the document originates, if any. The recommended format is the official name of the Working Group (with some capitalization).

In Internet-Drafts, this is used in the upper left corner of the boilerplate, replacing the "Network Working Group" string. Formatting software can append the words "Working Group" or "Research Group", depending on the "submissionType" property of the <rfc> element ([Section 2.44.12](#)).

This element appears as a child element of <front> ([Section 2.25](#)).

Content model: only text content.

2.65. <xref>

A reference to an anchor in this document. Formatters that have links (such as HTML and PDF) are likely to render <xref> elements as internal hyperlinks. This element is useful for referring to references in the "References" section, to specific sections of this

document, to specific figures, and so on. The "target" attribute is required.

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.10](#)), <c> ([Section 3.1](#)), <cref> ([Section 2.15](#)), <dd> ([Section 2.17](#)), <dt> ([Section 2.20](#)), ([Section 2.21](#)), ([Section 2.28](#)), <name> ([Section 2.31](#)), <postamble> ([Section 3.5](#)), <preamble> ([Section 3.6](#)), ([Section 2.49](#)), <sub> ([Section 2.50](#)), <sup> ([Section 2.51](#)), <t> ([Section 2.52](#)), <td> ([Section 2.55](#)), <th> ([Section 2.57](#)), <tt> ([Section 2.61](#)), and <ttcol> ([Section 3.9](#)).

Content model: only text content.

2.65.1. "format" Attribute

This attribute signals to formatters what the desired format of the reference should be. Formatters for document types that have linking capability should wrap the displayed text in hyperlinks.

"counter"

The "derivedContent" attribute will contain just a counter. This is used for targets that are <section>, <figure>, <table>, or items in an ordered list. Using "format='counter'" where the target is any other type of element is an error.

For example, with an input of:

```
<section anchor="overview">Protocol Overview</section>
. . .
See Section <xref target="overview" format="counter"/>
for an overview.
```

An HTML formatter might generate:

```
See Section <a href="#overview">1.7</a> for an overview.
```

"default"

If the element has no content, the "derivedContent" attribute will contain a text fragment that describes the referenced part completely, such as "XML" for a target that is a <reference>, or "[Section 2](#)" or "Table 4" for a target to a non-reference. (If the element has content, the "derivedContent" attribute is filled with the content.)

For example, with an input of:

```
<section anchor="overview">Protocol Overview</section>
```

```
. . .
```

```
See <xref target="overview"/> for an overview.
```

An HTML formatter might generate:

```
See <a href="#overview">Section 1.7</a> for an overview.
```

"none"

Deprecated.

"title"

If the target is a <reference> element, the "derivedContent" attribute will contain the name of the reference, extracted from the <title> child of the <front> child of the reference. Or, if the target element has a <name> child element, the "derivedContent" attribute will contain the text content of that <name> element concatenated with the text content of each descendant node of <name> (that is, stripping out all of the XML markup, leaving only the text). Or, if the target element does not contain a <name> child element, the "derivedContent" attribute will contain the name of the "anchor" attribute of that element with no other adornment.

Allowed values:

- o "default" (default)
- o "title"
- o "counter"
- o "none"

2.65.2. "pageno" Attribute

Deprecated.

Allowed values:

- o "true"
- o "false" (default)

[2.65.3.](#) "target" Attribute (Mandatory)

Identifies the document component being referenced. The value needs to match the value of the "anchor" attribute of an element in the document; otherwise, it is an error.

[3.](#) Elements from v2 That Have Been Deprecated

This section lists the elements from v2 that have been deprecated. Note that some elements in v3 have attributes from v2 that are deprecated; those are not listed here.

[3.1.](#) <c>

Deprecated. Instead, use <tr>, <td>, and <th>.

This element appears as a child element of <texttable> ([Section 3.8](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.9](#))
- o <cref> elements ([Section 2.15](#))
- o elements ([Section 2.21](#))
- o <eref> elements ([Section 2.23](#))
- o <iref> elements ([Section 2.26](#))
- o <spanx> elements ([Section 3.7](#))
- o elements ([Section 2.49](#))
- o <sub> elements ([Section 2.50](#))
- o <sup> elements ([Section 2.51](#))
- o <tt> elements ([Section 2.61](#))
- o <xref> elements ([Section 2.65](#))

[3.2.](#) <facsimile>

Deprecated. The <email> element is a much more useful way to get in touch with authors.

This element appears as a child element of <address> ([Section 2.2](#)).

Content model: only text content.

[3.3.](#) <format>

Deprecated. If the goal is to provide a single URI for a reference, use the "target" attribute in <reference> instead.

This element appears as a child element of <reference> ([Section 2.39](#)).

Content model: this element does not have any contents.

[3.3.1.](#) "octets" Attribute

Deprecated.

[3.3.2.](#) "target" Attribute

Deprecated.

[3.3.3.](#) "type" Attribute (Mandatory)

Deprecated.

[3.4.](#) <list>

Deprecated. Instead, use <dl> for list/@style "hanging"; for list/@style "empty" or "symbols"; and for list/@style "letters", "numbers", "counter", or "format".

This element appears as a child element of <t> ([Section 2.52](#)).

Content model:

One or more <t> elements ([Section 2.52](#))

[3.4.1.](#) "counter" Attribute

Deprecated. The functionality of this attribute has been replaced with /@start.

[3.4.2.](#) "hangIndent" Attribute

Deprecated. Use <dl> instead.

[3.4.3.](#) "style" Attribute

Deprecated.

[3.5.](#) <postamble>

Deprecated. Instead, use a regular paragraph after the figure or table.

This element appears as a child element of <figure> ([Section 2.24](#)) and <texttable> ([Section 3.8](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.9](#))
- o <cref> elements ([Section 2.15](#))
- o elements ([Section 2.21](#))
- o <eref> elements ([Section 2.23](#))
- o <iref> elements ([Section 2.26](#))
- o <spanx> elements ([Section 3.7](#))
- o elements ([Section 2.49](#))
- o <sub> elements ([Section 2.50](#))
- o <sup> elements ([Section 2.51](#))
- o <tt> elements ([Section 2.61](#))
- o <xref> elements ([Section 2.65](#))

3.6. <preamble>

Deprecated. Instead, use a regular paragraph before the figure or table.

This element appears as a child element of <figure> ([Section 2.24](#)) and <texttable> ([Section 3.8](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.9](#))
- o <cref> elements ([Section 2.15](#))
- o elements ([Section 2.21](#))
- o <eref> elements ([Section 2.23](#))
- o <iref> elements ([Section 2.26](#))
- o <spanx> elements ([Section 3.7](#))
- o elements ([Section 2.49](#))
- o <sub> elements ([Section 2.50](#))
- o <sup> elements ([Section 2.51](#))
- o <tt> elements ([Section 2.61](#))
- o <xref> elements ([Section 2.65](#))

3.7. <spanx>

Deprecated.

This element appears as a child element of <annotation> ([Section 2.3](#)), <c> ([Section 3.1](#)), <postamble> ([Section 3.5](#)), <preamble> ([Section 3.6](#)), and <t> ([Section 2.52](#)).

Content model: only text content.

[3.7.1.](#) "style" Attribute

Deprecated. Instead of `<spanx style="emph">`, use ``; instead of `<spanx style="strong">`, use ``; instead of `<spanx style="verb">`, use `<tt>`.

[3.7.2.](#) "xml:space" Attribute

Deprecated.

Allowed values:

- o "default"
- o "preserve" (default)

[3.8.](#) `<texttable>`

Deprecated. Use `<table>` instead.

This element appears as a child element of `<aside>` ([Section 2.6](#)) and `<section>` ([Section 2.45](#)).

Content model:

In this order:

1. One optional `<name>` element ([Section 2.31](#))
2. One optional `<preamble>` element ([Section 3.6](#))
3. One or more `<tocol>` elements ([Section 3.9](#))
4. Optional `<c>` elements ([Section 3.1](#))
5. One optional `<postamble>` element ([Section 3.5](#))

[3.8.1.](#) "align" Attribute

Deprecated.

Allowed values:

- o "left"
- o "center" (default)

- o "right"

[3.8.2.](#) "anchor" Attribute

Deprecated.

[3.8.3.](#) "style" Attribute

Deprecated.

[3.8.4.](#) "suppress-title" Attribute

Deprecated.

Allowed values:

- o "true"
- o "false" (default)

[3.8.5.](#) "title" Attribute

Deprecated.

[3.9.](#) <ttcol>

Deprecated. Instead, use <tr>, <td>, and <th>.

This element appears as a child element of <texttable> ([Section 3.8](#)).

Content model:

In any order:

- o Text
- o <cref> elements ([Section 2.15](#))
- o <eref> elements ([Section 2.23](#))
- o <iref> elements ([Section 2.26](#))
- o <xref> elements ([Section 2.65](#))

[3.9.1.](#) "align" Attribute

Deprecated.

Allowed values:

- o "left" (default)
- o "center"
- o "right"

[3.9.2.](#) "width" Attribute

Deprecated.

[3.10.](#) <vspace>

Deprecated. In earlier versions of this format, <vspace> was often used to get an extra blank line in a list element; in the v3 vocabulary, that can be done instead by using multiple <t> elements inside the element. Other uses have no direct replacement.

This element appears as a child element of <t> ([Section 2.52](#)).

Content model: this element does not have any contents.

[3.10.1.](#) "blankLines" Attribute

Deprecated.

[4.](#) SVG

The discussion of the use of SVG can be found in [[RFC7996](#)]. This element is part of the namespace "http://www.w3.org/2000/svg".

[5.](#) Use of CDATA Structures and Escaping

A common problem authors have with <artwork> and <sourcecode> elements is that the XML processor returns errors if the text in the artwork contains either the "&" or "<" character, or the string "]]>". To avoid these problems, the "&" and "<" characters may be escaped using the strings "&" and "<", respectively; the "]]>" string can be represented as "]]>". Alternatively, they may be surrounded in a CDATA structure: "<![CDATA[]]>". For example:

Desired output:

```
allowed-chars = "." | "," | "&" | "<" | ">" | "|"
```

Using escaping:

```
<sourcecode>
```

```
allowed-chars = "." | "," | "&#" | "&lt;#" | "&gt;#" | "|"
```

```
</sourcecode>
```

Using CDATA:

```
<sourcecode>
```

```
<![CDATA[ allowed-chars = "." | "," | "&" | "<" | ">" | "|"]]>
```

```
</sourcecode>
```

Using CDATA is not a panacea, but it does help prevent having to use escapes in places where using escapes can cause other problems, such as difficulty of inclusion from other documents.

6. Internationalization Considerations

This format is based on [\[XML\]](#) and thus does not have any issues representing arbitrary Unicode [\[UNICODE\]](#) characters in text content. The RFC Series Editor may restrict some of the characters that can be used in a particular RFC; the rules for such restrictions are covered in [\[RFC7997\]](#).

7. Security Considerations

The "name" attribute of the `<artwork>` element ([Section 2.5.5](#)) can be used to derive a filename for saving to a local file system. Trusting this kind of information without pre-processing is a known security risk; see [Section 4.3 of \[RFC6266\]](#) for more information.

The "src" attribute of the `<artwork>` element can be used to read files from the local system. Processing tools must be careful to not accept dangerous values for the filename, particularly those that contain absolute references outside the current directory.

The "type" attribute of the `<artwork>` and `<sourcecode>` elements is meant to encourage formatters to automatically extract known types of content from an RFC or Internet-Draft. While extraction is probably safe, those tools might also think that they could further process the extracted content, such as by rendering artwork or executing code. Doing so without first sanity-checking the extracted content is clearly a terrible idea from a security perspective. More generally, a tool that is reading XML input needs to be suspicious of any content that it intends to post-process.

When there is an external reference to a URL, a processor or renderer should fetch the content into a sandbox and should have only a localized impact on the document processing and rendering.

All security considerations related to XML processing are relevant as well (see [Section 7 of \[RFC3470\]](#)).

8. IANA Considerations

8.1. Internet Media Type Registration

IANA maintains the registry of Internet Media Types [[RFC6838](#)] at <https://www.iana.org/assignments/media-types>.

This document updates the specification for the Internet Media Type "application/rfc+xml" from the one in [[RFC7749](#)]. The following has been registered with IANA.

Type name: application

Subtype name: rfc+xml

Required parameters: There are no required parameters.

Optional parameters: "charset": This parameter has identical semantics to the charset parameter of the "application/xml" Media Type specified in [Section 9.1 of \[RFC7303\]](#).

Encoding considerations: Identical to those of "application/xml" as described in [Section 9.1 of \[RFC7303\]](#).

Security considerations: As defined in [Section 7](#). In addition, as this Media Type uses the "+xml" convention, it inherits the security considerations described in [Section 10 of \[RFC7303\]](#).

Interoperability considerations: Different implementations of this format have had interoperability issues. It is not expected that publication of this application will cause those implementations to be fixed.

Published specification: This specification.

Applications that use this Media Type: Applications that transform xml2rfc to output representations such as plain text or HTML, plus additional analysis tools.

Fragment identifier considerations: The "anchor" attribute is used for assigning document-wide unique identifiers that can be used as shorthand pointers, as described in [[XPOINTER](#)].

Additional information:

Deprecated alias names for this type: None

Magic number(s): As specified for "application/xml" in [[RFC7303](#)].

File extension(s): .xml or .rfcxml when disambiguation from other XML files is needed

Macintosh file type code(s): TEXT

Person & email address to contact for further information: See the Author's Address section of [RFC 7991](#).

Intended usage: COMMON

Restrictions on usage: None

Author: See the Author's Address section of [RFC 7991](#).

Change controller: RFC Series Editor (rse@rfc-editor.org)

[8.2.](#) Link Relation Registration

IANA has registered "convertedFrom" in the "Link Relation Types" registry [[LINKRELATIONS](#)].

Relation Name: convertedFrom

Description: The document linked to was later converted to the document that contains this link relation. For example, an RFC can have a link to the Internet-Draft that became the RFC; in that case, the link relation would be "convertedFrom".

Reference: This document.

Notes: This relation is different than "predecessor-version" in that "predecessor-version" is for items in a version control system. It is also different than "previous" in that this relation is used for converted resources, not those that are part of a sequence of resources.

Application Data: None

9. References

9.1. Normative References

- [BCP14] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997, <<http://www.rfc-editor.org/info/bcp14>>.
- [RFC7991] Hoffman, P., "The "xml2rfc" Version 3 Vocabulary", [RFC 7991](#), DOI 10.17487/RFC7991, December 2016, <<https://www.rfc-editor.org/info/rfc7991>>.
- [XML] Bray, T., Paoli, J., Sperberg-McQueen, C., Maler, E., and F. Yergeau, "Extensible Markup Language (XML) 1.0 (Fifth Edition)", W3C Recommendation REC-xml-20081126, November 2008, <<https://www.w3.org/TR/2008/REC-xml-20081126/>>.
- Latest version available at <<http://www.w3.org/TR/xml>>.

9.2. Informative References

- [IDGUIDE] Housley, R., "Guidelines to Authors of Internet-Drafts", December 2010, <<https://www.ietf.org/id-info/guidelines.html>>.
- [LINKRELATIONS] IANA, "Link Relations", <<https://www.iana.org/assignments/link-relations/link-relations.xhtml>>.
- [RFC2026] Bradner, S., "The Internet Standards Process -- Revision 3", [BCP 9](#), [RFC 2026](#), DOI 10.17487/RFC2026, October 1996, <<https://www.rfc-editor.org/info/rfc2026>>.
- [RFC2397] Masinter, L., "The "data" URL scheme", [RFC 2397](#), DOI 10.17487/RFC2397, August 1998, <<https://www.rfc-editor.org/info/rfc2397>>.
- [RFC2629] Rose, M., "Writing I-Ds and RFCs using XML", [RFC 2629](#), DOI 10.17487/RFC2629, June 1999, <<https://www.rfc-editor.org/info/rfc2629>>.
- [RFC3339] Klyne, G. and C. Newman, "Date and Time on the Internet: Timestamps", [RFC 3339](#), DOI 10.17487/[RFC3339](#), July 2002, <<https://www.rfc-editor.org/info/rfc3339>>.

- [RFC3470] Hollenbeck, S., Rose, M., and L. Masinter, "Guidelines for the Use of Extensible Markup Language (XML) within IETF Protocols", [BCP 70](#), [RFC 3470](#), DOI 10.17487/RFC3470, January 2003, <<https://www.rfc-editor.org/info/rfc3470>>.
- [RFC3667] Bradner, S., "IETF Rights in Contributions", [RFC 3667](#), DOI 10.17487/RFC3667, February 2004, <<https://www.rfc-editor.org/info/rfc3667>>.
- [RFC3966] Schulzrinne, H., "The tel URI for Telephone Numbers", [RFC 3966](#), DOI 10.17487/RFC3966, December 2004, <<https://www.rfc-editor.org/info/rfc3966>>.
- [RFC3978] Bradner, S., Ed., "IETF Rights in Contributions", [RFC 3978](#), DOI 10.17487/RFC3978, March 2005, <<https://www.rfc-editor.org/info/rfc3978>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), DOI 10.17487/RFC5234, January 2008, <<https://www.rfc-editor.org/info/rfc5234>>.
- [RFC5378] Bradner, S., Ed. and J. Contreras, Ed., "Rights Contributors Provide to the IETF Trust", [BCP 78](#), [RFC 5378](#), DOI 10.17487/RFC5378, November 2008, <<https://www.rfc-editor.org/info/rfc5378>>.
- [RFC6068] Duerst, M., Masinter, L., and J. Zawinski, "The 'mailto' URI Scheme", [RFC 6068](#), DOI 10.17487/[RFC6068](#), October 2010, <<https://www.rfc-editor.org/info/rfc6068>>.
- [RFC6266] Reschke, J., "Use of the Content-Disposition Header Field in the Hypertext Transfer Protocol (HTTP)", [RFC 6266](#), DOI 10.17487/RFC6266, June 2011, <<https://www.rfc-editor.org/info/rfc6266>>.
- [RFC6838] Freed, N., Klensin, J., and T. Hansen, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 6838](#), DOI 10.17487/RFC6838, January 2013,

- <<https://www.rfc-editor.org/info/rfc6838>>.
- [RFC6949] Flanagan, H. and N. Brownlee, "RFC Series Format Requirements and Future Development", [RFC 6949](#), DOI 10.17487/RFC6949, May 2013, <<https://www.rfc-editor.org/info/rfc6949>>.
- [RFC7303] Thompson, H. and C. Lilley, "XML Media Types", [RFC 7303](#), DOI 10.17487/RFC7303, July 2014, <<https://www.rfc-editor.org/info/rfc7303>>.
- [RFC7322] Flanagan, H. and S. Ginoza, "RFC Style Guide", [RFC 7322](#), DOI 10.17487/RFC7322, September 2014, <<https://www.rfc-editor.org/info/rfc7322>>.
- [RFC7669] Levine, J., "Assigning Digital Object Identifiers to RFCs", [RFC 7669](#), DOI 10.17487/RFC7669, October 2015, <<https://www.rfc-editor.org/info/rfc7669>>.
- [RFC7749] Reschke, J., "The "xml2rfc" Version 2 Vocabulary", [RFC 7749](#), DOI 10.17487/RFC7749, February 2016, <<https://www.rfc-editor.org/info/rfc7749>>.
- [RFC7841] Halpern, J., Ed., Daigle, L., Ed., and O. Kolkman, Ed., "RFC Streams, Headers, and Boilerplates", [RFC 7841](#), DOI 10.17487/RFC7841, May 2016, <<https://www.rfc-editor.org/info/rfc7841>>.
- [RFC7996] Brownlee, N., "SVG Drawings for RFCs: SVG 1.2 RFC", [RFC 7996](#), DOI 10.17487/RFC7996, December 2016, <<https://www.rfc-editor.org/info/rfc7996>>.
- [RFC7997] Flanagan, H., Ed., "The Use of Non-ASCII Characters in RFCs", [RFC 7997](#), DOI 10.17487/RFC7997, December 2016, <<https://www.rfc-editor.org/info/rfc7997>>.
- [RFC7998] Hoffman, P. and J. Hildebrand, "'xml2rfc" Version 3 Preparation Tool Description", [RFC 7998](#), DOI 10.17487/RFC7998, December 2016, <<https://www.rfc-editor.org/info/rfc7998>>.
- [RNC] Clark, J., "RELAX NG Compact Syntax", The Organization for the Advancement of Structured Information Standards (OASIS) , November 2002, <<https://www.oasis-open.org/committees/relax-ng/compact-20021121.html>>.

- [RNG] ISO/IEC, "Information Technology - Document Schema Definition Languages (DSDL) - Part 2: Regular-Grammar-Based Validation - RELAX NG (Second Edition)", ISO/IEC 19757-2:2008(E), December 2008.
- A useful source of RNG-related information is <<http://relaxng.org/>>.
- [TLP1.0] IETF Trust, "Legal Provisions Relating to IETF Documents", November 2008, <<http://trustee.ietf.org/license-info/IETF-TLP-1.htm>>.
- [TLP2.0] IETF Trust, "Legal Provisions Relating to IETF Documents", February 2009, <<http://trustee.ietf.org/license-info/IETF-TLP-2.htm>>.
- [TLP3.0] IETF Trust, "Legal Provisions Relating to IETF Documents", September 2009, <<http://trustee.ietf.org/license-info/IETF-TLP-3.htm>>.
- [TLP4.0] IETF Trust, "Legal Provisions Relating to IETF Documents", December 2009, <<http://trustee.ietf.org/license-info/IETF-TLP-4.htm>>.
- [TLP5.0] IETF Trust, "Legal Provisions Relating to IETF Documents", March 2015, <<http://trustee.ietf.org/license-info/IETF-TLP-5.htm>>.
- [UAX24] The Unicode Consortium, "UAX #24: Unicode Script Property", <<http://www.unicode.org/reports/tr24/>>.
- [UNICODE] The Unicode Consortium, "The Unicode Standard", <<http://www.unicode.org/versions/latest/>>.
- [USASCII] American National Standards Institute, "Coded Character Set -- 7-bit American Standard Code for Information Interchange", ANSI X3.4, 1986.
- [XInclude] Marsh, J., Orchard, D., and D. Veillard, "XML Inclusions (XInclude) Version 1.0 (Second Edition)", W3C Recommendation REC-xinclude-20061115, November 2006, <<https://www.w3.org/TR/xinclude/REC-xinclude-20061115/>>.
- Latest version available at <<http://www.w3.org/TR/xinclude/>>.
- [XPOINTER] Grosso, P., Maler, E., Marsh, J., and N. Walsh,

"XPointer Framework", W3C Recommendation REC-xptr-framework-20030325, March 2003, <<http://www.w3.org/TR/2003/REC-xptr-framework-20030325/>>.

Latest version available at
<<http://www.w3.org/TR/xptr-framework/>>.

Appendix A. Front-Page ("Boilerplate") Generation

The values listed here will be defined by the RFC Series Editor. Those listed here are believed to be the current values in use.

A.1. The "ipr" Attribute

This attribute value can take a long list of values, each of which describes an IPR policy for the document ([Section 2.44.5](#)). The values are not the result of a grand design, but they remain simply for historic reasons. Of these values, only a few are currently in use; all others are supported by various tools for backwards compatibility with old source files.

Note: Some variations of the boilerplate are selected based on the document's date; therefore, it is important to specify the "year", "month", and "day" attributes of the <date> element when archiving the XML source of an Internet-Draft on the day of submission.

`_Disclaimer: THIS ONLY PROVIDES IMPLEMENTATION INFORMATION. IF YOU NEED LEGAL ADVICE, PLEASE CONTACT A LAWYER._` For further information, refer to <<http://trustee.ietf.org/docs/IETF-Copyright-FAQ.pdf>>.

For the current "Copyright Notice" text, the `submissionType` attribute of the <rfc> element ([Section 2.44.12](#)) determines whether a statement about "Code Components" is inserted (which is the case for the value "IETF", which is the default). Other values, such as "independent", suppress this part of the text.

A.1.1. Current Values: "*trust200902"

The name for these values refers to version 2.0 of the IETF Trust's "Legal Provisions Relating to IETF Documents", sometimes simply called the "TLP", which went into effect on February 15, 2009 [[TLP2.0](#)]. Updates to the document were published on September 12, 2009 [[TLP3.0](#)] and on December 28, 2009 [[TLP4.0](#)], modifying the license for code components (see <<http://trustee.ietf.org/license-info/>> for further information). The actual text is located in [Section 6](#) ("Text to Be Included in IETF Documents") of these documents.

The prep tool automatically produces the "correct" text, depending on the document's date information (see above):

```
+-----+-----+
| TLP      | starting with publication date |
+-----+-----+
| [TLP3.0] | 2009-11-01                      |
| [TLP4.0] | 2010-04-01                      |
+-----+-----+
```

The TLP was again updated in March 2015 [[TLP5.0](#)], but the changes made in that version do not affect the boilerplate text.

[A.1.1.1.](#) **trust200902**

This value should be used unless one of the more specific "*trust200902" values is a better fit. It produces the text in Sections [6.a](#) and [6.b](#) of the TLP.

[A.1.1.2.](#) **noModificationTrust200902**

This produces the additional text from [Section 6.c.i](#) of the TLP:

This document may not be modified, and derivative works of it may not be created, except to format it for publication as an RFC or to translate it into languages other than English.

Note: this clause is incompatible with RFCs that are published on the Standards Track.

[A.1.1.3.](#) **noDerivativesTrust200902**

This produces the additional text from [Section 6.c.ii](#) of the TLP:

This document may not be modified, and derivative works of it may not be created, and it may not be published except as an Internet-Draft.

Note: this clause is incompatible with RFCs.

[A.1.1.4.](#) **pre5378Trust200902**

This produces the additional text from [Section 6.c.iii](#) of the TLP, frequently called the "pre-5378 escape clause" referring to changes introduced in [[RFC5378](#)]:

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

See [Section 4](#) of <http://trustee.ietf.org/docs/IETF-Copyright-FAQ.pdf> for further information about when to use this value.

Note: this text appears under "Copyright Notice", unless the document was published before November 2009, in which case it appears under "Status of This Memo".

[A.1.2.](#) Historic Values

[A.1.2.1.](#) Historic Values: `"*trust200811"`

The attribute values "trust200811", "noModificationTrust200811", and "noDerivativesTrust200811" are similar to their "trust200902" counterparts, except that they use text specified in [[TLP1.0](#)].

[A.1.2.2.](#) Historic Values: `"*3978"`

The attribute values "full3978", "noModification3978", and "noDerivatives3978" are similar to their counterparts above, except that they use text specified in [[RFC3978](#)].

[A.1.2.3.](#) Historic Values: `"*3667"`

The attribute values "full3667", "noModification3667", and "noDerivatives3667" are similar to their counterparts above, except that they use text specified in [[RFC3667](#)].

[A.1.2.4.](#) Historic Values: `"*2026"`

The attribute values "full2026" and "noDerivativeWorks2026" are similar to their counterparts above, except that they use text specified in [Section 10 of \[RFC2026\]](#).

The special value "none" was also used back then; it denied the IETF any rights beyond publication as an Internet-Draft.

[A.2.](#) The "submissionType" Attribute

The RFC Editor publishes documents from different "document streams", of which the "IETF stream" is the most prominent. Other streams are the "Independent Submissions stream" (used for things such as discussion of Internet-related technologies that are not part of the IETF agenda), the "IAB stream" (Internet Architecture Board), and the "IRTF stream" (Internet Research Task Force).

The values for the attribute are "IETF" (the default value), "independent", "IAB", and "IRTF".

Historically, this attribute did not affect the final appearance of RFCs, except for subtle differences in copyright notices. Nowadays (as of [\[RFC7841\]](#)), the stream name appears in the first line of the front page, and it also affects the text in the "Status of This Memo" section.

For current documents, setting the "submissionType" attribute will have the following effect:

- o For RFCs, the stream name appears in the upper left corner of the first page (in Internet-Drafts, this is either "Network Working Group" or the value of the <workgroup> element).
- o For RFCs, it affects the whole "Status of This Memo" section (see [Section 3.2 of \[RFC7841\]](#)).
- o For all RFCs and Internet-Drafts, it determines whether the "Copyright Notice" section mentions the Copyright on Code Components (see [Section 6](#) of the TLP ("Text to Be Included in IETF Documents"))).

[A.3.](#) The "consensus" Attribute

For some of the publication streams (see [Appendix A.2](#)), the "Status of This Memo" section depends on whether there was a consensus to publish (again, see [Section 3.4 of \[RFC7841\]](#)).

The consensus attribute can be used to supply this information. The acceptable values are "true" (the default) and "false"; "yes" and "no" from v2 are deprecated.

The effect of this value for the various streams is:

- o "independent": none.

- o "IAB": mention that there was an IAB consensus.
- o "IETF": mention that there was an IETF consensus.
- o "IRTF": mention that there was a research group consensus (where the name of the research group is extracted from the <workgroup> element).

Appendix B. The v3 Format and Processing Tools

This section describes topics that are specific to v3 processing tools. Note that there is some discussion of tools in the main body of the document as well. For example, some elements have descriptions of how a processing tool might create output from the element.

The expected design of the tools that will be used with v3 documents includes:

- o A "prep tool" that takes a v3 document, makes many checks, adds and changes many attribute values, and creates a file that is a "prepared document". The prepared document is a valid v3 document. The prep tool is described in [[RFC7998](#)].

The prep tool is expected to have many modes:

- * RFC mode -- The mode used by the RFC Editor to process the input from one of the RFC streams and to process XML produced during the RFC editing process. The restrictions on the canonical XML for RFCs, as well as how the non-canonical formats will look, are described at <<https://www.rfc-editor.org/rse/wiki/doku.php?id=design:format-and-content-rfcs>>.
- * Draft mode -- The mode used by the Internet-Draft submission tool. The restrictions for the XML from this mode will be described later.
- * Diagnostic mode -- A mode that can be used by document authors to look for errors or warnings before they submit their documents for publication.
- * Consolidation mode -- Produces output where no external resources are required to render the file output. This includes expanding the XInclude entities and DTD entities in place, and changing all elements that have "src" attributes with external links into either "data:" URI or content for the element, as specified in [[RFC7998](#)].

- o Formatting tools that will create HTML, PDF, plain text, and possibly other output formats. These formatters will be created by the IETF, but others can create such tools as well. The IETF tools are expected to take prepared documents as input.

There may also be processing tools that are meant to run on the computers of authors. These tools may be used to produce interim versions of the non-canonical representations so that authors can see how their XML might later be rendered, to create documents in representations different than those supported by the RFC Editor, to possibly create documents that are not meant to be Internet-Drafts or RFCs, and to convert XML that has external information into XML that has that external information included.

The prep tool is expected to have clear error reporting, giving more context than just a line number. For example, the error messages should differentiate between errors in XML and those from the v3 format.

In v2, the grammar was specified as a DTD. In v3, the grammar is specified only as RELAX Next Generation (RNG). This means that tools need to work from the RNG, not from a DTD. Some of the features of the v3 grammar cannot be specified as a DTD.

B.1. Including External Text with XInclude

All tools for the v3 format are expected to support XInclude [[XInclude](#)]. XInclude specifies a processing model and syntax for general-purpose inclusion of information that is either on the Internet or local to the user's computer.

In the v3 syntax, XInclude is expressed as the `<xi:include>` element. To use this element, you need to include the "xi" namespace in the `<rfc>` element; that is, you need to specify

```
xmlns:xi="http://www.w3.org/2001/XInclude"
```

as one of the attributes in the `<rfc>` element.

The most common way to use `<xi:include>` is to pull in references that are already formed as XML. Currently, this can be done from `xml2rfc.tools.ietf.org`, but later this is expected to be from the RFC Editor. For example, if a document has three normative references, all RFCs, the document might contain:


```
<references>
  <xi:include href="http://xml2rfc.tools.ietf.org/public/rfc/
    bibxml/reference.RFC.2119.xml"/>
  <xi:include href="http://xml2rfc.tools.ietf.org/public/rfc/
    bibxml/reference.RFC.4869.xml"/>
  <xi:include href="http://xml2rfc.tools.ietf.org/public/rfc/
    bibxml/reference.RFC.7169.xml"/>
</references>
```

`<xi:include>` can be used anywhere an XML element could be used (but not where free text is used). For example, if three Internet-Drafts are all including a particular paragraph or section verbatim, that text can be kept either in a file or somewhere on the web and can be included with `<xi:include>`. An example of pulling something from the local disk would be:

```
<x:include href="file://home/chris/ietf/drafts/commoncontext.xml"/>
```

In general, XInclude should be used instead of ENTITY references and XML Processing Instructions (PIs) that allow external inclusions.

B.2. Anchors and IDs

People writing and reading Internet-Drafts and RFCs often want to make reference to specific locations in those documents. In the case of RFC authors, it is common to want to reference another part of their document, such as "see [Section 3.2](#) of this document." Readers, on the other hand, want to reference parts of documents that they didn't write, such as "see [Section 3.2 of RFC 6949](#)." The XML vocabulary in this document attempts to support both sets of people.

Authors can leave anchors in a document that can later be used for references with the "anchor" attribute. Anchors can be included in the numerous elements. The author can then refer to that anchor in the "target" attribute of the `<xref>` element.

Readers can refer to any element that has an "anchor" attribute by that attribute. Note, however, that most of the time, elements won't have anchors. In the common case, the reader wants to refer to an element that does not have an "anchor" attribute, but that element has a "pn" attribute.

Processing tools add the "pn" attribute to many elements during processing. This attribute and its value are automatically generated by the tool if the attribute is not there; if the attribute is already there, the tool may replace the value.

B.2.1. Overlapping Values

In the HTML representation of this XML vocabulary, both anchors and "pn" attributes will be used in the "id" attributes of elements. Thus, there can be no overlap between the names entered in "anchor" attributes, in "slugifiedName" attributes, and those that are generated for the "pn" attributes. Also, there are some values for the "anchor" values that are reserved for sections, and those sections can only have those anchor values.

The following rules prevent this overlap:

- o "pn" for regular sections always has the format "s-nnn", where "nnn" is the section number, or the appendix identifier (which starts with a letter). For example, this would be "s-2.1.3" for [Section 2.1.3](#) and "s-a" for [Appendix A](#). For the <abstract> element, it is always "s-abstract". For the <note> element, it is always "s-note-nnn", where "nnn" is a sequential value. For sections in the <boilerplate> element, it is always "s-boilerplate-nnn", where "nnn" is a sequential value.
- o "pn" for <references> elements has the format "s-nnn". It is important to note that "nnn" is a number, not letters, even though the <references> appear in the back. It is the number that is one higher than the highest top-level section number in <middle>. If there are two or more <references>, "nnn" will include a dot as if the <references> are a subsection of a section that is numbered one higher than the highest top-level section number in <middle>.
- o "pn" for <figure> elements always has the format "f-nnn", where "nnn" is the figure number. For example, this would be "f-5" for Figure 5.
- o "pn" for <ieref> elements always has the format "i-ttt-nnn", where "ttt" is the slugified item (plus a hyphen and the slugified subitem if there is a subitem), and "nnn" is the instance of that item/subitem pair. For example, this would be "i-foo-1" for "<ieref item='foo'>" and "i-foo-bar-1" for "<ieref item='foo' subitem='bar'>".
- o "pn" for <table> elements always has the format "t-nnn", where "nnn" is the table number. For example, this would be "t-5" for Table 5.
- o "pn" for all elements not listed above always has the format "p-nnn-mmm", where "nnn" is the section number and "mmm" is the relative position in the section. For example, this would be "p-2.1.3-7" for the seventh part number in [Section 2.1.3](#).

- o "slugifiedName" always has the format "n-ttt", where "ttt" is the text of the name after slugification. For example, this would be "n-protocol-overview" for the name "Protocol Overview". The actual conversions done in slugification will be specified at a later time.
- o Anchors must never overlap with any of the above. The easiest way to assure that is to not pick an anchor name that starts with a single letter followed by a hyphen. If an anchor does overlap with one of the types of names above, the processing tool will reject the document.

B.3. Attributes Controlled by the Prep Tool

Many elements in the v3 vocabulary have new attributes whose role is to hold values generated by the prep tool. These attributes can exist in documents that are input to the prep tool; however, any of these attributes might be added, removed, or changed by the prep tool. Thus, it is explicitly unsafe for a document author to include these attributes and expect that their values will survive processing by the prep tool.

The attributes that are controlled by the prep tool are:

- o The "pn" attribute in any element -- The number for this item within the section. The numbering is shared with other elements of a section. The "pn" attribute is added to many block-level elements inside sections.
- o <artwork> originalSrc -- This attribute is filled with the original value of the "src" attribute if that attribute is removed by the prep tool.
- o <figure> originalSrc -- This attribute is filled with the original value of the "src" attribute if that attribute is removed by the prep tool.
- o <name> "slugifiedName" attribute -- This attribute is filled with a "slugified" version of the text in the element. This attribute can be used in the output formats for elements that have both names and numbers.
- o <relref> "derivedLink" attribute -- This attribute is filled with the link that is derived from combining the URI from the reference and the relative part that is either a copy of the "relative" attribute or a section number derived from the "section" attribute.

- o `<rfc>` "expiresDate" attribute -- This attribute is filled with the date that an Internet-Draft expires. The date is in the format yyyy-mm-dd.
- o `<rfc>` "mode" attribute -- This attribute is filled with a string that indicates what mode the prep tool was in when it processed the XML, such as whether it was processing a file to become an Internet-Draft or an RFC.
- o `<rfc>` "scripts" attribute -- This attribute is filled with a list of scripts needed to render this document. The list is comma-separated, with no spaces allowed. The order is unimportant. The names come from [UAX24]. For example, if the document has Chinese characters in it, the value might be "Common, Latin, Han".
- o `<sourcecode>` "originalSrc" attribute -- This attribute is filled with the original value of the "src" attribute if that attribute is removed by the prep tool.
- o `<xref>` "derivedContent" attribute -- This attribute is filled in if there is no content in the `<xref>` element. The value for this attribute is based on the value in the "displayFormat" attribute. Examples of how this value is filled can be found in [Section 2.65.1](#).

In addition, note that the contents of the `<boilerplate>` element are controlled by the prep tool.

[Appendix C](#). RELAX NG Schema

The following is the RELAX NG schema for the v3 format.

```
namespace a = "http://relaxng.org/ns/compatibility/annotations/1.0"

# xml2rfc Version 3 grammar

rfc =
  element rfc {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute number { text }?,
    [ a:defaultValue = "" ] attribute obsoletes { text }?,
    [ a:defaultValue = "" ] attribute updates { text }?,
    attribute category { text }?,
    attribute mode { text }?,
    [ a:defaultValue = "false" ]
    attribute consensus { "no" | "yes" | "false" | "true" }?,
```



```
    attribute seriesNo { text }?,
    attribute ipr { text }?,
    attribute iprExtract { xsd:IDREF }?,
    [ a:defaultValue = "IETF" ]
    attribute submissionType {
      "IETF" | "IAB" | "IRTF" | "independent"
    }?,
    attribute docName { text }?,
    [ a:defaultValue = "false" ]
    attribute sortRefs { "true" | "false" }?,
    [ a:defaultValue = "true" ]
    attribute symRefs { "true" | "false" }?,
    [ a:defaultValue = "true" ]
    attribute tocInclude { "true" | "false" }?,
    [ a:defaultValue = "3" ] attribute tocDepth { text }?,
    attribute prepTime { text }?,
    [ a:defaultValue = "true" ]
    attribute indexInclude { "true" | "false" }?,
    attribute version { text }?,
    [ a:defaultValue = "Common, Latin" ] attribute scripts { text }?,
    attribute expiresDate { text }?,
    link*,
    front,
    middle,
    back?
  }
```

link =

```
  element link {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute href { text },
    attribute rel { text }?
  }
```

front =

```
  element front {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    title,
    seriesInfo*,
    author+,
    date?,
    area*,
    workgroup*,
    keyword*,
    abstract?,
    note*,
```



```
    boilerplate?
  }

title =
  element title {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute abbrev { text }?,
    attribute ascii { text }?,
    text
  }

author =
  element author {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute initials { text }?,
    attribute asciiInitials { text }?,
    attribute surname { text }?,
    attribute asciiSurname { text }?,
    attribute fullname { text }?,
    attribute role { "editor" }?,
    attribute asciiFullname { text }?,
    organization?,
    address?
  }

organization =
  element organization {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute abbrev { text }?,
    attribute ascii { text }?,
    text
  }

address =
  element address {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    postal?,
    phone?,
    facsimile?,
    email?,
    uri?
  }

postal =
```



```
    element postal {
      attribute xml:base { text }?,
      attribute xml:lang { text }?,
      ((city | code | country | region | street)* | postalLine+)
    }

street =
  element street {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute ascii { text }?,
    text
  }

city =
  element city {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute ascii { text }?,
    text
  }

region =
  element region {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute ascii { text }?,
    text
  }

code =
  element code {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute ascii { text }?,
    text
  }

country =
  element country {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute ascii { text }?,
    text
  }

postalLine =
  element postalLine {
```



```
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute ascii { text }?,
    text
  }

phone =
  element phone {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    text
  }

facsimile =
  element facsimile {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    text
  }

email =
  element email {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute ascii { text }?,
    text
  }

uri =
  element uri {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    text
  }

date =
  element date {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute day { text }?,
    attribute month { text }?,
    attribute year { text }?,
    empty
  }

area =
  element area {
    attribute xml:base { text }?,
```



```
    attribute xml:lang { text }?,
    text
  }
```

```
workgroup =
  element workgroup {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    text
  }
```

```
keyword =
  element keyword {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    text
  }
```

```
abstract =
  element abstract {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    (dl | ol | t | ul)+
  }
```

```
note =
  element note {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute title { text }?,
    attribute pn { text }?,
    [ a:defaultValue = "false" ]
    attribute removeInRFC { "true" | "false" }?,
    name?,
    (dl | ol | t | ul)+
  }
```

```
boilerplate =
  element boilerplate {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    section+
  }
```

```
middle =
  element middle {
```



```
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    section+
  }
```

section =

```
  element section {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    attribute title { text }?,
    [ a:defaultValue = "true" ]
    attribute numbered { "true" | "false" }?,
    [ a:defaultValue = "default" ]
    attribute toc { "include" | "exclude" | "default" }?,
    [ a:defaultValue = "false" ]
    attribute removeInRFC { "true" | "false" }?,
    name?,
    (artwork
     | aside
     | blockquote
     | dl
     | figure
     | iref
     | ol
     | sourcecode
     | t
     | table
     | texttable
     | ul)*,
    section*
  }
```

name =

```
  element name {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute slugifiedName { text }?,
    (text | cref | eref | relref | tt | xref)*
  }
```

t =

```
  element t {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
```



```
attribute hangText { text }?,
[ a:defaultValue = "false" ]
attribute keepWithNext { "false" | "true" }?,
[ a:defaultValue = "false" ]
attribute keepWithPrevious { "false" | "true" }?,
(text
| bcp14
| cref
| em
| eref
| iref
| \list
| relref
| spanx
| strong
| sub
| sup
| tt
| vspace
| xref)*
}

aside =
element aside {
attribute xml:base { text }?,
attribute xml:lang { text }?,
attribute anchor { xsd:ID }?,
attribute pn { text }?,
(artwork | dl | figure | iref | \list | ol | t | table | ul)*
}

blockquote =
element blockquote {
attribute xml:base { text }?,
attribute xml:lang { text }?,
attribute anchor { xsd:ID }?,
attribute pn { text }?,
attribute cite { text }?,
attribute quotedFrom { text }?,
((artwork | dl | figure | ol | sourcecode | t | ul)+
| (text
| bcp14
| cref
| em
| eref
| iref
| relref
| strong
```



```
    | sub
    | sup
    | tt
    | xref)+)
}

\list =
element list {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  [ a:defaultValue = "empty" ] attribute style { text }?,
  attribute hangIndent { text }?,
  attribute counter { text }?,
  attribute pn { text }?,
  t+
}

ol =
element ol {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  [ a:defaultValue = "1" ] attribute type { text }?,
  [ a:defaultValue = "1" ] attribute start { text }?,
  attribute group { text }?,
  [ a:defaultValue = "normal" ]
  attribute spacing { "normal" | "compact" }?,
  attribute pn { text }?,
  li+
}

ul =
element ul {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  [ a:defaultValue = "normal" ]
  attribute spacing { "normal" | "compact" }?,
  ([ a:defaultValue = "false" ]
  attribute empty { "false" | "true" },
  attribute pn { text }?)?,
  li+
}

li =
element li {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
```



```
attribute anchor { xsd:ID }?,
attribute pn { text }?,
((artwork | blockquote | dl | figure | ol | sourcecode | t | ul)+
 | (text
   | bcp14
   | cref
   | em
   | eref
   | iref
   | relref
   | strong
   | sub
   | sup
   | tt
   | xref)+)
}

dl =
element dl {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  [ a:defaultValue = "normal" ]
  attribute spacing { "normal" | "compact" }?,
  [ a:defaultValue = "true" ]
  attribute newline { "false" | "true" }?,
  [ a:defaultValue = "0" ] attribute indent { text }?,
  attribute pn { text }?,
  (dt, dd)+
}

dt =
element dt {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  attribute pn { text }?,
  (text
   | bcp14
   | cref
   | em
   | eref
   | iref
   | relref
   | strong
   | sub
   | sup
   | tt
```



```
    | xref)*  
  }
```

dd =

```
element dd {  
  attribute xml:base { text }?,  
  attribute xml:lang { text }?,  
  attribute anchor { xsd:ID }?,  
  attribute pn { text }?,  
  ((artwork | dl | figure | ol | sourcecode | t | ul)+  
  | (text  
    | bcp14  
    | cref  
    | em  
    | eref  
    | iref  
    | relref  
    | strong  
    | sub  
    | sup  
    | tt  
    | xref)+)  
}
```

xref =

```
element xref {  
  attribute xml:base { text }?,  
  attribute xml:lang { text }?,  
  attribute target { xsd:IDREF },  
  [ a:defaultValue = "false" ]  
  attribute pageno { "true" | "false" }?,  
  [ a:defaultValue = "default" ]  
  attribute format { "default" | "title" | "counter" | "none" }?,  
  attribute derivedContent { text }?,  
  text  
}
```

relref =

```
element relref {  
  attribute xml:base { text }?,  
  attribute xml:lang { text }?,  
  attribute target { xsd:IDREF },  
  [ a:defaultValue = "of" ]  
  attribute displayFormat { "of" | "comma" | "parens" | "bare" }?,  
  attribute section { text },  
  attribute relative { text }?,  
  attribute derivedLink { text }?,  
  text
```



```
}
```

```
eref =
```

```
  element eref {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute target { text },  
    text  
  }
```

```
iref =
```

```
  element iref {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute item { text },  
    [ a:defaultValue = "" ] attribute subitem { text }?,  
    [ a:defaultValue = "false" ]  
    attribute primary { "true" | "false" }?,  
    attribute pn { text }?,  
    empty  
  }
```

```
cref =
```

```
  element cref {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute anchor { xsd:ID }?,  
    attribute source { text }?,  
    [ a:defaultValue = "true" ]  
    attribute display { "true" | "false" }?,  
    (text | em | eref | relref | strong | sub | sup | tt | xref)*  
  }
```

```
tt =
```

```
  element tt {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    (text  
    | bcp14  
    | cref  
    | em  
    | eref  
    | iref  
    | relref  
    | strong  
    | sub  
    | sup  
    | xref)*  
  }
```



```
}
```

```
strong =
```

```
  element strong {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text
     | bcp14
     | cref
     | em
     | eref
     | iref
     | relref
     | sub
     | sup
     | tt
     | xref)*
  }
```

```
em =
```

```
  element em {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text
     | bcp14
     | cref
     | eref
     | iref
     | relref
     | strong
     | sub
     | sup
     | tt
     | xref)*
  }
```

```
sub =
```

```
  element sub {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text
     | bcp14
     | cref
     | em
     | eref
     | iref
     | relref
     | strong
```



```
    | tt
    | xref)*
}
```

sup =

```
element sup {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  (text
  | bcp14
  | cref
  | em
  | eref
  | iref
  | relref
  | strong
  | tt
  | xref)*
}
```

spanx =

```
element spanx {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  [ a:defaultValue = "preserve" ]
  attribute xml:space { "default" | "preserve" }?,
  [ a:defaultValue = "emph" ] attribute style { text }?,
  text
}
```

vspace =

```
element vspace {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  [ a:defaultValue = "0" ] attribute blankLines { text }?,
  empty
}
```

figure =

```
element figure {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  attribute pn { text }?,
  [ a:defaultValue = "" ] attribute title { text }?,
  [ a:defaultValue = "false" ]
  attribute suppress-title { "true" | "false" }?,
  attribute src { text }?,
```



```
    attribute originalSrc { text }?,
    [ a:defaultValue = "left" ]
    attribute align { "left" | "center" | "right" }?,
    [ a:defaultValue = "" ] attribute alt { text }?,
    [ a:defaultValue = "" ] attribute width { text }?,
    [ a:defaultValue = "" ] attribute height { text }?,
    name?,
    iref*,
    preamble?,
    (artwork | sourcecode)+,
    postamble?
}

table =
  element table {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    [ a:defaultValue = "center" ]
    attribute align { "left" | "center" | "right" }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    name?,
    iref*,
    thead?,
    tbody+,
    tfoot?
  }

preamble =
  element preamble {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text
     | bcp14
     | cref
     | em
     |eref
     | iref
     | relref
     | spanx
     | strong
     | sub
     | sup
     | tt
     | xref)*
  }

artwork =
```



```
element artwork {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  attribute pn { text }?,
  attribute xml:space { text }?,
  [ a:defaultValue = "" ] attribute name { text }?,
  [ a:defaultValue = "" ] attribute type { text }?,
  attribute src { text }?,
  [ a:defaultValue = "left" ]
  attribute align { "left" | "center" | "right" }?,
  [ a:defaultValue = "" ] attribute alt { text }?,
  [ a:defaultValue = "" ] attribute width { text }?,
  [ a:defaultValue = "" ] attribute height { text }?,
  attribute originalSrc { text }?,
  (text* | svg)
}
```

```
# TODO: replace with link to RSE site, or provide an inline version
include "svg.rnc"
```

```
sourcecode =
```

```
element sourcecode {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  attribute pn { text }?,
  [ a:defaultValue = "" ] attribute name { text }?,
  [ a:defaultValue = "" ] attribute type { text }?,
  attribute src { text }?,
  attribute originalSrc { text }?,
  text
}
```

```
thead =
```

```
element thead {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  tr+
}
```

```
tbody =
```

```
element tbody {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  tr+
}
```



```
tfoot =
  element tfoot {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    tr+
  }

tr =
  element tr {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    (td | th)+
  }

td =
  element td {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    [ a:defaultValue = "0" ] attribute colspan { text }?,
    [ a:defaultValue = "0" ] attribute rowspan { text }?,
    [ a:defaultValue = "left" ]
    attribute align { "left" | "center" | "right" }?,
    ((artwork | dl | figure | ol | sourcecode | t | ul)+
    | (text
      | bcp14
      | cref
      | em
      | eref
      | iref
      | relref
      | strong
      | sub
      | sup
      | tt
      | xref)*)
  }

th =
  element th {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    [ a:defaultValue = "0" ] attribute colspan { text }?,
    [ a:defaultValue = "0" ] attribute rowspan { text }?,
    [ a:defaultValue = "left" ]
```



```
attribute align { "left" | "center" | "right" }?,
((artwork | dl | figure | ol | sourcecode | t | ul)+
 | (text
   | bcp14
   | cref
   | em
   | eref
   | iref
   | relref
   | strong
   | sub
   | sup
   | tt
   | xref)*)
}

postamble =
element postamble {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  (text | cref | eref | iref | spanx | xref)*
}

texttable =
element texttable {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  [ a:defaultValue = "" ] attribute title { text }?,
  [ a:defaultValue = "false" ]
  attribute suppress-title { "true" | "false" }?,
  [ a:defaultValue = "center" ]
  attribute align { "left" | "center" | "right" }?,
  [ a:defaultValue = "full" ]
  attribute style { "all" | "none" | "headers" | "full" }?,
  name?,
  preamble?,
  ttcoll+,
  c*,
  postamble?
}

ttcoll =
element ttcoll {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute width { text }?,
  [ a:defaultValue = "left" ]
```



```
    attribute align { "left" | "center" | "right" }?,
    (cref | eref | iref | xref | text)*
  }

c =
element c {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  (text | cref | eref | iref | spanx | xref)*
}

bcp14 =
element bcp14 {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  text
}

back =
element back {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  displayreference*,
  references*,
  section*
}

displayreference =
element displayreference {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute target { xsd:IDREF },
  attribute to { text }
}

references =
element references {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute pn { text }?,
  attribute anchor { xsd:ID }?,
  attribute title { text }?,
  name?,
  (reference | referencegroup)*
}

reference =
element reference {
```



```
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID },
    attribute target { text }?,
    [ a:defaultValue = "true" ]
    attribute quoteTitle { "true" | "false" }?,
    front,
    (annotation | format | refcontent | seriesInfo)*
  }
```

referencegroup =

```
  element referencegroup {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID },
    reference+
  }
```

seriesInfo =

```
  element seriesInfo {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute name { text },
    attribute value { text },
    attribute asciiName { text }?,
    attribute asciiValue { text }?,
    attribute status { text }?,
    [ a:defaultValue = "IETF" ]
    attribute stream { "IETF" | "IAB" | "IRTF" | "independent" }?,
    empty
  }
```

format =

```
  element format {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute target { text }?,
    attribute type { text },
    attribute octets { text }?,
    empty
  }
```

annotation =

```
  element annotation {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text
    | bcp14
```



```

    | cref
    | em
    | eref
    | iref
    | relref
    | spanx
    | strong
    | sub
    | sup
    | tt
    | xref)*
}

refcontent =
  element refcontent {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text | bcp14 | em | strong | sub | sup | tt)*
  }
start |= rfc

```

[Appendix D](#). Schema Differences from v2

The following is a non-normative comparison of the v3 format to the v2 format. A "-" indicates lines removed from the v2 schema, and a "+" indicates lines added to the v3 schema.

```

namespace a =
  "http://relaxng.org/ns/compatibility/annotations/1.0"

+ # xml2rfc Version 3 grammar
rfc =
  element rfc {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
    attribute number { text }?,
    [ a:defaultValue = "" ] attribute obsoletes { text }?,
    [ a:defaultValue = "" ] attribute updates { text }?,
-   attribute category { "std" | "bcp" | "info" | "exp" |
- "historic" }?,
-   attribute consensus { "no" | "yes" }?,
+   attribute category { text }?,
+   attribute mode { text }?,
+   [ a:defaultValue = "false" ]
+   attribute consensus { "no" | "yes" | "false" | "true" }?,
    attribute seriesNo { text }?,

```



```
-   attribute ipr {
-     "full2026"
-     | "noDerivativeWorks2026"
-     | "none"
-     | "full13667"
-     | "noModification3667"
-     | "noDerivatives3667"
-     | "full13978"
-     | "noModification3978"
-     | "noDerivatives3978"
-     | "trust200811"
-     | "noModificationTrust200811"
-     | "noDerivativesTrust200811"
-     | "trust200902"
-     | "noModificationTrust200902"
-     | "noDerivativesTrust200902"
-     | "pre5378Trust200902"
-   }?,
+   attribute ipr { text }?,
+   attribute iprExtract { xsd:IDREF }?,
+   [ a:defaultValue = "IETF" ]
+   attribute submissionType {
+     "IETF" | "IAB" | "IRTF" | "independent"
+   }?,
+   attribute docName { text }?,
-   [ a:defaultValue = "en" ] attribute xml:lang { text }?,
+   [ a:defaultValue = "false" ]
+   attribute sortRefs { "true" | "false" }?,
+   [ a:defaultValue = "true" ]
+   attribute symRefs { "true" | "false" }?,
+   [ a:defaultValue = "true" ]
+   attribute tocInclude { "true" | "false" }?,
+   [ a:defaultValue = "3" ] attribute tocDepth { text }?,
+   attribute prepTime { text }?,
+   [ a:defaultValue = "true" ]
+   attribute indexInclude { "true" | "false" }?,
+   attribute version { text }?,
+   [ a:defaultValue = "Common, Latin" ] attribute scripts { text
+ }?,
+   attribute expiresDate { text }?,
+   link*,
+   front,
+   middle,
+   back?
+ }
+ link =
+ element link {
+   attribute xml:base { text }?,
```



```
+   attribute xml:lang { text }?,
+   attribute href { text },
+   attribute rel { text }?
+ }
front =
  element front {
-   title, author+, date, area*, workgroup*, keyword*, abstract?,
- note*
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   title,
+   seriesInfo*,
+   author+,
+   date?,
+   area*,
+   workgroup*,
+   keyword*,
+   abstract?,
+   note*,
+   boilerplate?
  }
title =
  element title {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute abbrev { text }?,
+   attribute ascii { text }?,
  text
  }
author =
  element author {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute initials { text }?,
+   attribute asciiInitials { text }?,
+   attribute surname { text }?,
+   attribute asciiSurname { text }?,
+   attribute fullname { text }?,
+   attribute role { "editor" }?,
+   attribute asciiFullname { text }?,
  organization?,
  address?
  }
organization =
  element organization {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute abbrev { text }?,
```



```
+   attribute ascii { text }?,
+   text
+ }
+ address =
+   element address {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     postal?,
+     phone?,
+     facsimile?,
+     email?,
+     uri?
+   }
+ postal =
+   element postal {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     ((city | code | country | region | street)* | postalLine+)
+   }
+ street =
+   element street {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute ascii { text }?,
+     text
+   }
+ city =
+   element city {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute ascii { text }?,
+     text
+   }
+ region =
+   element region {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute ascii { text }?,
+     text
+   }
+ code =
+   element code {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute ascii { text }?,
+     text
+   }
+ country =
```



```
+ element country {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute ascii { text }?,
+   text
+ }
+ postalLine =
+ element postalLine {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute ascii { text }?,
+   text
+ }
+ phone =
+ element phone {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   text
+ }
+ facsimile =
+ element facsimile {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   text
+ }
+ email =
+ element email {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute ascii { text }?,
+   text
+ }
+ uri =
+ element uri {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   text
+ }
- address = element address { postal?, phone?, facsimile?, email?,
- uri? }
- postal = element postal { street+, (city | region | code |
- country)* }
- street = element street { text }
- city = element city { text }
- region = element region { text }
- code = element code { text }
- country = element country { text }
- phone = element phone { text }
```



```
- facsimile = element facsimile { text }
- email = element email { text }
- uri = element uri { text }
date =
  element date {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute day { text }?,
+   attribute month { text }?,
+   attribute year { text }?,
+   empty
  }
- area = element area { text }
- workgroup = element workgroup { text }
- keyword = element keyword { text }
- abstract = element abstract { t+ }
+ area =
+   element area {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   text
+   }
+ workgroup =
+   element workgroup {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   text
+   }
+ keyword =
+   element keyword {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   text
+   }
+ abstract =
+   element abstract {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   attribute pn { text }?,
+   (dl | ol | t | ul)+
+   }
note =
  element note {
-   attribute title { text },
-   t+
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
```



```
+   attribute title { text }?,
+   attribute pn { text }?,
+   [ a:defaultValue = "false" ]
+   attribute removeInRFC { "true" | "false" }?,
+   name?,
+   (dl | ol | t | ul)+
+ }
+ boilerplate =
+ element boilerplate {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   section+
+ }
+ middle =
+ element middle {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   section+
+ }
- middle = element middle { section+ }
section =
  element section {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
-   attribute title { text },
+   attribute pn { text }?,
+   attribute title { text }?,
+   [ a:defaultValue = "true" ]
+   attribute numbered { "true" | "false" }?,
+   [ a:defaultValue = "default" ]
+   attribute toc { "include" | "exclude" | "default" }?,
-   (t | figure | texttable | iref)*,
+   [ a:defaultValue = "false" ]
+   attribute removeInRFC { "true" | "false" }?,
+   name?,
+   (artwork
+   | aside
+   | blockquote
+   | dl
+   | figure
+   | iref
+   | ol
+   | sourcecode
+   | t
+   | table
+   | texttable
+   | ul)*,
```



```
        section*
    }
+ name =
+   element name {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute slugifiedName { text }?,
+     (text | cref | eref | relref | tt | xref)*
+   }
  t =
    element t {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     attribute hangText { text }?,
+     [ a:defaultValue = "false" ]
+     attribute keepWithNext { "false" | "true" }?,
+     [ a:defaultValue = "false" ]
+     attribute keepWithPrevious { "false" | "true" }?,
+     (text
-     | \list
-     | figure
-     | xref
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
-     | cref
+     | \list
+     | relref
+     | spanx
-     | vspace)*
+     | strong
+     | sub
+     | sup
+     | tt
+     | vspace
+     | xref)*
+   }
+ aside =
+   element aside {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     (artwork | dl | figure | iref | \list | ol | t | table | ul)*
```



```
+   }
+ blockquote =
+   element blockquote {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     attribute cite { text }?,
+     attribute quotedFrom { text }?,
+     ((artwork | dl | figure | ol | sourcecode | t | ul)+
+      | (text
+        | bcp14
+        | cref
+        | em
+        | eref
+        | iref
+        | relref
+        | strong
+        | sub
+        | sup
+        | tt
+        | xref)+)
+   }
+ \list =
+   element list {
+     - attribute style { text }?,
+     + attribute xml:base { text }?,
+     + attribute xml:lang { text }?,
+     + [ a:defaultValue = "empty" ] attribute style { text }?,
+     + attribute hangIndent { text }?,
+     + attribute counter { text }?,
+     + attribute pn { text }?,
+     + t+
+   }
+ ol =
+   element ol {
+     + attribute xml:base { text }?,
+     + attribute xml:lang { text }?,
+     + attribute anchor { xsd:ID }?,
+     + [ a:defaultValue = "1" ] attribute type { text }?,
+     + [ a:defaultValue = "1" ] attribute start { text }?,
+     + attribute group { text }?,
+     + [ a:defaultValue = "normal" ]
+     + attribute spacing { "normal" | "compact" }?,
+     + attribute pn { text }?,
+     + li+
+   }
+ ul =
```



```
+ element ul {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   [ a:defaultValue = "normal" ]
+   attribute spacing { "normal" | "compact" }?,
+   ([ a:defaultValue = "false" ]
+   attribute empty { "false" | "true" },
+   attribute pn { text }?)?,
+   li+
+ }
+ li =
+ element li {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   attribute pn { text }?,
+   ((artwork | blockquote | dl | figure | ol | sourcecode | t |
+ ul)+
+   | (text
+   | bcp14
+   | cref
+   | em
+   | eref
+   | iref
+   | relref
+   | strong
+   | sub
+   | sup
+   | tt
+   | xref)+)
+ }
+ dl =
+ element dl {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   [ a:defaultValue = "normal" ]
+   attribute spacing { "normal" | "compact" }?,
+   [ a:defaultValue = "true" ]
+   attribute newline { "false" | "true" }?,
+   [ a:defaultValue = "0" ] attribute indent { text }?,
+   attribute pn { text }?,
+   (dt, dd)+
+ }
+ dt =
+ element dt {
+   attribute xml:base { text }?,
```



```
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   attribute pn { text }?,
+   (text
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
+     | relref
+     | strong
+     | sub
+     | sup
+     | tt
+     | xref)*
+ }
+ dd =
+   element dd {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     ((artwork | dl | figure | ol | sourcecode | t | ul)+
+     | (text
+       | bcp14
+       | cref
+       | em
+       | eref
+       | iref
+       | relref
+       | strong
+       | sub
+       | sup
+       | tt
+       | xref)+)
+   }
+ xref =
+   element xref {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute target { xsd:IDREF },
+     - [ a:defaultValue = "false" ] attribute pageno { "true" |
+     - "false" }?,
+     + [ a:defaultValue = "false" ]
+     + attribute pageno { "true" | "false" }?,
+     + [ a:defaultValue = "default" ]
+     - attribute format { "counter" | "title" | "none" | "default"
+     + attribute format { "default" | "title" | "counter" | "none" }
```



```
+ }?,
+   attribute derivedContent { text }?,
+   text
+ }
+ relref =
+   element relref {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute target { xsd:IDREF },
+     [ a:defaultValue = "of" ]
+     attribute displayFormat { "of" | "comma" | "parens" | "bare"
+   }?,
+   attribute section { text },
+   attribute relative { text }?,
+   attribute derivedLink { text }?,
+   text
+ }
+   element eref {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute target { text },
+     text
+   }
+   element iref {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute item { text },
+     [ a:defaultValue = "" ] attribute subitem { text }?,
+     [ a:defaultValue = "false" ]
+     attribute primary { "true" | "false" }?,
+     attribute pn { text }?,
+     empty
+   }
+   element cref {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute source { text }?,
+     - text
+     + [ a:defaultValue = "true" ]
+     + attribute display { "true" | "false" }?,
+     + (text | em | eref | relref | strong | sub | sup | tt | xref)*
+   }
+   tt =
+   element tt {
```



```
+ attribute xml:base { text }?,
+ attribute xml:lang { text }?,
+ (text
+   | bcp14
+   | cref
+   | em
+   | eref
+   | iref
+   | relref
+   | strong
+   | sub
+   | sup
+   | xref)*
+ }
+ strong =
+ element strong {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   (text
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
+     | relref
+     | sub
+     | sup
+     | tt
+     | xref)*
+   }
+ em =
+ element em {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   (text
+     | bcp14
+     | cref
+     | eref
+     | iref
+     | relref
+     | strong
+     | sub
+     | sup
+     | tt
+     | xref)*
+   }
+ sub =
+ element sub {
```



```
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   (text
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
+     | relref
+     | strong
+     | tt
+     | xref)*
+   }
+ sup =
+   element sup {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     (text
+       | bcp14
+       | cref
+       | em
+       | eref
+       | iref
+       | relref
+       | strong
+       | tt
+       | xref)*
+     }
+ spanx =
+   element spanx {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     [ a:defaultValue = "preserve" ]
+     attribute xml:space { "default" | "preserve" }?,
+     [ a:defaultValue = "emph" ] attribute style { text }?,
+     text
+   }
+ vspace =
+   element vspace {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     [ a:defaultValue = "0" ] attribute blankLines { text }?,
+     empty
+   }
+ figure =
+   element figure {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
```



```
    attribute anchor { xsd:ID }?,
+   attribute pn { text }?,
    [ a:defaultValue = "" ] attribute title { text }?,
    [ a:defaultValue = "false" ]
    attribute suppress-title { "true" | "false" }?,
    attribute src { text }?,
+   attribute originalSrc { text }?,
    [ a:defaultValue = "left" ]
    attribute align { "left" | "center" | "right" }?,
    [ a:defaultValue = "" ] attribute alt { text }?,
    [ a:defaultValue = "" ] attribute width { text }?,
    [ a:defaultValue = "" ] attribute height { text }?,
+   name?,
    iref*,
    preamble?,
-   artwork,
+   (artwork | sourcecode)+,
    postamble?
  }
+ table =
+   element table {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     [ a:defaultValue = "center" ]
+     attribute align { "left" | "center" | "right" }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     name?,
+     iref*,
+     thead?,
+     tbody+,
+     tfoot?
+   }
  preamble =
-   element preamble { (text | xref | eref | iref | cref | spanx)* }
+   element preamble {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     (text
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
+     | relref
+     | spanx
+     | strong
+     | sub
```



```
+      | sup
+      | tt
+      | xref)*
+    }
  artwork =
    element artwork {
-     [ a:defaultValue = "preserve" ]
-     attribute xml:space { "default" | "preserve" }?,
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     attribute xml:space { text }?,
+     [ a:defaultValue = "" ] attribute name { text }?,
+     [ a:defaultValue = "" ] attribute type { text }?,
+     attribute src { text }?,
+     [ a:defaultValue = "left" ]
+     attribute align { "left" | "center" | "right" }?,
+     [ a:defaultValue = "" ] attribute alt { text }?,
+     [ a:defaultValue = "" ] attribute width { text }?,
+     [ a:defaultValue = "" ] attribute height { text }?,
-     text*
+     attribute originalSrc { text }?,
+     (text* | svg)
+   }
+ # TODO: replace with link to RSE site, or provide an inline
+ version
+ include "svg.rnc"
+ sourcecode =
+   element sourcecode {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     [ a:defaultValue = "" ] attribute name { text }?,
+     [ a:defaultValue = "" ] attribute type { text }?,
+     attribute src { text }?,
+     attribute originalSrc { text }?,
+     text
+   }
+ thead =
+   element thead {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     tr+
+   }
+ tbody =
```



```
+ element tbody {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   tr+
+ }
+ tfoot =
+ element tfoot {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   tr+
+ }
+ tr =
+ element tr {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   (td | th)+
+ }
+ td =
+ element td {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   [ a:defaultValue = "0" ] attribute colspan { text }?,
+   [ a:defaultValue = "0" ] attribute rowspan { text }?,
+   [ a:defaultValue = "left" ]
+   attribute align { "left" | "center" | "right" }?,
+   ((artwork | dl | figure | ol | sourcecode | t | ul)+
+   | (text
+   | bcp14
+   | cref
+   | em
+   | eref
+   | iref
+   | relref
+   | strong
+   | sub
+   | sup
+   | tt
+   | xref)*)
+ }
+ th =
+ element th {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
```



```

+   [ a:defaultValue = "0" ] attribute colspan { text }?,
+   [ a:defaultValue = "0" ] attribute rowspan { text }?,
+   [ a:defaultValue = "left" ]
+   attribute align { "left" | "center" | "right" }?,
+   ((artwork | dl | figure | ol | sourcecode | t | ul)+
+   | (text
+   | bcp14
+   | cref
+   | em
+   | eref
+   | iref
+   | relref
+   | strong
+   | sub
+   | sup
+   | tt
+   | xref)*)
  }
  postamble =
-   element postamble { (text | xref | eref | iref | cref | spanx)*
+   element postamble {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     (text | cref | eref | iref | spanx | xref)*
  }
  texttable =
    element texttable {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
      attribute anchor { xsd:ID }?,
      [ a:defaultValue = "" ] attribute title { text }?,
      [ a:defaultValue = "false" ]
      attribute suppress-title { "true" | "false" }?,
      [ a:defaultValue = "center" ]
      attribute align { "left" | "center" | "right" }?,
      [ a:defaultValue = "full" ]
      attribute style { "all" | "none" | "headers" | "full" }?,
+     name?,
      preamble?,
      ttcoll+,
      c*,
      postamble?
    }
  ttcoll =
    element ttcoll {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
      attribute width { text }?,

```



```
    [ a:defaultValue = "left" ]
    attribute align { "left" | "center" | "right" }?,
+   (cref | eref | iref | xref | text)*
+ }
+ c =
+ element c {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   (text | cref | eref | iref | spanx | xref)*
+ }
+ bcp14 =
+ element bcp14 {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   text
+ }
- c = element c { (text | xref | eref | iref | cref | spanx)* }
- back = element back { references*, section* }
+ back =
+ element back {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   displayreference*,
+   references*,
+   section*
+ }
+ displayreference =
+ element displayreference {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute target { xsd:IDREF },
+   attribute to { text }
+ }
references =
  element references {
-   [ a:defaultValue = "References" ] attribute title { text }?,
-   reference+
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute pn { text }?,
+   attribute anchor { xsd:ID }?,
+   attribute title { text }?,
+   name?,
+   (reference | referencegroup)*
  }
reference =
  element reference {
+   attribute xml:base { text }?,
```



```
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID },
+   attribute target { text }?,
+   [ a:defaultValue = "true" ]
+   attribute quoteTitle { "true" | "false" }?,
+   front,
-   seriesInfo*,
-   format*,
-   annotation*
+   (annotation | format | refcontent | seriesInfo)*
+ }
+ referencegroup =
+   element referencegroup {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID },
+     reference+
+   }
+ seriesInfo =
+   element seriesInfo {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute name { text },
+     attribute value { text },
+     attribute asciiName { text }?,
+     attribute asciiValue { text }?,
+     attribute status { text }?,
+     [ a:defaultValue = "IETF" ]
+     attribute stream { "IETF" | "IAB" | "IRTF" | "independent" }?,
+     empty
+   }
+ format =
+   element format {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute target { text }?,
+     attribute type { text },
+     attribute octets { text }?,
+     empty
+   }
+ annotation =
-   element annotation { (text | xref | eref | iref | cref |
- spanx)* }
- start = rfc
+   element annotation {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     (text
```



```

+   | bcp14
+   | cref
+   | em
+   | eref
+   | iref
+   | relref
+   | spanx
+   | strong
+   | sub
+   | sup
+   | tt
+   | xref)*
+ }
+ refcontent =
+   element refcontent {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     (text | bcp14 | em | strong | sub | sup | tt)*
+   }
+ start |= rfc

```

[Appendix E](#). IAB Members at the Time of Approval

The IAB members at the time this memo was approved were (in alphabetical order):

[[A list will go here just before publication as an RFC]]

[Appendix F](#). Acknowledgments

Thanks to everybody who reviewed this document and provided feedback and/or specification text. Thanks especially go to Julian Reschke for editing [[RFC7749](#)] and those who provided feedback on that document.

We also thank Marshall T. Rose for both the original design and the reference implementation of the "xml2rfc" processor.

Index

A

- abbrev attribute
 - in organization element 41
 - in title element 70
- abstract element 11, 98
- anchor attribute 12
- inside front 33

- address element 12, 98
 - inside author 18
- align attribute
 - in artwork element 15
 - in figure element 32
 - in table element 64
 - in td element 66
 - in texttable element 79
 - in th element 68
 - in ttable element 81
- alt attribute
 - in artwork element 15
 - in figure element 32
- anchor attribute
 - in abstract element 12
 - in artwork element 15
 - in aside element 17
 - in blockquote element 21
 - in cref element 23
 - in dd element 26
 - in dl element 27
 - in dt element 29
 - in figure element 32
 - in li element 36
 - in ol element 39
 - in reference element 44
 - in referencegroup element 45
 - in references element 45
 - in section element 54
 - in sourcecode element 58
 - in t element 63
 - in table element 65
 - in tbody element 65
 - in td element 66
 - in texttable element 80
 - in tfoot element 67
 - in th element 69
 - in thead element 69
 - in tr element 70
 - in ul element 71
- annotation element 12, 98
 - inside reference 44
- application/rfc+xml Media Type 83
- area element 13, 98
 - inside front 33
- artwork element 13, 98
 - align attribute 15
 - alt attribute 15

- anchor attribute 15
- height attribute 15
- inside aside 17
- inside blockquote 20
- inside dd 25
- inside figure 32
- inside li 35
- inside section 53
- inside td 65
- inside th 67
- name attribute 15
- src attribute 15
- type attribute 16
- width attribute 16
- xml:space attribute 17
- ascii attribute
 - in city element 22
 - in code element 22
 - in country element 22
 - in email element 30
 - in organization element 41
 - in postalLine element 42
 - in region element 46
 - in street element 59
 - in title element 70
- asciiFullname attribute
 - in author element 18
- asciiInitials attribute
 - in author element 18
- asciiName attribute
 - in seriesInfo element 55
- asciiSurname attribute
 - in author element 18
- asciiValue attribute
 - in seriesInfo element 55
- aside element 17, 98
 - anchor attribute 17
 - inside section 53
- Attributes
 - abbrev 41, 70
 - align 15, 32, 64, 66, 68, 79, 81
 - alt 15, 32
 - anchor 12, 15, 17, 21, 23, 26-27, 29, 32, 36, 39, 44-45, 54, 58, 63, 65-67, 69-71, 80
 - ascii 22, 30, 41-42, 46, 59, 70
 - asciiFullname 18
 - asciiInitials 18
 - asciiName 55

asciiSurname 18
asciiValue 55
blankLines 81
category 50
cite 21
colspan 67, 69
consensus 50
counter 76
day 24
display 23
displayFormat 47
docName 50
empty 71
format 73
fullname 18
group 39
hangIndent 77
hangText 63
height 15, 32
href 37
indent 27
indexInclude 50
initials 18
ipr 51
iprExtract 51
item 34
keepWithNext 63
keepWithPrevious 63
month 24
name 15, 56, 58
newline 27
number 51
numbered 54
obsoletes 51
octets 76
pageno 74
prepTime 51
primary 34
quotedFrom 21
quoteTitle 44
rel 37
relative 49
removeInRFC 39, 54
role 19
rowspan 67, 69
section 49
seriesNo 51
sortRefs 51

- source 24
- spacing 28, 39, 72
- src 15, 32, 58
- start 40
- status 56
- stream 56
- style 77, 79-80
- subitem 35
- submissionType 52
- suppress-title 32, 80
- surname 19
- symRefs 52
- target 26, 31, 44, 49, 75-76
- title 33, 39, 46, 54, 80
- to 27
- toc 54
- tocDepth 52
- tocInclude 52
- type 16, 40, 58, 76
- updates 52
- value 57
- version 53
- width 16, 33, 81
- xml:space 17, 79
- year 25
- author element 17, 98
 - asciiFullname attribute 18
 - asciiInitials attribute 18
 - asciiSurname attribute 18
 - fullname attribute 18
 - initials attribute 18
 - inside front 33
 - role attribute 19
 - surname attribute 19

B

- back element 19, 98
 - inside rfc 50
- [bcp14](#) element 19, 98
 - inside annotation 12
 - inside blockquote 20
 - inside c 75
 - inside dd 25
 - inside dt 28
 - inside em 29
 - inside li 36
 - inside postamble 77
 - inside preamble 78

- inside refcontent 43
- inside strong 60
- inside sub 61
- inside sup 61
- inside t 62
- inside td 66
- inside th 68
- inside tt 71
- blankLines attribute
 - in vspace element 81
- blockquote element 20, 98
 - anchor attribute 21
 - cite attribute 21
 - inside li 35
 - inside section 53
 - quotedFrom attribute 21
- boilerplate element 21, 98
 - inside front 34

C

- c element 75, 98
 - inside texttable 79
- category attribute
 - in rfc element 50
- cite attribute
 - in blockquote element 21
- city element 22, 98
 - ascii attribute 22
 - inside postal 42
- code element 22, 98
 - ascii attribute 22
 - inside postal 42
- colspan attribute
 - in td element 67
 - in th element 69
- consensus attribute
 - in rfc element 50
- counter attribute
 - in list element 76
- country element 22, 98
 - ascii attribute 22
 - inside postal 42
- cref element 22, 98
 - anchor attribute 23
 - display attribute 23
 - inside annotation 12
 - inside blockquote 20
 - inside c 75

- inside dd 25
- inside dt 28
- inside em 29
- inside li 36
- inside name 38
- inside postamble 77
- inside preamble 78
- inside strong 60
- inside sub 61
- inside sup 61
- inside t 62
- inside td 66
- inside th 68
- inside tt 71
- inside ttc01 80
- source attribute 24

D

- date element 24, 98
 - day attribute 24
 - inside front 33
 - month attribute 24
 - year attribute 25
- day attribute
 - in date element 24
- dd element 25, 98
 - anchor attribute 26
 - inside dl 27
- display attribute
 - in cref element 23
- displayFormat attribute
 - in relref element 47
- displayreference element 26, 98
 - inside back 19
 - target attribute 26
 - to attribute 27
- dl element 27, 98
 - anchor attribute 27
 - indent attribute 27
 - inside abstract 11
 - inside aside 17
 - inside blockquote 20
 - inside dd 25
 - inside li 35
 - inside note 38
 - inside section 53
 - inside td 65
 - inside th 67

- newline attribute 27
- spacing attribute 28
- docName attribute
 - in rfc element 50
- dt element 28, 98
 - anchor attribute 29
 - inside dl 27

E

Elements

- abstract 11, 33
- address 12, 18
- annotation 12, 44
- area 13, 33
- artwork 13, 17, 20, 25, 32, 35, 53, 65, 67
- aside 17, 53
- author 17, 33
- back 19, 50
- [bcp14](#) 12, 19-20, 25, 28-29, 36, 43, 60-62, 66, 68, 71, 75, 77-78
- blockquote 20, 35, 53
- boilerplate 21, 34
- c 75, 79
- city 22, 42
- code 22, 42
- country 22, 42
- cref 12, 20, 22, 25, 28-29, 36, 38, 60-62, 66, 68, 71, 75, 77-78, 80
- date 24, 33
- dd 25, 27
- displayreference 19, 26
- dl 11, 17, 20, 25, 27, 35, 38, 53, 65, 67
- dt 27-28
- em 12, 21, 23, 25, 28-29, 36, 43, 60-62, 66, 68, 71, 75, 77-78
- email 12, 30
- eref 12, 21, 23, 25, 28-30, 36, 38, 60-62, 66, 68, 71, 75, 77-78, 80
- facsimile 12, 76
- figure 17, 20, 25, 31, 35, 53, 65, 67
- format 44, 76
- front 33, 44, 50
- iref 13, 17, 21, 26, 28-29, 31, 34, 36, 53, 60-62, 64, 66, 68, 71, 75, 77-78, 80
- keyword 33, 35
- li 35, 39, 71
- link 36, 50
- list 17, 62, 76
- middle 37, 50

name 31, 37-38, 45, 53, 64, 79
note 33, 38
ol 11, 17, 20, 25, 35, 38-39, 53, 65, 68
organization 18, 41
phone 12, 41
postal 12, 42
postalline 42
postamble 32, 77, 79
preamble 31, 78-79
refcontent 43-44
reference 43, 45
referencegroup 44-45
references 19, 45
region 42, 46
relref 13, 21, 23, 26, 28-29, 36, 38, 46, 60-62, 66, 68, 71
rfc 49
section 19, 21, 37, 53-54
seriesInfo 33, 44, 55
sourcecode 20, 25, 32, 35, 53, 57, 65, 68
spanx 13, 62, 75, 77-78
street 42, 59
strong 13, 21, 23, 26, 28-29, 36, 43, 59, 61-62, 66, 68, 71,
75, 77-78
sub 13, 21, 23, 26, 28-29, 36, 43, 60, 63, 66, 68, 71, 75,
77-78
sup 13, 21, 23, 26, 28-29, 36, 43, 60-61, 63, 66, 68, 71, 75,
77-78
svg 14
t 11, 17, 20, 25, 35, 38, 53, 62, 65, 68, 76
table 17, 53, 64
tbody 64-65
td 65, 70
texttable 54, 79
tfoot 64, 67
th 67, 70
thead 64, 69
title 33, 69
tr 65, 67, 69-70
tt 13, 21, 23, 26, 29, 36, 38, 43, 60-63, 66, 68, 70, 75,
77-78
ttcol 79-80
ul 11, 17, 20, 25, 35, 38, 54, 65, 68, 71
uri 12, 72
vspace 63, 81
workgroup 33, 72
xref 13, 21, 23, 26, 29-30, 36, 38, 60-63, 66, 68, 71-72, 75,
77-78, 80
em element 29, 98

- inside annotation 12
- inside blockquote 21
- inside c 75
- inside cref 23
- inside dd 25
- inside dt 28
- inside li 36
- inside postamble 77
- inside preamble 78
- inside refcontent 43
- inside strong 60
- inside sub 61
- inside sup 62
- inside t 62
- inside td 66
- inside th 68
- inside tt 71
- email element 30, 98
 - ascii attribute 30
 - inside address 12
- empty attribute
 - in ul element 71
- eref element 30, 98
 - inside annotation 12
 - inside blockquote 21
 - inside c 75
 - inside cref 23
 - inside dd 25
 - inside dt 28
 - inside em 29
 - inside li 36
 - inside name 38
 - inside postamble 77
 - inside preamble 78
 - inside strong 60
 - inside sub 61
 - inside sup 62
 - inside t 62
 - inside td 66
 - inside th 68
 - inside tt 71
 - inside ttcoll 80
 - target attribute 31

F

- facsimile element 76, 98
 - inside address 12
- figure element 31, 98

- align attribute 32
- alt attribute 32
- anchor attribute 32
- height attribute 32
- inside aside 17
- inside blockquote 20
- inside dd 25
- inside li 35
- inside section 53
- inside td 65
- inside th 67
- src attribute 32
- suppress-title attribute 32
- title attribute 33
- width attribute 33
- format attribute
 - in xref element 73
- format element 76, 98
 - inside reference 44
 - octets attribute 76
 - target attribute 76
 - type attribute 76
- front element 33, 98
 - inside reference 44
 - inside rfc 50
- fullname attribute
 - in author element 18

G

- group attribute
 - in ol element 39

H

- hangIndent attribute
 - in list element 77
- hangText attribute
 - in t element 63
- height attribute
 - in artwork element 15
 - in figure element 32
- href attribute
 - in link element 37

I

- indent attribute
 - in dl element 27
- indexInclude attribute
 - in rfc element 50

initials attribute
 in author element 18

ipr attribute
 "*2026" 91
 "*3667" 91
 "*3978" 91
 "*trust200811" 91
 "*trust200902" 89
 "noDerivativesTrust200902" 90
 "noModificationTrust200902" 90
 "pre5378Trust200902" 90
 "trust200902" 90
 in rfc element 51

iprExtract attribute
 in rfc element 51

iref element 34, 98
 inside annotation 13
 inside aside 17
 inside blockquote 21
 inside c 75
 inside dd 26
 inside dt 28
 inside em 29
 inside figure 31
 inside li 36
 inside postamble 77
 inside preamble 78
 inside section 53
 inside strong 60
 inside sub 61
 inside sup 62
 inside t 62
 inside table 64
 inside td 66
 inside th 68
 inside tt 71
 inside ttcoll 80
 item attribute 34
 primary attribute 34
 subitem attribute 35

item attribute
 in iref element 34

K

keepWithNext attribute
 in t element 63

keepWithPrevious attribute
 in t element 63

- keyword element 35, 98
 - inside front 33

L

- li element 35, 98
 - anchor attribute 36
 - inside ol 39
 - inside ul 71
- link element 36, 98
 - href attribute 37
 - inside rfc 50
 - rel attribute 37
- list element 76, 98
 - counter attribute 76
 - hangIndent attribute 77
 - inside aside 17
 - inside t 62
 - style attribute 77

M

- Media Type
 - application/rfc+xml 83
- middle element 37, 98
 - inside rfc 50
- month attribute
 - in date element 24

N

- name attribute
 - in artwork element 15
 - in seriesInfo element 56
 - in sourcecode element 58
- name element 37, 98
 - inside figure 31
 - inside note 38
 - inside references 45
 - inside section 53
 - inside table 64
 - inside texttable 79
- newline attribute
 - in dl element 27
- note element 38, 98
 - inside front 33
 - removeInRFC attribute 39
 - title attribute 39
- number attribute
 - in rfc element 51
- numbered attribute

in section element 54

0

obsoletes attribute
in rfc element 51

octets attribute
in format element 76

ol element 39, 98
anchor attribute 39
group attribute 39
inside abstract 11
inside aside 17
inside blockquote 20
inside dd 25
inside li 35
inside note 38
inside section 53
inside td 65
inside th 68
spacing attribute 39
start attribute 40
type attribute 40

organization element 41, 98
abbrev attribute 41
ascii attribute 41
inside author 18

P

pageno attribute
in xref element 74

phone element 41, 98
inside address 12

postal element 42, 98
inside address 12

postalline element 42, 98
ascii attribute 42
inside postal 42

postamble element 77, 98
inside figure 32
inside texttable 79

preamble element 78, 98
inside figure 31
inside texttable 79

prepTime attribute
in rfc element 51

primary attribute
in iref element 34

Q

- quotedFrom attribute
 - in blockquote element 21
- quoteTitle attribute
 - in reference element 44

R

- refcontent element 43, 98
 - inside reference 44
- reference element 43, 98
 - anchor attribute 44
 - inside referencegroup 45
 - inside references 45
 - quoteTitle attribute 44
 - target attribute 44
- referencegroup element 44, 98
 - anchor attribute 45
 - inside references 45
- references element 45, 98
 - anchor attribute 45
 - inside back 19
 - title attribute 46
- region element 46, 98
 - ascii attribute 46
 - inside postal 42
- rel attribute
 - in link element 37
- relative attribute
 - in relref element 49
- relref element 46, 98
 - displayFormat attribute 47
 - inside annotation 13
 - inside blockquote 21
 - inside cref 23
 - inside dd 26
 - inside dt 28
 - inside em 29
 - inside li 36
 - inside name 38
 - inside strong 60
 - inside sub 61
 - inside sup 62
 - inside t 62
 - inside td 66
 - inside th 68
 - inside tt 71
 - relative attribute 49
 - section attribute 49

- target attribute 49
- removeInRFC attribute
 - in note element 39
 - in section element 54
- rfc element 49, 98
 - category attribute 50
 - consensus attribute 50
 - docName attribute 50
 - indexInclude attribute 50
 - ipr attribute 51
 - iprExtract attribute 51
 - number attribute 51
 - obsoletes attribute 51
 - prepTime attribute 51
 - seriesNo attribute 51
 - sortRefs attribute 51
 - submissionType attribute 52
 - symRefs attribute 52
 - tocDepth attribute 52
 - tocInclude attribute 52
 - updates attribute 52
 - version attribute 53
- role attribute
 - in author element 19
- rowspan attribute
 - in td element 67
 - in th element 69

S

- section attribute
 - in relref element 49
- section element 53, 98
 - anchor attribute 54
 - inside back 19
 - inside boilerplate 21
 - inside middle 37
 - inside section 54
 - numbered attribute 54
 - removeInRFC attribute 54
 - title attribute 54
 - toc attribute 54
- seriesInfo element 55, 98
 - asciiName attribute 55
 - asciiValue attribute 55
 - inside front 33
 - inside reference 44
 - name attribute 56
 - status attribute 56

- stream attribute 56
- value attribute 57
- seriesNo attribute
 - in rfc element 51
- sortRefs attribute
 - in rfc element 51
- source attribute
 - in cref element 24
- sourcecode element 57, 98
 - anchor attribute 58
 - inside blockquote 20
 - inside dd 25
 - inside figure 32
 - inside li 35
 - inside section 53
 - inside td 65
 - inside th 68
 - name attribute 58
 - src attribute 58
 - type attribute 58
- spacing attribute
 - in dl element 28
 - in ol element 39
 - in ul element 72
- spanx element 78, 98
 - inside annotation 13
 - inside c 75
 - inside postamble 77
 - inside preamble 78
 - inside t 62
 - style attribute 79
 - xml:space attribute 79
- src attribute
 - in artwork element 15
 - in figure element 32
 - in sourcecode element 58
- start attribute
 - in ol element 40
- status attribute
 - in seriesInfo element 56
- stream attribute
 - in seriesInfo element 56
- street element 59, 98
 - ascii attribute 59
 - inside postal 42
- strong element 59, 98
 - inside annotation 13
 - inside blockquote 21

- inside c 75
- inside cref 23
- inside dd 26
- inside dt 28
- inside em 29
- inside li 36
- inside postamble 77
- inside preamble 78
- inside refcontent 43
- inside sub 61
- inside sup 62
- inside t 62
- inside td 66
- inside th 68
- inside tt 71
- style attribute
 - in list element 77
 - in spanx element 79
 - in texttable element 80
- sub element 60, 98
 - inside annotation 13
 - inside blockquote 21
 - inside c 75
 - inside cref 23
 - inside dd 26
 - inside dt 28
 - inside em 29
 - inside li 36
 - inside postamble 77
 - inside preamble 78
 - inside refcontent 43
 - inside strong 60
 - inside t 63
 - inside td 66
 - inside th 68
 - inside tt 71
- subitem attribute
 - in iref element 35
- submissionType attribute
 - in rfc element 52
- sup element 61, 98
 - inside annotation 13
 - inside blockquote 21
 - inside c 75
 - inside cref 23
 - inside dd 26
 - inside dt 28
 - inside em 29

- inside li 36
- inside postamble 77
- inside preamble 78
- inside refcontent 43
- inside strong 60
- inside t 63
- inside td 66
- inside th 68
- inside tt 71
- suppress-title attribute
 - in figure element 32
 - in texttable element 80
- surname attribute
 - in author element 19
- svg element
 - inside artwork 14
- symRefs attribute
 - in rfc element 52

T

- t element 62, 98
 - anchor attribute 63
 - hangText attribute 63
 - inside abstract 11
 - inside aside 17
 - inside blockquote 20
 - inside dd 25
 - inside li 35
 - inside list 76
 - inside note 38
 - inside section 53
 - inside td 65
 - inside th 68
 - keepWithNext attribute 63
 - keepWithPrevious attribute 63
- table element 64, 98
 - align attribute 64
 - anchor attribute 65
 - inside aside 17
 - inside section 53
- target attribute
 - in displayreference element 26
 - in eref element 31
 - in format element 76
 - in reference element 44
 - in relref element 49
 - in xref element 75
- tbody element 65, 98

- anchor attribute 65
 - inside table 64
- td element 65, 98
 - align attribute 66
 - anchor attribute 66
 - colspan attribute 67
 - inside tr 70
 - rowspan attribute 67
- texttable element 79, 98
 - align attribute 79
 - anchor attribute 80
 - inside section 54
 - style attribute 80
 - suppress-title attribute 80
 - title attribute 80
- tfoot element 67, 98
 - anchor attribute 67
 - inside table 64
- th element 67, 98
 - align attribute 68
 - anchor attribute 69
 - colspan attribute 69
 - inside tr 70
 - rowspan attribute 69
- thead element 69, 98
 - anchor attribute 69
 - inside table 64
- title attribute
 - in figure element 33
 - in note element 39
 - in references element 46
 - in section element 54
 - in texttable element 80
- title element 69, 98
 - abbrev attribute 70
 - ascii attribute 70
 - inside front 33
- to attribute
 - in displayreference element 27
- toc attribute
 - in section element 54
- tocDepth attribute
 - in rfc element 52
- tocInclude attribute
 - in rfc element 52
- tr element 70, 98
 - anchor attribute 70
 - inside tbody 65

- inside tfoot 67
- inside thead 69
- tt element 70, 98
 - inside annotation 13
 - inside blockquote 21
 - inside c 75
 - inside cref 23
 - inside dd 26
 - inside dt 29
 - inside em 29
 - inside li 36
 - inside name 38
 - inside postamble 77
 - inside preamble 78
 - inside refcontent 43
 - inside strong 60
 - inside sub 61
 - inside sup 62
 - inside t 63
 - inside td 66
 - inside th 68
- ttcol element 80, 98
 - align attribute 81
 - inside texttable 79
 - width attribute 81
- type attribute
 - in artwork element 16
 - in format element 76
 - in ol element 40
 - in sourcecode element 58

U

- ul element 71, 98
 - anchor attribute 71
 - empty attribute 71
 - inside abstract 11
 - inside aside 17
 - inside blockquote 20
 - inside dd 25
 - inside li 35
 - inside note 38
 - inside section 54
 - inside td 65
 - inside th 68
 - spacing attribute 72
- updates attribute
 - in rfc element 52
- uri element 72, 98

inside address 12

V

value attribute
 in seriesInfo element 57
version attribute
 in rfc element 53
vspace element 81, 98
 blankLines attribute 81
 inside t 63

W

width attribute
 in artwork element 16
 in figure element 33
 in ttcoll element 81
workgroup element 72, 98
 inside front 33

X

xml:space attribute
 in artwork element 17
 in spanx element 79
xref element 72, 98
 format attribute 73
 inside annotation 13
 inside blockquote 21
 inside c 75
 inside cref 23
 inside dd 26
 inside dt 29
 inside em 30
 inside li 36
 inside name 38
 inside postamble 77
 inside preamble 78
 inside strong 60
 inside sub 61
 inside sup 62
 inside t 63
 inside td 66
 inside th 68
 inside tt 71
 inside ttcoll 80
 pageno attribute 74
 target attribute 75
xref formats
 counter 73

default 73
none 74
title 74

Y

year attribute
in date element 25

Author's Address

Paul Hoffman
ICANN

EMail: paul.hoffman@icann.org

