

Network Working Group
Internet-Draft
Obsoletes: [7991](#) (if approved)
Intended status: Informational
Expires: September 6, 2020

J. Levine, Ed.
Temporary RFC Series Project Manager
March 5, 2020

**The "xml2rfc" version 3 Vocabulary
draft-iab-rfc7991bis-02**

Abstract

This document defines the "xml2rfc" version 3 vocabulary: an XML-based language used for writing RFCs and Internet-Drafts. It is heavily derived from the version 2 vocabulary that is also under discussion. This document obsoletes the earlier v3 grammar described in [RFC 7991](#), which in turn obsoleted the v2 grammar in [RFC 7749](#).

Editorial Note (To be removed by RFC Editor)

Discussion of this draft takes place on the xml2rfc-dev@ietf.org mailing list, which has its home page at [<https://www.ietf.org/mailman/listinfo/xml2rfc-dev>](https://www.ietf.org/mailman/listinfo/xml2rfc-dev).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 6, 2020.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

(<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	4
1.1.	Expected Updates to the Specification	5
1.2.	Design Criteria for the Changes in v3	5
1.3.	Differences from RFC 7991 in This Document	6
1.4.	Differences from v2 to v3	6
1.4.1.	New Elements in v3	6
1.4.2.	New Attributes for Existing Elements	7
1.4.3.	Elements and Attributes Deprecated from v2	8
1.4.4.	Additional Changes from v2	9
1.5.	Syntax Notation	10
2.	Elements	10
2.1.	<abstract>	11
2.2.	<address>	12
2.3.	<annotation>	12
2.4.	<area>	13
2.5.	<artset>	13
2.6.	<artwork>	14
2.7.	<aside>	17
2.8.	<author>	18
2.9.	<back>	19
2.10.	<bcp14>	20
2.11.	<blockquote>	20
2.12.	<boilerplate>	22
2.13.	<city>	22
2.14.	<cityarea>	22
2.15.	<code>	23
2.16.	<country>	23
2.17.	<cref>	23
2.18.	<date>	24
2.19.	<dd>	25
2.20.	<displayreference>	27
2.21.	<dl>	28
2.22.	<dt>	29
2.23.		30
2.24.	<email>	31
2.25.	<eref>	31
2.26.	<extaddr>	32
2.27.	<figure>	32

Levine

Expires September 6, 2020

[Page 2]

2.28.	<front>	34
2.29.	<iref>	35
2.30.	<keyword>	36
2.31.		36
2.32.	<link>	38
2.33.	<middle>	39
2.34.	<name>	39
2.35.	<note>	40
2.36.		41
2.37.	<organization>	43
2.38.	<phone>	43
2.39.	<pobox>	44
2.40.	<postal>	44
2.41.	<postalLine>	45
2.42.	<refcontent>	45
2.43.	<reference>	46
2.44.	<referencegroup>	47
2.45.	<references>	47
2.46.	<region>	49
2.47.	<relref>	49
2.48.	<rfc>	53
2.49.	<section>	56
2.50.	<seriesInfo>	58
2.51.	<sortingcode>	60
2.52.	<sourcecode>	61
2.53.	<street>	63
2.54.		63
2.55.	<sub>	64
2.56.	<sup>	65
2.57.	<t>	65
2.58.	<table>	67
2.59.	<tbody>	68
2.60.	<td>	68
2.61.	<tfoot>	70
2.62.	<th>	71
2.63.	<thead>	73
2.64.	<title>	73
2.65.	<tr>	73
2.66.	<tt>	74
2.67.		75
2.68.	<uri>	76
2.69.	<workgroup>	76
2.70.	<xref>	76
3.	Elements from v2 That Have Been Deprecated	78
3.1.	<c>	79
3.2.	<facsimile>	79
3.3.	<format>	79
3.4.	<list>	80

3.5.	<postamble>	80
3.6.	<preamble>	81
3.7.	<spanx>	82
3.8.	<texttable>	82
3.9.	<ttable>	84
3.10.	<vspace>	84
4.	SVG	85
5.	Use of CDATA Structures and Escaping	85
6.	Internationalization Considerations	85
7.	Security Considerations	86
8.	IANA Considerations	86
8.1.	Internet Media Type Registration	86
8.2.	Link Relation Registration	88
9.	References	88
9.1.	Normative References	88
9.2.	Informative References	88
Appendix A.	Front-Page ("Boilerplate") Generation	93
A.1.	The "ipr" Attribute	93
A.1.1.	Current Values: "*trust200902"	93
A.1.2.	Historic Values	95
A.2.	The "submissionType" Attribute	95
A.3.	The "consensus" Attribute	96
Appendix B.	The v3 Format and Processing Tools	97
B.1.	Including External Text with XInclude	98
B.2.	Anchor and IDs	99
B.2.1.	Overlapping Values	100
B.3.	Attributes Controlled by the Prep Tool	101
Appendix C.	RELAX NG Schema	102
Appendix D.	Schema Differences from v2	124
Index		145
IAB Members at the Time of Approval		167
Acknowledgments		167
Author's Address		168

1. Introduction

This document describes version 3 ("v3") of the "xml2rfc" vocabulary: an XML-based language ("Extensible Markup Language" [XML]) used for writing RFCs [RFC7322] and Internet-Drafts [IDGUIDE].

This document obsoletes [RFC7991], [RFC7991] obsoleted the version 2 vocabulary ("v2") [RFC7749], which contains the extended language definition. [RFC7749] obsoleted the original version ("v1") [RFC2629]. This document directly copies the material from [RFC7749] where possible.

The v3 format will be used as part of the new RFC Series format described in [RFC6949]. The new format will be handled by one or

Levine

Expires September 6, 2020

[Page 4]

more new tools for preparing the XML and converting it to other representations. Features of the expected tools are described in [Appendix B](#). That section defines some terms used throughout this document, such as "prep tool" and "formatter".

Note that the vocabulary contains certain constructs that might not be used when generating the final text; however, they can provide useful data for other uses (such as index generation, populating a keyword database, or syntax checks).

In this document, the term "format" is used when describing types of documents, primarily XML and HTML. The term "representation" is used when talking about a specific instantiation of a format, such as an XML document or an HTML document that was created by an XML document.

1.1. Expected Updates to the Specification

Non-interoperable changes in later versions of this specification are likely based on experience gained in implementing the new publication toolsets. Revised documents will be published capturing those changes as the toolsets are completed. Other implementers must not expect those changes to remain backwards-compatible with the details described in this document.

1.2. Design Criteria for the Changes in v3

The design criteria of the changes from v2 to v3 are as follows:

- o The intention is that starting and editing a v3 document will be easier than for a v2 document.
- o There will be good v2-to-v3 conversion tools for when an author wants to change versions.
- o There are no current plans to make v3 XML the required submission format for drafts or RFCs. That might happen eventually, but it is likely to be years away.

There is a desire to keep as much of the v2 grammar as makes sense within the above design criteria and not to make gratuitous changes to the v2 grammar. Another way to say this is "we would rather encourage backwards compatibility but not be constrained by it." Still, the goal of starting and editing a v3 document being easier than for a v2 document is more important than backwards compatibility with v2, given the latter two design criteria.

v3 is upwards compatible with v2, meaning that a v2 document is meant to be a valid v3 document as well. However, some features of v2 are

deprecated in v3 in favor of new elements. Deprecated features are listed in [Section 1.4.3](#) and are described in [\[RFC7749\]](#).

[1.3.](#) Differences from [RFC 7991](#) in This Document

This is a (hopefully) complete list of all the technical changes between [\[RFC7991\]](#) and this document.

- o Changed the text about what this draft obsoletes and updates.
- o Allow `<blockquote>` as a child of ``.
- o Removed "It is an error to have both a "src" attribute and content in the `<artwork>` element." from [Section 2.6.6](#).
- o Removed `
` from the vocabulary.
- o Changed the "hanging" attribute of `<dl>` to "newline".
- o Added the "indent" attribute to `<dl>`.
- o Added the "align" attribute to `<table>`. Made the table title centered under the table.
- o The `<name>` element now allows many more elements inside of it.
- o Redefined `<references>` to allow `<references>` within it. In the typical case, an outer `<references>` will be used to hold an inner `<references>` for normative references and an inner `<references>` to hold informative references.

[1.4.](#) Differences from v2 to v3

This is a (hopefully) complete list of all the technical changes between [\[RFC7749\]](#) and this document.

[1.4.1.](#) New Elements in v3

- o Add `<dl>`, ``, and `` as new ways to make lists. This is a significant change from v2 in that the child under these elements is ``, not `<t>`. `` has a model of either containing one or more `<t>` elements, or containing the flowing text normally found in `<t>`. These lists are children of `<section>`s and other lists instead of `<t>`.
- o Add ``, ``, `<tt>`, `<sub>`, and `<sup>` for character formatting.

- o Add `<aside>` for incidental text that will be indented when displayed.
- o Add `<sourcecode>` to differentiate from `<artwork>`.
- o Add `<table>`, `<thead>`, `<tbody>`, `<tfoot>`, `<tr>`, `<td>`, and `<th>` to give table functionality like that in HTML.
- o Add `<boilerplate>` to hold the automatically generated boilerplate text.
- o Add `<blockquote>` to indicate a quotation as in a paragraph-like format.
- o Add `<name>` to sections, notes, figures, and texttables to allow character formatting (fixed-width font) in their titles and to allow references in the names.
- o Add `<postalLine>`, free text that represents one line of the address.
- o Add `<displayreference>` to allow display of more mnemonic anchor names for automatically included references.
- o Add `<refcontent>` to allow better control of text in a reference.
- o Add `<referencegroup>` to allow referencing multi-RFC documents such as STDs and BCPS.
- o Add `<relref>` to allow referencing specific sections or anchors in references.
- o Add `<link>` to point to a resource related to the RFC.
- o Add `
` to allow line breaks (but not blank lines) in the generated output for table cells.
- o Add `<svg>` to allow easy inclusion of SVG drawings in `<artwork>`.
- o Add `<artset>` to allow support of alternative artwork formats.

1.4.2. New Attributes for Existing Elements

- o Add "sortRefs", "symRefs", "tocDepth", and "tocInclude" attributes to `<rfc>` to cover Processing Instructions (PIs) that were in v2 that are still needed in the grammar. Add "prepTime" to indicate the time that the XML went through a preparation step. Add "version" to indicate the version of xml2rfc vocabulary used in

the document. Add "scripts" to indicate which scripts are needed to render the document. Add "expiresDate" when an Internet-Draft expires.

- o Add "ascii" attributes to <email>, <organization>, <street>, <city>, <region>, <country>, and <code>. Also add "asciiFullname", "asciiInitials", and "asciiSurname" to <author>. This allows an author to specify their information in their native scripts as the primary entry and still allow the ASCII-equivalent values to appear in the processed documents.
- o Add "anchor" attributes to many block elements to allow them to be linked with <relref> and <xref>.
- o Add the "section", "relative", and "sectionFormat" attributes to <xref>.
- o Add the "numbered" and "removeInRFC" attributes to <section>.
- o Add the "removeInRFC" attribute to <note>.
- o Add "pn" to <artwork>, <aside>, <blockquote>, <boilerplate>, <dt>, <figure>, <ieref>, , <references>, <section>, <sourcecode>, <t>, and <table> to hold automatically generated numbers for items in a section that don't have their own numbering (namely figures and tables).
- o Add "display" to <cref> to indicate to tools whether or not to display the comment.
- o Add "keepWithNext" and "keepWithPrevious" to <t> as a hint to tools that do pagination that they should try to keep the paragraph with the next/previous element.

1.4.3. Elements and Attributes Deprecated from v2

Deprecated elements and attributes are legacy vocabulary from v2 that are supported for input to v3 tools. They are likely to be removed from those tools in the future. Deprecated attributes are still listed in [Section 2](#), and deprecated elements are listed in [Section 3](#). See [Appendix B](#) for more information on tools and how they will handle deprecated features.

- o Deprecate <list> in favor of <dl>, , and .
- o Deprecate <spanx>; replace it with , , and <tt>.

- o Deprecate `<vspace>` because the major use for it, creating pseudo-paragraph-breaks in lists, is now handled properly.
- o Deprecate `<texttable>`, `<ttable>`, and `<c>`; replace them with the new table elements (`<table>` and the elements that can be contained within it).
- o Deprecate `<facsimile>` because it is rarely used.
- o Deprecate `<format>` because it is not useful and has caused surprise for authors in the past. If the goal is to provide a single URI (Uniform Resource Identifier) for a reference, use the "target" attribute in `<reference>` instead.
- o Deprecate `<preamble>` and `<postamble>` in favor of simply using `<t>` before or after the figure. This also deprecates the "align" attribute in `<figure>`.
- o Deprecate the "title" attribute in `<section>`, `<note>`, `<figure>`, `<references>`, and `<texttable>` in favor of the new `<name>`.
- o Deprecate the "alt" and "src" attributes in `<figure>` because they overlap with the attributes in `<artwork>`.
- o Deprecate the "xml:space" attribute in `<artwork>` because there was only one useful value. Deprecate the "height" and "width" attributes in both `<artwork>` and `<figure>` because they are not needed for the new output formats.
- o Deprecate the "pageno" attribute in `<xref>` because it was unused in v2. Deprecate the "none" values for the "format" attribute in `<xref>` because it makes no sense semantically.

1.4.4. Additional Changes from v2

- o Allow non-ASCII characters in the format; the characters that are actually allowed will be determined by the RFC Series Editor.
- o Allow `<artwork>` and `<sourcecode>` to be used on their own in `<section>` (no longer confine them to a figure).
- o Give more specifics of handling the "type" attribute in `<artwork>`.
- o Allow ``, ``, `<tt>`, `<eref>`, and `<xref>` in `<cref>`.
- o Allow the sub-elements inside a `<reference>` to be in any order.

- o Turn off the autogeneration of anchors in <cref> because there is no use case for them that cannot be achieved in other ways.
- o Allow more than one <artwork>, or more than one <sourcecode>, in <figure>.
- o In <front>, make <date> optional.
- o In <date>, add restrictions to the "date" and "year" attributes when used in the <front> for the document's boilerplate text.
- o In <postal>, allow the sub-elements to be in any order. Also allow the inclusion of the new <postalLine> instead of the older elements.
- o In <section>, restrict the names of the anchors that can be used on some types of sections.
- o Make <seriesInfo> a child of <front>, and deprecated it as a child of <reference>. This also deprecates some of the attributes from <rfc> and moves them into <seriesInfo>.
- o <t> now only contains non-block elements, so it no longer contains <figure> elements.
- o Do not generate the grammar from a DTD, but instead get it directly from the RELAX Next Generation (RNG) grammar [[RNG](#)].

[1.5.](#) Syntax Notation

The XML vocabulary here is defined in prose, based on the RELAX NG schema [[RNC](#)] contained in [Appendix C](#) (specified in RELAX NG Compact Notation (RNC)).

Note that the schema can be used for automated validity checks, but certain constraints are only described in prose (example: the conditionally required presence of the "abbrev" attribute).

[2.](#) Elements

The sections below describe all elements and their attributes.

Note that attributes not labeled "mandatory" are optional.

Many elements have an optional "anchor" attribute. In all cases, the value of the "anchor" attribute needs to be a valid XML "Name" (Section 2.3 of [[XML](#)]), additionally constrained to US-ASCII characters [[USASCII](#)]. Thus, the character repertoire consists of

"A-Z", "a-z", "0-9", "_", "-", ".", and ":", where "0-9", ".", and "-" are disallowed as start characters. Anchors are described in more detail in [Appendix B.2](#).

Tools interpreting the XML described here will collapse horizontal whitespace and line breaks to a single whitespace (except inside `<artwork>` and `<sourcecode>`) and will trim leading and trailing whitespace. Tab characters (U+0009) inside `<artwork>` and `<sourcecode>` are prohibited.

Some of the elements have attributes that are not described in this section because those attributes are specific to the prep tool. People writing tools to process this format should read all of the appendices for a complete description of these attributes.

Every element in the v3 vocabulary can have an "xml:lang" attribute, an "xml:base" attribute, or both. The xml:lang attribute specifies the language used in the element. This is sometimes useful for renderers that display different fonts for ideographic characters used in China and Japan. The xml:base attribute is sometimes added to an XML file when doing XML-to-XML conversion where the base file has XInclude attributes (see [Appendix B.1](#)).

[2.1.](#) <abstract>

Contains the Abstract of the document. See [[RFC7322](#)] for more information on restrictions for the Abstract.

This element appears as a child element of `<front>` ([Section 2.28](#)).

Content model:

In any order, but at least one of:

- o `<dl>` elements ([Section 2.21](#))
- o `` elements ([Section 2.36](#))
- o `<t>` elements ([Section 2.57](#))
- o `` elements ([Section 2.67](#))

[2.1.1.](#) "anchor" Attribute

Document-wide unique identifier for the Abstract.

2.2. <address>

Provides address information for the author.

This element appears as a child element of <author> ([Section 2.8](#)).

Content model:

In this order:

1. One optional <postal> element ([Section 2.40](#))
2. One optional <phone> element ([Section 2.38](#))
3. One optional <facsimile> element ([Section 3.2](#))
4. One optional <email> element ([Section 2.24](#))
5. One optional <uri> element ([Section 2.68](#))

2.3. <annotation>

Provides additional prose augmenting a bibliographic reference. This text is intended to be shown after the rest of the generated reference text.

This element appears as a child element of <reference> ([Section 2.43](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.10](#))
- o <cref> elements ([Section 2.17](#))
- o elements ([Section 2.23](#))
- o <eref> elements ([Section 2.25](#))
- o <iref> elements ([Section 2.29](#))
- o <relref> elements ([Section 2.47](#))
- o <spanx> elements ([Section 3.7](#))

- o elements ([Section 2.54](#))
- o <sub> elements ([Section 2.55](#))
- o <sup> elements ([Section 2.56](#))
- o <tt> elements ([Section 2.66](#))
- o <xref> elements ([Section 2.70](#))

[2.4.](#) <area>

Provides information about the IETF area to which this document relates (currently not used when generating documents).

The value ought to be either the full name or the abbreviation of one of the IETF areas as listed on <http://www.ietf.org/iesg/area.html>. A list of full names and abbreviations will be kept by the RFC Series Editor.

This element appears as a child element of <front> ([Section 2.28](#)).

Content model: only text content.

[2.5.](#) <artset>

This element allows for the support of alternative artwork formats. This will allow the renderer to pick the most appropriate <artwork> instance for its format from the alternatives present within an <artset> element.

If more than one <artwork> element is found within an <artset> element, with the same "type" attribute, the rendere could select the first one, or possibly choose between the alternative instances based on the output format and some quality of the alternative instances that made one more suitable than the other for that particular format, such as size, aspect ration, etc.

This element appears as a child element of <aside> ([Section 2.7](#)), <blockquote> ([Section 2.11](#)), <dd> ([Section 2.19](#)), <figure> ([Section 2.27](#)), ([Section 2.31](#)), <section> ([Section 2.49](#)), <td> ([Section 2.60](#)), and <th> ([Section 2.62](#)).

Content model:

One or more <artwork> elements ([Section 2.6](#))

2.5.1. "anchor" Attribute

Same as for the <artwork> element ([Section 2.6](#)).

2.6. <artwork>

This element allows the inclusion of "artwork" in the document. <artwork> provides full control of horizontal whitespace and line breaks; thus, it is used for a variety of things, such as diagrams ("line art") and protocol unit diagrams. Tab characters (U+0009) inside of this element are prohibited.

Alternatively, the "src" attribute allows referencing an external graphics file, such as a vector drawing in SVG or a bitmap graphic file, using a URI. In this case, the textual content acts as a fallback for output representations that do not support graphics; thus, it ought to contain either (1) a "line art" variant of the graphics or (2) prose that describes the included image in sufficient detail.

In [[RFC7749](#)], the <artwork> element was also used for source code and formal languages; in v3, this is now done with <sourcecode>.

There are at least five ways to include SVG in artwork in Internet-Drafts:

- o Inline, by including all of the SVG in the content of the element, such as: <artwork type="svg"><svg xmlns="http://www.w3.org/2000/svg...">
- o Inline, but using XInclude (see [Appendix B.1](#)), such as: <artwork type="svg"><xi:include href=...>
- o As a data: URI, such as: <artwork type="svg" src="data:image/svg+xml,%3Csvg%20xmlns%3D%22http%3A%2F%2Fwww.w3...">
- o As a URI to an external entity, such as: <artwork type="svg" src="http://www.example.com/...">
- o As a local file, such as: <artwork type="svg" src="diagram12.svg">

The use of SVG in Internet-Drafts and RFCs is covered in much more detail in [[RFC7996](#)].

The above methods for inclusion of SVG art can also be used for including text artwork, but using a data: URI is probably confusing for text artwork.

Formatters that do pagination should attempt to keep artwork on a single page. This is to prevent artwork that is split across pages from looking like two separate pieces of artwork.

See [Section 5](#) for a description of how to deal with issues of using "&" and "<" characters in artwork.

This element appears as a child element of <artset> ([Section 2.5](#)), <aside> ([Section 2.7](#)), <blockquote> ([Section 2.11](#)), <dd> ([Section 2.19](#)), <figure> ([Section 2.27](#)), ([Section 2.31](#)), <section> ([Section 2.49](#)), <td> ([Section 2.60](#)), and <th> ([Section 2.62](#)).

Content model:

Either:

Text

Or:

<svg> elements ([Section 4](#))

[2.6.1.](#) "align" Attribute

Controls whether the artwork appears left justified (default), centered, or right justified. Artwork is aligned relative to the left margin of the document.

Allowed values:

- o "left" (default)
- o "center"
- o "right"

[2.6.2.](#) "alt" Attribute

Alternative text description of the artwork (which is more than just a summary or caption). When the art comes from the "src" attribute and the format of that artwork supports alternate text, the alternative text comes from the text of the artwork itself, not from this attribute. The contents of this attribute are important to readers who are visually impaired, as well as those reading on devices that cannot show the artwork well, or at all.

[2.6.3.](#) "anchor" Attribute

Document-wide unique identifier for this artwork.

[2.6.4.](#) "height" Attribute

Deprecated.

[2.6.5.](#) "name" Attribute

A filename suitable for the contents (such as for extraction to a local file). This attribute can be helpful for other kinds of tools (such as automated syntax checkers, which work by extracting the artwork). Note that the "name" attribute does not need to be unique for <artwork> elements in a document. If multiple <artwork> elements have the same "name" attribute, a processing tool might assume that the elements are all fragments of a single file, and the tool can collect those fragments for later processing. See [Section 7](#) for a discussion of possible problems with the value of this attribute.

[2.6.6.](#) "src" Attribute

The URI reference of a graphics file [[RFC3986](#)], or the name of a file on the local disk. This can be a "data" URI [[RFC2397](#)] that contains the contents of the graphics file. Note that the inclusion of art with the "src" attribute depends on the capabilities of the processing tool reading the XML document. Tools need to be able to handle the file: URI, and they should be able to handle http: and https: URIs as well. The prep tool will be able to handle reading the "src" attribute.

If no URI scheme is given in the attribute, the attribute is considered to be a local filename relative to the current directory. Processing tools must be careful to not accept dangerous values for the filename, particularly those that contain absolute references outside the current directory. Document creators should think hard before using relative URIs due to possible later problems if files move around on the disk. Also, documents should most likely use explicit URI schemes wherever possible.

In some cases, the prep tool may remove the "src" attribute after processing its value. See [[RFC7998](#)] for a description of this.

[2.6.7.](#) "type" Attribute

Specifies the type of the artwork. The value of this attribute is free text with certain values designated as preferred.

The preferred values for <artwork> types are:

- o ascii-art
- o binary-art
- o call-flow
- o hex-dump
- o svg

The RFC Series Editor will maintain a complete list of the preferred values on the RFC Editor web site, and that list is expected to be updated over time. Thus, a consumer of v3 XML should not cause a failure when it encounters an unexpected type or no type is specified. The table will also indicate which type of art can appear in plain-text output (for example, type="svg" cannot).

[2.6.8.](#) "width" Attribute

Deprecated.

[2.6.9.](#) "xml:space" Attribute

Deprecated.

[2.7.](#) <aside>

This element is a container for content that is semantically less important or tangential to the content that surrounds it.

This element appears as a child element of <section> ([Section 2.49](#)).

Content model:

In any order:

- o <artset> elements ([Section 2.5](#))
- o <artwork> elements ([Section 2.6](#))
- o <dl> elements ([Section 2.21](#))
- o <figure> elements ([Section 2.27](#))
- o <iref> elements ([Section 2.29](#))

- o `` elements ([Section 2.36](#))
- o `<t>` elements ([Section 2.57](#))
- o `<table>` elements ([Section 2.58](#))
- o `` elements ([Section 2.67](#))

[2.7.1.](#) "anchor" Attribute

Document-wide unique identifier for this aside.

[2.8.](#) `<author>`

Provides information about a document's author. This is used both for the document itself (at the beginning of the document) and for referenced documents.

The `<author>` elements contained within the document's `<front>` element are used to fill the boilerplate and also to generate the "Author's Address" section (see [[RFC7322](#)]).

Note that an "author" can also be just an organization (by not specifying any of the "name" attributes, but adding the `<organization>` child element).

Furthermore, the "role" attribute can be used to mark an author as "editor". This is reflected both on the front page and in the "Author's Address" section, as well as in bibliographic references. Note that this specification does not define a precise meaning for the term "editor".

This element appears as a child element of `<front>` ([Section 2.28](#)).

Content model:

In this order:

1. One optional `<organization>` element ([Section 2.37](#))
2. One optional `<address>` element ([Section 2.2](#))

[2.8.1.](#) "asciiFullname" Attribute

The ASCII equivalent of the author's full name.

[2.8.2.](#) "asciiInitials" Attribute

The ASCII equivalent of the author's initials, to be used in conjunction with the separately specified `asciiSurname`.

[2.8.3.](#) "asciiSurname" Attribute

The ASCII equivalent of the author's surname, to be used in conjunction with the separately specified `asciiInitials`.

[2.8.4.](#) "fullname" Attribute

The full name (used in the automatically generated "Author's Address" section). Although this attribute is optional, if one or more of the `asciiFullname`, `asciiInitials`, or `asciiSurname` attributes have values, the `fullname` attribute is required.

[2.8.5.](#) "initials" Attribute

An abbreviated variant of the given name(s), to be used in conjunction with the separately specified surname. It usually appears on the front page, in footers, and in references.

Some processors will post-process the value -- for instance, when it only contains a single letter (in which case they might add a trailing dot). Relying on this kind of post-processing can lead to results varying across formatters and thus ought to be avoided.

[2.8.6.](#) "role" Attribute

Specifies the role the author had in creating the document.

Allowed values:

- o "editor"

[2.8.7.](#) "surname" Attribute

The author's surname, to be used in conjunction with the separately specified initials. It usually appears on the front page, in footers, and in references.

[2.9.](#) <back>

Contains the "back" part of the document: the references and appendices. In <back>, <section> elements indicate appendices.

This element appears as a child element of <rfc> ([Section 2.48](#)).

Content model:

In this order:

1. Optional <displayreference> elements ([Section 2.20](#))
2. One <references> element ([Section 2.45](#))
3. Optional <section> elements ([Section 2.49](#))

2.10. <bcp14>

Marks text that are phrases defined in [BCP14] such as "MUST", "SHOULD NOT", and so on. When shown in some of the output representations, the text in this element might be highlighted. The use of this element is optional.

This element is only to be used around the actual phrase from [BCP 14](#), not the full definition of a requirement. For example, it is correct to say "The packet <bcp14>MUST</bcp14> be dropped.", but it is not correct to say "<bcp14>The packet MUST be dropped.</bcp14>".

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.11](#)), <dd> ([Section 2.19](#)), <dt> ([Section 2.22](#)), ([Section 2.23](#)), ([Section 2.31](#)), <name> ([Section 2.34](#)), <preamble> ([Section 3.6](#)), <refcontent> ([Section 2.42](#)), ([Section 2.54](#)), <sub> ([Section 2.55](#)), <sup> ([Section 2.56](#)), <t> ([Section 2.57](#)), <td> ([Section 2.60](#)), <th> ([Section 2.62](#)), and <tt> ([Section 2.66](#)).

Content model: only text content.

2.11. <blockquote>

Specifies that a block of text is a quotation.

This element appears as a child element of ([Section 2.31](#)) and <section> ([Section 2.49](#)).

Content model:

Either:

In any order, but at least one of:

- * <artset> elements ([Section 2.5](#))

- * <artwork> elements ([Section 2.6](#))
- * <dl> elements ([Section 2.21](#))
- * <figure> elements ([Section 2.27](#))
- * elements ([Section 2.36](#))
- * <sourcecode> elements ([Section 2.52](#))
- * <t> elements ([Section 2.57](#))
- * <table> elements ([Section 2.58](#))
- * elements ([Section 2.67](#))

Or:

In any order, but at least one of:

- * Text
- * <bcp14> elements ([Section 2.10](#))
- * <cref> elements ([Section 2.17](#))
- * elements ([Section 2.23](#))
- * <eref> elements ([Section 2.25](#))
- * <iref> elements ([Section 2.29](#))
- * <relref> elements ([Section 2.47](#))
- * elements ([Section 2.54](#))
- * <sub> elements ([Section 2.55](#))
- * <sup> elements ([Section 2.56](#))
- * <tt> elements ([Section 2.66](#))
- * <xref> elements ([Section 2.70](#))

[2.11.1.](#) "anchor" Attribute

Document-wide unique identifier for this quotation.

[2.11.2.](#) "cite" Attribute

The source of the citation. This must be a URI. If the "quotedFrom" attribute is given, this URI will be used by processing tools as the link for the text of that attribute.

[2.11.3.](#) "quotedFrom" Attribute

Name of person or document the text in this element is quoted from. A formatter should render this as visible text at the end of the quotation.

[2.12.](#) <boilerplate>

Holds the boilerplate text for the document. This element is filled in by the prep tool.

This element contains <section> elements. Every <section> element in this element must have the "numbered" attribute set to "false".

This element appears as a child element of <front> ([Section 2.28](#)).

Content model:

One or more <section> elements ([Section 2.49](#))

[2.13.](#) <city>

Gives the city name in a postal address.

This element appears as a child element of <postal> ([Section 2.40](#)).

Content model: only text content.

[2.13.1.](#) "ascii" Attribute

The ASCII equivalent of the city name.

[2.14.](#) <cityarea>

TBD

This element appears as a child element of <postal> ([Section 2.40](#)).

Content model: only text content.

[2.14.1.](#) "ascii" Attribute

The ASCII equivalent of the city area name.

[2.15.](#) <code>

Gives the postal region code.

This element appears as a child element of <postal> ([Section 2.40](#)).

Content model: only text content.

[2.15.1.](#) "ascii" Attribute

The ASCII equivalent of the postal code.

[2.16.](#) <country>

Gives the country name or code in a postal address.

This element appears as a child element of <postal> ([Section 2.40](#)).

Content model: only text content.

[2.16.1.](#) "ascii" Attribute

The ASCII equivalent of the country name.

[2.17.](#) <cref>

Represents a comment.

Comments can be used in a document while it is work in progress. They might appear either inline and visually highlighted, at the end of the document, or not at all, depending on the formatting tool.

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.11](#)), <c> ([Section 3.1](#)), <dd> ([Section 2.19](#)), <dt> ([Section 2.22](#)), ([Section 2.23](#)), ([Section 2.31](#)), <name> ([Section 2.34](#)), <postamble> ([Section 3.5](#)), <preamble> ([Section 3.6](#)), ([Section 2.54](#)), <sub> ([Section 2.55](#)), <sup> ([Section 2.56](#)), <t> ([Section 2.57](#)), <td> ([Section 2.60](#)), <th> ([Section 2.62](#)), <tt> ([Section 2.66](#)), and <ttcol> ([Section 3.9](#)).

Content model:

In any order:

- o Text
- o `` elements ([Section 2.23](#))
- o `<eref>` elements ([Section 2.25](#))
- o `<relref>` elements ([Section 2.47](#))
- o `` elements ([Section 2.54](#))
- o `<sub>` elements ([Section 2.55](#))
- o `<sup>` elements ([Section 2.56](#))
- o `<tt>` elements ([Section 2.66](#))
- o `<xref>` elements ([Section 2.70](#))

[2.17.1.](#) "anchor" Attribute

Document-wide unique identifier for this comment.

[2.17.2.](#) "display" Attribute

Suggests whether or not the comment should be displayed by formatting tools. This might be set to "false" if you want to keep a comment in a document after the contents of the comment have already been dealt with.

Allowed values:

- o "true" (default)
- o "false"

[2.17.3.](#) "source" Attribute

Holds the "source" of a comment, such as the name or the initials of the person who made the comment.

[2.18.](#) `<date>`

Provides information about the publication date. This element is used for two cases: the boilerplate of the document being produced, and inside bibliographic references that use the `<front>` element.

Boilerplate for Internet-Drafts and RFCs: This element defines the date of publication for the current document (Internet-Draft or RFC). When producing Internet-Drafts, the prep tool uses this date to compute the expiration date (see [[IDGUIDE](#)]). When one or more of "year", "month", or "day" are left out, the prep tool will attempt to use the current system date if the attributes that are present are consistent with that date.

In dates in <rfc> elements, the month must be a number or a month in English. The prep tool will silently change text month names to numbers. Similarly, the year must be a four-digit number.

When the prep tool is used to create Internet-Drafts, it will reject a submitted Internet-Draft that has a <date> element in the boilerplate for itself that is anything other than today. That is, the tool will not allow a submitter to specify a date other than the day of submission. To avoid this problem, authors might simply not include a <date> element in the boilerplate.

Bibliographic references: In dates in <reference> elements, the date information can have prose text for the month or year. For example, vague dates (year="ca. 2000"), date ranges (year="2012-2013"), non-specific months (month="Second quarter"), and so on are allowed.

This element appears as a child element of <front> ([Section 2.28](#)).

Content model: this element does not have any contents.

[2.18.1](#). "day" Attribute

The day of publication.

[2.18.2](#). "month" Attribute

The month or months of publication.

[2.18.3](#). "year" Attribute

The year or years of publication.

[2.19](#). <dd>

The definition part of an entry in a definition list.

This element appears as a child element of <dl> ([Section 2.21](#)).

Content model:

Either:

In any order, but at least one of:

- * <artset> elements ([Section 2.5](#))
- * <artwork> elements ([Section 2.6](#))
- * <dl> elements ([Section 2.21](#))
- * <figure> elements ([Section 2.27](#))
- * elements ([Section 2.36](#))
- * <sourcecode> elements ([Section 2.52](#))
- * <t> elements ([Section 2.57](#))
- * elements ([Section 2.67](#))

Or:

In any order, but at least one of:

- * Text
- * <bcp14> elements ([Section 2.10](#))
- * <cref> elements ([Section 2.17](#))
- * elements ([Section 2.23](#))
- * <eref> elements ([Section 2.25](#))
- * <iref> elements ([Section 2.29](#))
- * <relref> elements ([Section 2.47](#))
- * elements ([Section 2.54](#))
- * <sub> elements ([Section 2.55](#))

- * <sup> elements ([Section 2.56](#))
- * <tt> elements ([Section 2.66](#))
- * <xref> elements ([Section 2.70](#))

[2.19.1.](#) "anchor" Attribute

Document-wide unique identifier for this definition.

[2.20.](#) <displayreference>

This element gives a mapping between the anchor of a reference and a name that will be displayed instead. This allows authors to display more mnemonic anchor names for automatically included references. The mapping in this element only applies to <xref> elements whose format is "default". For example, if the reference uses the anchor "[RFC6949](#)", the following would cause that anchor in the body of displayed documents to be "RFC-dev":

```
<displayreference target="RFC6949" to="RFC-dev"/>
```

If a reference section is sorted, this element changes the sort order.

It is expected that this element will only be valid in input documents. It will likely be removed by prep tools when preparing a final version after those tools have replaced all of the associated anchors, targets, and "derivedContent" attributes.

This element appears as a child element of <back> ([Section 2.9](#)).

Content model: this element does not have any contents.

[2.20.1.](#) "target" Attribute (Mandatory)

This attribute must be the name of an anchor in a <reference> or <referencegroup> element.

[2.20.2.](#) "to" Attribute (Mandatory)

This attribute is a name that will be displayed as the anchor instead of the anchor that is given in the <reference> element. The string given must start with one of the following characters: 0-9, a-z, or A-Z. The other characters in the string must be 0-9, a-z, A-Z, "-", ".", or "_".

[2.21.](#) <dl>

A definition list. Each entry has a pair of elements: a term (<dt>) and a definition (<dd>). (This is slightly different and simpler than the model used in HTML, which allows for multiple terms for a single definition.)

This element appears as a child element of <abstract> ([Section 2.1](#)), <aside> ([Section 2.7](#)), <blockquote> ([Section 2.11](#)), <dd> ([Section 2.19](#)), ([Section 2.31](#)), <note> ([Section 2.35](#)), <section> ([Section 2.49](#)), <td> ([Section 2.60](#)), and <th> ([Section 2.62](#)).

Content model:

One or more sequences of:

1. One <dt> element
2. One <dd> element

[2.21.1.](#) "anchor" Attribute

Document-wide unique identifier for the list.

[2.21.2.](#) "indent" Attribute

Indicates the indentation to be used for the rendering of the second and following lines of the item (the first line starts with the term, and is not indented). The indentation amount is interpreted as characters when rendering plain-text documents, and en-space units when rendering in formats that have richer typographic support such as HTML or PDF. One en-space is assumed to be the length of 0.5 em-space in CSS units.

[2.21.3.](#) "newline" Attribute

The "newline" attribute defines whether or not the term appears on the same line as the definition. `newline="true"` indicates that the term is to the left of the definition, while `newline="false"` indicates that the term will be on a separate line.

Allowed values:

- o "false"
- o "true" (default)

2.21.4. "spacing" Attribute

Defines whether or not there is a blank line between entries. spacing="normal" indicates a single blank line, while spacing="compact" indicates no space between.

Allowed values:

- o "normal" (default)
- o "compact"

2.22. <dt>

The term being defined in a definition list.

This element appears as a child element of <dl> ([Section 2.21](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.10](#))
- o <cref> elements ([Section 2.17](#))
- o elements ([Section 2.23](#))
- o <eref> elements ([Section 2.25](#))
- o <iref> elements ([Section 2.29](#))
- o <relref> elements ([Section 2.47](#))
- o elements ([Section 2.54](#))
- o <sub> elements ([Section 2.55](#))
- o <sup> elements ([Section 2.56](#))
- o <tt> elements ([Section 2.66](#))
- o <xref> elements ([Section 2.70](#))

[2.22.1.](#) "anchor" Attribute

Document-wide unique identifier for this term.

[2.23.](#)

Indicates text that is semantically emphasized. Text enclosed within this element will be displayed as italic after processing. This element can be combined with other character formatting elements, and the formatting will be additive.

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.11](#)), <cref> ([Section 2.17](#)), <dd> ([Section 2.19](#)), <dt> ([Section 2.22](#)), ([Section 2.31](#)), <name> ([Section 2.34](#)), <preamble> ([Section 3.6](#)), <refcontent> ([Section 2.42](#)), ([Section 2.54](#)), <sub> ([Section 2.55](#)), <sup> ([Section 2.56](#)), <t> ([Section 2.57](#)), <td> ([Section 2.60](#)), <th> ([Section 2.62](#)), and <tt> ([Section 2.66](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.10](#))
- o <cref> elements ([Section 2.17](#))
- o <eref> elements ([Section 2.25](#))
- o <iref> elements ([Section 2.29](#))
- o <relref> elements ([Section 2.47](#))
- o elements ([Section 2.54](#))
- o <sub> elements ([Section 2.55](#))
- o <sup> elements ([Section 2.56](#))
- o <tt> elements ([Section 2.66](#))
- o <xref> elements ([Section 2.70](#))

[2.24.](#) `<email>`

Provides an email address.

The value is expected to be the addr-spec defined in [Section 2 of \[RFC6068\]](#).

This element appears as a child element of `<address>` ([Section 2.2](#)).

Content model: only text content.

[2.24.1.](#) "ascii" Attribute

The ASCII equivalent of the author's email address. This is only used if the email address has any internationalized components.

[2.25.](#) `<eref>`

Represents an "external" link (as specified in the "target" attribute). This is useful for embedding URIs in the body of a document.

If the `<eref>` element has non-empty text content, formatters should use the content as the displayed text that is linked. Otherwise, the formatter should use the value of the "target" attribute as the displayed text. Formatters will link the displayed text to the value of the "target" attribute in a manner appropriate for the output format.

For example, with an input of:

```
This is described at
<eref target="http://www.example.com/reports/r12.html"/>.
```

An HTML formatter might generate:

```
This is described at
<a href="http://www.example.com/reports/r12.html">
http://www.example.com/reports/r12.html</a>.
```

With an input of:

```
This is described
<eref target="http://www.example.com/reports/r12.html">
in this interesting report</eref>.
```

An HTML formatter might generate:

This is described

```
<a href="http://www.example.com/reports/r12.html">
in this interesting report</a>.
```

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.11](#)), <c> ([Section 3.1](#)), <cref> ([Section 2.17](#)), <dd> ([Section 2.19](#)), <dt> ([Section 2.22](#)), ([Section 2.23](#)), ([Section 2.31](#)), <name> ([Section 2.34](#)), <postamble> ([Section 3.5](#)), <preamble> ([Section 3.6](#)), ([Section 2.54](#)), <sub> ([Section 2.55](#)), <sup> ([Section 2.56](#)), <t> ([Section 2.57](#)), <td> ([Section 2.60](#)), <th> ([Section 2.62](#)), <tt> ([Section 2.66](#)), and <ttcol> ([Section 3.9](#)).

Content model: only text content.

[2.25.1.](#) "target" Attribute (Mandatory)

URI of the link target [[RFC3986](#)]. This must begin with a scheme name (such as "https://") and thus not be relative to the URL of the current document.

[2.26.](#) <extaddr>

TBD

This element appears as a child element of <postal> ([Section 2.40](#)).

Content model: only text content.

[2.26.1.](#) "ascii" Attribute

ASCII equivalent for extaddr.

[2.27.](#) <figure>

Contains a figure with a caption with the figure number. If the element contains a <name> element, the caption will also show that name.

This element appears as a child element of <aside> ([Section 2.7](#)), <blockquote> ([Section 2.11](#)), <dd> ([Section 2.19](#)), ([Section 2.31](#)), <section> ([Section 2.49](#)), <td> ([Section 2.60](#)), and <th> ([Section 2.62](#)).

Content model:

In this order:

1. One optional <name> element ([Section 2.34](#))
2. Optional <iref> elements ([Section 2.29](#))
3. One optional <preamble> element ([Section 3.6](#))
4. In any order, but at least one of:
 - * <artset> elements ([Section 2.5](#))
 - * <artwork> elements ([Section 2.6](#))
 - * <sourcecode> elements ([Section 2.52](#))
5. One optional <postamble> element ([Section 3.5](#))

[2.27.1.](#) "align" Attribute

Deprecated.

Note: does not affect title or <artwork> alignment.

Allowed values:

- o "left" (default)
- o "center"
- o "right"

[2.27.2.](#) "alt" Attribute

Deprecated. If the goal is to provide a single URI for a reference, use the "target" attribute in <reference> instead.

[2.27.3.](#) "anchor" Attribute

Document-wide unique identifier for this figure.

[2.27.4.](#) "height" Attribute

Deprecated.

[2.27.5.](#) "src" Attribute

Deprecated.

[2.27.6.](#) "suppress-title" Attribute

Deprecated.

Allowed values:

- o "true"
- o "false" (default)

[2.27.7.](#) "title" Attribute

Deprecated. Use <name> instead.

[2.27.8.](#) "width" Attribute

Deprecated.

[2.28.](#) <front>

Represents the "front matter": metadata (such as author information), the Abstract, and additional notes.

A <front> element may have more than one <seriesInfo> element. A <seriesInfo> element determines the document number (for RFCs) or name (for Internet-Drafts). Another <seriesInfo> element determines the "maturity level" (defined in [[RFC2026](#)]), using values of "std" for "Standards Track", "bcp" for "BCP", "info" for "Informational", "exp" for "Experimental", and "historic" for "Historic". The "name" attributes of those multiple <seriesInfo> elements interact as described in [Section 2.50](#).

This element appears as a child element of <reference> ([Section 2.43](#)) and <rfc> ([Section 2.48](#)).

Content model:

In this order:

1. One <title> element ([Section 2.64](#))
2. Optional <seriesInfo> elements ([Section 2.50](#))
3. One or more <author> elements ([Section 2.8](#))

4. One optional <date> element ([Section 2.18](#))
5. Optional <area> elements ([Section 2.4](#))
6. Optional <workgroup> elements ([Section 2.69](#))
7. Optional <keyword> elements ([Section 2.30](#))
8. One optional <abstract> element ([Section 2.1](#))
9. Optional <note> elements ([Section 2.35](#))
10. One optional <boilerplate> element ([Section 2.12](#))

[2.29.](#) <ieref>

Provides terms for the document's index.

Index entries can be either regular entries (when just the "item" attribute is given) or nested entries (by specifying "subitem" as well), grouped under a regular entry.

Index entries generally refer to the exact place where the <ieref> element occurred. An exception is the occurrence as a child element of <section>, in which case the whole section is considered to be relevant for that index entry. In some formats, index entries of this type might be displayed as ranges.

When the prep tool is creating index content, it collects the items in a case-sensitive fashion for both the item and subitem level.

This element appears as a child element of <annotation> ([Section 2.3](#)), <aside> ([Section 2.7](#)), <blockquote> ([Section 2.11](#)), <c> ([Section 3.1](#)), <dd> ([Section 2.19](#)), <dt> ([Section 2.22](#)), ([Section 2.23](#)), <figure> ([Section 2.27](#)), ([Section 2.31](#)), <name> ([Section 2.34](#)), <postamble> ([Section 3.5](#)), <preamble> ([Section 3.6](#)), <section> ([Section 2.49](#)), ([Section 2.54](#)), <sub> ([Section 2.55](#)), <sup> ([Section 2.56](#)), <t> ([Section 2.57](#)), <td> ([Section 2.60](#)), <th> ([Section 2.62](#)), <tt> ([Section 2.66](#)), and <ttcol> ([Section 3.9](#)).

Content model: this element does not have any contents.

[2.29.1.](#) "item" Attribute (Mandatory)

The item to include.

[2.29.2.](#) "primary" Attribute

Setting this to "true" declares the occurrence as "primary", which might cause it to be highlighted in the index. There is no restriction on the number of occurrences that can be "primary".

Allowed values:

- o "true"
- o "false" (default)

[2.29.3.](#) "subitem" Attribute

The subitem to include.

[2.30.](#) <keyword>

Specifies a keyword applicable to the document.

Note that each element should only contain a single keyword; for multiple keywords, the element can simply be repeated.

Keywords are used both in the RFC Index and in the metadata of generated document representations.

This element appears as a child element of <front> ([Section 2.28](#)).

Content model: only text content.

[2.31.](#)

A list element, used in and .

This element appears as a child element of ([Section 2.36](#)) and ([Section 2.67](#)).

Content model:

Either:

In any order, but at least one of:

- * <artset> elements ([Section 2.5](#))
- * <artwork> elements ([Section 2.6](#))

- * `<blockquote>` elements ([Section 2.11](#))
- * `<dl>` elements ([Section 2.21](#))
- * `<figure>` elements ([Section 2.27](#))
- * `` elements ([Section 2.36](#))
- * `<sourcecode>` elements ([Section 2.52](#))
- * `<t>` elements ([Section 2.57](#))
- * `` elements ([Section 2.67](#))

Or:

In any order, but at least one of:

- * Text
- * `<bcp14>` elements ([Section 2.10](#))
- * `<cref>` elements ([Section 2.17](#))
- * `` elements ([Section 2.23](#))
- * `<eref>` elements ([Section 2.25](#))
- * `<iref>` elements ([Section 2.29](#))
- * `<relref>` elements ([Section 2.47](#))
- * `` elements ([Section 2.54](#))
- * `<sub>` elements ([Section 2.55](#))
- * `<sup>` elements ([Section 2.56](#))
- * `<tt>` elements ([Section 2.66](#))
- * `<xref>` elements ([Section 2.70](#))

2.31.1. "anchor" Attribute

Document-wide unique identifier for this list item.

2.32. <link>

A link to an external document that is related to the RFC.

The following are the supported types of external documents that can be pointed to in a <link> element:

- o The current International Standard Serial Number (ISSN) for the RFC Series. The value for the "rel" attribute is "item". The link should use the form "urn:issn:".
- o The Digital Object Identifier (DOI) for this document. The value for the "rel" attribute is "describedBy". The link should use the form specified in [[RFC7669](#)]; this is expected to change in the future.
- o The Internet-Draft that was submitted to the RFC Editor to become the published RFC. The value for the "rel" attribute is "convertedFrom". The link should be to an IETF-controlled web site that retains copies of Internet-Drafts.
- o A representation of the document offered by the document author. The value for the "rel" attribute is "alternate". The link can be to a personally run web site.

In RFC production mode, the prep tool needs to check the values for <link> before an RFC is published. In draft production mode, the prep tool might remove some <link> elements during the draft submission process.

This element appears as a child element of <rfc> ([Section 2.48](#)).

Content model: this element does not have any contents.

2.32.1. "href" Attribute (Mandatory)

The URI of the external document.

2.32.2. "rel" Attribute

The relationship of the external document to this one. The relationships are taken from the "Link Relations" registry maintained by IANA [[LINKRELATIONS](#)].

[2.33.](#) `<middle>`

Represents the main content of the document.

This element appears as a child element of `<rfc>` ([Section 2.48](#)).

Content model:

One or more `<section>` elements ([Section 2.49](#))

[2.34.](#) `<name>`

The name of the section, note, figure, or texttable. This name can indicate markup of flowing text (for example, including references or making some characters use a fixed-width font).

This element appears as a child element of `<figure>` ([Section 2.27](#)), `<note>` ([Section 2.35](#)), `<references>` ([Section 2.45](#)), `<section>` ([Section 2.49](#)), `<table>` ([Section 2.58](#)), and `<texttable>` ([Section 3.8](#)).

Content model:

In any order:

- o Text
- o `<bcp14>` elements ([Section 2.10](#))
- o `<cref>` elements ([Section 2.17](#))
- o `` elements ([Section 2.23](#))
- o `<eref>` elements ([Section 2.25](#))
- o `<iref>` elements ([Section 2.29](#))
- o `<relref>` elements ([Section 2.47](#))
- o `` elements ([Section 2.54](#))
- o `<sub>` elements ([Section 2.55](#))
- o `<sup>` elements ([Section 2.56](#))
- o `<tt>` elements ([Section 2.66](#))
- o `<xref>` elements ([Section 2.70](#))

[2.35.](#) <note>

Creates an unnumbered, titled block of text that appears after the Abstract.

It is usually used for additional information to reviewers (Working Group information, mailing list, ...) or for additional publication information such as "IESG Notes".

This element appears as a child element of <front> ([Section 2.28](#)).

Content model:

In this order:

1. One optional <name> element ([Section 2.34](#))
2. In any order, but at least one of:

- * <dl> elements ([Section 2.21](#))

- * elements ([Section 2.36](#))

- * <t> elements ([Section 2.57](#))

- * elements ([Section 2.67](#))

[2.35.1.](#) "removeInRFC" Attribute

If set to "true", this note is marked in the prep tool with text indicating that it should be removed before the document is published as an RFC. That text will be "This note is to be removed before publishing as an RFC."

Allowed values:

- o "true"
- o "false" (default)

[2.35.2.](#) "title" Attribute

Deprecated. Use <name> instead.

[2.36.](#)

An ordered list. The labels on the items will be either a number or a letter, depending on the value of the style attribute.

This element appears as a child element of <abstract> ([Section 2.1](#)), <aside> ([Section 2.7](#)), <blockquote> ([Section 2.11](#)), <dd> ([Section 2.19](#)), ([Section 2.31](#)), <note> ([Section 2.35](#)), <section> ([Section 2.49](#)), <td> ([Section 2.60](#)), and <th> ([Section 2.62](#)).

Content model:

One or more elements ([Section 2.31](#))

[2.36.1.](#) "anchor" Attribute

Document-wide unique identifier for the list.

[2.36.2.](#) "group" Attribute

When the prep tool sees an element with a "group" attribute that has already been seen, it continues the numbering of the list from where the previous list with the same group name left off. If an element has both a "group" attribute and a "start" attribute, the group's numbering is reset to the given start value.

[2.36.3.](#) "spacing" Attribute

Defines whether or not there is a blank line between entries. spacing="normal" indicates a single blank line, while spacing="compact" indicates no space between.

Allowed values:

- o "normal" (default)
- o "compact"

[2.36.4.](#) "start" Attribute

The ordinal value at which to start the list. This defaults to "1" and must be an integer of 0 or greater.

2.36.5. "type" Attribute

The type of the labels on list items. If the length of the type value is 1, the meaning is the same as it is for HTML:

- a Lowercase letters (a, b, c, ...)
- A Uppercase letters (A, B, C, ...)
- 1 Decimal numbers (1, 2, 3, ...)
- i Lowercase Roman numerals (i, ii, iii, ...)
- I Uppercase Roman numerals (I, II, III, ...)

For types "a" and "A", after the 26th entry, the numbering starts at "aa"/"AA", then "ab"/"AB", and so on.

If the length of the type value is greater than 1, the value must contain a percent-encoded indicator and other text. The value is a free-form text that allows counter values to be inserted using a "percent-letter" format. For instance, "[REQ%d]" generates labels of the form "[REQ1]", where "%d" inserts the item number as a decimal number.

The following formats are supported:

- %c Lowercase letters (a, b, c, ...)
- %C Uppercase letters (A, B, C, ...)
- %d Decimal numbers (1, 2, 3, ...)
- %i Lowercase Roman numerals (i, ii, iii, ...)
- %I Uppercase Roman numerals (I, II, III, ...)
- %% Represents a percent sign

Other formats are reserved for future use. Only one percent encoding other than "%%" is allowed in a type string.

It is an error for the type string to be empty. For bulleted lists, use the element. For lists that have neither bullets nor numbers, use the element with the 'empty="true"' attribute.

If no type attribute is given, the default type is the same as "type='%d.'".

[2.37.](#) <organization>

Specifies the affiliation [[RFC7322](#)] of an author.

This information appears both in the "Author's Address" section and on the front page (see [[RFC7322](#)] for more information). If the value is long, an abbreviated variant can be specified in the "abbrev" attribute.

This element appears as a child element of <author> ([Section 2.8](#)).

Content model: only text content.

[2.37.1.](#) "abbrev" Attribute

Abbreviated variant.

[2.37.2.](#) "ascii" Attribute

The ASCII equivalent of the organization's name.

[2.37.3.](#) "asciiAbbrev" Attribute

To support abbreviated organization names in both ASCII and non-ASCII contexts.

[2.37.4.](#) "showOnFrontPage" Attribute

To support turning off listing organization with author name.

Allowed values:

- o "true" (default)
- o "false"

[2.38.](#) <phone>

Represents a phone number.

The value is expected to be the scheme-specific part of a "tel" URI (and so does not include the prefix "tel:"), using the "global-number-digits" syntax. See [Section 3 of \[RFC3966\]](#) for details.

This element appears as a child element of <address> ([Section 2.2](#)).

Content model: only text content.

[2.39.](#) **<pobox>**

TBD

This element appears as a child element of <postal> ([Section 2.40](#)).

Content model: only text content.

[2.39.1.](#) **"ascii" Attribute**

ASCII equivalent for pobox.

[2.40.](#) **<postal>**

Contains optional child elements providing postal information. These elements will be displayed in an order that is specific to formatters. A postal address can contain only a set of <street>, <city>, <region>, <code>, and <country> elements, or only an ordered set of <postalline> elements, but not both.

This element appears as a child element of <address> ([Section 2.2](#)).

Content model:

Either:

In any order:

- * <city> elements ([Section 2.13](#))
- * <cityarea> elements ([Section 2.14](#))
- * <code> elements ([Section 2.15](#))
- * <country> elements ([Section 2.16](#))
- * <extaddr> elements ([Section 2.26](#))
- * <pobox> elements ([Section 2.39](#))
- * <region> elements ([Section 2.46](#))
- * <sortingcode> elements ([Section 2.51](#))
- * <street> elements ([Section 2.53](#))

Or:

One or more <postalLine> elements ([Section 2.41](#))

2.41. <postalLine>

Represents one line of a postal address. When more than one <postalLine> is given, the prep tool emits them in the order given.

This element appears as a child element of <postal> ([Section 2.40](#)).

Content model: only text content.

2.41.1. "ascii" Attribute

The ASCII equivalent of the text in the address line.

2.42. <refcontent>

Text that should appear between the title and the date of a reference. The purpose of this element is to prevent the need to abuse <seriesInfo> to get such text in a reference.

For example:

```
<reference anchor="April1">
  <front>
    <title>On Being A Fool</title>
    <author initials="K." surname="Phunny" fullname="Knot Phunny"/>
    <date year="2000" month="April"/>
  </front>
  <refcontent>Self-published pamphlet</refcontent>
</reference>
```

would render as:

```
[April1]    Phunny, K., "On Being A Fool", Self-published
            pamphlet, April 2000.
```

This element appears as a child element of <reference> ([Section 2.43](#)).

Content model:

In any order:

- o Text

- o `<bcp14>` elements ([Section 2.10](#))
- o `` elements ([Section 2.23](#))
- o `` elements ([Section 2.54](#))
- o `<sub>` elements ([Section 2.55](#))
- o `<sup>` elements ([Section 2.56](#))
- o `<tt>` elements ([Section 2.66](#))

[2.43.](#) `<reference>`

Represents a bibliographic reference.

This element appears as a child element of `<referencegroup>` ([Section 2.44](#)) and `<references>` ([Section 2.45](#)).

Content model:

In this order:

1. One `<front>` element ([Section 2.28](#))
2. In any order:
 - * `<annotation>` elements ([Section 2.3](#))
 - * `<format>` elements ([Section 3.3](#))
 - * `<refcontent>` elements ([Section 2.42](#))
 - * `<seriesInfo>` elements ([Section 2.50](#))

[2.43.1.](#) "anchor" Attribute (Mandatory)

Document-wide unique identifier for this reference. Usually, this will be used both to "label" the reference in the "References" section and as an identifier in links to this reference entry.

[2.43.2.](#) "quote-title" Attribute

Specifies whether or not the title in the reference should be quoted. This can be used to prevent quoting, such as on errata.

Allowed values:

- o "true" (default)
- o "false"

[2.43.3.](#) "target" Attribute

Holds the URI for the reference.

[2.44.](#) <referencegroup>

Represents a list of bibliographic references that will be represented as a single reference. This is most often used to reference STDs and BCPs, where a single reference (such as "[BCP 9](#)") may encompass more than one RFC.

This element appears as a child element of <references> ([Section 2.45](#)).

Content model:

One or more <reference> elements ([Section 2.43](#))

[2.44.1.](#) "anchor" Attribute (Mandatory)

Document-wide unique identifier for this reference group. Usually, this will be used both to "label" the reference group in the "References" section and as an identifier in links to this reference entry.

[2.44.2.](#) "target" Attribute

Holds the URI for the reference.

Holds the URI for the reference.

[2.45.](#) <references>

Contains a set of bibliographic references.

In the early days of the RFC Series, there was only one "References" section per RFC. This convention was later changed to group

references into two sets, "Normative" and "Informative", as described in [RFC7322]. This vocabulary supports the split with the <name> child element. In general, the title should be either "Normative References" or "Informative References".

This element appears as a child element of <back> ([Section 2.9](#)) and <references> ([Section 2.45](#)).

Content model:

In this order:

1. One optional <name> element ([Section 2.34](#))

2. Either:

* One or more <references> elements ([Section 2.45](#))

Or:

* In any order:

+ <reference> elements ([Section 2.43](#))

+ <referencegroup> elements ([Section 2.44](#))

[2.45.1](#). "anchor" Attribute

An optional user-supplied identifier for this set of references.

[2.45.2](#). "title" Attribute

Deprecated. Use <name> instead.

2.46. <region>

Provides the region name in a postal address.

This element appears as a child element of <postal> ([Section 2.40](#)).

Content model: only text content.

2.46.1. "ascii" Attribute

The ASCII equivalent of the region name.

2.47. <relref>

Represents a link to a specific part of a document that appears in a <reference> element. Formatters that have links (such as HTML and PDF) render <relref> elements as external hyperlinks to the specified part of the reference, creating the link target by combining the base URI from the <reference> element with the "relative" attribute from this element. The "target" attribute is required, and it must be the anchor of a <reference> element.

The "section" attribute is required, and the "relative" attribute is optional. If the reference is not an RFC or Internet-Draft that is in the v3 format, the element needs to have a "relative" attribute; in this case, the value of the "section" attribute is ignored.

An example of the <relref> element with text content might be:

```
See
  <relref section="2.3" target="RFC9999" displayFormat="bare">
    the protocol overview</relref>
  for more information.
```

An HTML formatter might generate:

```
See
  <a href="http://www.rfc-editor.org/rfc/rfc9999.html#s-2.3">
    the protocol overview</a>
  for more information.
```

Note that the URL in the above example might be different when the RFC Editor deploys the v3 format.

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.11](#)), <cref> ([Section 2.17](#)), <dd> ([Section 2.19](#)), <dt> ([Section 2.22](#)), ([Section 2.23](#)), ([Section 2.31](#)), <name> ([Section 2.34](#)), <preamble> ([Section 3.6](#)),

 ([Section 2.54](#)), <sub> ([Section 2.55](#)), <sup> ([Section 2.56](#)), <t> ([Section 2.57](#)), <td> ([Section 2.60](#)), <th> ([Section 2.62](#)), and <tt> ([Section 2.66](#)).

Content model: only text content.

2.47.1. "displayFormat" Attribute

This attribute is used to signal formatters what the desired format of the relative reference should be. Formatters for document types that have linking capability should wrap each part of the displayed text in hyperlinks. If there is content in the <relref> element, formatters will ignore the value of this attribute.

"of"

A formatter should display the relative reference as the word "Section" followed by a space, the contents of the "section" attribute followed by a space, the word "of", another space, and the value from the "target" attribute enclosed in square brackets.

For example, with an input of:

```
See
<relref section="2.3" target="RFC9999" displayFormat="of"/>
for an overview.
```

An HTML formatter might generate:

```
See
<a href="http://www.rfc-editor.org/info/rfc9999#s-2.3">
Section 2.3</a> of
[<a href="#RFC9999">RFC9999</a>]
for an overview.
```

Note that "displayFormat='of'" is the default for <relref>, so it does not need to be given in a <relref> element if that format is desired.

"comma"

A formatter should display the relative reference as the value from the "target" attribute enclosed in square brackets, a comma,

a space, the word "Section" followed by a space, and the "section" attribute.

For example, with an input of:

```
See
<relref section="2.3" target="RFC9999" displayFormat="comma"/>,
for an overview.
```

An HTML formatter might generate:

```
See
[<a href="#RFC9999">RFC9999</a>],
<a href="http://www.rfc-editor.org/info/rfc9999#s-2.3">
Section 2.3</a>, for an overview.
```

"parens"

A formatter should display the relative reference as the value from the "target" attribute enclosed in square brackets, a space, a left parenthesis, the word "Section" followed by a space, the "section" attribute, and a right parenthesis.

For example, with an input of:

```
See
<relref section="2.3" target="RFC9999" displayFormat="parens"/>
for an overview.
```

An HTML formatter might generate:

```
See
[<a href="#RFC9999">RFC9999</a>]
(<a href="http://www.rfc-editor.org/info/rfc9999#s-2.3">
Section 2.3</a>)
for an overview.
```

"bare"

A formatter should display the relative reference as the contents of the "section" attribute and nothing else. This is useful when there are multiple relative references to a single base reference.

For example:

```
See Sections
<relref section="2.3" target="RFC9999" displayFormat="bare"/>
and
<relref section="2.4" target="RFC9999" displayFormat="of"/>
for an overview.
```

An HTML formatter might generate:

```
See Sections
<a href="http://www.rfc-editor.org/info/rfc9999#s-2.3">
2.3</a>
and
<a href="http://www.rfc-editor.org/info/rfc9999#s-2.4">
Section 2.4</a> of
[<a href="#RFC9999">RFC9999</a>]
for an overview.
```

Allowed values:

- o "of" (default)
- o "comma"
- o "parens"
- o "bare"

2.47.2. "relative" Attribute

Specifies a relative reference from the URI in the target reference. This value must include whatever leading character is needed to create the relative reference; typically, this is "#" for HTML documents.

[2.47.3.](#) "section" Attribute (Mandatory)

Specifies a section of the target reference. If the reference is not an RFC or Internet-Draft in the v3 format, it is an error.

[2.47.4.](#) "target" Attribute (Mandatory)

The anchor of the reference for this element. If this value is not an anchor to a <reference> or <referencegroup> element, it is an error. If the reference at the target has no URI, it is an error.

[2.48.](#) <rfc>

This is the root element of the xml2rfc vocabulary.

Content model:

In this order:

1. Optional <link> elements ([Section 2.32](#))
2. One <front> element ([Section 2.28](#))
3. One <middle> element ([Section 2.33](#))
4. One optional <back> element ([Section 2.9](#))

[2.48.1.](#) "category" Attribute

Deprecated; instead, use the "name" attribute in <seriesInfo>.

[2.48.2.](#) "consensus" Attribute

Affects the generated boilerplate. Note that the values of "no" and "yes" are deprecated and are replaced by "false" (the default) and "true".

See [[RFC7841](#)] for more information.

Allowed values:

- o "no"
- o "yes"
- o "false" (default)
- o "true"

[2.48.3.](#) "docName" Attribute

Deprecated; instead, use the "value" attribute in <seriesInfo>.

[2.48.4.](#) "indexInclude" Attribute

Specifies whether or not a formatter is requested to include an index in generated files. If the source file has no <iref> elements, an index is never generated. This option is useful for generating documents where the source document has <iref> elements but the author no longer wants an index.

Allowed values:

- o "true" (default)
- o "false"

[2.48.5.](#) "ipr" Attribute

Represents the Intellectual Property status of the document. See [Appendix A.1](#) for details.

[2.48.6.](#) "iprExtract" Attribute

Identifies a single section within the document for which extraction "as is" is explicitly allowed (only relevant for historic values of the "ipr" attribute).

[2.48.7.](#) "number" Attribute

Used to determine whether to produce an RFC or an Internet-Draft.

[2.48.8.](#) "obsoletes" Attribute

A comma-separated list of RFC numbers or Internet-Draft names.

The prep tool will parse the attribute value so that incorrect references can be detected.

[2.48.9.](#) "prepTime" Attribute

The date that the XML was processed by a prep tool. This is included in the XML file just before it is saved to disk. The value is formatted using the "date-time" format defined in [Section 5.6 of \[RFC3339\]](#). The "time-offset" should be "Z".

2.48.10. "seriesNo" Attribute

Deprecated; instead, use the "value" attribute in <seriesInfo>.

2.48.11. "sortRefs" Attribute

Specifies whether or not the prep tool will sort the references in each reference section.

Allowed values:

- o "true"
- o "false" (default)

2.48.12. "submissionType" Attribute

The document stream, as described in [[RFC7841](#)]. (The RFC Series Editor may change the list of allowed values in the future.)

Allowed values:

- o "IETF" (default)
- o "IAB"
- o "IRTF"
- o "independent"

2.48.13. "symRefs" Attribute

Specifies whether or not a formatter is requested to use symbolic references (such as "[[RFC2119](#)]"). If the value for this is "false", the references come out as numbers (such as "[3]").

Allowed values:

- o "true" (default)
- o "false"

2.48.14. "tocDepth" Attribute

Specifies the number of levels of headings that a formatter is requested to include in the table of contents; the default is "3".

[2.48.15.](#) **"tocInclude" Attribute**

Specifies whether or not a formatter is requested to include a table of contents in generated files.

Allowed values:

- o "true" (default)
- o "false"

[2.48.16.](#) **"updates" Attribute**

A comma-separated list of RFC numbers or Internet-Draft names.

The prep tool will parse the attribute value so that incorrect references can be detected.

[2.48.17.](#) **"version" Attribute**

Specifies the version of xml2rfc syntax used in this document. The only expected value (for now) is "3".

[2.49.](#) **<section>**

Represents a section (when inside a <middle> element) or an appendix (when inside a <back> element).

Subsections are created by nesting <section> elements inside <section> elements. Sections are allowed to be empty.

This element appears as a child element of <back> ([Section 2.9](#)), <boilerplate> ([Section 2.12](#)), <middle> ([Section 2.33](#)), and <section> ([Section 2.49](#)).

Content model:

In this order:

1. One optional <name> element ([Section 2.34](#))
2. In any order:
 - * <artset> elements ([Section 2.5](#))
 - * <artwork> elements ([Section 2.6](#))

- * `<aside>` elements ([Section 2.7](#))
- * `<blockquote>` elements ([Section 2.11](#))
- * `<dl>` elements ([Section 2.21](#))
- * `<figure>` elements ([Section 2.27](#))
- * `<iref>` elements ([Section 2.29](#))
- * `` elements ([Section 2.36](#))
- * `<sourcecode>` elements ([Section 2.52](#))
- * `<t>` elements ([Section 2.57](#))
- * `<table>` elements ([Section 2.58](#))
- * `<texttable>` elements ([Section 3.8](#))
- * `` elements ([Section 2.67](#))

3. Optional `<section>` elements ([Section 2.49](#))

[2.49.1.](#) "anchor" Attribute

Document-wide unique identifier for this section.

[2.49.2.](#) "numbered" Attribute

If set to "false", the formatter is requested to not display a section number. The prep tool will verify that such a section is not followed by a numbered section in this part of the document and will verify that the section is a top-level section. Descendant sections of unnumbered sections are unnumbered by definition.

Allowed values:

- o "true" (default)
- o "false"

2.49.3. "removeInRFC" Attribute

If set to "true", this note is marked in the prep tool with text indicating that it should be removed before the document is published as an RFC. That text will be "This note is to be removed before publishing as an RFC."

Allowed values:

- o "true"
- o "false" (default)

2.49.4. "title" Attribute

Deprecated. Use <name> instead.

2.49.5. "toc" Attribute

Indicates to a formatter whether or not the section is to be included in a table of contents, if such a table of contents is produced. This only takes effect if the level of the section would have appeared in the table of contents based on the "tocDepth" attribute of the <rfc> element, and of course only if the table of contents is being created based on the "tocInclude" attribute of the <rfc> element. If this is set to "exclude", any section below this one will be excluded as well. The "default" value indicates inclusion of the section if it would be included by the tocDepth attribute of the <rfc> element.

Allowed values:

- o "include"
- o "exclude"
- o "default" (default)

2.50. <seriesInfo>

Specifies the document series in which this document appears, and also specifies an identifier within that series.

A processing tool determines whether it is working on an RFC or an Internet-Draft by inspecting the "name" attribute of a <seriesInfo> element inside the <front> element inside the <rfc> element, looking for "RFC" or "Internet-Draft". (Specifying neither value in any of

the <seriesInfo> elements can be useful for producing other types of documents but is out of scope for this specification.)

It is invalid to have multiple <seriesInfo> elements inside the same <front> element containing the same "name" value. Some combinations of <seriesInfo> "name" attribute values make no sense, such as having both <seriesInfo name="rfc"/> and <seriesInfo name="Internet-Draft"/> in the same <front> element.

This element appears as a child element of <front> ([Section 2.28](#)) and <reference> ([Section 2.43](#)).

Content model: this element does not have any contents.

[2.50.1.](#) "asciiName" Attribute

The ASCII equivalent of the name field.

[2.50.2.](#) "asciiValue" Attribute

The ASCII equivalent of the value field.

[2.50.3.](#) "name" Attribute (Mandatory)

Some series names might trigger specific processing (such as for autogenerating links, inserting descriptions such as "work in progress", or additional functionality like reference diagnostics). Examples for IETF-related series names are "BCP", "FYI", "Internet-Draft", "RFC", and "STD".

Some of the values for "name" interact as follows:

- o A <front> element that has a <seriesInfo> element that has the name "Internet-Draft" cannot also have a <seriesInfo> element that has the name "RFC".
- o The <seriesInfo> element can contain the DOI for the referenced document. This cannot be used when the <seriesInfo> element is an eventual child element of an <rfc> element -- only as an eventual child of a <reference> element. The "value" attribute should use the form specified in [[RFC7669](#)].

[2.50.4.](#) "status" Attribute

The status of this document. The currently known values are "standard", "informational", "experimental", "bcp", "fyi", and "full-standard". The RFC Series Editor may change this list in the future.

2.50.5. "stream" Attribute

The stream (as described in [[RFC7841](#)]) that originated the document. (The RFC Series Editor may change this list in the future.)

Allowed values:

- o "IETF" (default)
- o "IAB"
- o "IRTF"
- o "independent"

2.50.6. "value" Attribute (Mandatory)

The identifier within the series specified by the "name" attribute.

For BCPs, FYIs, RFCs, and STDs, this is the number within the series. For Internet-Drafts, it is the full draft name (ending with the two-digit version number). For DOIs, the value is given, such as "10.17487/rfc1149", as described in [[RFC7669](#)].

The name in the value should be the document name without any file extension. For Internet-Drafts, the value for this attribute should be "[draft-ietf-somewg-someprotocol-07](#)", not "[draft-ietf-somewg-someprotocol-07.txt](#)".

2.51. <sortingcode>

A sorting code is related to postal codes in that it is used in addresses to allow sorting, for example to route mail to a certain postal centre or to distinguish streets with the same name in two different areas of the same settlement.

This element appears as a child element of <postal> ([Section 2.40](#)).

Content model: only text content.

2.51.1. "ascii" Attribute

ASCII equivalent for sortingcode.

[2.52.](#) `<sourcecode>`

This element allows the inclusion of source code into the document.

When rendered, source code is always shown in a monospace font. When `<sourcecode>` is a child of `<figure>` or `<section>`, it provides full control of horizontal whitespace and line breaks. When formatted, it is indented relative to the left margin of the enclosing element. It is thus useful for source code and formal languages (such as ABNF [[RFC5234](#)] or the RNC notation used in this document). (When `<sourcecode>` is a child of other elements, it flows with the text that surrounds it.) Tab characters (U+0009) inside of this element are prohibited.

For artwork such as character-based art, diagrams of message layouts, and so on, use the `<artwork>` element instead.

Output formatters that do pagination should attempt to keep source code on a single page. This is to prevent source code that is split across pages from looking like two separate pieces of code.

See [Section 5](#) for a description of how to deal with issues of using "&" and "<" characters in source code.

This element appears as a child element of `<blockquote>` ([Section 2.11](#)), `<dd>` ([Section 2.19](#)), `<figure>` ([Section 2.27](#)), `` ([Section 2.31](#)), `<section>` ([Section 2.49](#)), `<td>` ([Section 2.60](#)), and `<th>` ([Section 2.62](#)).

Content model: only text content.

[2.52.1.](#) "anchor" Attribute

Document-wide unique identifier for this source code.

[2.52.2.](#) "name" Attribute

A filename suitable for the contents (such as for extraction to a local file). This attribute can be helpful for other kinds of tools (such as automated syntax checkers, which work by extracting the source code). Note that the "name" attribute does not need to be unique for `<artwork>` elements in a document. If multiple `<sourcecode>` elements have the same "name" attribute, a formatter might assume that the elements are all fragments of a single file, and such a formatter can collect those fragments for later processing.

2.52.3. "src" Attribute

The URI reference of a source file [[RFC3986](#)].

It is an error to have both a "src" attribute and content in the <sourcecode> element.

2.52.4. "type" Attribute

Specifies the type of the source code. The value of this attribute is free text with certain values designated as preferred.

The preferred values for <sourcecode> types are:

- o abnf
- o asn.1
- o bash
- o c++
- o c
- o cbor
- o dtd
- o java
- o javascript
- o json
- o mib
- o perl
- o pseudocode
- o python
- o rnc
- o xml
- o yang

The RFC Series Editor will maintain a complete list of the preferred values on the RFC Editor web site, and that list is expected to be updated over time. Thus, a consumer of v3 XML should not cause a failure when it encounters an unexpected type or no type is specified.

2.53. <street>

Provides a street address.

This element appears as a child element of <postal> ([Section 2.40](#)).

Content model: only text content.

2.53.1. "ascii" Attribute

The ASCII equivalent of the street address.

**2.54. **

Indicates text that is semantically strong. Text enclosed within this element will be displayed as bold after processing. This element can be combined with other character formatting elements, and the formatting will be additive.

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.11](#)), <cref> ([Section 2.17](#)), <dd> ([Section 2.19](#)), <dt> ([Section 2.22](#)), ([Section 2.23](#)), ([Section 2.31](#)), <name> ([Section 2.34](#)), <preamble> ([Section 3.6](#)), <refcontent> ([Section 2.42](#)), <sub> ([Section 2.55](#)), <sup> ([Section 2.56](#)), <t> ([Section 2.57](#)), <td> ([Section 2.60](#)), <th> ([Section 2.62](#)), and <tt> ([Section 2.66](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.10](#))
- o <cref> elements ([Section 2.17](#))
- o elements ([Section 2.23](#))
- o <eref> elements ([Section 2.25](#))
- o <iref> elements ([Section 2.29](#))

- o <relref> elements ([Section 2.47](#))
- o <sub> elements ([Section 2.55](#))
- o <sup> elements ([Section 2.56](#))
- o <tt> elements ([Section 2.66](#))
- o <xref> elements ([Section 2.70](#))

2.55. <sub>

Causes the text to be displayed as subscript, approximately half a letter-height lower than normal text. This element can be combined with other character formatting elements, and the formatting will be additive.

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.11](#)), <cref> ([Section 2.17](#)), <dd> ([Section 2.19](#)), <dt> ([Section 2.22](#)), ([Section 2.23](#)), ([Section 2.31](#)), <name> ([Section 2.34](#)), <preamble> ([Section 3.6](#)), <refcontent> ([Section 2.42](#)), ([Section 2.54](#)), <t> ([Section 2.57](#)), <td> ([Section 2.60](#)), <th> ([Section 2.62](#)), and <tt> ([Section 2.66](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.10](#))
- o <cref> elements ([Section 2.17](#))
- o elements ([Section 2.23](#))
- o <eref> elements ([Section 2.25](#))
- o <iref> elements ([Section 2.29](#))
- o <relref> elements ([Section 2.47](#))
- o elements ([Section 2.54](#))
- o <tt> elements ([Section 2.66](#))
- o <xref> elements ([Section 2.70](#))

[2.56.](#) `<sup>`

Causes the text to be displayed as superscript, approximately half a letter-height higher than normal text. This element can be combined with other character formatting elements, and the formatting will be additive.

This element appears as a child element of `<annotation>` ([Section 2.3](#)), `<blockquote>` ([Section 2.11](#)), `<cref>` ([Section 2.17](#)), `<dd>` ([Section 2.19](#)), `<dt>` ([Section 2.22](#)), `` ([Section 2.23](#)), `` ([Section 2.31](#)), `<name>` ([Section 2.34](#)), `<preamble>` ([Section 3.6](#)), `<refcontent>` ([Section 2.42](#)), `` ([Section 2.54](#)), `<t>` ([Section 2.57](#)), `<td>` ([Section 2.60](#)), `<th>` ([Section 2.62](#)), and `<tt>` ([Section 2.66](#)).

Content model:

In any order:

- o Text
- o `<bcp14>` elements ([Section 2.10](#))
- o `<cref>` elements ([Section 2.17](#))
- o `` elements ([Section 2.23](#))
- o `<eref>` elements ([Section 2.25](#))
- o `<iref>` elements ([Section 2.29](#))
- o `<relref>` elements ([Section 2.47](#))
- o `` elements ([Section 2.54](#))
- o `<tt>` elements ([Section 2.66](#))
- o `<xref>` elements ([Section 2.70](#))

[2.57.](#) `<t>`

Contains a paragraph of text.

This element appears as a child element of `<abstract>` ([Section 2.1](#)), `<aside>` ([Section 2.7](#)), `<blockquote>` ([Section 2.11](#)), `<dd>` ([Section 2.19](#)), `` ([Section 2.31](#)), `<list>` ([Section 3.4](#)), `<note>` ([Section 2.35](#)), `<section>` ([Section 2.49](#)), `<td>` ([Section 2.60](#)), and `<th>` ([Section 2.62](#)).

Content model:

In any order:

- o Text
- o `<bcp14>` elements ([Section 2.10](#))
- o `<cref>` elements ([Section 2.17](#))
- o `` elements ([Section 2.23](#))
- o `<eref>` elements ([Section 2.25](#))
- o `<iref>` elements ([Section 2.29](#))
- o `<list>` elements ([Section 3.4](#))
- o `<relref>` elements ([Section 2.47](#))
- o `<spanx>` elements ([Section 3.7](#))
- o `` elements ([Section 2.54](#))
- o `<sub>` elements ([Section 2.55](#))
- o `<sup>` elements ([Section 2.56](#))
- o `<tt>` elements ([Section 2.66](#))
- o `<vspace>` elements ([Section 3.10](#))
- o `<xref>` elements ([Section 2.70](#))

[2.57.1.](#) "anchor" Attribute

Document-wide unique identifier for this paragraph.

[2.57.2.](#) "hangText" Attribute

Deprecated. Instead, use `<dd>` inside of a definition list (`<dl>`).

[2.57.3.](#) "keepWithNext" Attribute

Acts as a hint to the output formatters that do pagination to do a best-effort attempt to keep the paragraph with the next element, whatever that happens to be. For example, the HTML output @media print CSS ("CSS" refers to Cascading Style Sheets) might translate

this to `page-break-after: avoid`. For PDF, the paginator could attempt to keep the paragraph with the next element. Note: this attribute is strictly a hint and not always actionable.

Allowed values:

- o "false" (default)
- o "true"

2.57.4. "keepWithPrevious" Attribute

Acts as a hint to the output formatters that do pagination to do a best-effort attempt to keep the paragraph with the previous element, whatever that happens to be. For example, the HTML output @media print CSS might translate this to `page-break-before: avoid`. For PDF, the paginator could attempt to keep the paragraph with the previous element. Note: this attribute is strictly a hint and not always actionable.

Allowed values:

- o "false" (default)
- o "true"

2.58. <table>

Contains a table with a caption with the table number. If the element contains a <name> element, the caption will also show that name.

Inside the <table> element is, optionally, a <thead> element to contain the rows that will be the table's heading and, optionally, a <tfoot> element to contain the rows of the table's footer. If the XML is converted to a representation that has page breaks (such as PDFs or printed HTML), the header and footer are meant to appear on each page.

This element appears as a child element of <aside> ([Section 2.7](#)), <blockquote> ([Section 2.11](#)), and <section> ([Section 2.49](#)).

Content model:

In this order:

1. One optional <name> element ([Section 2.34](#))

2. One optional <thead> element ([Section 2.63](#))
3. One or more <tbody> elements ([Section 2.59](#))
4. One optional <tfoot> element ([Section 2.61](#))

[2.58.1.](#) "align" Attribute

Controls whether the table appears left justified, centered (default), or right justified. The caption will be centered under the table, and the combined table and caption will be aligned according to the "align" attribute.

Allowed values:

- o "left"
- o "center" (default)
- o "right"

[2.58.2.](#) "anchor" Attribute

Document-wide unique identifier for this table.

[2.59.](#) <tbody>

A container for a set of body rows for a table.

This element appears as a child element of <table> ([Section 2.58](#)).

Content model:

One or more <tr> elements ([Section 2.65](#))

[2.59.1.](#) "anchor" Attribute

Document-wide unique identifier for the tbody.

[2.60.](#) <td>

A cell in a table row.

This element appears as a child element of <tr> ([Section 2.65](#)).

Content model:

Either:

In any order, but at least one of:

- * <artset> elements ([Section 2.5](#))
- * <artwork> elements ([Section 2.6](#))
- * <dl> elements ([Section 2.21](#))
- * <figure> elements ([Section 2.27](#))
- * elements ([Section 2.36](#))
- * <sourcecode> elements ([Section 2.52](#))
- * <t> elements ([Section 2.57](#))
- * elements ([Section 2.67](#))

Or:

In any order:

- * Text
- * <bcp14> elements ([Section 2.10](#))
- * <cref> elements ([Section 2.17](#))
- * elements ([Section 2.23](#))
- * <eref> elements ([Section 2.25](#))
- * <iref> elements ([Section 2.29](#))
- * <relref> elements ([Section 2.47](#))
- * elements ([Section 2.54](#))
- * <sub> elements ([Section 2.55](#))
- * <sup> elements ([Section 2.56](#))

- * `<tt>` elements ([Section 2.66](#))
- * `<xref>` elements ([Section 2.70](#))

[2.60.1.](#) "align" Attribute

Controls whether the content of the cell appears left justified (default), centered, or right justified. Note that "center" or "right" will probably only work well in cells with plain text; any other elements might make the contents render badly.

Allowed values:

- o "left" (default)
- o "center"
- o "right"

[2.60.2.](#) "anchor" Attribute

Document-wide unique identifier for the cell.

[2.60.3.](#) "colspan" Attribute

The number of columns that the cell is to span. For example, setting "colspan='3'" indicates that the cell occupies the same horizontal space as three cells of a row without any "colspan" attributes.

[2.60.4.](#) "rowspan" Attribute

The number of rows that the cell is to span. For example, setting "rowspan='3'" indicates that the cell occupies the same vertical space as three rows.

[2.61.](#) `<tfoot>`

A container for a set of footer rows for a table.

This element appears as a child element of `<table>` ([Section 2.58](#)).

Content model:

One or more `<tr>` elements ([Section 2.65](#))

[2.61.1.](#) "anchor" Attribute

Document-wide unique identifier for the tfoot.

[2.62.](#) <th>

A cell in a table row. When rendered, this will normally come out in boldface; other than that, there is no difference between this and the <td> element.

This element appears as a child element of <tr> ([Section 2.65](#)).

Content model:

Either:

In any order, but at least one of:

- * <artset> elements ([Section 2.5](#))
- * <artwork> elements ([Section 2.6](#))
- * <dl> elements ([Section 2.21](#))
- * <figure> elements ([Section 2.27](#))
- * elements ([Section 2.36](#))
- * <sourcecode> elements ([Section 2.52](#))
- * <t> elements ([Section 2.57](#))
- * elements ([Section 2.67](#))

Or:

In any order:

- * Text
- * <[bcp14](#)> elements ([Section 2.10](#))

- * <cref> elements ([Section 2.17](#))
- * elements ([Section 2.23](#))
- * <eref> elements ([Section 2.25](#))
- * <iref> elements ([Section 2.29](#))
- * <relref> elements ([Section 2.47](#))
- * elements ([Section 2.54](#))
- * <sub> elements ([Section 2.55](#))
- * <sup> elements ([Section 2.56](#))
- * <tt> elements ([Section 2.66](#))
- * <xref> elements ([Section 2.70](#))

[2.62.1.](#) "align" Attribute

Controls whether the content of the cell appears left justified (default), centered, or right justified. Note that "center" or "right" will probably only work well in cells with plain text; any other elements might make the contents render badly.

Allowed values:

- o "left" (default)
- o "center"
- o "right"

[2.62.2.](#) "anchor" Attribute

Document-wide unique identifier for the row.

[2.62.3.](#) "colspan" Attribute

The number of columns that the cell is to span. For example, setting "colspan='3'" indicates that the cell occupies the same horizontal space as three cells of a row without any "colspan" attributes.

[2.62.4.](#) "rowspan" Attribute

The number of rows that the cell is to span. For example, setting "rowspan='3'" indicates that the cell occupies the same vertical space as three rows.

[2.63.](#) <thead>

A container for a set of header rows for a table.

This element appears as a child element of <table> ([Section 2.58](#)).

Content model:

One or more <tr> elements ([Section 2.65](#))

[2.63.1.](#) "anchor" Attribute

Document-wide unique identifier for the thead.

[2.64.](#) <title>

Represents the document title.

When this element appears in the <front> element of the current document, the title might also appear in page headers or footers. If it is long (~40 characters), the "abbrev" attribute can be used to specify an abbreviated variant.

This element appears as a child element of <front> ([Section 2.28](#)).

Content model: only text content.

[2.64.1.](#) "abbrev" Attribute

Specifies an abbreviated variant of the document title.

[2.64.2.](#) "ascii" Attribute

The ASCII equivalent of the title.

[2.65.](#) <tr>

A row of a table.

This element appears as a child element of <tbody> ([Section 2.59](#)), <tfoot> ([Section 2.61](#)), and <thead> ([Section 2.63](#)).

Content model:

In any order, but at least one of:

- o <td> elements ([Section 2.60](#))
- o <th> elements ([Section 2.62](#))

[2.65.1.](#) "anchor" Attribute

Document-wide unique identifier for the row.

[2.66.](#) <tt>

Causes the text to be displayed in a constant-width font. This element can be combined with other character formatting elements, and the formatting will be additive.

This element appears as a child element of <annotation> ([Section 2.3](#)), <blockquote> ([Section 2.11](#)), <cref> ([Section 2.17](#)), <dd> ([Section 2.19](#)), <dt> ([Section 2.22](#)), ([Section 2.23](#)), ([Section 2.31](#)), <name> ([Section 2.34](#)), <preamble> ([Section 3.6](#)), <refcontent> ([Section 2.42](#)), ([Section 2.54](#)), <sub> ([Section 2.55](#)), <sup> ([Section 2.56](#)), <t> ([Section 2.57](#)), <td> ([Section 2.60](#)), and <th> ([Section 2.62](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.10](#))
- o <cref> elements ([Section 2.17](#))
- o elements ([Section 2.23](#))
- o <eref> elements ([Section 2.25](#))
- o <iref> elements ([Section 2.29](#))
- o <relref> elements ([Section 2.47](#))
- o elements ([Section 2.54](#))
- o <sub> elements ([Section 2.55](#))

- o <sup> elements ([Section 2.56](#))
- o <xref> elements ([Section 2.70](#))

**[2.67.](#) **

An unordered list. The labels on the items will be symbols picked by the formatter.

This element appears as a child element of <abstract> ([Section 2.1](#)), <aside> ([Section 2.7](#)), <blockquote> ([Section 2.11](#)), <dd> ([Section 2.19](#)), ([Section 2.31](#)), <note> ([Section 2.35](#)), <section> ([Section 2.49](#)), <td> ([Section 2.60](#)), and <th> ([Section 2.62](#)).

Content model:

One or more elements ([Section 2.31](#))

[2.67.1.](#) "anchor" Attribute

Document-wide unique identifier for the list.

[2.67.2.](#) "empty" Attribute

Defines whether or not the label is empty. empty="true" indicates that no label will be shown.

Allowed values:

- o "false" (default)
- o "true"

[2.67.3.](#) "spacing" Attribute

Defines whether or not there is a blank line between entries. spacing="normal" indicates a single blank line, while spacing="compact" indicates no space between.

Allowed values:

- o "normal" (default)
- o "compact"

[2.68.](#) `<uri>`

Contains a web address associated with the author.

The contents should be a valid URI; this most likely will be an "http:" or "https:" URI.

This element appears as a child element of `<address>` ([Section 2.2](#)).

Content model: only text content.

[2.69.](#) `<workgroup>`

This element is used to specify the Working Group (IETF) or Research Group (IRTF) from which the document originates, if any. The recommended format is the official name of the Working Group (with some capitalization).

In Internet-Drafts, this is used in the upper left corner of the boilerplate, replacing the "Network Working Group" string. Formatting software can append the words "Working Group" or "Research Group", depending on the "submissionType" property of the `<rfc>` element ([Section 2.48.12](#)).

This element appears as a child element of `<front>` ([Section 2.28](#)).

Content model: only text content.

[2.70.](#) `<xref>`

A reference to an anchor in this document. Formatters that have links (such as HTML and PDF) are likely to render `<xref>` elements as internal hyperlinks. This element is useful for referring to references in the "References" section, to specific sections of this document, to specific figures, and so on. The "target" attribute is required.

This element appears as a child element of `<annotation>` ([Section 2.3](#)), `<blockquote>` ([Section 2.11](#)), `<c>` ([Section 3.1](#)), `<cref>` ([Section 2.17](#)), `<dd>` ([Section 2.19](#)), `<dt>` ([Section 2.22](#)), `` ([Section 2.23](#)), `` ([Section 2.31](#)), `<name>` ([Section 2.34](#)), `<postamble>` ([Section 3.5](#)), `<preamble>` ([Section 3.6](#)), `` ([Section 2.54](#)), `<sub>` ([Section 2.55](#)), `<sup>` ([Section 2.56](#)), `<t>` ([Section 2.57](#)), `<td>` ([Section 2.60](#)), `<th>` ([Section 2.62](#)), `<tt>` ([Section 2.66](#)), and `<ttcol>` ([Section 3.9](#)).

Content model: only text content.

2.70.1. "format" Attribute

This attribute signals to formatters what the desired format of the reference should be. Formatters for document types that have linking capability should wrap the displayed text in hyperlinks.

"counter"

The "derivedContent" attribute will contain just a counter. This is used for targets that are <section>, <figure>, <table>, or items in an ordered list. Using "format='counter'" where the target is any other type of element is an error.

For example, with an input of:

```
<section anchor="overview">Protocol Overview</section>
. . .
See Section <xref target="overview" format="counter"/>
for an overview.
```

An HTML formatter might generate:

See Section 1.7 for an overview.

"default"

If the element has no content, the "derivedContent" attribute will contain a text fragment that describes the referenced part completely, such as "XML" for a target that is a <reference>, or "[Section 2](#)" or "Table 4" for a target to a non-reference. (If the element has content, the "derivedContent" attribute is filled with the content.)

For example, with an input of:

```
<section anchor="overview">Protocol Overview</section>
. . .
See <xref target="overview"/> for an overview.
```

An HTML formatter might generate:

See [Section 1.7](#) for an overview.

"none"

Deprecated.

"title"

If the target is a <reference> element, the "derivedContent" attribute will contain the name of the reference, extracted from the <title> child of the <front> child of the reference. Or, if the target element has a <name> child element, the "derivedContent" attribute will contain the text content of that <name> element concatenated with the text content of each descendant node of <name> (that is, stripping out all of the XML markup, leaving only the text). Or, if the target element does not contain a <name> child element, the "derivedContent" attribute will contain the name of the "anchor" attribute of that element with no other adornment.

Allowed values:

- o "default" (default)
- o "title"
- o "counter"
- o "none"

[2.70.2.](#) "pageno" Attribute

Deprecated.

Allowed values:

- o "true"
- o "false" (default)

[2.70.3.](#) "target" Attribute (Mandatory)

Identifies the document component being referenced. The value needs to match the value of the "anchor" attribute of an element in the document; otherwise, it is an error.

[3.](#) Elements from v2 That Have Been Deprecated

This section lists the elements from v2 that have been deprecated. Note that some elements in v3 have attributes from v2 that are deprecated; those are not listed here.

[3.1.](#) <c>

Deprecated. Instead, use <tr>, <td>, and <th>.

This element appears as a child element of <texttable> ([Section 3.8](#)).

Content model:

In any order:

- o Text
- o <cref> elements ([Section 2.17](#))
- o <eref> elements ([Section 2.25](#))
- o <iref> elements ([Section 2.29](#))
- o <spanx> elements ([Section 3.7](#))
- o <xref> elements ([Section 2.70](#))

[3.2.](#) <facsimile>

Deprecated. The <email> element is a much more useful way to get in touch with authors.

This element appears as a child element of <address> ([Section 2.2](#)).

Content model: only text content.

[3.3.](#) <format>

Deprecated. If the goal is to provide a single URI for a reference, use the "target" attribute in <reference> instead.

This element appears as a child element of <reference> ([Section 2.43](#)).

Content model: this element does not have any contents.

[3.3.1.](#) "octets" attribute

Deprecated.

[3.3.2.](#) "target" attribute

Deprecated.

[3.3.3.](#) "type" attribute (Mandatory)

Deprecated.

[3.4.](#) <list>

Deprecated. Instead, use <dl> for list/@style "hanging"; for list/@style "empty" or "symbols"; and for list/@style "letters", "numbers", "counter", or "format".

This element appears as a child element of <t> ([Section 2.57](#)).

Content model:

One or more <t> elements ([Section 2.57](#))

[3.4.1.](#) "counter" attribute

Deprecated. The functionality of this attribute has been replaced with /@start.

[3.4.2.](#) "hangIndent" attribute

Deprecated. Use <dl> instead.

[3.4.3.](#) "style" attribute

Deprecated.

[3.5.](#) <postamble>

Deprecated. Instead, use a regular paragraph after the figure or table.

This element appears as a child element of <figure> ([Section 2.27](#)) and <texttable> ([Section 3.8](#)).

Content model:

In any order:

- o Text
- o <cref> elements ([Section 2.17](#))

- o <eref> elements ([Section 2.25](#))
- o <iref> elements ([Section 2.29](#))
- o <spanx> elements ([Section 3.7](#))
- o <xref> elements ([Section 2.70](#))

[3.6.](#) <preamble>

Deprecated. Instead, use a regular paragraph before the figure or table.

This element appears as a child element of <figure> ([Section 2.27](#)) and <texttable> ([Section 3.8](#)).

Content model:

In any order:

- o Text
- o <bcp14> elements ([Section 2.10](#))
- o <cref> elements ([Section 2.17](#))
- o elements ([Section 2.23](#))
- o <eref> elements ([Section 2.25](#))
- o <iref> elements ([Section 2.29](#))
- o <relref> elements ([Section 2.47](#))
- o <spanx> elements ([Section 3.7](#))
- o elements ([Section 2.54](#))
- o <sub> elements ([Section 2.55](#))
- o <sup> elements ([Section 2.56](#))
- o <tt> elements ([Section 2.66](#))
- o <xref> elements ([Section 2.70](#))

[3.7.](#) <spanx>

Deprecated.

This element appears as a child element of <annotation> ([Section 2.3](#)), <c> ([Section 3.1](#)), <postamble> ([Section 3.5](#)), <preamble> ([Section 3.6](#)), and <t> ([Section 2.57](#)).

Content model: only text content.

[3.7.1.](#) "style" attribute

Deprecated. Instead of <spanx style="emph">, use ; instead of <spanx style="strong">, use ; instead of <spanx style="verb">, use <tt>.

[3.7.2.](#) "xml:space" attribute

Deprecated.

Allowed values:

- o "default"
- o "preserve" (default)

[3.8.](#) <texttable>

Deprecated. Use <table> instead.

This element appears as a child element of <section> ([Section 2.49](#)).

Content model:

In this order:

1. One optional <name> element ([Section 2.34](#))
2. One optional <preamble> element ([Section 3.6](#))
3. One or more <tocol> elements ([Section 3.9](#))
4. Optional <c> elements ([Section 3.1](#))
5. One optional <postamble> element ([Section 3.5](#))

3.8.1. "align" attribute

Deprecated.

Allowed values:

- o "left"
- o "center" (default)
- o "right"

3.8.2. "anchor" attribute

Deprecated.

3.8.3. "style" attribute

Deprecated.

Allowed values:

- o "all"
- o "none"
- o "headers"
- o "full" (default)

3.8.4. "suppress-title" attribute

Deprecated.

Allowed values:

- o "true"
- o "false" (default)

3.8.5. "title" attribute

Deprecated.

[3.9.](#) <ttcol>

Deprecated. Instead, use <tr>, <td>, and <th>.

This element appears as a child element of <texttable> ([Section 3.8](#)).

Content model:

In any order:

- o <cref> elements ([Section 2.17](#))
- o <eref> elements ([Section 2.25](#))
- o <iref> elements ([Section 2.29](#))
- o <xref> elements ([Section 2.70](#))
- o Text

[3.9.1.](#) "align" attribute

Deprecated.

Allowed values:

- o "left" (default)
- o "center"
- o "right"

[3.9.2.](#) "width" attribute

Deprecated.

[3.10.](#) <vspace>

Deprecated. In earlier versions of this format, <vspace> was often used to get an extra blank line in a list element; in the v3 vocabulary, that can be done instead by using multiple <t> elements inside the element. Other uses have no direct replacement.

This element appears as a child element of <t> ([Section 2.57](#)).

Content model: this element does not have any contents.

[3.10.1.](#) "blankLines" attribute

Deprecated.

[4.](#) SVG

The discussion of the use of SVG can be found in [[RFC7996](#)]. This element is part of the namespace "http://www.w3.org/2000/svg".

[5.](#) Use of CDATA Structures and Escaping

A common problem authors have with `<artwork>` and `<sourcecode>` elements is that the XML processor returns errors if the text in the artwork contains either the "&" or "<" character, or the string "]]>". To avoid these problems, the "&" and "<" characters may be escaped using the strings "&" and "<", respectively; the "]]>" string can be represented as "]]>". Alternatively, they may be surrounded in a CDATA structure: "`<![CDATA[]]>`". For example:

Desired output:

```
allowed-chars = "." | "," | "&" | "<" | ">" | "|"
```

Using escaping:

```
<sourcecode>
```

```
allowed-chars = "." | "," | "&amp;" | "&lt;" | "&gt;" | "|"
```

```
</sourcecode>
```

Using CDATA:

```
<sourcecode>
```

```
<![CDATA[ allowed-chars = "." | "," | "&" | "<" | ">" | "|"]]>
```

```
</sourcecode>
```

Using CDATA is not a panacea, but it does help prevent having to use escapes in places where using escapes can cause other problems, such as difficulty of inclusion from other documents.

[6.](#) Internationalization Considerations

This format is based on [[XML](#)] and thus does not have any issues representing arbitrary Unicode [[UNICODE](#)] characters in text content. The RFC Series Editor may restrict some of the characters that can be used in a particular RFC; the rules for such restrictions are covered in [[RFC7997](#)].

7. Security Considerations

The "name" attribute of the <artwork> element ([Section 2.6.5](#)) can be used to derive a filename for saving to a local file system. Trusting this kind of information without pre-processing is a known security risk; see [Section 4.3 of \[RFC6266\]](#) for more information.

The "src" attribute of the <artwork> element can be used to read files from the local system. Processing tools must be careful to not accept dangerous values for the filename, particularly those that contain absolute references outside the current directory.

The "type" attribute of the <artwork> and <sourcecode> elements is meant to encourage formatters to automatically extract known types of content from an RFC or Internet-Draft. While extraction is probably safe, those tools might also think that they could further process the extracted content, such as by rendering artwork or executing code. Doing so without first sanity-checking the extracted content is clearly a terrible idea from a security perspective. More generally, a tool that is reading XML input needs to be suspicious of any content that it intends to post-process.

When there is an external reference to a URL, a processor or renderer should fetch the content into a sandbox and should have only a localized impact on the document processing and rendering.

All security considerations related to XML processing are relevant as well (see [Section 7 of \[RFC3470\]](#)).

8. IANA Considerations

8.1. Internet Media Type Registration

IANA maintains the registry of Internet Media Types [[RFC6838](#)] at <https://www.iana.org/assignments/media-types>.

This document updates the specification for the Internet Media Type "application/rfc+xml" from the one in [[RFC7749](#)]. The following has been registered with IANA.

Type name: application

Subtype name: rfc+xml

Required parameters: There are no required parameters.

Optional parameters: "charset": This parameter has identical semantics to the charset parameter of the "application/xml" Media Type specified in [Section 9.1 of \[RFC7303\]](#).

Encoding considerations: Identical to those of "application/xml" as described in [Section 9.1 of \[RFC7303\]](#).

Security considerations: As defined in [Section 7](#). In addition, as this Media Type uses the "+xml" convention, it inherits the security considerations described in [Section 10 of \[RFC7303\]](#).

Interoperability considerations: Different implementations of this format have had interoperability issues. It is not expected that publication of this application will cause those implementations to be fixed.

Published specification: This specification.

Applications that use this Media Type: Applications that transform xml2rfc to output representations such as plain text or HTML, plus additional analysis tools.

Fragment identifier considerations: The "anchor" attribute is used for assigning document-wide unique identifiers that can be used as shorthand pointers, as described in [\[XPOINTER\]](#).

Additional information:

Deprecated alias names for this type: None

Magic number(s): As specified for "application/xml" in [\[RFC7303\]](#).

File extension(s): .xml or .rfcxml when disambiguation from other XML files is needed

Macintosh file type code(s): TEXT

Person & email address to contact for further information: See the Author's Address section of [RFC 7991](#).

Intended usage: COMMON

Restrictions on usage: None

Author: See the Author's Address section of [RFC 7991](#).

Change controller: RFC Series Editor (rse@rfc-editor.org)

8.2. Link Relation Registration

IANA has registered "convertedFrom" in the "Link Relation Types" registry [[LINKRELATIONS](#)].

Relation Name: convertedFrom

Description: The document linked to was later converted to the document that contains this link relation. For example, an RFC can have a link to the Internet-Draft that became the RFC; in that case, the link relation would be "convertedFrom".

Reference: This document.

Notes: This relation is different than "predecessor-version" in that "predecessor-version" is for items in a version control system. It is also different than "previous" in that this relation is used for converted resources, not those that are part of a sequence of resources.

Application Data: None

9. References

9.1. Normative References

[BCP14] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997, <<http://www.rfc-editor.org/info/bcp14>>.

[RFC7991] Hoffman, P., "The "xml2rfc" Version 3 Vocabulary", [RFC 7991](#), DOI 10.17487/RFC7991, December 2016, <<https://www.rfc-editor.org/info/rfc7991>>.

[XML] Bray, T., Paoli, J., Sperberg-McQueen, C., Maler, E., and F. Yergeau, "Extensible Markup Language (XML) 1.0 (Fifth Edition)", W3C Recommendation REC-xml-20081126, November 2008, <<https://www.w3.org/TR/2008/REC-xml-20081126/>>.

Latest version available at <<http://www.w3.org/TR/xml>>.

9.2. Informative References

[IDGUIDE] Housley, R., "Guidelines to Authors of Internet-Drafts", December 2010, <<https://www.ietf.org/id-info/guidelines.html>>.

[LINKRELATIONS]

- IANA, "Link Relations", <<https://www.iana.org/assignments/link-relations/link-relations.xhtml>>.
- [RFC2026] Bradner, S., "The Internet Standards Process -- Revision 3", [BCP 9](#), [RFC 2026](#), DOI 10.17487/RFC2026, October 1996, <<https://www.rfc-editor.org/info/rfc2026>>.
- [RFC2397] Masinter, L., "The "data" URL scheme", [RFC 2397](#), DOI 10.17487/RFC2397, August 1998, <<https://www.rfc-editor.org/info/rfc2397>>.
- [RFC2629] Rose, M., "Writing I-Ds and RFCs using XML", [RFC 2629](#), DOI 10.17487/RFC2629, June 1999, <<https://www.rfc-editor.org/info/rfc2629>>.
- [RFC3339] Klyne, G. and C. Newman, "Date and Time on the Internet: Timestamps", [RFC 3339](#), DOI 10.17487/RFC3339, July 2002, <<https://www.rfc-editor.org/info/rfc3339>>.
- [RFC3470] Hollenbeck, S., Rose, M., and L. Masinter, "Guidelines for the Use of Extensible Markup Language (XML) within IETF Protocols", [BCP 70](#), [RFC 3470](#), DOI 10.17487/RFC3470, January 2003, <<https://www.rfc-editor.org/info/rfc3470>>.
- [RFC3667] Bradner, S., "IETF Rights in Contributions", [RFC 3667](#), DOI 10.17487/RFC3667, February 2004, <<https://www.rfc-editor.org/info/rfc3667>>.
- [RFC3966] Schulzrinne, H., "The tel URI for Telephone Numbers", [RFC 3966](#), DOI 10.17487/RFC3966, December 2004, <<https://www.rfc-editor.org/info/rfc3966>>.
- [RFC3978] Bradner, S., Ed., "IETF Rights in Contributions", [RFC 3978](#), DOI 10.17487/RFC3978, March 2005, <<https://www.rfc-editor.org/info/rfc3978>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), DOI 10.17487/RFC5234, January 2008, <<https://www.rfc-editor.org/info/rfc5234>>.

- [RFC5378] Bradner, S., Ed. and J. Contreras, Ed., "Rights Contributors Provide to the IETF Trust", [BCP 78](#), [RFC 5378](#), DOI 10.17487/RFC5378, November 2008, <<https://www.rfc-editor.org/info/rfc5378>>.
- [RFC6068] Duerst, M., Masinter, L., and J. Zawinski, "The 'mailto' URI Scheme", [RFC 6068](#), DOI 10.17487/RFC6068, October 2010, <<https://www.rfc-editor.org/info/rfc6068>>.
- [RFC6266] Reschke, J., "Use of the Content-Disposition Header Field in the Hypertext Transfer Protocol (HTTP)", [RFC 6266](#), DOI 10.17487/RFC6266, June 2011, <<https://www.rfc-editor.org/info/rfc6266>>.
- [RFC6838] Freed, N., Klensin, J., and T. Hansen, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 6838](#), DOI 10.17487/RFC6838, January 2013, <<https://www.rfc-editor.org/info/rfc6838>>.
- [RFC6949] Flanagan, H. and N. Brownlee, "RFC Series Format Requirements and Future Development", [RFC 6949](#), DOI 10.17487/RFC6949, May 2013, <<https://www.rfc-editor.org/info/rfc6949>>.
- [RFC7303] Thompson, H. and C. Lilley, "XML Media Types", [RFC 7303](#), DOI 10.17487/RFC7303, July 2014, <<https://www.rfc-editor.org/info/rfc7303>>.
- [RFC7322] Flanagan, H. and S. Ginoza, "RFC Style Guide", [RFC 7322](#), DOI 10.17487/RFC7322, September 2014, <<https://www.rfc-editor.org/info/rfc7322>>.
- [RFC7669] Levine, J., "Assigning Digital Object Identifiers to RFCs", [RFC 7669](#), DOI 10.17487/RFC7669, October 2015, <<https://www.rfc-editor.org/info/rfc7669>>.
- [RFC7749] Reschke, J., "The "xml2rfc" Version 2 Vocabulary", [RFC 7749](#), DOI 10.17487/RFC7749, February 2016, <<https://www.rfc-editor.org/info/rfc7749>>.
- [RFC7841] Halpern, J., Ed., Daigle, L., Ed., and O. Kolkman, Ed., "RFC Streams, Headers, and Boilerplates", [RFC 7841](#), DOI 10.17487/RFC7841, May 2016, <<https://www.rfc-editor.org/info/rfc7841>>.
- [RFC7996] Brownlee, N., "SVG Drawings for RFCs: SVG 1.2 RFC", [RFC 7996](#), DOI 10.17487/RFC7996, December 2016, <<https://www.rfc-editor.org/info/rfc7996>>.

- [RFC7997] Flanagan, H., Ed., "The Use of Non-ASCII Characters in RFCs", [RFC 7997](#), DOI 10.17487/RFC7997, December 2016, <<https://www.rfc-editor.org/info/rfc7997>>.
- [RFC7998] Hoffman, P. and J. Hildebrand, "'xml2rfc' Version 3 Preparation Tool Description", [RFC 7998](#), DOI 10.17487/RFC7998, December 2016, <<https://www.rfc-editor.org/info/rfc7998>>.
- [RNC] Clark, J., "RELAX NG Compact Syntax", The Organization for the Advancement of Structured Information Standards (OASIS) , November 2002, <<https://www.oasis-open.org/committees/relax-ng/compact-20021121.html>>.
- [RNG] ISO/IEC, "Information Technology - Document Schema Definition Languages (DSDL) - Part 2: Regular-Grammar-Based Validation - RELAX NG (Second Edition)", ISO/IEC 19757-2:2008(E), December 2008.
- A useful source of RNG-related information is <<http://relaxng.org/>>.
- [TLP1.0] IETF Trust, "Legal Provisions Relating to IETF Documents", November 2008, <<http://trustee.ietf.org/license-info/IETF-TLP-1.htm>>.
- [TLP2.0] IETF Trust, "Legal Provisions Relating to IETF Documents", February 2009, <<http://trustee.ietf.org/license-info/IETF-TLP-2.htm>>.
- [TLP3.0] IETF Trust, "Legal Provisions Relating to IETF Documents", September 2009, <<http://trustee.ietf.org/license-info/IETF-TLP-3.htm>>.
- [TLP4.0] IETF Trust, "Legal Provisions Relating to IETF Documents", December 2009, <<http://trustee.ietf.org/license-info/IETF-TLP-4.htm>>.
- [TLP5.0] IETF Trust, "Legal Provisions Relating to IETF Documents", March 2015, <<http://trustee.ietf.org/license-info/IETF-TLP-5.htm>>.
- [UAX24] The Unicode Consortium, "UAX #24: Unicode Script Property", <<http://www.unicode.org/reports/tr24/>>.
- [UNICODE] The Unicode Consortium, "The Unicode Standard", <<http://www.unicode.org/versions/latest/>>.

[USASCII] American National Standards Institute, "Coded Character Set -- 7-bit American Standard Code for Information Interchange", ANSI X3.4, 1986.

[XInclude]

Marsh, J., Orchard, D., and D. Veillard, "XML Inclusions (XInclude) Version 1.0 (Second Edition)", W3C Recommendation REC-xinclude-20061115, November 2006, <<https://www.w3.org/TR/xinclude/REC-xinclude-20061115/>>.

Latest version available at <<http://www.w3.org/TR/xinclude/>>.

[XPOINTER]

Grosso, P., Maler, E., Marsh, J., and N. Walsh, "XPointer Framework", W3C Recommendation REC-xptr-framework-20030325, March 2003, <<http://www.w3.org/TR/2003/REC-xptr-framework-20030325/>>.

Latest version available at <<http://www.w3.org/TR/xptr-framework/>>.

Appendix A. Front-Page ("Boilerplate") Generation

The values listed here will be defined by the RFC Series Editor. Those listed here are believed to be the current values in use.

A.1. The "ipr" Attribute

This attribute value can take a long list of values, each of which describes an IPR policy for the document ([Section 2.48.5](#)). The values are not the result of a grand design, but they remain simply for historic reasons. Of these values, only a few are currently in use; all others are supported by various tools for backwards compatibility with old source files.

Note: Some variations of the boilerplate are selected based on the document's date; therefore, it is important to specify the "year", "month", and "day" attributes of the <date> element when archiving the XML source of an Internet-Draft on the day of submission.

Disclaimer: THIS ONLY PROVIDES IMPLEMENTATION INFORMATION. IF YOU NEED LEGAL ADVICE, PLEASE CONTACT A LAWYER. For further information, refer to <<http://trustee.ietf.org/docs/IETF-Copyright-FAQ.pdf>>.

For the current "Copyright Notice" text, the submissionType attribute of the <rfc> element ([Section 2.48.12](#)) determines whether a statement about "Code Components" is inserted (which is the case for the value "IETF", which is the default). Other values, such as "independent", suppress this part of the text.

A.1.1. Current Values: "*trust200902"

The name for these values refers to version 2.0 of the IETF Trust's "Legal Provisions Relating to IETF Documents", sometimes simply called the "TLP", which went into effect on February 15, 2009 [[TLP2.0](#)]. Updates to the document were published on September 12, 2009 [[TLP3.0](#)] and on December 28, 2009 [[TLP4.0](#)], modifying the license for code components (see <<http://trustee.ietf.org/license-info/>> for further information). The actual text is located in [Section 6](#) ("Text to Be Included in IETF Documents") of these documents.

The prep tool automatically produces the "correct" text, depending on the document's date information (see above):


```

+-----+-----+
| TLP      | starting with publication date |
+-----+-----+
| [TLP3.0] | 2009-11-01                      |
| [TLP4.0] | 2010-04-01                      |
+-----+-----+

```

The TLP was again updated in March 2015 [TLP5.0], but the changes made in that version do not affect the boilerplate text.

A.1.1.1. trust200902

This value should be used unless one of the more specific "*trust200902" values is a better fit. It produces the text in Sections 6.a and 6.b of the TLP.

A.1.1.2. noModificationTrust200902

This produces the additional text from [Section 6.c.i](#) of the TLP:

This document may not be modified, and derivative works of it may not be created, except to format it for publication as an RFC or to translate it into languages other than English.

Note: this clause is incompatible with RFCs that are published on the Standards Track.

A.1.1.3. noDerivativesTrust200902

This produces the additional text from [Section 6.c.ii](#) of the TLP:

This document may not be modified, and derivative works of it may not be created, and it may not be published except as an Internet-Draft.

Note: this clause is incompatible with RFCs.

A.1.1.4. pre5378Trust200902

This produces the additional text from [Section 6.c.iii](#) of the TLP, frequently called the "pre-5378 escape clause" referring to changes introduced in [[RFC5378](#)]:

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process.

Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

See [Section 4](#) of <<http://trustee.ietf.org/docs/IETF-Copyright-FAQ.pdf>> for further information about when to use this value.

Note: this text appears under "Copyright Notice", unless the document was published before November 2009, in which case it appears under "Status of This Memo".

[A.1.2.](#) Historic Values

[A.1.2.1.](#) Historic Values: "*trust200811"

The attribute values "trust200811", "noModificationTrust200811", and "noDerivativesTrust200811" are similar to their "trust200902" counterparts, except that they use text specified in [[TLP1.0](#)].

[A.1.2.2.](#) Historic Values: "*3978"

The attribute values "full3978", "noModification3978", and "noDerivatives3978" are similar to their counterparts above, except that they use text specified in [[RFC3978](#)].

[A.1.2.3.](#) Historic Values: "*3667"

The attribute values "full3667", "noModification3667", and "noDerivatives3667" are similar to their counterparts above, except that they use text specified in [[RFC3667](#)].

[A.1.2.4.](#) Historic Values: "*2026"

The attribute values "full2026" and "noDerivativeWorks2026" are similar to their counterparts above, except that they use text specified in [Section 10 of \[RFC2026\]](#).

The special value "none" was also used back then; it denied the IETF any rights beyond publication as an Internet-Draft.

[A.2.](#) The "submissionType" Attribute

The RFC Editor publishes documents from different "document streams", of which the "IETF stream" is the most prominent. Other streams are the "Independent Submissions stream" (used for things such as

discussion of Internet-related technologies that are not part of the IETF agenda), the "IAB stream" (Internet Architecture Board), and the "IRTF stream" (Internet Research Task Force).

The values for the attribute are "IETF" (the default value), "independent", "IAB", and "IRTF".

Historically, this attribute did not affect the final appearance of RFCs, except for subtle differences in copyright notices. Nowadays (as of [\[RFC7841\]](#)), the stream name appears in the first line of the front page, and it also affects the text in the "Status of This Memo" section.

For current documents, setting the "submissionType" attribute will have the following effect:

- o For RFCs, the stream name appears in the upper left corner of the first page (in Internet-Drafts, this is either "Network Working Group" or the value of the <workgroup> element).
- o For RFCs, it affects the whole "Status of This Memo" section (see [Section 3.2 of \[RFC7841\]](#)).
- o For all RFCs and Internet-Drafts, it determines whether the "Copyright Notice" section mentions the Copyright on Code Components (see [Section 6](#) of the TLP ("Text to Be Included in IETF Documents"))).

[A.3.](#) The "consensus" Attribute

For some of the publication streams (see [Appendix A.2](#)), the "Status of This Memo" section depends on whether there was a consensus to publish (again, see [Section 3.4 of \[RFC7841\]](#)).

The consensus attribute can be used to supply this information. The acceptable values are "true" (the default) and "false"; "yes" and "no" from v2 are deprecated.

The effect of this value for the various streams is:

- o "independent": none.
- o "IAB": mention that there was an IAB consensus.
- o "IETF": mention that there was an IETF consensus.

- o "IRTF": mention that there was a research group consensus (where the name of the research group is extracted from the <workgroup> element).

Appendix B. The v3 Format and Processing Tools

This section describes topics that are specific to v3 processing tools. Note that there is some discussion of tools in the main body of the document as well. For example, some elements have descriptions of how a processing tool might create output from the element.

The expected design of the tools that will be used with v3 documents includes:

- o A "prep tool" that takes a v3 document, makes many checks, adds and changes many attribute values, and creates a file that is a "prepared document". The prepared document is a valid v3 document. The prep tool is described in [[RFC7998](#)].

The prep tool is expected to have many modes:

- * RFC mode -- The mode used by the RFC Editor to process the input from one of the RFC streams and to process XML produced during the RFC editing process. The restrictions on the canonical XML for RFCs, as well as how the non-canonical formats will look, are described at <<https://www.rfc-editor.org/rse/wiki/doku.php?id=design:format-and-content-rfcs>>.
- * Draft mode -- The mode used by the Internet-Draft submission tool. The restrictions for the XML from this mode will be described later.
- * Diagnostic mode -- A mode that can be used by document authors to look for errors or warnings before they submit their documents for publication.
- * Consolidation mode -- Produces output where no external resources are required to render the file output. This includes expanding the XInclude entities and DTD entities in place, and changing all elements that have "src" attributes with external links into either "data:" URI or content for the element, as specified in [[RFC7998](#)].

- o Formatting tools that will create HTML, PDF, plain text, and possibly other output formats. These formatters will be created by the IETF, but others can create such tools as well. The IETF tools are expected to take prepared documents as input.

There may also be processing tools that are meant to run on the computers of authors. These tools may be used to produce interim versions of the non-canonical representations so that authors can see how their XML might later be rendered, to create documents in representations different than those supported by the RFC Editor, to possibly create documents that are not meant to be Internet-Drafts or RFCs, and to convert XML that has external information into XML that has that external information included.

The prep tool is expected to have clear error reporting, giving more context than just a line number. For example, the error messages should differentiate between errors in XML and those from the v3 format.

In v2, the grammar was specified as a DTD. In v3, the grammar is specified only as RELAX Next Generation (RNG). This means that tools need to work from the RNG, not from a DTD. Some of the features of the v3 grammar cannot be specified as a DTD.

B.1. Including External Text with XInclude

All tools for the v3 format are expected to support XInclude [[XInclude](#)]. XInclude specifies a processing model and syntax for general-purpose inclusion of information that is either on the Internet or local to the user's computer.

In the v3 syntax, XInclude is expressed as the `<xi:include>` element. To use this element, you need to include the "xi" namespace in the `<rfc>` element; that is, you need to specify

```
xmlns:xi="http://www.w3.org/2001/XInclude"
```

as one of the attributes in the `<rfc>` element.

The most common way to use `<xi:include>` is to pull in references that are already formed as XML. Currently, this can be done from `xml2rfc.tools.ietf.org`, but later this is expected to be from the RFC Editor. For example, if a document has three normative references, all RFCs, the document might contain:


```
<references>
  <xi:include href="http://xml2rfc.tools.ietf.org/public/rfc/
    bibxml/reference.RFC.2119.xml"/>
  <xi:include href="http://xml2rfc.tools.ietf.org/public/rfc/
    bibxml/reference.RFC.4869.xml"/>
  <xi:include href="http://xml2rfc.tools.ietf.org/public/rfc/
    bibxml/reference.RFC.7169.xml"/>
</references>
```

<xi:include> can be used anywhere an XML element could be used (but not where free text is used). For example, if three Internet-Drafts are all including a particular paragraph or section verbatim, that text can be kept either in a file or somewhere on the web and can be included with <xi:include>. An example of pulling something from the local disk would be:

```
<x:include href="file://home/chris/ietf/drafts/commoncontext.xml"/>
```

In general, XInclude should be used instead of ENTITY references and XML Processing Instructions (PIs) that allow external inclusions.

B.2. Anchors and IDs

People writing and reading Internet-Drafts and RFCs often want to make reference to specific locations in those documents. In the case of RFC authors, it is common to want to reference another part of their document, such as "see [Section 3.2](#) of this document." Readers, on the other hand, want to reference parts of documents that they didn't write, such as "see [Section 3.2 of RFC 6949](#)." The XML vocabulary in this document attempts to support both sets of people.

Authors can leave anchors in a document that can later be used for references with the "anchor" attribute. Anchors can be included in the numerous elements. The author can then refer to that anchor in the "target" attribute of the <xref> element.

Readers can refer to any element that has an "anchor" attribute by that attribute. Note, however, that most of the time, elements won't have anchors. In the common case, the reader wants to refer to an element that does not have an "anchor" attribute, but that element has a "pn" attribute.

Processing tools add the "pn" attribute to many elements during processing. This attribute and its value are automatically generated by the tool if the attribute is not there; if the attribute is already there, the tool may replace the value.

B.2.1. Overlapping Values

In the HTML representation of this XML vocabulary, both anchors and "pn" attributes will be used in the "id" attributes of elements. Thus, there can be no overlap between the names entered in "anchor" attributes, in "slugifiedName" attributes, and those that are generated for the "pn" attributes. Also, there are some values for the "anchor" values that are reserved for sections, and those sections can only have those anchor values.

The following rules prevent this overlap:

- o "pn" for regular sections always has the format "s-nnn", where "nnn" is the section number, or the appendix identifier (which starts with a letter). For example, this would be "s-2.1.3" for [Section 2.1.3](#) and "s-a" for [Appendix A](#). For the <abstract> element, it is always "s-abstract". For the <note> element, it is always "s-note-nnn", where "nnn" is a sequential value. For sections in the <boilerplate> element, it is always "s-boilerplate-nnn", where "nnn" is a sequential value.
- o "pn" for <references> elements has the format "s-nnn". It is important to note that "nnn" is a number, not letters, even though the <references> appear in the back. It is the number that is one higher than the highest top-level section number in <middle>. If there are two or more <references>, "nnn" will include a dot as if the <references> are a subsection of a section that is numbered one higher than the highest top-level section number in <middle>.
- o "pn" for <figure> elements always has the format "f-nnn", where "nnn" is the figure number. For example, this would be "f-5" for Figure 5.
- o "pn" for <ieref> elements always has the format "i-ttt-nnn", where "ttt" is the slugified item (plus a hyphen and the slugified subitem if there is a subitem), and "nnn" is the instance of that item/subitem pair. For example, this would be "i-foo-1" for "<ieref item='foo'>" and "i-foo-bar-1" for "<ieref item='foo' subitem='bar'>".
- o "pn" for <table> elements always has the format "t-nnn", where "nnn" is the table number. For example, this would be "t-5" for Table 5.
- o "pn" for all elements not listed above always has the format "p-nnn-mmm", where "nnn" is the section number and "mmm" is the relative position in the section. For example, this would be "p-2.1.3-7" for the seventh part number in [Section 2.1.3](#).

- o "slugifiedName" always has the format "n-ttt", where "ttt" is the text of the name after slugification. For example, this would be "n-protocol-overview" for the name "Protocol Overview". The actual conversions done in slugification will be specified at a later time.
- o Anchors must never overlap with any of the above. The easiest way to assure that is to not pick an anchor name that starts with a single letter followed by a hyphen. If an anchor does overlap with one of the types of names above, the processing tool will reject the document.

B.3. Attributes Controlled by the Prep Tool

Many elements in the v3 vocabulary have new attributes whose role is to hold values generated by the prep tool. These attributes can exist in documents that are input to the prep tool; however, any of these attributes might be added, removed, or changed by the prep tool. Thus, it is explicitly unsafe for a document author to include these attributes and expect that their values will survive processing by the prep tool.

The attributes that are controlled by the prep tool are:

- o The "pn" attribute in any element -- The number for this item within the section. The numbering is shared with other elements of a section. The "pn" attribute is added to many block-level elements inside sections.
- o <artwork> originalSrc -- This attribute is filled with the original value of the "src" attribute if that attribute is removed by the prep tool.
- o <figure> originalSrc -- This attribute is filled with the original value of the "src" attribute if that attribute is removed by the prep tool.
- o <name> "slugifiedName" attribute -- This attribute is filled with a "slugified" version of the text in the element. This attribute can be used in the output formats for elements that have both names and numbers.
- o <relref> "derivedLink" attribute -- This attribute is filled with the link that is derived from combining the URI from the reference and the relative part that is either a copy of the "relative" attribute or a section number derived from the "section" attribute.

- o `<rfc>` "expiresDate" attribute -- This attribute is filled with the date that an Internet-Draft expires. The date is in the format yyyy-mm-dd.
- o `<rfc>` "mode" attribute -- This attribute is filled with a string that indicates what mode the prep tool was in when it processed the XML, such as whether it was processing a file to become an Internet-Draft or an RFC.
- o `<rfc>` "scripts" attribute -- This attribute is filled with a list of scripts needed to render this document. The list is comma-separated, with no spaces allowed. The order is unimportant. The names come from [UAX24]. For example, if the document has Chinese characters in it, the value might be "Common, Latin, Han".
- o `<sourcecode>` "originalSrc" attribute -- This attribute is filled with the original value of the "src" attribute if that attribute is removed by the prep tool.
- o `<xref>` "derivedContent" attribute -- This attribute is filled in if there is no content in the `<xref>` element. The value for this attribute is based on the value in the "displayFormat" attribute. Examples of how this value is filled can be found in [Section 2.70.1](#).

In addition, note that the contents of the `<boilerplate>` element are controlled by the prep tool.

[Appendix C](#). RELAX NG Schema

The following is the RELAX NG schema for the v3 format.

```
namespace a = "http://relaxng.org/ns/compatibility/annotations/1.0"

# xml2rfc Version 3 grammar

rfc =
  element rfc {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute number { text }?,
    [ a:defaultValue = "" ] attribute obsoletes { text }?,
    [ a:defaultValue = "" ] attribute updates { text }?,
    attribute category { text }?,
    attribute mode { text }?,
    [ a:defaultValue = "false" ]
    attribute consensus { "no" | "yes" | "false" | "true" }?,
```



```
    attribute seriesNo { text }?,
    attribute ipr { text }?,
    attribute iprExtract { xsd:IDREF }?,
    [ a:defaultValue = "IETF" ]
    attribute submissionType {
      "IETF" | "IAB" | "IRTF" | "independent"
    }?,
    attribute docName { text }?,
    [ a:defaultValue = "false" ]
    attribute sortRefs { "true" | "false" }?,
    [ a:defaultValue = "true" ]
    attribute symRefs { "true" | "false" }?,
    [ a:defaultValue = "true" ]
    attribute tocInclude { "true" | "false" }?,
    [ a:defaultValue = "3" ] attribute tocDepth { text }?,
    attribute prepTime { text }?,
    [ a:defaultValue = "true" ]
    attribute indexInclude { "true" | "false" }?,
    attribute version { text }?,
    [ a:defaultValue = "Common, Latin" ] attribute scripts { text }?,
    attribute expiresDate { text }?,
    link*,
    front,
    middle,
    back?
  }
```

link =

```
  element link {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute href { text },
    attribute rel { text }?
  }
```

front =

```
  element front {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    title,
    seriesInfo*,
    author+,
    date?,
    area*,
    workgroup*,
    keyword*,
    abstract?,
    note*,
```



```
    boilerplate?
  }

title =
  element title {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute abbrev { text }?,
    attribute ascii { text }?,
    text
  }

author =
  element author {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute initials { text }?,
    attribute asciiInitials { text }?,
    attribute surname { text }?,
    attribute asciiSurname { text }?,
    attribute fullname { text }?,
    attribute role { "editor" }?,
    attribute asciiFullname { text }?,
    organization?,
    address?
  }

organization =
  element organization {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute abbrev { text }?,
    attribute ascii { text }?,
    attribute asciiAbbrev { text }?,
    [ a:defaultValue = "true" ]
    attribute showOnFrontPage { "true" | "false" }?,
    text
  }

address =
  element address {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    postal?,
    phone?,
    facsimile?,
    email?,
    uri?
```



```
}
```

```
postal =
```

```
  element postal {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    ((city  
      | cityarea  
      | code  
      | country  
      | extaddr  
      | pobox  
      | region  
      | sortingcode  
      | street)*  
      | postalLine+)  
  }
```

```
cityarea =
```

```
  element cityarea {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```

```
extaddr =
```

```
  element extaddr {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```

```
pobox =
```

```
  element pobox {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```

```
sortingcode =
```

```
  element sortingcode {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```



```
}
```

```
street =
```

```
  element street {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```

```
city =
```

```
  element city {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```

```
region =
```

```
  element region {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```

```
code =
```

```
  element code {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```

```
country =
```

```
  element country {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```

```
postallLine =
```

```
  element postallLine {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```



```
}
```

```
phone =
```

```
  element phone {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    text  
  }
```

```
facsimile =
```

```
  element facsimile {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    text  
  }
```

```
email =
```

```
  element email {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute ascii { text }?,  
    text  
  }
```

```
uri =
```

```
  element uri {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    text  
  }
```

```
date =
```

```
  element date {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute day { text }?,  
    attribute month { text }?,  
    attribute year { text }?,  
    empty  
  }
```

```
area =
```

```
  element area {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    text  
  }
```



```
workgroup =
  element workgroup {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    text
  }

keyword =
  element keyword {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    text
  }

abstract =
  element abstract {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    (dl | ol | t | ul)+
  }

note =
  element note {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute title { text }?,
    attribute pn { text }?,
    [ a:defaultValue = "false" ]
    attribute removeInRFC { "true" | "false" }?,
    name?,
    (dl | ol | t | ul)+
  }

boilerplate =
  element boilerplate {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    section+
  }

middle =
  element middle {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    section+
  }
```



```
section =
  element section {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    attribute title { text }?,
    [ a:defaultValue = "true" ]
    attribute numbered { "true" | "false" }?,
    [ a:defaultValue = "default" ]
    attribute toc { "include" | "exclude" | "default" }?,
    [ a:defaultValue = "false" ]
    attribute removeInRFC { "true" | "false" }?,
    name?,
    (artset
     | artwork
     | aside
     | blockquote
     | dl
     | figure
     | iref
     | ol
     | sourcecode
     | t
     | table
     | texttable
     | ul)*,
    section*
  }

name =
  element name {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute slugifiedName { text }?,
    (text
     | bcp14
     | cref
     | em
     | eref
     | iref
     | relref
     | strong
     | sub
     | sup
     | tt
     | xref)*
  }
```



```
t =
  element t {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    attribute hangText { text }?,
    [ a:defaultValue = "false" ]
    attribute keepWithNext { "false" | "true" }?,
    [ a:defaultValue = "false" ]
    attribute keepWithPrevious { "false" | "true" }?,
    (text
     | bcp14
     | cref
     | em
     | eref
     | iref
     | \list
     | relref
     | spanx
     | strong
     | sub
     | sup
     | tt
     | vspace
     | xref)*
  }

aside =
  element aside {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    (artset | artwork | dl | figure | iref | ol | t | table | ul)*
  }

blockquote =
  element blockquote {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    attribute cite { text }?,
    attribute quotedFrom { text }?,
    ((artset
     | artwork
     | dl
```



```
| figure
| ol
| sourcecode
| t
| table
| ul)+
| (text
  | bcp14
  | cref
  | em
  | eref
  | iref
  | relref
  | strong
  | sub
  | sup
  | tt
  | xref)+
}

\list =
element list {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  [ a:defaultValue = "empty" ] attribute style { text }?,
  attribute hangIndent { text }?,
  attribute counter { text }?,
  attribute pn { text }?,
  t+
}

ol =
element ol {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  [ a:defaultValue = "1" ] attribute type { text }?,
  [ a:defaultValue = "1" ] attribute start { text }?,
  attribute group { text }?,
  [ a:defaultValue = "normal" ]
  attribute spacing { "normal" | "compact" }?,
  attribute pn { text }?,
  li+
}

ul =
element ul {
  attribute xml:base { text }?,
```



```
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    [ a:defaultValue = "normal" ]
    attribute spacing { "normal" | "compact" }?,
    ([ a:defaultValue = "false" ]
     attribute empty { "false" | "true" },
     attribute pn { text }?)?,
    li+
  }

li =
element li {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  attribute pn { text }?,
  ((artset
   | artwork
   | blockquote
   | dl
   | figure
   | ol
   | sourcecode
   | t
   | ul)+
  | (text
   | bcp14
   | cref
   | em
   | eref
   | iref
   | relref
   | strong
   | sub
   | sup
   | tt
   | xref)+)
}

dl =
element dl {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  [ a:defaultValue = "normal" ]
  attribute spacing { "normal" | "compact" }?,
  [ a:defaultValue = "true" ]
  attribute newline { "false" | "true" }?,
```



```
[ a:defaultValue = "0" ] attribute indent { text }?,
attribute pn { text }?,
(dt, dd)+
}

dt =
element dt {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  attribute pn { text }?,
  (text
  | bcp14
  | cref
  | em
  | eref
  | iref
  | relref
  | strong
  | sub
  | sup
  | tt
  | xref)*
}

dd =
element dd {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  attribute pn { text }?,
  ((artset | artwork | dl | figure | ol | sourcecode | t | ul)+
  | (text
  | bcp14
  | cref
  | em
  | eref
  | iref
  | relref
  | strong
  | sub
  | sup
  | tt
  | xref)+)
}

xref =
element xref {
```



```
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute target { xsd:IDREF },
    [ a:defaultValue = "false" ]
    attribute pageno { "true" | "false" }?,
    [ a:defaultValue = "default" ]
    attribute format { "default" | "title" | "counter" | "none" }?,
    attribute derivedContent { text }?,
    text
  }

relref =
  element relref {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute target { xsd:IDREF },
    [ a:defaultValue = "of" ]
    attribute displayFormat { "of" | "comma" | "parens" | "bare" }?,
    attribute section { text },
    attribute relative { text }?,
    attribute derivedLink { text }?,
    text
  }

eref =
  element eref {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute target { text },
    text
  }

iref =
  element iref {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute item { text },
    [ a:defaultValue = "" ] attribute subitem { text }?,
    [ a:defaultValue = "false" ]
    attribute primary { "true" | "false" }?,
    attribute pn { text }?,
    empty
  }

cref =
  element cref {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
```



```
    attribute anchor { xsd:ID }?,
    attribute source { text }?,
    [ a:defaultValue = "true" ]
    attribute display { "true" | "false" }?,
    (text | em | eref | relref | strong | sub | sup | tt | xref)*
  }

tt =
  element tt {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text
     | bcp14
     | cref
     | em
     | eref
     | iref
     | relref
     | strong
     | sub
     | sup
     | xref)*
  }

strong =
  element strong {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text
     | bcp14
     | cref
     | em
     | eref
     | iref
     | relref
     | sub
     | sup
     | tt
     | xref)*
  }

em =
  element em {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text
     | bcp14
     | cref
```



```
    |eref  
    |iref  
    |relref  
    |strong  
    |sub  
    |sup  
    |tt  
    |xref)*  
}
```

sub =

```
element sub {  
  attribute xml:base { text }?,  
  attribute xml:lang { text }?,  
  (text  
  | bcp14  
  | cref  
  | em  
  |eref  
  |iref  
  |relref  
  |strong  
  |tt  
  |xref)*  
}
```

sup =

```
element sup {  
  attribute xml:base { text }?,  
  attribute xml:lang { text }?,  
  (text  
  | bcp14  
  | cref  
  | em  
  |eref  
  |iref  
  |relref  
  |strong  
  |tt  
  |xref)*  
}
```

spanx =

```
element spanx {  
  attribute xml:base { text }?,  
  attribute xml:lang { text }?,  
  [ a:defaultValue = "preserve" ]  
  attribute xml:space { "default" | "preserve" }?,
```



```
    [ a:defaultValue = "emph" ] attribute style { text }?,
    text
  }
```

```
vspace =
  element vspace {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    [ a:defaultValue = "0" ] attribute blankLines { text }?,
    empty
  }
```

```
figure =
  element figure {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    [ a:defaultValue = "" ] attribute title { text }?,
    [ a:defaultValue = "false" ]
    attribute suppress-title { "true" | "false" }?,
    attribute src { text }?,
    attribute originalSrc { text }?,
    [ a:defaultValue = "left" ]
    attribute align { "left" | "center" | "right" }?,
    [ a:defaultValue = "" ] attribute alt { text }?,
    [ a:defaultValue = "" ] attribute width { text }?,
    [ a:defaultValue = "" ] attribute height { text }?,
    name?,
    iref*,
    preamble?,
    (artset | artwork | sourcecode)+,
    postamble?
  }
```

```
table =
  element table {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    [ a:defaultValue = "center" ]
    attribute align { "left" | "center" | "right" }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    name?,
    thead?,
    tbody+,
    tfoot?
  }
```


preamble =

```
element preamble {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  (text
  | bcp14
  | cref
  | em
  |eref
  | iref
  | relref
  | spanx
  | strong
  | sub
  | sup
  | tt
  | xref)*
}
```

artset =

```
element artset {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  attribute pn { text }?,
  artwork+
}
```

artwork =

```
element artwork {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  attribute pn { text }?,
  attribute xml:space { text }?,
  [ a:defaultValue = "" ] attribute name { text }?,
  [ a:defaultValue = "" ] attribute type { text }?,
  attribute src { text }?,
  [ a:defaultValue = "left" ]
  attribute align { "left" | "center" | "right" }?,
  [ a:defaultValue = "" ] attribute alt { text }?,
  [ a:defaultValue = "" ] attribute width { text }?,
  [ a:defaultValue = "" ] attribute height { text }?,
  attribute originalSrc { text }?,
  (text* | svg)
}
```

TODO: replace with link to RSE site, or provide an inline version
include "svg.rnc"


```
sourcecode =
  element sourcecode {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    attribute pn { text }?,
    [ a:defaultValue = "" ] attribute name { text }?,
    [ a:defaultValue = "" ] attribute type { text }?,
    attribute src { text }?,
    attribute originalSrc { text }?,
    text
  }

thead =
  element thead {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    tr+
  }

tbody =
  element tbody {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    tr+
  }

tfoot =
  element tfoot {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    tr+
  }

tr =
  element tr {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID }?,
    (td | th)+
  }

td =
  element td {
    attribute xml:base { text }?,
```



```
attribute xml:lang { text }?,
attribute anchor { xsd:ID }?,
[ a:defaultValue = "0" ] attribute colspan { text }?,
[ a:defaultValue = "0" ] attribute rowspan { text }?,
[ a:defaultValue = "left" ]
attribute align { "left" | "center" | "right" }?,
((artset | artwork | dl | figure | ol | sourcecode | t | ul)+
 | (text
   | bcp14
   | cref
   | em
   | eref
   | iref
   | relref
   | strong
   | sub
   | sup
   | tt
   | xref)*)
}

th =
element th {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  attribute anchor { xsd:ID }?,
  [ a:defaultValue = "0" ] attribute colspan { text }?,
  [ a:defaultValue = "0" ] attribute rowspan { text }?,
  [ a:defaultValue = "left" ]
  attribute align { "left" | "center" | "right" }?,
  ((artset | artwork | dl | figure | ol | sourcecode | t | ul)+
   | (text
     | bcp14
     | cref
     | em
     | eref
     | iref
     | relref
     | strong
     | sub
     | sup
     | tt
     | xref)*)
}

postamble =
element postamble {
  attribute xml:base { text }?,
```



```
    attribute xml:lang { text }?,  
    (text | cref | eref | iref | spanx | xref)*  
  }
```

texttable =

```
  element texttable {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute anchor { xsd:ID }?,  
    [ a:defaultValue = "" ] attribute title { text }?,  
    [ a:defaultValue = "false" ]  
    attribute suppress-title { "true" | "false" }?,  
    [ a:defaultValue = "center" ]  
    attribute align { "left" | "center" | "right" }?,  
    [ a:defaultValue = "full" ]  
    attribute style { "all" | "none" | "headers" | "full" }?,  
    name?,  
    preamble?,  
    ttcoll+,  
    c*,  
    postamble?  
  }
```

ttcol =

```
  element ttcol {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    attribute width { text }?,  
    [ a:defaultValue = "left" ]  
    attribute align { "left" | "center" | "right" }?,  
    (cref | eref | iref | xref | text)*  
  }
```

c =

```
  element c {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    (text | cref | eref | iref | spanx | xref)*  
  }
```

[bcp14](#) =

```
  element bcp14 {  
    attribute xml:base { text }?,  
    attribute xml:lang { text }?,  
    text  
  }
```

back =


```
element back {
  attribute xml:base { text }?,
  attribute xml:lang { text }?,
  displayreference*,
  references,
  section*
}

displayreference =
  element displayreference {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute target { xsd:IDREF },
    attribute to { text }
  }

references =
  element references {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute pn { text }?,
    attribute anchor { xsd:ID }?,
    attribute title { text }?,
    name?,
    (references+ | (reference | referencegroup)*)
  }

reference =
  element reference {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID },
    attribute target { text }?,
    [ a:defaultValue = "true" ]
    attribute quote-title { "true" | "false" }?,
    front,
    (annotation | format | refcontent | seriesInfo)*
  }

referencegroup =
  element referencegroup {
    attribute xml:base { text }?,
    attribute target { text }?,
    attribute xml:lang { text }?,
    attribute anchor { xsd:ID },
    reference+
  }
```



```
seriesInfo =
  element seriesInfo {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute name { text },
    attribute value { text },
    attribute asciiName { text }?,
    attribute asciiValue { text }?,
    attribute status { text }?,
    [ a:defaultValue = "IETF" ]
    attribute stream { "IETF" | "IAB" | "IRTF" | "independent" }?,
    empty
  }

format =
  element format {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    attribute target { text }?,
    attribute type { text },
    attribute octets { text }?,
    empty
  }

annotation =
  element annotation {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text
     | bcp14
     | cref
     | em
     |eref
     | iref
     | relref
     | spanx
     | strong
     | sub
     | sup
     | tt
     | xref)*
  }

refcontent =
  element refcontent {
    attribute xml:base { text }?,
    attribute xml:lang { text }?,
    (text | bcp14 | em | strong | sub | sup | tt)*
```



```

}
start |= rfc

```

[Appendix D](#). Schema Differences from v2

The following is a non-normative comparison of the v3 format to the v2 format. A "-" indicates lines removed from the v2 schema, and a "+" indicates lines added to the v3 schema.

```

namespace a =
  "http://relaxng.org/ns/compatibility/annotations/1.0"

+ # xml2rfc Version 3 grammar
  rfc =
    element rfc {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
      attribute number { text }?,
      [ a:defaultValue = "" ] attribute obsoletes { text }?,
      [ a:defaultValue = "" ] attribute updates { text }?,
-     attribute category { "std" | "bcp" | "info" | "exp" |
- "historic" }?,
-     attribute consensus { "no" | "yes" }?,
+     attribute category { text }?,
+     attribute mode { text }?,
+     [ a:defaultValue = "false" ]
+     attribute consensus { "no" | "yes" | "false" | "true" }?,
      attribute seriesNo { text }?,
-     attribute ipr {
-       "full2026"
-       | "noDerivativeWorks2026"
-       | "none"
-       | "full3667"
-       | "noModification3667"
-       | "noDerivatives3667"
-       | "full3978"
-       | "noModification3978"
-       | "noDerivatives3978"
-       | "trust200811"
-       | "noModificationTrust200811"
-       | "noDerivativesTrust200811"
-       | "trust200902"
-       | "noModificationTrust200902"
-       | "noDerivativesTrust200902"
-       | "pre5378Trust200902"
-     }?,

```



```
+   attribute ipr { text }?,
+   attribute iprExtract { xsd:IDREF }?,
+   [ a:defaultValue = "IETF" ]
+   attribute submissionType {
+     "IETF" | "IAB" | "IRTF" | "independent"
+   }?,
+   attribute docName { text }?,
-   [ a:defaultValue = "en" ] attribute xml:lang { text }?,
+   [ a:defaultValue = "false" ]
+   attribute sortRefs { "true" | "false" }?,
+   [ a:defaultValue = "true" ]
+   attribute symRefs { "true" | "false" }?,
+   [ a:defaultValue = "true" ]
+   attribute tocInclude { "true" | "false" }?,
+   [ a:defaultValue = "3" ] attribute tocDepth { text }?,
+   attribute prepTime { text }?,
+   [ a:defaultValue = "true" ]
+   attribute indexInclude { "true" | "false" }?,
+   attribute version { text }?,
+   [ a:defaultValue = "Common, Latin" ] attribute scripts { text
+ }?,
+   attribute expiresDate { text }?,
+   link*,
+   front,
+   middle,
+   back?
+ }
+ link =
+ element link {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute href { text },
+   attribute rel { text }?
+ }
front =
  element front {
-   title, author+, date, area*, workgroup*, keyword*, abstract?,
- note*
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   title,
+   seriesInfo*,
+   author+,
+   date?,
+   area*,
+   workgroup*,
+   keyword*,
+   abstract?,
```



```
+   note*,
+   boilerplate?
  }
  title =
    element title {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
    attribute abbrev { text }?,
+   attribute ascii { text }?,
    text
  }
  author =
    element author {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
    attribute initials { text }?,
+   attribute asciiInitials { text }?,
    attribute surname { text }?,
+   attribute asciiSurname { text }?,
    attribute fullname { text }?,
    attribute role { "editor" }?,
+   attribute asciiFullname { text }?,
    organization?,
    address?
  }
  organization =
    element organization {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
    attribute abbrev { text }?,
+   attribute ascii { text }?,
+   attribute asciiAbbrev { text }?,
+   [ a:defaultValue = "true" ]
+   attribute showOnFrontPage { "true" | "false" }?,
+   text
+ }
+ address =
+   element address {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   postal?,
+   phone?,
+   facsimile?,
+   email?,
+   uri?
+ }
+ postal =
+   element postal {
```



```
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   ((city
+     | cityarea
+     | code
+     | country
+     | extaddr
+     | pobox
+     | region
+     | sortingcode
+     | street)*
+     | postalLine+)
+ }
+ cityarea =
+ element cityarea {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute ascii { text }?,
+   text
+ }
+ extaddr =
+ element extaddr {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute ascii { text }?,
+   text
+ }
+ pobox =
+ element pobox {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute ascii { text }?,
+   text
+ }
+ sortingcode =
+ element sortingcode {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute ascii { text }?,
+   text
+ }
+ street =
+ element street {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute ascii { text }?,
+   text
+ }
```



```
+ city =
+   element city {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute ascii { text }?,
+     text
+   }
+ region =
+   element region {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute ascii { text }?,
+     text
+   }
+ code =
+   element code {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute ascii { text }?,
+     text
+   }
+ country =
+   element country {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute ascii { text }?,
+     text
+   }
+ postalline =
+   element postalline {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute ascii { text }?,
+     text
+   }
+ phone =
+   element phone {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     text
+   }
+ facsimile =
+   element facsimile {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     text
+   }
+ email =
```



```
+ element email {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute ascii { text }?,
+   text
+ }
+ uri =
+ element uri {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   text
+ }
- address = element address { postal?, phone?, facsimile?, email?,
- uri? }
- postal = element postal { street+, (city | region | code |
- country)* }
- street = element street { text }
- city = element city { text }
- region = element region { text }
- code = element code { text }
- country = element country { text }
- phone = element phone { text }
- facsimile = element facsimile { text }
- email = element email { text }
- uri = element uri { text }
date =
  element date {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute day { text }?,
+   attribute month { text }?,
+   attribute year { text }?,
+   empty
  }
- area = element area { text }
- workgroup = element workgroup { text }
- keyword = element keyword { text }
- abstract = element abstract { t+ }
+ area =
+ element area {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   text
+ }
+ workgroup =
+ element workgroup {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
```



```
+   text
+ }
+ keyword =
+   element keyword {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     text
+   }
+ abstract =
+   element abstract {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     (dl | ol | t | ul)+
+   }
+ note =
+   element note {
-     attribute title { text },
-     t+
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute title { text }?,
+     attribute pn { text }?,
+     [ a:defaultValue = "false" ]
+     attribute removeInRFC { "true" | "false" }?,
+     name?,
+     (dl | ol | t | ul)+
+   }
+ boilerplate =
+   element boilerplate {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     section+
+   }
+ middle =
+   element middle {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     section+
+   }
- middle = element middle { section+ }
+ section =
+   element section {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
-     attribute title { text },
```



```

+   attribute pn { text }?,
+   attribute title { text }?,
+   [ a:defaultValue = "true" ]
+   attribute numbered { "true" | "false" }?,
+   [ a:defaultValue = "default" ]
+   attribute toc { "include" | "exclude" | "default" }?,
-   (t | figure | texttable | iref)*,
+   [ a:defaultValue = "false" ]
+   attribute removeInRFC { "true" | "false" }?,
+   name?,
+   (artset
+     | artwork
+     | aside
+     | blockquote
+     | dl
+     | figure
+     | iref
+     | ol
+     | sourcecode
+     | t
+     | table
+     | texttable
+     | ul)*,
+   section*
+ }
+ name =
+   element name {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute slugifiedName { text }?,
+     (text
+       | bcp14
+       | cref
+       | em
+       | eref
+       | iref
+       | relref
+       | strong
+       | sub
+       | sup
+       | tt
+       | xref)*
+   }
+ t =
+   element t {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,

```



```
+   attribute pn { text }?,
+   attribute hangText { text }?,
+   [ a:defaultValue = "false" ]
+   attribute keepWithNext { "false" | "true" }?,
+   [ a:defaultValue = "false" ]
+   attribute keepWithPrevious { "false" | "true" }?,
+   (text
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
+     | \list
+     | relref
+     | spanx
+     | strong
+     | sub
+     | sup
+     | tt
+     | vspace
+     | xref)*
+   }
+ aside =
+   element aside {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     (artset | artwork | dl | figure | iref | ol | t | table | ul)*
+   }
+ blockquote =
+   element blockquote {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     attribute cite { text }?,
+     attribute quotedFrom { text }?,
+     ((artset
+       | artwork
+       | dl
+       | figure
+       - | xref
+       + | ol
+       + | sourcecode
+       + | t
+       + | table
+       + | ul)+
```



```

+      | (text
+        | bcp14
+        | cref
+        | em
+        | eref
+        | iref
-      | cref
-      | spanx
-      | vspace)*
+      | relref
+      | strong
+      | sub
+      | sup
+      | tt
+      | xref)+)
    }
  \list =
    element list {
-     attribute style { text }?,
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     [ a:defaultValue = "empty" ] attribute style { text }?,
+     attribute hangIndent { text }?,
+     attribute counter { text }?,
+     attribute pn { text }?,
+     t+
    }
+ ol =
+   element ol {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     [ a:defaultValue = "1" ] attribute type { text }?,
+     [ a:defaultValue = "1" ] attribute start { text }?,
+     attribute group { text }?,
+     [ a:defaultValue = "normal" ]
+     attribute spacing { "normal" | "compact" }?,
+     attribute pn { text }?,
+     li+
+   }
+ ul =
+   element ul {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     [ a:defaultValue = "normal" ]
+     attribute spacing { "normal" | "compact" }?,
+     ([ a:defaultValue = "false" ]

```



```
+     attribute empty { "false" | "true" },
+     attribute pn { text }?)?,
+     li+
+   }
+ li =
+ element li {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   attribute pn { text }?,
+   ((artset
+     | artwork
+     | blockquote
+     | dl
+     | figure
+     | ol
+     | sourcecode
+     | t
+     | ul)+
+   | (text
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
+     | relref
+     | strong
+     | sub
+     | sup
+     | tt
+     | xref)+)
+ }
+ dl =
+ element dl {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   [ a:defaultValue = "normal" ]
+   attribute spacing { "normal" | "compact" }?,
+   [ a:defaultValue = "true" ]
+   attribute newline { "false" | "true" }?,
+   [ a:defaultValue = "0" ] attribute indent { text }?,
+   attribute pn { text }?,
+   (dt, dd)+
+ }
+ dt =
+ element dt {
+   attribute xml:base { text }?,
```



```
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   attribute pn { text }?,
+   (text
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
+     | relref
+     | strong
+     | sub
+     | sup
+     | tt
+     | xref)*
+ }
+ dd =
+   element dd {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     ((artset | artwork | dl | figure | ol | sourcecode | t | ul)+
+     | (text
+       | bcp14
+       | cref
+       | em
+       | eref
+       | iref
+       | relref
+       | strong
+       | sub
+       | sup
+       | tt
+       | xref)+)
+   }
xref =
  element xref {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute target { xsd:IDREF },
-   [ a:defaultValue = "false" ] attribute pageno { "true" |
- "false" }?,
+   [ a:defaultValue = "false" ]
+   attribute pageno { "true" | "false" }?,
+   [ a:defaultValue = "default" ]
-   attribute format { "counter" | "title" | "none" | "default"
+   attribute format { "default" | "title" | "counter" | "none" }
```



```
    }?,
+   attribute derivedContent { text }?,
+   text
+ }
+ relref =
+   element relref {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute target { xsd:IDREF },
+     [ a:defaultValue = "of" ]
+     attribute displayFormat { "of" | "comma" | "parens" | "bare"
+ }?,
+   attribute section { text },
+   attribute relative { text }?,
+   attribute derivedLink { text }?,
+   text
+ }
+   element eref {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute target { text },
+     text
+   }
+   iref =
+     element iref {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute item { text },
+     [ a:defaultValue = "" ] attribute subitem { text }?,
+     [ a:defaultValue = "false" ]
+     attribute primary { "true" | "false" }?,
+     attribute pn { text }?,
+     empty
+   }
+   cref =
+     element cref {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute source { text }?,
+     -   text
+     +   [ a:defaultValue = "true" ]
+     +   attribute display { "true" | "false" }?,
+     +   (text | em | eref | relref | strong | sub | sup | tt | xref)*
+     + }
+   tt =
+     element tt {
```



```
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   (text
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
+     | relref
+     | strong
+     | sub
+     | sup
+     | xref)*
+   }
+ strong =
+   element strong {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     (text
+       | bcp14
+       | cref
+       | em
+       | eref
+       | iref
+       | relref
+       | sub
+       | sup
+       | tt
+       | xref)*
+     }
+ em =
+   element em {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     (text
+       | bcp14
+       | cref
+       | eref
+       | iref
+       | relref
+       | strong
+       | sub
+       | sup
+       | tt
+       | xref)*
+     }
+ sub =
+   element sub {
```



```
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   (text
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
+     | relref
+     | strong
+     | tt
+     | xref)*
+   }
+ sup =
+   element sup {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     (text
+       | bcp14
+       | cref
+       | em
+       | eref
+       | iref
+       | relref
+       | strong
+       | tt
+       | xref)*
+     }
+ spanx =
+   element spanx {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     [ a:defaultValue = "preserve" ]
+     attribute xml:space { "default" | "preserve" }?,
+     [ a:defaultValue = "emph" ] attribute style { text }?,
+     text
+   }
+ vspace =
+   element vspace {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     [ a:defaultValue = "0" ] attribute blankLines { text }?,
+     empty
+   }
+ figure =
+   element figure {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
```



```
    attribute anchor { xsd:ID }?,
+   attribute pn { text }?,
    [ a:defaultValue = "" ] attribute title { text }?,
    [ a:defaultValue = "false" ]
    attribute suppress-title { "true" | "false" }?,
    attribute src { text }?,
+   attribute originalSrc { text }?,
    [ a:defaultValue = "left" ]
    attribute align { "left" | "center" | "right" }?,
    [ a:defaultValue = "" ] attribute alt { text }?,
    [ a:defaultValue = "" ] attribute width { text }?,
    [ a:defaultValue = "" ] attribute height { text }?,
+   name?,
    iref*,
    preamble?,
-   artwork,
+   (artset | artwork | sourcecode)+,
    postamble?
  }
+ table =
+   element table {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     [ a:defaultValue = "center" ]
+     attribute align { "left" | "center" | "right" }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     name?,
+     thead?,
+     tbody+,
+     tfoot?
+   }
  preamble =
-   element preamble { (text | xref | eref | iref | cref | spanx)* }
+   element preamble {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     (text
+     | bcp14
+     | cref
+     | em
+     | eref
+     | iref
+     | relref
+     | spanx
+     | strong
+     | sub
+     | sup
```



```
+      | tt
+      | xref)*
+    }
+ artset =
+   element artset {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     artwork+
+   }
  artwork =
    element artwork {
-     [ a:defaultValue = "preserve" ]
-     attribute xml:space { "default" | "preserve" }?,
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     attribute xml:space { text }?,
+     [ a:defaultValue = "" ] attribute name { text }?,
+     [ a:defaultValue = "" ] attribute type { text }?,
+     attribute src { text }?,
+     [ a:defaultValue = "left" ]
+     attribute align { "left" | "center" | "right" }?,
+     [ a:defaultValue = "" ] attribute alt { text }?,
+     [ a:defaultValue = "" ] attribute width { text }?,
+     [ a:defaultValue = "" ] attribute height { text }?,
-     text*
+     attribute originalSrc { text }?,
+     (text* | svg)
+   }
+ # TODO: replace with link to RSE site, or provide an inline
+ version
+ include "svg.rnc"
+ sourcecode =
+   element sourcecode {
+     attribute xml:base { text }?,
+     attribute xml:lang { text }?,
+     attribute anchor { xsd:ID }?,
+     attribute pn { text }?,
+     [ a:defaultValue = "" ] attribute name { text }?,
+     [ a:defaultValue = "" ] attribute type { text }?,
+     attribute src { text }?,
+     attribute originalSrc { text }?,
+     text
+   }
+ thead =
```



```
+ element thead {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   tr+
+ }
+ tbody =
+ element tbody {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   tr+
+ }
+ tfoot =
+ element tfoot {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   tr+
+ }
+ tr =
+ element tr {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   (td | th)+
+ }
+ td =
+ element td {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID }?,
+   [ a:defaultValue = "0" ] attribute colspan { text }?,
+   [ a:defaultValue = "0" ] attribute rowspan { text }?,
+   [ a:defaultValue = "left" ]
+   attribute align { "left" | "center" | "right" }?,
+   ((artset | artwork | dl | figure | ol | sourcecode | t | ul)+
+   | (text
+   | bcp14
+   | cref
+   | em
+   | eref
+   | iref
+   | relref
+   | strong
+   | sub
+   | sup
+   | tt
```



```

+         | xref)*)
+     }
+ th =
+     element th {
+         attribute xml:base { text }?,
+         attribute xml:lang { text }?,
+         attribute anchor { xsd:ID }?,
+         [ a:defaultValue = "0" ] attribute colspan { text }?,
+         [ a:defaultValue = "0" ] attribute rowspan { text }?,
+         [ a:defaultValue = "left" ]
+         attribute align { "left" | "center" | "right" }?,
+         ((artset | artwork | dl | figure | ol | sourcecode | t | ul)+
+         | (text
+         | bcp14
+         | cref
+         | em
+         | eref
+         | iref
+         | relref
+         | strong
+         | sub
+         | sup
+         | tt
+         | xref)*)
+     }
+ postamble =
-     element postamble { (text | xref | eref | iref | cref | spanx)*
+     element postamble {
+         attribute xml:base { text }?,
+         attribute xml:lang { text }?,
+         (text | cref | eref | iref | spanx | xref)*
+     }
+ texttable =
+     element texttable {
+         attribute xml:base { text }?,
+         attribute xml:lang { text }?,
+         attribute anchor { xsd:ID }?,
+         [ a:defaultValue = "" ] attribute title { text }?,
+         [ a:defaultValue = "false" ]
+         attribute suppress-title { "true" | "false" }?,
+         [ a:defaultValue = "center" ]
+         attribute align { "left" | "center" | "right" }?,
+         [ a:defaultValue = "full" ]
+         attribute style { "all" | "none" | "headers" | "full" }?,
+         name?,
+         preamble?,
+         ttcoll+,
+         c*,

```



```
    postamble?
  }
  ttcol =
    element ttcol {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
    attribute width { text }?,
    [ a:defaultValue = "left" ]
    attribute align { "left" | "center" | "right" }?,
+   (cref | eref | iref | xref | text)*
+   }
+ c =
+   element c {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   (text | cref | eref | iref | spanx | xref)*
+   }
+ bcp14 =
+   element bcp14 {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
    text
  }
- c = element c { (text | xref | eref | iref | cref | spanx)* }
- back = element back { references*, section* }
+ back =
+   element back {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   displayreference*,
+   references,
+   section*
+   }
+ displayreference =
+   element displayreference {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute target { xsd:IDREF },
+   attribute to { text }
+   }
  references =
    element references {
-   [ a:defaultValue = "References" ] attribute title { text }?,
-   reference+
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute pn { text }?,
+   attribute anchor { xsd:ID }?,
```



```
+   attribute title { text }?,
+   name?,
+   (references+ | (reference | referencegroup)*)
  }
reference =
  element reference {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID },
+   attribute target { text }?,
+   [ a:defaultValue = "true" ]
+   attribute quote-title { "true" | "false" }?,
+   front,
-   seriesInfo*,
-   format*,
-   annotation*
+   (annotation | format | refcontent | seriesInfo)*
+  }
+ referencegroup =
+   element referencegroup {
+   attribute xml:base { text }?,
+   attribute target { text }?,
+   attribute xml:lang { text }?,
+   attribute anchor { xsd:ID },
+   reference+
+   }
seriesInfo =
  element seriesInfo {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute name { text },
+   attribute value { text },
+   attribute asciiName { text }?,
+   attribute asciiValue { text }?,
+   attribute status { text }?,
+   [ a:defaultValue = "IETF" ]
+   attribute stream { "IETF" | "IAB" | "IRTF" | "independent" }?,
+   empty
+   }
format =
  element format {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   attribute target { text }?,
+   attribute type { text },
+   attribute octets { text }?,
+   empty
+   }
```



```
annotation =
- element annotation { (text | xref | eref | iref | cref |
- spanx)* }
- start = rfc
+ element annotation {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   (text
+   | bcp14
+   | cref
+   | em
+   | eref
+   | iref
+   | relref
+   | spanx
+   | strong
+   | sub
+   | sup
+   | tt
+   | xref)*
+ }
+ refcontent =
+ element refcontent {
+   attribute xml:base { text }?,
+   attribute xml:lang { text }?,
+   (text | bcp14 | em | strong | sub | sup | tt)*
+ }
+ start |= rfc
```

Index

A

Attributes

abbrev 43, 73
align 15, 33, 68, 70, 72, 83-84
alt 15, 33
anchor 11, 14, 16, 18, 22, 24, 27-28, 30, 33, 38, 41, 46-48,
57, 61, 66, 68, 70-75, 83
ascii 22-23, 31-32, 43-45, 49, 60, 63, 73
asciiAbbrev 43
asciiFullname 18
asciiInitials 19
asciiName 59
asciiSurname 19
asciiValue 59
blankLines 85
category 53

cite 22
colspan 70, 72
consensus 53
counter 80
day 25
display 24
displayFormat 50
docName 54
empty 75
format 77
fullname 19
group 41
hangIndent 80
hangText 66
height 16, 33
href 38
indent 28
indexInclude 54
initials 19
ipr 54
iprExtract 54
item 35
keepWithNext 66
keepWithPrevious 67
month 25
name 16, 59, 61
newline 28
number 54
numbered 57
obsoletes 54
octets 79
pageno 78
prepTime 54
primary 36
quote-title 47
quotedFrom 22
rel 38
relative 52
removeInRFC 40, 58
role 19
rowspan 70, 73
section 53
seriesNo 55
showOnFrontPage 43
sortRefs 55
source 24
spacing 29, 41, 75
src 16, 34, 62

- start 41
- status 59
- stream 60
- style 80, 82-83
- subitem 36
- submissionType 55
- suppress-title 34, 83
- surname 19
- symRefs 55
- target 27, 32, 47, 53, 78, 80
- title 34, 41, 48, 58, 83
- to 27
- toc 58
- tocDepth 55
- tocInclude 56
- type 16, 42, 62, 80
- updates 56
- value 60
- version 56
- width 17, 34, 84
- xml:space 17, 82
- year 25

abbrev attribute

- in organization element 43
- in title element 73

abstract element 11, 102

- anchor attribute 11
- inside front 35

address element 12, 102

- inside author 18

align attribute

- in artwork element 15
- in figure element 33
- in table element 68
- in td element 70
- in texttable element 83
- in th element 72
- in tthead element 84

alt attribute

- in artwork element 15
- in figure element 33

anchor attribute

- in abstract element 11
- in artset element 14
- in artwork element 16
- in aside element 18
- in blockquote element 22
- in cref element 24

- in dd element 27
- in dl element 28
- in dt element 30
- in figure element 33
- in li element 38
- in ol element 41
- in reference element 46
- in referencegroup element 47
- in references element 48
- in section element 57
- in sourcecode element 61
- in t element 66
- in table element 68
- in tbody element 68
- in td element 70
- in texttable element 83
- in tfoot element 71
- in th element 72
- in thead element 73
- in tr element 74
- in ul element 75
- annotation element 12, 102
 - inside reference 46
- application/rfc+xml Media Type 86
- area element 13, 102
 - inside front 35
- artset element 13, 102
 - anchor attribute 14
 - inside aside 17
 - inside blockquote 20
 - inside dd 26
 - inside figure 33
 - inside li 36
 - inside section 56
 - inside td 69
 - inside th 71
- artwork element 14, 102
 - align attribute 15
 - alt attribute 15
 - anchor attribute 16
 - height attribute 16
 - inside artset 13
 - inside aside 17
 - inside blockquote 21
 - inside dd 26
 - inside figure 33
 - inside li 36
 - inside section 56

- inside td 69
- inside th 71
- name attribute 16
- src attribute 16
- type attribute 16
- width attribute 17
- xml:space attribute 17
- ascii attribute
 - in city element 22
 - in cityarea element 23
 - in code element 23
 - in country element 23
 - in email element 31
 - in extaddr element 32
 - in organization element 43
 - in pobox element 44
 - in postalline element 45
 - in region element 49
 - in sortingcode element 60
 - in street element 63
 - in title element 73
- asciiAbbrev attribute
 - in organization element 43
- asciiFullname attribute
 - in author element 18
- asciiInitials attribute
 - in author element 19
- asciiName attribute
 - in seriesInfo element 59
- asciiSurname attribute
 - in author element 19
- asciiValue attribute
 - in seriesInfo element 59
- aside element 17, 102
 - anchor attribute 18
 - inside section 57
- author element 18, 102
 - asciiFullname attribute 18
 - asciiInitials attribute 19
 - asciiSurname attribute 19
 - fullname attribute 19
 - initials attribute 19
 - inside front 34
 - role attribute 19
 - surname attribute 19

B

- back element 19, 102

- inside rfc 53
- [bcp14](#) element 20, 102
 - inside annotation 12
 - inside blockquote 21
 - inside dd 26
 - inside dt 29
 - inside em 30
 - inside li 37
 - inside name 39
 - inside preamble 81
 - inside refcontent 46
 - inside strong 63
 - inside sub 64
 - inside sup 65
 - inside t 66
 - inside td 69
 - inside th 71
 - inside tt 74
- blankLines attribute
 - in vspace element 85
- blockquote element 20, 102
 - anchor attribute 22
 - cite attribute 22
 - inside li 37
 - inside section 57
 - quotedFrom attribute 22
- boilerplate element 22, 102
 - inside front 35

C

- c element 79, 102
 - inside texttable 82
- category attribute
 - in rfc element 53
- cite attribute
 - in blockquote element 22
- city element 22, 102
 - ascii attribute 22
 - inside postal 44
- cityarea element 22, 102
 - ascii attribute 23
 - inside postal 44
- code element 23, 102
 - ascii attribute 23
 - inside postal 44
- colspan attribute
 - in td element 70
 - in th element 72

- consensus attribute
 - in rfc element 53
- counter attribute
 - in list element 80
- country element 23, 102
 - ascii attribute 23
 - inside postal 44
- cref element 23, 102
 - anchor attribute 24
 - display attribute 24
 - inside annotation 12
 - inside blockquote 21
 - inside c 79
 - inside dd 26
 - inside dt 29
 - inside em 30
 - inside li 37
 - inside name 39
 - inside postamble 80
 - inside preamble 81
 - inside strong 63
 - inside sub 64
 - inside sup 65
 - inside t 66
 - inside td 69
 - inside th 72
 - inside tt 74
 - inside ttc01 84
 - source attribute 24

D

- date element 24, 102
 - day attribute 25
 - inside front 35
 - month attribute 25
 - year attribute 25
- day attribute
 - in date element 25
- dd element 25, 102
 - anchor attribute 27
 - inside dl 28
- display attribute
 - in cref element 24
- displayFormat attribute
 - in relref element 50
- displayreference element 27, 102
 - inside back 20
 - target attribute 27

- to attribute 27
- dl element 28, 102
 - anchor attribute 28
 - indent attribute 28
 - inside abstract 11
 - inside aside 17
 - inside blockquote 21
 - inside dd 26
 - inside li 37
 - inside note 40
 - inside section 57
 - inside td 69
 - inside th 71
 - newline attribute 28
 - spacing attribute 29
- docName attribute
 - in rfc element 54
- dt element 29, 102
 - anchor attribute 30
 - inside dl 28

E

Elements

- abstract 11, 35
- address 12, 18
- annotation 12, 46
- area 13, 35
- artset 13, 17, 20, 26, 33, 36, 56, 69, 71
- artwork 13-14, 17, 21, 26, 33, 36, 56, 69, 71
- aside 17, 57
- author 18, 34
- back 19, 53
- [bcp14](#) 12, 20-21, 26, 29-30, 37, 39, 46, 63-66, 69, 71, 74, 81
- blockquote 20, 37, 57
- boilerplate 22, 35
- c 79, 82
- city 22, 44
- cityarea 22, 44
- code 23, 44
- country 23, 44
- cref 12, 21, 23, 26, 29-30, 37, 39, 63-66, 69, 72, 74, 79-81, 84
- date 24, 35
- dd 25, 28
- displayreference 20, 27
- dl 11, 17, 21, 26, 28, 37, 40, 57, 69, 71
- dt 28-29
- em 12, 21, 24, 26, 29-30, 37, 39, 46, 63-66, 69, 72, 74, 81

email 12, 31
eref 12, 21, 24, 26, 29-31, 37, 39, 63-66, 69, 72, 74, 79, 81, 84
extaddr 32, 44
facsimile 12, 79
figure 17, 21, 26, 32, 37, 57, 69, 71
format 46, 79
front 34, 46, 53
iref 12, 17, 21, 26, 29-30, 33, 35, 37, 39, 57, 63-66, 69, 72, 74, 79, 81, 84
keyword 35-36
li 36, 41, 75
link 38, 53
list 66, 80
middle 39, 53
name 33, 39-40, 48, 56, 67, 82
note 35, 40
ol 11, 18, 21, 26, 37, 40-41, 57, 69, 71
organization 18, 43
phone 12, 43
pobox 44
postal 12, 44
postalLine 45
postamble 33, 80, 82
preamble 33, 81-82
refcontent 45-46
reference 46-48
referencegroup 47-48
references 20, 47-48
region 44, 49
relref 12, 21, 24, 26, 29-30, 37, 39, 49, 64-66, 69, 72, 74, 81
rfc 53
section 20, 22, 39, 56-57
seriesInfo 34, 46, 58
sortingcode 44, 60
sourcecode 21, 26, 33, 37, 57, 61, 69, 71
spanx 12, 66, 79, 81-82
street 44, 63
strong 13, 21, 24, 26, 29-30, 37, 39, 46, 63-66, 69, 72, 74, 81
sub 13, 21, 24, 26, 29-30, 37, 39, 46, 64, 66, 69, 72, 74, 81
sup 13, 21, 24, 27, 29-30, 37, 39, 46, 64-66, 69, 72, 75, 81
svg 15
t 11, 18, 21, 26, 37, 40, 57, 65, 69, 71, 80
table 18, 21, 57, 67
tbody 68
td 68, 74

- texttable 57, 82
- tfoot 68, 70
- th 71, 74
- thead 68, 73
- title 34, 73
- tr 68, 70, 73
- tt 13, 21, 24, 27, 29-30, 37, 39, 46, 64-66, 70, 72, 74, 81
- ttcol 82, 84
- ul 11, 18, 21, 26, 37, 40, 57, 69, 71, 75
- uri 12, 76
- vspace 66, 84
- workgroup 35, 76
- xref 13, 21, 24, 27, 29-30, 37, 39, 64-66, 70, 72, 75-76, 79, 81, 84

em element 30, 102

- inside annotation 12
- inside blockquote 21
- inside cref 24
- inside dd 26
- inside dt 29
- inside li 37
- inside name 39
- inside preamble 81
- inside refcontent 46
- inside strong 63
- inside sub 64
- inside sup 65
- inside t 66
- inside td 69
- inside th 72
- inside tt 74

email element 31, 102

- ascii attribute 31
- inside address 12

empty attribute

- in ul element 75

eref element 31, 102

- inside annotation 12
- inside blockquote 21
- inside c 79
- inside cref 24
- inside dd 26
- inside dt 29
- inside em 30
- inside li 37
- inside name 39
- inside postamble 81
- inside preamble 81

- inside strong 63
- inside sub 64
- inside sup 65
- inside t 66
- inside td 69
- inside th 72
- inside tt 74
- inside ttc01 84
- target attribute 32
- extaddr element 32, 102
 - ascii attribute 32
 - inside postal 44

F

- facsimile element 79, 102
 - inside address 12
- figure element 32, 102
 - align attribute 33
 - alt attribute 33
 - anchor attribute 33
 - height attribute 33
 - inside aside 17
 - inside blockquote 21
 - inside dd 26
 - inside li 37
 - inside section 57
 - inside td 69
 - inside th 71
 - src attribute 34
 - suppress-title attribute 34
 - title attribute 34
 - width attribute 34
- format attribute
 - in xref element 77
- format element 79, 102
 - inside reference 46
 - octets attribute 79
 - target attribute 80
 - type attribute 80
- front element 34, 102
 - inside reference 46
 - inside rfc 53
- fullname attribute
 - in author element 19

G

- group attribute
 - in ol element 41

H

hangIndent attribute
 in list element 80
hangText attribute
 in t element 66
height attribute
 in artwork element 16
 in figure element 33
href attribute
 in link element 38

I

indent attribute
 in dl element 28
indexInclude attribute
 in rfc element 54
initials attribute
 in author element 19
ipr attribute
 "*2026" 95
 "*3667" 95
 "*3978" 95
 "*trust200811" 95
 "*trust200902" 93
 "noDerivativesTrust200902" 94
 "noModificationTrust200902" 94
 "pre5378Trust200902" 94
 "trust200902" 94
 in rfc element 54
iprExtract attribute
 in rfc element 54
iref element 35, 102
 inside annotation 12
 inside aside 17
 inside blockquote 21
 inside c 79
 inside dd 26
 inside dt 29
 inside em 30
 inside figure 33
 inside li 37
 inside name 39
 inside postamble 81
 inside preamble 81
 inside section 57
 inside strong 63
 inside sub 64
 inside sup 65

- inside t 66
- inside td 69
- inside th 72
- inside tt 74
- inside ttc01 84
- item attribute 35
- primary attribute 36
- subitem attribute 36
- item attribute
 - in iref element 35

K

- keepWithNext attribute
 - in t element 66
- keepWithPrevious attribute
 - in t element 67
- keyword element 36, 102
 - inside front 35

L

- li element 36, 102
 - anchor attribute 38
 - inside ol 41
 - inside ul 75
- link element 38, 102
 - href attribute 38
 - inside rfc 53
 - rel attribute 38
- list element 80, 102
 - counter attribute 80
 - hangIndent attribute 80
 - inside t 66
 - style attribute 80

M

- Media Type
 - application/rfc+xml 86
- middle element 39, 102
 - inside rfc 53
- month attribute
 - in date element 25

N

- name attribute
 - in artwork element 16
 - in seriesInfo element 59
 - in sourcecode element 61
- name element 39, 102

- inside figure 33
- inside note 40
- inside references 48
- inside section 56
- inside table 67
- inside texttable 82
- newline attribute
 - in dl element 28
- note element 40, 102
 - inside front 35
 - removeInRFC attribute 40
 - title attribute 41
- number attribute
 - in rfc element 54
- numbered attribute
 - in section element 57

O

- obsoletes attribute
 - in rfc element 54
- octets attribute
 - in format element 79
- ol element 41, 102
 - anchor attribute 41
 - group attribute 41
 - inside abstract 11
 - inside aside 18
 - inside blockquote 21
 - inside dd 26
 - inside li 37
 - inside note 40
 - inside section 57
 - inside td 69
 - inside th 71
 - spacing attribute 41
 - start attribute 41
 - type attribute 42
- organization element 43, 102
 - abbrev attribute 43
 - ascii attribute 43
 - asciiAbbrev attribute 43
 - inside author 18
 - showOnFrontPage attribute 43

P

- pageno attribute
 - in xref element 78
- phone element 43, 102

- inside address 12
- pobox element 44, 102
 - ascii attribute 44
 - inside postal 44
- postal element 44, 102
 - inside address 12
- postalline element 45, 102
 - ascii attribute 45
 - inside postal 45
- postamble element 80, 102
 - inside figure 33
 - inside texttable 82
- preamble element 81, 102
 - inside figure 33
 - inside texttable 82
- prepTime attribute
 - in rfc element 54
- primary attribute
 - in iref element 36

Q

- quote-title attribute
 - in reference element 47
- quotedFrom attribute
 - in blockquote element 22

R

- refcontent element 45, 102
 - inside reference 46
- reference element 46, 102
 - anchor attribute 46
 - inside referencegroup 47
 - inside references 48
 - quote-title attribute 47
 - target attribute 47
- referencegroup element 47, 102
 - anchor attribute 47
 - inside references 48
 - target attribute 47
- references element 47, 102
 - anchor attribute 48
 - inside back 20
 - inside references 48
 - title attribute 48
- region element 49, 102
 - ascii attribute 49
 - inside postal 44
- rel attribute

- in link element 38
- relative attribute
 - in relref element 52
- relref element 49, 102
 - displayFormat attribute 50
 - inside annotation 12
 - inside blockquote 21
 - inside cref 24
 - inside dd 26
 - inside dt 29
 - inside em 30
 - inside li 37
 - inside name 39
 - inside preamble 81
 - inside strong 64
 - inside sub 64
 - inside sup 65
 - inside t 66
 - inside td 69
 - inside th 72
 - inside tt 74
 - relative attribute 52
 - section attribute 53
 - target attribute 53
- removeInRFC attribute
 - in note element 40
 - in section element 58
- rfc element 53, 102
 - category attribute 53
 - consensus attribute 53
 - docName attribute 54
 - indexInclude attribute 54
 - ipr attribute 54
 - iprExtract attribute 54
 - number attribute 54
 - obsoletes attribute 54
 - prepTime attribute 54
 - seriesNo attribute 55
 - sortRefs attribute 55
 - submissionType attribute 55
 - symRefs attribute 55
 - tocDepth attribute 55
 - tocInclude attribute 56
 - updates attribute 56
 - version attribute 56
- role attribute
 - in author element 19
- rowspan attribute

- in td element 70
- in th element 73

S

- section attribute
 - in relref element 53
- section element 56, 102
 - anchor attribute 57
 - inside back 20
 - inside boilerplate 22
 - inside middle 39
 - inside section 57
 - numbered attribute 57
 - removeInRFC attribute 58
 - title attribute 58
 - toc attribute 58
- seriesInfo element 58, 102
 - asciiName attribute 59
 - asciiValue attribute 59
 - inside front 34
 - inside reference 46
 - name attribute 59
 - status attribute 59
 - stream attribute 60
 - value attribute 60
- seriesNo attribute
 - in rfc element 55
- showOnFrontPage attribute
 - in organization element 43
- sortRefs attribute
 - in rfc element 55
- sortingcode element 60, 102
 - ascii attribute 60
 - inside postal 44
- source attribute
 - in cref element 24
- sourcecode element 61, 102
 - anchor attribute 61
 - inside blockquote 21
 - inside dd 26
 - inside figure 33
 - inside li 37
 - inside section 57
 - inside td 69
 - inside th 71
 - name attribute 61
 - src attribute 62
 - type attribute 62

- spacing attribute
 - in dl element 29
 - in ol element 41
 - in ul element 75
- spanx element 82, 102
 - inside annotation 12
 - inside c 79
 - inside postamble 81
 - inside preamble 81
 - inside t 66
 - style attribute 82
 - xml:space attribute 82
- src attribute
 - in artwork element 16
 - in figure element 34
 - in sourcecode element 62
- start attribute
 - in ol element 41
- status attribute
 - in seriesInfo element 59
- stream attribute
 - in seriesInfo element 60
- street element 63, 102
 - ascii attribute 63
 - inside postal 44
- strong element 63, 102
 - inside annotation 13
 - inside blockquote 21
 - inside cref 24
 - inside dd 26
 - inside dt 29
 - inside em 30
 - inside li 37
 - inside name 39
 - inside preamble 81
 - inside refcontent 46
 - inside sub 64
 - inside sup 65
 - inside t 66
 - inside td 69
 - inside th 72
 - inside tt 74
- style attribute
 - in list element 80
 - in spanx element 82
 - in texttable element 83
- sub element 64, 102
 - inside annotation 13

- inside blockquote 21
- inside cref 24
- inside dd 26
- inside dt 29
- inside em 30
- inside li 37
- inside name 39
- inside preamble 81
- inside refcontent 46
- inside strong 64
- inside t 66
- inside td 69
- inside th 72
- inside tt 74
- subitem attribute
 - in iref element 36
- submissionType attribute
 - in rfc element 55
- sup element 65, 102
 - inside annotation 13
 - inside blockquote 21
 - inside cref 24
 - inside dd 27
 - inside dt 29
 - inside em 30
 - inside li 37
 - inside name 39
 - inside preamble 81
 - inside refcontent 46
 - inside strong 64
 - inside t 66
 - inside td 69
 - inside th 72
 - inside tt 75
- suppress-title attribute
 - in figure element 34
 - in texttable element 83
- surname attribute
 - in author element 19
- svg element
 - inside artwork 15
- symRefs attribute
 - in rfc element 55

T

- t element 65, 102
 - anchor attribute 66
 - hangText attribute 66

- inside abstract 11
- inside aside 18
- inside blockquote 21
- inside dd 26
- inside li 37
- inside list 80
- inside note 40
- inside section 57
- inside td 69
- inside th 71
- keepWithNext attribute 66
- keepWithPrevious attribute 67
- table element 67, 102
 - align attribute 68
 - anchor attribute 68
 - inside aside 18
 - inside blockquote 21
 - inside section 57
- target attribute
 - in displayreference element 27
 - in eref element 32
 - in format element 80
 - in reference element 47
 - in referencegroup element 47
 - in relref element 53
 - in xref element 78
- tbody element 68, 102
 - anchor attribute 68
 - inside table 68
- td element 68, 102
 - align attribute 70
 - anchor attribute 70
 - colspan attribute 70
 - inside tr 74
 - rowspan attribute 70
- texttable element 82, 102
 - align attribute 83
 - anchor attribute 83
 - inside section 57
 - style attribute 83
 - suppress-title attribute 83
 - title attribute 83
- tfoot element 70, 102
 - anchor attribute 71
 - inside table 68
- th element 71, 102
 - align attribute 72
 - anchor attribute 72

- colspan attribute 72
 - inside tr 74
- rowspan attribute 73
- thead element 73, 102
 - anchor attribute 73
 - inside table 68
- title attribute
 - in figure element 34
 - in note element 41
 - in references element 48
 - in section element 58
 - in texttable element 83
- title element 73, 102
 - abbrev attribute 73
 - ascii attribute 73
 - inside front 34
- to attribute
 - in displayreference element 27
- toc attribute
 - in section element 58
- tocDepth attribute
 - in rfc element 55
- tocInclude attribute
 - in rfc element 56
- tr element 73, 102
 - anchor attribute 74
 - inside tbody 68
 - inside tfoot 70
 - inside thead 73
- tt element 74, 102
 - inside annotation 13
 - inside blockquote 21
 - inside cref 24
 - inside dd 27
 - inside dt 29
 - inside em 30
 - inside li 37
 - inside name 39
 - inside preamble 81
 - inside refcontent 46
 - inside strong 64
 - inside sub 64
 - inside sup 65
 - inside t 66
 - inside td 70
 - inside th 72
- ttcol element 84, 102
 - align attribute 84

- inside texttable 82
- width attribute 84
- type attribute
 - in artwork element 16
 - in format element 80
 - in ol element 42
 - in sourcecode element 62

U

- ul element 75, 102
 - anchor attribute 75
 - empty attribute 75
 - inside abstract 11
 - inside aside 18
 - inside blockquote 21
 - inside dd 26
 - inside li 37
 - inside note 40
 - inside section 57
 - inside td 69
 - inside th 71
 - spacing attribute 75
- updates attribute
 - in rfc element 56
- uri element 76, 102
 - inside address 12

V

- value attribute
 - in seriesInfo element 60
- version attribute
 - in rfc element 56
- vspace element 84, 102
 - blankLines attribute 85
 - inside t 66

W

- width attribute
 - in artwork element 17
 - in figure element 34
 - in ttcot element 84
- workgroup element 76, 102
 - inside front 35

X

- xml:space attribute
 - in artwork element 17
 - in spanx element 82

- xref element 76, 102
 - format attribute 77
 - inside annotation 13
 - inside blockquote 21
 - inside c 79
 - inside cref 24
 - inside dd 27
 - inside dt 29
 - inside em 30
 - inside li 37
 - inside name 39
 - inside postamble 81
 - inside preamble 81
 - inside strong 64
 - inside sub 64
 - inside sup 65
 - inside t 66
 - inside td 70
 - inside th 72
 - inside tt 75
 - inside ttc1 84
 - pageno attribute 78
 - target attribute 78
- xref formats
 - counter 77
 - default 77
 - none 78
 - title 78

Y

- year attribute
 - in date element 25

IAB Members at the Time of Approval

The IAB members at the time this memo was approved were (in alphabetical order):

[[A list will go here just before publication as an RFC]]

Acknowledgments

Thanks to everybody who reviewed this document and provided feedback and/or specification text. Thanks especially go to Julian Reschke for editing [[RFC7749](#)] and those who provided feedback on that document.

Most of the changes between this document and [RFC 7991](#) came from the diligent work of Henrik Levkowetz.

We also thank Marshall T. Rose for both the original design and the reference implementation of the "xml2rfc" processor.

Author's Address

John Levine (editor)
Temporary RFC Series Project Manager

EMail: rse@rfc-editor.org