

Network Working Group
Internet-Draft
Expires: December 24, 2006

N. Kushalnagar
Intel Corp
G. Montenegro
Microsoft Corporation
June 22, 2006

6LoWPAN: Overview, Assumptions, Problem Statement and Goals
[draft-ietf-6lowpan-problem-03.txt](#)

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on December 24, 2006.

Copyright Notice

Copyright (C) The Internet Society (2006).

Abstract

This document describes the assumptions, problem statement and goals for transmitting IP over IEEE 802.15.4 networks. The set of goals enumerated in this document form an initial set only. Additional goals may be found necessary over time and may be added to this document.

Table of Contents

1.	Introduction	3
1.1.	Requirements notation	3
2.	Overview	3
3.	Assumptions	4
4.	Problems	5
4.1.	IP Connectivity	5
4.2.	Topologies	6
4.3.	Limited Packet Size	6
4.4.	Limited configuration and management	6
4.5.	Service discovery	7
4.6.	Security	7
5.	Goals	7
6.	IANA Considerations	9
7.	Security Considerations	9
8.	Acknowledgements	10
9.	References	11
9.1.	Normative References	11
9.2.	Informative References	11
	Authors' Addresses	13
	Intellectual Property and Copyright Statements	14

1. Introduction

Low-power wireless personal area networks (LoWPANs) comprise devices that conform to the IEEE 802.15.4-2003 standard by the IEEE [[ieee802.15.4](#)]. IEEE 802.15.4 devices are characterized by short range, low bit rate, low power and low cost.

This document gives an overview of LoWPANs and describes how they benefit from IP and IPv6 networking. It describes LoWPAN requirements with regards to the IP layer and above, and spells out the underlying assumptions of IP for LoWPANs. Finally, it describes problems associated with enabling IP communication between devices in a LoWPAN, and defines goals to address these in a prioritized manner. Admittedly, not all items on this list are necessarily appropriate tasks for the IETF. Nevertheless, they are documented here to give a general overview of the larger problem. This is useful both to structure work within the IETF as well as to understand better how to coordinate with external organizations.

1.1. Requirements notation

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

2. Overview

A LoWPAN is a simple low cost communication network that allows wireless connectivity in applications with limited power and relaxed throughput requirements. A LoWPAN typically includes devices that work together to connect the physical environment to real-world applications, e.g., wireless sensors. LoWPANs conform to the IEEE 802.15.4-2003 standard. [[ieee802.15.4](#)].

Some of the characteristics of LoWPANs are:

1. Small packet size. Given that the maximum physical layer packet is 127 bytes, the resulting maximum frame size at the media access control layer is 102 octets. Link-layer security imposes further overhead, which in the maximum case (21 octets of overhead in the AES-CCM-128 case, versus 9 and 13 for AES-CCM-32 and AES-CCM-64, respectively) leaves 81 octets for data packets.
2. Support for both 16-bit short or IEEE 64-bit extended media access control addresses.

3. Low bandwidth. Data rates of 250 kbps, 40 kbps and 20 kbps for each of the currently defined physical layers (2.4 GHz, 915 MHz and 868 MHz, respectively).
4. Topologies include star and mesh operation.
5. Low power. Typically, some or all devices are battery operated.
6. Low cost. These devices are typically associated with sensors, switches, etc. This drives some of the other characteristics such as low processing, low memory, etc. Numerical values for "low" elided on purpose since costs tend to change over time.
7. Large number of devices expected to be deployed during the life-time of the technology. This number is expected to dwarf the number of deployed personal computers, for example.
8. Location of the devices is typically not predefined, as they tend to be deployed in an ad hoc fashion. Furthermore, sometimes the location of these devices may not be easily accessible. Additionally, these devices may move to new locations.
9. Devices within LoWPANs tend to be unreliable due to variety of reasons: uncertain radio connectivity, battery drain, device lockups, physical tampering, etc.
10. Devices within LoWPANs tend to be unavailable because they often are in sleep mode or in a power-down mode to conserve power.

The following sections take into account these characteristics in describing the assumptions, problems statement and goals for LoWPANs, and, in particular, for 6LoWPANs (IPv6-based LoWPAN networks).

3. Assumptions

Given the small packet size of LoWPANs, this document presumes applications typically send small amounts of data. However, the protocols themselves do not restrict bulk data transfers.

LoWPANs as described in this document are based on IEEE 802.15.4-2003. It is possible that the specification may undergo changes in the future and may change some of the requirements mentioned above.

Some of these assumptions are based on the limited capabilities of devices within LoWPANs. As devices become more powerful, and consume

less power, some of the requirements mentioned above may be somewhat relaxed.

While some LOWPAN devices are expected to be extremely limited (the so-called "Reduced Function Devices" or RFDs), more capable "Full Function Devices" (FFDs) will also be present, albeit in much smaller numbers. FFDs will typically have more resources and be mains powered. Accordingly, FFDs will aid RFDs by providing functions such as network coordination, packet forwarding, interfacing with other types of networks, etc.

The application of IP technology is assumed to provide the following benefits:

1. The pervasive nature of IP networks allows use of existing infrastructure.
2. IP-based technologies already exist, are well known and proven to be working.
3. An admittedly non-technical but important consideration is that intellectual property conditions for IP networking technology are either more favorable or at least better understood than proprietary and newer solutions.
4. Tools for diagnostics, management and commissioning of IP networks already exist.
5. IP-based devices can be connected readily to other IP-based networks, without the need for intermediate entities like translation gateways or proxies.

4. Problems

Based on the characteristics defined in the overview section, the following sections elaborate on the main problems with IP for LOWPANs.

4.1. IP Connectivity

The requirement for IP connectivity within a LOWPAN is driven by the following:

1. The many devices in a LOWPAN make network auto configuration and statelessness highly desirable. And for this, IPv6 has ready solutions.
2. The large number of devices poses the need for a large address space, well met by IPv6.
3. Given the limited packet size of LOWPANs, the IPv6 address format allows subsuming of IEEE 802.15.4 addresses if so desired.

4. Simple interconnectivity to other IP networks including the Internet.

However, given the limited packet size, headers for IPv6 and layers above must be compressed whenever possible.

4.2. Topologies

LOWPANs must support various topologies including mesh and star.

Mesh topologies imply multi-hop routing, to a desired destination. In this case, intermediate devices act as packet forwarders at the link layer (akin to routers at the network layer). Typically these are "full function devices" that have more capabilities in terms of power, computation, etc. The requirements on the routing protocol are:

1. Given the minimal packet size of LOWPANs, the routing protocol must impose low (or no) overhead on data packets, hopefully independently of the number of hops.
2. The routing protocols should have low routing overhead (low chattiness) balanced with topology changes and power conservation.
3. The computation and memory requirements in the routing protocol should be minimal to satisfy the low cost and low power objectives. Thus, storage and maintenance of large routing tables is detrimental.

As with mesh topologies, star topologies include provisioning a subset of devices with packet forwarding functionality. If, in addition to IEEE 802.15.4, these devices use other kinds of network interfaces such as ethernet or IEEE 802.11, the goal is to seamlessly integrate the networks built over those different technologies. This, of course, is a primary motivation to use IP to begin with.

4.3. Limited Packet Size

Applications within LOWPANs are expected to originate small packets. Adding all layers for IP connectivity should still allow transmission in one frame without incurring excessive fragmentation and reassembly. Furthermore, protocols must be designed or chosen so that the individual "control/protocol packets" fit within a single 802.15.4 frame.

4.4. Limited configuration and management

As alluded to above, devices within LOWPANs are expected to be deployed in exceedingly large numbers. Additionally, they are

expected to have limited display and input capabilities. Furthermore, the location of some of these devices may be hard to reach. Accordingly, protocols used in LowPANs should have minimal configuration, preferably work "out of the box", be easy to bootstrap, and enable the network to self heal given the inherent unreliable characteristic of these devices. Network management should have little overhead yet be powerful enough to control dense deployment of devices.

4.5. Service discovery

LowPANs require simple service discovery network protocols to discover, control and maintain services provided by devices. In some cases, especially in dense deployments, abstraction of several nodes to provide a service may be beneficial. In order to enable such features, new protocols may have to be designed.

4.6. Security

IEEE 802.15.4 mandates link-layer security based on AES, but it omits any details about topics like bootstrapping, key management and security at higher layers. Of course, a complete security solution for LowPAN devices must consider application needs very carefully. Please refer to the security consideration section below for a more detailed discussion and in-depth security requirements.

5. Goals

The goals mentioned below are general and not limited to IETF activities. As such, they may not only refer to work that can be done within the IETF (e.g., specification required to transmit IP, profile of best practices for transmitting IP packets, and associated upper level protocols, etc). They also point at work more relevant to other standards bodies (e.g., desirable changes to or profiles relevant to IEEE 802.15.4, W3C, etc). When the goals fall under the IETF's purview, they serve to point out what those efforts should strive to accomplish, regardless of whether they are pursued within one (or more) new (or existing) working groups. When the goals do not fall under the purview of the IETF, documenting them here serves as input to other organizations [[liaison](#)].

Note that a common underlying goal is to reduce packet overhead, bandwidth consumption, processing requirements and power consumption.

The following are the goals according to priority for LowPANs:

1. Fragmentation and Reassembly layer: As mentioned in the overview, the protocol data units may be as small 81 bytes. This is obviously far below the minimum IPv6 packet size of 1280 octets, and in keeping with [section 5](#) of the IPv6 specification [[RFC2460](#)], a fragmentation and reassembly adaptation layer must be provided at the layer below IP.
2. Header Compression: Given that in the worst case the maximum size available for transmitting IP packets over IEEE 802.15.4 frame is 81 octets, and that the IPv6 header is 40 octets long, (without optional headers), this leaves only 41 octets for upper-layer protocols, like UDP and TCP. UDP uses 8 octets in the header and TCP uses 20 octets. This leaves 33 octets for data over UDP and 21 octets for data over TCP. Additionally, as pointed above, there is also a need for a fragmentation and reassembly layer, which will use even more octets leaving very few octets for data. Thus if one were to use the protocols as is, it would lead to excessive fragmentation and reassembly even when data packets are just 10s of octets long. This points to the need for header compression. As there is much published and in-progress standardization work on header compression, the 6LOWPAN community needs to investigate using existing header compression techniques, and, if necessary, specify new ones.
3. Address Autoconfiguration: [[I-D.ietf-ipv6-rfc2462bis](#)] specifies methods for creating IPv6 stateless address auto configuration. Stateless auto configuration (as compared to stateful) is attractive for 6LOWPANs, because it reduces the configuration overhead on the hosts. There is a need for a method to generate an "interface identifier" from the EUI-64 [[EUI64](#)] assigned to the IEEE 802.15.4 device.
4. Mesh Routing Protocol: A routing protocol to support a multi-hop mesh network is necessary. There is much published work on adhoc multi hop routing for devices. Some examples include [[RFC3561](#)], [[RFC3626](#)], [[RFC3684](#)], all experimental. Also, these protocols are designed to use IP-based addresses that have large overheads. For example, the AODV [[RFC3561](#)] routing protocol uses 48 octets for a route request based on IPv6 addressing. Given the packet-size constraints, transmitting this packet without fragmentation and reassembly may be difficult. Thus, care should be taken when using existing routing protocols (or designing new ones) so that the routing packets fit within a single IEEE 802.15.4 frame.
5. Network Management: One of the points of transmitting IPv6 packets, is to reuse existing protocols as much as possible. Network management functionality is critical for LOWPANs. [[RFC3411](#)] specifies SNMPv3 protocol operations. SNMP

functionality may be translated "as is" to LoWPANs. However, further investigation is required to determine if it is suitable, or if an appropriate adaption is in order. This adaptation could include limiting the data types and simplifying the Basic Encoding Rules so as to reduce the size and complexity of the ASN.1 parser, thereby reducing the memory and processing needs to better fit into the limited memory and power of LoWPAN devices.

6. Implementation Considerations: It may be the case that transmitting IP over IEEE 802.15.4 would become more beneficial if implemented in a "certain" way. Accordingly, implementation considerations are to be documented.
7. Application and higher layer Considerations: As header compression becomes more prevalent, overall performance will depend even more on efficiency of application protocols. Heavyweight protocols based on XML such as SOAP [[SOAP](#)], may not be suitable for LoWPANs. As such, more compact encodings (and perhaps protocols) may become necessary. The goal here is to specify or suggest modifications to existing protocols so that they are suitable for LoWPANs. Furthermore, application level interoperability specifications may also become necessary in the future and may thus be specified.
8. Security Considerations: Security threats at different layers must be clearly understood and documented. Bootstrapping of devices into a secure network could also be considered given the location, limited display, high density and ad hoc deployment of devices.

6. IANA Considerations

This document contains no IANA considerations.

7. Security Considerations

IPv6 over LoWPAN (6LoWPAN) applications often require confidentiality and integrity protection. This can be provided at the application, transport, network, and/or at the link layer (i.e., within the 6LoWPAN set of specifications). In all these cases, prevailing constraints will influence the choice of a particular protocol. Some of the more relevant constraints are small code size, low power operation, low complexity, and small bandwidth requirements.

Given these constraints, first, a threat model for 6LoWPAN devices needs to be developed in order to weigh any risks against the cost of

their mitigations while making meaningful assumptions and simplifications. Some examples for threats that should be considered are man-in-the-middle attacks and denial of service attacks.

A separate set of security considerations apply to bootstrapping a 6LoWPAN device into the network (e.g., for initial key establishment). This generally involves application level exchanges or out-of-band techniques for the initial key establishment, and may rely on application-specific trust models; thus, it is considered extraneous to 6LoWPAN and is not addressed in these specifications. In order to be able to select (or design) this next set of protocols, there needs to be a common model of the keying material created by the initial key establishment.

Beyond initial key establishment, protocols for subsequent key management as well as to secure the data traffic do fall under the purview of 6LoWPAN. Here, the different alternatives (TLS, IKE/IPsec, etc.) must be evaluated in light of the 6LoWPAN constraints.

One argument for using link layer security is that most IEEE 802.15.4 devices already have support for AES link-layer security. AES is a block cipher operating on blocks of fixed length, i.e., 128 bits. To encrypt longer messages, several modes of operation may be used. The earliest modes described, such as ECB, CBC, OFB and CFB provide only confidentiality, and this does not ensure message integrity. Other modes have been designed which ensure both confidentiality and message integrity, such as CCM* mode. 6LoWPAN networks can operate in any of the previous modes, but it is desirable to utilize the most secure modes available for link-layer security (e.g., CCM*), and build upon it.

For network layer security, two models are applicable: end-to-end security, e.g. using IPsec transport mode, or security that is limited to the wireless portion of the network, e.g. using a security gateway and IPsec tunnel mode. The disadvantage of the latter is the larger header size, which is significant at the 6LoWPAN frame MTUs. To simplify 6LoWPAN implementations, it is beneficial to identify the relevant security model, and to identify a preferred set of cipher suites that are appropriate given the constraints.

8. Acknowledgements

Thanks to Geoff Mulligan, Soohong Daniel Park, Samita Chakrabarti and Brijesh Kumar for their comments and help in shaping this document.

9. References

9.1. Normative References

- [EUI64] "GUIDELINES FOR 64-BIT GLOBAL IDENTIFIER (EUI-64) REGISTRATION AUTHORITY", IEEE <http://standards.ieee.org/regauth/oui/tutorials/EUI64.html>.
- [I-D.ietf-ipv6-2461bis] Narten, T., "Neighbor Discovery for IP version 6 (IPv6)", [draft-ietf-ipv6-2461bis-07](#) (work in progress), May 2006.
- [I-D.ietf-ipv6-rfc2462bis] Thomson, S., "IPv6 Stateless Address Autoconfiguration", [draft-ietf-ipv6-rfc2462bis-08](#) (work in progress), May 2005.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2460] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), December 1998.
- [ieee802.15.4] IEEE Computer Society, "IEEE Std. 802.15.4-2003", October 2003.

9.2. Informative References

- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, [RFC 3411](#), December 2002.
- [RFC3561] Perkins, C., Belding-Royer, E., and S. Das, "Ad hoc On-Demand Distance Vector (AODV) Routing", [RFC 3561](#), July 2003.
- [RFC3626] Clausen, T. and P. Jacquet, "Optimized Link State Routing Protocol (OLSR)", [RFC 3626](#), October 2003.
- [RFC3684] Ogier, R., Templin, F., and M. Lewis, "Topology Dissemination Based on Reverse-Path Forwarding (TBRPF)", [RFC 3684](#), February 2004.
- [RFC3756] Nikander, P., Kempf, J., and E. Nordmark, "IPv6 Neighbor Discovery (ND) Trust Models and Threats", [RFC 3756](#), May 2004.
- [SOAP] "SOAP", W3C <http://www.w3c.org/2000/xp/Group/>.

[liaison] "LIASONS",
IETF <http://www.ietf.org/liaisonActivities.html>.

Authors' Addresses

Nandakishore Kushalnagar
Intel Corp

Email: nandakishore.kushalnagar@intel.com

Gabriel Montenegro
Microsoft Corporation

Email: gabriel_montenegro_2000@yahoo.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2006). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

