

6man  
Internet-Draft  
Updates: [2460](#), [2780](#) (if approved)  
Intended status: Standards Track  
Expires: April 20, 2014

B. Carpenter  
Univ. of Auckland  
S. Jiang  
Huawei Technologies Co., Ltd  
October 17, 2013

**Transmission and Processing of IPv6 Extension Headers**  
**draft-ietf-6man-ext-transmit-05**

Abstract

Various IPv6 extension headers have been standardised since the IPv6 standard was first published. This document updates [RFC 2460](#) to clarify how intermediate nodes should deal with such extension headers and with any that are defined in future. It also specifies how extension headers should be registered by IANA, with a corresponding minor update to [RFC 2780](#).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 20, 2014.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction and Problem Statement . . . . .	<a href="#">2</a>
<a href="#">1.1.</a>	Terminology . . . . .	<a href="#">4</a>
<a href="#">2.</a>	Requirement to Transmit Extension Headers . . . . .	<a href="#">4</a>
<a href="#">2.1.</a>	All Extension Headers . . . . .	<a href="#">5</a>
<a href="#">2.2.</a>	Hop-by-Hop Options . . . . .	<a href="#">6</a>
<a href="#">3.</a>	Security Considerations . . . . .	<a href="#">6</a>
<a href="#">4.</a>	IANA Considerations . . . . .	<a href="#">7</a>
<a href="#">5.</a>	Acknowledgements . . . . .	<a href="#">8</a>
<a href="#">6.</a>	Change log [RFC Editor: Please remove] . . . . .	<a href="#">8</a>
<a href="#">7.</a>	References . . . . .	<a href="#">9</a>
<a href="#">7.1.</a>	Normative References . . . . .	<a href="#">9</a>
<a href="#">7.2.</a>	Informative References . . . . .	<a href="#">9</a>
	Authors' Addresses . . . . .	<a href="#">10</a>

## [1.](#) Introduction and Problem Statement

In IPv6, an extension header is any header that follows the initial 40 bytes of the packet and precedes the upper layer header (which might be a transport header, an ICMPv6 header, or a notional "No Next Header").

An initial set of IPv6 extension headers was defined by [\[RFC2460\]](#), which also described how they should be handled by intermediate nodes, with the exception of the hop-by-hop options header:

"...extension headers are not examined or processed by any node along a packet's delivery path, until the packet reaches the node (or each of the set of nodes, in the case of multicast) identified in the Destination Address field of the IPv6 header."

This provision meant that forwarding nodes should be completely transparent to extension headers. There was no provision for forwarding nodes to modify them, remove them, insert them, or use them to affect forwarding behaviour. Thus, new extension headers could be introduced progressively, used only by hosts that have been updated to create and interpret them [\[RFC6564\]](#). The extension header mechanism is an important part of the IPv6 architecture, and several new extension headers have been standardised since [RFC 2460](#).

Today, IPv6 packets are often forwarded not only on the basis of their first 40 bytes by straightforward IP routing. Some routers, and a variety of intermediate nodes often referred to as middleboxes,



such as firewalls, load balancers, or packet classifiers, might inspect other parts of each packet. Indeed, such middlebox functions are often embedded in routers. However, experience has shown that as a result, the network is not transparent to IPv6 extension headers. Contrary to [Section 4 of RFC 2460](#), middleboxes sometimes examine and process the entire IPv6 packet before making a decision to either forward or discard the packet. This means that they need to traverse the chain of extension headers, if present, until they find the transport header (or an encrypted payload). Unfortunately, because not all IPv6 extension headers follow a uniform TLV format, this process is clumsy and requires knowledge of each extension header's format. A separate problem is that the header chain may even be fragmented [[I-D.ietf-6man-oversized-header-chain](#)].

The process is potentially slow as well as clumsy, possibly precluding its use in nodes attempting to process packets at line speed. The present document does not intend to solve this problem, which is caused by the fundamental architecture of IPv6 extension headers. This document focuses on clarifying how the header chain should be handled in the current IPv6 architecture.

If they encounter an unrecognised extension header type, some firewalls treat the packet as suspect and drop it. Unfortunately, it is an established fact that several widely used firewalls do not recognise some or all of the extension headers standardised since [RFC 2460](#). It has also been observed that certain firewalls do not even handle all the extension headers standardised in [RFC 2460](#), including the fragment header [[I-D.taylor-v6ops-fragdrop](#)], causing fundamental problems of end-to-end connectivity. This applies in particular to firewalls that attempt to inspect packets at very high speed, since they cannot take the time to reassemble fragmented packets, especially when under a denial of service attack.

Other types of middlebox, such as load balancers or packet classifiers, might also fail in the presence of extension headers that they do not recognise.

A contributory factor to this problem is that, because extension headers are numbered out of the existing IP Protocol Number space, there is no collected list of them. For this reason, it is hard for an implementor to quickly identify the full set of standard extension headers. An implementor who consults only [RFC 2460](#) will miss all extension headers defined subsequently.

This combination of circumstances creates a "Catch-22" situation [[Heller](#)] for the deployment of any newly standardised extension header except for local use. It cannot be widely deployed, because existing middleboxes will drop it on many paths through the Internet.



However, most middleboxes will not be updated to allow the new header to pass until it has been proved safe and useful on the open Internet, which is impossible until the middleboxes have been updated.

The uniform TLV format now defined for extension headers [[RFC6564](#)] will improve the situation, but only for future extensions. Some tricky and potentially malicious cases will be avoided by forbidding very long chains of extension headers that need to be fragmented [[I-D.ietf-6man-oversized-header-chain](#)]. This will alleviate concerns that stateless firewalls cannot locate a complete header chain as required by the present document.

However, these changes are insufficient to correct the underlying problem. The present document clarifies that the above requirement from [RFC 2460](#) applies to all types of nodes that forward IPv6 packets and to all extension headers standardised now and in the future. It also requests IANA to create a subsidiary registry that clearly identifies extension header types, and updates [RFC 2780](#) accordingly. Fundamental changes to the IPv6 extension header architecture are out of scope for this document.

Also, Hop-by-Hop options are not handled by many high speed routers, or are processed only on a slow path. This document also updates the requirements for processing the Hop-by-Hop options header to make them more realistic.

### **[1.1.](#) Terminology**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

In the remainder of this document, the term "forwarding node" refers to any router, firewall, load balancer, prefix translator, or any other device or middlebox that forwards IPv6 packets with or without examining the packet in any way.

In this document "standard" IPv6 extension headers are those specified in detail by IETF standards actions. "Experimental" extension headers include those defined by any Experimental RFC, and the header values 253 and 254 defined by [[RFC3692](#)] and [[RFC4727](#)] when used as experimental extension headers. "Defined" extension headers are the "standard" extension headers plus the "experimental" ones.

## **[2.](#) Requirement to Transmit Extension Headers**



## **2.1. All Extension Headers**

As mentioned above, forwarding nodes that discard packets containing extension headers are known to cause connectivity failures and deployment problems. Therefore, it is important that forwarding nodes that inspect IPv6 headers can parse all defined extension headers and deal with them appropriately, as specified in this section.

Any forwarding node along an IPv6 packet's path, which forwards the packet for any reason, **SHOULD** do so regardless of any extension headers that are present, as required by [RFC 2460](#). Exceptionally, if a forwarding node is designed to examine extension headers for any reason, such as firewalling, it **MUST** recognise and deal appropriately with all standard IPv6 extension header types and **SHOULD** recognise and deal appropriately with experimental IPv6 extension header types. The list of standard and experimental extension header types is maintained by IANA (see [Section 4](#)) and implementors are advised to check this list regularly for updates.

[RFC 2460](#) requires destination hosts to discard packets containing unrecognised extension headers. However, intermediate forwarding nodes **SHOULD NOT** do this, since that might cause them to inadvertently discard traffic using a recently standardised extension header, not yet recognised by the intermediate node. The exceptions to this rule are discussed next.

If a forwarding node discards a packet containing a standard IPv6 extension header, it **MUST** be the result of a configurable policy, and not just the result of a failure to recognise such a header. This means that the discard policy for each standard type of extension header **MUST** be individually configurable. The default configuration **SHOULD** allow all standard extension headers.

Experimental IPv6 extension headers **SHOULD** be treated in the same way as standard extension headers, including an individually configurable discard policy. However, the default configuration **MAY** drop experimental extension headers.

Forwarding nodes **MUST** be configurable to allow packets containing unrecognised extension headers, but the default configuration **MAY** drop such packets.

The IPv6 Routing Header Types 0 and 1 have been deprecated [[RFC5095](#)]. However, this does not mean that the IPv6 Routing Header can be unconditionally dropped by forwarding nodes. Packets containing standardised and undeprecated Routing Headers **SHOULD** be forwarded by default. At the time of writing, these include Type 2 [[RFC6275](#)],





Type 3 [[RFC6554](#)], and the experimental Routing Header Types 253 and 254 [[RFC4727](#)]. Others may be defined in future.

## 2.2. Hop-by-Hop Options

The IPv6 Hop-by-Hop Options header SHOULD be processed by intermediate forwarding nodes as described in [[RFC2460](#)]. However, it is to be expected that high performance routers will either ignore it, or assign packets containing it to a slow processing path. Designers planning to use a Hop-by-Hop option need to be aware of this likely behaviour.

As a reminder, in [RFC 2460](#), it is stated that the Hop-by-Hop Options header, if present, must be first.

## 3. Security Considerations

Forwarding nodes that operate as firewalls MUST conform to the requirements in the previous section in order to respect the IPv6 extension header architecture. In particular, packets containing standard extension headers are only to be discarded as a result of an intentionally configured policy.

These changes do not affect a firewall's ability to filter out traffic containing unwanted or suspect extension headers, if configured to do so. However, the changes do require firewalls to be capable of permitting any or all extension headers, if configured to do so. The default configurations are intended to allow normal use of any standard extension header, avoiding the connectivity issues described in [Section 1](#) and [Section 2.1](#).

As noted above, the default configuration might drop packets containing experimental extension headers. There is no header length field in an IPv6 header, and header types 253 and 254 might be used either for experimental extension headers or for experimental payload types. Therefore, there is no generic algorithm by which a firewall can distinguish these two cases and analyze the remainder of the packet. This should be considered when deciding on the appropriate default action for header types 253 and 254.

When new extension headers are standardised in the future, those implementing and configuring forwarding nodes, including firewalls, will need to take them into account. A newly defined header will exercise new code paths in a host that does recognise it, so caution may be required. Additional security issues with experimental values or new extension headers are to be found in [[RFC4727](#)] and [[RFC6564](#)]. As a result, it is to be expected that the deployment process will be slow and will depend on satisfactory operational experience. Until



deployment is complete, the new extension will fail in some parts of the Internet. This aspect needs to be considered when deciding to standardise a new extension. Specific security considerations for each new extension should be documented in the document that defines it.

#### **4. IANA Considerations**

IANA is requested to clearly mark in the Assigned Internet Protocol Numbers registry those values which are also IPv6 Extension Header types defined by an IETF Standards Action or IESG Approval (see list below), for example by adding an extra column title "IPv6 Extension Header" to indicate this. This will also apply to any IPv6 Extension Header types defined in the future.

Additionally, IANA is requested to close the existing empty IPv6 Next Header Types registry to new entries, and redirect its users to a new IPv6 Extension Header Types registry. This will contain only those protocol numbers which are also marked as IPv6 Extension Header types in the Assigned Internet Protocol Numbers registry. Experimental values will be marked as such. The initial list will be as follows:

- o 0, Hop-by-Hop Options, [[RFC2460](#)]
- o 43, Routing, [[RFC2460](#)], [[RFC5095](#)]
- o 44, Fragment, [[RFC2460](#)]
- o 50, Encapsulating Security Payload, [[RFC4303](#)]
- o 51, Authentication, [[RFC4302](#)]
- o 60, Destination Options, [[RFC2460](#)]
- o 135, MIPv6, [[RFC6275](#)]
- o 139, experimental use, HIP, [[RFC5201](#)]
- o 140, shim6, [[RFC5533](#)]
- o 253, experimental use, [[RFC3692](#)], [[RFC4727](#)]
- o 254, experimental use, [[RFC3692](#)], [[RFC4727](#)]

This list excludes type 59, No Next Header, [[RFC2460](#)], which is not an extension header as such.



The references to the IPv6 Next Header field in [[RFC2780](#)] are to be interpreted as also applying to the IPv6 Extension Header field and the IPv6 Extension Header Types registry will be managed accordingly.

## 5. Acknowledgements

This document was triggered by mailing list discussions including John Leslie, Stefan Marksteiner and others. Valuable comments and contributions were made by Dominique Barthel, Tim Chown, Lorenzo Colitti, Fernando Gont, C. M. Heard, Bob Hinden, Ray Hunter, Suresh Krishnan, Marc Lampo, Sandra Murphy, Michael Richardson, Dan Romascanu, Dave Thaler, Joe Touch, Bjoern Zeeb, and others.

Brian Carpenter was a visitor at the Computer Laboratory, Cambridge University during part of this work.

This document was produced using the xml2rfc tool [[RFC2629](#)].

## 6. Change log [RFC Editor: Please remove]

[draft-ietf-6man-ext-transmit-05](#): updates following IESG comments, 2013-10-17.

[draft-ietf-6man-ext-transmit-04](#): updates following IETF Last Call, normative requirements clarified, IANA considerations clarified, security considerations expanded, 2013-09-26.

[draft-ietf-6man-ext-transmit-03](#): added details for experimental values, various clarifications and minor corrections, 2013-08-22.

[draft-ietf-6man-ext-transmit-02](#): explicit mention of header types 253 and 254, editorial fixes, 2013-08-06.

[draft-ietf-6man-ext-transmit-01](#): tuned use of normative language, clarified that only standardised extensions are covered (hence excluding HIP), 2013-05-29.

[draft-ietf-6man-ext-transmit-00](#): first WG version, more clarifications, 2013-03-26.

[draft-carpenter-6man-ext-transmit-02](#): clarifications following WG comments, recalibrated firewall requirements, 2013-02-22.

[draft-carpenter-6man-ext-transmit-01](#): feedback at IETF85: clarify scope and impact on firewalls, discuss line-speed processing and lack of uniform TLV format, added references, restructured IANA considerations, 2012-11-13.



[draft-carpenter-6man-ext-transmit-00](#): original version, 2012-08-14.

## 7. References

### 7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2460] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), December 1998.
- [RFC2780] Bradner, S. and V. Paxson, "IANA Allocation Guidelines For Values In the Internet Protocol and Related Headers", [BCP 37](#), [RFC 2780](#), March 2000.
- [RFC3692] Narten, T., "Assigning Experimental and Testing Numbers Considered Useful", [BCP 82](#), [RFC 3692](#), January 2004.
- [RFC4727] Fenner, B., "Experimental Values In IPv4, IPv6, ICMPv4, ICMPv6, UDP, and TCP Headers", [RFC 4727](#), November 2006.
- [RFC6564] Krishnan, S., Woodyatt, J., Kline, E., Hoagland, J., and M. Bhatia, "A Uniform Format for IPv6 Extension Headers", [RFC 6564](#), April 2012.

### 7.2. Informative References

- [Heller] Heller, J., "Catch-22", Simon and Schuster , 1961.
- [I-D.ietf-6man-oversized-header-chain]  
Gont, F., Manral, V., and R. Bonica, "Implications of Oversized IPv6 Header Chains", [draft-ietf-6man-oversized-header-chain-08](#) (work in progress), October 2013.
- [I-D.taylor-v6ops-fragdrop]  
Jaeggli, J., Colitti, L., Kumari, W., Vyncke, E., Kaeo, M., and T. Taylor, "Why Operators Filter Fragments and What It Implies", [draft-taylor-v6ops-fragdrop-01](#) (work in progress), June 2013.
- [RFC2629] Rose, M., "Writing I-Ds and RFCs using XML", [RFC 2629](#), June 1999.
- [RFC4302] Kent, S., "IP Authentication Header", [RFC 4302](#), December 2005.





- [RFC4303] Kent, S., "IP Encapsulating Security Payload (ESP)", [RFC 4303](#), December 2005.
- [RFC5095] Abley, J., Savola, P., and G. Neville-Neil, "Deprecation of Type 0 Routing Headers in IPv6", [RFC 5095](#), December 2007.
- [RFC5201] Moskowitz, R., Nikander, P., Jokela, P., and T. Henderson, "Host Identity Protocol", [RFC 5201](#), April 2008.
- [RFC5533] Nordmark, E. and M. Bagnulo, "Shim6: Level 3 Multihoming Shim Protocol for IPv6", [RFC 5533](#), June 2009.
- [RFC6275] Perkins, C., Johnson, D., and J. Arkko, "Mobility Support in IPv6", [RFC 6275](#), July 2011.
- [RFC6554] Hui, J., Vasseur, JP., Culler, D., and V. Manral, "An IPv6 Routing Header for Source Routes with the Routing Protocol for Low-Power and Lossy Networks (RPL)", [RFC 6554](#), March 2012.

#### Authors' Addresses

Brian Carpenter  
Department of Computer Science  
University of Auckland  
PB 92019  
Auckland 1142  
New Zealand

Email: [brian.e.carpenter@gmail.com](mailto:brian.e.carpenter@gmail.com)

Sheng Jiang  
Huawei Technologies Co., Ltd  
Q14, Huawei Campus  
No.156 Beiqing Road  
Hai-Dian District, Beijing 100095  
P.R. China

Email: [jiangsheng@huawei.com](mailto:jiangsheng@huawei.com)

