

IPv6 Maintenance
Internet-Draft
Obsoletes: [2452](#), [2454](#), [2465](#), [2466](#) (if
approved)
Intended status: Informational
Expires: February 26, 2016

B. Fenner
Arista Networks, Inc.
August 25, 2015

Republishing the IPV6-specific MIB modules as obsolete
draft-ietf-6man-ipv6-mibs-obsolete-00

Abstract

In 2005, the IPv6 MIB update group published updated versions of the IP-MIB, UDP-MIB, TCP-MIB and IP-FORWARD-MIB modules, which use the InetAddressType/InetAddress construct to handle IPv4 and IPv6 in the same table. This document contains versions of the obsoleted IPV6-MIB, IPV6-TC, IPV6-ICMP-MIB, IPV6-TCP-MIB and IPV6-UDP-MIB modules, for the purpose of updating MIB module repositories.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 26, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

Internet-Draft

ipv6-mibs-obsolete

August 2015

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1.	Motivation	2
2.	Historic IPV6-TC	3
3.	Historic IPV6-MIB	4
4.	Historic IPV6-ICMP-MIB	38
5.	Historic IPV6-UDP-MIB	52
6.	Historic IPV6-TCP-MIB	55
7.	Reclassification	60
8.	Security Considerations	60
9.	IANA Considerations	61
10.	References	61
10.1.	Normative References	61
10.2.	Informative References	62
10.3.	URIs	62
Appendix A.	Change history	63
A.1.	Changes since draft-fenner-ipv6-mibs-obsolete-00	63
A.2.	Changes since draft-fenner-ipv6-mibs-obsolete-01	63
A.3.	Changes since draft-fenner-ipv6-mibs-obsolete-02	63
	Author's Address	63

[1.](#) Motivation

In 2005, the IPv6 MIB update group published updated versions of the IP-MIB [[RFC4293](#)], UDP-MIB [[RFC4113](#)], TCP-MIB [[RFC4022](#)] and IP-FORWARD-MIB [[RFC4292](#)] modules, which use the InetAddressType/InetAddress construct to handle IPv4 and IPv6 in the same table.

These documents were marked in the RFC Index as obsoleting the corresponding IPV6-MIBs, but the extracted content of these MIBs never changed in MIB repositories, and the original RFCs (as is normal IETF policy) never changed from being Proposed Standard.

This causes an unclear situation when simply looking at MIB repositories, so we are simply republishing these MIB modules with the SMI syntax changed to obsolete.

[2.](#) Historic IPV6-TC

```
IPV6-TC DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    Integer32                FROM SNMPv2-SMI
    TEXTUAL-CONVENTION        FROM SNMPv2-TC;
```

```
-- definition of textual conventions
```

```
Ipv6Address ::= TEXTUAL-CONVENTION
```

```
    DISPLAY-HINT "2x:"
    STATUS        obsolete
    DESCRIPTION
        "This data type is used to model IPv6 addresses.
        This is a binary string of 16 octets in network
        byte-order."
    SYNTAX        OCTET STRING (SIZE (16))
```

```
Ipv6AddressPrefix ::= TEXTUAL-CONVENTION
```

```
    DISPLAY-HINT "2x:"
    STATUS        obsolete
    DESCRIPTION
        "This data type is used to model IPv6 address
        prefixes. This is a binary string of up to 16
        octets in network byte-order."
    SYNTAX        OCTET STRING (SIZE (0..16))
```

```
Ipv6AddressIfIdentifier ::= TEXTUAL-CONVENTION
```

```
    DISPLAY-HINT "2x:"
    STATUS        obsolete
    DESCRIPTION
        "This data type is used to model IPv6 address
```

interface identifiers. This is a binary string
of up to 8 octets in network byte-order."
SYNTAX OCTET STRING (SIZE (0..8))

Ipv6IfIndex ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS obsolete
DESCRIPTION
"A unique value, greater than zero for each
internetwork-layer interface in the managed
system. It is recommended that values are assigned
contiguously starting from 1. The value for each

internetwork-layer interface must remain constant
at least from one re-initialization of the entity's
network management system to the next
re-initialization."
SYNTAX Integer32 (1..2147483647)

Ipv6IfIndexOrZero ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS obsolete
DESCRIPTION
"This textual convention is an extension of the
Ipv6IfIndex convention. The latter defines
a greater than zero value used to identify an IPv6
interface in the managed system. This extension
permits the additional value of zero. The value
zero is object-specific and must therefore be
defined as part of the description of any object
which uses this syntax. Examples of the usage of
zero might include situations where interface was
unknown, or when none or all interfaces need to be
referenced."
SYNTAX Integer32 (0..2147483647)

END

[3.](#) Historic IPV6-MIB

IPV6-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
mib-2, Counter32, Unsigned32, Integer32,
Gauge32 FROM SNMPv2-SMI
DisplayString, PhysAddress, TruthValue, TimeStamp,
VariablePointer, RowPointer FROM SNMPv2-TC
MODULE-COMPLIANCE, OBJECT-GROUP,
NOTIFICATION-GROUP FROM SNMPv2-CONF
Ipv6IfIndex, Ipv6Address, Ipv6AddressPrefix,
Ipv6AddressIfIdentifier,
Ipv6IfIndexOrZero FROM IPV6-TC;

ipv6MIB MODULE-IDENTITY

LAST-UPDATED "201505282112Z"
ORGANIZATION "IETF IPv6 Working Group"
CONTACT-INFO
" Dimitry Haskin

Postal: Bay Networks, Inc.

Fenner

Expires February 26, 2016

[Page 4]

Internet-Draft

ipv6-mibs-obsolete

August 2015

660 Techology Park Drive.
Billerica, MA 01821

US

Tel: +1-978-916-8124
E-mail: dhaskin@baynetworks.com

Steve Onishi

Postal: Bay Networks, Inc.
3 Federal Street
Billerica, MA 01821
US

Tel: +1-978-916-3816

E-mail: sonishi@baynetworks.com"

DESCRIPTION

"The obsolete MIB module for entities implementing the IPv6
protocol. Use the IP-MIB or IP-FORWARD-MIB instead."

REVISION "201505282112Z"

DESCRIPTION

```
"Obsoleting this MIB module; it has been replaced by
the revised IP-MIB (RFC4293) and IP-FORWARD-MIB
(RFC4292)."
REVISION "9801082155Z"
DESCRIPTION
  "First revision, published as RFC2465"
 ::= { mib-2 55 }
```

```
-- the IPv6 general group
```

```
ipv6MIBObjects OBJECT IDENTIFIER ::= { ipv6MIB 1 }
```

```
ipv6Forwarding OBJECT-TYPE
  SYNTAX      INTEGER {
                forwarding(1),    -- acting as a router
                                     -- NOT acting as
                notForwarding(2) -- a router
              }
  MAX-ACCESS  read-write
  STATUS      obsolete
  DESCRIPTION
```

```
  "The indication of whether this entity is acting
  as an IPv6 router in respect to the forwarding of
  datagrams received by, but not addressed to, this
  entity.  IPv6 routers forward datagrams.  IPv6
```

Fenner

Expires February 26, 2016

[Page 5]

Internet-Draft

ipv6-mibs-obsolete

August 2015

hosts do not (except those source-routed via the host).

Note that for some managed nodes, this object may take on only a subset of the values possible. Accordingly, it is appropriate for an agent to return a 'wrongValue' response if a management station attempts to change this object to an inappropriate value.

```
  This object is obsoleted by IP-MIB::ipv6IpForwarding."
 ::= { ipv6MIBObjects 1 }
```

```
ipv6DefaultHopLimit OBJECT-TYPE
  SYNTAX      INTEGER(0..255)
```

MAX-ACCESS read-write

STATUS obsolete

DESCRIPTION

"The default value inserted into the Hop Limit field of the IPv6 header of datagrams originated at this entity, whenever a Hop Limit value is not supplied by the transport layer protocol.

This object is obsoleted by IP-MIB::ipv6IpDefaultHopLimit."

DEFVAL { 64 }

::= { ipv6MIBObjects 2 }

ipv6Interfaces OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of IPv6 interfaces (regardless of their current state) present on this system.

This object is obsolete; there is no direct replacement but its value can be derived from the number of rows in the IP-MIB::ipv6InterfaceTable."

::= { ipv6MIBObjects 3 }

ipv6IfTableLastChange OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The value of sysUpTime at the time of the last insertion or removal of an entry in the ipv6IfTable. If the number of entries has been

unchanged since the last re-initialization of the local network management subsystem, then this object contains a zero value.

This object is obsoleted by
IP-MIB::ipv6InterfaceTableLastChange."

::= { ipv6MIBObjects 4 }

-- the IPv6 Interfaces table

ipv6IfTable OBJECT-TYPE

SYNTAX SEQUENCE OF Ipv6IfEntry

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"The IPv6 Interfaces table contains information on the entity's internetwork-layer interfaces. An IPv6 interface constitutes a logical network layer attachment to the layer immediately below

IPv6 including internet layer 'tunnels', such as tunnels over IPv4 or IPv6 itself.

This table is obsoleted by IP-MIB::ipv6InterfaceTable."
 ::= { ipv6MIBObjects 5 }

ipv6IfEntry OBJECT-TYPE

SYNTAX Ipv6IfEntry

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"An interface entry containing objects about a particular IPv6 interface.

This object is obsoleted by IP-MIB::ipv6InterfaceEntry."
 INDEX { ipv6IfIndex }
 ::= { ipv6IfTable 1 }

Ipv6IfEntry ::= SEQUENCE {

ipv6IfIndex	Ipv6IfIndex,
ipv6IfDescr	DisplayString,
ipv6IfLowerLayer	VariablePointer,
ipv6IfEffectiveMtu	Unsigned32,
ipv6IfReasmMaxSize	Unsigned32,
ipv6IfIdentifier	Ipv6AddressIfIdentifier,
ipv6IfIdentifierLength	INTEGER,
ipv6IfPhysicalAddress	PhysAddress,
ipv6IfAdminStatus	INTEGER,


```
        ipv6IfLastChange      TimeStamp
    }
```

ipv6IfIndex OBJECT-TYPE

```
SYNTAX      Ipv6IfIndex
MAX-ACCESS  not-accessible
STATUS      obsolete
DESCRIPTION
```

"A unique non-zero value identifying the particular IPv6 interface.

This object is obsoleted. In the IP-MIB, interfaces are simply identified by IfIndex."

```
::= { ipv6IfEntry 1 }
```

ipv6IfDescr OBJECT-TYPE

```
SYNTAX      DisplayString
MAX-ACCESS  read-write
STATUS      obsolete
DESCRIPTION
```

"A textual string containing information about the interface. This string may be set by the network management system.

This object is obsoleted by IF-MIB::ifDescr."

```
::= { ipv6IfEntry 2 }
```

ipv6IfLowerLayer OBJECT-TYPE

```
SYNTAX      VariablePointer
MAX-ACCESS  read-only
STATUS      obsolete
DESCRIPTION
```

"This object identifies the protocol layer over which this network interface operates. If this network interface operates over the data-link layer, then the value of this object refers to an instance of ifIndex [6]. If this network interface operates over an IPv4 interface, the value of this object refers to an instance of ipAdEntAddr [3].

If this network interface operates over another IPv6 interface, the value of this object refers to an instance of ipv6IfIndex. If this network interface is not currently operating over an active protocol layer, then the value of this object should be set to the OBJECT ID { 0 0 }.

This object is obsolete. The IF-STACK-TABLE may be used to express relationships between interfaces."
 ::= { ipv6IfEntry 3 }

ipv6IfEffectiveMtu OBJECT-TYPE

SYNTAX Unsigned32
UNITS "octets"
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION

"The size of the largest IPv6 packet which can be sent/received on the interface, specified in octets.

This object is obsolete. The value of IF-MIB::ifMtu for the corresponding value of ifIndex represents the MTU of the interface."

::= { ipv6IfEntry 4 }

ipv6IfReasmMaxSize OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)
UNITS "octets"
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION

"The size of the largest IPv6 datagram which this entity can re-assemble from incoming IPv6 fragmented datagrams received on this interface.

This object is obsoleted by IP-MIB::ipv6InterfaceReasmMaxSize."

::= { ipv6IfEntry 5 }

ipv6IfIdentifier OBJECT-TYPE

SYNTAX Ipv6AddressIfIdentifier
MAX-ACCESS read-write
STATUS obsolete
DESCRIPTION

"The Interface Identifier for this interface that is (at least) unique on the link this interface is attached to. The Interface Identifier is combined with an address prefix to form an interface address.

By default, the Interface Identifier is autoconfigured according to the rules of the link type this interface is attached to.

This object is obsoleted by IP-MIB::ipv6InterfaceIdentifier."
 ::= { ipv6IfEntry 6 }

ipv6IfIdentifierLength OBJECT-TYPE

SYNTAX INTEGER (0..64)

UNITS "bits"

MAX-ACCESS read-write

STATUS obsolete

DESCRIPTION

"The length of the Interface Identifier in bits.

This object is obsolete. It can be derived from the length of IP-MIB::ipv6InterfaceIdentifier; Interface Identifiers that are not an even number of octets are not supported."

::= { ipv6IfEntry 7 }

ipv6IfPhysicalAddress OBJECT-TYPE

SYNTAX PhysAddress

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The interface's physical address. For example, for an IPv6 interface attached to an 802.x link, this object normally contains a MAC address. Note that in some cases this address may differ from the address of the interface's protocol sub-layer. The interface's media-specific MIB must define the bit and byte ordering and the format of the value of this object. For interfaces which do not have such an address (e.g., a serial line), this object should contain an octet string of zero length.

This object is obsoleted by IF-MIB::ifPhysAddress."
 ::= { ipv6IfEntry 8 }

ipv6IfAdminStatus OBJECT-TYPE

SYNTAX INTEGER {
 up(1), -- ready to pass packets
 down(2)
}

MAX-ACCESS read-write

STATUS obsolete

DESCRIPTION

"The desired state of the interface. When a managed system initializes, all IPv6 interfaces start with ipv6IfAdminStatus in the down(2) state. As a result of either explicit management action or per configuration information retained by the managed system, ipv6IfAdminStatus is then changed to the up(1) state (or remains in the down(2) state).

Fenner

Expires February 26, 2016

[Page 10]

Internet-Draft

ipv6-mibs-obsolete

August 2015

This object is obsolete. IPv6 does not have a separate admin status; the admin status of the interface is represented by IF-MIB::ifAdminStatus."
 ::= { ipv6IfEntry 9 }

ipv6IfOperStatus OBJECT-TYPE

```
SYNTAX  INTEGER {
    up(1),                -- ready to pass packets

    down(2),
    noIfIdentifier(3), -- no interface identifier

                                -- status can not be
                                -- determined for some
    unknown(4),          -- reason

                                -- some component is
    notPresent(5)       -- missing
}
MAX-ACCESS  read-only
STATUS      obsolete
```

DESCRIPTION

"The current operational state of the interface. The noIfIdentifier(3) state indicates that no valid Interface Identifier is assigned to the interface. This state usually indicates that the link-local interface address failed Duplicate Address Detection. If ipv6IfAdminStatus is down(2) then ipv6IfOperStatus should be down(2). If ipv6IfAdminStatus is changed to up(1) then ipv6IfOperStatus should change to up(1) if the interface is ready to transmit and receive network traffic; it should remain in the down(2) or

noIfIdentifier(3) state if and only if there is a fault that prevents it from going to the up(1) state; it should remain in the notPresent(5) state if the interface has missing (typically, lower layer) components.

This object is obsolete. IPv6 does not have a separate operational status; the operational status of the interface is represented by IF-MIB::ifOperStatus."
 ::= { ipv6IfEntry 10 }

ipv6IfLastChange OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION

Fenner

Expires February 26, 2016

[Page 11]

Internet-Draft

ipv6-mibs-obsolete

August 2015

"The value of sysUpTime at the time the interface entered its current operational state. If the current state was entered prior to the last re-initialization of the local network management subsystem, then this object contains a zero value.

This object is obsolete. The last change of IF-MIB::ifOperStatus is represented by IF-MIB::ifLastChange."
 ::= { ipv6IfEntry 11 }

-- IPv6 Interface Statistics table

ipv6IfStatsTable OBJECT-TYPE
SYNTAX SEQUENCE OF Ipv6IfStatsEntry
MAX-ACCESS not-accessible
STATUS obsolete
DESCRIPTION
"IPv6 interface traffic statistics.

This table is obsoleted by the IP-MIB::ipIfStatsTable."
 ::= { ipv6MIBObjects 6 }

ipv6IfStatsEntry OBJECT-TYPE
SYNTAX Ipv6IfStatsEntry

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"An interface statistics entry containing objects
at a particular IPv6 interface.

This object is obsoleted by the IP-MIB::ipIfStatsEntry."

AUGMENTS { ipv6IfEntry }

::= { ipv6IfStatsTable 1 }

```
Ipv6IfStatsEntry ::= SEQUENCE {
    ipv6IfStatsInReceives
        Counter32,
    ipv6IfStatsInHdrErrors
        Counter32,
    ipv6IfStatsInTooBigErrors
        Counter32,
    ipv6IfStatsInNoRoutes
        Counter32,
    ipv6IfStatsInAddrErrors
        Counter32,
    ipv6IfStatsInUnknownProtos
        Counter32,
```

```
    ipv6IfStatsInTruncatedPkts
        Counter32,
    ipv6IfStatsInDiscards
        Counter32,
    ipv6IfStatsInDelivers
        Counter32,
    ipv6IfStatsOutForwDatagrams
        Counter32,
    ipv6IfStatsOutRequests
        Counter32,
    ipv6IfStatsOutDiscards
        Counter32,
    ipv6IfStatsOutFragOKs
        Counter32,
    ipv6IfStatsOutFragFails
        Counter32,
    ipv6IfStatsOutFragCreates
        Counter32,
```

```
    ipv6IfStatsReasmReqds
        Counter32,
    ipv6IfStatsReasmOKs
        Counter32,
    ipv6IfStatsReasmFails
        Counter32,
    ipv6IfStatsInMcastPkts
        Counter32,
    ipv6IfStatsOutMcastPkts
        Counter32
}
```

ipv6IfStatsInReceives OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The total number of input datagrams received by the interface, including those received in error.

This object is obsoleted by IP-MIB::ipIfStatsHCInReceives."
 ::= { ipv6IfStatsEntry 1 }

ipv6IfStatsInHdrErrors OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of input datagrams discarded due to errors in their IPv6 headers, including version

number mismatch, other format errors, hop count exceeded, errors discovered in processing their IPv6 options, etc.

This object is obsoleted by IP-MIB::ipIfStatsInHdrErrors."
 ::= { ipv6IfStatsEntry 2 }

ipv6IfStatsInTooBigErrors OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of input datagrams that could not be forwarded because their size exceeded the link MTU of outgoing interface.

This object is obsoleted. It was not replicated in the IP-MIB due to feedback that systems did not retain the incoming interface of a packet that failed fragmentation."

::= { ipv6IfStatsEntry 3 }

ipv6IfStatsInNoRoutes OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of input datagrams discarded because no route could be found to transmit them to their destination.

This object is obsoleted by IP-MIB::ipIfStatsInNoRoutes."

::= { ipv6IfStatsEntry 4 }

ipv6IfStatsInAddrErrors OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of input datagrams discarded because the IPv6 address in their IPv6 header's destination field was not a valid address to be received at this entity. This count includes invalid addresses (e.g., ::0) and unsupported addresses (e.g., addresses with unallocated prefixes). For entities which are not IPv6 routers and therefore do not forward datagrams, this counter includes datagrams discarded because the destination address was not a local address.

This object is obsoleted by IP-MIB::ipIfStatsInAddrErrors."
::= { ipv6IfStatsEntry 5 }

ipv6IfStatsInUnknownProtos OBJECT-TYPE

SYNTAX Counter32
MAX-ACCESS read-only
STATUS obsolete

DESCRIPTION

"The number of locally-addressed datagrams received successfully but discarded because of an unknown or unsupported protocol. This counter is incremented at the interface to which these datagrams were addressed which might not be necessarily the input interface for some of the datagrams.

This object is obsoleted by IP-MIB::ipIfStatsInUnknownProtos."
 ::= { ipv6IfStatsEntry 6 }

ipv6IfStatsInTruncatedPkts OBJECT-TYPE

SYNTAX Counter32
MAX-ACCESS read-only
STATUS obsolete

DESCRIPTION

"The number of input datagrams discarded because datagram frame didn't carry enough data.

This object is obsoleted by IP-MIB::ipIfStatsInTruncatedPkts."
 ::= { ipv6IfStatsEntry 7 }

ipv6IfStatsInDiscards OBJECT-TYPE

SYNTAX Counter32
MAX-ACCESS read-only
STATUS obsolete

DESCRIPTION

"The number of input IPv6 datagrams for which no problems were encountered to prevent their continued processing, but which were discarded (e.g., for lack of buffer space). Note that this counter does not include any datagrams discarded while awaiting re-assembly.

This object is obsoleted by IP-MIB::ipIfStatsInDiscards."
 ::= { ipv6IfStatsEntry 8 }

ipv6IfStatsInDelivers OBJECT-TYPE

SYNTAX Counter32
MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The total number of datagrams successfully delivered to IPv6 user-protocols (including ICMP). This counter is incremented at the interface to which these datagrams were addressed which might not be necessarily the input interface for some of the datagrams.

This object is obsoleted by IP-MIB::ipIfStatsHCInDelivers."
 ::= { ipv6IfStatsEntry 9 }

ipv6IfStatsOutForwDatagrams OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of output datagrams which this entity received and forwarded to their final destinations. In entities which do not act as IPv6 routers, this counter will include only those packets which were Source-Routed via this entity, and the Source-Route processing was successful. Note that for a successfully forwarded datagram the counter of the outgoing interface is incremented.

This object is obsoleted by
 IP-MIB::ipIfStatsHCOutForwDatagrams."
 ::= { ipv6IfStatsEntry 10 }

ipv6IfStatsOutRequests OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The total number of IPv6 datagrams which local IPv6 user-protocols (including ICMP) supplied to IPv6 in requests for transmission. Note that this counter does not include any datagrams counted in ipv6IfStatsOutForwDatagrams.

This object is obsoleted by IP-MIB::ipIfStatsHCOutRequests."
 ::= { ipv6IfStatsEntry 11 }

ipv6IfStatsOutDiscards OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

Fenner

Expires February 26, 2016

[Page 16]

Internet-Draft

ipv6-mibs-obsolete

August 2015

STATUS obsolete

DESCRIPTION

"The number of output IPv6 datagrams for which no problem was encountered to prevent their transmission to their destination, but which were discarded (e.g., for lack of buffer space). Note that this counter would include datagrams counted in ipv6IfStatsOutForwDatagrams if any such packets met this (discretionary) discard criterion.

This object is obsoleted by IP-MIB::ipIfStatsOutDiscards."
::= { ipv6IfStatsEntry 12 }

ipv6IfStatsOutFragOKs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of IPv6 datagrams that have been successfully fragmented at this output interface.

This object is obsoleted by IP-MIB::ipIfStatsOutFragOKs."
::= { ipv6IfStatsEntry 13 }

ipv6IfStatsOutFragFails OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of IPv6 datagrams that have been discarded because they needed to be fragmented at this output interface but could not be.

This object is obsoleted by IP-MIB::ipIfStatsOutFragFails."
::= { ipv6IfStatsEntry 14 }

ipv6IfStatsOutFragCreates OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of output datagram fragments that have been generated as a result of fragmentation at this output interface.

This object is obsoleted by IP-MIB::ipIfStatsOutFragCreates."
 ::= { ipv6IfStatsEntry 15 }

Fenner

Expires February 26, 2016

[Page 17]

Internet-Draft

ipv6-mibs-obsolete

August 2015

ipv6IfStatsReasmReqds OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of IPv6 fragments received which needed to be reassembled at this interface. Note that this counter is incremented at the interface to which these fragments were addressed which might not be necessarily the input interface for some of the fragments.

This object is obsoleted by IP-MIB::ipIfStatsReasmReqds."
 ::= { ipv6IfStatsEntry 16 }

ipv6IfStatsReasmOKs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of IPv6 datagrams successfully reassembled. Note that this counter is incremented at the interface to which these datagrams were addressed which might not be necessarily the input interface for some of the fragments.

This object is obsoleted by IP-MIB::ipIfStatsReasmOKs."
 ::= { ipv6IfStatsEntry 17 }

ipv6IfStatsReasmFails OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of failures detected by the IPv6 re-assembly algorithm (for whatever reason: timed out, errors, etc.). Note that this is not necessarily a count of discarded IPv6 fragments since some algorithms (notably the algorithm in [RFC 815](#)) can lose track of the number of fragments by combining them as they are received.

This counter is incremented at the interface to which these fragments were addressed which might not be necessarily the input interface for some of the fragments.

This object is obsoleted by IP-MIB::ipIfStatsReasmFails."
 ::= { ipv6IfStatsEntry 18 }

Fenner

Expires February 26, 2016

[Page 18]

Internet-Draft

ipv6-mibs-obsolete

August 2015

ipv6IfStatsInMcastPkts OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of multicast packets received by the interface

This object is obsoleted by IP-MIB::ipIfStatsHCInMcastPkts."
 ::= { ipv6IfStatsEntry 19 }

ipv6IfStatsOutMcastPkts OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of multicast packets transmitted by the interface

This object is obsoleted by IP-MIB::ipIfStatsHCOutMcastPkts."
 ::= { ipv6IfStatsEntry 20 }

-- Address Prefix table

-- The IPv6 Address Prefix table contains information on
-- the entity's IPv6 Address Prefixes that are associated

-- with IPv6 interfaces.

```
ipv6AddrPrefixTable OBJECT-TYPE
    SYNTAX SEQUENCE OF Ipv6AddrPrefixEntry
    MAX-ACCESS not-accessible
    STATUS obsolete
    DESCRIPTION
        "The list of IPv6 address prefixes of
        IPv6 interfaces.

        This table is obsoleted by IP-MIB::ipAddressPrefixTable."
    ::= { ipv6MIBObjects 7 }
```

```
ipv6AddrPrefixEntry OBJECT-TYPE
    SYNTAX Ipv6AddrPrefixEntry
    MAX-ACCESS not-accessible
    STATUS obsolete
    DESCRIPTION
        "An interface entry containing objects of
        a particular IPv6 address prefix.

        This entry is obsoleted by IP-MIB::ipAddressPrefixEntry."
```

```
INDEX { ipv6IfIndex,
        ipv6AddrPrefix,
        ipv6AddrPrefixLength }
::= { ipv6AddrPrefixTable 1 }
```

```
Ipv6AddrPrefixEntry ::= SEQUENCE {
    ipv6AddrPrefix          Ipv6AddressPrefix,
    ipv6AddrPrefixLength    INTEGER (0..128),
    ipv6AddrPrefixOnLinkFlag TruthValue,
    ipv6AddrPrefixAutonomousFlag TruthValue,
    ipv6AddrPrefixAdvPreferredLifetime Unsigned32,
    ipv6AddrPrefixAdvValidLifetime Unsigned32
}
```

```
ipv6AddrPrefix OBJECT-TYPE
    SYNTAX Ipv6AddressPrefix
    MAX-ACCESS not-accessible
    STATUS obsolete
    DESCRIPTION
```

"The prefix associated with the this interface.

This object is obsoleted by IP-MIB::ipAddressPrefixPrefix."
 ::= { ipv6AddrPrefixEntry 1 }

ipv6AddrPrefixLength OBJECT-TYPE

SYNTAX INTEGER (0..128)

UNITS "bits"

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"The length of the prefix (in bits).

This object is obsoleted by IP-MIB::ipAddressPrefixLength."
 ::= { ipv6AddrPrefixEntry 2 }

ipv6AddrPrefixOnLinkFlag OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"This object has the value 'true(1)', if this prefix can be used for on-link determination and the value 'false(2)' otherwise.

This object is obsoleted by IP-MIB::ipAddressPrefixOnLinkFlag."
 ::= { ipv6AddrPrefixEntry 3 }

ipv6AddrPrefixAutonomousFlag OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"Autonomous address configuration flag. When true(1), indicates that this prefix can be used for autonomous address configuration (i.e. can be used to form a local interface address). If false(2), it is not used to autoconfigure a local interface address.

This object is obsoleted by

```
IP-MIB::ipAddressPrefixAutonomousFlag."  
 ::= { ipv6AddrPrefixEntry 4 }
```

ipv6AddrPrefixAdvPreferredLifetime OBJECT-TYPE

SYNTAX Unsigned32

UNITS "seconds"

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"It is the length of time in seconds that this prefix will remain preferred, i.e. time until deprecation. A value of 4,294,967,295 represents infinity.

The address generated from a deprecated prefix should no longer be used as a source address in new communications, but packets received on such an interface are processed as expected.

This object is obsoleted by
IP-MIB::ipAddressPrefixAdvPreferredLifetime."

```
 ::= { ipv6AddrPrefixEntry 5 }
```

ipv6AddrPrefixAdvValidLifetime OBJECT-TYPE

SYNTAX Unsigned32

UNITS "seconds"

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"It is the length of time in seconds that this prefix will remain valid, i.e. time until invalidation. A value of 4,294,967,295 represents infinity.

The address generated from an invalidated prefix should not appear as the destination or source

address of a packet.

This object is obsoleted by
IP-MIB::ipAddressPrefixAdvValidLifetime."

```
 ::= { ipv6AddrPrefixEntry 6 }
```



```

-- the IPv6 Address table

-- The IPv6 address table contains this node's IPv6
-- addressing information.

ipv6AddrTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ipv6AddrEntry
    MAX-ACCESS  not-accessible
    STATUS      obsolete
    DESCRIPTION
        "The table of addressing information relevant to
        this node's interface addresses.

        This table is obsoleted by IP-MIB::ipAddressTable."
    ::= { ipv6MIBObjects 8 }

ipv6AddrEntry OBJECT-TYPE
    SYNTAX      Ipv6AddrEntry
    MAX-ACCESS  not-accessible
    STATUS      obsolete
    DESCRIPTION
        "The addressing information for one of this
        node's interface addresses.

        This entry is obsoleted by IP-MIB::ipAddressEntry."
    INDEX      { ipv6IfIndex, ipv6AddrAddress }
    ::= { ipv6AddrTable 1 }

Ipv6AddrEntry ::=
    SEQUENCE {
        ipv6AddrAddress      Ipv6Address,
        ipv6AddrPfxLength    INTEGER,
        ipv6AddrType         INTEGER,
        ipv6AddrAnycastFlag  TruthValue,
        ipv6AddrStatus       INTEGER
    }

ipv6AddrAddress OBJECT-TYPE
    SYNTAX      Ipv6Address
    MAX-ACCESS  not-accessible
    STATUS      obsolete
    DESCRIPTION

```

"The IPv6 address to which this entry's addressing information pertains.

This object is obsoleted by IP-MIB::ipAddressAddr."
 ::= { ipv6AddrEntry 1 }

ipv6AddrPfxLength OBJECT-TYPE

SYNTAX INTEGER(0..128)

UNITS "bits"

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The length of the prefix (in bits) associated with the IPv6 address of this entry.

This object is obsoleted by the IP-MIB::ipAddressPrefixLength in the row of the IP-MIB::ipAddressPrefixTable to which the IP-MIB::ipAddressPrefix points."

::= { ipv6AddrEntry 2 }

ipv6AddrType OBJECT-TYPE

SYNTAX INTEGER {

 -- address has been formed

 -- using stateless

 stateless(1), -- autoconfiguration

 -- address has been acquired

 -- by stateful means

 -- (e.g. DHCPv6, manual

 stateful(2), -- configuration)

 -- type can not be determined

 unknown(3) -- for some reason.

}

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The type of address. Note that 'stateless(1)' refers to an address that was statelessly autoconfigured; 'stateful(2)' refers to a address which was acquired by via a stateful protocol (e.g. DHCPv6, manual configuration).

This object is obsoleted by IP-MIB::ipAddressOrigin."
 ::= { ipv6AddrEntry 3 }

ipv6AddrAnycastFlag OBJECT-TYPE

SYNTAX TruthValue

Internet-Draft

ipv6-mibs-obsolete

August 2015

```
MAX-ACCESS  read-only
STATUS      obsolete
```

DESCRIPTION

```
"This object has the value 'true(1)', if this
address is an anycast address and the value
'false(2)' otherwise.
```

```
This object is obsoleted by a value of 'anycast(2)'
in IP-MIB::ipAddressType."
```

```
::= { ipv6AddrEntry 4 }
```

```
ipv6AddrStatus OBJECT-TYPE
```

```
SYNTAX      INTEGER {
              preferred(1),
              deprecated(2),
              invalid(3),
              inaccessible(4),
              unknown(5)  -- status can not be determined
                          -- for some reason.
            }
```

```
MAX-ACCESS  read-only
STATUS      obsolete
```

DESCRIPTION

```
"Address status.  The preferred(1) state indicates
that this is a valid address that can appear as
the destination or source address of a packet.
The deprecated(2) state indicates that this is
a valid but deprecated address that should no longer
be used as a source address in new communications,
but packets addressed to such an address are
processed as expected.  The invalid(3) state indicates
that this is not valid address which should not
appear as the destination or source address of
a packet.  The inaccessible(4) state indicates that
the address is not accessible because the interface
to which this address is assigned is not operational.
```

```
This object is obsoleted by IP-MIB::ipAddressStatus."
```

```
::= { ipv6AddrEntry 5 }
```

```
-- IPv6 Routing objects
```

ipv6RouteNumber OBJECT-TYPE
SYNTAX Gauge32
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION
"The number of current ipv6RouteTable entries.

Fenner

Expires February 26, 2016

[Page 24]

Internet-Draft

ipv6-mibs-obsolete

August 2015

This is primarily to avoid having to read
the table in order to determine this number.

This object is obsoleted by IP-FORWARD-MIB::inetCidrRouteNumber."
::= { ipv6MIBObjects 9 }

ipv6DiscardedRoutes OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION
"The number of routing entries which were chosen
to be discarded even though they are valid. One
possible reason for discarding such an entry could
be to free-up buffer space for other routing
entries.

This object is obsoleted by
IP-FORWARD-MIB::inetCidrRouteDiscards."
::= { ipv6MIBObjects 10 }

-- IPv6 Routing table

ipv6RouteTable OBJECT-TYPE
SYNTAX SEQUENCE OF Ipv6RouteEntry
MAX-ACCESS not-accessible
STATUS obsolete
DESCRIPTION
"IPv6 Routing table. This table contains
an entry for each valid IPv6 unicast route
that can be used for packet forwarding
determination.

This table is obsoleted by IP-FORWARD-MIB::inetCidrRouteTable."
::= { ipv6MIBObjects 11 }

```

ipv6RouteEntry OBJECT-TYPE
    SYNTAX      Ipv6RouteEntry
    MAX-ACCESS  not-accessible
    STATUS      obsolete
    DESCRIPTION
        "A routing entry.

        This entry is obsoleted by
        IP-FORWARD-MIB::inetCidrRouteEntry."
    INDEX       { ipv6RouteDest,
                  ipv6RoutePfxLength,
                  ipv6RouteIndex }

```

```
 ::= { ipv6RouteTable 1 }
```

```

Ipv6RouteEntry ::= SEQUENCE {
    ipv6RouteDest          Ipv6Address,
    ipv6RoutePfxLength     INTEGER,
    ipv6RouteIndex        Unsigned32,
    ipv6RouteIfIndex      Ipv6IfIndexOrZero,
    ipv6RouteNextHop      Ipv6Address,
    ipv6RouteType         INTEGER,
    ipv6RouteProtocol     INTEGER,
    ipv6RoutePolicy       Integer32,
    ipv6RouteAge          Unsigned32,
    ipv6RouteNextHopRDI   Unsigned32,
    ipv6RouteMetric       Unsigned32,
    ipv6RouteWeight       Unsigned32,
    ipv6RouteInfo         RowPointer,
    ipv6RouteValid        TruthValue
}

```

```

ipv6RouteDest OBJECT-TYPE
    SYNTAX      Ipv6Address
    MAX-ACCESS  not-accessible
    STATUS      obsolete
    DESCRIPTION
        "The destination IPv6 address of this route.
        This object may not take a Multicast address
        value."

```

This object is obsoleted by IP-FORWARD-MIB::inetCidrRouteDest."
 ::= { ipv6RouteEntry 1 }

ipv6RoutePfxLength OBJECT-TYPE

SYNTAX INTEGER(0..128)

UNITS "bits"

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"Indicates the prefix length of the destination address.

This object is obsoleted by IP-FORWARD-MIB::inetCidrRoutePfxLen."
 ::= { ipv6RouteEntry 2 }

ipv6RouteIndex OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

Fenner

Expires February 26, 2016

[Page 26]

Internet-Draft

ipv6-mibs-obsolete

August 2015

"The value which uniquely identifies the route among the routes to the same network layer destination. The way this value is chosen is implementation specific but it must be unique for ipv6RouteDest/ipv6RoutePfxLength pair and remain constant for the life of the route.

This object is obsoleted by IP-FORWARD-MIB::inetCidrRoutePolicy."
 ::= { ipv6RouteEntry 3 }

ipv6RouteIfIndex OBJECT-TYPE

SYNTAX Ipv6IfIndexOrZero

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The index value which uniquely identifies the local interface through which the next hop of this route should be reached. The interface identified by a particular value of this index is the same interface as identified by the same value of ipv6IfIndex. For routes of the discard type this

value can be zero.

This object is obsoleted by
IP-FORWARD-MIB::inetCidrRouteIfIndex."
 ::= { ipv6RouteEntry 4 }

ipv6RouteNextHop OBJECT-TYPE

SYNTAX Ipv6Address

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"On remote routes, the address of the next system en route; otherwise, ::0 ('00000000000000000000000000000000'H in ASN.1 string representation).

This object is obsoleted by
IP-FORWARD-MIB::inetCidrRouteNextHop."
 ::= { ipv6RouteEntry 5 }

ipv6RouteType OBJECT-TYPE

SYNTAX INTEGER {

other(1), -- none of the following

-- an route indicating that
-- packets to destinations
-- matching this route are

Fenner

Expires February 26, 2016

[Page 27]

Internet-Draft

ipv6-mibs-obsolete

August 2015

discard(2), -- to be discarded

local(3), -- route to directly
-- connected (sub-)network

-- route to a remote

remote(4) -- destination

}

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The type of route. Note that 'local(3)' refers

to a route for which the next hop is the final destination; 'remote(4)' refers to a route for which the next hop is not the final destination; 'discard(2)' refers to a route indicating that packets to destinations matching this route are to be discarded (sometimes called black-hole route).

This object is obsoleted by IP-FORWARD-MIB::inetCidrRouteType."
 ::= { ipv6RouteEntry 6 }

ipv6RouteProtocol OBJECT-TYPE

```
SYNTAX      INTEGER {
    other(1),      -- none of the following
                  -- non-protocol information,
                  -- e.g., manually configured
    local(2),     -- entries
    netmgmt(3),   -- static route
                  -- obtained via Neighbor
                  -- Discovery protocol,
    ndisc(4),     -- e.g., result of Redirect
                  -- the following are all
                  -- dynamic routing protocols
    rip(5),       -- RIPng
    ospf(6),      -- Open Shortest Path First
    bgp(7),       -- Border Gateway Protocol
    idrp(8),      -- InterDomain Routing Protocol
    igrp(9)       -- InterGateway Routing Protocol
}
MAX-ACCESS read-only
```

STATUS obsolete

DESCRIPTION

"The routing mechanism via which this route was learned.

This object is obsoleted by IP-FORWARD-MIB::inetCidrRouteProto."
 ::= { ipv6RouteEntry 7 }

ipv6RoutePolicy OBJECT-TYPE

SYNTAX Integer32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The general set of conditions that would cause the selection of one multipath route (set of next hops for a given destination) is referred to as 'policy'. Unless the mechanism indicated by ipv6RouteProtocol specified otherwise, the policy specifier is the 8-bit Traffic Class field of the IPv6 packet header that is zero extended at the left to a 32-bit value.

Protocols defining 'policy' otherwise must either define a set of values which are valid for this object or must implement an integer-instanced policy table for which this object's value acts as an index.

This object is obsoleted by IP-FORWARD-MIB::inetCidrRoutePolicy."
 ::= { ipv6RouteEntry 8 }

ipv6RouteAge OBJECT-TYPE

SYNTAX Unsigned32

UNITS "seconds"

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of seconds since this route was last updated or otherwise determined to be correct. Note that no semantics of 'too old' can be implied except through knowledge of the routing protocol by which the route was learned.

This object is obsoleted by IP-FORWARD-MIB::inetCidrRouteAge."
 ::= { ipv6RouteEntry 9 }

ipv6RouteNextHopRDI OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The Routing Domain ID of the Next Hop.
The semantics of this object are determined by the routing-protocol specified in the route's ipv6RouteProtocol value. When this object is unknown or not relevant its value should be set to zero.

This object is obsolete, and has no replacement.
The Routing Domain ID concept did not catch on."

::= { ipv6RouteEntry 10 }

ipv6RouteMetric OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The routing metric for this route. The semantics of this metric are determined by the routing protocol specified in the route's ipv6RouteProtocol value. When this is unknown or not relevant to the protocol indicated by ipv6RouteProtocol, the object value should be set to its maximum value (4,294,967,295).

This object is obsoleted by
IP-FORWARD-MIB::inetCidrRouteMetric1."

::= { ipv6RouteEntry 11 }

ipv6RouteWeight OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The system internal weight value for this route. The semantics of this value are determined by the implementation specific rules. Generally, within routes with the same ipv6RoutePolicy value, the lower the weight value the more preferred is the route.

This object is obsoleted, and has not been replaced."

::= { ipv6RouteEntry 12 }

ipv6RouteInfo OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-only

Internet-Draft

ipv6-mibs-obsolete

August 2015

STATUS obsolete

DESCRIPTION

"A reference to MIB definitions specific to the particular routing protocol which is responsible for this route, as determined by the value specified in the route's ipv6RouteProto value. If this information is not present, its value should be set to the OBJECT ID { 0 0 }, which is a syntactically valid object identifier, and any implementation conforming to ASN.1 and the Basic Encoding Rules must be able to generate and recognize this value.

This object is obsoleted, and has not been replaced."
 ::= { ipv6RouteEntry 13 }

ipv6RouteValid OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS obsolete

DESCRIPTION

"Setting this object to the value 'false(2)' has the effect of invalidating the corresponding entry in the ipv6RouteTable object. That is, it effectively disassociates the destination identified with said entry from the route identified with said entry. It is an implementation-specific matter as to whether the agent removes an invalidated entry from the table. Accordingly, management stations must be prepared to receive tabular information from agents that corresponds to entries not currently in use. Proper interpretation of such entries requires examination of the relevant ipv6RouteValid object.

This object is obsoleted by
IP-FORWARD-MIB::inetCidrRouteStatus."

DEFVAL { true }

::= { ipv6RouteEntry 14 }

-- IPv6 Address Translation table

ipv6NetToMediaTable OBJECT-TYPE
SYNTAX SEQUENCE OF Ipv6NetToMediaEntry
MAX-ACCESS not-accessible
STATUS obsolete
DESCRIPTION

Fenner

Expires February 26, 2016

[Page 31]

Internet-Draft

ipv6-mibs-obsolete

August 2015

"The IPv6 Address Translation table used for mapping from IPv6 addresses to physical addresses.

The IPv6 address translation table contain the Ipv6Address to 'physical' address equivalencies. Some interfaces do not use translation tables for determining address equivalencies; if all interfaces are of this type, then the Address Translation table is empty, i.e., has zero entries.

This table is obsoleted by IP-MIB::ipNetToPhysicalTable."
 ::= { ipv6MIBObjects 12 }

ipv6NetToMediaEntry OBJECT-TYPE
SYNTAX Ipv6NetToMediaEntry
MAX-ACCESS not-accessible
STATUS obsolete
DESCRIPTION

"Each entry contains one IPv6 address to 'physical' address equivalence.

This entry is obsoleted by IP-MIB::ipNetToPhysicalEntry."
INDEX { ipv6IfIndex,
 ipv6NetToMediaNetAddress }
 ::= { ipv6NetToMediaTable 1 }

Ipv6NetToMediaEntry ::= SEQUENCE {
 ipv6NetToMediaNetAddress
 Ipv6Address,
 ipv6NetToMediaPhysAddress
 PhysAddress,
 ipv6NetToMediaType
 INTEGER,
 ipv6IfNetToMediaState
 INTEGER,

```
    ipv6IfNetToMediaLastUpdated
        TimeStamp,
    ipv6NetToMediaValid
        TruthValue
}
```

```
ipv6NetToMediaNetAddress OBJECT-TYPE
    SYNTAX      Ipv6Address
    MAX-ACCESS  not-accessible
    STATUS      obsolete
    DESCRIPTION
        "The IPv6 Address corresponding to
```

Fenner

Expires February 26, 2016

[Page 32]

Internet-Draft

ipv6-mibs-obsolete

August 2015

the media-dependent `physical' address.

This object is obsoleted by IP-MIB::ipNetToPhysicalNetAddress."
 ::= { ipv6NetToMediaEntry 1 }

```
ipv6NetToMediaPhysAddress OBJECT-TYPE
    SYNTAX      PhysAddress
    MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The media-dependent `physical' address.
```

This object is obsoleted by IP-MIB::ipNetToPhysicalPhysAddress."
 ::= { ipv6NetToMediaEntry 2 }

```
ipv6NetToMediaType OBJECT-TYPE
    SYNTAX      INTEGER {
        other(1),      -- none of the following
        dynamic(2),   -- dynamically resolved
        static(3),    -- statically configured
        local(4)      -- local interface
    }
    MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The type of the mapping. The 'dynamic(2)' type
        indicates that the IPv6 address to physical
        addresses mapping has been dynamically
        resolved using the IPv6 Neighbor Discovery
```

protocol. The static(3)' types indicates that the mapping has been statically configured. The local(4) indicates that the mapping is provided for an entity's own interface address.

This object is obsoleted by IP-MIB::ipNetToPhysicalType."
 ::= { ipv6NetToMediaEntry 3 }

ipv6IfNetToMediaState OBJECT-TYPE

```
SYNTAX      INTEGER {
    reachable(1), -- confirmed reachability

    stale(2),    -- unconfirmed reachability

    delay(3),    -- waiting for reachability
                 -- confirmation before entering
                 -- the probe state

    probe(4),    -- actively probing
```

Fenner

Expires February 26, 2016

[Page 33]

Internet-Draft

ipv6-mibs-obsolete

August 2015

```
    invalid(5), -- an invalidated mapping

    unknown(6)  -- state can not be determined
                 -- for some reason.
```

```
}
```

```
MAX-ACCESS  read-only
```

```
STATUS      obsolete
```

```
DESCRIPTION
```

```
"The Neighbor Unreachability Detection [8] state
for the interface when the address mapping in
this entry is used.
```

This object is obsoleted by IP-MIB::ipNetToPhysicalState."
 ::= { ipv6NetToMediaEntry 4 }

ipv6IfNetToMediaLastUpdated OBJECT-TYPE

```
SYNTAX      TimeStamp
```

```
MAX-ACCESS  read-only
```

```
STATUS      obsolete
```

```
DESCRIPTION
```

```
"The value of sysUpTime at the time this entry
was last updated. If this entry was updated prior
```

to the last re-initialization of the local network management subsystem, then this object contains a zero value.

This object is obsoleted by IP-MIB::ipNetToPhysicalLastUpdated."
 ::= { ipv6NetToMediaEntry 5 }

ipv6NetToMediaValid OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS obsolete

DESCRIPTION

"Setting this object to the value 'false(2)' has the effect of invalidating the corresponding entry in the ipv6NetToMediaTable. That is, it effectively disassociates the interface identified with said entry from the mapping identified with said entry. It is an implementation-specific matter as to whether the agent removes an invalidated entry from the table. Accordingly, management stations must be prepared to receive tabular information from agents that corresponds to entries not currently in use. Proper interpretation of such entries requires examination of the relevant ipv6NetToMediaValid object.

Fenner

Expires February 26, 2016

[Page 34]

Internet-Draft

ipv6-mibs-obsolete

August 2015

This object is obsoleted by IP-MIB::ipNetToPhysicalRowStatus."

DEFVAL { true }

::= { ipv6NetToMediaEntry 6 }

-- definition of IPv6-related notifications.
-- Note that we need ipv6NotificationPrefix with the 0
-- sub-identifier to make this MIB to translate to
-- an SNMPv1 format in a reversible way. For example
-- it is needed for proxies that convert SNMPv1 traps
-- to SNMPv2 notifications without MIB knowledge.

ipv6Notifications OBJECT IDENTIFIER

::= { ipv6MIB 2 }

ipv6NotificationPrefix OBJECT IDENTIFIER

::= { ipv6Notifications 0 }

```

ipv6IfStateChange NOTIFICATION-TYPE
    OBJECTS {
        ipv6IfDescr,
        ipv6IfOperStatus -- the new state of the If.
    }
    STATUS          obsolete
    DESCRIPTION
        "An ipv6IfStateChange notification signifies
        that there has been a change in the state of
        an ipv6 interface. This notification should
        be generated when the interface's operational
        status transitions to or from the up(1) state.

        This object is obsoleted by IF-MIB::linkUp
        and IF-MIB::linkDown notifications."
        ::= { ipv6NotificationPrefix 1 }

-- conformance information

ipv6Conformance OBJECT IDENTIFIER ::= { ipv6MIB 3 }

ipv6Compliances OBJECT IDENTIFIER ::= { ipv6Conformance 1 }
ipv6Groups      OBJECT IDENTIFIER ::= { ipv6Conformance 2 }

-- compliance statements

ipv6Compliance MODULE-COMPLIANCE
    STATUS obsolete
    DESCRIPTION
        "The compliance statement for SNMPv2 entities which
        implement ipv6 MIB.

```

```

        This compliance statement is obsoleted by
        IP-MIB::ipMIBCompliance2."
MODULE -- this module
    MANDATORY-GROUPS { ipv6GeneralGroup,
                        ipv6NotificationGroup }
    OBJECT      ipv6Forwarding
        MIN-ACCESS read-only
        DESCRIPTION

```



```

        "An agent is not required to provide write
          access to this object"
OBJECT    ipv6DefaultHopLimit
MIN-ACCESS read-only
DESCRIPTION
        "An agent is not required to provide write
          access to this object"
OBJECT    ipv6IfDescr
MIN-ACCESS read-only
DESCRIPTION
        "An agent is not required to provide write
          access to this object"
OBJECT    ipv6IfIdentifier
MIN-ACCESS read-only
DESCRIPTION
        "An agent is not required to provide write
          access to this object"
OBJECT    ipv6IfIdentifierLength
MIN-ACCESS read-only
DESCRIPTION
        "An agent is not required to provide write
          access to this object"

OBJECT    ipv6IfAdminStatus
MIN-ACCESS read-only
DESCRIPTION
        "An agent is not required to provide write
          access to this object"
OBJECT    ipv6RouteValid
MIN-ACCESS read-only
DESCRIPTION
        "An agent is not required to provide write
          access to this object"
OBJECT    ipv6NetToMediaValid
MIN-ACCESS read-only
DESCRIPTION
        "An agent is not required to provide write
          access to this object"
 ::= { ipv6Compliances 1 }

```

```
OBJECTS { ipv6Forwarding,  
          ipv6DefaultHopLimit,  
          ipv6Interfaces,  
          ipv6IfTableLastChange,  
          ipv6IfDescr,  
          ipv6IfLowerLayer,  
          ipv6IfEffectiveMtu,  
          ipv6IfReasmMaxSize,  
          ipv6IfIdentifier,  
          ipv6IfIdentifierLength,  
          ipv6IfPhysicalAddress,  
          ipv6IfAdminStatus,  
          ipv6IfOperStatus,  
          ipv6IfLastChange,  
          ipv6IfStatsInReceives,  
          ipv6IfStatsInHdrErrors,  
          ipv6IfStatsInTooBigErrors,  
          ipv6IfStatsInNoRoutes,  
          ipv6IfStatsInAddrErrors,  
          ipv6IfStatsInUnknownProtos,  
          ipv6IfStatsInTruncatedPkts,  
          ipv6IfStatsInDiscards,  
          ipv6IfStatsInDelivers,  
          ipv6IfStatsOutForwDatagrams,  
          ipv6IfStatsOutRequests,  
          ipv6IfStatsOutDiscards,  
          ipv6IfStatsOutFragOKs,  
          ipv6IfStatsOutFragFails,  
          ipv6IfStatsOutFragCreates,  
          ipv6IfStatsReasmReqs,  
          ipv6IfStatsReasmOKs,  
          ipv6IfStatsReasmFails,  
          ipv6IfStatsInMcastPkts,  
          ipv6IfStatsOutMcastPkts,  
          ipv6AddrPrefixOnLinkFlag,  
          ipv6AddrPrefixAutonomousFlag,  
          ipv6AddrPrefixAdvPreferredLifetime,  
          ipv6AddrPrefixAdvValidLifetime,  
          ipv6AddrPfxLength,  
          ipv6AddrType,  
          ipv6AddrAnycastFlag,  
          ipv6AddrStatus,  
          ipv6RouteNumber,  
          ipv6DiscardedRoutes,  
          ipv6RouteIfIndex,  
          ipv6RouteNextHop,  
          ipv6RouteType,
```

```
        ipv6RouteProtocol,
        ipv6RoutePolicy,
        ipv6RouteAge,
        ipv6RouteNextHopRDI,
        ipv6RouteMetric,
        ipv6RouteWeight,
        ipv6RouteInfo,
        ipv6RouteValid,
        ipv6NetToMediaPhysAddress,
        ipv6NetToMediaType,
        ipv6IfNetToMediaState,
        ipv6IfNetToMediaLastUpdated,
        ipv6NetToMediaValid }
STATUS      obsolete
DESCRIPTION
    "The IPv6 group of objects providing for basic
    management of IPv6 entities.

    This group is obsoleted by various groups in
    IP-MIB."
 ::= { ipv6Groups 1 }

ipv6NotificationGroup NOTIFICATION-GROUP
NOTIFICATIONS { ipv6IfStateChange }
STATUS      obsolete
DESCRIPTION
    "The notification that an IPv6 entity is required
    to implement.

    This group is obsoleted by
    IF-MIB::linkUpDownNotificationsGroup."
 ::= { ipv6Groups 2 }

END
```

[4.](#) Historic IPV6-ICMP-MIB

```
IPV6-ICMP-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE,
    Counter32, mib-2          FROM SNMPv2-SMI
    MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF
    ipv6IfEntry              FROM IPV6-MIB;
```

```
ipv6IcmpMIB MODULE-IDENTITY
```

LAST-UPDATED "201505282112Z"
ORGANIZATION "IETF IPv6 Working Group"

Fenner

Expires February 26, 2016

[Page 38]

Internet-Draft

ipv6-mibs-obsolete

August 2015

CONTACT-INFO

" Dimitry Haskin

Postal: Bay Networks, Inc.
660 Technology Park Drive.
Billerica, MA 01821
US

Tel: +1-978-916-8124
E-mail: dhaskin@baynetworks.com

Steve Onishi

Postal: Bay Networks, Inc.
3 Federal Street
Billerica, MA 01821
US

Tel: +1-978-916-3816
E-mail: sonishi@baynetworks.com"

DESCRIPTION

"The obsolete MIB module for entities implementing
the ICMPv6. Use the IP-MIB instead."

REVISION "201505282112Z"

DESCRIPTION

"Obsoleting this MIB module; it has been replaced by
the revised IP-MIB ([RFC4293](#))."

REVISION "9801082155Z"

DESCRIPTION

"First revision, published as [RFC2466](#)"
 ::= { mib-2 56 }

-- the ICMPv6 group

ipv6IcmpMIBObjects OBJECT IDENTIFIER ::= { ipv6IcmpMIB 1 }

-- Per-interface ICMPv6 statistics table

ipv6IfIcmpTable OBJECT-TYPE

SYNTAX SEQUENCE OF Ipv6IfIcmpEntry

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"IPv6 ICMP statistics. This table contains statistics of ICMPv6 messages that are received and sourced by the entity.

This table is obsolete, because systems were found

Fenner

Expires February 26, 2016

[Page 39]

Internet-Draft

ipv6-mibs-obsolete

August 2015

not to maintain these statistics per-interface."
::= { ipv6IcmpMIBObjects 1 }

ipv6IfIcmpEntry OBJECT-TYPE

SYNTAX Ipv6IfIcmpEntry

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"An ICMPv6 statistics entry containing objects at a particular IPv6 interface.

Note that a receiving interface is the interface to which a given ICMPv6 message is addressed which may not be necessarily the input interface for the message.

Similarly, the sending interface is the interface that sources a given ICMP message which is usually but not necessarily the output interface for the message.

This table is obsolete, because systems were found not to maintain these statistics per-interface."

AUGMENTS { ipv6IfEntry }

::= { ipv6IfIcmpTable 1 }

Ipv6IfIcmpEntry ::= SEQUENCE {

 ipv6IfIcmpInMsgs

 Counter32 ,

 ipv6IfIcmpInErrors

 Counter32 ,

 ipv6IfIcmpInDestUnreachs

Counter32 ,
ipv6IfIcmpInAdminProhibs
Counter32 ,
ipv6IfIcmpInTimeExcds
Counter32 ,
ipv6IfIcmpInParmProblems
Counter32 ,
ipv6IfIcmpInPktTooBig
Counter32 ,
ipv6IfIcmpInEchos
Counter32 ,
ipv6IfIcmpInEchoReplies
Counter32 ,
ipv6IfIcmpInRouterSolicits
Counter32 ,
ipv6IfIcmpInRouterAdvertisements

Counter32 ,
ipv6IfIcmpInNeighborSolicits
Counter32 ,
ipv6IfIcmpInNeighborAdvertisements
Counter32 ,
ipv6IfIcmpInRedirects
Counter32 ,
ipv6IfIcmpInGroupMembQueries
Counter32 ,
ipv6IfIcmpInGroupMembResponses
Counter32 ,
ipv6IfIcmpInGroupMembReductions
Counter32 ,
ipv6IfIcmpOutMsgs
Counter32 ,
ipv6IfIcmpOutErrors
Counter32 ,
ipv6IfIcmpOutDestUnreaches
Counter32 ,
ipv6IfIcmpOutAdminProhibs
Counter32 ,
ipv6IfIcmpOutTimeExcds
Counter32 ,
ipv6IfIcmpOutParmProblems
Counter32 ,

```

    ipv6IfIcmpOutPktTooBigs
        Counter32      ,
    ipv6IfIcmpOutEchos
        Counter32      ,
    ipv6IfIcmpOutEchoReplies
        Counter32      ,
    ipv6IfIcmpOutRouterSolicits
        Counter32      ,
    ipv6IfIcmpOutRouterAdvertisements
        Counter32      ,
    ipv6IfIcmpOutNeighborSolicits
        Counter32      ,
    ipv6IfIcmpOutNeighborAdvertisements
        Counter32      ,
    ipv6IfIcmpOutRedirects
        Counter32      ,
    ipv6IfIcmpOutGroupMembQueries
        Counter32      ,
    ipv6IfIcmpOutGroupMembResponses
        Counter32      ,
    ipv6IfIcmpOutGroupMembReductions
        Counter32
}

```

ipv6IfIcmpInMsgs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The total number of ICMP messages received by the interface which includes all those counted by ipv6IfIcmpInErrors. Note that this interface is the interface to which the ICMP messages were addressed which may not be necessarily the input interface for the messages.

This object has been obsoleted by IP-MIB::icmpStatsInMsgs."
 ::= { ipv6IfIcmpEntry 1 }

ipv6IfIcmpInErrors OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP messages which the interface received but determined as having ICMP-specific errors (bad ICMP checksums, bad length, etc.).

This object has been obsoleted by IP-MIB::icmpStatsInErrors."
::= { ipv6IfIcmpEntry 2 }

ipv6IfIcmpInDestUnreachs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Destination Unreachable messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
::= { ipv6IfIcmpEntry 3 }

ipv6IfIcmpInAdminProhibs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP destination unreachable/communication administratively prohibited messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
::= { ipv6IfIcmpEntry 4 }

ipv6IfIcmpInTimeExcds OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Time Exceeded messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 5 }

ipv6IfIcmpInParmProblems OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Parameter Problem messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 6 }

ipv6IfIcmpInPktTooBig OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Packet Too Big messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 7 }

ipv6IfIcmpInEchos OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Echo (request) messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 8 }

ipv6IfIcmpInEchoReplies OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Echo Reply messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."

::= { ipv6IfIcmpEntry 9 }

ipv6IfIcmpInRouterSolicits OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Router Solicit messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."

::= { ipv6IfIcmpEntry 10 }

ipv6IfIcmpInRouterAdvertisements OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Router Advertisement messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."

::= { ipv6IfIcmpEntry 11 }

ipv6IfIcmpInNeighborSolicits OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Neighbor Solicit messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 12 }

ipv6IfIcmpInNeighborAdvertisements OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Neighbor Advertisement messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 13 }

ipv6IfIcmpInRedirects OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of Redirect messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 14 }

ipv6IfIcmpInGroupMembQueries OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMPv6 Group Membership Query messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 15 }

ipv6IfIcmpInGroupMembResponses OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMPv6 Group Membership Response messages received by the interface.

Internet-Draft

ipv6-mibs-obsolete

August 2015

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 16}

ipv6IfIcmpInGroupMembReductions OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMPv6 Group Membership Reduction messages received by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsInPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 17}

ipv6IfIcmpOutMsgs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The total number of ICMP messages which this interface attempted to send. Note that this counter includes all those counted by icmpOutErrors.

This object has been obsoleted by IP-MIB::icmpStatsOutMsgs."
 ::= { ipv6IfIcmpEntry 18 }

ipv6IfIcmpOutErrors OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP messages which this interface did not send due to problems discovered within ICMP such as a lack of buffers. This value should not include errors discovered outside the ICMP layer such as the inability of IPv6 to route the resultant datagram. In some implementations there may be no types of error which contribute to this counter's

value.

This object has been obsoleted by IP-MIB::icmpStatsOutErrors."
::= { ipv6IfIcmpEntry 19 }

ipv6IfIcmpOutDestUnreachs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

Fenner

Expires February 26, 2016

[Page 46]

Internet-Draft

ipv6-mibs-obsolete

August 2015

STATUS obsolete

DESCRIPTION

"The number of ICMP Destination Unreachable
messages sent by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts
in the row corresponding to this message type."
::= { ipv6IfIcmpEntry 20 }

ipv6IfIcmpOutAdminProhibs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"Number of ICMP dest unreachable/communication
administratively prohibited messages sent.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts
in the row corresponding to this message type."
::= { ipv6IfIcmpEntry 21 }

ipv6IfIcmpOutTimeExcds OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Time Exceeded messages sent
by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts
in the row corresponding to this message type."
::= { ipv6IfIcmpEntry 22 }

ipv6IfIcmpOutParmProblems OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Parameter Problem messages sent by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."

::= { ipv6IfIcmpEntry 23 }

ipv6IfIcmpOutPktTooBig OBJECT-TYPE

SYNTAX Counter32

Fenner

Expires February 26, 2016

[Page 47]

Internet-Draft

ipv6-mibs-obsolete

August 2015

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Packet Too Big messages sent by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."

::= { ipv6IfIcmpEntry 24 }

ipv6IfIcmpOutEchos OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Echo (request) messages sent by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."

::= { ipv6IfIcmpEntry 25 }

ipv6IfIcmpOutEchoReplies OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Echo Reply messages sent by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 26 }

ipv6IfIcmpOutRouterSolicits OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Router Solicitation messages sent by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 27 }

ipv6IfIcmpOutRouterAdvertisements OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Router Advertisement messages sent by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 28 }

ipv6IfIcmpOutNeighborSolicits OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Neighbor Solicitation messages sent by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts

in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 29 }

ipv6IfIcmpOutNeighborAdvertisements OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMP Neighbor Advertisement messages sent by the interface.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 30 }

ipv6IfIcmpOutRedirects OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of Redirect messages sent. For a host, this object will always be zero, since hosts do not send redirects.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 31 }

ipv6IfIcmpOutGroupMembQueries OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS obsolete

DESCRIPTION

"The number of ICMPv6 Group Membership Query messages sent.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."
 ::= { ipv6IfIcmpEntry 32}

ipv6IfIcmpOutGroupMembResponses OBJECT-TYPE

SYNTAX Counter32
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION
"The number of ICMPv6 Group Membership Response messages sent.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."
::= { ipv6IfIcmpEntry 33}

ipv6IfIcmpOutGroupMembReductions OBJECT-TYPE

SYNTAX Counter32
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION
"The number of ICMPv6 Group Membership Reduction messages sent.

This object has been obsoleted by IP-MIB::icmpMsgStatsOutPkts in the row corresponding to this message type."
::= { ipv6IfIcmpEntry 34}

-- conformance information

ipv6IcmpConformance OBJECT IDENTIFIER ::= { ipv6IcmpMIB 2 }

ipv6IcmpCompliances

OBJECT IDENTIFIER ::= { ipv6IcmpConformance 1 }

ipv6IcmpGroups

OBJECT IDENTIFIER ::= { ipv6IcmpConformance 2 }

-- compliance statements

ipv6IcmpCompliance MODULE-COMPLIANCE

STATUS obsolete

DESCRIPTION

"The compliance statement for SNMPv2 entities which implement ICMPv6.

This compliance statement has been obsoleted by

```

    IP-MIB::ipMIBCompliance2."
MODULE -- this module
    MANDATORY-GROUPS { ipv6IcmpGroup }
 ::= { ipv6IcmpCompliances 1 }

ipv6IcmpGroup OBJECT-GROUP
    OBJECTS {
        ipv6IfIcmpInMsgs,
        ipv6IfIcmpInErrors,
        ipv6IfIcmpInDestUnreachs,
        ipv6IfIcmpInAdminProhibs,
        ipv6IfIcmpInTimeExcds,
        ipv6IfIcmpInParmProblems,
        ipv6IfIcmpInPktTooBig,
        ipv6IfIcmpInEchos,
        ipv6IfIcmpInEchoReplies,
        ipv6IfIcmpInRouterSolicits,
        ipv6IfIcmpInRouterAdvertisements,
        ipv6IfIcmpInNeighborSolicits,
        ipv6IfIcmpInNeighborAdvertisements,
        ipv6IfIcmpInRedirects,
        ipv6IfIcmpInGroupMembQueries,
        ipv6IfIcmpInGroupMembResponses,
        ipv6IfIcmpInGroupMembReductions,
        ipv6IfIcmpOutMsgs,
        ipv6IfIcmpOutErrors,
        ipv6IfIcmpOutDestUnreachs,
        ipv6IfIcmpOutAdminProhibs,
        ipv6IfIcmpOutTimeExcds,
        ipv6IfIcmpOutParmProblems,
        ipv6IfIcmpOutPktTooBig,
        ipv6IfIcmpOutEchos,
        ipv6IfIcmpOutEchoReplies,
        ipv6IfIcmpOutRouterSolicits,
        ipv6IfIcmpOutRouterAdvertisements,
        ipv6IfIcmpOutNeighborSolicits,
        ipv6IfIcmpOutNeighborAdvertisements,
        ipv6IfIcmpOutRedirects,
        ipv6IfIcmpOutGroupMembQueries,
        ipv6IfIcmpOutGroupMembResponses,
        ipv6IfIcmpOutGroupMembReductions
    }
    STATUS      obsolete

```

DESCRIPTION

"The ICMPv6 group of objects providing information specific to ICMPv6.

This group has been obsoleted by IP-MIB::icmpStatsGroup."
 ::= { ipv6IcmpGroups 1 }

END

5. Historic IPV6-UDP-MIB

IPV6-UDP-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF
MODULE-IDENTITY, OBJECT-TYPE,
mib-2, experimental FROM SNMPv2-SMI
Ipv6Address, Ipv6IfIndexOrZero FROM IPV6-TC;

ipv6UdpMIB MODULE-IDENTITY

LAST-UPDATED "201505282112Z"

ORGANIZATION "IETF IPv6 MIB Working Group"

CONTACT-INFO

" Mike Daniele

Postal: Compaq Computer Corporation
110 Spitbrook Rd
Nashua, NH 03062.
US

Phone: +1 603 884 1423

Email: daniele@zk3.dec.com"

DESCRIPTION

"The obsolete MIB module for entities implementing UDP over IPv6. Use the UDP-MIB instead."

REVISION "201505282112Z"

DESCRIPTION

"Obsoleting this MIB module; it has been replaced by the revised UDP-MIB ([RFC4113](#))."

REVISION "9801290000Z"

DESCRIPTION

"First revision, published as [RFC2454](#)"

::= { experimental 87 }

-- objects specific to UDP for IPv6

udp OBJECT IDENTIFIER ::= { mib-2 7 }

Internet-Draft

ipv6-mibs-obsolete

August 2015

```
-- the UDP over IPv6 Listener table
```

```
-- This table contains information about this entity's
-- UDP/IPv6 endpoints. Only endpoints utilizing IPv6 addresses
-- are contained in this table. This entity's UDP/IPv4 endpoints
-- are contained in udpTable.
```

```
ipv6UdpTable OBJECT-TYPE
```

```
SYNTAX SEQUENCE OF Ipv6UdpEntry
```

```
MAX-ACCESS not-accessible
```

```
STATUS obsolete
```

```
DESCRIPTION
```

```
"A table containing UDP listener information for
UDP/IPv6 endpoints.
```

```
This table is obsoleted by UDP-MIB::udpEndpointTable."
```

```
::= { udp 6 }
```

```
ipv6UdpEntry OBJECT-TYPE
```

```
SYNTAX Ipv6UdpEntry
```

```
MAX-ACCESS not-accessible
```

```
STATUS obsolete
```

```
DESCRIPTION
```

```
"Information about a particular current UDP listener.
```

```
Note that conceptual rows in this table require an
additional index object compared to udpTable, since
IPv6 addresses are not guaranteed to be unique on the
managed node.
```

```
This entry is obsoleted by UDP-MIB::udpEndpointTable."
```

```
INDEX { ipv6UdpLocalAddress,
        ipv6UdpLocalPort,
        ipv6UdpIfIndex }
```

```
::= { ipv6UdpTable 1 }
```

```
Ipv6UdpEntry ::= SEQUENCE {
```

```
    ipv6UdpLocalAddress Ipv6Address,
```

```
    ipv6UdpLocalPort INTEGER (0..65535),
```

```
    ipv6UdpIfIndex Ipv6IfIndexOrZero }
```

```
ipv6UdpLocalAddress OBJECT-TYPE
```

SYNTAX Ipv6Address
MAX-ACCESS not-accessible
STATUS obsolete
DESCRIPTION

"The local IPv6 address for this UDP listener.
In the case of a UDP listener which is willing

to accept datagrams for any IPv6 address
associated with the managed node, the value ::0
is used.

This object is obsoleted by UDP-MIB::udpEndpointLocalAddress."
::= { ipv6UdpEntry 1 }

ipv6UdpLocalPort OBJECT-TYPE

SYNTAX INTEGER (0..65535)
MAX-ACCESS not-accessible
STATUS obsolete
DESCRIPTION

"The local port number for this UDP listener.

This object is obsoleted by UDP-MIB::udpEndpointLocalPort."
::= { ipv6UdpEntry 2 }

ipv6UdpIfIndex OBJECT-TYPE

SYNTAX Ipv6IfIndexOrZero
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION

"An index object used to disambiguate conceptual rows in
the table, since the ipv6UdpLocalAddress/ipv6UdpLocalPort
pair may not be unique.

This object identifies the local interface that is
associated with ipv6UdpLocalAddress for this UDP listener.
If such a local interface cannot be determined, this object
should take on the value 0. (A possible example of this
would be if the value of ipv6UdpLocalAddress is ::0.)

The interface identified by a particular non-0 value of
this index is the same interface as identified by the same
value of ipv6IfIndex.

The value of this object must remain constant during the life of this UDP endpoint.

This object is obsoleted by the zone identifier in an InetAddressIPv6z address in UDP-MIB::udpEndpointLocalAddress."

::= { ipv6UdpEntry 3 }

--
-- conformance information
--

Fenner

Expires February 26, 2016

[Page 54]

Internet-Draft

ipv6-mibs-obsolete

August 2015

ipv6UdpConformance OBJECT IDENTIFIER ::= { ipv6UdpMIB 2 }

ipv6UdpCompliances OBJECT IDENTIFIER ::= { ipv6UdpConformance 1 }
ipv6UdpGroups OBJECT IDENTIFIER ::= { ipv6UdpConformance 2 }

-- compliance statements

ipv6UdpCompliance MODULE-COMPLIANCE

STATUS obsolete

DESCRIPTION

"The compliance statement for SNMPv2 entities which implement UDP over IPv6.

This object is obsoleted by UDP-MIB::udpMIBCompliance2."

MODULE -- this module

MANDATORY-GROUPS { ipv6UdpGroup }

::= { ipv6UdpCompliances 1 }

ipv6UdpGroup OBJECT-GROUP

OBJECTS { -- these are defined in this module
-- ipv6UdpLocalAddress (not-accessible)
-- ipv6UdpLocalPort (not-accessible)
ipv6UdpIfIndex }

STATUS obsolete

DESCRIPTION

"The group of objects providing management of UDP over IPv6.

This group is obsoleted by several groups in UDP-MIB."
 ::= { ipv6UdpGroups 1 }

END

6. Historic IPV6-TCP-MIB

IPV6-TCP-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF
MODULE-IDENTITY, OBJECT-TYPE,
mib-2, experimental FROM SNMPv2-SMI
Ipv6Address, Ipv6IfIndexOrZero FROM IPV6-TC;

ipv6TcpMIB MODULE-IDENTITY
LAST-UPDATED "201505282112Z"
ORGANIZATION "IETF IPv6 MIB Working Group"
CONTACT-INFO
" Mike Daniele

Fenner

Expires February 26, 2016

[Page 55]

Internet-Draft

ipv6-mibs-obsolete

August 2015

Postal: Compaq Computer Corporation
110 Spitbrook Rd
Nashua, NH 03062.
US

Phone: +1 603 884 1423
Email: daniele@zk3.dec.com"

DESCRIPTION

"The obsolete MIB module for entities implementing TCP
over IPv6. Use the TCP-MIB instead."

REVISION "201505282112Z"

DESCRIPTION

"Obsoleting this MIB module; it has been replaced by
the revised TCP-MIB ([RFC4022](#))."

REVISION "9801290000Z"

DESCRIPTION

"First revision, published as [RFC2452](#)"

::= { experimental 86 }

-- objects specific to TCP for IPv6

tcp OBJECT IDENTIFIER ::= { mib-2 6 }

-- the TCP over IPv6 Connection table

-- This connection table contains information about this
-- entity's existing TCP connections between IPv6 endpoints.
-- Only connections between IPv6 addresses are contained in
-- this table. This entity's connections between IPv4
-- endpoints are contained in tcpConnTable.

ipv6TcpConnTable OBJECT-TYPE

SYNTAX SEQUENCE OF Ipv6TcpConnEntry

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"A table containing TCP connection-specific information,
for only those connections whose endpoints are IPv6 addresses.

This table is obsoleted by TCP-MIB::tcpConnectionTable."

::= { tcp 16 }

ipv6TcpConnEntry OBJECT-TYPE

SYNTAX Ipv6TcpConnEntry

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"A conceptual row of the ipv6TcpConnTable containing

information about a particular current TCP connection.
Each row of this table is transient, in that it ceases to
exist when (or soon after) the connection makes the transition
to the CLOSED state.

Note that conceptual rows in this table require an additional
index object compared to tcpConnTable, since IPv6 addresses
are not guaranteed to be unique on the managed node.

This entry is obsoleted by TCP-MIB::tcpConnectionEntry."

INDEX { ipv6TcpConnLocalAddress,
ipv6TcpConnLocalPort,
ipv6TcpConnRemAddress,
ipv6TcpConnRemPort,


```
        ipv6TcpConnIfIndex }
 ::= { ipv6TcpConnTable 1 }
```

```
Ipv6TcpConnEntry ::=
  SEQUENCE { ipv6TcpConnLocalAddress    Ipv6Address,
             ipv6TcpConnLocalPort      INTEGER (0..65535),
             ipv6TcpConnRemAddress     Ipv6Address,
             ipv6TcpConnRemPort        INTEGER (0..65535),
             ipv6TcpConnIfIndex        Ipv6IfIndexOrZero,
             ipv6TcpConnState          INTEGER }
```

```
ipv6TcpConnLocalAddress OBJECT-TYPE
  SYNTAX      Ipv6Address
  MAX-ACCESS  not-accessible
  STATUS      obsolete
  DESCRIPTION
    "The local IPv6 address for this TCP connection. In
    the case of a connection in the listen state which
    is willing to accept connections for any IPv6
    address associated with the managed node, the value
    ::0 is used.

    This object is obsoleted by
    TCP-MIB::tcpConnectionLocalAddressType."
 ::= { ipv6TcpConnEntry 1 }
```

```
ipv6TcpConnLocalPort OBJECT-TYPE
  SYNTAX      INTEGER (0..65535)
  MAX-ACCESS  not-accessible
  STATUS      obsolete
  DESCRIPTION
    "The local port number for this TCP connection.

    This object is obsoleted by TCP-MIB::tcpConnectionLocalPort."
```

```
 ::= { ipv6TcpConnEntry 2 }
```

```
ipv6TcpConnRemAddress OBJECT-TYPE
  SYNTAX      Ipv6Address
  MAX-ACCESS  not-accessible
  STATUS      obsolete
  DESCRIPTION
```

"The remote IPv6 address for this TCP connection.

This object is obsoleted by TCP-MIB::tcpConnectionRemAddress."
 ::= { ipv6TcpConnEntry 3 }

ipv6TcpConnRemPort OBJECT-TYPE

SYNTAX INTEGER (0..65535)

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"The remote port number for this TCP connection.

This object is obsoleted by TCP-MIB::tcpConnectionRemPort."
 ::= { ipv6TcpConnEntry 4 }

ipv6TcpConnIfIndex OBJECT-TYPE

SYNTAX Ipv6IfIndexOrZero

MAX-ACCESS not-accessible

STATUS obsolete

DESCRIPTION

"An index object used to disambiguate conceptual rows in the table, since the connection 4-tuple may not be unique.

If the connection's remote address (ipv6TcpConnRemAddress) is a link-local address and the connection's local address (ipv6TcpConnLocalAddress) is not a link-local address, this object identifies a local interface on the same link as the connection's remote link-local address.

Otherwise, this object identifies the local interface that is associated with the ipv6TcpConnLocalAddress for this TCP connection. If such a local interface cannot be determined, this object should take on the value 0. (A possible example of this would be if the value of ipv6TcpConnLocalAddress is ::0.)

The interface identified by a particular non-0 value of this index is the same interface as identified by the same value of ipv6IfIndex.

The value of this object must remain constant during the life of the TCP connection.

This object is obsoleted by the zone identifier in an InetAddressIPv6z address in either TCP-MIB::tcpConnectionLocalAddress or TCP-MIB::tcpConnectionRemAddress."

```
::= { ipv6TcpConnEntry 5 }
```

ipv6TcpConnState OBJECT-TYPE

```
SYNTAX      INTEGER {  
    closed(1),  
    listen(2),  
    synSent(3),  
    synReceived(4),  
    established(5),  
    finWait1(6),  
    finWait2(7),  
    closeWait(8),  
    lastAck(9),  
    closing(10),  
    timeWait(11),  
    deleteTCB(12) }
```

MAX-ACCESS read-write

STATUS obsolete

DESCRIPTION

"The state of this TCP connection.

The only value which may be set by a management station is deleteTCB(12). Accordingly, it is appropriate for an agent to return an error response ('badValue' for SNMPv1, 'wrongValue' for SNMPv2) if a management station attempts to set this object to any other value.

If a management station sets this object to the value deleteTCB(12), then this has the effect of deleting the TCB (as defined in [RFC 793](#)) of the corresponding connection on the managed node, resulting in immediate termination of the connection.

As an implementation-specific option, a RST segment may be sent from the managed node to the other TCP endpoint (note however that RST segments are not sent reliably).

This object is obsoleted by TCP-MIB::tcpConnectionState."

```
::= { ipv6TcpConnEntry 6 }
```

--

-- conformance information

--

Internet-Draft

ipv6-mibs-obsolete

August 2015

```
ipv6TcpConformance OBJECT IDENTIFIER ::= { ipv6TcpMIB 2 }

ipv6TcpCompliances OBJECT IDENTIFIER ::= { ipv6TcpConformance 1 }
ipv6TcpGroups      OBJECT IDENTIFIER ::= { ipv6TcpConformance 2 }

-- compliance statements

ipv6TcpCompliance MODULE-COMPLIANCE
  STATUS obsolete
  DESCRIPTION
    "The compliance statement for SNMPv2 entities which
    implement TCP over IPv6.

    This compliance statement is obsoleted by
    TCP-MIB::tcpMIBCompliance2."
  MODULE -- this module
  MANDATORY-GROUPS { ipv6TcpGroup }
  ::= { ipv6TcpCompliances 1 }

ipv6TcpGroup OBJECT-GROUP
  OBJECTS { -- these are defined in this module
    -- ipv6TcpConnLocalAddress (not-accessible)
    -- ipv6TcpConnLocalPort (not-accessible)
    -- ipv6TcpConnRemAddress (not-accessible)
    -- ipv6TcpConnRemPort (not-accessible)
    -- ipv6TcpConnIfIndex (not-accessible)
    ipv6TcpConnState }
  STATUS obsolete
  DESCRIPTION
    "The group of objects providing management of
    TCP over IPv6.

    This group is obsoleted by several groups in TCP-MIB."
  ::= { ipv6TcpGroups 1 }
```

END

7. Reclassification

This document reclassifies [[RFC2452](#)], [[RFC2454](#)], [[RFC2465](#)], and [[RFC2466](#)] to Historic.

8. Security Considerations

This document contains only obsolete objects, which [[RFC2578](#)] says "should not be implemented and/or can be removed if previously implemented". Since the contents of this document should not be implemented, it has no security implications. If there were any

security implications based on these objects in an implementation, removing these objects as [[RFC2578](#)] suggests would improve the security of that implementation.

9. IANA Considerations

In smi-numbers [[1](#)], the entries for [RFC2452](#) and [RFC2454](#), in the "SMI Experimental Codes" section, have an annotation "(Historic)" or "(Historical)".

IANA is asked to make the following changes to the "SMI Network Management MGMT Codes Internet-standard MIB" section:

- o Remove [RFC1213](#) from the references for mib-2.5 "icmp".
- o Update the reference for mib-2.6 "tcp" to point to [RFC4022](#).
- o Remove [RFC1213](#) from the references for mib-2.7 "udp".
- o Remove [RFC2012](#) from the references for mib-2.49 "tcpMIB".
- o Add the "(Historic)" annotation for the entries for mib-2.55 "ipv6MIB" and for mib-2.56 "ipv6IcmpMIB", and update the reference to point to this document.

IANA is asked to make the following changes to the "SMI Experimental Codes" section:

- o Add the "(Historic)" annotation for experimental.74 "IPV6 MIB"
- o Change the "(Historical)" annotation for experimental.87 "ipv6UdpMIB" to "(Historic)"
- o Update the reference for experimental.86 "ipv6TcpMIB" and experimental.87 "ipv6UdpMIB" to point to this document.

10. References

10.1. Normative References

- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIPv2)", STD 58, [RFC 2578](#), DOI 10.17487/[RFC2578](#), April 1999, <<http://www.rfc-editor.org/info/rfc2578>>.

Fenner

Expires February 26, 2016

[Page 61]

Internet-Draft

ipv6-mibs-obsolete

August 2015

10.2. Informative References

- [RFC2452] Daniele, M., "IP Version 6 Management Information Base for the Transmission Control Protocol", [RFC 2452](#), DOI 10.17487/RFC2452, December 1998, <<http://www.rfc-editor.org/info/rfc2452>>.
- [RFC2454] Daniele, M., "IP Version 6 Management Information Base for the User Datagram Protocol", [RFC 2454](#), DOI 10.17487/[RFC2454](#), December 1998, <<http://www.rfc-editor.org/info/rfc2454>>.
- [RFC2465] Haskin, D. and S. Onishi, "Management Information Base for IP Version 6: Textual Conventions and General Group", [RFC 2465](#), DOI 10.17487/RFC2465, December 1998, <<http://www.rfc-editor.org/info/rfc2465>>.
- [RFC2466] Haskin, D. and S. Onishi, "Management Information Base for IP Version 6: ICMPv6 Group", [RFC 2466](#), DOI 10.17487/[RFC2466](#), December 1998, <<http://www.rfc-editor.org/info/rfc2466>>.
- [RFC4022] Raghunathan, R., Ed., "Management Information Base for the Transmission Control Protocol (TCP)", [RFC 4022](#), DOI 10.17487/RFC4022, March 2005, <<http://www.rfc-editor.org/info/rfc4022>>.
- [RFC4113] Fenner, B. and J. Flick, "Management Information Base for the User Datagram Protocol (UDP)", [RFC 4113](#), DOI 10.17487/

[RFC4113](#), June 2005,
<<http://www.rfc-editor.org/info/rfc4113>>.

[RFC4292] Haberman, B., "IP Forwarding Table MIB", [RFC 4292](#), DOI 10.17487/RFC4292, April 2006,
<<http://www.rfc-editor.org/info/rfc4292>>.

[RFC4293] Routhier, S., Ed., "Management Information Base for the Internet Protocol (IP)", [RFC 4293](#), DOI 10.17487/RFC4293, April 2006, <<http://www.rfc-editor.org/info/rfc4293>>.

[10.3.](#) URIs

[1] <http://www.iana.org/assignments/smi-numbers/smi-numbers.xhtml>

Fenner

Expires February 26, 2016

[Page 62]

Internet-Draft

ipv6-mibs-obsolete

August 2015

[Appendix A.](#) Change history

[A.1.](#) Changes since [draft-fenner-ipv6-mibs-obsolete-00](#)

- o Realized that IPV6-ICMP-MIB was [[RFC2466](#)], so modified the added REVISION clause and the Reclassification section.
- o Added Security Considerations
- o Added IANA Considerations
- o Added the 6.c.iii Legend to the copyright statement, since the original RFCs were published before pre-5378.
- o Used "MIB module" instead of "MIB" when referring to a module, and changed REVISION DESCRIPTION to "Obsoleting", not "Deprecating".
- o Added "Obsoletes:" header to document
- o Switched to pre-5378 IPR statement, since the original RFCs were pre-5378.

[A.2.](#) Changes since [draft-fenner-ipv6-mibs-obsolete-01](#)

- o Updated the DESCRIPTION of MODULE-IDENTITY to improve the "MIB index" problem.
- o Updated IANA considerations.

[A.3.](#) Changes since [draft-fenner-ipv6-mibs-obsolete-02](#)

- o Fixed "IPV6-MIB" in title
- o Fixed some extra blank lines in the source MIBs, introduced by the process of extraction from RFCs.

Author's Address

Bill Fenner
Arista Networks, Inc.
5453 Great America Parkway
Santa Clara 95054
USA

Phone: +1-408-547-5572
Email: fenner@fenron.com