

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: November 8, 2008

H. Singh
W. Beebe
Cisco Systems, Inc.
E. Nordmark
Sun Microsystems
May 7, 2008

IPv6 Subnet Model: the Relationship between Links and Subnet Prefixes
draft-ietf-6man-ipv6-subnet-model-00

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on November 8, 2008.

Abstract

IPv6 specifies a model of a subnet that is different than the IPv4 subnet model. The subtlety of the differences has resulted in incorrect implementations that do not interoperate. This document spells out the most important difference; that an IPv6 address isn't automatically associated with an IPv6 on-link prefix.

Table of Contents

1.	Introduction	3
2.	Host Behavior Rules	4
3.	Observed Incorrect Implementation Behavior	5
4.	Conclusion	5
5.	Security Considerations	5
6.	IANA Considerations	5
7.	Acknowledgements	6
8.	References	6
8.1.	Normative References	6
8.2.	Informative References	6
	Authors' Addresses	7
	Intellectual Property and Copyright Statements	8

1. Introduction

IPv4 implementations associate a netmask when an IPv4 address is assigned to an interface. That netmask together with the IPv4 address designates an on-link prefix. Addresses that match this prefix are viewed as on-link i.e., traffic to these addresses is not sent to a router. See [section 3.3.1 in \[RFC1122\]](#). Further, note that implementations of IPv4 point-to-point interfaces might not have an associated IPv4 subnet prefix.

The behavior of IPv6 as specified in Neighbor Discovery [\[RFC4861\]](#) is quite different. The on-link determination is separate from the address assignment. A host can have IPv6 addresses without any related on-link prefixes or have on-link prefixes that are not related to any IPv6 addresses that are assigned to the host. Any assigned address on an interface should initially be considered as having no internal structure as shown in [\[RFC4291\]](#).

In IPv6, by default, a host treats only the link-local prefix as on-link.

The reception of a Prefix Information Option (PIO) with the L-bit set [\[RFC4861\]](#) and a non-zero valid lifetime creates an entry (or updates the valid lifetime for an existing entry) in the Prefix List. All the prefixes that are on the Prefix List, i.e., have not yet timed out, are on-link.

In addition to the Prefix List, individual addresses are on-link if they are the target of a Redirect Message indicating on-link, or the source of a valid Neighbor Solicitation or Neighbor Advertisement message. Note that Redirect Messages can also indicate an address is off-link. Individual address entries can be expired by the Neighbor Unreachability Detection mechanism.

A host only performs address resolution for IPv6 addresses that are on-link. Packets to any other address are sent to a default router. If there is no default router, then the node should send an ICMPv6 Destination Unreachable indication as specified in [\[RFC4861\]](#) - more details are provided in the Host Behavior Rules section. (Note that [RFC 4861](#) changed the behavior when the Default Router List is empty. The behavior in the old version of Neighbor Discovery [\[RFC2461\]](#) was different when there were no default routers.)

Failure of host implementations to correctly implement the IPv6 subnet model can result in lack of IPv6 connectivity. See the Observed Incorrect Implementation Behavior section for details.

Host behavior is clarified in the Host Behavior Rules section.

Finally, this document merely restates and clarifies [[RFC4861](#)].

2. Host Behavior Rules

A correctly implemented IPv6 host MUST adhere to the following rules:

1. By default only the link-local prefix is on-link.
2. The configuration of an IPv6 address, whether through IPv6 stateless address autoconfiguration [[RFC4862](#)], DHCPv6 [[RFC3315](#)], or manual configuration MUST NOT imply that any prefix is on-link. A host is explicitly told that prefixes or addresses are on-link through the means specified in [[RFC4861](#)]. Note that this requirement for manually configured addresses is not explicitly mentioned in [[RFC4861](#)].
3. On-link determination SHOULD NOT persist across IPv6 interface initializations. Note that [section 5.7 of \[RFC4862\]](#) describes the use of stable storage for addresses acquired with stateless address autoconfiguration with a note that the Preferred and Valid Lifetimes must be retained if this approach is used. However no RFC suggests or recommends retaining the on-link prefixes.
4. In the absence of other sources of on-link information, including Redirects, if the RA advertises a prefix with the on-link(L) bit set and later the Valid Lifetime expires, the host MUST then consider addresses of the prefix to be off-link, as specified by the PIO paragraph of [section 6.3.4 of \[RFC4861\]](#).
5. Newer implementations, which are compliant with [[RFC4861](#)] MUST adhere to the following rules. Older implementations, which are compliant with [[RFC2461](#)] but not [[RFC4861](#)] may remain as is. If the Default Router List is empty and there is no other source of on-link information about any address or prefix:
 1. The host MUST NOT assume that all destinations are on-link.
 2. The host MUST NOT perform address resolution for non-link-local addresses.
 3. Since the host cannot assume the destination is on-link, and off-link traffic cannot be sent to a default router (since the Default Router List is empty), address resolution cannot be performed. This case is analogous to the behavior specified in the last paragraph of [section 7.2.2 of \[RFC4861\]](#): when address resolution fails, the host SHOULD

send an ICMPv6 Destination Unreachable indication as specified in [\[RFC4861\]](#). The specified behavior MAY be extended to cover this case where address resolution cannot be performed.

On-link information concerning particular addresses and prefixes can make those specific addresses and prefixes on-link, but does not change the default behavior mentioned above for addresses and prefixes not specified. [\[RFC4943\]](#) provides justification for these rules.

[3.](#) Observed Incorrect Implementation Behavior

One incorrect implementation behavior illustrates the severe consequences when the IPv6 subnet model is not understood by the implementers of several popular host operating systems. In an access concentrator network ([\[RFC4388\]](#)), a host receives a Router Advertisement Message with no on-link prefix advertised. The host incorrectly assumes the prefix is on-link and performs address resolution when the host should send all non-link-local traffic to a default router. Neither the router nor any other host will respond to the address resolution, preventing this host from sending IPv6 traffic.

[4.](#) Conclusion

This document clarifies and summarizes the relationship between links and subnet prefixes described in [\[RFC4861\]](#). Configuration of an IPv6 address does not imply the existence of corresponding on-link prefixes. One should also look at API considerations for prefix length as described in last paragraph of [section 4.2 of \[RFC4903\]](#).

[5.](#) Security Considerations

As this document merely restates and clarifies [\[RFC4861\]](#), it does not introduce any new security issues.

[6.](#) IANA Considerations

None.

7. Acknowledgements

Thanks (in alphabetical order) to Adeel Ahmed, Jari Arkko, Ralph Droms, Alun Evans, Dave Forster, Prashanth Krishnamurthy, Suresh Krishnan, Josh Littlefield, Thomas Narten, Madhu Sudan, Jinmei Tatuya, Dave Thaler, Bernie Volz, and Vlad Yasevich for their consistent input, ideas and review during the production of this document.

8. References

8.1. Normative References

- [RFC4861] Narten, T., Nordmark, E., Simpson, W., and H. Soliman, "Neighbor Discovery for IP version 6 (IPv6)", [RFC 4861](#), September 2007.

8.2. Informative References

- [RFC1122] Braden, R., "Requirements for Internet Hosts - Communication Layers", STD 3, [RFC 1122](#), October 1989.
- [RFC2461] Narten, T., Nordmark, E., and W. Simpson, "Neighbor Discovery for IP Version 6 (IPv6)", [RFC 2461](#), December 1998.
- [RFC3315] Droms, R., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", [RFC 3315](#), July 2003.
- [RFC4291] Hinden, R. and S. Deering, "IP Version 6 Addressing Architecture", [RFC 4291](#), February 2006.
- [RFC4388] Woundy, R. and K. Kinnear, "Dynamic Host Configuration Protocol (DHCP) Leasequery", [RFC 4388](#), February 2006.
- [RFC4862] Thomson, S., Narten, T., and T. Jinmei, "IPv6 Stateless Address Autoconfiguration", [RFC 4862](#), September 2007.
- [RFC4903] Thaler, D., "Multi-Link Subnet Issues", [RFC 4903](#), June 2007.
- [RFC4943] Roy, S., Durand, A., and J. Paugh, "IPv6 Neighbor Discovery On-Link Assumption Considered Harmful", [RFC 4943](#), September 2007.

Authors' Addresses

Hemant Singh
Cisco Systems, Inc.
1414 Massachusetts Ave.
Boxborough, MA 01719
USA

Phone: +1 978 936 1622
Email: shemant@cisco.com
URI: <http://www.cisco.com/>

Wes Beebee
Cisco Systems, Inc.
1414 Massachusetts Ave.
Boxborough, MA 01719
USA

Phone: +1 978 936 2030
Email: wbeebee@cisco.com
URI: <http://www.cisco.com/>

Erik Nordmark
Sun Microsystems
17 Network Circle
Menlo Park, CA 94025
USA

Phone: +1 650 786 2921
Email: erik.nordmark@sun.com

Full Copyright Statement

Copyright (C) The IETF Trust (2008).

This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

