

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: November 24, 2018

S. Previdi  
Individual  
C. Filsfils, Ed.  
Cisco Systems, Inc.  
J. Leddy  
Comcast  
S. Matsushima  
Softbank  
D. Voyer, Ed.  
Bell Canada  
May 23, 2018

**IPv6 Segment Routing Header (SRH)**  
**draft-ietf-6man-segment-routing-header-13**

Abstract

Segment Routing can be applied to the IPv6 data plane using a new type of Routing Extension Header. This document describes the Segment Routing Extension Header and how it is used by Segment Routing capable nodes.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 24, 2018.

## Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">3</a>
<a href="#">2.</a>	<a href="#">Segment Routing Extension Header</a>	<a href="#">4</a>
<a href="#">2.1.</a>	<a href="#">SRH TLVs</a>	<a href="#">5</a>
<a href="#">2.1.1.</a>	<a href="#">Padding TLVs</a>	<a href="#">7</a>
<a href="#">2.1.2.</a>	<a href="#">HMAC TLV</a>	<a href="#">8</a>
<a href="#">3.</a>	<a href="#">SR Nodes</a>	<a href="#">9</a>
<a href="#">3.1.</a>	<a href="#">Source SR Node</a>	<a href="#">9</a>
<a href="#">3.2.</a>	<a href="#">Transit Node</a>	<a href="#">9</a>
<a href="#">3.3.</a>	<a href="#">SR Segment Endpoint Node</a>	<a href="#">10</a>
<a href="#">4.</a>	<a href="#">Packet Processing</a>	<a href="#">10</a>
<a href="#">4.1.</a>	<a href="#">Source SR Node</a>	<a href="#">10</a>
<a href="#">4.1.1.</a>	<a href="#">Reduced SRH</a>	<a href="#">10</a>
<a href="#">4.2.</a>	<a href="#">Transit Node</a>	<a href="#">11</a>
<a href="#">4.3.</a>	<a href="#">Segment Endpoint Node</a>	<a href="#">11</a>
<a href="#">4.3.1.</a>	<a href="#">FIB Entry Is Locally Instantiated SRv6 END SID</a>	<a href="#">11</a>
<a href="#">4.3.2.</a>	<a href="#">FIB Entry is a Local Interface</a>	<a href="#">12</a>
<a href="#">4.3.3.</a>	<a href="#">FIB Entry Is A Non-Local Route</a>	<a href="#">13</a>
<a href="#">4.3.4.</a>	<a href="#">FIB Entry Is A No Match</a>	<a href="#">13</a>
<a href="#">4.4.</a>	<a href="#">Load Balancing and ECMP</a>	<a href="#">13</a>
<a href="#">5.</a>	<a href="#">Illustrations</a>	<a href="#">13</a>
<a href="#">5.1.</a>	<a href="#">Abstract Representation of an SRH</a>	<a href="#">13</a>
<a href="#">5.2.</a>	<a href="#">Example Topology</a>	<a href="#">14</a>
<a href="#">5.3.</a>	<a href="#">Source SR Node</a>	<a href="#">15</a>
<a href="#">5.3.1.</a>	<a href="#">Intra SR Domain Packet</a>	<a href="#">15</a>
<a href="#">5.3.2.</a>	<a href="#">Transit Packet Through SR Domain</a>	<a href="#">15</a>
<a href="#">5.4.</a>	<a href="#">Transit Node</a>	<a href="#">15</a>
<a href="#">5.5.</a>	<a href="#">SR End Node</a>	<a href="#">16</a>
<a href="#">6.</a>	<a href="#">Security Considerations</a>	<a href="#">16</a>
<a href="#">6.1.</a>	<a href="#">Threat model</a>	<a href="#">17</a>
<a href="#">6.1.1.</a>	<a href="#">Source routing threats</a>	<a href="#">17</a>
<a href="#">6.1.2.</a>	<a href="#">Applicability of <a href="#">RFC 5095</a> to SRH</a>	<a href="#">17</a>



6.1.3.	Service stealing threat . . . . .	18
6.1.4.	Topology disclosure . . . . .	18
6.1.5.	ICMP Generation . . . . .	18
6.2.	Security fields in SRH . . . . .	19
6.2.1.	Selecting a hash algorithm . . . . .	20
6.2.2.	Performance impact of HMAC . . . . .	20
6.2.3.	Pre-shared key management . . . . .	21
6.3.	Deployment Models . . . . .	22
6.3.1.	Nodes within the SR domain . . . . .	22
6.3.2.	Nodes outside of the SR domain . . . . .	22
6.3.3.	SR path exposure . . . . .	23
6.3.4.	Impact of <a href="#">BCP-38</a> . . . . .	23
7.	IANA Considerations . . . . .	23
7.1.	Segment Routing Header Flags Register . . . . .	24
7.2.	Segment Routing Header TLVs Register . . . . .	24
8.	Implementation Status . . . . .	24
8.1.	Linux . . . . .	24
8.2.	Cisco Systems . . . . .	25
8.3.	FD.io . . . . .	25
8.4.	Barefoot . . . . .	25
8.5.	Juniper . . . . .	25
9.	Contributors . . . . .	25
10.	Acknowledgements . . . . .	26
11.	References . . . . .	26
11.1.	Normative References . . . . .	26
11.2.	Informative References . . . . .	27
	Authors' Addresses . . . . .	28

## 1. Introduction

Segment Routing can be applied to the IPv6 data plane using a new type of Routing Extension Header (SRH). This document describes the Segment Routing Extension Header and how it is used by Segment Routing capable nodes.

The Segment Routing Architecture [[I-D.ietf-spring-segment-routing](#)] describes Segment Routing and its instantiation in two data planes MPLS and IPv6.

SR with the MPLS data plane is defined in [[I-D.ietf-spring-segment-routing-mpls](#)].

SR with the IPv6 data plane is defined in [[I-D.filsfils-spring-srv6-network-programming](#)].

The encoding of MPLS labels and label stacking are defined in [[RFC3032](#)].




The encoding of IPv6 segments in the Segment Routing Extension header is defined in this document.

Terminology used within this document is defined in detail in [\[I-D.ietf-spring-segment-routing\]](#). Specifically, these terms: Segment Routing, SR Domain, SRv6, Segment ID (SID), SRv6 SID, Active Segment, and SR Policy.

## 2. Segment Routing Extension Header

Routing Headers are defined in [\[RFC8200\]](#). The Segment Routing Header has a new Routing Type (suggested value 4) to be assigned by IANA.

The Segment Routing Header (SRH) is defined as follows:



where:

- o Next Header: Defined in [\[RFC8200\]](#)



- o Hdr Ext Len: Defined in [[RFC8200](#)]
- o Routing Type: TBD, to be assigned by IANA (suggested value: 4).
- o Segments Left: Defined in [[RFC8200](#)]
- o Last Entry: contains the index (zero based), in the Segment List, of the last element of the Segment List.
- o Flags: 8 bits of flags. Following flags are defined:

```

  0 1 2 3 4 5 6 7
+-+--+--+--+--+--+
|   U  |H|   U  |
+-+--+--+--+--+--+

```

U: Unused and for future use. SHOULD be 0 on transmission and MUST be ignored on receipt.

H-flag: HMAC flag. If set, the HMAC TLV is present and is encoded as the last TLV of the SRH. In other words, the last 36 octets of the SRH represent the HMAC information. See [Section 2.1.2](#) for details on the HMAC TLV.

- o Tag: tag a packet as part of a class or group of packets, e.g., packets sharing the same set of properties. When tag is not used at source it SHOULD be set to zero on transmission. When tag is not used during SRH Processing it MUST be ignored. The allocation and use of tag is outside the scope of this document.
- o Segment List[n]: 128 bit IPv6 addresses representing the nth segment in the Segment List. The Segment List is encoded starting from the last segment of the SR Policy. I.e., the first element of the segment list (Segment List [0]) contains the last segment of the SR Policy, the second element contains the penultimate segment of the SR Policy and so on.
- o Type Length Value (TLV) are described in [Section 2.1](#).

## **[2.1](#). SRH TLVs**

This section defines TLVs of the Segment Routing Header.





```

      0                               1
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Type   |   Length   | Variable length data
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Type: An 8 bit value. Unrecognized Types MUST be ignored on receipt.

Length: The length of the Variable length data. It is RECOMMENDED that the total length of new TLVs be multiple of 8 bytes to avoid the use of Padding TLVs.

Variable length data: Length bytes of data that is specific to the Type.

Type Length Value (TLV) contain optional information that may be used by the node identified in the Destination Address (DA) of the packet. The information carried in the TLVs is not intended to be used by the routing layer. Typically, TLVs carry information that is consumed by other components (e.g.: OAM) than the routing function.

Each TLV has its own length, format and semantic. The code-point allocated (by IANA) to each TLV Type defines both the format and the semantic of the information carried in the TLV. Multiple TLVs may be encoded in the same SRH.

TLVs may change en route at each segment. To identify when a TLV type may change en route the most significant bit of the Type has the following significance:

0: TLV data does not change en route

1: TLV data does change en route

Identifying which TLVs change en route, without having to understand the Type, is required for Authentication Header Integrity Check Value (ICV) computation. Any TLV that changes en route is considered mutable for the purpose of ICV computation, the Type Length and Variable Length Data is ignored for the purpose of ICV Computation as defined in [\[RFC4302\]](#).

The "Length" field of the TLV is used to skip the TLV while inspecting the SRH in case the node doesn't support or recognize the Type. The "Length" defines the TLV length in octets, not including the "Type" and "Length" fields.

The following TLVs are defined in this document:



Padding TLV

HMAC TLV

Additional TLVs may be defined in the future.

#### **2.1.1.1. Padding TLVs**

There are two types of padding TLVs, pad0 and padN, the following applies to both:

Padding TLVs are optional and more than one Padding TLV MUST NOT appear in the SRH.

The Padding TLVs are used to align the SRH total length on the 8 octet boundary.

When present, a single Pad0 or PadN TLV MUST appear as the last TLV before the HMAC TLV (if HMAC TLV is present).

When present, a PadN TLV MUST have a length from 0 to 5 in order to align the SRH total length on a 8-octet boundary.

Padding TLVs are ignored by a node processing the SRH TLV, even if more than one is present.

Padding TLVs are ignored during ICV calculation.

##### **2.1.1.1.1. PAD0**

```

0 1 2 3 4 5 6 7
+-+--+--+--+--+
|      Type      |
+-+--+--+--+--+

```

Type: to be assigned by IANA (Suggested value 128)

A single Pad0 TLV MUST be used when a single byte of padding is required. If more than one byte of padding is required a Pad0 TLV MUST NOT be used, the PadN TLV MUST be used.

##### **2.1.1.1.2. PADN**



```

      0                   1                   2                   3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Type   |   Length   |   Padding (variable)   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
//                                     Padding (variable)                                     //
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Type: to be assigned by IANA (suggested value 129).

Length: 0 to 5

Padding: Length octets of padding. Padding bits have no semantics. They SHOULD be set to 0 on transmission and MUST be ignored on receipt.

The PadN TLV MUST be used when more than one byte of padding is required.

### [2.1.2.](#) HMAC TLV

HMAC TLV is optional and contains the HMAC information. The HMAC TLV has the following format:

```

      0                   1                   2                   3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Type   |   Length   |   RESERVED   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     HMAC Key ID (4 octets)                                     |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                                                 //
|                                     HMAC (32 octets)                                     //
|                                                                 //
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

where:

- o Type: to be assigned by IANA (suggested value 5).
- o Length: 38.
- o RESERVED: 2 octets. SHOULD be unset on transmission and MUST be ignored on receipt.
- o HMAC Key ID: 4 octets.
- o HMAC: 32 octets.



- o HMAC and HMAC Key ID usage is described in [Section 6](#)

The Following applies to the HMAC TLV:

- o When present, the HMAC TLV MUST be encoded as the last TLV of the SRH.
- o If the HMAC TLV is present, the SRH H-Flag (Figure 2) MUST be set. Nodes processing SRH SHOULD process the HMAC TLV only when the H-Flag is set, and local policy.
- o When the H-flag is set in the SRH, the router inspecting the SRH MUST find the HMAC TLV in the last 38 octets of the SRH.

### **3. SR Nodes**

There are different types of nodes that may be involved in segment routing networks: source SR nodes originate packets with a segment in the destination address of the IPv6 header, transit nodes that forward packets destined to a remote segment, and segment endpoint nodes that process a local segment in the destination address of an IPv6 header.

#### **3.1. Source SR Node**

A Source SR Node is any node that originates an IPv6 packet with a segment (i.e. SRv6 SID) in the destination address of the IPv6 header. The packet leaving the source SR Node may or may not contain an SRH. This includes either:

A host originating an IPv6 packet.

An SR domain ingress router encapsulating a received packet in an outer IPv6 header, followed by an optional SRH.

The mechanism through which a segment in the destination address of the IPv6 header and the Segment List in the SRH, is derived is outside the scope of this document. For example, the Segment List may be obtained through local SR Policy computation, local configuration, interaction with a controller instantiating an SR Policy, or any other mechanism.

#### **3.2. Transit Node**

A transit node is any node forwarding an IPv6 packet where the destination address of that packet is not locally configured as a segment nor a local interface. A transit node is not required to be capable of processing a segment nor SRH.





### **3.3. SR Segment Endpoint Node**

A SR segment endpoint node is any node receiving an IPv6 packet where the destination address of that packet is locally configured as a segment or local interface.

## **4. Packet Processing**

This section describes SRv6 packet processing at the Source, Transit and Segment Endpoint nodes.

### **4.1. Source SR Node**

A Source node steers a packet into an SR Policy and the SRH is created as follows:

Next Header and Hdr Ext Len fields are set as specified in [[RFC8200](#)].

Routing Type field is set as TBD (to be allocated by IANA, suggested value 4).

The DA of the packet is set with the value of the first segment.

The first element of the SRH Segment List is the ultimate segment. The second element is the penultimate segment and so on.

The Segments Left field is set to n-1 where n is the number of elements in the SR Policy.

The Last Entry field is set to n-1 where n is the number of elements in the SR Policy.

HMAC TLV may be set according to [Section 6](#).

If the segment list contains a single segment and there is no need for information in flag or TLV, then the SRH MAY be omitted.

The packet is forwarded toward the packet's Destination Address (the first segment).

#### **4.1.1. Reduced SRH**

When a source does not require the entire SID list to be preserved in the SRH, a reduced SRH may be used.

A reduced SRH does not contain the first segment of the related SR Policy (the first segment is the one already in the DA of the IPv6



header), and the Last Entry field is set to  $n-2$  where  $n$  is the number of elements in the SR Policy.

#### **4.2. Transit Node**

As specified in [RFC8200], the only node allowed to inspect the Routing Extension Header (and therefore the SRH), is the node corresponding to the DA of the packet. Any other transit node MUST NOT inspect the underneath routing header and MUST forward the packet toward the DA according to its IPv6 routing table.

When a SID is in the destination address of an IPv6 header of a packet, it's routed through an IPv6 network as an IPv6 address. SIDs, or the prefix(es) covering SIDs, and their reachability may be distributed by means outside the scope of this document. For example, [RFC5308] or [RFC5340] may be used to advertise a prefix covering the SIDs on a node.

#### **4.3. Segment Endpoint Node**

Without constraining the details of an implementation, the Segment Endpoint Node creates Forwarding Information Base (FIB) entries for its local SIDs.

When an SRv6-capable node receives an IPv6 packet, it performs a longest-prefix-match lookup on the packets destination address. This lookup can return any of the following:

- A FIB entry that represents a locally instantiated SRv6 SID
- A FIB entry that represents a local interface, not locally instantiated as an SRv6 SID
- A FIB entry that represents a non-local route
- No Match

##### **4.3.1. FIB Entry Is Locally Instantiated SRv6 END SID**

This document, and section, defines a single SRv6 SID called END. Future documents may define additional SRv6 SIDs. In which case, the entire content of this section will be defined in that document.

If the FIB entry represents a locally instantiated SRv6 SID, process the next header of the IPv6 header as defined in [section 4 of \[RFC8200\]](#) until the upper-layer header, or "No Next Header" is reached.



```
When an SRH is processed {
  If Segments Left is equal to zero {
    Skip SRH Processing
  }
  Else {
    If Segments Left is greater than (Last Entry+1) {
      Send an ICMP Parameter Problem, Code 0, message to the
      Source Address, pointing to the Segments Left field, and
      discard the packet.
    }
    Else {
      Decrement Segments Left by 1.
      Copy Segment List[Segments Left] from the SRH to the
      destination address of the IPv6 header.
      If the IPv6 Hop Limit is less than or equal to 1 {
        Send an ICMP Time Exceeded -- Hop Limit Exceeded in
        Transit message to the Source Address and discard
        the packet.
      }
      Else {
        Decrement the Hop Limit by 1
        Resubmit the packet to the IPv6 module for transmission
        to the new destination.
      }
    }
  }
}

If the upper-layer header or No Next Header is reached {
  Send an ICMP destination unreachable to
  the Source Address and discard the packet.
}
```

#### **4.3.2. FIB Entry is a Local Interface**

If the FIB entry represents a local interface, not locally instantiated as an SRv6 SID, the SRH is processed as follows:

If Segments Left is zero, the node must ignore the Routing header and proceed to process the next header in the packet, whose type is identified by the Next Header field in the Routing header.

If Segments Left is non-zero, the node must discard the packet and send an ICMP Parameter Problem, Code 0, message to the packet's Source Address, pointing to the unrecognized Routing Type.



#### **4.3.3. FIB Entry Is A Non-Local Route**

Processing is not changed by this document.

#### **4.3.4. FIB Entry Is A No Match**

Processing is not changed by this document.

#### **4.4. Load Balancing and ECMP**

Within an SR domain, an SR source node encapsulates a packet in an outer IPv6 header for transport to an endpoint. The SR source node MUST impose a flow label computed based on the inner packet. The computation of the flow label is as recommended in [[RFC6438](#)] for the sending Tunnel End Point.

At any transit node within an SR domain, the flow label MUST be used as defined in [[RFC6438](#)] to calculate the ECMP hash toward the destination address. If flow label is not used, the transit node may hash all packets between a pair of SR Edge nodes to the same link.

At an SR segment endpoint node, the flow label MUST be used as defined in [[RFC6438](#)] to calculate any ECMP hash used to forward the processed packet to the next segment.

### **5. Illustrations**

This section provides illustrations of SRv6 packet processing at source, transit and endpoint nodes.

#### **5.1. Abstract Representation of an SRH**

For a node  $k$ , its IPv6 address is represented as  $A_k$ , its SRv6 SID is represented as  $S_k$ .

IPv6 headers are represented as the tuple of (source, destination). For example, a packet with source address  $A_1$  and destination address  $A_2$  is represented as  $(A_1, A_2)$ . The payload of the packet is omitted.

An SR Policy is a list of segments. A list of segments is represented as  $\langle S_1, S_2, S_3 \rangle$  where  $S_1$  is the first SID to visit,  $S_2$  is the second SID to visit and  $S_3$  is the last SID to visit.

$(SA, DA) (S_3, S_2, S_1; SL)$  represents an IPv6 packet with:

- o Source Address is SA, Destination Addresses is DA, and next-header is SRH.





- o SRH with SID list <S1, S2, S3> with SegmentsLeft = SL.
- o Note the difference between the <> and () symbols. <S1, S2, S3> represents a SID list where the leftmost segment is the first segment. Whereas, (S3, S2, S1; SL) represents the same SID list but encoded in the SRH Segment List format where the leftmost segment is the last segment. When referring to an SR policy in a high-level use-case, it is simpler to use the <S1, S2, S3> notation. When referring to an illustration of detailed behavior, the (S3, S2, S1; SL) notation is more convenient.

At its SR Policy headend, the Segment List <S1,S2,S3> results in SRH (S3,S2,S1; SL=2) represented fully as:


```

Segments Left=2
Last Entry=2
Flags=0
Tag=0
Segment List[0]=S3
Segment List[1]=S2
Segment List[2]=S1

```

## 5.2. Example Topology

The following topology is used in examples below:



- o 3 and 4 are SR Domain edge routers
- o 5, 6, and 7 are all SR Domain routers
- o 8 and 9 are hosts within the SR Domain
- o 1 and 2 are hosts outside the SR Domain



### **5.3. Source SR Node**

#### **5.3.1. Intra SR Domain Packet**

When host 8 sends a packet to host 9 via an SR Policy <S7,A9> the packet is

P1: (A8,S7)(A9,S7; SL=1)

##### **5.3.1.1. Reduced Variant**

When host 8 sends a packet to host 9 via an SR Policy <S7,A9> and it wants to use a reduced SRH, the packet is

P2: (A8,S7)(A9; SL=1)

#### **5.3.2. Transit Packet Through SR Domain**

When host 1 sends a packet to host 2, the packet is

P3: (A1,A2)

The SR Domain ingress router 3 receives P3 and steers it to SR Domain egress router 4 via an SR Policy <S7, S4>. Router 3 encapsulates the received packet P3 in an outer header with an SRH. The packet is

P4: (A3, S7)(S4, S7; SL=1)(A1, A2)

If the SR Policy contains only one segment (the egress router 4), the ingress Router 3 encapsulates P3 into an outer header (A3, S4). The packet is

P5: (A3, S4)(A1, A2)

##### **5.3.2.1. Reduced Variant**

The SR Domain ingress router 3 receives P3 and steers it to SR Domain egress router 4 via an SR Policy <S7, S4>. If router 3 wants to use a reduced SRH, Router 3 encapsulates the received packet P3 in an outer header with a reduced SRH. The packet is

P6: (A3, S7)(S4; SL=1)(A1, A2)

### **5.4. Transit Node**

Nodes 5 acts as transit nodes for packet P1, and sends packet

P1: (A8,S7)(A9,S7;SL=1)



on the interface toward node 7.

### 5.5. SR End Node

Node 7 receives packet P1 and, using the logic in [section 4.3.1](#), sends packet

P7: (A8,A9)(A9,S7; SL=0)

on the interface toward router 6.

## 6. Security Considerations

This section analyzes the security threat model, the security issues and proposed solutions related to the new Segment Routing Header.

The Segment Routing Header (SRH) is simply another type of the routing header as described in [\[RFC8200\]](#) and is:

- o Added by an SR edge router when entering the segment routing domain or by the originating host itself. The source host can even be outside the SR domain;
- o inspected and acted upon when reaching the destination address of the IP header per [\[RFC8200\]](#).

Per [\[RFC8200\]](#), routers on the path that simply forward an IPv6 packet (i.e. the IPv6 destination address is none of theirs) will never inspect and process the content of the SRH. Routers whose FIB contains a locally instantiated SRv6 SID equal to the destination address field of the IPv6 packet MUST parse the SRH and, if supported and if the local configuration allows it, MUST act accordingly to the SRH content.

As specified in [\[RFC8200\]](#), the default behavior of a non SR-capable router upon receipt of an IPv6 packet with SRH destined to an address of its, is to:

- o ignore the SRH completely if the Segment Left field is 0 and proceed to process the next header in the IPv6 packet;
- o discard the IPv6 packet if Segment Left field is greater than 0, it MAY send a Parameter Problem ICMP message back to the Source Address.



## **6.1. Threat model**

### **6.1.1. Source routing threats**

Using an SRH is similar to source routing, therefore it has some well-known security issues as described in [\[RFC4942\] section 2.1.1](#) and [\[RFC5095\]](#):

- o amplification attacks: where a packet could be forged in such a way to cause looping among a set of SR-enabled routers causing unnecessary traffic, hence a Denial of Service (DoS) against bandwidth;
- o reflection attack: where a hacker could force an intermediate node to appear as the immediate attacker, hence hiding the real attacker from naive forensic;
- o bypass attack: where an intermediate node could be used as a stepping stone (for example in a De-Militarized Zone) to attack another host (for example in the datacenter or any back-end server).

### **6.1.2. Applicability of [RFC 5095](#) to SRH**

First of all, the reader must remember this specific part of [section 1 of \[RFC5095\]](#), "A side effect is that this also eliminates benign RH0 use-cases; however, such applications may be facilitated by future Routing Header specifications.". In short, it is not forbidden to create new secure type of Routing Header; for example, [\[RFC6554\]](#) (RPL) also creates a new Routing Header type for a specific application confined in a single network.

In the segment routing architecture described in [\[I-D.ietf-spring-segment-routing\]](#) there are basically two kinds of nodes (routers and hosts):

- o nodes within the SR domain, which is within one single administrative domain, i.e., where all nodes are trusted anyway else the damage caused by those nodes could be worse than amplification attacks: traffic interception, man-in-the-middle attacks, more server DoS by dropping packets, and so on.
- o nodes outside of the SR domain, which is outside of the administrative segment routing domain hence they cannot be trusted because there is no physical security for those nodes, i.e., they can be replaced by hostile nodes or can be coerced in wrong behaviors.





The main use case for SR consists of the single administrative domain where only trusted nodes with SR enabled and configured participate in SR: this is the same model as in [\[RFC6554\]](#). All non-trusted nodes do not participate as either SR processing is not enabled by default or because they only process SRH from nodes within their domain.

Moreover, all SR nodes ignore SRH created by outsiders based on topology information (received on a peering or internal interface) or on presence and validity of the HMAC field. Therefore, if intermediate nodes ONLY act on valid and authorized SRH (such as within a single administrative domain), then there is no security threat similar to RH-0. Hence, the [\[RFC5095\]](#) attacks are not applicable.

#### **[6.1.3.](#) Service stealing threat**

Segment routing is used for added value services, there is also a need to prevent non-participating nodes to use those services; this is called 'service stealing prevention'.

#### **[6.1.4.](#) Topology disclosure**

The SRH may also contains SIDs of some intermediate SR-nodes in the path towards the destination, this obviously reveals those addresses to the potentially hostile attackers if those attackers are able to intercept packets containing SRH. On the other hand, if the attacker can do a traceroute whose probes will be forwarded along the SR Policy, then there is little learned by intercepting the SRH itself.

#### **[6.1.5.](#) ICMP Generation**

Per [Section 4.4 of \[RFC8200\]](#), when destination nodes (i.e. where the destination address is one of theirs) receive a Routing Header with unsupported Routing Type, the required behavior is:

- o If Segments Left is zero, the node must ignore the Routing header and proceed to process the next header in the packet.
- o If Segments Left is non-zero, the node must discard the packet and send an ICMP Parameter Problem, Code 0, message to the packet's Source Address, pointing to the unrecognized Routing Type.

This required behavior could be used by an attacker to force the generation of ICMP message by any node. The attacker could send packets with SRH (with Segment Left not set to 0) destined to a node not supporting SRH. Per [\[RFC8200\]](#), the destination node could generate an ICMP message, causing a local CPU utilization and if the



source of the offending packet with SRH was spoofed could lead to a reflection attack without any amplification.

It must be noted that this is a required behavior for any unsupported Routing Type and not limited to SRH packets. So, it is not specific to SRH and the usual rate limiting for ICMP generation is required anyway for any IPv6 implementation and has been implemented and deployed for many years.

## **6.2. Security fields in SRH**

This section summarizes the use of specific fields in the SRH. They are based on a key-hashed message authentication code (HMAC).

The security-related fields in the SRH are instantiated by the HMAC TLV, containing:

- o HMAC Key-id, 32 bits wide;
- o HMAC, 256 bits wide (optional, exists only if HMAC Key-id is not 0).

The HMAC field is the output of the HMAC computation (per [[RFC2104](#)]) using a pre-shared key identified by HMAC Key-id and of the text which consists of the concatenation of:

- o the source IPv6 address;
- o Last Entry field;
- o an octet of bit flags;
- o HMAC Key-id;
- o all addresses in the Segment List.

The purpose of the HMAC TLV is to verify the validity, the integrity and the authorization of the SRH itself. If an outsider of the SR domain does not have access to a current pre-shared secret, then it cannot compute the right HMAC field and the first SR router on the path processing the SRH and configured to check the validity of the HMAC will simply reject the packet.

The HMAC TLV is located at the end of the SRH simply because only the router on the ingress of the SR domain needs to process it, then all other SR nodes can ignore it (based on local policy) because they trust the upstream router. This is to speed up forwarding operations



because SR routers which do not validate the SRH do not need to parse the SRH until the end.

The HMAC Key-id field allows for the simultaneous existence of several hash algorithms (SHA-256, SHA3-256 ... or future ones) as well as pre-shared keys. The HMAC Key-id field is opaque, i.e., it has neither syntax nor semantic except as an index to the right combination of pre-shared key and hash algorithm and except that a value of 0 means that there is no HMAC field. Having an HMAC Key-id field allows for pre-shared key roll-over when two pre-shared keys are supported for a while when all SR nodes converged to a fresher pre-shared key. It could also allow for interoperation among different SR domains if allowed by local policy and assuming a collision-free HMAC Key Id allocation.

When a specific SRH is linked to a time-related service (such as turbo-QoS for a 1-hour period) where the DA, Segment ID (SID) are identical, then it is important to refresh the shared-secret frequently as the HMAC validity period expires only when the HMAC Key-id and its associated shared-secret expires.

#### **6.2.1. Selecting a hash algorithm**

The HMAC field in the HMAC TLV is 256 bit wide. Therefore, the HMAC MUST be based on a hash function whose output is at least 256 bits. If the output of the hash function is 256, then this output is simply inserted in the HMAC field. If the output of the hash function is larger than 256 bits, then the output value is truncated to 256 by taking the least-significant 256 bits and inserting them in the HMAC field.

SRH implementations can support multiple hash functions but MUST implement SHA-2 [[FIPS180-4](#)] in its SHA-256 variant.

NOTE: SHA-1 is currently used by some early implementations used for quick interoperations testing, the 160-bit hash value must then be right-hand padded with 96 bits set to 0. The authors understand that this is not secure but is ok for limited tests.

#### **6.2.2. Performance impact of HMAC**

While adding an HMAC to each and every SR packet increases the security, it has a performance impact. Nevertheless, it must be noted that:

- o the HMAC field is used only when SRH is added by a device (such as a home set-up box) which is outside of the segment routing domain. If the SRH is added by a router in the trusted segment routing



domain, then, there is no need for an HMAC field, hence no performance impact.

- o when present, the HMAC field MUST only be checked and validated by the first router of the segment routing domain, this router is named 'validating SR router'. Downstream routers may not inspect the HMAC field.
- o this validating router can also have a cache of <IPv6 header + SRH, HMAC field value> to improve the performance. It is not the same use case as in IPsec where HMAC value was unique per packet, in SRH, the HMAC value is unique per flow.
- o Last point, hash functions such as SHA-2 have been optimized for security and performance and there are multiple implementations with good performance.

With the above points in mind, the performance impact of using HMAC is minimized.

### **6.2.3. Pre-shared key management**

The field HMAC Key-id allows for:

- o key roll-over: when there is a need to change the key (the hash pre-shared secret), then multiple pre-shared keys can be used simultaneously. The validating routing can have a table of <HMAC Key-id, pre-shared secret> for the currently active and future keys.
- o different algorithms: by extending the previous table to <HMAC Key-id, hash function, pre-shared secret>, the validating router can also support simultaneously several hash algorithms (see section [Section 6.2.1](#))

The pre-shared secret distribution can be done:

- o in the configuration of the validating routers, either by static configuration or any SDN oriented approach;
- o dynamically using a trusted key distribution such as [\[RFC6407\]](#)

The intent of this document is NOT to define yet-another-key-distribution-protocol.





### **6.3. Deployment Models**

#### **6.3.1. Nodes within the SR domain**

An SR domain is defined as a set of interconnected routers where all routers at the perimeter are configured to add and act on SRH. Some routers inside the SR domain can also act on SRH or simply forward IPv6 packets.

The routers inside an SR domain can be trusted to generate SRH and to process SRH received on interfaces that are part of the SR domain. These nodes **MUST** drop all SRH packets received on an interface that is not part of the SR domain, destined to a locally instantiated SID, and containing an SRH whose HMAC field cannot be validated by local policies. This includes obviously packet with an SRH generated by a non-cooperative SR domain.

If the validation fails, then these packets **MUST** be dropped, ICMP error messages (parameter problem) **SHOULD** be generated (but rate limited) and **SHOULD** be logged.

#### **6.3.2. Nodes outside of the SR domain**

Nodes outside of the SR domain cannot be trusted for physical security; hence, they need to request by some trusted means (outside the scope of this document) a complete SRH for each new connection (i.e. new destination address). The received SRH **MUST** include an HMAC TLV which is computed correctly (see [Section 6.2](#)).

When an outside node sends a packet with an SRH and towards an SR domain ingress node, the packet **MUST** contain the HMAC TLV (with a Key-id and HMAC fields) and the the destination address **MUST** be an address of an SR domain ingress node .

The ingress SR router, i.e., the router with a SID equal to the destination address, **MUST** verify the HMAC TLV.

If the validation is successful, then the packet is simply forwarded as usual for an SR packet. As long as the packet travels within the SR domain, no further HMAC check needs to be done. Subsequent routers in the SR domain **MAY** verify the HMAC TLV when they process the SRH (i.e. when they are the destination).

If the validation fails, then this packet **MUST** be dropped, an ICMP error message (parameter problem) **SHOULD** be generated (but rate limited) and **SHOULD** be logged.



### **6.3.3. SR path exposure**

As the intermediate SR nodes addresses appears in the SRH, if this SRH is visible to an outsider then he/she could reuse this knowledge to launch an attack on the intermediate SR nodes or get some insider knowledge on the topology. This is especially applicable when the path between the source node and the first SR domain ingress router is on the public Internet.

The first remark is to state that 'security by obscurity' is never enough; in other words, the security policy of the SR domain MUST assume that the internal topology and addressing is known by the attacker. A simple traceroute will also give the same information (with even more information as all intermediate nodes between SID will also be exposed). IPsec Encapsulating Security Payload [[RFC4303](#)] cannot be use to protect the SRH as per [RFC4303](#) the ESP header must appear after any routing header (including SRH).

To prevent a user to leverage the gained knowledge by intercepting SRH, it is recommended to apply an infrastructure Access Control List (iACL) at the edge of the SR domain. This iACL will drop all packets from outside the SR-domain whose destination is any address of any router interface or SID inside the domain. This security policy should be tuned for local operations.

### **6.3.4. Impact of [BCP-38](#)**

[BCP-38](#) [[RFC2827](#)], also known as "Network Ingress Filtering", checks whether the source address of packets received on an interface is valid for this interface. The use of loose source routing such as SRH forces packets to follow a path which differs from the expected routing. Therefore, if [BCP-38](#) was implemented in all routers inside the SR domain, then SR packets could be received by an interface which is not expected one and the packets could be dropped.

As an SR domain is usually a subset of one administrative domain, and as [BCP-38](#) is only deployed at the ingress routers of this administrative domain and as packets arriving at those ingress routers have been normally forwarded using the normal routing information, then there is no reason why this ingress router should drop the SRH packet based on [BCP-38](#). Routers inside the domain commonly do not apply [BCP-38](#); so, this is not a problem.

## **7. IANA Considerations**

This document makes the following registrations in the Internet Protocol Version 6 (IPv6) Parameters "Routing Type" registry maintained by IANA:



Suggested Value	Description	Reference
-----		
4	Segment Routing Header (SRH)	This document

This document request IANA to create and maintain a new Registry:  
"Segment Routing Header TLVs"

### **7.1. Segment Routing Header Flags Register**

This document requests the creation of a new IANA managed registry to identify SRH Flags Bits. The registration procedure is "Expert Review" as defined in [[RFC8126](#)]. Suggested registry name is "Segment Routing Header Flags". Flags is 8 bits, the following bits are defined in this document:

Suggested Bit	Description	Reference
-----		
4	HMAC	This document

### **7.2. Segment Routing Header TLVs Register**

This document requests the creation of a new IANA managed registry to identify SRH TLVs. The registration procedure is "Expert Review" as defined in [[RFC8126](#)]. Suggested registry name is "Segment Routing Header TLVs". A TLV is identified through an unsigned 8 bit codepoint value. The following codepoints are defined in this document:

Suggested Value	Description	Reference
-----		
5	HMAC TLV	This document
128	Pad0 TLV	This document
129	PadN TLV	This document

## **8. Implementation Status**

This section is to be removed prior to publishing as an RFC.

### **8.1. Linux**

Name: Linux Kernel v4.14

Status: Production

Implementation: adds SRH, performs END processing, supports HMAC TLV



Details: <https://irtf.org/anrw/2017/anrw17-final3.pdf> and  
[[I-D.filsfils-spring-srv6-interop](#)]

## **8.2. Cisco Systems**

Name: IOS XR and IOS XE

Status: Pre-production

Implementation: adds SRH, performs END processing, no TLV processing

Details: [[I-D.filsfils-spring-srv6-interop](#)]

## **8.3. FD.io**

Name: VPP/Segment Routing for IPv6

Status: Production

Implementation: adds SRH, performs END processing, no TLV processing

Details: [https://wiki.fd.io/view/VPP/Segment\\_Routing\\_for\\_IPv6](https://wiki.fd.io/view/VPP/Segment_Routing_for_IPv6) and  
[[I-D.filsfils-spring-srv6-interop](#)]

## **8.4. Barefoot**

Name: Barefoot Networks Tofino NPU

Status: Prototype

Implementation: performs END processing, no TLV processing

Details: [[I-D.filsfils-spring-srv6-interop](#)]

## **8.5. Juniper**

Name: Juniper Networks Trio and vTrio NPU's

Status: Prototype & Experimental

Implementation: SRH insertion mode, Process SID where SID is an  
interface address, no TLV processing

## **9. Contributors**

Kamran Raza, Darren Dukes, Brian Field, Daniel Bernier, Ida Leung,  
Jen Linkova, Ebben Aries, Tomoya Kosugi, Eric Vyncke, David Lebrun,  
Dirk Steinberg, Robert Raszuk, Dave Barach, John Brzozowski, Pierre





Francois, Nagendra Kumar, Mark Townsley, Christian Martin, Roberta Maglione, James Connolly, Aloys Augustin contributed to the content of this document.

## **10. Acknowledgements**

The authors would like to thank Ole Troan, Bob Hinden, Ron Bonica, Fred Baker, Brian Carpenter, Alexandru Petrescu, Punit Kumar Jaiswal, and David Lebrun for their comments to this document.

## **11. References**

### **11.1. Normative References**

- [FIPS180-4]  
National Institute of Standards and Technology, "FIPS 180-4 Secure Hash Standard (SHS)", March 2012,  
<<http://csrc.nist.gov/publications/fips/fips180-4/fips-180-4.pdf>>.
- [I-D.ietf-spring-segment-routing]  
Filsfils, C., Previdi, S., Ginsberg, L., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing Architecture", [draft-ietf-spring-segment-routing-15](#) (work in progress), January 2018.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997,  
<<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC4303] Kent, S., "IP Encapsulating Security Payload (ESP)", [RFC 4303](#), DOI 10.17487/RFC4303, December 2005,  
<<https://www.rfc-editor.org/info/rfc4303>>.
- [RFC5095] Abley, J., Savola, P., and G. Neville-Neil, "Deprecation of Type 0 Routing Headers in IPv6", [RFC 5095](#), DOI 10.17487/RFC5095, December 2007,  
<<https://www.rfc-editor.org/info/rfc5095>>.
- [RFC6407] Weis, B., Rowles, S., and T. Hardjono, "The Group Domain of Interpretation", [RFC 6407](#), DOI 10.17487/RFC6407, October 2011, <<https://www.rfc-editor.org/info/rfc6407>>.
- [RFC8200] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", STD 86, [RFC 8200](#), DOI 10.17487/RFC8200, July 2017,  
<<https://www.rfc-editor.org/info/rfc8200>>.



## 11.2. Informative References

- [I-D.filsfils-spring-srv6-interop]  
Filsfils, C., Clad, F., Camarillo, P., Abdelsalam, A., Salsano, S., Bonaventure, O., Horn, J., and J. Liste, "SRv6 interoperability report", [draft-filsfils-spring-srv6-interop-00](#) (work in progress), March 2018.
- [I-D.filsfils-spring-srv6-network-programming]  
Filsfils, C., Li, Z., Leddy, J., daniel.voyer@bell.ca, d., daniel.bernier@bell.ca, d., Steinberg, D., Raszuk, R., Matsushima, S., Lebrun, D., Decraene, B., Peirens, B., Salsano, S., Naik, G., Elmalky, H., Jonnalagadda, P., and M. Sharif, "SRv6 Network Programming", [draft-filsfils-spring-srv6-network-programming-04](#) (work in progress), March 2018.
- [I-D.ietf-spring-segment-routing-mpls]  
Bashandy, A., Filsfils, C., Previdi, S., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing with MPLS data plane", [draft-ietf-spring-segment-routing-mpls-13](#) (work in progress), April 2018.
- [RFC2104] Krawczyk, H., Bellare, M., and R. Canetti, "HMAC: Keyed-Hashing for Message Authentication", [RFC 2104](#), DOI 10.17487/RFC2104, February 1997, <<https://www.rfc-editor.org/info/rfc2104>>.
- [RFC2827] Ferguson, P. and D. Senie, "Network Ingress Filtering: Defeating Denial of Service Attacks which employ IP Source Address Spoofing", [BCP 38](#), [RFC 2827](#), DOI 10.17487/RFC2827, May 2000, <<https://www.rfc-editor.org/info/rfc2827>>.
- [RFC3032] Rosen, E., Tappan, D., Fedorkow, G., Rekhter, Y., Farinacci, D., Li, T., and A. Conta, "MPLS Label Stack Encoding", [RFC 3032](#), DOI 10.17487/RFC3032, January 2001, <<https://www.rfc-editor.org/info/rfc3032>>.
- [RFC4302] Kent, S., "IP Authentication Header", [RFC 4302](#), DOI 10.17487/RFC4302, December 2005, <<https://www.rfc-editor.org/info/rfc4302>>.
- [RFC4942] Davies, E., Krishnan, S., and P. Savola, "IPv6 Transition/Co-existence Security Considerations", [RFC 4942](#), DOI 10.17487/RFC4942, September 2007, <<https://www.rfc-editor.org/info/rfc4942>>.



- [RFC5308] Hopps, C., "Routing IPv6 with IS-IS", [RFC 5308](#), DOI 10.17487/RFC5308, October 2008, <<https://www.rfc-editor.org/info/rfc5308>>.
- [RFC5340] Coltun, R., Ferguson, D., Moy, J., and A. Lindem, "OSPF for IPv6", [RFC 5340](#), DOI 10.17487/RFC5340, July 2008, <<https://www.rfc-editor.org/info/rfc5340>>.
- [RFC6438] Carpenter, B. and S. Amante, "Using the IPv6 Flow Label for Equal Cost Multipath Routing and Link Aggregation in Tunnels", [RFC 6438](#), DOI 10.17487/RFC6438, November 2011, <<https://www.rfc-editor.org/info/rfc6438>>.
- [RFC6554] Hui, J., Vasseur, JP., Culler, D., and V. Manral, "An IPv6 Routing Header for Source Routes with the Routing Protocol for Low-Power and Lossy Networks (RPL)", [RFC 6554](#), DOI 10.17487/RFC6554, March 2012, <<https://www.rfc-editor.org/info/rfc6554>>.
- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 8126](#), DOI 10.17487/RFC8126, June 2017, <<https://www.rfc-editor.org/info/rfc8126>>.

#### Authors' Addresses

Stefano Previdi  
Individual  
Italy

Email: stefano@previdi.net

Clarence Filsfils (editor)  
Cisco Systems, Inc.  
Brussels  
BE

Email: cfilsfil@cisco.com

John Leddy  
Comcast  
4100 East Dry Creek Road  
Centennial, CO 80122  
US

Email: John\_Leddy@comcast.com



Satoru Matsushima  
Softbank

Email: [satoru.matsushima@g.softbank.co.jp](mailto:satoru.matsushima@g.softbank.co.jp)

Daniel Voyer (editor)  
Bell Canada

Email: [daniel.voyer@bell.ca](mailto:daniel.voyer@bell.ca)