

IPv6 Maintenance (6man) Working Group
Internet-Draft
Updates: [4861](#), [4862](#) (if approved)
Intended status: Standards Track
Expires: February 27, 2021

F. Gont
SI6 Networks
J. Zorz
6connect
R. Patterson
Sky UK
August 26, 2020

Improving the Robustness of Stateless Address Autoconfiguration (SLAAC)
to Flash Renumbering Events
[draft-ietf-6man-slaac-renum-01](#)

Abstract

In renumbering scenarios where an IPv6 prefix suddenly becomes invalid, hosts on the local network will continue using stale prefixes for an unacceptably long period of time, thus resulting in connectivity problems. This document improves the reaction of IPv6 Stateless Address Autoconfiguration to such renumbering scenarios.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 27, 2021.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Terminology	3
3.	SLAAC reaction to Flash-renumbering Events	4
3.1.	Renumbering without Explicit Signaling	4
3.2.	Renumbering with Explicit Signaling	5
4.	Improvements to Stateless Address Autoconfiguration (SLAAC)	6
4.1.	More Appropriate Lifetime Values	7
4.1.1.	Router Configuration Variables	7
4.1.2.	Processing of PIO Lifetimes at Hosts	7
4.2.	Honor Small PIO Valid Lifetimes	7
4.3.	Interface Initialization	8
4.4.	Conveying Information in Router Advertisement (RA) Messages	8
4.5.	Recovery from Stale Configuration Information without Explicit Signaling	8
5.	IANA Considerations	9
6.	Implementation Status	9
6.1.	More Appropriate Lifetime Values	9
6.1.1.	Router Configuration Variables	9
6.1.2.	Processing of PIO Lifetimes at Hosts	9
6.2.	Honor Small PIO Valid Lifetimes	10
6.2.1.	Linux Kernel	10
6.2.2.	NetworkManager	10
6.3.	Conveying Information in Router Advertisement (RA) Messages	10
6.4.	Recovery from Stale Configuration Information without Explicit Signaling	10
6.4.1.	dhcpcd(8)	10
6.5.	Other mitigations implemented in products	11
7.	Security Considerations	11
8.	Acknowledgments	12
9.	References	12
9.1.	Normative References	12
9.2.	Informative References	13
Appendix A.	Analysis of Some Suggested Workarounds	15
A.1.	On a Possible Reaction to ICMPv6 Error Messages	15

A.2. On a Possible Improvement to Source Address Selection . .	16
Authors' Addresses	18

[1.](#) Introduction

IPv6 network renumbering is expected to take place in a planned manner, with old/stale prefixes being phased-out via reduced prefix lifetimes while new prefixes (with normal lifetimes) are introduced. However, there are a number of scenarios that may lead to the so-called "flash-renumbering" events, where the prefix being employed on a network suddenly becomes invalid and replaced by a new prefix [[I-D.ietf-v6ops-slaac-renum](#)]. In such scenarios, hosts on the local network will continue using stale prefixes for an unacceptably long period of time, thus resulting in connectivity problems. [[I-D.ietf-v6ops-slaac-renum](#)] discusses this problem in detail.

In some scenarios, the local router producing the network renumbering event may try to deprecate the currently-employed prefixes (thus explicitly signaling the network about the renumbering event), whereas in other scenarios it may be unaware about the renumbering event and thus unable signal hosts about it.

From the perspective of a Stateless Address Autoconfiguration (SLAAC) host, there are two different (but related) problems to be solved:

- o Avoiding the use of stale addresses for new communication instances
- o Performing "garbage collection" for the stale prefixes (and related network configuration information)

Clearly, if a host has both working and stale addresses, it is paramount that it employs working addresses for new communication instances. Additionally, a host should also perform garbage collection for the stale prefixes/addresses, since they not only tie system resources, but also prevent communication with the new "owners" of the stale prefixes.

[2.](#) Terminology

The term "globally reachable" is used in this document as defined in [\[RFC8190\]](#).

The term "Global Unicast Address" (or its acronym "GUA") is used throughout this document to refer to "globally reachable" [\[RFC8190\]](#) addresses. That is, when used throughout this document, GUAs do NOT include Unique Local Addresses (ULAs) [\[RFC4193\]](#). Similarly, the term "Global Unicast prefix" (or "GUA prefix") is employed throughout this document to refer to network prefixes that specify GUAs, and does NOT include the ULA prefix (FC00::/7) [\[RFC4193\]](#).

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [\[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

[3.](#) SLAAC reaction to Flash-renumbering Events

As noted in [Section 1](#), in some scenarios the router triggering the renumbering event may be able to explicitly signal the network about this event, while in other scenarios the renumbered hosts may need to infer a renumbering event is taking place. The following subsections analyze specific considerations for each of these scenarios.

[3.1.](#) Renumbering without Explicit Signaling

In the absence of explicit signalling from SLAAC routers (such as sending Prefix Information Options (PIOs) with small lifetimes to deprecate the stale prefixes), stale prefixes will remain preferred and valid according to the Preferred Lifetime and Valid Lifetime values (respectively) of the last received PIO. IPv6 SLAAC employs the following default values for PIOs:

- o Preferred Lifetime (AdvPreferredLifetime): 604800 seconds (7 days)
- o Valid Lifetime (AdvValidLifetime): 2592000 seconds (30 days)

This means that, in the absence of explicit signaling by a SLAAC router to deprecate a prefix, it will take a host 7 days (one week)

to deprecate the corresponding addresses, and 30 days (one month) to eventually remove any addresses configured for the stale prefix. Clearly, for any practical purposes, employing such long default values is the equivalent of not using any timers at all, since taking 7 days or 30 days (respectively) to recover from a network problem is simply unacceptable.

Use of more appropriate timers in Router Advertisement messages can help limit the amount of time that hosts will maintain stale configuration information. Additionally, hosts are normally in a position to infer that a prefix has become stale -- for example, if a given router ceases to advertise an existing prefix and at the same time starts to advertise a new prefix.

[Section 4.1.1](#) recommends the use of more appropriate lifetimes for PIOs, while [Section 4.1.2](#) proposes to cap the accepted Valid Lifetime and Preferred Lifetime values at hosts, such that more appropriate values are employed even in the presence of legacy routers.

[Section 4.5](#) specifies a local policy that SLAAC hosts can implement to heuristically infer that network configuration information has changed, such that stale configuration information can be phased out.

[3.2.](#) Renumbering with Explicit Signaling

In scenarios where a local router is aware about the renumbering event, it may try to phase out the stale network configuration information. In these scenarios, there are two aspects to be considered:

- o The amount of time during which the router should continue trying to deprecate the stale network configuration information
- o The ability of SLAAC hosts to phase out stale configuration in a timelier manner.

In the absence of Router Advertisements (RAs) that include PIOs that would reduce the Valid Lifetime and Preferred Lifetime of a prefix, hosts would normally employ the lifetime values from PIO options of the last received RA messages. Since the network could be partitioned for an arbitrarily long period of time, a router would

need to try to deprecate a prefix for the amount of time employed for the "Preferred Lifetime", and try to invalidate the prefix for the amount of time employed for the "Valid Lifetime" (see [Section 12 of \[RFC4861\]](#)).

NOTE:

Once the number of seconds in the original "Preferred Lifetime" have elapsed, all hosts would have deprecated the corresponding addresses anyway, while once the number of seconds in the "Valid Lifetime" have elapsed, the corresponding addresses would be invalidated and removed.

Thus, use of more appropriate default lifetimes for PIOs, as proposed in [Section 4.1.1](#), would reduce the amount of time a stale prefix would need to be announced as such by a router in order to make sure that it is deprecated/invalidated.

In scenarios where a router has positive knowledge that a prefix has become invalid and thus could signal this condition to local hosts, the current specifications will prevent SLAAC hosts from fully recovering from such stale information. Item "e)" of [Section 5.5.3 of \[RFC4862\]](#) specifies that an RA may never reduce the "RemainingLifetime" to less than two hours. Additionally, if the RemainingLifetime of an address is smaller than 2 hours, then a Valid Lifetime smaller than 2 hours will be ignored. The inability to invalidate a stale prefix would prevent communication with the new

"owners" of the stale prefix, and thus is highly undesirable. On the other hand, the Preferred Lifetime of an address *can* be reduced to any value to avoid the use of a stale prefix for new communications.

[Section 4.2](#) updates [\[RFC4862\]](#) such that this restriction is removed, and hosts react to the advertised "Valid Lifetime" (even if it is smaller than 2 hours).

Finally, [Section 4.3](#) recommends that routers disseminate network configuration information when a network interface is initialized, such that possibly new configuration information propagates in a timelier manner.

[4.](#) Improvements to Stateless Address Autoconfiguration (SLAAC)

The following subsections update [\[RFC4861\]](#) and [\[RFC4862\]](#), such that the problem discussed in this document is mitigated. The aforementioned updates are mostly orthogonal, and mitigate different aspects of SLAAC that prevent a timely reaction to flash renumbering events.

- o Reduce the default Valid Lifetime and Preferred Lifetime of PIOs ([Section 4.1.1](#)):
This helps limit the amount of time a host will employ stale information, and also limits the amount of time a router needs to try to obsolete stale information.
- o Cap the received Valid Lifetime and Preferred Lifetime of PIOs ([Section 4.1.2](#)):
This helps limit the amount of time a host will employ stale information, even in the presence of legacy ([\[RFC4861\]](#)) routers.
- o Honor PIOs with small Valid Lifetimes ([Section 4.2](#)):
This allows routers to invalidate stale prefixes, since otherwise [\[RFC4861\]](#) prevents hosts from honoring PIOs with a Valid Lifetime smaller than two hours.
- o Recommend routers to retransmit configuration information upon interface initialization/reinitialization ([Section 4.3](#)):
This helps spread the new information in a timelier manner, and also deprecate stale information via host-side heuristics (see [Section 4.5](#)).
- o Recommend routers to always send all options (i.e. the complete configuration information) in RA messages, and in the smallest possible number of packets ([Section 4.4](#)):

This helps propagate the same information to all hosts, and also allows hosts to better infer that information missing in RA messages has become stale (see [Section 4.5](#)).

- o Infer stale network configuration information from received RAs ([Section 4.5](#)):
This allows hosts to deprecate stale network configuration information, even in the absence of explicit signaling.

[4.1.](#) More Appropriate Lifetime Values

[4.1.1.](#) Router Configuration Variables

[TBD]

[4.1.2.](#) Processing of PIO Lifetimes at Hosts

[TBD]

[4.2.](#) Honor Small PIO Valid Lifetimes

The entire item "e)" (pp. 19-20) from [Section 5.5.3 of \[RFC4862\]](#) is replaced with the following text:

e) If the advertised prefix is equal to the prefix of an address configured by stateless autoconfiguration in the list, the valid lifetime and the preferred lifetime of the address should be updated by processing the Valid Lifetime and the Preferred Lifetime (respectively) in the received advertisement.

NOTE:

"Processing" the Valid Lifetime and Preferred Lifetime includes capping the received values as specified in [Section 4.1.2](#) of this document.

RATIONALE:

- * This change allows hosts to react to the information provided by a router that has positive knowledge that a prefix has become invalid.
- * The behavior described in [RFC4862](#) had been incorporated during the revision of the original IPv6 Stateless Address Autoconfiguration specification ([\[RFC1971\]](#)). At the time, the IPNG working group decided to mitigate the attack vector represented by Prefix Information Options with very short lifetimes, on the premise these packets represented a bigger risk than other ND-based attack vectors [\[IPNG-minutes\]](#).

decision, we conclude that the drawbacks of mitigating the aforementioned attack vector outweigh the possible benefits.

In scenarios where RA-based attacks are of concern, proper mitigations such as RA-Guard [[RFC6105](#)] [[RFC7113](#)] or SEND [[RFC3971](#)] should be implemented.

[4.3.](#) Interface Initialization

When an interface is initialized, it is paramount that network configuration information is spread on the corresponding network (particularly in scenarios where an interface has been re-initialized, and the conveyed information has changed). Thus, this document replaces the following text from [Section 6.2.4 of \[RFC4861\]](#):

In such cases, the router MAY transmit up to MAX_INITIAL_RTR_ADVERTISEMENTS unsolicited advertisements, using the same rules as when an interface becomes an advertising interface.

with:

In such cases, the router SHOULD transmit MAX_INITIAL_RTR_ADVERTISEMENTS unsolicited advertisements, using the same rules as when an interface becomes an advertising interface.

RATIONALE:

- * Use of stale information can lead to interoperability problems. Therefore, it is important that new configuration information propagates in a timelier manner to all hosts.

NOTE:

[[I-D.ietf-v6ops-cpe-slaac-renum](#)] specifies recommendations for CPE routers to deprecate any stale network configuration information.

[4.4.](#) Conveying Information in Router Advertisement (RA) Messages

[TBD]

[4.5.](#) Recovery from Stale Configuration Information without Explicit Signaling

[TBD]

[5.](#) IANA Considerations

This document has no actions for IANA.

[6.](#) Implementation Status

[NOTE: This section is to be removed by the RFC-Editor before this document is published as an RFC.]

This section summarizes the implementation status of the updates proposed in this document. In some cases, they correspond to variants of the mitigations proposed in this document (e.g., use of reduced default lifetimes for PIOs, albeit using different values than those recommended in this document). In such cases, we believe these implementations signal the intent to deal with the problems described in [[I-D.ietf-v6ops-slaac-renum](#)] while lacking any guidance on the best possible approach to do it.

[6.1.](#) More Appropriate Lifetime Values

[6.1.1.](#) Router Configuration Variables

[6.1.1.1.](#) rad(8)

We have produced a patch for OpenBSD's rad(8) [[rad](#)] that employs the default lifetimes recommended in this document, albeit it has not yet been committed to the tree. The patch is available at:
<<https://www.gont.com.ar/code/fgont-patch-rad-pio-lifetimes.txt>>.

[6.1.1.2.](#) radvd(8)

The radvd(8) daemon [[radvd](#)], normally employed by Linux-based router implementations, currently employs different default lifetimes than those recommended in [[RFC4861](#)]. radvd(8) employs the following default values [[radvd.conf](#)]:

- o Preferred Lifetime: 14400 seconds (4 hours)
- o Valid Lifetime: 86400 seconds (1 day)

This is not following the specific recommendation in this document, but is already a deviation from the current standards.

[6.1.2.](#) Processing of PIO Lifetimes at Hosts

[6.1.2.1.](#) NetworkManager

NetworkManager [[NetworkManager](#)], user-space SLAAC implementation employed by some Linux-based operating systems (such as Fedora or Ubuntu), caps the lifetimes of the received PIOs as recommended in this document.

[6.1.2.2.](#) slaacd(8)

slaacd(8) [[slaacd](#)], a user-space SLAAC implementation employed by OpenBSD, caps the lifetimes of the received PIOs as recommended in this document.

[6.1.2.3.](#) systemd-networkd

systemd-networkd [[systemd](#)], a user-space SLAAC implementation employed by some Linux-based operating systems, caps the lifetimes of the received PIOs as recommended in this document.

[6.2.](#) Honor Small PIO Valid Lifetimes

[6.2.1.](#) Linux Kernel

A Linux kernel implementation of this document has been committed to the net-next tree. The implementation was produced in April 2020 by Fernando Gont <fgont@si6networks.com>. The corresponding patch can be found at: <<https://patchwork.ozlabs.org/project/netdev/patch/20200419122457.GA971@archlinux-current.localdomain/>>

[6.2.2.](#) NetworkManager

NetworkManager [[NetworkManager](#)] processes RA messages with a Valid Lifetime smaller than two hours as recommended in this document.

[6.3.](#) Conveying Information in Router Advertisement (RA) Messages

We know of no implementation that splits network configuration information into multiple RA messages.

[6.4.](#) Recovery from Stale Configuration Information without Explicit Signaling

[6.4.1.](#) dhcpcd(8)

The dhcpcd(8) daemon [[dhcpcd](#)], a user-space SLAAC implementation employed by some Linux-based and BSD-derived operating systems, will set the Preferred Lifetime of addresses corresponding to a given prefix to 0 when a single RA from the router that previously

Gont, et al.

Expires February 27, 2021

[Page 10]

Internet-Draft

Reaction to Renumbering Events

August 2020

advertised the prefix fails to advertise the corresponding prefix. However, it does not affect the corresponding Valid Lifetime. Therefore, it can be considered a partial implementation of this feature.

[6.5.](#) Other mitigations implemented in products

[FRITZ] is a Customer Edge Router that tries to deprecate stale prefixes by advertising stale prefixes with a Preferred Lifetime of 0, and a Valid Lifetime of 2 hours (or less). There are two things to note with respect to this implementation:

- o Rather than recording prefixes on stable storage (as recommended in [[I-D.ietf-v6ops-cpe-slaac-renum](#)]), this implementation checks the source address of IPv6 packets, and assumes that usage of any address that does not correspond to a prefix currently-advertised by the Customer Edge Router is the result of stale network configuration information. Hence, upon receipt of a packet that employs a source address that does not correspond to a currently-advertised prefix, this implementation will start advertising the corresponding prefix with small lifetimes, with the intent of deprecating it.
- o Possibly as a result of item "e)" (pp. 19-20) from [Section 5.5.3 of \[RFC4862\]](#) (discussed in [Section 4.2](#) of this document), upon first occurrence of a stale prefix, this implementation will employ a decreasing Valid Lifetime, starting from 2 hours (7200 seconds), as opposed to a Valid Lifetime of 0.

[7.](#) Security Considerations

The protocol update in [Section 4.2](#) could allow an on-link attacker to

perform a Denial of Service attack againsts local hosts, by sending a forged RA with a PIO with a Valid Lifetime of 0. Upon receipt of that packet, local hosts would invalidate the corresponding prefix, and therefore remove any addresses configured for that prefix, possibly terminating e.g. TCP connections employing such addresses. However, an attacker may achieve similar effects via a number for ND-based attack vectors, such as directing traffic to a non-existing node until ongoing TCP connections time out, or performing a ND-based man-in-the-middle (MITM) attack and subsequently forging TCP RST segments to cause on-going TCP connections to be aborted. Thus, for all practical purposes, this attack vector does not really represent a greater risk than other ND attack vectors. As noted in [Section 4.2](#), in scenarios where RA-based attacks are of concern, proper mitigations such as RA-Guard [[RFC6105](#)] [[RFC7113](#)] or SEND [[RFC3971](#)] should be implemented.

[8.](#) Acknowledgments

The authors would like to thank (in alphabetical order) Mikael Abrahamsson, Tore Anderson, Luis Balbinot, Brian Carpenter, Lorenzo Colitti, Owen DeLong, Gert Doering, Thomas Haller, Nick Hilliard, Bob Hinden, Philip Homburg, Lee Howard, Christian Huitema, Tatuya Jinmei, Erik Kline, Ted Lemon, Jen Linkova, Albert Manfredi, Roy Marples, Florian Obser, Jordi Palet Martinez, Michael Richardson, Hiroki Sato, Mark Smith, Hannes Frederic Sowa, Dave Thaler, Tarko Tikan, Ole Troan, Eduard Vasilenko, and Loganaden Velvindron, for providing valuable comments on earlier versions of this document.

The algorithm specified in [Section 4.5](#) is the result of mailing-list discussions over previous versions of this document with Philip Homburg.

Fernando would like to thank Alejandro D'Egidio and Sander Steffann for a discussion of these issues, which led to the publication of [[I-D.ietf-v6ops-slaac-renum](#)], and eventually to this document.

Fernando would also like to thank Brian Carpenter who, over the years, has answered many questions and provided valuable comments that has benefited his protocol-related work.

The problem discussed in this document has been previously documented

by Jen Linkova in [[I-D.linkova-6man-default-addr-selection-update](#)], and also in [[RIPE-690](#)].

[9.](#) References

[9.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC4193] Hinden, R. and B. Haberman, "Unique Local IPv6 Unicast Addresses", [RFC 4193](#), DOI 10.17487/RFC4193, October 2005, <<https://www.rfc-editor.org/info/rfc4193>>.
- [RFC4861] Narten, T., Nordmark, E., Simpson, W., and H. Soliman, "Neighbor Discovery for IP version 6 (IPv6)", [RFC 4861](#), DOI 10.17487/RFC4861, September 2007, <<https://www.rfc-editor.org/info/rfc4861>>.

Gont, et al.

Expires February 27, 2021

[Page 12]

Internet-Draft

Reaction to Renumbering Events

August 2020

- [RFC4862] Thomson, S., Narten, T., and T. Jinmei, "IPv6 Stateless Address Autoconfiguration", [RFC 4862](#), DOI 10.17487/RFC4862, September 2007, <<https://www.rfc-editor.org/info/rfc4862>>.
- [RFC8028] Baker, F. and B. Carpenter, "First-Hop Router Selection by Hosts in a Multi-Prefix Network", [RFC 8028](#), DOI 10.17487/RFC8028, November 2016, <<https://www.rfc-editor.org/info/rfc8028>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8190] Bonica, R., Cotton, M., Haberman, B., and L. Vegoda, "Updates to the Special-Purpose IP Address Registries", [BCP 153](#), [RFC 8190](#), DOI 10.17487/RFC8190, June 2017, <<https://www.rfc-editor.org/info/rfc8190>>.

[RFC8504] Chown, T., Loughney, J., and T. Winters, "IPv6 Node Requirements", [BCP 220](#), [RFC 8504](#), DOI 10.17487/RFC8504, January 2019, <<https://www.rfc-editor.org/info/rfc8504>>.

9.2. Informative References

[dhcpcd] Marples, R., "dhcpcd - a DHCP client", <<https://roy.marples.name/projects/dhcpcd/>>.

[FRITZ] Gont, F., "Quiz: Weird IPv6 Traffic on the Local Network (updated with solution)", SI6 Networks Blog, February 2016, <<https://www.si6networks.com/2016/02/16/quiz-weird-ipv6-traffic-on-the-local-network-updated-with-solution/>>.

[I-D.ietf-v6ops-cpe-slaac-renum]
Gont, F., Zorz, J., Patterson, R., and B. Volz, "Improving the Reaction of Customer Edge Routers to Renumbering Events", [draft-ietf-v6ops-cpe-slaac-renum-04](#) (work in progress), August 2020.

[I-D.ietf-v6ops-slaac-renum]
Gont, F., Zorz, J., and R. Patterson, "Reaction of Stateless Address Autoconfiguration (SLAAC) to Flash-Renumbering Events", [draft-ietf-v6ops-slaac-renum-03](#) (work in progress), August 2020.

Gont, et al. Expires February 27, 2021 [Page 13]

Internet-Draft Reaction to Renumbering Events August 2020

[I-D.linkova-6man-default-addr-selection-update]
Linkova, J., "Default Address Selection and Subnet Renumbering", [draft-linkova-6man-default-addr-selection-update-00](#) (work in progress), March 2017.

[IPNG-minutes]
IETF, "IPNG working group (ipngwg) Meeting Minutes", Proceedings of the thirty-eightth Internet Engineering Task Force , April 1997, <<https://www.ietf.org/proceedings/38/97apr-final/xrtftr47.htm>>.

- [NetworkManager] NetworkManager, "NetworkManager web site", <<https://wiki.gnome.org/Projects/NetworkManager>>.
- [rad] Obser, F., "OpenBSD Router Advertisement Daemon - rad(8)", <<https://cvsweb.openbsd.org/src/usr.sbin/rad/>>.
- [radvd] Hawkins, R. and R. Johnson, "Linux IPv6 Router Advertisement Daemon (radvd)", <<http://www.litech.org/radvd/>>.
- [radvd.conf] Hawkins, R. and R. Johnson, "radvd.conf - configuration file of the router advertisement daemon", <<https://github.com/reubenhwk/radvd/blob/master/radvd.conf.5.man>>.
- [RFC1971] Thomson, S. and T. Narten, "IPv6 Stateless Address Autoconfiguration", [RFC 1971](#), DOI 10.17487/RFC1971, August 1996, <<https://www.rfc-editor.org/info/rfc1971>>.
- [RFC2827] Ferguson, P. and D. Senie, "Network Ingress Filtering: Defeating Denial of Service Attacks which employ IP Source Address Spoofing", [BCP 38](#), [RFC 2827](#), DOI 10.17487/RFC2827, May 2000, <<https://www.rfc-editor.org/info/rfc2827>>.
- [RFC3971] Arkko, J., Ed., Kempf, J., Zill, B., and P. Nikander, "SEcure Neighbor Discovery (SEND)", [RFC 3971](#), DOI 10.17487/RFC3971, March 2005, <<https://www.rfc-editor.org/info/rfc3971>>.
- [RFC5927] Gont, F., "ICMP Attacks against TCP", [RFC 5927](#), DOI 10.17487/RFC5927, July 2010, <<https://www.rfc-editor.org/info/rfc5927>>.

- [RFC6105] Levy-Abegnoli, E., Van de Velde, G., Popoviciu, C., and J. Mohacsi, "IPv6 Router Advertisement Guard", [RFC 6105](#), DOI 10.17487/RFC6105, February 2011, <<https://www.rfc-editor.org/info/rfc6105>>.

- [RFC6724] Thaler, D., Ed., Draves, R., Matsumoto, A., and T. Chown, "Default Address Selection for Internet Protocol Version 6 (IPv6)", [RFC 6724](#), DOI 10.17487/RFC6724, September 2012, <<https://www.rfc-editor.org/info/rfc6724>>.
- [RFC7113] Gont, F., "Implementation Advice for IPv6 Router Advertisement Guard (RA-Guard)", [RFC 7113](#), DOI 10.17487/RFC7113, February 2014, <<https://www.rfc-editor.org/info/rfc7113>>.
- [RIPE-690] Zorz, J., Zorz, S., Drazumeric, P., Townsley, M., Alston, J., Doering, G., Palet, J., Linkova, J., Balbinot, L., Meynell, K., and L. Howard, "Best Current Operational Practice for Operators: IPv6 prefix assignment for end-users - persistent vs non-persistent, and what size to choose", RIPE 690, October 2017, <<https://www.ripe.net/publications/docs/ripe-690>>.
- [slaacd] Obser, F., "OpenBSD SLAAC Daemon - slaacd(8)", <<https://cvsweb.openbsd.org/src/usr.sbin/slaacd/>>.
- [systemd] systemd, "systemd web site", <<https://systemd.io/>>.

[Appendix A](#). Analysis of Some Suggested Workarounds

[This section is to be removed before publication of this document as an RFC].

During the discussion of this document, some alternative workarounds were suggested on the 6man mailing-list. The following subsections analyze these suggested workarounds, in the hopes of avoiding rehashing the same discussions.

[A.1](#). On a Possible Reaction to ICMPv6 Error Messages

It has been suggested that if configured addresses become stale, a CPE enforcing ingress/egress filtering ([BCP38](#)) ([RFC2827](#)) could send ICMPv6 Type 1 (Destination Unreachable) Code 5 (Source address failed ingress/egress policy) error messages to the sending node, and that, upon receipt of such error messages, the sending node could perform heuristics that might help to mitigate the problem discussed in this document.

The aforementioned proposal has a number of drawbacks and limitations:

- o It assumes that the CPE routers enforce ingress/egress filtering [[RFC2827](#)]. While this is desirable behaviour, it cannot be relied upon.
- o It assumes that if the CPE enforces ingress/egress filtering, the CPE will signal the packet drops to the sending node with ICMPv6 Type 1 (Destination Unreachable) Code 5 (Source address failed ingress/egress policy) error messages. While this may be desirable, [[RFC2827](#)] does not suggest signaling the packet drops with ICMPv6 error messages, let alone the use of specific error messages (such as Type 1 Code 5) as suggested.
- o ICMPv6 Type 1 Code 5 could be interpreted as the employed address being stale, but also as a selected route being inappropriate/suboptimal. If the later, deprecating addresses or invalidating addresses upon receipt of these error messages would be inappropriate.
- o Reacting to these error messages would create a new attack vector that could be exploited from remote networks. This is of particular concern since ICMP-based attacks do not even require that the Source Address of the attack packets be spoofed [[RFC5927](#)].

[A.2.](#) On a Possible Improvement to Source Address Selection

[RFC6724] specifies source address selection (SAS) for IPv6. Conceptually, it sorts the candidate set of source addresses for a given destination, based on a number of pair-wise comparison rules that must be successively applied until there is a "winning" address.

An implementation might improve source address selection, and prefer the most-recently advertised information. In order to incorporate the "freshness" of information in source address selection, an implementation would be updated as follows:

- o The node is assumed to maintain a timer/counter that is updated at least once per second. For example, the time(2) function from unix-like systems could be employed for this purpose.
- o The local information associated with each prefix advertised via RAs on the local network is augmented with a "LastAdvertised" timestamp value. Whenever an RA with a PIO with the "A" bit set for such prefix is received, the "LastAdvertised" timestamp is

updated with the current value of the timer/counter.

- o [\[RFC6724\]](#) is updated such that this rule is incorporated:

Rule 7.5: Prefer fresh information If one of the two source addresses corresponds to a prefix that has been more recently advertised, say $\text{LastAdvertised}(\text{SA}) > \text{LastAdvertised}(\text{SA})$, then prefer that address (SA in our case).

A clear benefit of this approach is that a host will normally prefer "fresh" addresses over possibly stale addresses.

However, there are a number of drawbacks associated with this approach:

- o In scenarios where multiple prefixes are being advertised on the same LAN segment, the new SAS rule is **guaranteed** to result in non-deterministic behaviour, with hosts frequently changing the default source address. This is certainly not desirable from a troubleshooting perspective.
- o Since the rule must be incorporated before "Rule 8: Use longest matching prefix" from [\[RFC6724\]](#), it may lead to suboptimal paths.
- o This new rule may help to improve the selection of a source address, but it does not help with the housekeeping (garbage collection) of configured information:
 - * If the stale prefix is re-used in another network, nodes employing stale addresses and routes for this prefix will be unable to communicate with the new "owner" of the prefix, since the stale prefix will most likely be considered "on-link".
 - * Given that the currently recommended default value for the "Valid Lifetime" of PIOs is 2592000 seconds (30 days), it would take too long for hosts to remove the configured addresses and routes for the stale prefix. While the proposed update in [Section 4.1](#) of this document would mitigate this problem, the lifetimes advertised by the local SLAAC router are not under the control of hosts.

As a result, updating IPv6 source address selection does not relieve

nodes from improving their SLAAC implementations as specified in [Section 4](#), if at all desirable. On the other hand, the algorithm specified in [Section 4.5](#) would result in Rule 3 of [[RFC6724](#)] employing fresh addresses, without leading to non-deterministic behaviour.

Gont, et al.

Expires February 27, 2021

[Page 17]

Internet-Draft

Reaction to Renumbering Events

August 2020

Authors' Addresses

Fernando Gont
SI6 Networks
Segurola y Habana 4310, 7mo Piso
Villa Devoto, Ciudad Autonoma de Buenos Aires
Argentina

Email: fgont@si6networks.com
URI: <https://www.si6networks.com>

Jan Zorz
6connect

Email: jan@connect.com

Richard Patterson
Sky UK

Email: richard.patterson@sky.uk

