

6TiSCH  
Internet-Draft  
Intended status: Standards Track  
Expires: December 17, 2015

X. Vilajosana, Ed.  
Universitat Oberta de Catalunya  
K. Pister  
University of California Berkeley  
June 15, 2015

**Minimal 6TiSCH Configuration**  
**draft-ietf-6tisch-minimal-09**

Abstract

This document describes the minimal set of rules to operate an IEEE 802.15.4 Timeslotted Channel Hopping (TSCH) network. This minimal mode of operation can be used during network bootstrap, as a fall-back mode of operation when no dynamic scheduling solution is available or functioning, or during early interoperability testing and development.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 17, 2015.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">2</a>
<a href="#">2.</a>	<a href="#">Requirements Language</a>	<a href="#">3</a>
<a href="#">3.</a>	<a href="#">Minimal Schedule Configuration</a>	<a href="#">3</a>
<a href="#">3.1.</a>	<a href="#">Slotframe</a>	<a href="#">3</a>
<a href="#">3.2.</a>	<a href="#">Cell Options</a>	<a href="#">5</a>
<a href="#">3.3.</a>	<a href="#">Retransmissions</a>	<a href="#">6</a>
<a href="#">3.4.</a>	<a href="#">Time Slot timing</a>	<a href="#">6</a>
<a href="#">4.</a>	<a href="#">Enhanced Beacons Configuration and Content</a>	<a href="#">7</a>
<a href="#">5.</a>	<a href="#">Acknowledgment</a>	<a href="#">8</a>
<a href="#">6.</a>	<a href="#">Neighbor information</a>	<a href="#">9</a>
<a href="#">6.1.</a>	<a href="#">Neighbor Table</a>	<a href="#">9</a>
<a href="#">6.2.</a>	<a href="#">Time Source Neighbor Selection</a>	<a href="#">9</a>
<a href="#">7.</a>	<a href="#">Queues and Priorities</a>	<a href="#">10</a>
<a href="#">8.</a>	<a href="#">Security</a>	<a href="#">11</a>
<a href="#">9.</a>	<a href="#">RPL on TSCH</a>	<a href="#">11</a>
<a href="#">9.1.</a>	<a href="#">RPL Objective Function Zero</a>	<a href="#">11</a>
<a href="#">9.1.1.</a>	<a href="#">Rank computation</a>	<a href="#">11</a>
<a href="#">9.1.2.</a>	<a href="#">Rank computation Example</a>	<a href="#">13</a>
<a href="#">9.2.</a>	<a href="#">RPL Configuration</a>	<a href="#">14</a>
<a href="#">9.2.1.</a>	<a href="#">Mode of Operation</a>	<a href="#">15</a>
<a href="#">9.2.2.</a>	<a href="#">Trickle Timer</a>	<a href="#">15</a>
<a href="#">9.2.3.</a>	<a href="#">Hysteresis</a>	<a href="#">15</a>
<a href="#">9.2.4.</a>	<a href="#">Variable Values</a>	<a href="#">15</a>
<a href="#">10.</a>	<a href="#">Examples</a>	<a href="#">16</a>
<a href="#">10.1.</a>	<a href="#">Example 1. Information Elements in EBs</a>	<a href="#">16</a>
10.2.	<a href="#">Example 2. Information Elements in EBs not using default timeslot template</a>	<a href="#">18</a>
<a href="#">10.3.</a>	<a href="#">Example 3. Information Elements in ACKs</a>	<a href="#">20</a>
<a href="#">10.4.</a>	<a href="#">Example 4. Auxiliary Security Header</a>	<a href="#">21</a>
<a href="#">11.</a>	<a href="#">IANA Considerations</a>	<a href="#">22</a>
<a href="#">12.</a>	<a href="#">Acknowledgments</a>	<a href="#">22</a>
<a href="#">13.</a>	<a href="#">References</a>	<a href="#">22</a>
<a href="#">13.1.</a>	<a href="#">Normative References</a>	<a href="#">22</a>
<a href="#">13.2.</a>	<a href="#">Informative References</a>	<a href="#">24</a>
<a href="#">13.3.</a>	<a href="#">External Informative References</a>	<a href="#">24</a>
	<a href="#">Authors' Addresses</a>	<a href="#">25</a>

## [1. Introduction](#)

The nodes in a IEEE 802.15.4 TSCH network follow a communication schedule. The entity (centralized or decentralized) responsible for building and maintaining that schedule has precise control over the trade-off between the network's latency, bandwidth, reliability and



power consumption. During early interoperability testing and development, however, simplicity is more important than efficiency. One goal of this document is to define the simplest set of rules for building a TSCH-compliant network, at the necessary price of lesser efficiency. Yet, this minimal mode of operation MAY also be used during network bootstrap before any schedule is installed into the network so nodes can self-organize and the management and configuration information be distributed. In addition, the minimal configuration MAY be used as a fall-back mode of operation, ensuring connectivity of nodes in case that dynamic scheduling mechanisms fail or are not available. [IEEE802154] provides a mechanism whereby the details of slotframe length, timeslot timing, and channel hopping pattern are communicated when a node synchronizes to the network. This document describes specific settings for these parameters. Nodes MUST broadcast properly-formed Enhanced Beacons to announce these values.

## **2. Requirements Language**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

## **3. Minimal Schedule Configuration**

In order to form a network, a minimum schedule configuration is required so nodes can advertise the presence of the network, and allow other nodes to join.

### **3.1. Slotframe**

The slotframe, as defined in [I-D.ietf-6tisch-terminology], is an abstraction of the link layer that defines a collection of time slots of equal length, and which repeats over time. In order to set up a minimal TSCH network, nodes need to be synchronized with the same slotframe configuration so they can communicate. This document recommends the following slotframe configuration.



## Minimal configuration

Property	Value
Number of time slots per Slotframe	Variable
Number of available frequencies	16
Number of scheduled cells	1 (slotOffset 0) (macLinkType NORMAL)
Number of unscheduled cells	The remainder of the slotframe
Number of MAC retransmissions (max)	3 (4 transmission attempts)

The slotframe is composed of a configurable number of time slots. Choosing the number of time slots per slotframe needs to take into account network requirements such as density, bandwidth per node, etc. In the minimal configuration, there is only a single active slot in slotframe, used to transmit/receive both EBs and data link-layer frames. The trade-off between bandwidth, latency and energy consumption can be controlled by choosing a different slotframe length. The active slot MAY be scheduled at the slotOffset 0x00 and channelOffset 0x00 and MUST be announced in the EBs. EBs are sent using this active slot to the link-layer broadcast address (and are therefore not acknowledged). Data packets, as described in [Section 3.2](#), use the same active slot. Per [\[IEEE802154\]](#), data packets sent unicast on this cell are acknowledged by the receiver. The remaining cells in the slotframe are unscheduled, and MAY be used by dynamic scheduling solutions. Details about such dynamic scheduling solution are out of scope of this document.

The slotframe length (expressed in number of time slots) is configurable. The length used determines the duty cycle of the network. For example, a network with a 0.99% duty cycle is composed of a slotframe of 101 slots, which includes 1 active slot. The present document RECOMMENDS the use of a default slot duration set to 10ms and its corresponding default timeslot timings defined by the [\[IEEE802154\]](#) macTimeslotTemplate. The use of the default macTimeslotTemplate MUST be announced in the EB by using the Timeslot IE containing only the default macTimeslotTemplateId. Other time slot durations MAY be supported and MUST be announced in the EBs. If one uses a timeslot duration different than 10ms, EBs MUST contain the complete TimeSlot IE as described in [Section 3.4](#). This document



also recommends to clearly indicate nodes not supporting the default timeslot value.

Example schedule with 0.99% duty cycle

Chan.	+-----+-----+				+-----+		
Off.0		TxRxS/EB		OFF		OFF	
Chan.	+-----+-----+				+-----+		
Off.1				...			
	+-----+-----+				+-----+		
	.						
	.						
	.						
Chan.	+-----+-----+				+-----+		
Off.15							
	+-----+-----+				+-----+		
slotOffset	0		1			100	

EB: Enhanced Beacon

Tx: Transmit

Rx: Receive

S: Shared

OFF: Unscheduled (MAY be used by a dynamic scheduling mechanism)

### 3.2. Cell Options

Per [IEEE802154] TSCH, each scheduled cell has an associated bitmap of cell options, called LinkOptions. The scheduled cell in the minimal schedule is configured as a Hard cell [RFC7554][I-D.ietf-6tisch-6top-interface]. Additional available cells MAY be scheduled by a dynamic scheduling solution. The dynamic scheduling solution is out of scope, and this specification does not make any restriction on the LinkOption associated with those dynamically scheduled cells (i.e. they can be hard cells or soft cells).

The active cell is assigned the bitmap of cell options below. Because both the "Transmit" and "Receive" bits are set, a node transmits if there is a packet in its queue, listens otherwise. Because the "shared" bit is set, the back-off mechanism defined in [IEEE802154] is used to resolve contention when transmitting. This results in "Slotted Aloha" behavior. The "Timekeeping" flag is never set, since the time source neighbor is selected using the DODAG structure of the network (detailed below).

b0 = Transmit = 1 (set)





b1 = Receive = 1 (set)

b2 = Shared = 1 (set)

b3 = Timekeeping = 0 (clear)

b4-b7 = Reserved (clear)

All remaining cells are unscheduled. In unscheduled cells, the nodes SHOULD keep their radio off. In a memory-efficient implementation, scheduled cells can be represented by a circular linked list. Unscheduled cells SHOULD NOT occupy any memory.

### **3.3. Retransmissions**


The maximum number of link layer retransmissions is set to 3. For packets which require an acknowledgment, if none is received after a total of 4 attempts, the transmission is considered failed and the link layer MUST notify the upper layer. Packets sent to the broadcast MAC address (including EBs) are not acknowledged and therefore not retransmitted.

### **3.4. Time Slot timing**

The figure below shows an active timeslot in which a packet is sent from the transmitter node (TX) to the receiver node (RX). A link-layer acknowledgment is sent by the RX node to the TX node when the packet is to be acknowledged. The TsTxOffset duration defines the instant in the timeslot when the first bit after the Start of Frame Delimiter (SFD) of the transmitted packet leaves the radio of the TX node. The radio of the RX node is turned on tsRxWait/2 before that instant, and listens for at least tsRxWait. This allows for a de-synchronization between the two nodes of at most tsRxWait/2 in either direction (early or late). The RX node needs to send the first bit after the SFD of the MAC acknowledgment exactly TsTxAckDelay after the end of the last byte of the received packet. TX's radio has to be turned on tsAckWait/2 before that time, and keep listening for at least tsAckWait. The TX node can perform a Clear Channel Assessment (CCA) if required, this does not interfere with the scope of this draft. As for a minimal configuration, CCA is OPTIONAL.



Time slot internal timing diagram



The timing parameters for the default `macTimeslotTemplate` (`macTimeslotTemplateId = 0`) MUST be used when utilizing the default time slot duration. In this case, the Timeslot IE only transports the `macTimeslotTemplateId` with value `0x00`. If a timeslot template other than the default is used, the EB MUST contain a complete `TimeSlot` IE indicating the timeslot duration and the corresponding timeslot timings. Note however that in case of discrepancy between the values in this document and [IEEE802154], the IEEE standard has precedence.

#### 4. Enhanced Beacons Configuration and Content

[IEEE802154] does not define how often EBs are sent, nor their contents. EBs MUST NOT in general be used for synchronization. Synchronization is achieved via acknowledgements to normal packet traffic, and keepalives. For a minimal TSCH configuration, a mote SHOULD send an EB every `EB_PERIOD`. For additional reference see [RFC7554] where different synchronization approaches are summarized. EBs are only authenticated and neither Payload IEs nor the frame payload are encrypted. Refer to the 6TiSCH architecture document [I-D.ietf-6tisch-architecture] for further details on security aspects.



EBs MUST be sent as per [[IEEE802154](#)] and MUST carry the Information Elements (IEs) listed below. Refer to [Section 10.1](#) for an example of the Information Elements Header Content.

Synchronization IE: Contains synchronization information such as ASN and Join Priority. The value of Join Priority is discussed in [Section 6.2](#).

TSCH Timeslot IE: Contains the timeslot template identifier. This specification uses the default timeslot template as defined in [[IEEE802154](#)]. In the case that a non-default timeslot template is used, the IE Content MUST follow the specification as defined in [[IEEE802154](#)]. Refer to [Section 10.1](#) for an illustrative example of non default timeslot template.

Channel Hopping IE: Contains the channel hopping template identifier. This specification uses the default channel hopping template, as defined in [[IEEE802154](#)]. The default sequence for the 2.4GHz OQPSK PHY is [5, 6, 12, 7, 15, 4, 14, 11, 8, 0, 1, 2, 13, 3, 9, 10] [[IEEE802154](#)]. Note however that in case of discrepancy between the values in this document and [[IEEE802154](#)], the IEEE standard specification has preference.

Frame and Link IE: Each node MUST indicate the schedule in each EB through a Frame and Link IE. This enables nodes which implement [[IEEE802154](#)] to learn the schedule used in the network as they join it. This draft defines the use of a single cell set at channel offset 0x00, slot offset 0x00 and with linkOption 0xE0 (TX, RX, SHARED bits set).

## **5. Acknowledgment**

Link-layer acknowledgment frames are built according to [[IEEE802154](#)]. Unicast frames sent to a unicast MAC destination address request an acknowledgment. The sender node MUST set the ACK requested bit in the MAC header. The acknowledgment frame is of type ACK (version 0x10). Each acknowledgment contains the following IE:

ACK/NACK Time Correction IE: The ACK/NACK time correction IE carries the measured de-synchronization between the sender and the receiver. Refer to [Section 10.3](#) for an example of the Header IE content. The possible values for the Time Synchronization Information and ACK status are described in [[IEEE802154](#)].



## **6. Neighbor information**

[IEEE802154] does not define how and when each node in the network keeps information about its neighbors. Keeping the following information in the neighbor table is RECOMMENDED:

### **6.1. Neighbor Table**

The exact format of the neighbor table is implementation-specific, but it SHOULD contain the following information for each neighbor:

Neighbor statistics:

numTx: number of transmitted packets to that neighbor

numTxAck: number of transmitted packets that have been acknowledged by that neighbor

numRx: number of received packets from that neighbor

The EUI64 of the neighbor.

Timestamp of the last frame received from that neighbor. This can be based on the ASN counter or any other time base. It can be used to trigger a keep-alive message.

RPL rank of that neighbor.

A flag indicating whether this neighbor is a time source neighbor.

Connectivity statistics (e.g., RSSI), which can be used to determine the quality of the link.

In addition to that information, each node has to be able to compute some RPL Objective Function (OF), taking into account the neighbor and connectivity statistics. An example RPL objective function is the OF Zero as described in [[RFC6552](#)] and [Section 9.1.1](#).

### **6.2. Time Source Neighbor Selection**

Each node MUST select at least one Time Source Neighbor among the nodes in its RPL routing parent set. When a node joins a network, it has no routing information. To select its time source neighbor, it uses the Join Priority field in the EB, as described in [[IEEE802154](#)]. The Sync IE contains the ASN and 1 Byte field named Join Priority. The Join Priority of any node MUST be equivalent to the result of the function DAGRank(rank) as defined by [[RFC6550](#)] and [Section 9.1.1](#). The Join Priority of the DAG root is zero, i.e., EBs sent from the





DAG root are sent with Join Priority equal to 0. A lower value of the Join Priority indicates higher preference to connect to that device. When a node joins the network, it MUST NOT send EBs before having acquired a RPL rank. This avoids routing loops and matches RPL topology with underlying mesh topology. As soon as a node acquires a RPL rank (see [[RFC6550](#)] and [Section 9.1.1](#)), it SHOULD send Enhanced Beacons including a Sync IE with Join Priority field set to DAGRank(rank), where rank is the node's rank. If a node receives EBs from different nodes with equal Join Priority, the time source neighbor selection SHOULD be assessed by other metrics that can help determine the better connectivity link. Time source neighbor hysteresis SHOULD be used, according to the rules defined in [Section 9.2.3](#). If connectivity to the time source neighbor is lost, a new time source neighbor MUST be chosen among the neighbors in the RPL routing parent set.

The decision for a node to select one Time Source Neighbor when multiple EBs are received is implementation-specific.

For example, a node MAY wait until one EB from NUM\_NEIGHBOURS\_TO\_WAIT neighbors have been received to select the best Time Source Neighbor. This condition MAY apply unless a second EB is not received after MAX\_EB\_DELAY seconds. This avoids initial hysteresis when selecting a first Time Source Neighbor.

Optionally, some form of hysteresis SHOULD be implemented to avoid frequent changes in time source neighbors.

## **7. Queues and Priorities**

[IEEE802154] does not define the use of queues to handle upper layer data (either application or control data from upper layers). The use of a single queue with the following rules is RECOMMENDED:

When the node is not synchronized to the network, higher layers are not able to insert packets into the queue.

Frames generated by the MAC layer (e.g., EBs and ACK) have a higher queuing priority than packets received from a higher layer.

Frame types Beacon and Command have a higher queuing priority than frame types Data and ACK.

One entry in the queue is reserved at all times for frames of types Beacon or Command frames.



## 8. Security

As this document refers to the interaction between Layer 3 and Layer 2 protocols, this interaction MUST be secured by L2 security mechanisms as defined by [\[IEEE802154\]](#). Two security mechanisms are considered, authentication and encryption, authentication applies to all packet content while encryption applies to header IEs and MAC payload. Key distribution is out of scope of this document, but examples include pre-configured keys at the nodes, shared keys among peers or well-known keys. Refer to the 6TiSCH architecture document [\[I-D.ietf-6tisch-architecture\]](#) for further details on key distribution and advanced security aspects.

The present document assumes the existence of two cryptographic keys, which can be pre-configured. One of the keys (K1) is used to authenticate EBs. As defined in [Section 4](#), EBs MUST be authenticated, with no payload encryption. This facilitates logical segregation of distinct networks. A second key (K2) is used to authenticate DATA, ACKNOWLEDGEMENT, MAC COMMAND frame types and respective header IEs, with payload encryption. Depending on security policy, these keys could be the same (i.e., K1=K2).

For early interoperability, K1 MAY be set to 36 54 69 53 43 48 20 6D 69 6E 69 6D 61 6C 31 35 ("6TiSCH minimal15").

## 9. RPL on TSCH

Nodes in the network MUST use the RPL routing protocol [\[RFC6550\]](#).

### 9.1. RPL Objective Function Zero

Nodes in the network MUST use the RPL routing protocol [\[RFC6550\]](#) and implement the RPL Objective Function Zero [\[RFC6552\]](#).

#### 9.1.1. Rank computation

The rank computation is described at [\[RFC6552\], Section 4.1](#). A node rank is computed by the following equation:

$$R(N) = R(P) + \text{rank\_increment}$$

$$\text{rank\_increment} = (R_f * S_p + S_r) * \text{MinHopRankIncrease}$$

Where:

R(N): Rank of the node.

R(P): Rank of the parent obtained as part of the DIO information.



**rank\_increment:** The result of a function that determines the rank increment.

**Rf (rank\_factor):** A configurable factor that is used to multiply the effect of the link properties in the rank\_increment computation. If none is configured, rank\_factor of 1 is used. In this specification, a rank\_factor of 1 MUST be used.

**Sp (step\_of\_rank):** (strictly positive integer) - an intermediate computation based on the link properties with a certain neighbor, i.e., the Expected Transmission Count (ETX) which provides an average of number of packet transmissions between two nodes. ETX is defined in detail by [\[decouto03high\]](#) and [\[RFC6551\]](#). The ETX is computed as the inverse of the Packet Delivery Ratio (PDR), this is the number of transmitted packets, divided by the number of acknowledged packets to a certain node (e.g.,  $ETX = \text{numTX} / \text{numTXAck}$ ). According to this specification, Sp MUST be set to  $2 * ETX$ , for the reason of preferring shorter routes.

**Sr (stretch\_of\_rank):** (unsigned integer) - the maximum increment to the step\_of\_rank of a preferred parent, to allow the selection of an additional feasible successor. If none is configured to the device, then the step\_of\_rank is not stretched. In this specification, stretch\_of\_rank MUST be set to 0.

**MinHopRankIncrease:** the MinHopRankIncrease is set to the fixed constant DEFAULT\_MIN\_HOP\_rank\_increment [\[RFC6550\]](#). DEFAULT\_MIN\_HOP\_rank\_increment has a value of 256.

**DAGRank(rank):** Equivalent to the floor of  $(Rf * Sp + Sr)$  as defined by [\[RFC6550\]](#). Specifically, when an Objective Function computes Rank, this is defined as an unsigned integer (i.e., a 16-bit value) Rank quantity. When the Rank is compared, e.g. to determine parent relationships or loop detection, the integer portion of the Rank is used. The integer portion of the Rank is computed by the DAGRank() macro as  $\text{floor}(x)$  where  $\text{floor}(x)$  is the function that evaluates to the greatest integer less than or equal to  $x$ .  $\text{DAGRank}(\text{rank}) = \text{floor}(\text{rank} / \text{MinHopRankIncrease})$



## Rank computation scenario

```

+-----+
|   P   | R(P)
|       |
+-----+
      |
      |
+-----+
|   N   | R(N)=R(P) + rank_increment
|       | rank_increment = (Rf*Sp + Sr) * MinHopRankIncrease
+-----+ Sp=2*ETX

```

**9.1.2. Rank computation Example**

This section illustrates with an example the use of the Objective Function Zero. Assume the following parameters:

$R_f = 1$

$S_p = 2 * ETX$

$S_r = 0$

$minHopRankIncrease = 256$  (default in RPL)

$ETX = (numTX / numTXAck)$

$r(n) = r(p) + rank\_increment$

$rank\_increment = (R_f * S_p + S_r) * minHopRankIncrease$

$rank\_increment = 512 * numTx / numTxAck$





Rank computation example for 5 hop network where numTx=100 and numTxAck=75 for all nodes

```

+-----+
|  0  | R(minHopRankIncrease) = 256
|      | DAGRank(R(0)) = 1
+-----+
|      |
|      |
+-----+
|  1  | R(1)=R(0) + 683 = 939
|      | DAGRank(R(1)) = 3
+-----+
|      |
|      |
+-----+
|  2  | R(2)=R(1) + 683 = 1622
|      | DAGRank(R(2)) = 6
+-----+
|      |
|      |
+-----+
|  3  | R(3)=R(2)+683=2305
|      | DAGRank(R(3)) = 9
+-----+
|      |
|      |
+-----+
|  4  | R(4)=R(3)+683=2988
|      | DAGRank(R(4)) = 11
+-----+
|      |
|      |
+-----+
|  5  | R(5)=R(4)+683=3671
|      | DAGRank(R(5)) = 14
+-----+

```

## 9.2. RPL Configuration

In addition to the Objective Function (OF), a minimal configuration for RPL SHOULD indicate the preferred mode of operation (either Storing Mode or Non-Storing Mode) so different RPL implementations can inter-operate. RPL information and hop-by-hop extension headers MUST follow [\[RFC6553\]](#) and [\[RFC6554\]](#) specification. In the case that the packets formed at the LLN need to cross through intermediate routers, these MUST obey to the IP in IP encapsulation requirement specified by the [\[RFC6282\]](#) and [\[RFC2460\]](#). RPI and RH3 extension



headers and inner IP headers MUST be compressed according to [\[RFC6282\]](#).

#### **[9.2.1.](#) Mode of Operation**

For downstream route maintenance, in a minimal configuration, RPL SHOULD be set to operate in the Non-Storing mode as described by [\[RFC6550\] Section 9.7](#). Storing mode ([\[RFC6550\] Section 9.8](#)) MAY be supported in less constrained devices.

#### **[9.2.2.](#) Trickle Timer**

RPL signaling messages such as DIOs are sent using the Trickle Algorithm [\[RFC6550\]](#) ([Section 8.3.1](#)) and [\[RFC6206\]](#). For this specification, the Trickle Timer MUST be used with the RPL defined default values [\[RFC6550\]](#) ([Section 8.3.1](#)). For a description of the Trickle timer operation see [Section 4.2](#) on [\[RFC6206\]](#).

#### **[9.2.3.](#) Hysteresis**

According to [\[RFC6552\]](#), [\[RFC6719\]](#) recommends the use of a boundary value (PARENT\_SWITCH\_THRESHOLD) to avoid constant changes of parent when ranks are compared. When evaluating a parent that belongs to a smaller path cost than current minimum path, the candidate node is selected as new parent only if the difference between the new path and the current path is greater than the defined PARENT\_SWITCH\_THRESHOLD. Otherwise the node MAY continue to use the current preferred parent. As for [\[RFC6719\]](#) the recommended value for PARENT\_SWITCH\_THRESHOLD is 192 when ETX metric is used (in the form  $128 * \text{ETX}$ ), the recommendation for this document is to use PARENT\_SWITCH\_THRESHOLD equal to 768 as the metric being used is  $2 * \text{ETX} * \text{minHopRankIncrease}$ . This mechanism is suited to deal with parent hysteresis in both cases routing parent and time source neighbor selection.

#### **[9.2.4.](#) Variable Values**

The following table presents the RECOMMENDED values for the RPL-related variables defined in the previous section.



## Recommended variable values

Variable	Value
EB_PERIOD	10s
MAX_EB_DELAY	180
NUM_NEIGHBOURS_TO_WAIT	2
PARENT_SWITCH_THRESHOLD	768

## 10. Examples

Several examples are provided to illustrate the content of the packets used by the minimal configuration as proposed by this document. Each example follows the same structure presenting first a schematic header diagram, then the LSB stream of bytes that conform the header and finally a description of each of the IEs the form the packet. The packet formats are specific for the [IEEE802154-2012] revision and MAY vary in future releases of the IEEE standard. In case of differences between the packet content presented in this section and the [IEEE802154-2012], the later has presedence.

The MAC header fields are described in a specific order. All field formats in this examples are depicted in the order in which they are transmitted by the PHY, from left to right, where the leftmost bit is transmitted first in time. Bits within each field are numbered from 0 (leftmost and least significant) to  $k - 1$  (rightmost and most significant), where the length of the field is  $k$  bits. Fields that are longer than a single octet are sent to the PHY in the order from the octet containing the lowest numbered bits to the octet containing the highest numbered bits, hence LSB format.

### 10.1. Example 1. Information Elements in EBs

Mandatory content for the EB as proposed by this draft. The example uses a slotframe of 101 slots. The following figure represents schematically the Header IE and Payload IE content of an EB.

Schematic representation of the IE header in an EB:

1										2										3											
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-



```

| Len1 = 0 |Element ID=0x7e|0| Len2 = 26 |GrpId=1|1|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Len3 = 6 |Sub ID = 0x1a|0| ASN
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---
ASN | Join Priority |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---
| Len4 = 1 |Sub ID = 0x1c|0| TT ID = 0x00 | Len5 = 0x01
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---
|ID=0x9 |1| CH ID = 0x00 | Len6 = 0x0A |Sub ID = 0x1b|0|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---
| #SF = 0x01 | SF ID = 0x01 | SF LEN = 0x65 (101 slots) |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---
| #Links = 0x01 | SLOT OFFSET = 0x0000 | CHANNEL
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---
OFF = 0x0000 |Link OPT = 0x07| Len7 = 0x00 |ID=0xf |1|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---
REST OF MAC PAYLOAD ...
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---

```

Stream of bytes (in LSB format) that derive from the previous schematic header:

```

00 FC 1A 88 06 34 ASN#0 ASN#1 ASN#2 ASN#3 ASN#4 JP 01 38 00
00 33 00 0A 36 01 01 65 00 01 00 00 00 00 07 00 1F ...

```

Description of the IE fields in the example:

#Header IE Header

Len1 = Header IE Length (0)

Element ID = 0x7e - termination IE indicating Payload IE coming next  
Type 0

#Payload IE Header (MLME)

Len2 = Payload IE Len (26 Bytes)

GroupID = 1 MLME (Nested)

Type = 1

#MLME-SubIE TSCH Synchronization

Len3 = Length in bytes of the sub-IE payload (6 Bytes)

SubID = 0x1a (MLME-SubIE TSCH Synchronization)

Type = Short (0)

ASN = Absolute Sequence Number (5 Bytes)

Join Priority = 1 Byte

#MLME-SubIE TSCH TimeSlot

Len4 = Length in bytes of the sub-IE payload (1 Byte)

SubID = 0x1c (MLME-SubIE Timeslot)

Type = Short (0)









```

+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
= 1200      | macTsTxAckDelay = 1500      | macTsRxWait
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
= 3300      | macTsAckWait = 600          | macTsRXTx
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
= 192       | macTsMaxAck = 2400          | macTsMaxTx
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
= 4256      | macTsTimeslotLength = 15000 | Len5 = 0x01
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
      | ID=0x9 | 1 | CH ID = 0x00 | Len6 = 0x0A | ...
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Stream of bytes (in LSB format) that derive from the previous schematic header:

```

00 FC 1A 88 06 34 ASN#0 ASN#1 ASN#2 ASN#3 ASN#4 JP 19 38 00 33 0A 80
00 6C 0C 90 06 B0 04 DC 05 E4 0C 58 02 C0 00 60 09 A0 10 98 3A 01 C8
00 0A ...

```

Description of the IE fields in the example:

#Header IE Header

Len1 = Header IE Length (none)

Element ID = 0x7e - termination IE indicating Payload IE coming next

Type 0

#Payload IE Header (MLME)

Len2 = Payload IE Len (53 Bytes)

GroupID = 1 MLME (Nested)

Type = 1

#MLME-SubIE TSCH Synchronization

Len3 = Length in bytes of the sub-IE payload (6 Bytes)

SubID = 0x1a (MLME-SubIE TSCH Synchronization)

Type = Short (0)

ASN = Absolute Sequence Number (5 Bytes)

Join Priority = 1 Byte

#MLME-SubIE TSCH TimeSlot

Len4 = Length in bytes of the sub-IE payload (25 Bytes)

SubID = 0x1c (MLME-SubIE Timeslot)

Type = Short (0)

TimeSlot template ID = 0x01 (non-default)

Example timeslot timing using 15ms timeslot.

```

+-----+-----+
| IEEE802.15.4 TSCH parameter | Value (us) |
+-----+-----+

```



tsCCAOffset	2700	
+-----+	+-----+	
tsCCA	128	
+-----+	+-----+	
tsTxOffset	3180	
+-----+	+-----+	
tsRxOffset	1680	
+-----+	+-----+	
tsRxAckDelay	1200	
+-----+	+-----+	
tsTxAckDelay	1500	
+-----+	+-----+	
tsRxWait	3300	
+-----+	+-----+	
tsAckWait	600	
+-----+	+-----+	
tsRXTx	192	
+-----+	+-----+	
tsMaxAck	2400	
+-----+	+-----+	
tsMaxTx	4256	
+-----+	+-----+	
Time Slot duration	15000	
+-----+	+-----+	

#MLME-SubIE Ch. Hopping

Len5 = Length in bytes of the sub-IE payload. (1 Byte)

SubID = 0x09 (MLME-SubIE Ch. Hopping)

Type = Long (1)

Channel Hopping Sequence ID = 0x00 (default)

### **10.3. Example 3. Information Elements in ACKs**

Acknowledgement packets carry the ACK/NACK Time Correction IE (Header IE). The following example illustrates the IE format as specified in [\[IEEE802154-2012\]](#).



```

          1                      2                      3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| Len1 =   2  |Element ID=0x1e|0|          Time Sync Info          |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

Stream of bytes (in LSB format) that derive from the previous schematic header:

```
40 F0 TS#0 TS#1
```

Description of the IE fields in the example:

```
#Header IE Header
```

```
Len1 = Header IE Length (2 Bytes)
```

```
Element ID = 0x1e - ACK/NACK Time Correction IE
```

```
Type 0
```

#### [10.4.](#) **Example 4.** Auxiliary Security Header

The example illustrates content of the Auxiliary Security Header as mandated by this document, if security is enabled. Security Level in the example is set to ENC-MIC-32 (5).





```

          1
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5
+-+--+--+--+--+--+--+--+--+--+
|L = 5|M=1|1|1|0|Key Index = IDX|
+-+--+--+--+--+--+--+--+--+--+

```

Stream of bytes (in LSB format) that derive from the previous schematic header:

6D IDX#0

Description of the Security Auxiliary Header fields in the example:

#Security Control (1 byte)

L = Security Level ENC-MIC-32 (5)

M = Key Identifier Mode (0x01)

Frame Counter Suppression = 1 (omitting Frame Counter field)

Frame Counter Size = 1 (construct Nonce from 5 byte ASN)

Reserved = 0

#Key Identifier (1 byte)

Key Index = IDX (deployment-specific KeyIndex parameter that identifies the cryptographic key)

## **11. IANA Considerations**

This document requests no immediate action by IANA.

## **12. Acknowledgments**

The authors would like to acknowledge the guidance and input provided by Rene Struik, Pat Kinney, Michael Richardson, Tero Kivinen, Nicola Accettura, Malisa Vucinic and the 6TiSCH Chairs Pascal Thubert and Thomas Watteyne.

## **13. References**

### **13.1. Normative References**

- [RFC6719] Gnawali, O. and P. Levis, "The Minimum Rank with Hysteresis Objective Function", [RFC 6719](#), September 2012.
- [RFC6282] Hui, J. and P. Thubert, "Compression Format for IPv6 Datagrams over IEEE 802.15.4-Based Networks", [RFC 6282](#), September 2011.



- [RFC6554] Hui, J., Vasseur, JP., Culler, D., and V. Manral, "An IPv6 Routing Header for Source Routes with the Routing Protocol for Low-Power and Lossy Networks (RPL)", [RFC 6554](#), March 2012.
- [RFC6553] Hui, J. and JP. Vasseur, "The Routing Protocol for Low-Power and Lossy Networks (RPL) Option for Carrying RPL Information in Data-Plane Datagrams", [RFC 6553](#), March 2012.
- [RFC6552] Thubert, P., "Objective Function Zero for the Routing Protocol for Low-Power and Lossy Networks (RPL)", [RFC 6552](#), March 2012.
- [RFC6551] Vasseur, JP., Kim, M., Pister, K., Dejean, N., and D. Barthel, "Routing Metrics Used for Path Calculation in Low-Power and Lossy Networks", [RFC 6551](#), March 2012.
- [RFC6550] Winter, T., Thubert, P., Brandt, A., Hui, J., Kelsey, R., Levis, P., Pister, K., Struik, R., Vasseur, JP., and R. Alexander, "RPL: IPv6 Routing Protocol for Low-Power and Lossy Networks", [RFC 6550](#), March 2012.
- [RFC6206] Levis, P., Clausen, T., Hui, J., Gnawali, O., and J. Ko, "The Trickle Algorithm", [RFC 6206](#), March 2011.
- [RFC2460] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), December 1998.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [IEEE802154-2012]  
IEEE standard for Information Technology, "IEEE standard for Information Technology, IEEE std. 802.15.4, Part. 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks, June 2011 as amended by IEEE std. 802.15.4e, Part. 15.4: Low-Rate Wireless Personal Area Networks (LR-WPANs) Amendment 1: MAC sublayer", April 2012.
- [IEEE802154]  
IEEE standard for Information Technology, "IEEE standard for Information Technology, IEEE std. 802.15.4, Part. 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks".



[decouto03high]

De Couto, D., Aguayo, D., Bicket, J., and R. Morris, "A High-Throughput Path Metric for Multi-Hop Wireless Routing", ACM International Conference on Mobile Computing and Networking (MobiCom) , June 2003.

### **13.2. Informative References**

- [RFC7554] Watteyne, T., Palattella, M., and L. Grieco, "Using IEEE 802.15.4e Time-Slotted Channel Hopping (TSCH) in the Internet of Things (IoT): Problem Statement", [RFC 7554](#), May 2015.
- [RFC7102] Vasseur, JP., "Terms Used in Routing for Low-Power and Lossy Networks", [RFC 7102](#), January 2014.
- [RFC3610] Whiting, D., Housley, R., and N. Ferguson, "Counter with CBC-MAC (CCM)", [RFC 3610](#), September 2003.
- [I-D.ietf-6tisch-architecture]  
Thubert, P., "An Architecture for IPv6 over the TSCH mode of IEEE 802.15.4", [draft-ietf-6tisch-architecture-08](#) (work in progress), May 2015.
- [I-D.ietf-6tisch-terminology]  
Palattella, M., Thubert, P., Watteyne, T., and Q. Wang, "Terminology in IPv6 over the TSCH mode of IEEE 802.15.4e", [draft-ietf-6tisch-terminology-04](#) (work in progress), March 2015.
- [I-D.ietf-6tisch-6top-interface]  
Wang, Q., Vilajosana, X., and T. Watteyne, "6TiSCH Operation Sublayer (6top) Interface", [draft-ietf-6tisch-6top-interface-03](#) (work in progress), March 2015.

### **13.3. External Informative References**

- [CCM] National Institute of Standards and Technology, "Recommendation for Block Cipher Modes of Operation: The CCM Mode for Authentication and Confidentiality. SP 800-38C", May 2004.
- [CCM-Star]  
Struik, R., "Formal Specification of the CCM\* Mode of Operation, IEEE P802.15 Working Group for Wireless Personal Area Networks (WPANs).", September 2005.



[OpenWSN] Watteyne, T., Vilajosana, X., Kerkez, B., Chraim, F., Weekly, K., Wang, Q., Glaser, S., and K. Pister, "OpenWSN: a Standards-Based Low-Power Wireless Development Environment", Transactions on Emerging Telecommunications Technologies , August 2012.

#### Authors' Addresses

Xavier Vilajosana (editor)  
Universitat Oberta de Catalunya  
156 Rambla Poblenou  
Barcelona, Catalonia 08018  
Spain

Phone: +34 (646) 633 681  
Email: xvilajosana@uoc.edu

Kris Pister  
University of California Berkeley  
490 Cory Hall  
Berkeley, California 94720  
USA

Email: pister@eecs.berkeley.edu



