

6TiSCH
Internet-Draft
Intended status: Informational
Expires: June 22, 2015

T. Watteyne, Ed.
Linear Technology
MR. Palattella
University of Luxembourg
LA. Grieco
Politecnico di Bari
December 19, 2014

**Using IEEE802.15.4e TSCH in an IoT context:
Overview, Problem Statement and Goals
draft-ietf-6tisch-tsch-04**

Abstract

This document describes the environment, problem statement, and goals for using the IEEE802.15.4e TSCH MAC protocol in the context of LLNs. The set of goals enumerated in this document form an initial set only.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 22, 2015.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Requirements Language	4
3.	TSCH in the LLN Context	4
4.	Problems and Goals	6
4.1.	Network Formation	7
4.2.	Network Maintenance	7
4.3.	Multi-Hop Topology	7
4.4.	Routing and Timing Parents	8
4.5.	Resource Management	8
4.6.	Dataflow Control	8
4.7.	Deterministic Behavior	8
4.8.	Scheduling Mechanisms	9
4.9.	Secure Communication	9
5.	IANA Considerations	9
6.	Security Considerations	9
7.	Acknowledgments	10
8.	References	10
8.1.	Normative References	10
8.2.	Informative References	10
8.3.	External Informative References	13
Appendix A.	TSCH Protocol Highlights	15
A.1.	Timeslots	15
A.2.	Slotframes	16
A.3.	Node TSCH Schedule	16
A.4.	Cells and Bundles	16
A.5.	Dedicated vs. Shared Cells	17
A.6.	Absolute Slot Number	17
A.7.	Channel Hopping	18
A.8.	Time Synchronization	18
A.9.	Power Consumption	19
A.10.	Network TSCH Schedule	19
A.11.	Join Process	20
A.12.	Information Elements	20
A.13.	Extensibility	20
Appendix B.	TSCH Gotchas	21
B.1.	Collision Free Communication	21
B.2.	Multi-Channel vs. Channel Hopping	21
B.3.	Cost of (continuous) Synchronization	21
B.4.	Topology Stability	22
B.5.	Multiple Concurrent Slotframes	22
	Authors' Addresses	22

1. Introduction

IEEE802.15.4e [[IEEE802154e](#)] was published in 2012 as an amendment to the Medium Access Control (MAC) protocol defined by the IEEE802.15.4-2011 [[IEEE802154](#)] standard. IEEE802.15.4e will be rolled into the next revision of IEEE802.15.4, scheduled to be published in 2015. The Timeslotted Channel Hopping (TSCH) mode of IEEE802.15.4e is the object of this document.

This document describes the main issues arising from the adoption of the IEEE802.15.4e TSCH in the LLN context, following the terminology defined in [[I-D.ietf-6tisch-terminology](#)].

TSCH was designed to allow IEEE802.15.4 devices to support a wide range of applications including, but not limited to, industrial ones [[IEEE802154e](#)]. At its core is a medium access technique which uses time synchronization to achieve ultra low-power operation and channel hopping to enable high reliability. Synchronization accuracy impacts power consumption, and can vary from micro-seconds to milli-seconds depending on the solution. This is very different from the "legacy" IEEE802.15.4 MAC protocol, and is therefore better described as a "redesign". TSCH does not amend the physical layer; i.e., it can operate on any IEEE802.15.4-compliant hardware.

IEEE802.15.4e is the latest generation of ultra-lower power and reliable networking solutions for LLNs. [[RFC5673](#)] discusses industrial applications, and highlights the harsh operating conditions as well as the stringent reliability, availability, and security requirements for an LLN to operate in an industrial environment. In these environments, vast deployment environments with large (metallic) equipment cause multi-path fading and interference to thwart any attempt of a single-channel solution to be reliable; the channel agility of TSCH is the key to its ultra high reliability. Commercial networking solutions are available today in which nodes consume 10's of micro-amps on average [[CurrentCalculator](#)] with end-to-end packet delivery ratios over 99.999% [[doherty07channel](#)].

IEEE802.15.4e has been designed for low-power constrained devices, often called "motes". Several terms are used in the IETF to refer to those devices, including "LLN nodes" [[RFC7102](#)] and "constrained nodes" [[RFC7228](#)]. In this document, we use the generic (and shorter) term "node", used as a synonym for "LLN node", "constrained node" or "mote".

Bringing industrial-like performance into the LLN stack developed by Internet of Things (IoT) related IETF working groups such as 6Lo, ROLL and CoRE opens up new application domains for these networks.

Sensors deployed in smart cities [[RFC5548](#)] will be able to be installed for years without needing battery replacement. "Umbrella" networks will interconnect smart elements from different entities in smart buildings [[RFC5867](#)]. Peel-and-stick switches will obsolete the need for costly conduits for lighting solutions in smart homes [[RFC5826](#)].

IEEE802.15.4e TSCH focuses on the MAC layer only. This clean layering allows for TSCH to fit under an IPv6 enabled protocol stack for LLNs, running 6LoWPAN [[RFC6282](#)], IPv6 Routing Protocol for Low power and Lossy Networks (RPL) [[RFC6550](#)] and the Constrained Application Protocol (CoAP) [[RFC7252](#)]. What is missing is a Logical Link Control (LLC) layer between the IP abstraction of a link and the TSCH MAC, which is in charge of scheduling a timeslot for a given packet coming down the stack from the upper layer.

While [[IEEE802154e](#)] defines the mechanisms for a TSCH node to communicate, it does not define the policies to build and maintain the communication schedule, match that schedule to the multi-hop paths maintained by RPL, adapt the resources allocated between neighbor nodes to the data traffic flows, enforce a differentiated treatment for data generated at the application layer and signaling messages needed by 6LoWPAN and RPL to discover neighbors, react to topology changes, self-configure IP addresses, or manage keying material.

In other words, IEEE802.15.4e TSCH is designed to allow optimizations and strong customizations, simplifying the merging of TSCH with a protocol stack based on IPv6, 6LoWPAN, and RPL.

2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

3. TSCH in the LLN Context

To map the services required by the IP layer to the services provided by the link layer, an adaptation layer is used [[palattella12standardized](#)]. The 6LoWPAN working group started working in 2007 on specifications for transmitting IPv6 packets over IEEE802.15.4 networks [[RFC4919](#)]. Low-power WPANs are characterized by small packet sizes, support for addresses with different lengths, low bandwidth, star and mesh topologies, battery powered devices, low cost, large number of devices, unknown node positions, high unreliability, and periods during which communication interfaces are turned off to save energy. Given these features, it is clear that

the adoption of IPv6 on top of a Low-Power WPAN is not straightforward, but poses strong requirements for the optimization of this adaptation layer.

For instance, due to the IPv6 default minimum MTU size (1280 bytes), an un-fragmented IPv6 packet is too large to fit in an IEEE802.15.4 frame. Moreover, the overhead due to the 40-byte long IPv6 header wastes the scarce bandwidth available at the PHY layer [[RFC4944](#)]. For these reasons, the 6LoWPAN working group has defined an effective adaptation layer [[RFC6282](#)]. Further issues encompass the auto-configuration of IPv6 addresses [[RFC2460](#)][RFC4862], the compliance with the recommendation on supporting link-layer subnet broadcast in shared networks [[RFC3819](#)], the reduction of routing and management overhead [[RFC6606](#)], the adoption of lightweight application protocols (or novel data encoding techniques), and the support for security mechanisms (confidentiality and integrity protection, device bootstrapping, key establishment, and management).

These features can run on top of TSCH. There are, however, important issues to solve, as highlighted in [Section 4](#).

Routing issues are challenging for 6LoWPAN, given the low-power and lossy radio links, the battery-powered nodes, the multi-hop mesh topologies, and the frequent topology changes due to mobility. Successful solutions take into account the specific application requirements, along with IPv6 behavior and 6LoWPAN mechanisms [[palattella12standardized](#)]. The ROLL working group has defined RPL in [[RFC6550](#)]. RPL can support a wide variety of link layers, including ones that are constrained, potentially lossy, or typically utilized in conjunction with host or router devices with very limited resources, as in building/home automation [[RFC5867](#)][RFC5826], industrial environments [[RFC5673](#)], and urban applications [[RFC5548](#)]. RPL is able to quickly build up network routes, distribute routing knowledge among nodes, and adapt to a changing topology. In a typical setting, nodes are connected through multi-hop paths to a small set of root devices, which are usually responsible for data collection and coordination. For each of them, a Destination Oriented Directed Acyclic Graph (DODAG) is created by accounting for link costs, node attributes/status information, and an Objective Function, which maps the optimization requirements of the target scenario.

The topology is set up based on a Rank metric, which encodes the distance of each node with respect to its reference root, as specified by the Objective Function. Regardless of the way it is computed, the Rank monotonically decreases along the DODAG towards the root, building a gradient. RPL encompasses different kinds of traffic and signaling information. Multipoint-to-Point (MP2P) is the

dominant traffic in LLN applications. Data is routed towards nodes with some application relevance, such as the LLN gateway to the larger Internet, or to the core of private IP networks. In general, these destinations are the DODAG roots and act as data collection points for distributed monitoring applications. Point-to-Multipoint (P2MP) data streams are used for actuation purposes, where messages are sent from DODAG roots to destination nodes. Point-to-Point (P2P) traffic allows communication between two devices belonging to the same LLN, such as a sensor and an actuator. A packet flows from the source to the common ancestor of those two communicating devices, then downward towards the destination. RPL therefore has to discover both upward routes (i.e. from nodes to DODAG roots) in order to enable MP2P and P2P flows, and downward routes (i.e. from DODAG roots to nodes) to support P2MP and P2P traffic.

[Section 4](#) highlights the challenges that need to be addressed to use RPL on top of TSCH.

Several open-source initiatives have emerged around TSCH. The OpenWSN project [[OpenWSN](#)][OpenWSNETT] is an open-source implementation of a standards-based protocol stack, which aims at evaluating the applicability of TSCH to different applications. This implementation was used as the foundation for an IP for Smart Objects Alliance (IPSO) [[IPSO](#)] interoperability event in 2011. In the absence of a standardized scheduling mechanism for TSCH, a "slotted Aloha" schedule was used.

4. Problems and Goals

As highlighted in [Appendix A](#), TSCH differs from traditional low-power MAC protocols because of its scheduled nature. TSCH defines the mechanisms to execute a communication schedule, yet it is the entity that sets up that schedule which controls the topology of the network. This scheduling entity also controls the resources allocated to each link in that topology.

How this entity should operate is out of scope of TSCH. The remainder of this section highlights the problems this entity needs to address. For simplicity, we refer to this entity by the generic name "LLC". Note that the 6top sublayer, currently being defined in [[I-D.wang-6tisch-6top-sublayer](#)], can be seen as an embodiment of this generic "LLC".

Some of the issues the LLC needs to target might overlap with the scope of other protocols (e.g., 6LoWPAN, RPL, and RSVP). In this case, it is entailed that the LLC will profit from the services provided by other protocols to pursue these objectives.

4.1. Network Formation

The LLC needs to control the way the network is formed, including how new nodes join, and how already joined nodes advertise the presence of the network. The LLC needs to:

1. Define the Information Elements included in the Enhanced Beacons advertising the presence of the network.
2. For a new node, define rules to process and filter received Enhanced Beacons.
3. Define the joining procedure. This might include a mechanism to assign a unique 16-bit address to a node, and the management of initial keying material.
4. Define a mechanism to secure the joining process and the subsequent optional process of scheduling more communication cells.

4.2. Network Maintenance

Once a network is formed, the LLC needs to maintain the network's health, allowing for nodes to stay synchronized. The LLC needs to:

1. Manage each node's time source neighbor.
2. Define a mechanism for a node to update the join priority it announces in its Enhanced Beacon.
3. Schedule transmissions of Enhanced Beacons to advertise the presence of the network.

4.3. Multi-Hop Topology

RPL, given a weighted connectivity graph, determines multi-hop routes. The LLC needs to:

1. Define a mechanism to gather topological information, node and link state, which it can then feed to RPL.
2. Ensure that the TSCH schedule contains cells along the multi-hop routes identified by RPL.
3. Where applicable, maintain independent sets of cells to transport independent flows of data.

4.4. Routing and Timing Parents

At all times, a TSCH node needs to have a time source neighbor it can synchronize to. The LLC therefore needs to assign a time source neighbor to allow for correct operation of the TSCH network. A time source neighbors could, or not, be taken from the RPL routing parent set.

4.5. Resource Management

A cell in a TSCH schedule is an atomic "unit" of resource. The number of cells to assign between neighbor nodes needs to be appropriate for the size of the traffic flow. The LLC needs to:

1. Define a mechanism for neighbor nodes to exchange information about their schedule and, if applicable, negotiate the addition/deletion of cells.
2. Allow for an entity (e.g., a set of devices, a distributed protocol, a PCE, etc.) to take control of the schedule.

4.6. Dataflow Control

TSCH defines mechanisms for a node to signal it cannot accept an incoming packet. It does not, however, define the policy which determines when to stop accepting packets. The LLC needs to:

1. Define a queuing policy for incoming and outgoing packets.
2. Manage the buffer space, and indicate to TSCH when to stop accepting incoming packets.
3. Handle transmissions that have failed. A transmission is declared failed when TSCH has retransmitted the packet multiple times, without receiving an acknowledgment. This covers both dedicated and shared cells.

4.7. Deterministic Behavior

As highlighted in [[RFC5673](#)], in some applications, data is generated periodically and has a well understood data bandwidth requirement, which is deterministic and predictable. The LLC needs to:

1. Ensure timely delivery of such data.
2. Provide a mechanism for such deterministic flows to coexist with bursty or infrequent traffic flows of different priorities.

4.8. Scheduling Mechanisms

Several scheduling mechanisms can be envisioned, and possibly coexist in the same network. For example, [[I-D.phinney-roll-rpl-industrial-applicability](#)] describes how the allocation of bandwidth can be optimized by an external Path Computation Element (PCE). Alternatively, two neighbor nodes can adapt the number of cells autonomously by monitoring the amount of traffic, and negotiating the allocation to extra cell when needed. This mechanism can be used to establish multi-hop paths in a fashion similar to RSVP. The LLC needs to:

1. Provide a mechanism for two 6TiSCH devices to negotiate the allocation and deallocation of cells between them.
2. Provide a mechanism for device to monitor and manage the 6TiSCH capabilities of a node several hops away.
3. Define an mechanism for these different scheduling mechanisms to coexist in the same network.

4.9. Secure Communication

Given some keying material, TSCH defines mechanisms to encrypt and authenticate MAC frames. It does not define how this keying material is generated. The LLC needs to:

1. Define the keying material and authentication mechanism needed by a new node to join an existing network.
2. Define a mechanism to allow for the secure transfer of application data between neighbor nodes.
3. Define a mechanism to allow for the secure transfer of signaling data between nodes and the LLC.

5. IANA Considerations

This memo includes no request to IANA.

6. Security Considerations

This memo is an informational overview of existing standards, and does define any new mechanisms or protocols.

It does describe the need for the 6TiSCH WG to define a secure solution. In particular, [Section 4.1](#) describes security in the join process. [Section 4.9](#) discusses data frame protection.

7. Acknowledgments

Special thanks to Jonathan Simon for his review and valuable comments. Thanks to Guillaume Gaillard and Dominique Barthel for their in-depth review. Thanks to the IoT6 European Project (STREP) of the 7th Framework Program (Grant 288445).

8. References

8.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

8.2. Informative References

[RFC7252] Shelby, Z., Hartke, K., and C. Bormann, "The Constrained Application Protocol (CoAP)", [RFC 7252](#), June 2014.

[RFC7228] Bormann, C., Ersue, M., and A. Keranen, "Terminology for Constrained-Node Networks", [RFC 7228](#), May 2014.

[RFC7102] Vasseur, JP., "Terms Used in Routing for Low-Power and Lossy Networks", [RFC 7102](#), January 2014.

[RFC6606] Kim, E., Kaspar, D., Gomez, C., and C. Bormann, "Problem Statement and Requirements for IPv6 over Low-Power Wireless Personal Area Network (6LoWPAN) Routing", [RFC 6606](#), May 2012.

[RFC6568] Kim, E., Kaspar, D., and JP. Vasseur, "Design and Application Spaces for IPv6 over Low-Power Wireless Personal Area Networks (6LoWPANs)", [RFC 6568](#), April 2012.

[RFC6550] Winter, T., Thubert, P., Brandt, A., Hui, J., Kelsey, R., Levis, P., Pister, K., Struik, R., Vasseur, JP., and R. Alexander, "RPL: IPv6 Routing Protocol for Low-Power and Lossy Networks", [RFC 6550](#), March 2012.

[RFC6282] Hui, J. and P. Thubert, "Compression Format for IPv6 Datagrams over IEEE 802.15.4-Based Networks", [RFC 6282](#), September 2011.

[RFC5867] Martocci, J., De Mil, P., Riou, N., and W. Vermeylen, "Building Automation Routing Requirements in Low-Power and Lossy Networks", [RFC 5867](#), June 2010.

- [RFC5826] Brandt, A., Buron, J., and G. Porcu, "Home Automation Routing Requirements in Low-Power and Lossy Networks", [RFC 5826](#), April 2010.
- [RFC5673] Pister, K., Thubert, P., Dwars, S., and T. Phinney, "Industrial Routing Requirements in Low-Power and Lossy Networks", [RFC 5673](#), October 2009.
- [RFC5548] Dohler, M., Watteyne, T., Winter, T., and D. Barthel, "Routing Requirements for Urban Low-Power and Lossy Networks", [RFC 5548](#), May 2009.
- [RFC4944] Montenegro, G., Kushalnagar, N., Hui, J., and D. Culler, "Transmission of IPv6 Packets over IEEE 802.15.4 Networks", [RFC 4944](#), September 2007.
- [RFC4919] Kushalnagar, N., Montenegro, G., and C. Schumacher, "IPv6 over Low-Power Wireless Personal Area Networks (6LoWPANs): Overview, Assumptions, Problem Statement, and Goals", [RFC 4919](#), August 2007.
- [RFC4862] Thomson, S., Narten, T., and T. Jinmei, "IPv6 Stateless Address Autoconfiguration", [RFC 4862](#), September 2007.
- [RFC3819] Karn, P., Bormann, C., Fairhurst, G., Grossman, D., Ludwig, R., Mahdavi, J., Montenegro, G., Touch, J., and L. Wood, "Advice for Internet Subnetwork Designers", [BCP 89](#), [RFC 3819](#), July 2004.
- [RFC2460] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), December 1998.
- [I-D.ietf-6tisch-6top-interface]
Wang, Q., Vilajosana, X., and T. Watteyne, "6TiSCH Operation Sublayer (6top) Interface", [draft-ietf-6tisch-6top-interface-02](#) (work in progress), October 2014.
- [I-D.ietf-6tisch-architecture]
Thubert, P., Watteyne, T., and R. Assimiti, "An Architecture for IPv6 over the TSCH mode of IEEE 802.15.4e", [draft-ietf-6tisch-architecture-04](#) (work in progress), October 2014.
- [I-D.ietf-6tisch-coap]
Sudhaakar, R. and P. Zand, "6TiSCH Resource Management and Interaction using CoAP", [draft-ietf-6tisch-coap-02](#) (work in progress), December 2014.

[I-D.ietf-6tisch-minimal]

Vilajosana, X. and K. Pister, "Minimal 6TiSCH Configuration", [draft-ietf-6tisch-minimal-04](#) (work in progress), November 2014.

[I-D.ietf-6tisch-terminology]

Palattella, M., Thubert, P., Watteyne, T., and Q. Wang, "Terminology in IPv6 over the TSCH mode of IEEE 802.15.4e", [draft-ietf-6tisch-terminology-02](#) (work in progress), July 2014.

[I-D.wang-6tisch-6top-sublayer]

Wang, Q., Vilajosana, X., and T. Watteyne, "6TiSCH Operation Sublayer (6top)", [draft-wang-6tisch-6top-sublayer-01](#) (work in progress), July 2014.

[I-D.thubert-roll-forwarding-frags]

Thubert, P. and J. Hui, "LLN Fragment Forwarding and Recovery", [draft-thubert-roll-forwarding-frags-02](#) (work in progress), September 2013.

[I-D.tsao-roll-security-framework]

Tsao, T., Alexander, R., Daza, V., and A. Lozano, "A Security Framework for Routing over Low Power and Lossy Networks", [draft-tsao-roll-security-framework-02](#) (work in progress), March 2010.

[I-D.thubert-roll-asymlink]

Thubert, P., "RPL adaptation for asymmetrical links", [draft-thubert-roll-asymlink-02](#) (work in progress), December 2011.

[I-D.ietf-roll-terminology]

Vasseur, J., "Terms used in Routing for Low power And Lossy Networks", [draft-ietf-roll-terminology-13](#) (work in progress), October 2013.

[I-D.ietf-roll-p2p-rpl]

Goyal, M., Baccelli, E., Philipp, M., Brandt, A., and J. Martocci, "Reactive Discovery of Point-to-Point Routes in Low Power and Lossy Networks", [draft-ietf-roll-p2p-rpl-17](#) (work in progress), March 2013.

[I-D.ietf-roll-trickle-mcast]

Hui, J. and R. Kelsey, "Multicast Protocol for Low power and Lossy Networks (MPL)", [draft-ietf-roll-trickle-mcast-11](#) (work in progress), November 2014.

[I-D.thubert-6lowpan-backbone-router]

Thubert, P., "6LoWPAN Backbone Router", [draft-thubert-6lowpan-backbone-router-03](#) (work in progress), February 2013.

[I-D.sarikaya-core-sbootstrapping]

Sarikaya, B., Ohba, Y., Moskowitz, R., Cao, Z., and R. Cragie, "Security Bootstrapping Solution for Resource-Constrained Devices", [draft-sarikaya-core-sbootstrapping-04](#) (work in progress), April 2012.

[I-D.gilger-smart-object-security-workshop]

Gilger, J. and H. Tschofenig, "Report from the 'Smart Object Security Workshop', 23rd March 2012, Paris, France", [draft-gilger-smart-object-security-workshop-00](#) (work in progress), October 2012.

[I-D.phinney-roll-rpl-industrial-applicability]

Phinney, T., Thubert, P., and R. Assimiti, "RPL applicability in industrial networks", [draft-phinney-roll-rpl-industrial-applicability-02](#) (work in progress), February 2013.

8.3. External Informative References

[IEEE802154e]

IEEE standard for Information Technology, "IEEE std. 802.15.4e, Part. 15.4: Low-Rate Wireless Personal Area Networks (LR-WPANs) Amendment 1: MAC sublayer", April 2012.

[IEEE802154]

IEEE standard for Information Technology, "IEEE std. 802.15.4, Part. 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks", June 2011.

[OpenWSN] "Berkeley's OpenWSN Project Homepage",
<<http://www.openwsn.org/>>.

[OpenWSNETT]

Watteyne, T., Vilajosana, X., Kerkez, B., Chraim, F., Weekly, K., Wang, Q., Glaser, S., and K. Pister, "OpenWSN: a Standards-Based Low-Power Wireless Development Environment", Transactions on Emerging Telecommunications Technologies , August 2012.

[IPSO] "IP for Smart Objects Alliance Homepage",
<<http://www.ipso-alliance.org/>>.

[CurrentCalculator]
Linear Technology, "Application Note: Using the Current Calculator to Estimate Mote Power", August 2012,
<[http://cds.linear.com/docs/en/application-note/Application_Note - Using the Current Calculator to Estimate Mote Power.pdf](http://cds.linear.com/docs/en/application-note/Application_Note_-_Using_the_Current_Calculator_to_Estimate_Mote_Power.pdf)>.

[doherty07channel]
Doherty, L., Lindsay, W., and J. Simon, "Channel-Specific Wireless Sensor Network Path Data", IEEE International Conference on Computer Communications and Networks (ICCCN) 2008, 2007.

[tinka10decentralized]
Tinka, A., Watteyne, T., and K. Pister, "A Decentralized Scheduling Algorithm for Time Synchronized Channel Hopping", Ad Hoc Networks 2010, 2010, <
<http://robotics.eecs.berkeley.edu/~pister/publications/2008/TSMP%20DSN08.pdf>>.

[watteyne09reliability]
Watteyne, T., Mehta, A., and K. Pister, "Reliability Through Frequency Diversity: Why Channel Hopping Makes Sense", International Conference on Performance Evaluation of Wireless Ad Hoc, Sensor, and Ubiquitous Networks (PE-WASUN) 2009, Oct. 2009, <http://www.ietf.org/mail-archive/web/roll/current/pdf/a_EzmuDIv3.pdf>.

[kerkez09feasibility]
Kerkez, B., Watteyne, T., and M. Magliocco, "Feasibility analysis of controller design for adaptive channel hopping", International Workshop on Performance Methodologies and Tools for Wireless Sensor Networks (WSNPERF) 2009, Oct. 2009, <http://www-bsac.eecs.berkeley.edu/publications/search/send_publication_pdf2client.php?pubID=1249681245>.

[TASA-PIMRC]
Palattella, MR., Accettura, N., Dohler, M., Grieco, LA., and G. Boggia, "Traffic Aware Scheduling Algorithm for Multi-Hop IEEE 802.15.4e Networks", IEEE PIMRC 2012, Sept. 2012, <
<http://www.cttc.es/resources/doc/120531-submitted-tasa-25511.pdf>>.

[TASA-SENSORS]

Palattella, MR., Accettura, N., Dohler, M., Grieco, LA., and G. Boggia, "Traffic-Aware Time-Critical Scheduling In Heavily Duty-Cycled IEEE 802.15.4e For An Industrial IoT", IEEE SENSORS 2012, Oct. 2012, < <http://www.cttc.es/resources/doc/120821-sensors2012-4396981770946977737.pdf>>.

[TASA-WCNC]

Accettura, N., Palattella, MR., Dohler, M., Grieco, LA., and G. Boggia, "Standardized Power-Efficient and Internet-Enabled Communication Stack for Capillary M2M Networks", IEEE WCNC 2012, Apr. 2012, < <http://www.cttc.es/resources/doc/120109-1569521283-submitted-58230.pdf>>.

[palattella12standardized]

Palattella, MR., Accettura, N., Vilajosana, X., Watteyne, T., Grieco, LA., Boggia, G., and M. Dohler, "Standardized Protocol Stack For The Internet Of (Important) Things", IEEE Communications Surveys and Tutorials 2012, Dec. 2012, < <http://www.cttc.es/resources/doc/121025-completestackforiot-clean-4818610916636121981.pdf>>.

[PANA]

Kanda, M., Ohba, Y., Das, S., and S. Chasko, "PANA applicability in constrained environments", Febr. 2012, <<http://www.lix.polytechnique.fr/hipercom/SmartObjectSecurity/papers/MitsuruKanda.pdf>>.

Appendix A. TSCH Protocol Highlights

This appendix gives an overview of the key features of the IEEE802.15.4e Timeslotted Channel Hopping (TSCH) amendment. It makes no attempt at repeating the standard, but rather focuses on the following:

- o Concepts which are sufficiently different from traditional IEEE802.15.4 networking that they may need to be defined and presented precisely.
- o Techniques and ideas which are part of IEEE802.15.4e and which might be useful for the work of the 6TiSCH WG.

A.1. Timeslots

All nodes in a TSCH network are synchronized. Time is sliced up into timeslots. A timeslot is long enough for a MAC frame of maximum size to be sent from node A to node B, and for node B to reply with an acknowledgment (ACK) frame indicating successful reception.

The duration of a timeslot is not defined by the standard. With IEEE802.15.4-compliant radios operating in the 2.4GHz frequency band, a maximum-length frame of 127 bytes takes about 4ms to transmit; a shorter ACK takes about 1ms. With a 10ms slot (a typical duration), this leaves 5ms to radio turnaround, packet processing and security operations.

A.2. Slotframes

Timeslots are grouped into one or more slotframes. A slotframe continuously repeats over time. TSCH does not impose a slotframe size. Depending on the application needs, these can range from 10s to 1000s of timeslots. The shorter the slotframe, the more often a timeslot repeats, resulting in more available bandwidth, but also in a higher power consumption.

A.3. Node TSCH Schedule

A TSCH schedule instructs each node what to do in each timeslot: transmit, receive or sleep. The schedule indicates, for each scheduled (transmit or receive) cell, a channelOffset and the address of the neighbor to communicate with.

Once a node obtains its schedule, it executes it:

- o For each transmit cell, the node checks whether there is a packet in the outgoing buffer which matches the neighbor written in the schedule information for that timeslot. If there is none, the node keeps its radio off for the duration of the timeslot. If there is one, the node can ask for the neighbor to acknowledge it, in which case it has to listen for the acknowledgment after transmitting.
- o For each receive cell, the node listens for possible incoming packets. If none is received after some listening period, it shuts down its radio. If a packet is received, addressed to the node, and passes security checks, the node can send back an acknowledgment.

How the schedule is built, updated and maintained, and by which entity, is outside of the scope of the IEEE802.15.4e standard.

A.4. Cells and Bundles

Assuming the schedule is well built, if node A is scheduled to transmit to node B at slotOffset 5 and channelOffset 11, node B will be scheduled to receive from node A at the same slotOffset and channelOffset.

A single element of the schedule characterized by a `slotOffset` and `channelOffset`, and reserved for node A to transmit to node B (or for node B to receive from node A) within a given slotframe, is called a "scheduled cell".

If there is a lot of data flowing from node A to node B, the schedule might contain multiple cells from A to B, at different times. Multiple cells scheduled to the same neighbor can be equivalent, i.e. the MAC layer sends the packet on whichever of these cells shows up first after the packet was put in the MAC queue. The union of all cells between two neighbors, A and B, is called a "bundle". Since the slotframe repeats over time (and the length of the slotframe is typically constant), each cell gives a "quantum" of bandwidth to a given neighbor. Modifying the number of equivalent cells in a bundle modifies the amount of resources allocated between two neighbors.

A.5. Dedicated vs. Shared Cells

By default, each scheduled transmit cell within the TSCH schedule is dedicated, i.e., reserved only for node A to transmit to node B. IEEE802.15.4e allows also to mark a cell as shared. In a shared cell, multiple nodes can transmit at the same time, on the same frequency. To avoid contention, TSCH defines a back-off algorithm for shared cells.

A scheduled cell can be marked as both transmitting and receiving. In this case, a node transmits if it has an appropriate packet in its output buffer, or listens otherwise. Marking a cell as [transmit, receive, shared] results in slotted-Aloha behavior.

A.6. Absolute Slot Number

TSCH defines a timeslot counter called Absolute Slot Number (ASN). When a new network is created, the ASN is initialized to 0; from then on, it increments by 1 at each timeslot. In detail:

$$\text{ASN} = (k * S + t)$$

where k is the slotframe cycle (i.e., the number of slotframe repetitions since the network was started), S the slotframe size and t the `slotOffset`. A node learns the current ASN when it joins the network. Since nodes are synchronized, they all know the current value of the ASN, at any time. The ASN is encoded as a 5-byte number: this allows it to increment for hundreds of years (the exact value depends on the duration of a timeslot) without wrapping over. The ASN is used to calculate the frequency to communicate on, and can be used for security-related operations.

[A.7.](#) Channel Hopping

For each scheduled cell, the schedule specifies a slotOffset and a channelOffset. In a well-built schedule, when node A has a transmit cell to node B on channelOffset 5, node B has a receive cell from node A on the same channelOffset. The channelOffset is translated by both nodes into a frequency using the following function:

$$\text{frequency} = F \{(\text{ASN} + \text{channelOffset}) \bmod \text{nFreq}\}$$

The function F consists of a look-up table containing the set of available channels. The value nFreq (the number of available frequencies) is the size of this look-up table. There are as many channelOffset values as there are frequencies available (e.g. 16 when using IEEE802.15.4-compliant radios at 2.4GHz, when all channels are used). Since both nodes have the same channelOffset written in their schedule for that scheduled cell, and the same ASN counter, they compute the same frequency. At the next iteration (cycle) of the slotframe, however, while the channelOffset is the same, the ASN has changed, resulting in the computation of a different frequency.

This results in "channel hopping": even with a static schedule, pairs of neighbors "hop" between the different frequencies when communicating. A way of ensuring communication happens on all available frequencies is to set the number of timeslots in a slotframe to a prime number. Channel hopping is a technique known to efficiently combat multi-path fading and external interference.

[A.8.](#) Time Synchronization

Because of the slotted nature of communication in a TSCH network, nodes have to maintain tight synchronization. All nodes are assumed to be equipped with clocks to keep track of time. Yet, because clocks in different nodes drift with respect to one another, neighbor nodes need to periodically re-synchronize.

Each node needs to periodically synchronize its network clock to another node, and it also provides its network time to its neighbors. It is up to the entity that manages the schedule to assign an adequate time source neighbor to each node, i.e., to indicate in the schedule which of neighbor is its "time source neighbor". While setting the time source neighbor, it is important to avoid synchronization loops, which could result in the formation of independent clusters of synchronized nodes.

TSCH adds timing information in all packets that are exchanged (both data and ACK frames). This means that neighbor nodes can resynchronize to one another whenever they exchange data. In detail,

two methods are defined in IEEE802.15.4e-2012 for allowing a device to synchronize in a TSCH network: (i) Acknowledgment-Based and (ii) Frame-Based synchronization. In both cases, the receiver calculates the difference in time between the expected time of frame arrival and its actual arrival. In Acknowledgment-Based synchronization, the receiver provides such information to the sender node in its acknowledgment. In this case, it is the sender node that synchronizes to the clock of the receiver. In Frame-Based synchronization, the receiver uses the computed delta for adjusting its own clock. In this case, it is the receiver node that synchronizes to the clock of the sender.

Different synchronization policies are possible. Nodes can keep synchronization exclusively by exchanging EBs. Nodes can also keep synchronized by periodically sending valid frames to a time source neighbor and use the acknowledgment to resynchronize. Both method (or a combination thereof) are valid synchronization policies; which one to use depends on network requirements.

A.9. Power Consumption

There are only a handful of activities a node can perform during a timeslot: transmit, receive, or sleep. Each of these operations has some energy cost associated to them, the exact value depends on the the hardware used. Given the schedule of a node, it is straightforward to calculate the expected average power consumption of that node.

A.10. Network TSCH Schedule

The schedule entirely defines the synchronization and communication between nodes. By adding/removing cells between neighbors, one can adapt a schedule to the needs of the application. Intuitive examples are:

- o Make the schedule "sparse" for applications where nodes need to consume as little energy as possible, at the price of reduced bandwidth.
- o Make the schedule "dense" for applications where nodes generate a lot of data, at the price of increased power consumption.
- o Add more cells along a multi-hop route over which many packets flow.

A.11. Join Process

Nodes already part of the network can periodically send Enhanced Beacon (EB) frames to announce the presence of the network. These contain information about the size of the timeslot used in the network, the current ASN, information about the slotframes and timeslots the beaconing node is listening on, and a 1-byte join priority. The join priority field gives information to make a better decision of which node to join. Even if a node is configured to send all EB frames on the same channel offset, because of the channel hopping nature of TSCH described in [Appendix A.7](#), this channel offset translates into a different frequency at different slotframe cycles. As a result, EB frames are sent on all frequencies.

A node wishing to join the network listens for EBs. Since EBs are sent on all frequencies, the joining node can listen on any frequency until it hears an EB. What frequency it listens on is implementation-specific. Once it has received one or more EBs, the new node enables the TSCH mode and uses the ASN and the other timing information from the EB to synchronize to the network. Using the slotframe and cell information from the EB, it knows how to contact other nodes in the network.

The IEEE802.15.4e TSCH standard does not define the steps beyond this network "bootstrap".

A.12. Information Elements

TSCH introduces the concept of Information Elements (IEs). An information element is a list of Type-Length-Value containers placed at the end of the MAC header. A small number of types are defined for TSCH (e.g., the ASN in the EB is contained in an IE), and an unmanaged range is available for extensions.

A data bit in the MAC header indicates whether the frame contains IEs. IEs are grouped into Header IEs, consumed by the MAC layer and therefore typically invisible to the next higher layer, and Payload IEs, which are passed untouched to the next higher layer, possibly followed by regular payload. Payload IEs can therefore be used for the next higher layers of two neighbor nodes to exchange information.

A.13. Extensibility

The TSCH standard is designed to be extensible. It introduces the mechanisms as "building block" (e.g., cells, bundles, slotframes, etc.), but leaves entire freedom to the upper layer to assemble those. The MAC protocol can be extended by defining new Header IEs.

An intermediate layer can be defined to manage the MAC layer by defining new Payload IEs.

Appendix B. TSCH Gotchas

This section lists features of TSCH which we believe are important and beneficial to the work of 6TiSCH.

B.1. Collision Free Communication

TSCH allows one to design a schedule which yields collision-free communication. This is done by building the schedule with dedicated cells in such a way that at most one node communicates with a specific neighbor in each slotOffset/channelOffset cell. Multiple pairs of neighbor nodes can exchange data at the same time, but on different frequencies.

B.2. Multi-Channel vs. Channel Hopping

A TSCH schedule looks like a matrix of width "slotframe size", S, and of height "number of frequencies", nFreq. For a scheduling algorithm, cells can be considered atomic "units" to schedule. In particular, because of the channel hopping nature of TSCH, the scheduling algorithm should not worry about the actual frequency communication happens on, since it changes at each slotframe iteration.

B.3. Cost of (continuous) Synchronization

When there is traffic in the network, nodes which are communicating implicitly re-synchronize using the data frames they exchange. In the absence of data traffic, nodes are required to synchronize to their time source neighbor(s) periodically not to drift in time. If they have not been communicating for some time (typically 30s), nodes can exchange an dummy data frame to re-synchronize. The frequency at which such messages need to be transmitted depends on the stability of the clock source, and on how "early" each node starts listening for data (the "guard time"). Theoretically, with a 10ppm clock and a 1ms guard time, this period can be 100s. Assuming this exchange causes the node's radio to be on for 5ms, this yields a radio duty cycle needed to keep synchronized of $5\text{ms}/100\text{s}=0.005\%$. While TSCH does requires nodes to resynchronize periodically, the cost of doing so is very low.

B.4. Topology Stability

The channel hopping nature of TSCH causes links to be very "stable". Wireless phenomena such as multi-path fading and external interference impact a wireless link between two nodes differently on each frequency. If a transmission from node A to node B fails, retransmitting on a different frequency has a higher likelihood of succeeding than retransmitting on the same frequency. As a result, even when some frequencies are "behaving bad", channel hopping "smoothens" the contribution of each frequency, resulting in more stable links, and therefore a more stable topology.

B.5. Multiple Concurrent Slotframes

The TSCH standard allows for multiple slotframes to coexist in a node's schedule. It is possible that, at some timeslot, a node has multiple activities scheduled (e.g. transmit to node B on slotframe 2, receive from node C on slotframe 1). To handle this situation, the TSCH standard defines the following precedence rules:

1. Transmissions take precedence over receptions;
2. Lower slotframe identifiers take precedence over higher slotframe identifiers.

In the example above, the node would transmit to node B on slotframe 2.

Authors' Addresses

Thomas Watteyne (editor)
Linear Technology
32990 Alvarado-Niles Road, Suite 910
Union City, CA 94587
USA

Phone: +1 (510) 400-2978
Email: twatteyne@linear.com

Maria Rita Palattella
University of Luxembourg
Interdisciplinary Centre for Security, Reliability and Trust
4, rue Alphonse Weicker
Luxembourg L-2721
LUXEMBOURG

Phone: +352 46 66 44 5841
Email: maria-rita.palattella@uni.lu

Luigi Alfredo Grieco
Politecnico di Bari
Department of Electrical and Information Engineering
Via Orabona 4
Bari 70125
Italy

Phone: +39 08 05 96 3911
Email: a.grieco@poliba.it

