

Network Working Group
Internet Draft

Nathaniel Borenstein
Ned Freed

[<draft-ietf-822ext-mime-imt-03.txt>](mailto:draft-ietf-822ext-mime-imt-03.txt)

Multipurpose Internet Mail Extensions
(MIME) Part Two:

Media Types

January 1996

Status of this Memo

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months. Internet-Drafts may be updated, replaced, or obsoleted by other documents at any time. It is not appropriate to use Internet-Drafts as reference material or to cite them other than as a "working draft" or "work in progress".

To learn the current status of any Internet-Draft, please check the `l1d-abstracts.txt` listing contained in the Internet-Drafts Shadow Directories on `ds.internic.net` (US East Coast), `nic.nordu.net` (Europe), `ftp.isi.edu` (US West Coast), or `munari.oz.au` (Pacific Rim).

1. Abstract

STD 11, [RFC 822](#) defines a message representation protocol specifying considerable detail about US-ASCII message headers, but which leaves the message content, or message body, as flat US-ASCII text. This set of documents, collectively called the Multipurpose Internet Mail Extensions, or MIME, redefines the format of messages to allow for

- (1) textual message bodies in character sets other than US-ASCII,
- (2) non-textual message bodies,
- (3) multi-part message bodies, and
- (4) textual header information in character sets other than US-ASCII.

These documents are based on earlier work documented in RFC 934, STD 11, and [RFC 1049](#), but extends and revises them. Because [RFC 822](#) said so little about message bodies, these documents are largely orthogonal to (rather than a revision of) [RFC 822](#).

In particular, these documents are designed to provide facilities to include multiple parts in a single message, to represent body and header text in character sets other than US-ASCII, to represent formatted multi-font text messages, to represent non-textual material such as images and audio clips, and generally to facilitate later extensions defining new types of Internet mail for use by cooperating mail agents.

The initial document in this set, RFC MIME-IMB, specifies the various headers used to describe the structure of MIME messages. This second document defines the general structure of the MIME media typing system and defines an initial set of media types. The third document, RFC MIME-HEADERS, describes extensions to [RFC 822](#) to allow non-US-ASCII text data in Internet mail header fields. The fourth document, RFC MIME-REG, specifies various IANA registration procedures for MIME-related facilities. The fifth and final document, RFC MIME-CONF, describes MIME conformance criteria as well as providing some illustrative examples of MIME message formats, acknowledgements, and the bibliography.

These documents are revisions of RFCs 1521 and 1522, which themselves were revisions of RFCs 1341 and 1342. An appendix in RFC MIME-CONF describes differences and changes from previous versions.

Internet Draft

Media Types

January 1996

[2.](#) Table of Contents

1 Abstract	1
2 Table of Contents	3
3 Introduction	4
4 Definition of a Top-Level Media Type	5
5 Overview Of The Initial Top-Level Media Types	5
6 Discrete Media Type Values	7
6.1 Text Media Type	7
6.1.1 Representation of Line Breaks	8
6.1.2 Charset Parameter	8
6.1.3 Plain Subtype	12
6.1.4 Unrecognized Subtypes	12
6.2 Image Media Type	12
6.3 Audio Media Type	13
6.4 Video Media Type	13
6.5 Application Media Type	14
6.5.1 Octet-Stream Subtype	15
6.5.2 PostScript Subtype	15
6.5.3 Other Application Subtypes	19
7 Composite Media Type Values	19
7.1 Multipart Media Type	19
7.1.1 Common Syntax	21
7.1.2 Handling Nested Messages and Multiparts	27
7.1.3 Mixed Subtype	28
7.1.4 Alternative Subtype	28
7.1.5 Digest Subtype	30
7.1.6 Parallel Subtype	32
7.1.7 Other Multipart Subtypes	32
7.2 Message Media Type	32
7.2.1 RFC822 Subtype	33
7.2.2 Partial Subtype	33
7.2.2.1 Message Fragmentation and Reassembly	35
7.2.2.2 Fragmentation and Reassembly Example	36
7.2.3 External-Body Subtype	38

7.2.4 Other Message Subtypes	46
8 Experimental Media Type Values	46
9 Summary	47
10 Security Considerations	47
11 Authors' Addresses	48
A Collected Grammar	49

Expires July 1996

[Page 3]

Internet Draft

Media Types

January 1996

[3. Introduction](#)

The first document in this set, RFC MIME-IMB, defines a number of header fields, including Content-Type. The Content-Type field is used to specify the nature of the data in the body of a MIME entity, by giving media type and subtype identifiers, and by providing auxiliary information that may be required for certain media types. After the type and subtype names, the remainder of the header field is simply a set of parameters, specified in an attribute/value notation. The ordering of parameters is not significant.

In general, the top-level media type is used to declare the general type of data, while the subtype specifies a specific format for that type of data. Thus, a media type of "image/xyz" is enough to tell a user agent that the data is an image, even if the user agent has no knowledge of the specific image format "xyz". Such information can be used, for example, to decide whether or not to show a user the raw data from an unrecognized subtype -- such an action might be reasonable for unrecognized subtypes of text, but not for unrecognized subtypes of image or audio. For this reason, registered subtypes of text, image, audio, and video should not contain embedded information that is really of a different type. Such compound formats should be represented using the "multipart" or "application" types.

Parameters are modifiers of the media subtype, and as such do not fundamentally affect the nature of the content. The set of meaningful parameters depends on the media type and

subtype. Most parameters are associated with a single specific subtype. However, a given top-level media type may define parameters which are applicable to any subtype of that type. Parameters may be required by their defining media type or subtype or they may be optional. MIME implementations must also ignore any parameters whose names they do not recognize.

MIME's Content-Type header field and media type mechanism has been carefully designed to be extensible, and it is expected that the set of media type/subtype pairs and their associated parameters will grow significantly over time. Several other MIME facilities, most notably the list of the name of character sets registered for MIME usage, are likely to have new values defined over time. In order to ensure that the set of such values is developed in an orderly, well-specified, and

Expires July 1996

[Page 4]

Internet Draft

Media Types

January 1996

public manner, MIME sets up a registration process which uses the Internet Assigned Numbers Authority (IANA) as a central registry for MIME's extension areas. The registration process is described in a companion document, RFC MIME-REG.

The initial seven standard top-level media type are defined and described in the remainder of this document.

[4.](#) Definition of a Top-Level Media Type

The definition of a top-level media type consists of:

- (1) a name and a description of the type, including criteria for whether a particular type would qualify under that type,
- (2) the names and definitions of parameters, if any, which are defined for all subtypes of that type (including whether such parameters are required or optional),
- (3) how a user agent and/or gateway should handle unknown subtypes of this type,

- (4) general considerations on gatewaying entities of this top-level type, if any, and
- (5) any restrictions on content-transfer-encodings for entities of this top-level type.

5. Overview Of The Initial Top-Level Media Types

The five discrete top-level media types are:

- (1) text -- textual information. The subtype "plain" in particular indicates plain (unformatted) text. No special software is required to get the full meaning of the text, aside from support for the indicated character set. Other subtypes are to be used for enriched text in forms where application software may enhance the appearance of the text, but such software must not be required in order to get the general idea of the content. Possible subtypes thus include any word processor format that can be read without

Expires July 1996

[Page 5]

Internet Draft

Media Types

January 1996

resorting to software that understands the format. In particular, formats that employ embedded binary formatting information are not considered directly readable. A very simple and portable subtype, "richtext", was defined in [RFC 1341](#), with a further revision in [RFC 1563](#) under the name "enriched".

- (2) image -- image data. Image requires a display device (such as a graphical display, a graphics printer, or a FAX machine) to view the information. An initial subtype is defined for the widely-used image format JPEG.
- (3) audio -- audio data. Audio requires an audio output device (such as a speaker or a telephone) to "display" the contents. An initial subtype "basic" is defined in this document.

- (4) video -- video data. Video requires the capability to display moving images, typically including specialized hardware and software. An initial subtype "mpeg" is defined in this document.
- (5) application -- some other kind of data, typically either uninterpreted binary data or information to be processed by an application. The subtype "octet-stream" is to be used in the case of uninterpreted binary data, in which case the simplest recommended action is to offer to write the information into a file for the user. The "PostScript" subtype is also defined for the transport of PostScript material. Other expected uses for "application" include spreadsheets, data for mail-based scheduling systems, and languages for "active" (computational) messaging, and word processing formats that are not directly readable. Note that security considerations may exist for some types of application data, most notably application/PostScript and any form of active messaging. These issues are discussed later in this document.

The two composite top-level media types are:

- (1) multipart -- data consisting of multiple entities of independent data types. Four subtypes are initially

defined, including the basic "mixed" subtype specifying a generic mixed set of parts, "alternative" for representing the same data in multiple formats, "parallel" for parts intended to be viewed simultaneously, and "digest" for multipart entities in which each part has a default type of "message/rfc822".

- (2) message -- an encapsulated message. A body of media type "message" is itself all or a portion of some kind of message object. Such objects may or may not in turn contain other entities. The "[rfc822](#)" subtype is used when the encapsulated content is itself an [RFC 822](#)

message. The "partial" subtype is defined for partial [RFC 822](#) messages, to permit the fragmented transmission of bodies that are thought to be too large to be passed through transport facilities in one piece. Another subtype, "external-body", is defined for specifying large bodies by reference to an external data source.

It should be noted that the list of media type values given here may be augmented in time, via the mechanisms described above, and that the set of subtypes is expected to grow substantially.

[6.](#) Discrete Media Type Values

Five of the seven initial media type values refer to discrete bodies. The content of these types must be handled by non-MIME mechanisms; they are opaque to MIME processors.

[6.1.](#) Text Media Type

The text media type is intended for sending material which is principally textual in form. A "charset" parameter may be used to indicate the character set of the body text for text subtypes, notably including the subtype "text/plain", which indicates plain (unformatted) text.

Beyond plain text, there are many formats for representing what might be known as "extended text" -- text with embedded formatting and presentation information. An interesting characteristic of many such representations is that they are to some extent readable even without the software that

interprets them. It is useful, then, to distinguish them, at the highest level, from such unreadable data as images, audio, or text represented in an unreadable form. In the absence of appropriate interpretation software, it is reasonable to show subtypes of text to the user, while it is not reasonable to do so with most nontextual data.

Such formatted textual data should be represented using subtypes of text. Plausible subtypes of text are typically given by the common name of the representation format, e.g., "text/enriched" [[RFC-1563](#)].

[6.1.1.](#) Representation of Line Breaks

The canonical form of any MIME text type MUST represent a line break as a CRLF sequence. Similarly, any occurrence of CRLF in text MUST represent a line break. Use of CR and LF outside of line break sequences is also forbidden.

This rule applies regardless of format or character set or sets involved.

NOTE: The proper interpretation of line breaks when a body is displayed depends on the media type. In particular, while it is appropriate to treat a line break as a transition to a new line when displaying a text/plain body, this treatment is actually incorrect for other subtypes of text like text/enriched [[RFC-1563](#)].

[6.1.2.](#) Charset Parameter

A critical parameter that may be specified in the Content-Type field for text/plain data is the character set. This is specified with a "charset" parameter, as in:

Content-type: text/plain; charset=iso-8859-1

Unlike some other parameter values, the values of the charset parameter are NOT case sensitive. The default character set, which must be assumed in the absence of a charset parameter, is US-ASCII.

The specification for any future subtypes of "text" must specify whether or not they will also utilize a "charset" parameter, and may possibly restrict its values as well. When used with a particular body, the semantics of the "charset" parameter should be identical to those specified here for "text/plain", i.e., the body consists entirely of characters in the given charset. In particular, definers of future text subtypes should pay close attention to the implications of multioctet character sets for their subtype definitions.

This RFC specifies the definition of the charset parameter for the purposes of MIME to be the name of a character set, as "character set" as defined in MIME-IMB. The rules regarding line breaks detailed in the previous section must also be observed -- a character set whose definition does not conform to these rules cannot be used in a MIME text type.

An initial list of predefined character set names can be found at the end of this section. Additional character sets may be registered with IANA as described in RFC MIME-REG.

Note that if the specified character set includes 8bit data, a Content-Transfer-Encoding header field and a corresponding encoding on the data are required in order to transmit the body via some mail transfer protocols, such as SMTP [[RFC-821](#)].

The default character set, US-ASCII, has been the subject of some confusion and ambiguity in the past. Not only were there some ambiguities in the definition, there have been wide variations in practice. In order to eliminate such ambiguity and variations in the future, it is strongly recommended that new user agents explicitly specify a character set as a media type parameter in the Content-Type header field. "US-ASCII" does not indicate an arbitrary -bit character code, but specifies that the body uses character coding that uses the exact correspondence of octets to characters specified in US-ASCII. National use variations of ISO 646 [ISO-646] are NOT US-ASCII and their use in Internet mail is explicitly discouraged. The omission of the ISO 646 character set from this document is deliberate in this regard. The character set name of "US-ASCII" explicitly refers to ANSI X3.4-1986 [US-ASCII] only. The character set name "ASCII" is reserved and must not be used for any purpose.

NOTE: [RFC 821](#) explicitly specifies "ASCII", and references an earlier version of the American Standard. Insofar as one of the purposes of specifying a media type and character set is to permit the receiver to unambiguously determine how the sender intended the coded message to be interpreted, assuming anything other than "strict ASCII" as the default would risk unintentional and incompatible changes to the semantics of messages now being transmitted. This also implies that messages containing characters coded according to national variations on ISO 646, or using code-switching procedures (e.g., those of ISO 2022), as well as 8bit or multiple octet character encodings MUST use an appropriate character set specification to be consistent with this specification.

The complete US-ASCII character set is listed in ANSI X3.4-[1986](#). Note that the control characters including DEL (0-31, 127) have no defined meaning apart from the combination CRLF (US-ASCII values 13 and 10) indicating a new line. Two of the characters have de facto meanings in wide use: FF (12) often means "start subsequent text on the beginning of a new page"; and TAB or HT (9) often (though not always) means "move the cursor to the next available column after the current position where the column number is a multiple of 8 (counting the first column as column 0)." Aside from these conventions, any use of the control characters or DEL in a body must occur within the context of a private agreement between the sender and recipient. Such private agreements are discouraged and should be replaced by the other capabilities of this document.

NOTE: Beyond US-ASCII, an enormous proliferation of character sets is possible. It is the opinion of the IETF working group that a large number of character sets is NOT a good thing. We would prefer to specify a SINGLE character set that can be used universally for representing all of the world's languages in Internet mail. Unfortunately, existing practice in several communities seems to point to the continued use of multiple character sets in the near future. For this reason, we define names for a small number of character sets for which a strong constituent base exists.

The defined charset values are:

- (1) US-ASCII -- as defined in ANSI X3.4-1986 [US-ASCII].

Internet Draft

Media Types

January 1996

- (2) ISO-8859-X -- where "X" is to be replaced, as necessary, for the parts of ISO-8859 [ISO-8859]. Note that the ISO 646 character sets have deliberately been omitted in favor of their 8859 replacements, which are the designated character sets for Internet mail. As of the publication of this document, the legitimate values for "X" are the digits 1 through 9.

All of these character sets are used as pure 7bit or 8bit sets without any shift or escape functions. The meaning of shift and escape sequences in these character sets is not defined.

The character sets specified above are the ones that were relatively uncontroversial during the drafting of MIME. This document does not endorse the use of any particular character set other than US-ASCII, and recognizes that the future evolution of world character sets remains unclear. It is expected that in the future, additional character sets will be registered for use in MIME.

Note that the character set used, if anything other than US-ASCII, must always be explicitly specified in the Content-Type field.

No other character set name may be used in Internet mail without the publication of a formal specification and its registration with IANA, or by private agreement, in which case the character set name must begin with "X-".

Implementors are discouraged from defining new character sets unless absolutely necessary.

The "charset" parameter has been defined primarily for the purpose of textual data, and is described in this section for that reason. However, it is conceivable that non-textual data might also wish to specify a charset value for some purpose, in which case the same syntax and values should be used.

In general, composition software should always use the "lowest common denominator" character set possible. For example, if a

body contains only US-ASCII characters, it SHOULD be marked as being in the US-ASCII character set, not ISO-8859-1, which, like all the ISO-8859 family of character sets, is a superset of US-ASCII. More generally, if a widely-used character set is a subset of another character set, and a body contains only

Internet Draft

Media Types

January 1996

characters in the widely-used subset, it should be labelled as being in that subset. This will increase the chances that the recipient will be able to view the resulting entity correctly.

[6.1.3.](#) Plain Subtype

The simplest and most important subtype of text is "plain". This indicates plain (unformatted) text. The default media type of "text/plain; charset=us-ascii" for Internet mail describes existing Internet practice. That is, it is the type of body defined by [RFC 822](#).

No other text subtype is defined by this document.

[6.1.4.](#) Unrecognized Subtypes

Unrecognized subtypes of text should be treated as subtype "plain" as long as the MIME implementation knows how to handle the charset. Unrecognized subtypes which also specify an unrecognized charset should be treated as "application/octet-stream".

[6.2.](#) Image Media Type

A media type of "image" indicates that the body contains an image. The subtype names the specific image format. These names are not case sensitive. An initial subtype is "jpeg" for the JPEG format using JFIF encoding [JPEG].

The list of image subtypes given here is neither exclusive nor

exhaustive, and is expected to grow as more types are registered with IANA, as described in RFC MIME-REG.

Unrecognized subtypes of image should at a minimum be treated as "application/octet-stream". Implementations may optionally elect to pass subtypes of image that they do not specifically recognize to a secure and robust general-purpose image viewing application, if such an application is available.

NOTE: Using of a generic-purpose image viewing application this way inherits the security problems of the most dangerous

Expires July 1996

[Page 12]

Internet Draft

Media Types

January 1996

type supported by the application.

[6.3.](#) Audio Media Type

A media type of "audio" indicates that the body contains audio data. Although there is not yet a consensus on an "ideal" audio format for use with computers, there is a pressing need for a format capable of providing interoperable behavior.

The initial subtype of "basic" is specified to meet this requirement by providing an absolutely minimal lowest common denominator audio format. It is expected that richer formats for higher quality and/or lower bandwidth audio will be defined by a later document.

The content of the "audio/basic" subtype is single channel audio encoded using 8bit ISDN mu-law [PCM] at a sample rate of [8000](#) Hz.

Unrecognized subtypes of audio should at a minimum be treated as "application/octet-stream". Implementations may optionally elect to pass subtypes of audio that they do not specifically recognize to a robust general-purpose audio playing application, if such an application is available.

[6.4.](#) Video Media Type

A media type of "video" indicates that the body contains a time-varying-picture image, possibly with color and coordinated sound. The term "video" is used extremely generically, rather than with reference to any particular technology or format, and is not meant to preclude subtypes such as animated drawings encoded compactly. The subtype "mpeg" refers to video coded according to the MPEG standard [MPEG].

Note that although in general this document strongly discourages the mixing of multiple media in a single body, it is recognized that many so-called "video" formats include a representation for synchronized audio, and this is explicitly permitted for subtypes of "video".

Expires July 1996

[Page 13]

Internet Draft

Media Types

January 1996

Unrecognized subtypes of video should at a minimum be treated as "application/octet-stream". Implementations may optionally elect to pass subtypes of video that they do not specifically recognize to a robust general-purpose video display application, if such an application is available.

[6.5.](#) Application Media Type

The "application" media type is to be used for discrete data which do not fit in any of the other categories, and particularly for data to be processed by some type of application program. This is information which must be processed by an application before it is viewable or usable by a user. Expected uses for the application media type include file transfer, spreadsheets, data for mail-based scheduling systems, and languages for "active" (computational) material. (The latter, in particular, can pose security problems which must be understood by implementors, and are considered in detail in the discussion of the application/PostScript media type.)

For example, a meeting scheduler might define a standard representation for information about proposed meeting dates. An intelligent user agent would use this information to conduct a dialog with the user, and might then send additional material based on that dialog. More generally, there have been several "active" messaging languages developed in which programs in a suitably specialized language are transported to a remote location and automatically run in the recipient's environment.

Such applications may be defined as subtypes of the "application" media type. This document defines two subtypes: octet-stream, and PostScript.

The subtype of application will often be the name of the application for which the data are intended. This does not mean, however, that any application program name may be used freely as a subtype of application. Usage of any subtype (other than subtypes beginning with "x-") must be registered with IANA, as described in RFC MIME-REG.

[6.5.1.](#) Octet-Stream Subtype

The "octet-stream" subtype is used to indicate that a body contains arbitrary binary data. The set of currently defined parameters is:

- (1) TYPE -- the general type or category of binary data. This is intended as information for the human recipient rather than for any automatic processing.
- (2) PADDING -- the number of bits of padding that were appended to the bit-stream comprising the actual contents to produce the enclosed 8bit byte-oriented data. This is useful for enclosing a bit-stream in a body when the total number of bits is not a multiple of 8.

Both of these parameters are optional.

An additional parameter, "CONVERSIONS", was defined in RFC [1341](#) but has since been removed. [RFC 1341](#) also defined the use of a "NAME" parameter which gave a suggested file name to be used if the data were to be written to a file. This has been deprecated in anticipation of a separate Content-Disposition header field, to be defined in a subsequent RFC.

The recommended action for an implementation that receives an application/octet-stream entity is to simply offer to put the data in a file, with any Content-Transfer-Encoding undone, or perhaps to use it as input to a user-specified process.

To reduce the danger of transmitting rogue programs, it is strongly recommended that implementations NOT implement a path-search mechanism whereby an arbitrary program named in the Content-Type parameter (e.g., an "interpreter=" parameter) is found and executed using the message body as input.

[6.5.2.](#) PostScript Subtype

A media type of "application/postscript" indicates a PostScript program. Currently two variants of the PostScript language are allowed; the original level 1 variant is described in [POSTSCRIPT] and the more recent level 2 variant is described in [POSTSCRIPT2].

Expires July 1996

[Page 15]

Internet Draft

Media Types

January 1996

PostScript is a registered trademark of Adobe Systems, Inc. Use of the MIME media type "application/postscript" implies recognition of that trademark and all the rights it entails.

The PostScript language definition provides facilities for internal labelling of the specific language features a given program uses. This labelling, called the PostScript document structuring conventions, or DSC, is very general and provides substantially more information than just the language level. The use of document structuring conventions, while not

required, is strongly recommended as an aid to interoperability. Documents which lack proper structuring conventions cannot be tested to see whether or not they will work in a given environment. As such, some systems may assume the worst and refuse to process unstructured documents.

The execution of general-purpose PostScript interpreters entails serious security risks, and implementors are discouraged from simply sending PostScript bodies to "off-the-shelf" interpreters. While it is usually safe to send PostScript to a printer, where the potential for harm is greatly constrained by typical printer environments, implementors should consider all of the following before they add interactive display of PostScript bodies to their MIME readers.

The remainder of this section outlines some, though probably not all, of the possible problems with the transport of PostScript entities.

- (1) Dangerous operations in the PostScript language include, but may not be limited to, the PostScript operators "deletefile", "renamefile", "filenameforall", and "file". "File" is only dangerous when applied to something other than standard input or output. Implementations may also define additional nonstandard file operators; these may also pose a threat to security. "Filenameforall", the wildcard file search operator, may appear at first glance to be harmless. Note, however, that this operator has the potential to reveal information about what files the recipient has access to, and this information may itself be sensitive. Message senders should avoid the use of potentially dangerous file operators, since these operators are quite likely to be unavailable in secure

PostScript implementations. Message receiving and displaying software should either completely disable all potentially dangerous file operators or take special care not to delegate any special authority to

their operation. These operators should be viewed as being done by an outside agency when interpreting PostScript documents. Such disabling and/or checking should be done completely outside of the reach of the PostScript language itself; care should be taken to insure that no method exists for re-enabling full-function versions of these operators.

- (2) The PostScript language provides facilities for exiting the normal interpreter, or server, loop. Changes made in this "outer" environment are customarily retained across documents, and may in some cases be retained semipermanently in nonvolatile memory. The operators associated with exiting the interpreter loop have the potential to interfere with subsequent document processing. As such, their unrestrained use constitutes a threat of service denial. PostScript operators that exit the interpreter loop include, but may not be limited to, the `exitserver` and `startjob` operators. Message sending software should not generate PostScript that depends on exiting the interpreter loop to operate, since the ability to exit will probably be unavailable in secure PostScript implementations. Message receiving and displaying software should completely disable the ability to make retained changes to the PostScript environment by eliminating or disabling the `"startjob"` and `"exitserver"` operations. If these operations cannot be eliminated or completely disabled the password associated with them should at least be set to a hard-to-guess value.
- (3) PostScript provides operators for setting system-wide and device-specific parameters. These parameter settings may be retained across jobs and may potentially pose a threat to the correct operation of the interpreter. The PostScript operators that set system and device parameters include, but may not be limited to, the `"setsystemparams"` and `"setdevparams"` operators. Message sending software should not generate PostScript that depends on the setting of

system or device parameters to operate correctly. The ability to set these parameters will probably be unavailable in secure PostScript implementations. Message receiving and displaying software should disable the ability to change system and device parameters. If these operators cannot be completely disabled the password associated with them should at least be set to a hard-to-guess value.

- (4) Some PostScript implementations provide nonstandard facilities for the direct loading and execution of machine code. Such facilities are quite obviously open to substantial abuse. Message sending software should not make use of such features. Besides being totally hardware-specific, they are also likely to be unavailable in secure implementations of PostScript. Message receiving and displaying software should not allow such operators to be used if they exist.
- (5) PostScript is an extensible language, and many, if not most, implementations of it provide a number of their own extensions. This document does not deal with such extensions explicitly since they constitute an unknown factor. Message sending software should not make use of nonstandard extensions; they are likely to be missing from some implementations. Message receiving and displaying software should make sure that any nonstandard PostScript operators are secure and don't present any kind of threat.
- (6) It is possible to write PostScript that consumes huge amounts of various system resources. It is also possible to write PostScript programs that loop indefinitely. Both types of programs have the potential to cause damage if sent to unsuspecting recipients. Message-sending software should avoid the construction and dissemination of such programs, which is antisocial. Message receiving and displaying software should provide appropriate mechanisms to abort processing of a document after a reasonable amount of time has elapsed. In addition, PostScript interpreters should be limited to the consumption of only a reasonable amount of any given system resource.

Internet Draft

Media Types

January 1996

- (7) It is possible to include raw binary information inside PostScript in various forms. This is not recommended for use in Internet mail, both because it is not supported by all PostScript interpreters and because it significantly complicates the use of a MIME Content-Transfer-Encoding. (Without such binary, PostScript may typically be viewed as line-oriented data. The treatment of CRLF sequences becomes extremely problematic if binary and line-oriented data are mixed in a single Postscript data stream.)
- (8) Finally, bugs may exist in some PostScript interpreters which could possibly be exploited to gain unauthorized access to a recipient's system. Apart from noting this possibility, there is no specific action to take to prevent this, apart from the timely correction of such bugs if any are found.

[6.5.3.](#) Other Application Subtypes

It is expected that many other subtypes of application will be defined in the future. MIME implementations must at a minimum treat any unrecognized subtypes as being equivalent to "application/octet-stream".

[7.](#) Composite Media Type Values

The remaining two of the seven initial Content-Type values refer to composite entities. Composite entities are handled using MIME mechanisms -- a MIME processor typically handles the body directly.

[7.1.](#) Multipart Media Type

In the case of multipart entities, in which one or more different sets of data are combined in a single body, a "multipart" media type field must appear in the entity's header. The body must then contain one or more body parts, each preceded by a boundary delimiter line, and the last one

followed by a closing boundary delimiter line. After its boundary delimiter line, each body part then consists of a

Expires July 1996

[Page 19]

Internet Draft

Media Types

January 1996

header area, a blank line, and a body area. Thus a body part is similar to an [RFC 822](#) message in syntax, but different in meaning.

A body part is an entity and hence is NOT to be interpreted as actually being an [RFC 822](#) message. To begin with, NO header fields are actually required in body parts. A body part that starts with a blank line, therefore, is allowed and is a body part for which all default values are to be assumed. In such a case, the absence of a Content-Type header usually indicates that the corresponding body has a content-type of "text/plain; charset=US-ASCII".

The only header fields that have defined meaning for body parts are those the names of which begin with "Content-". All other header fields may be ignored in body parts. Although they should generally be retained if at all possible, they may be discarded by gateways if necessary. Such other fields are permitted to appear in body parts but must not be depended on. "X-" fields may be created for experimental or private purposes, with the recognition that the information they contain may be lost at some gateways.

NOTE: The distinction between an [RFC 822](#) message and a body part is subtle, but important. A gateway between Internet and [X.400](#) mail, for example, must be able to tell the difference between a body part that contains an image and a body part that contains an encapsulated message, the body of which is a JPEG image. In order to represent the latter, the body part must have "Content-Type: message/rfc822", and its body (after the blank line) must be the encapsulated message, with its own "Content-Type: image/jpeg" header field. The use of similar syntax facilitates the conversion of messages to body parts, and vice versa, but the distinction between the two must be understood by implementors. (For the special case in which parts actually are messages, a "digest" subtype is also defined.)

As stated previously, each body part is preceded by a boundary delimiter line that contains the boundary delimiter. The boundary delimiter MUST NOT appear inside any of the encapsulated parts, on a line by itself or as the prefix of any line. This implies that it is crucial that the composing agent be able to choose and specify a unique boundary parameter value that does not contain the boundary parameter

Expires July 1996

[Page 20]

Internet Draft

Media Types

January 1996

value of an enclosing multipart as a prefix.

All present and future subtypes of the "multipart" type must use an identical syntax. Subtypes may differ in their semantics, and may impose additional restrictions on syntax, but must conform to the required syntax for the multipart type. This requirement ensures that all conformant user agents will at least be able to recognize and separate the parts of any multipart entity, even those of an unrecognized subtype.

As stated in the definition of the Content-Transfer-Encoding field [MIME-IMB], no encoding other than "7bit", "8bit", or "binary" is permitted for entities of type "multipart". The multipart boundary delimiters and header fields are always represented as 7bit US-ASCII in any case (though the header fields may encode non-US-ASCII header text as per RFC MIME-HEADERS) and data within the body parts can be encoded on a part-by-part basis, with Content-Transfer-Encoding fields for each appropriate body part.

[7.1.1.1.](#) Common Syntax

This section defines a common syntax for subtypes of multipart. All subtypes of multipart must use this syntax. A simple example of a multipart message also appears in this section. An example of a more complex multipart message is given in RFC MIME-CONF.

The Content-Type field for multipart entities requires one

parameter, "boundary". The boundary delimiter line is then defined as a line consisting entirely of two hyphen characters ("-", decimal value 45) followed by the boundary parameter value from the Content-Type header field, optional linear whitespace, and a terminating CRLF.

NOTE: The hyphens are for rough compatibility with the earlier [RFC 934](#) method of message encapsulation, and for ease of searching for the boundaries in some implementations. However, it should be noted that multipart messages are NOT completely compatible with [RFC 934](#) encapsulations; in particular, they do not obey [RFC 934](#) quoting conventions for embedded lines that begin with hyphens. This mechanism was chosen over the [RFC 934](#) mechanism because the latter causes

Expires July 1996

[Page 21]

Internet Draft

Media Types

January 1996

lines to grow with each level of quoting. The combination of this growth with the fact that SMTP implementations sometimes wrap long lines made the [RFC 934](#) mechanism unsuitable for use in the event that deeply-nested multipart structuring is ever desired.

WARNING TO IMPLEMENTORS: The grammar for parameters on the Content-type field is such that it is often necessary to enclose the boundary parameter values in quotes on the Content-type line. This is not always necessary, but never hurts. Implementors should be sure to study the grammar carefully in order to avoid producing invalid Content-type fields. Thus, a typical multipart Content-Type header field might look like this:

```
Content-Type: multipart/mixed; boundary=gc0p4Jq0M2Yt08j34c0p
```

But the following is not valid:

```
Content-Type: multipart/mixed; boundary=gc0pJq0M:08jU534c0p
```

(because of the colon) and must instead be represented as

```
Content-Type: multipart/mixed; boundary="gc0pJq0M:08jU534c0p"
```

This Content-Type value indicates that the content consists of one or more parts, each with a structure that is syntactically identical to an [RFC 822](#) message, except that the header area is allowed to be completely empty, and that the parts are each preceded by the line

--gc0pJq0M:08jU534c0p

The boundary delimiter MUST occur at the beginning of a line, i.e., following a CRLF, and the initial CRLF is considered to be attached to the boundary delimiter line rather than part of the preceding part. The boundary may be followed by zero or more characters of linear whitespace. It is then terminated by either another CRLF and the header fields for the next part, or by two CRLFs, in which case there are no header fields for the next part. If no Content-Type field is present it is assumed to be of message/rfc822 in a multipart/digest and text/plain otherwise.

Expires July 1996

[Page 22]

Internet Draft

Media Types

January 1996

NOTE: The CRLF preceding the boundary delimiter line is conceptually attached to the boundary so that it is possible to have a part that does not end with a CRLF (line break). Body parts that must be considered to end with line breaks, therefore, must have two CRLFs preceding the boundary delimiter line, the first of which is part of the preceding body part, and the second of which is part of the encapsulation boundary.

Boundary delimiters must not appear within the encapsulated material, and must be no longer than 70 characters, not counting the two leading hyphens.

The boundary delimiter line following the last body part is a distinguished delimiter that indicates that no further body parts will follow. Such a delimiter line is identical to the previous delimiter lines, with the addition of two more hyphens after the boundary parameter value.

--gc0pJq0M:08jU534c0p--

NOTE TO IMPLEMENTORS: Boundary string comparisons must compare the boundary value with the beginning of each candidate line. An exact match of the entire candidate line is not required; it is sufficient that the boundary appear in its entirety following the CRLF.

There appears to be room for additional information prior to the first boundary delimiter line and following the final boundary delimiter line. These areas should generally be left blank, and implementations must ignore anything that appears before the first boundary delimiter line or after the last one.

NOTE: These "preamble" and "epilogue" areas are generally not used because of the lack of proper typing of these parts and the lack of clear semantics for handling these areas at gateways, particularly X.400 gateways. However, rather than leaving the preamble area blank, many MIME implementations have found this to be a convenient place to insert an explanatory note for recipients who read the message with pre-MIME software, since such notes will be ignored by MIME-compliant software.

Expires July 1996

[Page 23]

Internet Draft

Media Types

January 1996

NOTE: Because boundary delimiters must not appear in the body parts being encapsulated, a user agent must exercise care to choose a unique boundary parameter value. The boundary parameter value in the example above could have been the result of an algorithm designed to produce boundary delimiters with a very low probability of already existing in the data to be encapsulated without having to prescan the data. Alternate algorithms might result in more "readable" boundary delimiters for a recipient with an old user agent, but would require more attention to the possibility that the boundary delimiter might appear at the beginning of some line in the encapsulated part. The simplest boundary delimiter line possible is something like "---", with a closing boundary delimiter line of "-----".

As a very simple example, the following multipart message has two parts, both of them plain text, one of them explicitly typed and one of them implicitly typed:

```
From: Nathaniel Borenstein <nsb@bellcore.com>
To: Ned Freed <ned@innosoft.com>
Date: Sun, 21 Mar 1993 23:56:48 -0800 (PST)
Subject: Sample message
MIME-Version: 1.0
Content-type: multipart/mixed; boundary="simple boundary"
```

This is the preamble. It is to be ignored, though it is a handy place for composition agents to include an explanatory note to non-MIME conformant readers.

--simple boundary

This is implicitly typed plain US-ASCII text.
It does NOT end with a linebreak.

--simple boundary

Content-type: text/plain; charset=us-ascii

This is explicitly typed plain US-ASCII text.
It DOES end with a linebreak.

--simple boundary--

This is the epilogue. It is also to be ignored.

The use of a media type of multipart in a body part within another multipart entity is explicitly allowed. In such

cases, for obvious reasons, care must be taken to ensure that each nested multipart entity uses a different boundary delimiter. See RFC MIME-CONF for an example of nested multipart entities.

The use of the multipart media type with only a single body part may be useful in certain contexts, and is explicitly

permitted.

NOTE: Experience has shown that a multipart media type with a single body part is useful for sending non-text media types. It has the advantage of providing the preamble as a place to include decoding instructions. In addition, a number of SMTP gateways move or remove the MIME headers, and a clever MIME decoder can take a good guess at multipart boundaries even in the absence of the Content-Type header and thereby successfully decode the message.

The only mandatory global parameter for the multipart media type is the boundary parameter, which consists of 1 to 70 characters from a set of characters known to be very robust through mail gateways, and NOT ending with white space. (If a boundary delimiter line appears to end with white space, the white space must be presumed to have been added by a gateway, and must be deleted.) It is formally specified by the following BNF:

```
boundary := 0*69<bchars> bcharsnospace
```

```
bchars := bcharsnospace / " "
```

```
bcharsnospace := DIGIT / ALPHA / "'" / "(" / ")" /  
                "+" / "_" / "," / "-" / "." /  
                "/" / ":" / "=" / "?"
```

Overall, the body of a multipart entity may be specified as follows:

```
dash-boundary := "--" boundary  
                ; boundary taken from the value of  
                ; boundary parameter of the  
                ; Content-Type field.
```

```
multipart-body := [preamble CRLF]
```

```
dash-boundary transport-padding CRLF
body-part *encapsulation
close-delimiter transport-padding
[CRLF epilogue]
```

```
transport-padding := *LWSP-char
                    ; Composers MUST NOT generate
                    ; non-zero length transport
                    ; padding, but receivers MUST
                    ; be able to handle padding
                    ; added by message transports.
```

```
encapsulation := delimiter transport-padding
                CRLF body-part
```

```
delimiter := CRLF dash-boundary
```

```
close-delimiter := delimiter "--"
```

```
preamble := discard-text
```

```
epilogue := discard-text
```

```
discard-text := *(*text CRLF) *text
               ; May be ignored or discarded.
```

```
body-part := MIME-part-headers [CRLF *OCTET]
            ; Lines in a body-part must not start
            ; with the specified dash-boundary and
            ; the delimiter must not appear anywhere
            ; in the body part. Note that the
            ; semantics of a body-part differ from
            ; the semantics of a message, as
            ; described in the text.
```

```
OCTET := <any 0-255 octet value>
```

IMPORTANT: The free insertion of linear-white-space and RFC [822](#) comments between the elements shown in this BNF is NOT allowed since this BNF does not specify a structured header field.

NOTE: In certain transport enclaves, [RFC 822](#) restrictions such as the one that limits bodies to printable US-ASCII

characters may not be in force. (That is, the transport domains may exist that resemble standard Internet mail transport as specified in [RFC 821](#) and assumed by [RFC 822](#), but without certain restrictions.) The relaxation of these restrictions should be construed as locally extending the definition of bodies, for example to include octets outside of the US-ASCII range, as long as these extensions are supported by the transport and adequately documented in the Content-Transfer-Encoding header field. However, in no event are headers (either message headers or body part headers) allowed to contain anything other than US-ASCII characters.

NOTE: Conspicuously missing from the multipart type is a notion of structured, related body parts. It is recommended that those wishing to provide more structured or integrated multipart messaging facilities should define subtypes of multipart that are syntactically identical but define relationships between the various parts. For example, subtypes of multipart could be defined that include a distinguished part which in turn is used to specify the relationships between the other parts, probably referring to them by their Content-ID field. Old implementations will not recognize the new subtype if this approach is used, but will treat it as multipart/mixed and will thus be able to show the user the parts that are recognized.

[7.1.2.](#) Handling Nested Messages and Multiparts

The "message/rfc822" subtype defined in a subsequent section of this document has no terminating condition other than running out of data. Similarly, an improperly truncated multipart entity may not have any terminating boundary marker, and can turn up operationally due to mail system malfunctions.

It is essential that such entities be handled correctly when they are themselves imbedded inside of another multipart structure. MIME implementations are therefore required to recognize outer level boundary markers at ANY level of inner nesting. It is not sufficient to only check for the next expected marker or other terminating condition.

Internet Draft

Media Types

January 1996

[7.1.3.](#) Mixed Subtype

The "mixed" subtype of multipart is intended for use when the body parts are independent and need to be bundled in a particular order. Any multipart subtypes that an implementation does not recognize must be treated as being of subtype "mixed".

[7.1.4.](#) Alternative Subtype

The multipart/alternative type is syntactically identical to multipart/mixed, but the semantics are different. In particular, each of the body parts is an "alternative" version of the same information.

Systems should recognize that the content of the various parts are interchangeable. Systems should choose the "best" type based on the local environment and references, in some cases even through user interaction. As with multipart/mixed, the order of body parts is significant. In this case, the alternatives appear in an order of increasing faithfulness to the original content. In general, the best choice is the LAST part of a type supported by the recipient system's local environment.

Multipart/alternative may be used, for example, to send a message in a fancy text format in such a way that it can easily be displayed anywhere:

Internet Draft

Media Types

January 1996

From: Nathaniel Borenstein <nsb@bellcore.com>
To: Ned Freed <ned@innosoft.com>
Date: Mon, 22 Mar 1993 09:41:09 -0800 (PST)
Subject: Formatted text mail
MIME-Version: 1.0
Content-Type: multipart/alternative; boundary=boundary42

--boundary42

Content-Type: text/plain; charset=us-ascii

... plain text version of message goes here ...

--boundary42

Content-Type: text/enriched

... [RFC 1563](#) text/enriched version of same message
goes here ...

--boundary42

Content-Type: application/x-whatever

... fanciest version of same message goes here ...

--boundary42--

In this example, users whose mail systems understood the "application/x-whatever" format would see only the fancy version, while other users would see only the enriched or plain text version, depending on the capabilities of their system.

In general, user agents that compose multipart/alternative entities must place the body parts in increasing order of preference, that is, with the preferred format last. For fancy text, the sending user agent should put the plainest

format first and the richest format last. Receiving user agents should pick and display the last format they are capable of displaying. In the case where one of the alternatives is itself of type "multipart" and contains unrecognized sub-parts, the user agent may choose either to show that alternative, an earlier alternative, or both.

NOTE: From an implementor's perspective, it might seem more sensible to reverse this ordering, and have the plainest alternative last. However, placing the plainest alternative

Expires July 1996

[Page 29]

Internet Draft

Media Types

January 1996

first is the friendliest possible option when multipart/alternative entities are viewed using a non-MIME-conformant viewer. While this approach does impose some burden on conformant MIME viewers, interoperability with older mail readers was deemed to be more important in this case.

It may be the case that some user agents, if they can recognize more than one of the formats, will prefer to offer the user the choice of which format to view. This makes sense, for example, if a message includes both a nicely-formatted image version and an easily-edited text version. What is most critical, however, is that the user not automatically be shown multiple versions of the same data. Either the user should be shown the last recognized version or should be given the choice.

THE SEMANTICS OF CONTENT-ID IN MULTIPART/ALTERNATIVE: Each part of a multipart/alternative entity represents the same data, but the mappings between the two are not necessarily without information loss. For example, information is lost when translating ODA to PostScript or plain text. It is recommended that each part should have a different Content-ID value in the case where the information content of the two parts is not identical. And when the information content is identical -- for example, where several parts of type "message/external-body" specify alternate ways to access the identical data -- the same Content-ID field value should be used, to optimize any caching mechanisms that might be present on the recipient's end. However, the Content-ID values used

by the parts should NOT be the same Content-ID value that describes the multipart/alternative as a whole, if there is any such Content-ID field. That is, one Content-ID value will refer to the multipart/alternative entity, while one or more other Content-ID values will refer to the parts inside it.

[7.1.5.](#) Digest Subtype

This document defines a "digest" subtype of the multipart Content-Type. This type is syntactically identical to multipart/mixed, but the semantics are different. In particular, in a digest, the default Content-Type value for a body part is changed from "text/plain" to "message/rfc822". This is done to allow a more readable digest format that is largely compatible (except for the quoting convention) with

Expires July 1996

[Page 30]

Internet Draft

Media Types

January 1996

[RFC 934.](#)

Note: Though it is possible to specify a Content-Type value for a body part in a digest which is other than "message/rfc822", such as a text/plain part containing a description of the material in the digest, actually doing so is undesirable. The "multipart/digest" Content-Type is intended to be used to send collections of messages. If a "text/plain" part is needed, it should be included as a separate part of a "multipart/mixed" message.

A digest in this format might, then, look something like this:

```
From: Moderator-Address
To: Recipient-List
Date: Mon, 22 Mar 1994 13:34:51 +0000
Subject: Internet Digest, volume 42
MIME-Version: 1.0
Content-Type: multipart/mixed;
              boundary="---- main boundary ----"
```

```
----- main boundary ----
```

...Introductory text or table of contents...

----- main boundary ----
Content-Type: multipart/digest;
 boundary="----- next message ----"

----- next message ----

From: someone-else
Date: Fri, 26 Mar 1993 11:13:32 +0200
Subject: my opinion

...body goes here ...

----- next message ----

From: someone-else-again
Date: Fri, 26 Mar 1993 10:07:13 -0500
Subject: my different opinion

... another body goes here ...

Expires July 1996

[Page 31]

Internet Draft

Media Types

January 1996

----- next message -----

----- main boundary -----

[7.1.6.](#) Parallel Subtype

This document defines a "parallel" subtype of the multipart Content-Type. This type is syntactically identical to multipart/mixed, but the semantics are different. In particular, in a parallel entity, the order of body parts is not significant.

A common presentation of this type is to display all of the parts simultaneously on hardware and software that are capable of doing so. However, composing agents should be aware that many mail readers will lack this capability and will show the

parts serially in any event.

[7.1.7.](#) Other Multipart Subtypes

Other multipart subtypes are expected in the future. MIME implementations must in general treat unrecognized subtypes of multipart as being equivalent to "multipart/mixed".

[7.2.](#) Message Media Type

It is frequently desirable, in sending mail, to encapsulate another mail message. A special media type, "message", is defined to facilitate this. In particular, the "[rfc822](#)" subtype of "message" is used to encapsulate [RFC 822](#) messages.

NOTE: It has been suggested that subtypes of message might be defined for forwarded or rejected messages. However, forwarded and rejected messages can be handled as multipart messages in which the first part contains any control or descriptive information, and a second part, of type message/rfc822, is the forwarded or rejected message. Composing rejection and forwarding messages in this manner will preserve the type information on the original message and allow it to be correctly presented to the recipient, and hence is strongly encouraged.

Subtypes of message often impose restrictions on what encodings are allowed. These restrictions are described in conjunction with each specific subtype.

Mail gateways, relays, and other mail handling agents are commonly known to alter the top-level header of an [RFC 822](#) message. In particular, they frequently add, remove, or reorder header fields. These operations are explicitly forbidden for the encapsulated headers embedded in the bodies of messages of type "message."

[7.2.1.](#) [RFC822](#) Subtype

A media type of "message/rfc822" indicates that the body contains an encapsulated message, with the syntax of an [RFC 822](#) message. However, unlike top-level [RFC 822](#) messages, the restriction that each message/rfc822 body must include a "From", "Date", and at least one destination header is removed and replaced with the requirement that at least one of "From", "Subject", or "Date" must be present.

It should be noted that, despite the use of the numbers "822", a message/rfc822 entity isn't restricted to material in strict conformance to [RFC822](#). Such entities can also include enhanced information as defined in this document. In other words, a message/rfc822 message could well be a News article or a MIME message.

No encoding other than "7bit", "8bit", or "binary" is permitted for the body of a "message/rfc822" entity. The message header fields are always US-ASCII in any case, and data within the body can still be encoded, in which case the Content-Transfer-Encoding header field in the encapsulated message will reflect this. Non-US-ASCII text in the headers of an encapsulated message can be specified using the mechanisms described in RFC MIME-HEADERS.

[7.2.2.](#) Partial Subtype

The "partial" subtype is defined to allow large entities to be delivered as several separate pieces of mail and automatically reassembled by a receiving user agent. (The concept is similar to IP fragmentation and reassembly in the basic

Internet Protocols.) This mechanism can be used when intermediate transport agents limit the size of individual messages that can be sent. The media type "message/partial" thus indicates that the body contains a fragment of a larger entity.

Because data of type "message" may never be encoded in base64 or quoted-printable, a problem might arise if message/partial entities are constructed in an environment that supports binary or 8bit transport. The problem is that the binary data would be split into multiple message/partial messages, each of them requiring binary transport. If such messages were encountered at a gateway into a 7bit transport environment, there would be no way to properly encode them for the 7bit world, aside from waiting for all of the fragments, reassembling the inner message, and then encoding the reassembled data in base64 or quoted-printable. Since it is possible that different fragments might go through different gateways, even this is not an acceptable solution. For this reason, it is specified that entities of type message/partial must always have a content-transfer-encoding of 7bit (the default). In particular, even in environments that support binary or 8bit transport, the use of a content-transfer-encoding of "8bit" or "binary" is explicitly prohibited for MIME entities of type message/partial. This in turn implies that the inner message must not use "8bit" or "binary" encoding.

Because some message transfer agents may choose to automatically fragment large messages, and because such agents may use very different fragmentation thresholds, it is possible that the pieces of a partial message, upon reassembly, may prove themselves to comprise a partial message. This is explicitly permitted.

Three parameters must be specified in the Content-Type field of type message/partial: The first, "id", is a unique identifier, as close to a world-unique identifier as possible, to be used to match the fragments together. (In general, the identifier is essentially a message-id; if placed in double quotes, it can be ANY message-id, in accordance with the BNF for "parameter" given earlier in this specification.) The second, "number", an integer, is the fragment number, which indicates where this fragment fits into the sequence of fragments. The third, "total", another integer, is the total

number of fragments. This third subfield is required on the final fragment, and is optional (though encouraged) on the earlier fragments. Note also that these parameters may be given in any order.

Thus, the second piece of a 3-piece message may have either of the following header fields:

```
Content-Type: Message/Partial; number=2; total=3;
             id="oc=jpbe0M2Yt4s@thumper.bellcore.com"
```

```
Content-Type: Message/Partial;
             id="oc=jpbe0M2Yt4s@thumper.bellcore.com";
             number=2
```

But the third piece MUST specify the total number of fragments:

```
Content-Type: Message/Partial; number=3; total=3;
             id="oc=jpbe0M2Yt4s@thumper.bellcore.com"
```

Note that fragment numbering begins with 1, not 0.

When the fragments of an entity broken up in this manner are put together, the result is always a complete MIME entity, which may have its own Content-Type header field, and thus may contain any other data type.

[7.2.2.1](#). Message Fragmentation and Reassembly

The semantics of a reassembled partial message must be those of the "inner" message, rather than of a message containing the inner message. This makes it possible, for example, to send a large audio message as several partial messages, and still have it appear to the recipient as a simple audio message rather than as an encapsulated message containing an audio message. That is, the encapsulation of the message is considered to be "transparent".

When generating and reassembling the pieces of a message/partial message, the headers of the encapsulated message must be merged with the headers of the enclosing entities. In this process the following rules must be observed:

Internet Draft

Media Types

January 1996

- (1) All of the header fields from the initial enclosing message, except those that start with "Content-" and the specific header fields "Subject", "Message-ID", "Encrypted", and "MIME-Version", must be copied, in order, to the new message.
- (2) The header fields in the enclosed message which start with "Content-", plus the "Subject", "Message-ID", "Encrypted", and "MIME-Version" fields, must be appended, in order, to the header fields of the new message. Any header fields in the enclosed message which do not start with "Content-" (except for the "Subject", "Message-ID", "Encrypted", and "MIME-Version" fields) will be ignored and dropped.
- (3) All of the header fields from the second and any subsequent enclosing messages are discarded by the reassembly process.

[7.2.2.2](#). Fragmentation and Reassembly Example

If an audio message is broken into two pieces, the first piece might look something like this:

```
X-Weird-Header-1: Foo
From: Bill@host.com
To: joe@otherhost.com
Date: Fri, 26 Mar 1993 12:59:38 -0500 (EST)
Subject: Audio mail (part 1 of 2)
Message-ID: <id1@host.com>
MIME-Version: 1.0
Content-type: message/partial; id="ABC@host.com";
            number=1; total=2
```

```
X-Weird-Header-1: Bar
X-Weird-Header-2: Hello
Message-ID: <anotherid@foo.com>
Subject: Audio mail
MIME-Version: 1.0
Content-type: audio/basic
Content-transfer-encoding: base64
```

... first half of encoded audio data goes here ...

Expires July 1996

[Page 36]

Internet Draft

Media Types

January 1996

and the second half might look something like this:

```
From: Bill@host.com
To: joe@otherhost.com
Date: Fri, 26 Mar 1993 12:59:38 -0500 (EST)
Subject: Audio mail (part 2 of 2)
MIME-Version: 1.0
Message-ID: <id2@host.com>
Content-type: message/partial;
            id="ABC@host.com"; number=2; total=2
```

... second half of encoded audio data goes here ...

Then, when the fragmented message is reassembled, the resulting message to be displayed to the user should look something like this:

```
X-Weird-Header-1: Foo
From: Bill@host.com
To: joe@otherhost.com
Date: Fri, 26 Mar 1993 12:59:38 -0500 (EST)
Subject: Audio mail
Message-ID: <anotherid@foo.com>
MIME-Version: 1.0
Content-type: audio/basic
Content-transfer-encoding: base64
```

... first half of encoded audio data goes here ...

... second half of encoded audio data goes here ...

The inclusion of a "References" field in the headers of the second and subsequent pieces of a fragmented message that references the Message-Id on the previous piece may be of benefit to mail readers that understand and track references. However, the generation of such "References" fields is entirely optional.

Finally, it should be noted that the "Encrypted" header field has been made obsolete by Privacy Enhanced Messaging (PEM) [RFC1421, [RFC1422](#), [RFC1423](#), and [RFC1424](#)], but the rules above are nevertheless believed to describe the correct way to treat it if it is encountered in the context of conversion to and from message/partial fragments.

Expires July 1996

[Page 37]

Internet Draft

Media Types

January 1996

[7.2.3](#). External-Body Subtype

The external-body subtype indicates that the actual body data are not included, but merely referenced. In this case, the parameters describe a mechanism for accessing the external data.

When a MIME entity is of type "message/external-body", it consists of a header, two consecutive CRLFs, and the message header for the encapsulated message. If another pair of consecutive CRLFs appears, this of course ends the message header for the encapsulated message. However, since the encapsulated message's body is itself external, it does NOT appear in the area that follows. For example, consider the following message:

```
Content-type: message/external-body;  
              access-type=local-file;  
              name="/u/nsb/Me.jpeg"
```

```
Content-type: image/jpeg  
Content-ID: <id42@guppylake.bellcore.com>  
Content-Transfer-Encoding: binary
```

THIS IS NOT REALLY THE BODY!

The area at the end, which might be called the "phantom body", is ignored for most external-body messages. However, it may be used to contain auxiliary information for some such messages, as indeed it is when the access-type is "mail-server". The only access-type defined in this document that

uses the phantom body is "mail-server", but other access-types may be defined in the future in other documents that use this area.

The encapsulated headers in ALL message/external-body entities MUST include a Content-ID header field to give a unique identifier by which to reference the data. This identifier may be used for caching mechanisms, and for recognizing the receipt of the data when the access-type is "mail-server".

Note that, as specified here, the tokens that describe external-body data, such as file names and mail server commands, are required to be in the US-ASCII character set. If this proves problematic in practice, a new mechanism may be

Expires July 1996

[Page 38]

Internet Draft

Media Types

January 1996

required as a future extension to MIME, either as newly defined access-types for message/external-body or by some other mechanism.

As with message/partial, MIME entities of type message/external-body MUST have a content-transfer-encoding of 7bit (the default). In particular, even in environments that support binary or 8bit transport, the use of a content-transfer-encoding of "8bit" or "binary" is explicitly prohibited for entities of type message/external-body.

[7.2.3.1](#). General External-Body Parameters

The parameters that may be used with any message/external-body are:

- (1) ACCESS-TYPE -- A word indicating the supported access mechanism by which the file or data may be obtained. This word is not case sensitive. Values include, but are not limited to, "FTP", "ANON-FTP", "TFTP", "LOCAL-FILE", and "MAIL-SERVER". Future values, except for experimental values beginning with "X-", must be registered with IANA, as described in RFC MIME-REG. This parameter is unconditionally mandatory and MUST be

present on EVERY message/external-body.

- (2) EXPIRATION -- The date (in the [RFC 822](#) "date-time" syntax, as extended by [RFC 1123](#) to permit 4 digits in the year field) after which the existence of the external data is not guaranteed. This parameter may be used with ANY access-type and is ALWAYS optional.
- (3) SIZE -- The size (in octets) of the data. The intent of this parameter is to help the recipient decide whether or not to expend the necessary resources to retrieve the external data. Note that this describes the size of the data in its canonical form, that is, before any Content-Transfer-Encoding has been applied or after the data have been decoded. This parameter may be used with ANY access-type and is ALWAYS optional.
- (4) PERMISSION -- A case-insensitive field that indicates whether or not it is expected that clients might also

Expires July 1996

[Page 39]

Internet Draft

Media Types

January 1996

attempt to overwrite the data. By default, or if permission is "read", the assumption is that they are not, and that if the data is retrieved once, it is never needed again. If PERMISSION is "read-write", this assumption is invalid, and any local copy must be considered no more than a cache. "Read" and "Read-write" are the only defined values of permission. This parameter may be used with ANY access-type and is ALWAYS optional.

The precise semantics of the access-types defined here are described in the sections that follow.

[7.2.3.2](#). The 'ftp' and 'tftp' Access-Types

An access-type of FTP or TFTP indicates that the message body is accessible as a file using the FTP [[RFC-959](#)] or TFTP [[RFC-783](#)] protocols, respectively. For these access-types, the

following additional parameters are mandatory:

- (1) NAME -- The name of the file that contains the actual body data.
- (2) SITE -- A machine from which the file may be obtained, using the given protocol. This must be a fully qualified domain name, not a nickname.
- (3) Before any data are retrieved, using FTP, the user will generally need to be asked to provide a login id and a password for the machine named by the site parameter. For security reasons, such an id and password are not specified as content-type parameters, but must be obtained from the user.

In addition, the following parameters are optional:

- (1) DIRECTORY -- A directory from which the data named by NAME should be retrieved.
- (2) MODE -- A case-insensitive string indicating the mode to be used when retrieving the information. The valid values for access-type "TFTP" are "NETASCII", "OCTET", and "MAIL", as specified by the TFTP protocol [RFC-783]. The valid values for access-type "FTP" are

Expires July 1996

[Page 40]

Internet Draft

Media Types

January 1996

"ASCII", "EBCDIC", "IMAGE", and "LOCALn" where "n" is a decimal integer, typically 8. These correspond to the representation types "A" "E" "I" and "L n" as specified by the FTP protocol [[RFC-959](#)]. Note that "BINARY" and "TENEX" are not valid values for MODE and that "OCTET" or "IMAGE" or "LOCAL8" should be used instead. IF MODE is not specified, the default value is "NETASCII" for TFTP and "ASCII" otherwise.

7.2.3.3. The 'anon-ftp' Access-Type

The "anon-ftp" access-type is identical to the "ftp" access

type, except that the user need not be asked to provide a name and password for the specified site. Instead, the ftp protocol will be used with login "anonymous" and a password that corresponds to the user's mail address.

[7.2.3.4.](#) The 'local-file' Access-Type

An access-type of "local-file" indicates that the actual body is accessible as a file on the local machine. Two additional parameters are defined for this access type:

- (1) NAME -- The name of the file that contains the actual body data. This parameter is mandatory for the "local-file" access-type.
- (2) SITE -- A domain specifier for a machine or set of machines that are known to have access to the data file. This optional parameter is used to describe the locality of reference for the data, that is, the site or sites at which the file is expected to be visible. Asterisks may be used for wildcard matching to a part of a domain name, such as "*.bellcore.com", to indicate a set of machines on which the data should be directly visible, while a single asterisk may be used to indicate a file that is expected to be universally available, e.g., via a global file system.

[7.2.3.5.](#) The 'mail-server' Access-Type

The "mail-server" access-type indicates that the actual body is available from a mail server. Two additional parameters are defined for this access-type:

- (1) SERVER -- The addr-spec of the mail server from which

the actual body data can be obtained. This parameter is mandatory for the "mail-server" access-type.

- (2) SUBJECT -- The subject that is to be used in the mail that is sent to obtain the data. Note that keying mail servers on Subject lines is NOT recommended, but such mail servers are known to exist. This is an optional parameter.

Because mail servers accept a variety of syntaxes, some of which is multiline, the full command to be sent to a mail server is not included as a parameter in the content-type header field. Instead, it is provided as the "phantom body" when the media type is message/external-body and the access-type is mail-server.

Note that MIME does not define a mail server syntax. Rather, it allows the inclusion of arbitrary mail server commands in the phantom body. Implementations must include the phantom body in the body of the message it sends to the mail server address to retrieve the relevant data.

Unlike other access-types, mail-server access is asynchronous and will happen at an unpredictable time in the future. For this reason, it is important that there be a mechanism by which the returned data can be matched up with the original message/external-body entity. MIME mail servers must use the same Content-ID field on the returned message that was used in the original message/external-body entities, to facilitate such matching.

[7.2.3.6](#). External-Body Security Issues

Message/external-body entities give rise to two important security issues:

- (1) Accessing data via a message/external-body reference

effectively results in the message recipient performing an operation that was specified by the message originator. It is therefore possible for the message originator to trick a recipient into doing something they would not have done otherwise. For example, an originator could specify an action that attempts retrieval of material that the recipient is not authorized to obtain, causing the recipient to unwittingly violate some security policy. For this reason, user agents capable of resolving external references must always take steps to describe the action they are to take to the recipient and ask for explicit permission prior to performing it.

The 'mail-server' access-type is particularly vulnerable, in that it causes the recipient to send a new message whose contents are specified by the original message's originator. Given the potential for abuse, any such request messages that are constructed should contain a clear indication that they were generated automatically (e.g. in a Comments: header field) in an attempt to resolve a MIME message/external-body reference.

- (2) MIME will sometimes be used in environments that provide some guarantee of message integrity and authenticity. If present, such guarantees may apply only to the actual direct content of messages -- they may or may not apply to data accessed through MIME's message/external-body mechanism. In particular, it may be possible to subvert certain access mechanisms even when the messaging system itself is secure.

It should be noted that this problem exists either with or without the availability of MIME mechanisms. A casual reference to an FTP site containing a document in the text of a secure message brings up similar issues -- the only difference is that MIME provides for automatic retrieval of such material, and users may place unwarranted trust in such automatic retrieval mechanisms.

[7.2.3.7.](#) Examples and Further Explanations

When the external-body mechanism is used in conjunction with the multipart/alternative media type it extends the functionality of multipart/alternative to include the case where the same entity is provided in the same format but via different access mechanisms. When this is done the originator of the message must order the parts first in terms of preferred formats and then by preferred access mechanisms. The recipient's viewer should then evaluate the list both in terms of format and access mechanisms.

With the emerging possibility of very wide-area file systems, it becomes very hard to know in advance the set of machines where a file will and will not be accessible directly from the file system. Therefore it may make sense to provide both a file name, to be tried directly, and the name of one or more sites from which the file is known to be accessible. An implementation can try to retrieve remote files using FTP or any other protocol, using anonymous file retrieval or prompting the user for the necessary name and password. If an external body is accessible via multiple mechanisms, the sender may include multiple entities of type message/external-body within the body parts of an enclosing multipart/alternative entity.

However, the external-body mechanism is not intended to be limited to file retrieval, as shown by the mail-server access-type. Beyond this, one can imagine, for example, using a video server for external references to video clips.

The embedded message header fields which appear in the body of the message/external-body data must be used to declare the media type of the external body if it is anything other than plain US-ASCII text, since the external body does not have a header section to declare its type. Similarly, any Content-transfer-encoding other than "7bit" must also be declared here. Thus a complete message/external-body message, referring to a document in PostScript format, might look like this:

Internet Draft

Media Types

January 1996

From: Whomever
To: Someone
Date: Whenever
Subject: whatever
MIME-Version: 1.0
Message-ID: <id1@host.com>
Content-Type: multipart/alternative; boundary=42
Content-ID: <id001@guppylake.bellcore.com>

--42

Content-Type: message/external-body; name="BodyFormats.ps";
site="thumper.bellcore.com"; mode="image";
access-type=ANON-FTP; directory="pub";
expiration="Fri, 14 Jun 1991 19:13:14 -0400 (EDT)"

Content-type: application/postscript
Content-ID: <id42@guppylake.bellcore.com>

--42

Content-Type: message/external-body; access-type=local-file;
name="/u/nsb/writing/rfcs/RFC-MIME.ps";
site="thumper.bellcore.com";
expiration="Fri, 14 Jun 1991 19:13:14 -0400 (EDT)"

Content-type: application/postscript
Content-ID: <id42@guppylake.bellcore.com>

--42

Content-Type: message/external-body;
access-type=mail-server
server="listserv@bogus.bitnet";
expiration="Fri, 14 Jun 1991 19:13:14 -0400 (EDT)"

Content-type: application/postscript
Content-ID: <id42@guppylake.bellcore.com>

get RFC-MIME.DOC

--42--

Note that in the above examples, the default Content-

transfer-encoding of "7bit" is assumed for the external postscript data.

Expires July 1996

[Page 45]

Internet Draft

Media Types

January 1996

Like the message/partial type, the message/external-body media type is intended to be transparent, that is, to convey the data type in the external body rather than to convey a message with a body of that type. Thus the headers on the outer and inner parts must be merged using the same rules as for message/partial. In particular, this means that the Content-type and Subject fields are overridden, but the From field is preserved.

Note that since the external bodies are not transported along with the external body reference, they need not conform to transport limitations that apply to the reference itself. In particular, Internet mail transports may impose 7bit and line length limits, but these do not automatically apply to binary external body references. Thus a Content-Transfer-Encoding is not generally necessary, though it is permitted.

Note that the body of a message of type "message/external-body" is governed by the basic syntax for an [RFC 822](#) message. In particular, anything before the first consecutive pair of CRLFs is header information, while anything after it is body information, which is ignored for most access-types.

[7.2.4](#). Other Message Subtypes

MIME implementations must in general treat unrecognized subtypes of message as being equivalent to "application/octet-stream".

Future subtypes of message intended for use with email should be restricted to "7bit" encoding. A type other than message should be used if restriction to "7bit" is not possible.

8. Experimental Media Type Values

A media type value beginning with the characters "X-" is a private value, to be used by consenting systems by mutual agreement. Any format without a rigorous and public definition must be named with an "X-" prefix, and publicly specified values shall never begin with "X-". (Older versions of the widely used Andrew system use the "X-BE2" name, so new systems should probably choose a different name.)

Expires July 1996

[Page 46]

Internet Draft

Media Types

January 1996

In general, the use of "X-" top-level types is strongly discouraged. Implementors should invent subtypes of the existing types whenever possible. In many cases, a subtype of application will be more appropriate than a new top-level type.

9. Summary

The five discrete media types provide provide a standardized mechanism for tagging entities as audio, image, or several other kinds of data. The composite "multipart" and "message" media types allow mixing and hierarchical structuring of entities of different types in a single message. A distinguished parameter syntax allows further specification of data format details, particularly the specification of alternate character sets. Additional optional header fields provide mechanisms for certain extensions deemed desirable by many implementors. Finally, a number of useful media types are defined for general use by consenting user agents, notably message/partial, and message/external-body.

10. Security Considerations

Security issues are discussed in the context of the application/postscript type, the message/external-body type, and in RFC MIME-REG. Implementors should pay special attention to the security implications of any media types that

can cause the remote execution of any actions in the recipient's environment. In such cases, the discussion of the application/postscript type may serve as a model for considering other media types with remote execution capabilities.

Expires July 1996

[Page 47]

Internet Draft

Media Types

January 1996

[11](#). Authors' Addresses

For more information, the authors of this document are best contacted via Internet mail:

Nathaniel S. Borenstein
First Virtual Holdings
[25](#) Washington Avenue
Morristown, NJ 07960
USA

Email: nsb@nsb.fv.com
Phone: +1 201 540 8967
Fax: +1 201 993 3032

Ned Freed
Innosoft International, Inc.
[1050](#) East Garvey Avenue South
West Covina, CA 91790
USA

Email: ned@innosoft.com
Phone: +1 818 919 3600

Fax: +1 818 919 3614

MIME is a result of the work of the Internet Engineering Task Force Working Group on Email Extensions. The chairman of that group, Greg Vaudreuil, may be reached at:

Gregory M. Vaudreuil
Tigon Corporation
[17060](#) Dallas Parkway
Dallas Texas, 75248

Email: greg.vaudreuil@ons.octel.com
Phone: +1 214 733 2722

Expires July 1996

[Page 48]

Internet Draft

Media Types

January 1996

[Appendix A](#) -- Collected Grammar

This appendix contains the complete BNF grammar for all the syntax specified by this document.

By itself, however, this grammar is incomplete. It refers by name to several syntax rules that are defined by [RFC 822](#). Rather than reproduce those definitions here, and risk unintentional differences between the two, this document simply refers the reader to [RFC 822](#) for the remaining definitions. Wherever a term is undefined, it refers to the [RFC 822](#) definition.

boundary := 0*69<bchars> bcharsnospace

bchars := bcharsnospace / " "

bcharsnospace := DIGIT / ALPHA / "'" / "(" / ")" /
 "+" / "_" / "," / "-" / "." /
 "/" / ":" / "=" / "?"

body-part := <"message" as defined in [RFC 822](#), with all
 header fields optional, not starting with the
 specified dash-boundary, and with the
 delimiter not occurring anywhere in the
 body part. Note that the semantics of a
 part differ from the semantics of a message,
 as described in the text.>

close-delimiter := delimiter "--"

dash-boundary := "--" boundary
 ; boundary taken from the value of
 ; boundary parameter of the
 ; Content-Type field.

delimiter := CRLF dash-boundary

discard-text := *(text CRLF)
 ; May be ignored or discarded.

encapsulation := delimiter transport-padding
 CRLF body-part

epilogue := discard-text

multipart-body := [preamble CRLF]
 dash-boundary transport-padding CRLF
 body-part *encapsulation
 close-delimiter transport-padding
 [CRLF epilogue]

preamble := discard-text

transport-padding := *LWSP-char
; Composers MUST NOT generate
; non-zero length transport
; padding, but receivers MUST
; be able to handle padding
; added by message transports.