

AAA Working Group
INTERNET-DRAFT
Category: Informational
<[draft-ietf-aaa-na-reqts-02.txt](#)>
26 February 2000

Bernard Aboba, Microsoft
Pat R. Calhoun
Steven M. Glass
Sun Microsystems, Inc.
Tom Hiller
Pete McCann
Hajime Shiino
Lucent
Glen Zorn
Gopal Dommety
Cisco Systems, Inc.
Charles Perkins
Basavaraj Patil
Nokia Telecommunications
Dave Mitton
Serge Manning
Nortel Networks
Mark Beadles, SmartPipes Inc
Pat Walsh, Ameritech
Xing Chen, Alcatel
Takahiro Ayaki, DDI Corporation
Sanjeevan Sivalingham, Ericsson Wireless Communications
Alan Hameed, Fujitsu
Mark Munson, GTE Wireless
Stuart Jacobs, GTE Laboratories
Takuo Seki, IDO Corporation
Byng-Keun Lim, LG Information & Communications, Ltd.
Brent Hirschman, Motorola
Ray Hsu, Qualcomm, Inc.
Haeng Koo, Samsung Telecommunications America, Inc.
Mark Lipford, Sprint PCS
Yingchun Xu
Ed Campbell
3Com Corporation
Shinich Baba, Toshiba America Research, Inc.
Eric Jaques, Vodaphone Airtouch

Criteria for Evaluating AAA Protocols for Network Access

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet- Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any

time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

1. Copyright Notice

Copyright (C) The Internet Society (2000). All Rights Reserved.

2. Abstract

This document represents a summary of AAA protocol requirements for network access. In creating this documents, inputs were taken from documents produced by the NASREQ, ROAMOPS, and MOBILEIP working groups, as well as from TIA 45.6. This document summarizes the requirements collected from those sources, separating requirements for authentication, authorization and accounting. Details on the requirements are available in the original documents.

3. Change history

02 revision: added terminology definitions (largely taken from Mobile IP AAA requirements document), requirements clarifications. Many requirements eliminated as a result of feedback at the interim AAA WG meeting in San Jose. Created a General Requirements section for requirements relating to all elements of AAA. Updated references. Merged Mobile IP and TIA 45.6 requirements.

4. Introduction

This document represents a summary of AAA protocol requirements for network access. In creating this documents, inputs were taken from documents produced by the NASREQ, ROAMOPS, and MOBILEIP working groups, as well as from TIA 45.6. This document summarizes the requirements collected from those sources, separating requirements for authentication, authorization and accounting. Details on the requirements are available in the original documents.

4.1. Requirements language

In this document, the key words "MAY", "MUST", "MUST NOT", "optional", "recommended", "SHOULD", and "SHOULD NOT", are to be interpreted as described in [1].

Please note that the requirements specified in this document are to be used in evaluating AAA protocol submissions. As such, the requirements language refers to capabilities of these protocols; the protocol documents will specify whether these features are required, recommended, or optional. For example, requiring that a protocol support confidentiality is NOT the same thing as requiring that all protocol traffic be encrypted.

A protocol submission is not compliant if it fails to satisfy one or more of the MUST or MUST NOT requirements for the capabilities that it implements. A protocol submission that satisfies all the MUST, MUST NOT, SHOULD and SHOULD NOT requirements for its capabilities is said to be "unconditionally compliant"; one that satisfies all the MUST and MUST NOT requirements but not all the SHOULD or SHOULD NOT requirements for its protocols is said to be "conditionally compliant."

4.2. Terminology

Accounting

The act of collecting information on resource usage for the purpose of trend analysis, auditing, billing, or cost allocation.

Administrative Domain

An intranet, or a collection of networks, computers, and databases under a common administration. Computer entities operating in a common administration may be assumed to share administratively created security associations.

Attendant A node designed to provide the service interface between a client and the local domain.

Authentication

The act of verifying a claimed identity, in the form of a pre-existing label from a mutually known name space, as the originator of a message (message authentication) or as the end-point of a channel (entity authentication).

Authorization

The act of determining if a particular right, such as access to some resource, can be granted to the presenter of a particular credential.

Billing The act of preparing an invoice.

Broker A Broker is an entity that is in a different administrative domain from both the home AAA server and the local ISP, and

which provides services, such as facilitating payments between the local ISP and home administrative entities. There are two different types of brokers; proxy and routing.

Client A node wishing to obtain service from an attendant within an administrative domain.

End-to-End

End-to-End is the security model that requires that security information be able to traverse, and validated even when an AAA message is processed by intermediate nodes such as proxies, brokers, etc.

Foreign Domain

An administrative domain, visited by a Mobile IP client, and containing the AAA infrastructure needed to carry out the necessary operations enabling Mobile IP registrations. From the point of view of the foreign agent, the foreign domain is the local domain.

Home Domain

An administrative domain, containing the network whose prefix matches that of a mobile node's home address, and containing the AAA infrastructure needed to carry out the necessary operations enabling Mobile IP registrations. From the point of view of the home agent, the home domain is the local domain.

Hop-by-hop

Hop-by-hop is the security model that requires that each direct set of peers in a proxy network share a security association, and the security information does not traverse an AAA entity.

Inter-domain Accounting

Inter-domain accounting is the collection of information on resource usage of an entity with an administrative domain, for use within another administrative domain. In inter-domain accounting, accounting packets and session records will typically cross administrative boundaries.

Intra-domain Accounting

Intra-domain accounting is the collection of information on resource within an administrative domain, for use within that domain. In intra-domain accounting, accounting packets and session records typically do not cross administrative boundaries.

Local Domain

An administrative domain containing the AAA infrastructure of immediate interest to a Mobile IP client when it is away from home.

Local Proxy

A Local Proxy is a AAA server that satisfies the definition of a Proxy, and exists within the same administrative domain as the network device (e.g. NAS) that issued the AAA request. Typically, a local proxy will enforce local policies prior to forwarding responses to the network devices, and are generally used to multiplex AAA messages from a large number of network devices.

Network Access Identifier

The Network Access Identifier (NAI) is the userID submitted by the client during network access authentication. In roaming, the purpose of the NAI is to identify the user as well as to assist in the routing of the authentication request. The NAI may not necessarily be the same as the user's e-mail address or the userID submitted in an application layer authentication.

Non-Proxy Broker

A Routing Broker is occasionally referred to as a Non-Proxy Broker.

Proxy

A AAA proxy is an entity that acts as both a client and a server. When a request is received from a client, the proxy acts as a AAA server. When the same request needs to be forwarded to another AAA entity, the proxy acts as a AAA client.

Proxy Broker

A Proxy Broker is a AAA entity that satisfies the definition of a Broker, and acts as a Transparent Proxy by acting as the forwarding agent for all AAA messages between the local ISP and the home domain's AAA servers.

Real-time Accounting

Real-time accounting involves the processing of information on resource usage within a defined time window. Time constraints are typically imposed in order to limit financial risk.

Roaming Capability

Roaming capability can be loosely defined as the ability to use any one of multiple Internet service providers (ISPs), while maintaining a formal, customer-vendor relationship with

only one. Examples of cases where roaming capability might be required include ISP "confederations" and ISP- provided corporate network access support.

Routing Broker

A Routing Broker is a AAA entity that satisfies the definition of a Broker, but is NOT in the transmission path of AAA messages between the local ISP and the home domain's AAA servers. When a request is received by a Routing Broker, information is returned to the AAA requestor that includes the information necessary for it to be able to contact the Home AAA server directly. Certain organizations providing Routing Broker services MAY also act as a Certificate Authority, and allows the Routing Broker to return the certificates necessary for the local ISP and the home AAA servers to communicate securely.

Session record

A session record represents a summary of the resource consumption of a user over the entire session. Accounting gateways creating the session record may do so by processing interim accounting events.

Transparent Proxy

A Local Proxy is a AAA server that satisfies the definition of a Proxy, but does not enforce any local policies (meaning that it does not add, delete or modify attributes or modify information within messages it forwards).

5. Requirements Summary

The AAA protocol evaluation criteria for network access are summarized below. For details on the requirements, please consult the documents referenced in the footnotes.

General Reqts.				NASREQ	ROAMOPS	MOBILE IP
Scalability a				M 12	M 3	M 30 39
Failover b				M 12		M 31
Mutual auth AAA client/server c				M 16		M 30
Transmission level security d					M 6	S 31 39
Data object Confidentiality e				M 26	M 6	S 33
Data object Integrity f				M 16	M 6	M 31 39
Certificate transport g				M 42		S 31 33
Reliable AAA transport				M		M

- [b] In the event of failure to communicate with a given server, the protocol must provide a mechanism to change service to another backup or secondary server.
- [c] This requirement refers to the ability to support mutual authentication between the AAA client and server.
- [d] The AAA protocol requires authentication, integrity protection and confidentiality at the transmission layer. This security model is also referred to as hop-by-hop security, whereas the security is established between two communicating peers. All of the security is removed when the AAA message is processed by a receiving AAA entity.
- [e] The AAA protocol requires confidentiality at the object level, where an object consists of one or more attributes. Object level confidentiality implies that only the target AAA entity for whom the data is ultimately destined may decrypt the data, regardless of the fact that the message may traverse one or more intermediate AAA entities (e.g. proxies, brokers).
- [f] The AAA protocol requires authentication and integrity protection at the object level, which consists of one or more attributes. Object level authentication must be persistent across one or more intermediate AAA entity (e.g. proxy, broker, etc), meaning that any AAA entity in a proxy chain may verify the authentication. This implies that data that is covered by object level security CANNOT be modified by intermediate servers.
- [g] The AAA protocol MUST be capable to transporting certificates. This requirement is intended as an optimization, in lieu of requiring that an out-of-band protocol be used to fetch certificates.
- [h] This requirement refers to resilience against packet loss, including:
 - 1. Hop-by-hop retransmission and failover so that reliability does not solely depend on single hop transport retransmission.
 - 2. Control of the retransmission mechanism by the AAA application.
 - 3. Acknowledgement by the transport that a message was delivered successfully, separate from message semantics or syntax evaluation.
 - 5. Piggybacking of acknowledgements in AAA messages.
 - 6. Timely delivery of AAA responses.
- [i] In the Mobile IP AAA architecture, brokers can be in the forwarding path, in which case they act as transparent proxies (proxy brokers). Alternatively, it is also possible to conceive of brokers operating as certifying authorities outside of the forwarding path (routing brokers).

- [j] An auditable process is one in which it is possible to definitively determine what actions have been performed on AAA packets as they travel from the home AAA server to the network device and back.
- [k] The AAA protocol MUST allow communication to be secured. However, the AAA protocol MUST also allow an underlying security service (e.g. IP Security) to be used. When the latter is used, the former MUST NOT be required.
- [l] The AAA protocol MUST be extensible by third parties (e.g. other IETF Working Groups), in order to define attributes that are specific to the service being defined. This requirement simply means that the AAA protocol MUST allow groups other than the AAA WG to define standard attributes.

5.2. Authentication Requirements

Authentication Reqts.	NASREQ	ROAMOPS	MOBILE IP
NAI Support a	M 9	M 2	S 32 34 38
CHAP Support b	M 10	M 3	O
EAP Support c	M 10	S 3	O
PAP/Clear-Text Support d	M 10	B 3	O
Re-authentication on demand e	M 17		S 30 33
Authorization Only without Authentication f	M 9		O 30

Key

M = MUST

S = SHOULD

O = MAY

N = MUST NOT

B = SHOULD NOT

Clarifications

- [a] The AAA protocol MUST allow the use of Network Access Identifiers (NAI) [8] to identify users and/or devices.
- [b] The AAA protocol MUST allow CHAP [20] authentication information to be transported. This is commonly used by Network Access Servers that request authentication of a PPP user.
- [c] The AAA protocol MUST allow for Extensible Authentication Protocol (EAP) [14] payload to be transported. Since some EAP authentication mechanisms require more than one round trip, the AAA protocol must allow for such authentication mechanisms to be used. The actual EAP authentication mechanism negotiated MUST be transparent to the AAA protocol. When EAP is used, authentication typically occurs between the user being authenticated and his/her home AAA server.
- [d] While PAP is deprecated, it is still in widespread use for its original intended purpose, which is support of cleartext passwords. As a result, a AAA protocol will need to be able to securely transport cleartext passwords. This includes providing for confidentiality of cleartext passwords traveling over the wire, as well as protecting against disclosure of cleartext passwords to proxies in the forwarding path.
- [e] The AAA protocol MUST allow for a user to be re-authenticated on-demand. The protocol MUST allow for this event to be triggered by either the user, access device (AAA client), or the home or visited AAA server.
- [f] This requirement refers to the ability to authorize usage based on a user claim of identity, without requiring that the claim be authenticated.

5.3. Authorization Requirements

Authorization Reqts.	NASREQ	ROAMOPS	MOBILE IP
Static and Dynamic IPv4/6 Address Assign. a	M 11	M 1	M 32 36
RADIUS gateway capability b	M 44	M 3	0 30
Reject capability c	M 12	M 4	M 39
Precludes layer 2 tunneling	N 11	N 5	
Re-Authorization on demand d	M 18		S 30 33
Support for Access Rules, Restrictions, Filters e	M 11, 19		0 30 37
State Reconciliation f	M 20		
Unsolicited Disconnect g	M 18		

Key

M = MUST

S = SHOULD

O = MAY

N = MUST NOT

B = SHOULD NOT

Clarifications

- [a] The AAA protocol MUST allow a server to provide a static or dynamic address during the authorization phase of a user and/or device. The address assigned MUST be either of type IPv4 or IPv6. An address is considered static when a user requests a specific address, and it is present in the authorization request. An address is considered dynamic when the AAA server assigns an address to the user that is either defined in his profile, or from an address pool managed by the server.
- [b] This requirement refers to the ability of a new AAA protocol be sufficiently compatible with the large installed base of attributes for existing approaches (RADIUS), such that a server implementation could speak both protocols, or translate between them.
- [c] This requirement refers to the ability of a proxy broker to deny access without forwarding the access request to the AAA server, or to deny access after receiving an access accept from the AAA server.
- [d] This requirement refers to the ability of the AAA client or server to trigger re-authorization, or to the ability of the server to send updated authorization information to the device, such as "stop service." Authorization can allow for a time period, then additional authorization can be sought to continue. A server can initially authorize a user to connect and receive services, but later decide the user is no longer allowed use of the service, for example after N minutes. Authorizations can have a time limit. Re-authorization does not necessarily imply re-authentication.
- [e] This requirement refers to the ability to of the protocol to describe access operational limitations and authorization restrictions to usage to the NAS which includes (but is not limited to):
 - 1. Time/Day restrictions
 - 2. Port location restrictions
 - 3. Dialed/Dialing number
 - 4. Concurrent login limits
 - 5. Session expirations and Idle Timeouts
 - 6. Packet filters

7. Static routes

8. QoS parameters

- [f] This requirement refers to the ability of the NAS to use the AAA server to manage resource allocation state. This capability can assist with, but it is not synonymous with, simultaneous user login control, port usage limitations, or IP address pooling. The design must provide for recovery from data loss during NAS/AAA server communication outages.
- [g] This requirement refers to the ability of the AAA server to request the NAS to disconnect an active session for authorization policy reasons.

Key
M = MUST
S = SHOULD
O = MAY

N = MUST NOT

B = SHOULD NOT

Clarifications

- [a] This requirement may be loosely defined as reporting synchronously with events. Typically the time window is on the order of seconds, not ms.
- [b] The AAA protocol's Accounting data format MUST NOT be bloated, imposing a large overhead for one or more accounting data elements.
- [c] This requirement refers to the ability to buffer or store multiple accounting records, and send them together at some later time.
- [d] This is an application layer acknowledgement. This is sent when the receiving server is willing to take responsibility for the message data.
- [e] This requirement refers to the ability to reflect the time of occurrence of events such as logon, logoff, authentication, authorization and interim accounting. It also implies the ability to provide for unambiguous timestamps.
- [f] This requirement refers to the ability to account for dynamic authentication and authorization. To support this, there can be multiple accounting records for a single session.

5.5. Unique Mobile IP requirements

In addition Mobile IP also has the following requirements:

	Encoding of Mobile IP			M
	registration messages			33
	Firewall friendly			M
	a			35
	Allocation of local Home			S/M
	agent			37/41

Key

M = MUST

S = SHOULD

O = MAY

N = MUST NOT

B = SHOULD NOT

Clarifications

- [a] A firewall friendly protocol is one which is designed to accomodate a firewall acting as a proxy. For example, this would permit a Home Agent AAA server situated behind a firewall to be reachable from the Internet for the purposes of providing AAA services to a Mobile IP Foreign Agent.

Footnotes

- [1] Section 4.2.1 of [2]
 [2] Section 4.2.2 of [2]. Also see [8].
 [3] Section 4.2.3 of [2]. Also see [14].
 [4] Section 4.2.4 of [2].
 [5] Section 4.2.5 of [2].
 [6] Section 4.2.6 of [2].
 [7] Section 4.3 of [2].
 [8] Section 6 of [3]. Also see [6].
 [9] Section 8.2.2.2 of [3]. Also see [14].
 [10] Section 8.2.2.1 of [3]. Also see [14].

- [11] Section 8.3.2.2 of [3]. Also see [7].
- [12] Section 8.1.1 of [3].
- [13] Section 8.1.4.4 of [3].
- [14] Section 8.4.1.2 of [3].
- [15] Section 8.4.2 of [3].
- [16] Section 8.1.3 of [3].
- [17] Section 8.2.1.2 of [3].
- [18] Section 8.3.1.1 of [3].
- [19] Section 8.3.2.1 of [3]. Also see [7].
- [20] Section 8.3.2.3 of [3]. Also see [6], [7].
- [21] Section 8.4.1.3 of [3].
- [22] Section 8.4.1.1 of [3].
- [23] Section 8.4.1.4 of [3].
- [24] Section 8.4.3.1 of [3].
- [25] Section 8.4.3.2 of [3].
- [26] Section 8.2.3.1 of [3].
- [27] Section 8.3.3.1 of [3].
- [28] Section 8.1.4.1 of [3].
- [29] Refer [15]
- [30] Section 3 of [5]
- [31] Section 3.1 of [5]
- [32] Section 4 of [5]
- [33] Section 5 of [5]
- [34] Section 5.1 of [5]
- [35] Section 5.2 of [5]
- [36] Section 5.3 of [5]
- [37] Section 5.4 of [5]
- [38] Section 5.5 of [5]
- [39] Section 6 of [5]
- [40] Section 3.1 of [4]
- [41] Section 3.2.2 of [4]
- [42] Section 8.2.2.2 of [3]
- [43] Section 8.1.2.3 of [3]
- [44] Section 8.1.2.2 of [3]

6. References

- [1] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [2] Aboba, B., Zorn, G., "Criteria for Evaluating Roaming Protocols", [RFC 2477](#), January 1999.
- [3] Beadles, M., Mitton, D. "Criteria for Evaluating Network Access Server Protocols", Internet draft (work in progress), [draft-ietf-nasreq-criteria-04.txt](#), February 2000.

- [4] Hiller, T., et al., "Cdma2000 Wireless Data Requirements for AAA", Internet draft (work in progress), [draft-hiller-cdma2000-AAA-00.txt](#), October 1999.
- [5] Glass, S., Hiller, T., Jacobs, S., Perkins, C., "Mobile IP Authentication, Authorization, and Accounting Requirements", Internet draft (work in progress), [draft-ietf-mobileip-aaa-reqs-01.txt](#), January 2000.
- [6] Mitton, D., Beadles, M., "Network Access Server Requirements Next Generation (NASREQNG) NAS Model", Internet draft (work in progress), [draft-ietf-nasreq-nasmodel-01.txt](#), October 1999.
- [7] Mitton, D., "Network Access Server Requirements: Extended RADIUS Practices", Internet draft (work in progress), [draft-ietf-nasreq-ext-radiuspract-02.txt](#), February 2000.
- [8] Aboba, B., Beadles, M., "The Network Access Identifier", [RFC 2486](#), January 1999.
- [9] Rigney, C., Rubens, A., Simpson, W., Willens, S., "Remote Authentication Dial In User Service (RADIUS)", RFC 2138, April, 1997.
- [10] Rigney, C., "RADIUS Accounting", [RFC 2139](#), April 1997.
- [11] Simpson, W., Editor, "The Point-to-Point Protocol (PPP)", STD 51, [RFC 1661](#), July 1994.
- [12] Sklower, K., Lloyd, B., McGregor, G., Carr, D., and T. Coradetti, "The PPP Multilink Protocol (MP)", [RFC 1990](#), August 1996.
- [13] Simpson, W., Editor, "PPP LCP Extensions", [RFC 1570](#), January 1994.
- [14] Blunk, L., Vollbrecht, J., "PPP Extensible Authentication Protocol (EAP)", [RFC 2284](#), March 1998.
- [15] Solomon, J., Glass, S., "Mobile-IPv4 Configuration Option for PPP IPCP" [RFC 2290](#), Feb 1998
- [16] Calhoun, P., Perkins, C. "Mobile IP Network Access Identifier Extension", [draft-ietf-mobileip-mn-nai-06.txt](#), January 2000.
- [17] Perkins, C., "IP Mobility Support", [RFC 2002](#), Oct 1996.
- [18] Johnson, D., Perkins, C., "Mobility Support in IPv6", [draft-ietf-mobileip-ipv6-09.txt](#), October 1999.

- [19] Aboba, B., Vollbrecht, J., "Proxy Chaining and Policy Implementation in Roaming", [RFC 2607](#), June 1999.
- [20] Simpson, W., "PPP Challenge Handshake Authentication Protocol (CHAP)", [RFC 1994](#), August 1996.

7. Security Considerations

This document, being a requirements document, does not have any security concerns. The security requirements on protocols to be evaluated using this document are described in the referenced documents.

8. IANA Considerations

This draft does not create any new number spaces for IANA administration.

9. Acknowledgements

Thanks to the members of the Mobile IP, AAA, and NASREQ working groups who have discussed and commented on these requirements.

10. Authors' Addresses

Bernard Aboba
Microsoft Corporation
One Microsoft Way
Redmond, WA 98052

Phone: +1 (425) 936-6605
Fax: +1 (425) 936-7329
EMail: bernarda@microsoft.com

Pat R. Calhoun
Network and Security Research Center, Sun Labs
Sun Microsystems, Inc.

15 Network Circle

Menlo Park, CA 94025

Phone: +1 (650) 786-7733
EMail: pcalhoun@eng.sun.com

Steven M. Glass
Sun Microsystems

1 Network Drive

Burlington, MA. 01845

Phone: +1 (781) 442-0504

Fax: +1 (781) 442-1677
EMail: steven.glass@sun.com

Tom Hiller
Wireless Data Standards & Architectures
Lucent Technologies
[263 Shuman Drive](#)
Room 1HP2F-218
Naperville, IL 60563

Phone: +1 (630) 976-7673
EMail: tom.hiller@lucent.com

Peter J. McCann
Lucent Technologies
Rm 2Z-305
[263 Shuman Blvd](#)
Naperville, IL 60566

Phone: +1 (630) 713 9359
EMail: mccap@lucent.com

Hajime Shiino
Lucent Technologies Japan Ltd.
[25 Mori Bldg. 1-4-30 Roppongi](#),
Minato-ku Tokyo

Phone: +81-3-5561-3695
EMail: hshiino@lucent.com

Glen Zorn
Cisco Systems, Inc.
[500 108th Avenue N.E., Suite 500](#)
Bellevue, WA 98004
USA

Phone: +1 425 468 0955
EMail: gwz@acm.org

Gopal Dommety
IOS Network Protocols
Cisco Systems, Inc.
[170 West Tasman Drive](#)
San Jose, CA 95134-1706

Phone: +1 (408) 525-1404
Fax: +1 (408) 526-4952
EMail: gdommety@cisco.com

Charles E. Perkins
Communications Systems Lab
Nokia Research Center
[313 Fairchild Drive](#)
Mountain View, California

Phone: +1 (650) 625-2986
Fax: +1 (650) 691-2170
EMail: charliep@iprg.nokia.com

Basavaraj Patil
Nokia Networks
[6000 Connection Dr.](#)
Irving, Texas 75039

Phone: +1 972-894-6709
Fax: +1 972-894-5349
EMail: Basavaraj.Patil@nokia.com

David Mitton
Nortel Networks
[8 Federal St](#)
Billerica, MA 01821

Phone: 978-288-4570
Fax: 978-288-3030
EMail: dmitton@nortelnetworks.com

Serge Manning
Nortel Networks
[2201 Lakeside Blvd](#)
Richardson, TX 75082-4399

Phone: +1 (972) 684-7277
EMail: smanning@nortelnetworks.com

Mark Anthony Beadles
SmartPipes, Inc.
[545 Metro Place South](#)
Suite 100
Dublin, OH 43017

Phone: 614-327-8046
EMail: mbeadles@smartpipes.com

Pat Walsh
Ameritech
[2000 W. Ameritech Ctr. Dr.](#)

Hoffman Estates, IL 60195

Phone: +1 (847) 765-5845
EMail: pwalsh@ameritechcell.com

Xing Chen
Alcatel USA
1000 Coit Road
Plano, TX 75075, USA

Phone: +1 (972) 519-4142
Fax: +1 (972) 519-4843
EMail: xing.chen@usa.alcatel.com

Takahiro Ayaki
DDI corporation
Ichibancho FS Bldg.
8, Ichibancho, Chiyoda-ku Tokyo

Phone: +81-3-3221-9682
EMail: ayaki@ddi.co.jp

Sanjeevan Sivalingham
Ericsson Wireless Communications Inc.,
Rm Q-356C
6455 Lusk Blvd
San Diego, CA 92126

Phone: +1 (858) 332-5670
EMail: s.sivalingham@ericsson.com

Alan Hameed
Fujitsu
2801 Telecom Parkway
Richardson, Texas 75082

Phone: +1 (972) 479-2089

Mark Munson
GTE Wireless
One GTE Place
Alpharetta, GA 30004

Phone: +1 (678) 339-4439
EMail: mmunson@mobilnet.gte.com

Stuart Jacobs
Secure Systems Department

GTE Laboratories

[40](#) **Sylvan Road,**

Waltham, MA 02451-1128

Phone: +1 (781) 466-3076

Fax: +1 (781)466-2838

EMail: sjacobs@gte.com

Takuo Seki

IDO Corporation

Gobancho YS Bldg.

12-3, Gobancho, Chiyoda-ku Tokyo

Phone: +81-3-3263-9660

EMail: t-seli@ido.co.jp

Byng-Keun Lim

LG Information & Communications, Ltd.

533, Hogye-dong, Dongan-ku, Anyang-shi,

Kyungki-do, 431-080, Korea

Phone: +82-343-450-7199

Fax: +82-343-450-7050

EMail: bklim@lgic.co.kr

Brent Hirschman

[1501](#) **Shure Dr.**

Arlington Hieghts, IL 60006

Phone: +1 (847) 632-1563

EMail: qa4053@email.mot.com

Raymond T. Hsu

Qualcomm Inc.

[6455](#) **Lusk Blvd.**

San Diego, CA 92121

Phone: +1 (619) 651-3623

EMail: rhsu@qualcomm.com

Haeng Koo

Samsung Telecommunications America, Inc.

[1130](#) **E. Arapaho Road**

Richardson, TX, USA 75025

Phone: +1 (972) 761-7735

EMail: hkoo@telecom.sna.samsung.com

Mark A. Lipford
Sprint PCS
[8001 College Blvd.](#); Suite 210
Overland Park, KS 66210

Phone: +1 (913) 664-8335
EMail: mlipfo01@sprintspectrum.com

Ed Campbell
3Com Corporation
[1800 W. Central Rd.](#)
Mount Prospect, IL 60056

Phone: +1 (847) 342-6769
EMail: ed_campbell@3com.com

Yingchun Xu
3Com Corporation
[1800 W. Central Rd.](#)
Mount Prospect, IL 60056

Phone: +1 (847) 342-6814
EMail: Yingchun_Xu@3com.com

Shinich Baba
Toshiba America Research, Inc.
PO Box 136,
Convent Station, NJ 07961-0136

Phone: +1 (973) 829-4795
EMail: sbaba@tari.toshiba.com

Eric Jaques
Vodafone AirTouch
[2999 Oak Road](#), MS-750
Walnut Creek, CA 94596

Phone: +1 (925) 279-6142
EMail: ejaques@akamail.com

[11.](#) Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's

procedures with respect to rights in standards-track and standards-related documentation can be found in [BCP-11](#). Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

12. Full Copyright Statement

Copyright (C) The Internet Society (2000). All Rights Reserved.
This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English. The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns. This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE."

13. Expiration Date

This memo is filed as [<draft-ietf-aaa-na-reqts-02.txt>](#), and expires October 1, 2000.

