Workgroup: Network Working Group Internet-Draft: draft-ietf-ace-aif-01 Published: 11 February 2021 Intended Status: Informational Expires: 15 August 2021 Authors: C. Bormann Universität Bremen TZI An Authorization Information Format (AIF) for ACE

Abstract

Constrained Devices as they are used in the "Internet of Things" need security. One important element of this security is that devices in the Internet of Things need to be able to decide which operations requested of them should be considered authorized, need to ascertain that the authorization to request the operation does apply to the actual requester, and need to ascertain that other devices they place requests on are the ones they intended.

To transfer detailed authorization information from an authorization manager (such as an ACE-OAuth Authorization Server) to a device, a representation format is needed. This document provides a suggestion for such a format, the Authorization Information Format (AIF). AIF is defined both as a general structure that can be used for many different applications and as a specific refinement that describes REST resources and the permissions on them.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>https://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 15 August 2021.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>https://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without

warranty as described in the Simplified BSD License.

Table of Contents

- <u>1</u>. <u>Introduction</u>
 - <u>1.1</u>. <u>Terminology</u>
- 2. Information Model
 - 2.1. REST-specific model
 - 2.2. Limitations
 - 2.3. Extended REST-specific model
- <u>3. Data Model</u>
- <u>4</u>. <u>Media Types</u>
- 5. <u>IANA Considerations</u>
 - 5.1. Media Types
 - 5.2. <u>Registries</u>
 - 5.3. Content-Format
- <u>6</u>. <u>Security Considerations</u>
- <u>7</u>. <u>References</u>
 - 7.1. Normative References
- <u>7.2</u>. <u>Informative References</u> Acknowledgements

Author's Address

1. Introduction

Constrained Devices as they are used in the "Internet of Things" need security. One important element of this security is that devices in the Internet of Things need to be able to decide which operations requested of them should be considered authorized, need to ascertain that the authorization to request the operation does apply to the actual requester, and need to ascertain that other devices they place requests on are the ones they intended.

To transfer detailed authorization information from an authorization manager (such as an ACE-OAuth Authorization Server [I-D.ietf-aceoauth-authz]) to a device, a representation format is needed. This document provides a suggestion for such a format, the Authorization Information Format (AIF). AIF is defined both as a general structure that can be used for many different applications and as a specific refinement that describes REST resources and the permissions on them.

1.1. Terminology

This memo uses terms from [RFC7252] and [RFC4949].

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here. These words may also appear in this document in lower case as plain English words, absent their normative meanings.

(Note that this document is itself informational, but it is discussing normative statements that MUST be put into concrete terms in each specification that makes use of this document.)

The term "byte", abbreviated by "B", is used in its now customary sense as a synonym for "octet".

2. Information Model

Authorizations are generally expressed through some data structures that are cryptographically secured (or transmitted in a secure way). This section discusses the information model underlying the payload of that data (as opposed to the cryptographic armor around it).

For the purposes of this specification, the underlying access control model will be that of an access matrix, which gives a set of permissions for each possible combination of a subject and an object. We do not concern the AIF format with the subject for which the AIF object is issued, focusing the AIF object on a single row in the access matrix (such a row traditionally is also called a capability list). As a consequence, AIF MUST be used in a way that the subject of the authorizations is unambiguously identified (e.g., as part of the armor around it).

The generic model of a such a capability list is a list of pairs of object identifiers and the permissions the subject has on the object(s) identified.

AIF-Generic<Toid, Tperm> = [* [Toid, Tperm]]

Figure 1: Definition of Generic AIF

In a specific data model, the object identifier (Toid) will often be a text string, and the set of permissions (Tperm) will be represented by a bitset in turn represented as a number (see Section $\underline{3}$). AIF-Specific = AIF-Generic<tstr, uint>

Figure 2: Likely shape of a specific AIF

2.1. REST-specific model

In the specific instantiation of the REST resources and the permissions on them, for the object identifiers (Toid), we use the URI of a resource on a CoAP server. More specifically, the parts of the URI that identify the server ("authority" in [RFC3986]) are considered the realm of the authentication mechanism (which are handled in the cryptographic armor); we therefore focus on the "path-absolute" and "query" parts of the URI (URI "local-part" in this specification, as expressed by the Uri-Path and Uri-Query options in CoAP). As a consequence, AIF MUST be used in a way that it is unambiguous who is the target (enforcement point) of these authorizations.

For the permissions (Tperm), we simplify the model permissions to giving the subset of the CoAP methods permitted. This model is summarized in <u>Table 1</u>.

local-part	Permission Set	
/s/light	GET	
/a/led	PUT, GET	
/dtls	POST	
Table 1: An authorization		

instance in the AIF Information Model

2.2. Limitations

This simple information model only allows granting permissions for statically identifiable objects, e.g. URIs for the REST-specific instantiation. One might be tempted to extend the model towards URI templates [RFC6570], however, that requires some considerations of the ease and unambiguity of matching a given URI against a set of templates in an AIF object.

This simple information model also doesn't allow further conditionalizing access based on state outside the identification of objects (e.g., "opening a door is allowed if that isn't locked").

Finally, the model does not provide any special access for a set of resources that are specific to a subject, e.g. that the subject created itself by previous operations (PUT, POST) or that were specifically created for the subject by others.

2.3. Extended REST-specific model

The extended REST-specific model addresses the need to provide defined access to dynamic resources that were created by the subject itself, specifically, a resource that is made known to the subject by providing Location-* options in a CoAP result or using the Location header field in HTTP [RFC7231] (the Location-indicating mechanisms). (The concept is somewhat comparable to "ACL inheritance" in NFSv4 [rfc5661], except that it does not use a containment relationship but the fact that the dynamic resource was created from a resource to which the subject had access.)

local-part	Permission Set	
/a/make-coffee	POST, Dynamic-GET, Dynamic-DELETE	
Table 2: An authorization instance in the AIF		
Information Model		

For a method X, the presence of a Dynamic-X permission means that the subject holds permission to exercise the method X on resources that have been returned by a Location-indicating mechanism to a request that the subject made to the resource listed (/a/make-coffee in the example, which might return the location of a resource that allows GET to find out about the status and DELETE to cancel the coffee-making operation).

Since the use of the extension defined in this section can be detected by the mentioning of the Dynamic-X permissions, there is no need for another explicit switch between the basic and the extended model; the extended model is always presumed once a Dynamic-X permission is present.

3. Data Model

Different data model specializations can be defined for the generic information model given above.

In this section, we will give the data model for basic REST authorization. As discussed, the object identifier is specialized as a text string giving a relative URI (local-part as absolute path on the server serving as enforcement point). The permission set is specialized to a single number by the following steps:

*The entries in the table that specify the same local-part are merged into a single entry that specifies the union of the permission sets.

*The (non-dynamic) methods in the permission sets are converted into their CoAP method numbers, minus 1.

```
*Dynamic-X permissions are converted into what the number would
      have been for X, plus a Dynamic-Offset chosen as 32 (e.g., 35 for
      Dynamic-DELETE).
     *The set of numbers is converted into a single number by taking
      each number to the power of two and computing the inclusive OR of
      the binary representations of all the power values.
   This data model could be interchanged in the JSON [RFC8259]
   representation given in Figure 3.
[["/s/light", 1], ["/a/led", 5], ["/dtls", 2]]
     Figure 3: An authorization instance encoded in JSON (46 bytes)
   In CDDL [<u>RFC8610</u>], a straightforward specification of the data model
   (including both the methods from [RFC7252] and the new ones from
   [<u>RFC8132</u>], identified by the method code minus 1) is:
AIF-REST = AIF-Generic<path, permissions>
path = tstr ; URI relative to enforcement point
permissions = uint .bits methods
methods = \&(
  GET: 0
  POST: 1
  PUT: 2
  DELETE: 3
  FETCH: 4
  PATCH: 5
  iPATCH: 6
  Dynamic-GET: 32; 0 .plus Dynamic-Offset
  Dynamic-POST: 33; 1 .plus Dynamic-Offset
  Dynamic-PUT: 34; 2 .plus Dynamic-Offset
  Dynamic-DELETE: 35; 3 .plus Dynamic-Offset
  Dynamic-FETCH: 36; 4 .plus Dynamic-Offset
  Dynamic-PATCH: 37; 5 .plus Dynamic-Offset
  Dynamic-iPATCH: 38; 6 .plus Dynamic-Offset
)
```

Figure 4: AIF in CDDL

A representation of this information in CBOR [<u>RFC8949</u>] is given in <u>Figure 5</u>; again, several optimizations/improvements are possible.

83			#	array(3)
82			#	array(2)
	68		#	text(8)
		2f732f6c69676874	#	"/s/light"
	01		#	unsigned(1)
82			#	array(2)
	66		#	text(6)
		2f612f6c6564	#	"/a/led"
	05		#	unsigned(5)
82			#	array(2)
	65		#	text(5)
		2f64746c73	#	"/dtls"
	02		#	unsigned(2)

Figure 5: An authorization instance encoded in CBOR (29 bytes)

Note that choosing 32 as Dynamic-Offset means that all future CoAP methods that can be registered can be represented both as themselves and in the Dynamic-X variant, but only the dynamic forms of methods 1 to 21 are typically usable in a JSON form [RFC7493].

4. Media Types

This specification defines media types for the generic information model, expressed in JSON (application/aif+json) or in CBOR (application/aif+cbor). These media types have parameters for specifying Toid and Tperm; default values are the values "local-uri" for Toid and "REST-method-set" for Tperm.

[Insert lots of boilerplate here]

A specification that wants to use Generic AIF with different Toid and/or Tperm is expected to request these as media type parameters (Section 5.2) and register a corresponding Content-Format (Section 5.3).

5. IANA Considerations

5.1. Media Types

IANA is requested to add the following Media-Type to the "Media Types" registry.

Name	Template	Reference	
aif+cbor	application/aif+cbor	RFC XXXX, <u>Section 4</u>	
aif+json	application/aif+json	RFC XXXX, <u>Section 4</u>	
	Table 3		

// RFC Ed.: please replace RFC XXXX with this RFC number and remove this note.

```
Type name: application
Subtype name: aif+cbor
Required parameters: none
Optional parameters: none
Encoding considerations: binary (CBOR)
Security considerations: Section 6 of RFC XXXX
Published specification: Section 4 of RFC XXXX
Person & email address to contact for further information: ACE WG
   mailing list (ace@ietf.org), or IETF Applications and Real-Time
   Area (art@ietf.org)
Intended usage: COMMON
Restrictions on usage: none
Author/Change controller: IETF
Type name: application
Subtype name: aif+json
Required parameters: none
Optional parameters: none
Encoding considerations: binary (JSON is UTF-8-encoded text)
Security considerations: Section 6 of RFC XXXX
Published specification: Section 4 of RFC XXXX
Person & email address to contact for further information: ACE WG
   mailing list (ace@ietf.org), or IETF Applications and Real-Time
   Area (art@ietf.org)
Intended usage: COMMON
Restrictions on usage: none
Author/Change controller: IETF
```

5.2. Registries

IANA is requested to create a registry for AIF with two subregistries for Toid and Tperm, populated with:

Subregistry	name	Description/Specification
Toid	local-part	local-part of URI as specified in [RFCthis]
Tperm	REST-method- set	set of REST methods represented as specified in [RFCthis]
Table 4		

The registration policy is Specification required [RFC8126]. The designated expert will engage with the submitter to ascertain the requirements of this document are addressed.

5.3. Content-Format

IANA is requested to register Content-Format numbers in the "CoAP Content-Formats" subregistry, within the "Constrained RESTful Environments (CoRE) Parameters" Registry [IANA.core-parameters], as follows:

Media Type	Content Coding	ID	Reference	
application/aif+cbor	-	TBD1	RFC XXXX	
application/aif+json	-	TBD2	RFC XXXX	

Table 5

// RFC Ed.: please replace TBD1 and TBD2 with assigned IDs and remove this note. // RFC Ed.: please replace RFC XXXX with this RFC number and remove this note.

6. Security Considerations

The security considerations of [RFC7252] apply. Some wider issues are discussed in [RFC8576].

When applying these formats, the referencing specification must be careful to:

*ensure that the cryptographic armor employed around this format fulfills the security objectives, and that the armor or some additional information included in it with the AIF information unambiguously identifies the subject to which the authorizations shall apply, and

*ensure that the types used for Toid and Tperm provide the appropriate granularity so that application requirements on the precision of the authorization information are fulfilled.

For the data formats, the security considerations of [<u>RFC8259</u>] and [<u>RFC8949</u>] apply.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/ RFC2119, March 1997, <<u>https://www.rfc-editor.org/info/</u> rfc2119>.
- [RFC7252] Shelby, Z., Hartke, K., and C. Bormann, "The Constrained Application Protocol (CoAP)", RFC 7252, DOI 10.17487/ RFC7252, June 2014, <<u>https://www.rfc-editor.org/info/</u> rfc7252>.
- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26,

RFC 8126, DOI 10.17487/RFC8126, June 2017, <<u>https://</u> www.rfc-editor.org/info/rfc8126.

- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<u>https://www.rfc-editor.org/info/rfc8174</u>>.
- [RFC8610] Birkholz, H., Vigano, C., and C. Bormann, "Concise Data Definition Language (CDDL): A Notational Convention to Express Concise Binary Object Representation (CBOR) and JSON Data Structures", RFC 8610, DOI 10.17487/RFC8610, June 2019, <<u>https://www.rfc-editor.org/info/rfc8610</u>>.

7.2. Informative References

[I-D.ietf-ace-oauth-authz]

Seitz, L., Selander, G., Wahlstroem, E., Erdtman, S., and H. Tschofenig, "Authentication and Authorization for Constrained Environments (ACE) using the OAuth 2.0 Framework (ACE-OAuth)", Work in Progress, Internet-Draft, draft-ietf-ace-oauth-authz-36, 16 November 2020, <<u>http://</u> www.ietf.org/internet-drafts/draft-ietf-ace-oauthauthz-36.txt>.

- [IANA.core-parameters] IANA, "Constrained RESTful Environments (CoRE) Parameters", <<u>http://www.iana.org/assignments/</u> <u>core-parameters</u>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, DOI 10.17487/RFC3986, January 2005, <<u>https://</u> www.rfc-editor.org/info/rfc3986>.
- [RFC4949] Shirey, R., "Internet Security Glossary, Version 2", FYI 36, RFC 4949, DOI 10.17487/RFC4949, August 2007, <<u>https://www.rfc-editor.org/info/rfc4949</u>>.
- [rfc5661] Shepler, S., Ed., Eisler, M., Ed., and D. Noveck, Ed., "Network File System (NFS) Version 4 Minor Version 1 Protocol", RFC 5661, DOI 10.17487/RFC5661, January 2010, <<u>https://www.rfc-editor.org/info/rfc5661</u>>.
- [RFC6570] Gregorio, J., Fielding, R., Hadley, M., Nottingham, M., and D. Orchard, "URI Template", RFC 6570, DOI 10.17487/ RFC6570, March 2012, <<u>https://www.rfc-editor.org/info/</u> rfc6570>.
- [RFC7231] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content", RFC

7231, DOI 10.17487/RFC7231, June 2014, <<u>https://www.rfc-</u> editor.org/info/rfc7231>.

- [RFC7493] Bray, T., Ed., "The I-JSON Message Format", RFC 7493, DOI 10.17487/RFC7493, March 2015, <<u>https://www.rfc-</u> editor.org/info/rfc7493>.
- [RFC8132] van der Stok, P., Bormann, C., and A. Sehgal, "PATCH and FETCH Methods for the Constrained Application Protocol (CoAP)", RFC 8132, DOI 10.17487/RFC8132, April 2017, <<u>https://www.rfc-editor.org/info/rfc8132</u>>.
- [RFC8259] Bray, T., Ed., "The JavaScript Object Notation (JSON)
 Data Interchange Format", STD 90, RFC 8259, DOI 10.17487/
 RFC8259, December 2017, <<u>https://www.rfc-editor.org/info/
 rfc8259</u>>.
- [RFC8576] Garcia-Morchon, O., Kumar, S., and M. Sethi, "Internet of Things (IoT) Security: State of the Art and Challenges", RFC 8576, DOI 10.17487/RFC8576, April 2019, <<u>https://</u> www.rfc-editor.org/info/rfc8576>.
- [RFC8949] Bormann, C. and P. Hoffman, "Concise Binary Object Representation (CBOR)", STD 94, RFC 8949, DOI 10.17487/ RFC8949, December 2020, <<u>https://www.rfc-editor.org/info/</u> rfc8949>.

Acknowledgements

Jim Schaad and Francesca Palombini provided comments that shaped the direction of this document.

Author's Address

Carsten Bormann Universität Bremen TZI Postfach 330440 D-28359 Bremen Germany

Phone: <u>+49-421-218-63921</u> Email: <u>cabo@tzi.org</u>