

**Additional OAuth Parameters for Authorization in Constrained
Environments (ACE)
draft-ietf-ace-oauth-params-07**

Abstract

This specification defines new parameters for the OAuth 2.0 token and introspection endpoints when used with the framework for authentication and authorization for constrained environments (ACE). These are used to express the proof-of-possession key the client wishes to use, the proof-of-possession key that the AS has selected, and the key the RS should use to authenticate to the client.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 19, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4](#).e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Terminology	3
3.	Parameters for the Token Endpoint	3
3.1.	Client-to-AS Request	3
3.2.	AS-to-Client Response	4
3.3.	The Resource Server Confirmation Claim	5
4.	Parameters for the Introspection Endpoint	6
4.1.	AS-to-RS Response	6
5.	Confirmation Method Parameters	7
6.	CBOR Mappings	8
7.	Security Considerations	9
8.	Privacy Considerations	9
9.	IANA Considerations	9
9.1.	JSON Web Token Claims	9
9.2.	CBOR Web Token Claims	9
9.3.	OAuth Parameter Registration	9
9.4.	OAuth Introspection Response Parameter Registration . . .	10
9.5.	OAuth Parameters CBOR Mappings Registraton	10
9.6.	OAuth Token Introspection Response CBOR Mappings Registration	11
10.	Acknowledgments	11
11.	References	11
11.1.	Normative References	11
11.2.	Informative References	12
Appendix A.	Overlap with OAuth work	12
	Author's Address	13

[1.](#) Introduction

The Authentication and Authorization for Constrained Environments (ACE) specification [[I-D.ietf-ace-oauth-authz](#)] requires some new parameters for interactions with the OAuth 2.0 [[RFC6749](#)] token and introspection endpoints, as well as some new claims to be used in access tokens. These parameters and claims can also be used in other contexts, and may need to be updated to align them with ongoing OAuth work. Therefore, these parameters and claims have been put into a dedicated document, to facilitate their use and any potential updates in a manner independent of [[I-D.ietf-ace-oauth-authz](#)].

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

Readers are assumed to be familiar with the terminology from [[I-D.ietf-ace-oauth-authz](#)].

Note that the term "endpoint" is used here following its OAuth 2.0 [[RFC6749](#)] definition, which is to denote resources such as token and introspection at the AS and authz-info at the RS. The CoAP [[RFC7252](#)] definition, which is "An entity participating in the CoAP protocol" is not used in this specification.

3. Parameters for the Token Endpoint

3.1. Client-to-AS Request

This document defines the following additional parameters for requesting an access token from a token endpoint in the ACE framework [[I-D.ietf-ace-oauth-authz](#)]:

req_cnf

OPTIONAL. This field contains information about the key the client would like to bind to the access token for proof-of-possession. It is RECOMMENDED that an AS reject a request containing a symmetric key value in the 'req_cnf' field, since the AS is expected to be able to generate better symmetric keys than a constrained client. The AS MUST verify that the client really is in possession of the corresponding key. Values of this parameter follow the syntax of the "cnf" claim from section 3.1 of [[I-D.ietf-ace-cwt-proof-of-possession](#)].

Figure 1 shows a request for an access token using the "req_cnf" parameter to request a specific public key as proof-of-possession key. The content is displayed in CBOR diagnostic notation, without abbreviations for better readability.


```
Header: POST (Code=0.02)
Uri-Host: "as.example.com"
Uri-Path: "token"
Content-Format: "application/ace+cbor"
Payload:
{
  "req_cnf" : {
    "COSE_Key" : {
      "kty" : "EC",
      "kid" : h'11',
      "crv" : "P-256",
      "x" : b64'usWxHK2PmfnHKwXPS54m0kTcGJ90UiglWiGahtagnv8',
      "y" : b64'IB0L+C3BttVivg+lSreASjpkttcsz+1rb7btKLv8EX4'
    }
  }
}
```

Figure 1: Example request for an access token bound to an asymmetric key.

3.2. AS-to-Client Response

This document defines the following additional parameters for an AS response to a request to the token endpoint:

cnf

REQUIRED if the token type is "pop" and a symmetric key is used. MAY be present for asymmetric proof-of-possession keys. This field contains the proof-of-possession key that the AS selected for the token. Values of this parameter follow the syntax of the "cnf" claim from section 3.1 of [\[I-D.ietf-ace-cwt-proof-of-possession\]](#). See [Section 5](#) for additional discussion of the usage of this parameter.

rs_cnf

OPTIONAL if the token type is "pop" and asymmetric keys are used. MUST NOT be present otherwise. This field contains information about the public key used by the RS to authenticate. If this parameter is absent, either the RS does not use a public key or the AS knows that the RS can authenticate itself to the client without additional information. Values of this parameter follow the syntax of the "cnf" claim from section 3.1 of [\[I-D.ietf-ace-cwt-proof-of-possession\]](#). See [Section 5](#) for additional discussion of the usage of this parameter.

Figure 2 shows an AS response containing a token and a "cnf" parameter with a symmetric proof-of-possession key.


```

Header: Created (Code=2.01)
Content-Format: "application/ace+cbor"
Payload:
{
  "access_token" : b64'SlAV32hkKG ...
    (remainder of CWT omitted for brevity;
    CWT contains COSE_Key in the "cnf" claim)',
  "cnf" : {
    "COSE_Key" : {
      "kty" : "Symmetric",
      "kid" : b64'39Gqlw',
      "k" : b64'hJtXhkV8FJG+Onbc6mxCcQh'
    }
  }
}

```

Figure 2: Example AS response with an access token bound to a symmetric key.

Figure 3 shows an AS response containing a token bound to a previously requested asymmetric proof-of-possession key (not shown) and a "rs_cnf" parameter containing the public key of the RS.

```

Header: Created (Code=2.01)
Content-Format: "application/ace+cbor"
Payload:
{
  "access_token" : b64'0INDoQEkoQVnKkXfb7xaWqMTf6 ...
    (remainder of CWT omitted for brevity;
    CWT contains COSE_Key in the "cnf" claim)',
  "rs_cnf" : {
    "COSE_Key" : {
      "kty" : "EC",
      "kid" : h'12',
      "crv" : "P-256",
      "x" : b64'v05+qsFi+R5vMw9XcSEeIguLVGyWWJsKxK0P0kx34fE',
      "y" : b64'xkezjFXvu8TmLmUXIPAC1ddbLgwCzRMm5mK8oiK5BBY'
    }
  }
}

```

Figure 3: Example AS response, including the RS's public key.

3.3. The Resource Server Confirmation Claim

If the AS needs to convey a hint to the RS about which key it should use to authenticate towards the client, this specification defines

the "rs_cnf" claim, which MAY be used in the access token, with the same syntax and semantics as defined in for the "rs_cnf" parameter.

4. Parameters for the Introspection Endpoint

4.1. AS-to-RS Response

This document defines the following additional parameters for an AS response to a request to the introspection endpoint:

cnf

OPTIONAL. This field contains information about the proof-of-possession key that binds the client to the access token. Values of this parameter follow the syntax of the "cnf" claim from section 3.1 of [[I-D.ietf-ace-cwt-proof-of-possession](#)]. See [Section 5](#) for additional discussion of the usage of this parameter.

rs_cnf

OPTIONAL. If the RS uses asymmetric keys to authenticate towards the client (e.g. with a DTLS-RPK handshake) and it has several such keys (e.g. for different elliptic curves), the AS can give the RS a hint using this parameter, as to which key it should use. Values of this parameter follow the syntax of the "cnf" claim from section 3.1 of [[I-D.ietf-ace-cwt-proof-of-possession](#)]. See [Section 5](#) for additional discussion of the usage of this parameter.

Figure 4 shows an AS response to an introspection request including the "cnf" parameter to indicate the proof-of-possession key bound to the token and the "rs_cnf" parameter to indicate the key the RS is supposed to use to authenticate to the client.


```
Header: Created Code=2.01)
Content-Format: "application/ace+cbor"
Payload:
{
  "active" : true,
  "scope" : "read",
  "aud" : "tempSensor4711",
  "cnf" : {
    "COSE_Key" : {
      "kty" : "EC",
      "kid" : h'11',
      "crv" : "P-256",
      "x" : b64'usWxHK2PmfnHKwXPS54m0kTcGJ90UiglWiGahtagnv8',
      "y" : b64'IBOL+C3BttVivg+lSreASjpkttcsz+1rb7btKLv8EX4'
    }
  },
  "rs_cnf" : {
    "COSE_Key" : {
      "kty" : "EC",
      "kid" : h'12',
      "crv" : "P-256",
      "x" : b64'v05+qsFi+R5vMw9XcSEeIguLVGyWWJsKxK0P0kx34fE',
      "y" : b64'xkezjFXvu8TmLmUXIPAC1ddbLgwCzRMm5mK8oiK5BBY'
    }
  }
}
```

Figure 4: Example introspection response.

5. Confirmation Method Parameters

The confirmation method parameters are used as follows:

- o "req_cnf" in the access token request C -> AS, OPTIONAL to indicate the client's raw public key, or the key-identifier of a previously established key between C and RS that the client wishes to use for proof-of-possession of the access token.
- o "cnf" in the token response AS -> C, OPTIONAL if using an asymmetric key or a key that the client requested via a key identifier in the request. REQUIRED if the client didn't specify a "req_cnf" and symmetric keys are used. Used to indicate the symmetric key generated by the AS for proof-of-possession of the access token.
- o "cnf" in the introspection response AS -> RS, REQUIRED if the access token that was subject to introspection is a proof-of-

possession token, absent otherwise. Indicates the proof-of-possession key bound to the access token.

- o "rs_cnf" in the token response AS -> C, OPTIONAL to indicate the public key of the RS, if it uses one to authenticate itself to the client and the binding between key and RS identity is not established through other means.
- o "rs_cnf" in the introspection response AS -> RS, OPTIONAL, contains the public key that the RS should use for authenticating itself to the client (e.g. if the RS has several different public keys, and there may be ambiguity as to which key to use).

Note that the COSE_Key structure in a confirmation claim or parameter may contain an "alg" or "key_ops" parameter. If such parameters are present, a client MUST NOT use a key that is incompatible with the profile or proof-of-possession algorithm according to those parameters. An RS MUST reject a proof-of-possession using such a key.

If an access token is issued for an audience that includes several RS, the "rs_cnf" parameter MUST NOT be used, since the client cannot determine for which RS the key applies. This document recommends to specify a different endpoint that the client can use to acquire RS authentication keys in such cases. The specification of such an endpoint is out of scope for this document.

6. CBOR Mappings

If CBOR is used, the new parameters and claims defined in this document MUST be mapped to CBOR types as specified in Figure 5, using the given integer abbreviation for the map key.

/-----+-----+-----\			
Name	CBOR Key	Value Type	Usage
-----+-----+-----			
req_cnf	TBD (4)	map	token request
cnf	TBD (8)	map	token response
cnf	TBD (8)	map	introspection response
rs_cnf	TBD (41)	map	token response
rs_cnf	TBD (41)	map	introspection response
rs_cnf	TBD (41)	map	CWT claim
\-----+-----+-----/			

Figure 5: CBOR mappings for new parameters and claims.

7. Security Considerations

This document is an extension to [[I-D.ietf-ace-oauth-authz](#)]. All security considerations from that document apply here as well.

8. Privacy Considerations

This document is an extension to [[I-D.ietf-ace-oauth-authz](#)]. All privacy considerations from that document apply here as well.

9. IANA Considerations

9.1. JSON Web Token Claims

This specification registers the following new claim in the JSON Web Token (JWT) registry of JSON Web Token Claims [[IANA.JsonWebTokenClaims](#)]:

- o Claim Name: "rs_cnf"
- o Claim Description: public key used by RS to authenticate itself to the client.
- o Change Controller: IESG
- o Reference: [Section 3.3](#) of [this document]

9.2. CBOR Web Token Claims

This specification registers the following new claim in the "CBOR Web Token (CWT) Claims" registry [[IANA.CborWebTokenClaims](#)].

- o Claim Name: "rs_cnf"
- o Claim Description: public key used by RS to authenticate itself to the client.
- o JWT Claim Name: rs_cnf
- o Claim Key: TBD (suggested: 41)
- o Claim Value Type(s): map
- o Change Controller: IESG
- o Specification Document(s): [Section 3.3](#) of [this document]

9.3. OAuth Parameter Registration

This section registers the following parameters in the "OAuth Parameters" registry [[IANA.OAuthParameters](#)]:

- o Name: "req_cnf"
- o Parameter Usage Location: token request
- o Change Controller: IESG
- o Reference: [Section 5](#) of [this document]

- o Name: "rs_cnf"
- o Parameter Usage Location: token response
- o Change Controller: IESG
- o Reference: [Section 5](#) of [this document]
- o Name: "cnf"
- o Parameter Usage Location: token response
- o Change Controller: IESG
- o Reference: [Section 5](#) of [this document]

9.4. OAuth Introspection Response Parameter Registration

This section registers the following parameters in the OAuth Token Introspection Response registry [[IANA.TokenIntrospectionResponse](#)].

- o Name: "cnf"
- o Description: Key to prove the right to use a PoP token.
- o Change Controller: IESG
- o Reference: [Section 4.1](#) of [this document]
- o Name: "rs_cnf"
- o Description: public key used by RS to authenticate itself to the client.
- o Change Controller: IESG
- o Reference: [Section 4.1](#) of [this document]

9.5. OAuth Parameters CBOR Mappings Registraton

This section registers the following parameter mappings in the "OAuth Parameters CBOR Mappings" registry established in section 8.9. of [[I-D.ietf-ace-oauth-authz](#)].

- o Name: "req_cnf"
- o CBOR key: TBD (suggested: 4)
- o Change Controller: IESG
- o Reference: [Section 3.1](#) of [this document]
- o Name: "cnf"
- o CBOR key: TBD (suggested: 8)
- o Change Controller: IESG
- o Reference: [Section 3.2](#) of [this document]
- o Name: "rs_cnf"
- o CBOR key: TBD (suggested: 41)
- o Change Controller: IESG
- o Reference: [Section 3.2](#) of [this document]

9.6. OAuth Token Introspection Response CBOR Mappings Registration

This section registers the following parameter mappings in the "OAuth Token Introspection Response CBOR Mappings" registry established in section 8.11. of [[I-D.ietf-ace-oauth-authz](#)].

- o Name: "cnf"
- o CBOR key: TBD (suggested: 8)
- o Change Controller: IESG
- o Reference: [Section 4.1](#) of [this document]

- o Name: "rs_cnf"
- o CBOR key: TBD (suggested: 41)
- o Change Controller: IESG
- o Reference: [Section 4.1](#) of [this document]

10. Acknowledgments

This document is a product of the ACE working group of the IETF.

Ludwig Seitz worked on this document as part of the CelticNext projects CyberWI, and CRITISEC with funding from Vinnova.

11. References

11.1. Normative References

[I-D.ietf-ace-cwt-proof-of-possession]

Jones, M., Seitz, L., Selander, G., Erdtman, S., and H. Tschofenig, "Proof-of-Possession Key Semantics for CBOR Web Tokens (CWTs)", [draft-ietf-ace-cwt-proof-of-possession-11](#) (work in progress), October 2019.

[I-D.ietf-ace-oauth-authz]

Seitz, L., Selander, G., Wahlstroem, E., Erdtman, S., and H. Tschofenig, "Authentication and Authorization for Constrained Environments (ACE) using the OAuth 2.0 Framework (ACE-OAuth)", [draft-ietf-ace-oauth-authz-27](#) (work in progress), November 2019.

[IANA.CborWebTokenClaims]

IANA, "CBOR Web Token (CWT) Claims",
<<https://www.iana.org/assignments/cwt/cwt.xhtml#claims-registry>>.

[IANA.JsonWebTokenClaims]

IANA, "JSON Web Token Claims",
<<https://www.iana.org/assignments/jwt/jwt.xhtml#claims>>.

[IANA.OAuthParameters]

IANA, "OAuth Parameters",
<<https://www.iana.org/assignments/oauth-parameters/oauth-parameters.xhtml#parameters>>.

[IANA.TokenIntrospectionResponse]

IANA, "OAuth Token Introspection Response",
<<https://www.iana.org/assignments/oauth-parameters/oauth-parameters.xhtml#token-introspection-response>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997,
<<https://www.rfc-editor.org/info/rfc2119>>.

[RFC6749] Hardt, D., Ed., "The OAuth 2.0 Authorization Framework", [RFC 6749](#), DOI 10.17487/RFC6749, October 2012,
<<https://www.rfc-editor.org/info/rfc6749>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

11.2. Informative References

[I-D.ietf-oauth-pop-key-distribution]

Bradley, J., Hunt, P., Jones, M., Tschofenig, H., and M. Meszaros, "OAuth 2.0 Proof-of-Possession: Authorization Server to Client Key Distribution", [draft-ietf-oauth-pop-key-distribution-07](#) (work in progress), March 2019.

[RFC7252] Shelby, Z., Hartke, K., and C. Bormann, "The Constrained Application Protocol (CoAP)", [RFC 7252](#), DOI 10.17487/RFC7252, June 2014,
<<https://www.rfc-editor.org/info/rfc7252>>.

Appendix A. Overlap with OAuth work

This document overlaps with draft work from OAuth on proof-of-possession keys [[I-D.ietf-oauth-pop-key-distribution](#)].

The OAuth draft specifies the use of "req_cnf" and "cnf" for requesting proof-of-possession tokens and indicating the key that the AS has selected. It was initially deemed that the work at OAuth had been discontinued and therefore equivalent functionality was defined here. Work in OAuth has since resumed, but it is lagging behind the planned milestones of the ACE working group. We have therefore split this work out into a separate document so that it can

later be updated or obsoleted to align it with the final result of the OAuth work, without affecting [[I-D.ietf-ace-oauth-authz](#)].

Author's Address

Ludwig Seitz
Combitech
Djaeknegatan 31
Malmö 211 35
Sweden

Email: ludwig.seitz@combitech.se