

**Definitions of Extension Managed Objects
for ADSL Lines**

April 23, 2002

[draft-ietf-adslmib-adslext-09.txt](#)

1. Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as ``work in progress.''

Copyright Notice

Copyright (C) The Internet Society (2002). All Rights Reserved.

2. Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes additional managed objects used for managing Asymmetric Digital Subscriber Line (ADSL) interfaces not covered by the ADSL Line MIB [[RFC2662](#)].

3. The SNMP Network Management Framework

The SNMP Management Framework presently consists of five major components:

- o An overall architecture, described in [RFC 2571](#) [[RFC2571](#)].
- o Mechanisms for describing and naming objects and events for the purpose of management. The first version of this Structure of Management Information (SMI) is called SMIV1 and described in STD 16, [RFC 1155](#) [[RFC1155](#)], STD 16, [RFC 1212](#) [[RFC1212](#)] and [RFC 1215](#) [[RFC1215](#)]. The second version, called SMIV2, is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].
- o Message protocols for transferring management information. The first version of the SNMP message protocol is called SNMPv1 and described in STD 15, [RFC 1157](#) [[RFC1157](#)]. A second version of the SNMP message protocol, which is not an Internet standards track protocol, is called SNMPv2c and described in [RFC 1901](#) [[RFC1901](#)] and [RFC 1906](#) [[RFC1906](#)]. The third version of the message protocol is called SNMPv3 and described in [RFC 1906](#) [[RFC1906](#)], [RFC2572](#) [[RFC2572](#)] and [RFC 2574](#) [[RFC2574](#)].
- o Protocol operations for accessing management information. The first set of protocol operations and associated PDU formats is described in STD 15, [RFC 1157](#) [[RFC1157](#)]. A second set of protocol operations and associated PDU formats is described in [RFC 1905](#) [[RFC1905](#)].
- o A set of fundamental applications described in [RFC 2573](#) [[RFC2573](#)] and the view-based access control mechanism described in [RFC 2575](#) [[RFC2575](#)].

A more detailed introduction to the current SNMP Management Framework can be found in [RFC 2570](#) [[RFC2570](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the mechanisms defined in the SMI.

This memo specifies a MIB module that is compliant to the SMIV2. A MIB conforming to the SMIV1 can be produced through the appropriate translations. The resulting translated MIB must be semantically equivalent, except where objects or events are omitted because no translation is possible (use of Counter64). Some machine-readable information in SMIV2 will be converted into textual descriptions in SMIV1 during the translation process. However, this loss of machine readable information is not considered to change the semantics of the MIB.

Expires August 2002

[Page 2]

4. Introduction

The purpose of this memo is to define a supplemental set of managed objects that is not covered by ADSL Line MIB as defined in [[RFC2662](#)]. This memo addresses the additional objects defined in ITU G.997.1 [ITU G.997.1].

5. Relationship of ADSL Line Extension MIB with standard MIBs

This section outlines the relationship of ADSL Line Extension MIB with other MIBs described in RFCs and in their various degrees of standardization. In regards to these relationship, the ADSL Line Extension MIB follows conventions as used by the ADSL Line MIB with one exception. The value of the [RFC2863](#) object, ifOperstatus, SHALL be down(2) when the ADSL line interface is in power state L3 as defined in ITU G.992.1 [ITU G.992.1], which means no power. Its value shall be up(1) if the ADSL line interface is in power state L0 (power on) [ITU G.992.1] or L1 (reduced power). Power Status L2 [ITU G.992.1] is not applicable.

6. Conventions used in the MIB

6.1 Structure

The MIB is organized to follow the same structure of the ADSL Line MIB [[RFC2662](#)].

6.2 Additional Managed Objects

Objects specific to the management of ADSL G.Lite as defined in ITU G.992.2 [ITU G.992.2] are:

- ADSL Transceiver Unit - Central Office End (ATU-C)
Transmission System and Line Mode
- Power Management
- Counters for Fast Retrains and Failed Fast Retrains
- Counters for Severe Error Second-line and Unavailable Second
- Alternative profile configuration for the Dual line mode interface

Besides the management of G.Lite, another object has been added in order to manage the ADSL line profile. The object is the line mode configuration.

6.2.1 ATU-C ADSL Transmission System Parameters and Line Mode

The adslLineConfigTable needs to be extended to cover control of the ATU-C ADSL Transmission system. Three objects are defined to monitor

Expires August 2002

[Page 3]

and configure the transmission mode as well as the actual line mode:

- Capability
- Configuration
- Actual Status

Transmission modes can further determine the line mode of the ADSL interface. For example, if g9921PotsNonOverlapped(2) is the actual value of the ADSL interface, the interface is operating in Full rate ADSL. If the interface is set to g9922PotsOverlapped(9), the interface is operating in G.Lite mode.

The transmission mode and the corresponding line mode are defined as:

Transmission mode	Line Mode

Regional Std. (ANSI T1.413)	Full
[ANSI T1.413]	
Regional Std. (ETSI DTS/TM06006)	Full
[ETSI DTS/TM06006]	
G.992.1 [ITU G992.1] POTS non-overlapped	Full
G.992.1 POTS overlapped	Full
G.992.1 Integrated Services Digital	
Network (ISDN) non-overlapped	Full
G.992.1 ISDN overlapped	Full
G.992.1 TCM-ISDN non-overlapped	Full
G.992.1 TCM-ISDN overlapped	Full
G.992.2 POTS non-overlapped	G.Lite
G.992.2 POTS overlapped	G.Lite
G.992.2 with TCM-ISDN	G.Lite
non-overlapped	
G.992.2 with TCM-ISDN overlapped	G.Lite
G.992.1 TCM-ISDN symmetric	Full

Table 1: Transmission Mode and Line Mode

In case more than one bit is configured for an ADSL interface and both Full and G.Lite modes are selected, the interface is said to be configured in the dual mode. Only one bit can be set in the Actual object that reflects the actual mode of transmission as well as the line mode.

6.2.2 Power Management

There are three possible power states for each managed ADSL interface operating in the G.Lite mode. L0 is power on, L1 is power on but reduced and L3 is power off. Power state cannot be configured by an operator but it can be viewed via the ifOperStatus object for the

Expires August 2002

[Page 4]

managed ADSL interface. The value of the object `ifOperStatus` is set to `down(2)` if the ADSL interface is in power state L3 and is set to `up(1)` if the ADSL line interface is in power state L0 or L1.

An ADSL line power state, if the interface is operating in the G.Lite mode, can also be monitored by the `adslLineGlitePowerState` object defined in the ADSL Line Extension table. The value of the object enumerates the three power states attainable by the managed interface.

6.2.3 Fast Retrain Parameters

[Section 7.4.15](#) [ITU G.997.1] specifies fast retrain parameters. Fast retrain parameters include two counters: fast retrain count and failed fast retrain count. These two counters have been added to all performance tables.

6.2.4 Counters for Severely Errored Second-line and Unavailable Seconds-line

ITU G.997.1 sections [6.2.1.1.7](#) and [6.2.1.1.9](#) specify two counters that are not covered by the ADSL Line MIB [[RFC2662](#)]. These two counters (severely errored seconds-line and unavailable seconds-line) are added to all the performance tables.

Unavailable seconds counts cumulative number of seconds in which the interface was unavailable during the measured period. This counter does not include the seconds in which unavailability was caused solely by fast retrains and failed fast retrains. Fast retrains and failed fast retrains are considered to be part of the normal network operation and thus are not counted as unavailable errors.

6.2.5 Counters, Interval Buckets and Thresholds

For physical-level events, there are counters, current 15-minute and one (up to 96) 15-minute history bucket(s) of "interval-counters", as well as current and previous 1-day interval-counters. Threshold notification can be configured for each physical-layer current 15-minute bucket.

There is no requirement for an agent to ensure fixed relationship between the start of a fifteen minute and any wall clock; however some implementations may align the fifteen-minute intervals with quarter hours. Likewise, an implementation may choose to align one day intervals with start of a day.

Separate tables are provided for the 96 interval-counters. They are indexed by `{ifIndex, AdslAtu*IntervalNumber}`.

Expires August 2002

[Page 5]

Counters are not reset when an ATU-C or ATU-R is reinitialized, only when the agent is reset or reinitialized (or under specific request outside the scope of this MIB).

The 15-minute event counters are of type PerfCurrentCount and PerfIntervalCount. The 1-day event counters are of type AdslPerfCurrDayCount and AdslPerfPrevDayCount. Both 15-minute and 1-day time elapsed counters are of type AdslPerfTimeElapsed.

6.2.6 Alternative profile configuration for the dual line mode interface

The object, adslLineConfProfileDualLite, is used only when the interface (the ADSL line and, if applicable, channel) is configured as dual mode, that is, the object adslLineTransAtucConfig is configured with one or more full-rate modes and one or more G.Lite modes.

The object adslLineConfProfile defined in ADSL-MIB [[RFC2662](#)] is used as the primary full-rate profile. The newly added object in this MIB module, adslLineConfProfileDualLite, is used to describe and configure the G.Lite profile. Note that if one or more full-rate modes are configured, or only G.Lite modes are configured, only the original full-rate profile is needed. The dual-mode profile object is only needed when both full-rate and G.Lite profiles are needed. In this case, it will be set to the value of adslLineConfProfile when 'dynamic' profiles are implemented.

When 'static' profiles are implemented, however, similar to the case of the object, adslLineConfProfileName [[RFC2662](#)], this object's value will need to algorithmically represent the line. In this case, the value of the line's ifIndex plus a value indicating the line mode type (e.g., G.Lite, Full-rate) will be used. Therefore, the profile's name is a string of the concatenation of ifIndex and one of the follow values: Full or Lite. This string will be fixed-length (i.e., 14) with leading zero(s). For example, the profile name for ifIndex that equals '15' and is a full rate line, it will be '0000000015Full'.

7. Conformance and Compliance

See the conformance and compliance statements within the information module.

8. Definitions

ADSL-LINE-EXT-MIB DEFINITIONS ::= BEGIN

Expires August 2002

[Page 6]

IMPORTS

```
Counter32,
Integer32,
NOTIFICATION-TYPE,
MODULE-IDENTITY,
OBJECT-TYPE                                FROM SNMPv2-SMI
MODULE-COMPLIANCE, OBJECT-GROUP,
NOTIFICATION-GROUP                        FROM SNMPv2-CONF
TEXTUAL-CONVENTION                        FROM SNMPv2-TC
PerfCurrentCount,
PerfIntervalCount                        FROM PerfHist-TC-MIB
AdslPerfCurrDayCount,
AdslPerfPrevDayCount                    FROM ADSL-TC-MIB
SnmAdminString                          FROM SNMP-FRAMEWORK-MIB
adslLineAlarmConfProfileEntry,
adslLineConfProfileEntry,
adslAturIntervalEntry,
adslAturPerfDataEntry,
adslAtucIntervalEntry,
adslAtucPerfDataEntry,
adslLineEntry,
adslMIB                                FROM ADSL-LINE-MIB
;
```

adslExtMIB MODULE-IDENTITY

LAST-UPDATED "200204231200Z"

ORGANIZATION "IETF ADSL MIB Working Group"

CONTACT-INFO

"

Faye Ly
Pedestal Networks
3045 Park Boulevard
Palo Alto, CA 94306
Tel: +1 650-475-1274
Fax: +1 650-688-3119
E-Mail: faye@pedestalnetworks.com

Gregory Bathrick
NOKIA High Speed Access Nodes
1310 Redwood Way,
Petaluma, CA 94954
Tel: +1 707-793-7030
Fax: +1 707-792-0850
E-Mail: greg.bathrick@nokia.com

Expires August 2002

[Page 7]

IETF ADSL MIB Working Group
<XDSTMIB@LISTSERV.ECIRALEIGH.COM>
"

DESCRIPTION

"This MIB Module is a supplement to the ADSL-LINE-MIB
[RFC2662]."

REVISION "200204231200Z"

DESCRIPTION "Initial Version, published as RFC xxxx. This MIB
module supplements the ADSL-LINE-MIB [RFC2662]."
::= { adslMIB 3 }

adslExtMibObjects OBJECT IDENTIFIER ::= { adslExtMIB 1 }

AdslTransmissionModeType ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"A set of ADSL line transmission modes, with one bit
per mode. The notes (F) and (L) denote Full-Rate
and G.Lite respectively:

Bit 00 : Regional Std. (ANSI T1.413) (F)
Bit 01 : Regional Std. (ETSI DTS/TM06006) (F)
Bit 02 : G.992.1 POTS non-overlapped (F)
Bit 03 : G.992.1 POTS overlapped (F)
Bit 04 : G.992.1 ISDN non-overlapped (F)
Bit 05 : G.992.1 ISDN overlapped (F)
Bit 06 : G.992.1 TCM-ISDN non-overlapped (F)
Bit 07 : G.992.1 TCM-ISDN overlapped (F)
Bit 08 : G.992.2 POTS non-overlapped (L)
Bit 09 : G.992.2 POTS overlapped (L)
Bit 10 : G.992.2 with TCM-ISDN non-overlapped (L)
Bit 11 : G.992.2 with TCM-ISDN overlapped (L)
Bit 12 : G.992.1 TCM-ISDN symmetric (F)

"

SYNTAX BITS {
ansit1413(0),
etsi(1),
q9921PotsNonOverlapped(2),
q9921PotsOverlapped(3),
q9921IsdnNonOverlapped(4),
q9921IsdnOverlapped(5),
q9921tcmIsdnNonOverlapped(6),
q9921tcmIsdnOverlapped(7),
q9922potsNonOverlapped(8),
q9922potsOverlapped(9),
q9922tcmIsdnNonOverlapped(10),
q9922tcmIsdnOverlapped(11),
q9921tcmIsdnSymmetric(12)

}

Expires August 2002

[Page 8]

```
adslLineExtTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF AdslLineExtEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "This table is an extension of RFC2662. It
        contains ADSL line configuration and
        monitoring information. This includes the ADSL
        line's capabilities and actual ADSL transmission
        system."
    ::= { adslExtMibObjects 17 }

adslLineExtEntry OBJECT-TYPE
    SYNTAX      AdslLineExtEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "An entry extends the adslLineEntry defined in
        [RFC2662]. Each entry corresponds to an ADSL
        line."
    AUGMENTS { adslLineEntry }
    ::= { adslLineExtTable 1 }

AdslLineExtEntry ::=
    SEQUENCE {
        adslLineTransAtucCap      AdslTransmissionModeType,
        adslLineTransAtucConfig   AdslTransmissionModeType,
        adslLineTransAtucActual   AdslTransmissionModeType,
        adslLineGlitePowerState   INTEGER,
        adslLineConfProfileDualLite SnmpAdminString
    }

adslLineTransAtucCap OBJECT-TYPE
    SYNTAX      AdslTransmissionModeType
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The transmission modes, represented by a
        bitmask that the ATU-C is capable of
        supporting. The modes available are limited
        by the design of the equipment."
    REFERENCE   "Section 7.3.2 ITU G.997.1"
    ::= { adslLineExtEntry 1 }

adslLineTransAtucConfig OBJECT-TYPE
    SYNTAX      AdslTransmissionModeType
    MAX-ACCESS   read-write
    STATUS      current
```


Expires August 2002

[Page 9]

DESCRIPTION

"The transmission modes, represented by a bitmask, currently enabled by the ATU-C. The manager can only set those modes that are supported by the ATU-C. An ATU-C's supported modes are provided by AdslLineTransAtucCap."

REFERENCE "[Section 7.3.2](#) ITU G.997.1"

::= { adslLineExtEntry 2 }

adslLineTransAtucActual OBJECT-TYPE

SYNTAX AdslTransmissionModeType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The actual transmission mode of the ATU-C. During ADSL line initialization, the ADSL Transceiver Unit - Remote terminal end (ATU-R) will determine the mode used for the link. This value will be limited a single transmission mode that is a subset of those modes enabled by the ATU-C and denoted by adslLineTransAtucConfig. After an initialization has occurred, its mode is saved as the 'Current' mode and its persistence should the link go down. This object returns 0 (i.e. BITS with no mode bit set) if the mode is not known."

REFERENCE "[Section 7.3.2](#) ITU G.997.1 "

::= { adslLineExtEntry 3 }

adslLineGlitePowerState OBJECT-TYPE

SYNTAX INTEGER {
 none(1),
 l0(2), -- L0 Power on
 l1(3), -- L1 Power on but reduced
 l3(4) -- L3 Power off
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of this object specifies the power state of this interface. L0 is power on, L1 is power on but reduced and L3 is power off. Power state cannot be configured by an operator but it can be viewed via the ifOperStatus object for the managed ADSL interface. The value of the object ifOperStatus is set to down(2) if the ADSL interface is in power state L3 and is set to up(1) if the ADSL line interface is in power state L0 or L1. If the

Expires August 2002

[Page 10]

object adslLineTransAtucActual is set to a G.992.2 (G.Lite)-type transmission mode, the value of this object will be one of the valid power states: L0(2), L1(3), or L3(4). Otherwise, its value will be none(1)."

::= { adslLineExtEntry 4 }

adslLineConfProfileDualLite OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"This object extends the definition an ADSL line and associated channels (when applicable) for cases when it is configured in dual mode, and operating in a G.Lite-type mode as denoted by adslLineTransAtucActual. Dual mode exists when the object, adslLineTransAtucConfig, is configured with one or more full-rate modes and one or more G.Lite modes simultaneously.

When 'dynamic' profiles are implemented, the value of object is equal to the index of the applicable row in the ADSL Line Configuration Profile Table, AdslLineConfProfileTable defined in ADSL-MIB [[RFC2662](#)].

In the case when dual-mode has not been enabled, the value of the object will be equal to the value of the object adslLineConfProfile [[RFC2662](#)].

When 'static' profiles are implemented, in much like the case of the object, adslLineConfProfileName [[RFC2662](#)], this object's value will need to algorithmically represent the characteristics of the line. In this case, the value of the line's ifIndex plus a value indicating the line mode type (e.g., G.Lite, Full-rate) will be used. Therefore, the profile's name is a string concatenating the ifIndex and one of the follow values: Full or Lite. This string will be fixed-length (i.e., 14) with leading zero(s). For example, the profile name for ifIndex that equals '15' and is a full rate line, it will be '0000000015Full'."

REFERENCE "[Section 5.4](#) Profiles, [RFC 2662](#)"

::= { adslLineExtEntry 5 }

adslAtucPerfDataExtTable OBJECT-TYPE

Expires August 2002

[Page 11]

SYNTAX SEQUENCE OF AdslAtucPerfDataExtEntry
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION
 "This table extends adslAtucPerfDataTable [[RFC2662](#)]
 with additional ADSL physical line counter
 information such as unavailable seconds-line and
 severely errored seconds-line."

::= { adslExtMibObjects 18 }

adslAtucPerfDataExtEntry OBJECT-TYPE

SYNTAX AdslAtucPerfDataExtEntry
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION

 "An entry extends the adslAtucPerfDataEntry defined
 in [[RFC2662](#)]. Each entry corresponds to an ADSL
 line."

AUGMENTS { adslAtucPerfDataEntry }

::= { adslAtucPerfDataExtTable 1 }

AdslAtucPerfDataExtEntry ::=

SEQUENCE {
 adslAtucPerfStatFastR Counter32,
 adslAtucPerfStatFailedFastR Counter32,
 adslAtucPerfStatSesL Counter32,
 adslAtucPerfStatUasL Counter32,
 adslAtucPerfCurr15MinFastR PerfCurrentCount,
 adslAtucPerfCurr15MinFailedFastR PerfCurrentCount,
 adslAtucPerfCurr15MinSesL PerfCurrentCount,
 adslAtucPerfCurr15MinUasL PerfCurrentCount,
 adslAtucPerfCurr1DayFastR AdslPerfCurrDayCount,
 adslAtucPerfCurr1DayFailedFastR AdslPerfCurrDayCount,
 adslAtucPerfCurr1DaySesL AdslPerfCurrDayCount,
 adslAtucPerfCurr1DayUasL AdslPerfCurrDayCount,
 adslAtucPerfPrev1DayFastR AdslPerfPrevDayCount,
 adslAtucPerfPrev1DayFailedFastR AdslPerfPrevDayCount,
 adslAtucPerfPrev1DaySesL AdslPerfPrevDayCount,
 adslAtucPerfPrev1DayUasL AdslPerfPrevDayCount
 }

adslAtucPerfStatFastR OBJECT-TYPE

SYNTAX Counter32
 UNITS "line retrains"
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION

 "The value of this object reports the count of

Expires August 2002

[Page 12]

```
        the number of fast line bs since last
        agent reset."
    REFERENCE "ITU G.997.1 Section 7.4.15.1 "
 ::= { adslAtucPerfDataExtEntry 1 }

adslAtucPerfStatFailedFastR OBJECT-TYPE
    SYNTAX      Counter32
    UNITS        "line retrains"
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The value of this object reports the count of
         the number of failed fast line retrains since
         last agent reset."
    REFERENCE "ITU G.997.1 Section 7.4.15.2 "
 ::= { adslAtucPerfDataExtEntry 2 }

adslAtucPerfStatSesL OBJECT-TYPE
    SYNTAX      Counter32
    UNITS        "seconds"
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The value of this object reports the count of
         the number of severely errored seconds-line since
         last agent reset."
    REFERENCE "ITU G.997.1 Section 7.2.1.1.7 "
 ::= { adslAtucPerfDataExtEntry 3 }

adslAtucPerfStatUasL OBJECT-TYPE
    SYNTAX      Counter32
    UNITS        "seconds"
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The value of this object reports the count of
         the number of unavailable seconds-line since
         last agent reset."
    REFERENCE "ITU G.997.1 Section 7.2.1.1.9 "
 ::= { adslAtucPerfDataExtEntry 4 }

adslAtucPerfCurr15MinFastR OBJECT-TYPE
    SYNTAX      PerfCurrentCount
    UNITS        "seconds"
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "For the current 15-minute interval,
```


Expires August 2002

[Page 13]

adslAtucPerfCurr15MinFastR reports the current number of seconds during which there have been fast retrains."

REFERENCE "ITU G.997.1 [Section 7.4.15.1](#) "

::= { adslAtucPerfDataExtEntry 5 }

adslAtucPerfCurr15MinFailedFastR OBJECT-TYPE

SYNTAX PerfCurrentCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the current 15-minute interval, adslAtucPerfCurr15MinFailedFastR reports the current number of seconds during which there have been failed fast retrains."

REFERENCE "ITU G.997.1 [Section 7.4.15.2](#) "

::= { adslAtucPerfDataExtEntry 6 }

adslAtucPerfCurr15MinSesL OBJECT-TYPE

SYNTAX PerfCurrentCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the current 15-minute interval, adslAtucPerfCurr15MinSesL reports the current number of seconds during which there have been severely errored seconds-line."

REFERENCE "ITU G.997.1 [Section 7.2.1.1.7](#) "

::= { adslAtucPerfDataExtEntry 7 }

adslAtucPerfCurr15MinUasL OBJECT-TYPE

SYNTAX PerfCurrentCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the current 15-minute interval, adslAtucPerfCurr15MinUasL reports the current number of seconds during which there have been unavailable seconds-line."

REFERENCE "ITU G.997.1 [Section 7.2.1.1.9](#) "

::= { adslAtucPerfDataExtEntry 8 }

adslAtucPerfCurr1DayFastR OBJECT-TYPE

SYNTAX AdslPerfCurrDayCount

UNITS "seconds"

Expires August 2002

[Page 14]

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the current day as measured by
adslAtucPerfCurr1DayTimeElapsed [[RFC 2662](#)],
adslAtucPerfCurr1DayFastR reports the number
of seconds during which there have been
fast retrains."

REFERENCE "ITU G.997.1 [Section 7.4.15.1](#) "

::= { adslAtucPerfDataExtEntry 9 }

adslAtucPerfCurr1DayFailedFastR OBJECT-TYPE

SYNTAX AdslPerfCurrDayCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the current day as measured by
adslAtucPerfCurr1DayTimeElapsed [[RFC 2662](#)],
adslAtucPerfCurr1DayFailedFastR reports the
number of seconds during which there have been
failed fast retrains."

REFERENCE "ITU G.997.1 [Section 7.4.15.2](#) "

::= { adslAtucPerfDataExtEntry 10 }

adslAtucPerfCurr1DaySesL OBJECT-TYPE

SYNTAX AdslPerfCurrDayCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the current day as measured by
adslAtucPerfCurr1DayTimeElapsed [[RFC 2662](#)],
adslAtucPerfCurr1DaySesL reports the
number of seconds during which there have been
severely errored seconds-line."

REFERENCE "ITU G.997.1 [Section 7.2.1.1.7](#) "

::= { adslAtucPerfDataExtEntry 11 }

adslAtucPerfCurr1DayUasL OBJECT-TYPE

SYNTAX AdslPerfCurrDayCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the current day as measured by
adslAtucPerfCurr1DayTimeElapsed [[RFC 2662](#)],
adslAtucPerfCurr1DayUasL reports the

Expires August 2002

[Page 15]

number of seconds during which there have been
unavailable seconds-line."

REFERENCE "ITU G.997.1 [Section 7.2.1.1.9](#) "

::= { adslAtucPerfDataExtEntry 12 }

adslAtucPerfPrev1DayFastR OBJECT-TYPE

SYNTAX AdslPerfPrevDayCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the previous day, adslAtucPerfPrev1DayFastR
reports the number of seconds during which there
were fast retrains."

REFERENCE "ITU G.997.1 [Section 7.4.15.1](#) "

::= { adslAtucPerfDataExtEntry 13 }

adslAtucPerfPrev1DayFailedFastR OBJECT-TYPE

SYNTAX AdslPerfPrevDayCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the previous day, adslAtucPerfPrev1DayFailedFastR
reports the number of seconds during which there
were failed fast retrains."

REFERENCE "ITU G.997.1 [Section 7.4.15.2](#) "

::= { adslAtucPerfDataExtEntry 14 }

adslAtucPerfPrev1DaySesL OBJECT-TYPE

SYNTAX AdslPerfPrevDayCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the previous day, adslAtucPerfPrev1DaySesL
reports the number of seconds during which there
were severely errored seconds-line."

REFERENCE "ITU G.997.1 [Section 7.2.1.1.7](#) "

::= { adslAtucPerfDataExtEntry 15 }

adslAtucPerfPrev1DayUasL OBJECT-TYPE

SYNTAX AdslPerfPrevDayCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the previous day, adslAtucPerfPrev1DayUasL

Expires August 2002

[Page 16]

reports the number of seconds during which there were unavailable seconds-line."

REFERENCE "ITU G.997.1 [Section 7.2.1.1.9](#) "

::= { adslAtucPerfDataExtEntry 16 }

adslAtucIntervalExtTable OBJECT-TYPE

SYNTAX SEQUENCE OF AdslAtucIntervalExtEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table provides one row for each ATU-C performance data collection interval for ADSL physical interfaces whose IfEntries' ifType is equal to adsl(94)."

::= { adslExtMibObjects 19 }

adslAtucIntervalExtEntry OBJECT-TYPE

SYNTAX AdslAtucIntervalExtEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION "An entry in the adslAtucIntervalExtTable."

AUGMENTS { adslAtucIntervalEntry }

::= { adslAtucIntervalExtTable 1 }

AdslAtucIntervalExtEntry ::=

SEQUENCE {

adslAtucIntervalFastR PerfIntervalCount,

adslAtucIntervalFailedFastR PerfIntervalCount,

adslAtucIntervalSesL PerfIntervalCount,

adslAtucIntervalUasL PerfIntervalCount

}

adslAtucIntervalFastR OBJECT-TYPE

SYNTAX PerfIntervalCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the current interval, adslAtucIntervalFastR reports the current number of seconds during which there have been fast retrains."

::= { adslAtucIntervalExtEntry 1 }

adslAtucIntervalFailedFastR OBJECT-TYPE

SYNTAX PerfIntervalCount

UNITS "seconds"

MAX-ACCESS read-only

Expires August 2002

[Page 17]

```
STATUS      current
DESCRIPTION
    "For the each interval, adslAtucIntervalFailedFastR
    reports the number of seconds during which
    there have been failed fast retrains."
::= { adslAtucIntervalExtEntry 2 }

adslAtucIntervalSesL OBJECT-TYPE
    SYNTAX      PerfIntervalCount
    UNITS        "seconds"
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "For the each interval, adslAtucIntervalSesL
        reports the number of seconds during which
        there have been severely errored seconds-line."
    ::= { adslAtucIntervalExtEntry 3 }

adslAtucIntervalUasL OBJECT-TYPE
    SYNTAX      PerfIntervalCount
    UNITS        "seconds"
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "For the each interval, adslAtucIntervalUasL
        reports the number of seconds during which
        there have been unavailable seconds-line."
    ::= { adslAtucIntervalExtEntry 4 }

adslAturPerfDataExtTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF AdslAturPerfDataExtEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains ADSL physical line counters
        not defined in the adslAturPerfDataTable
        from the ADSL-LINE-MIB [RFC2662]."
    ::= { adslExtMibObjects 20 }

adslAturPerfDataExtEntry OBJECT-TYPE
    SYNTAX      AdslAturPerfDataExtEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "An entry extends the adslAturPerfDataEntry defined
        in [RFC2662]. Each entry corresponds to an ADSL
        line."
    AUGMENTS { adslAturPerfDataEntry }
```

Expires August 2002

[Page 18]

```
::= { adslAturPerfDataExtTable 1 }
```

```
AdslAturPerfDataExtEntry ::=
```

```
    SEQUENCE {
        adslAturPerfStatSesL          Counter32,
        adslAturPerfStatUasL          Counter32,
        adslAturPerfCurr15MinSesL     PerfCurrentCount,
        adslAturPerfCurr15MinUasL     PerfCurrentCount,
        adslAturPerfCurr1DaySesL      AdslPerfCurrDayCount,
        adslAturPerfCurr1DayUasL      AdslPerfCurrDayCount,
        adslAturPerfPrev1DaySesL      AdslPerfPrevDayCount,
        adslAturPerfPrev1DayUasL      AdslPerfPrevDayCount
    }
```

```
adslAturPerfStatSesL OBJECT-TYPE
```

```
    SYNTAX      Counter32
```

```
    UNITS       "seconds"
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The value of this object reports the count of
         severely errored second-line since the last agent
         reset."
```

```
    REFERENCE "ITU G.997.1 Section 7.2.1.1.7 "
```

```
::= { adslAturPerfDataExtEntry 1 }
```

```
adslAturPerfStatUasL OBJECT-TYPE
```

```
    SYNTAX      Counter32
```

```
    UNITS       "seconds"
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The value of this object reports the count of
         unavailable seconds-line since the last agent
         reset."
```

```
    REFERENCE "ITU G.997.1 Section 7.2.1.2.9 "
```

```
::= { adslAturPerfDataExtEntry 2 }
```

```
adslAturPerfCurr15MinSesL OBJECT-TYPE
```

```
    SYNTAX      PerfCurrentCount
```

```
    UNITS       "seconds"
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "For the current 15-minute interval,
         adslAturPerfCurr15MinSesL reports the current
         number of seconds during which there have been
         severely errored seconds-line."
```

Expires August 2002

[Page 19]

```
REFERENCE "ITU G.997.1 Section 7.2.1.2.7 "  
 ::= { adslAturPerfDataExtEntry 3 }  
  
adslAturPerfCurr15MinUasL    OBJECT-TYPE  
    SYNTAX      PerfCurrentCount  
    UNITS       "seconds"  
    MAX-ACCESS  read-only  
    STATUS      current  
    DESCRIPTION  
        "For the current 15-minute interval,  
        adslAturPerfCurr15MinUasL reports the current  
        number of seconds during which there have been  
        available seconds-line."  
    REFERENCE "ITU G.997.1 Section 7.2.1.2.9 "  
 ::= { adslAturPerfDataExtEntry 4 }  
  
adslAturPerfCurr1DaySesL    OBJECT-TYPE  
    SYNTAX      AdslPerfCurrDayCount  
    UNITS       "seconds"  
    MAX-ACCESS  read-only  
    STATUS      current  
    DESCRIPTION  
        "For the current day as measured by  
        adslAturPerfCurr1DayTimeElapsed [RFC 2662],  
        adslAturPerfCurr1DaySesL reports the  
        number of seconds during which there have been  
        severely errored seconds-line."  
    REFERENCE "ITU G.997.1 Section 7.2.1.2.7 "  
 ::= { adslAturPerfDataExtEntry 5 }  
  
adslAturPerfCurr1DayUasL    OBJECT-TYPE  
    SYNTAX      AdslPerfCurrDayCount  
    UNITS       "seconds"  
    MAX-ACCESS  read-only  
    STATUS      current  
    DESCRIPTION  
        "For the current day as measured by  
        adslAturPerfCurr1DayTimeElapsed [RFC 2662],  
        adslAturPerfCurr1DayUasL reports the  
        number of seconds during which there have been  
        unavailable seconds-line."  
    REFERENCE "ITU G.997.1 Section 7.2.1.2.9 "  
 ::= { adslAturPerfDataExtEntry 6 }  
  
adslAturPerfPrev1DaySesL    OBJECT-TYPE  
    SYNTAX      AdslPerfPrevDayCount  
    UNITS       "seconds"  
    MAX-ACCESS  read-only
```

Expires August 2002

[Page 20]

STATUS current

DESCRIPTION

"For the previous day, adslAturPerfPrev1DaySesL reports the number of seconds during which there were severely errored seconds-line."

REFERENCE "ITU G.997.1 [Section 7.2.1.2.7](#) "

::= { adslAturPerfDataExtEntry 7 }

adslAturPerfPrev1DayUasL OBJECT-TYPE

SYNTAX AdslPerfPrevDayCount

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"For the previous day, adslAturPerfPrev1DayUasL reports the number of seconds during which there were severely errored seconds-line."

REFERENCE "ITU G.997.1 [Section 7.2.1.2.9](#) "

::= { adslAturPerfDataExtEntry 8 }

adslAturIntervalExtTable OBJECT-TYPE

SYNTAX SEQUENCE OF AdslAturIntervalExtEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table provides one row for each ATU-R performance data collection interval for ADSL physical interfaces whose IfEntries' ifType is equal to adsl(94)."

::= { adslExtMibObjects 21 }

adslAturIntervalExtEntry OBJECT-TYPE

SYNTAX AdslAturIntervalExtEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION "An entry in the adslAturIntervalExtTable."

AUGMENTS { adslAturIntervalEntry }

::= { adslAturIntervalExtTable 1 }

AdslAturIntervalExtEntry ::=

SEQUENCE {

adslAturIntervalSesL PerfIntervalCount,

adslAturIntervalUasL PerfIntervalCount

}

adslAturIntervalSesL OBJECT-TYPE

SYNTAX PerfIntervalCount

Expires August 2002

[Page 21]

UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"For the each interval, adslAturIntervalSesL
reports the number of seconds during which
there have been severely errored seconds-line."
::= { adslAturIntervalExtEntry 1 }

adslAturIntervalUasL OBJECT-TYPE
SYNTAX PerfIntervalCount
UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"For the each interval, adslAturIntervalUasL
reports the number of seconds during which
there have been unavailable seconds-line."
::= { adslAturIntervalExtEntry 2 }

adslConfProfileExtTable OBJECT-TYPE
SYNTAX SEQUENCE OF AdslConfProfileExtEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The adslConfProfileExtTable extends the ADSL line
profile configuration information in the
adslLineConfProfileTable from the ADSL-LINE-MIB
[[RFC2662](#)] by adding the ability to configure the
ADSL physical line mode."
::= { adslExtMibObjects 22 }

adslConfProfileExtEntry OBJECT-TYPE
SYNTAX AdslConfProfileExtEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"An entry extends the adslLineConfProfileEntry defined
in [[RFC2662](#)]. Each entry corresponds to an ADSL line
profile."
AUGMENTS { adslLineConfProfileEntry }
::= { adslConfProfileExtTable 1 }

AdslConfProfileExtEntry ::=
SEQUENCE {
adslConfProfileLineType INTEGER
}

Expires August 2002

[Page 22]

adslConfProfileLineType OBJECT-TYPE

```
SYNTAX      INTEGER {
    noChannel (1),          -- no channels exist
    fastOnly (2),           -- only fast channel exists
    interleavedOnly (3),    -- only interleaved channel
                           -- exist
    fastOrInterleaved (4),  -- either fast or interleaved
                           -- channels can exist, but
                           -- only one at any time
    fastAndInterleaved (5) -- both the fast channel and
                           -- the interleaved channel
                           -- exist
}
```

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object is used to configure the ADSL physical line mode. It has following valid values:

noChannel(1), when no channels exist.

fastOnly(2), when only fast channel exists.

interleavedOnly(3), when only interleaved channel exist.

fastOrInterleaved(4), when either fast or interleaved channels can exist, but only one at any time.

fastAndInterleaved(5), when both the fast channel and the interleaved channel exist.

In the case when no value has been set, the default Value is noChannel(1).

"

DEFVAL { fastOnly }

::= { adslConfProfileExtEntry 1 }

adslAlarmConfProfileExtTable OBJECT-TYPE

SYNTAX SEQUENCE OF AdslAlarmConfProfileExtEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table extends the adslLineAlarmConfProfileTable and provides threshold parameters for all the counters defined in this MIB module."

::= { adslExtMibObjects 23 }

adslAlarmConfProfileExtEntry OBJECT-TYPE

SYNTAX AdslAlarmConfProfileExtEntry

MAX-ACCESS not-accessible

Expires August 2002

[Page 23]

```
STATUS          current
DESCRIPTION
    "An entry extends the adslLineAlarmConfProfileTable
    defined in [RFC2662]. Each entry corresponds to
    an ADSL alarm profile."
AUGMENTS { adslLineAlarmConfProfileEntry }
 ::= { adslAlarmConfProfileExtTable 1 }

AdslAlarmConfProfileExtEntry ::=
    SEQUENCE {
        adslAtucThreshold15MinFailedFastR      Integer32,
        adslAtucThreshold15MinSesL              Integer32,
        adslAtucThreshold15MinUasL              Integer32,
        adslAturThreshold15MinSesL              Integer32,
        adslAturThreshold15MinUasL              Integer32
    }

adslAtucThreshold15MinFailedFastR  OBJECT-TYPE
    SYNTAX      Integer32(0..900)
    UNITS        "seconds"
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The first time the value of the corresponding
        instance of adslAtucPerfCurr15MinFailedFastR reaches
        or exceeds this value within a given 15-minute
        performance data collection period, an
        adslAtucFailedFastRThreshTrap notification will
        be generated. The value '0' will disable the
        notification. The default value of this object is
        '0'."
    DEFVAL { 0 }
 ::= { adslAlarmConfProfileExtEntry 1 }

adslAtucThreshold15MinSesL OBJECT-TYPE
    SYNTAX      Integer32(0..900)
    UNITS        "seconds"
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The first time the value of the corresponding instance
        of adslAtucPerf15MinSesL reaches or exceeds
        this value within a given 15-minute performance data
        collection period, an adslAtucSesLThreshTrap
        notification will be generated. The value '0' will
        disable the notification. The default value of this
        object is '0'."
    DEFVAL { 0 }
```

Expires August 2002

[Page 24]

```
::= { adslAlarmConfProfileExtEntry 2 }
```

```
adslAtucThreshold15MinUasL OBJECT-TYPE
```

```
    SYNTAX      Integer32(0..900)
```

```
    UNITS       "seconds"
```

```
    MAX-ACCESS  read-create
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The first time the value of the corresponding instance
        of adslAtucPerf15MinUasL reaches or exceeds
        this value within a given 15-minute performance data
        collection period, an adslAtucUasLThreshTrap
        notification will be generated. The value '0' will
        disable the notification. The default value of this
        object is '0'."
```

```
    DEFVAL { 0 }
```

```
::= { adslAlarmConfProfileExtEntry 3 }
```

```
adslAturThreshold15MinSesL OBJECT-TYPE
```

```
    SYNTAX      Integer32(0..900)
```

```
    UNITS       "seconds"
```

```
    MAX-ACCESS  read-create
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The first time the value of the corresponding instance
        of adslAturPerf15MinSesL reaches or exceeds
        this value within a given 15-minute performance data
        collection period, an adslAturSesLThreshTrap
        notification will be generated. The value '0' will
        disable the notification. The default value of this
        object is '0'."
```

```
    DEFVAL { 0 }
```

```
::= { adslAlarmConfProfileExtEntry 4 }
```

```
adslAturThreshold15MinUasL OBJECT-TYPE
```

```
    SYNTAX      Integer32(0..900)
```

```
    UNITS       "seconds"
```

```
    MAX-ACCESS  read-create
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The first time the value of the corresponding instance
        of adslAturPerf15MinUasL reaches or exceeds
        this value within a given 15-minute performance data
        collection period, an adslAturUasLThreshTrap
        notification will be generated. The value '0' will
        disable the notification. The default value of this
        object is '0'."
```

```
    DEFVAL { 0 }
```


Expires August 2002

[Page 25]

```
 ::= { adslAlarmConfProfileExtEntry 5 }

-- definitions

adslExtTraps OBJECT IDENTIFIER ::= { adslExtMibObjects 24 }

adslExtAtucTraps OBJECT IDENTIFIER ::= { adslExtTraps 1 }

adslExtAtucTrapsPrefix OBJECT IDENTIFIER ::= { adslExtAtucTraps 0 }

adslAtucFailedFastRThreshTrap      NOTIFICATION-TYPE
    OBJECTS { adslAtucPerfCurr15MinFailedFastR }
    STATUS current
    DESCRIPTION
        "Failed Fast Retrains 15-minute threshold reached."
 ::= { adslExtAtucTrapsPrefix 1 }

adslAtucSesLThreshTrap             NOTIFICATION-TYPE
    OBJECTS { adslAtucPerfCurr15MinSesL }
    STATUS current
    DESCRIPTION
        "Severely errored seconds-line 15-minute threshold
        reached."
 ::= { adslExtAtucTrapsPrefix 2 }

adslAtucUasLThreshTrap             NOTIFICATION-TYPE
    OBJECTS { adslAtucPerfCurr15MinUasL }
    STATUS current
    DESCRIPTION
        "Unavailable seconds-line 15-minute threshold reached."
 ::= { adslExtAtucTrapsPrefix 3 }

adslExtAturTraps OBJECT IDENTIFIER ::= { adslExtTraps 2 }

adslExtAturTrapsPrefix OBJECT IDENTIFIER ::= { adslExtAturTraps 0 }

adslAturSesLThreshTrap             NOTIFICATION-TYPE
    OBJECTS { adslAturPerfCurr15MinSesL }
    STATUS current
    DESCRIPTION
        "Severely errored seconds-line 15-minute threshold
        reached."
 ::= { adslExtAturTrapsPrefix 1 }

adslAturUasLThreshTrap             NOTIFICATION-TYPE
    OBJECTS { adslAturPerfCurr15MinUasL }
    STATUS current
```


DESCRIPTION

"Unavailable seconds-line 15-minute threshold reached."

::= { adslExtAturTrapsPrefix 2 }

-- conformance information

adslExtConformance OBJECT IDENTIFIER ::= { adslExtMIB 2 }

adslExtGroups OBJECT IDENTIFIER ::= { adslExtConformance 1 }

adslExtCompliances OBJECT IDENTIFIER ::= { adslExtConformance 2 }

-- ATU-C agent compliance statements

adslExtLineMibAtucCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for SNMP entities which
represent ADSL ATU-C interfaces."

MODULE -- this module

MANDATORY-GROUPS

```
{
  adslExtLineGroup,
  adslExtLineConfProfileControlGroup,
  adslExtLineAlarmConfProfileGroup
}
```

GROUP adslExtAtucPhysPerfCounterGroup

DESCRIPTION

"This group is optional. Implementations which
require continuous ATU-C physical event counters
should implement this group."

GROUP adslExtAturPhysPerfCounterGroup

DESCRIPTION

"This group is optional. Implementations which
require continuous ATU-R physical event counters
should implement this group."

GROUP adslExtNotificationsGroup

DESCRIPTION

"This group is optional. Implementations which
support TCA (Threshold Crossing Alert) should
implement this group."

OBJECT adslAtucThreshold15MinFailedFastR

MIN-ACCESS read-write

DESCRIPTION

"Read-write access is applicable only when static profiles as defined in ADSL Line MIB [[RFC2662](#)] are implemented."

OBJECT adslAtucThreshold15MinSesL

MIN-ACCESS read-write

DESCRIPTION

"Read-write access is applicable only when static profiles as defined in ADSL Line MIB [[RFC2662](#)] are implemented."

OBJECT adslAtucThreshold15MinUasL

MIN-ACCESS read-write

DESCRIPTION

"Read-write access is applicable only when static profiles as defined in ADSL Line MIB [[RFC2662](#)] are implemented."

OBJECT adslAturThreshold15MinSesL

MIN-ACCESS read-write

DESCRIPTION

"Read-write access is applicable only when static profiles as defined in ADSL Line MIB [[RFC2662](#)] are implemented."

OBJECT adslAturThreshold15MinUasL

MIN-ACCESS read-write

DESCRIPTION

"Read-write access is applicable only when static profiles as defined in ADSL Line MIB [[RFC2662](#)] are implemented."

OBJECT adslLineConfProfileDualLite

MIN-ACCESS read-only

DESCRIPTION

"Read-only access is applicable only when static profiles as defined in ADSL Line MIB [[RFC2662](#)] are implemented."

::= { adslExtCompliances 1 }

-- units of conformance

adslExtLineGroup OBJECT-GROUP

OBJECTS {

 adslLineConfProfileDualLite,
 adslLineTransAtucCap,
 adslLineTransAtucConfig,


```
        adslLineTransAtucActual,
        adslLineGlitePowerState
    }
    STATUS      current
    DESCRIPTION
        "A collection of objects providing extended
        configuration information about an ADSL Line."
 ::= { adslExtGroups 1 }

adslExtAtucPhysPerfCounterGroup OBJECT-GROUP
    OBJECTS {
        adslAtucPerfStatFastR,
        adslAtucPerfStatFailedFastR,
        adslAtucPerfCurr15MinFastR,
        adslAtucPerfCurr15MinFailedFastR,
        adslAtucPerfCurr1DayFastR,
        adslAtucPerfCurr1DayFailedFastR,
        adslAtucPerfPrev1DayFastR,
        adslAtucPerfPrev1DayFailedFastR,
        adslAtucPerfStatSesL,
        adslAtucPerfStatUasL,
        adslAtucPerfCurr15MinSesL,
        adslAtucPerfCurr15MinUasL,
        adslAtucPerfCurr1DaySesL,
        adslAtucPerfCurr1DayUasL,
        adslAtucPerfPrev1DaySesL,
        adslAtucPerfPrev1DayUasL,
        adslAtucIntervalFastR,
        adslAtucIntervalFailedFastR,
        adslAtucIntervalSesL,
        adslAtucIntervalUasL
    }
    STATUS      current
    DESCRIPTION
        "A collection of objects providing raw performance
        counts on an ADSL Line (ATU-C end)."
 ::= { adslExtGroups 2 }

adslExtAturPhysPerfCounterGroup OBJECT-GROUP
    OBJECTS {
        adslAturPerfStatSesL,
        adslAturPerfStatUasL,
        adslAturPerfCurr15MinSesL,
        adslAturPerfCurr15MinUasL,
        adslAturPerfCurr1DaySesL,
        adslAturPerfCurr1DayUasL,
        adslAturPerfPrev1DaySesL,
        adslAturPerfPrev1DayUasL,
```


Expires August 2002

[Page 29]

```
        adslAturIntervalSesL, adslAturIntervalUasL
    }
    STATUS      current
    DESCRIPTION
        "A collection of objects providing raw performance
        counts on an ADSL Line (ATU-C end)."
```

::= { adslExtGroups 3 }

adslExtLineConfProfileControlGroup OBJECT-GROUP

```
    OBJECTS {
        adslConfProfileLineType
    }
    STATUS      current
    DESCRIPTION
        "A collection of objects providing profile
        control for the ADSL system."
```

::= { adslExtGroups 4 }

adslExtLineAlarmConfProfileGroup OBJECT-GROUP

```
    OBJECTS {
        adslAtucThreshold15MinFailedFastR,
        adslAtucThreshold15MinSesL,
        adslAtucThreshold15MinUasL,
        adslAturThreshold15MinSesL,
        adslAturThreshold15MinUasL
    }
    STATUS      current
    DESCRIPTION
        "A collection of objects providing alarm profile
        control for the ADSL system."
```

::= { adslExtGroups 5 }

adslExtNotificationsGroup NOTIFICATION-GROUP

```
    NOTIFICATIONS {
        adslAtucFailedFastRThreshTrap,
        adslAtucSesLThreshTrap,
        adslAtucUasLThreshTrap,
        adslAturSesLThreshTrap,
        adslAturUasLThreshTrap
    }
    STATUS      current
    DESCRIPTION
        "The collection of ADSL extension notifications."
```

::= { adslExtGroups 6 }

END

9. Acknowledgments

Expires August 2002

[Page 30]

This document is a product of the ADSL MIB Working Group.

10. Normative References

- [ANSI T1.413] American National Standards Institute, ANSI T1.413, Issue 2, "Standards Project for Interfaces Relating to Carrier to Customer Connection of ADSL Equipment", 1998.
- [ETSI DTS/TM06006] European Telecommunications Standards Institute "ADSL European Specific Requirements", November 2000.
- [ITU G.992.1] ITU-T Telecommunication Standardization Sector, "Asymmetric digital subscriber line (ADSL) transceivers", June 1999.
- [ITU G.992.2] ITU-T Telecommunication Standardization Sector, "Splitterless asymmetric digital subscriber line (ADSL) transceivers", June 1999.
- [ITU G.997.1] ITU-T Telecommunication Standardization Sector, "Physical Layer Management of Digital Subscriber Transceivers", June 1999.
- [RFC1155] Rose, M., and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based Internets", STD 16, [RFC 1155](#), May 1990.
- [RFC1157] Case, J., Fedor, M., Schoffstall, M., and J. Davin, "Simple Network Management Protocol", STD 15, [RFC 1157](#), May 1990.
- [RFC1212] Rose, M. and K. McCloghrie, "Concise MIB Definitions", STD 16, [RFC 1212](#), March 1991.
- [RFC1215] M. Rose, "A Convention for Defining Traps for use with the SNMP", [RFC 1215](#), March 1991.
- [RFC1901] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Introduction to Community-based SNMPv2", [RFC 1901](#), January 1996.
- [RFC1905] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1905](#), January 1996.
- [RFC1906] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser,

- "Transport Mappings for Version 2 of the Simple Network Management Protocol (SNMPv2)", [RFC 1906](#), January 1996.
- [RFC2026] Bradner S., "The Internet Standards Process - Revision 3", October 1996.
- [RFC2028] Hovey R., S. Bradner, "The Organizations Involved in the IETF Standards Process", October 1996.
- [RFC2570] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction to Version 3 of the Internet-standard Network Management Framework", [RFC 2570](#), April 1999.
- [RFC2571] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing SNMP Management Frameworks", [RFC 2571](#), April 1999.
- [RFC2572] Case, J., Harrington D., Presuhn R., and B. Wijnen, "Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)", [RFC 2572](#), April 1999.
- [RFC2573] Levi, D., Meyer, P., and B. Stewart, "SNMPv3 Applications", [RFC 2573](#), April 1999.
- [RFC2574] Blumenthal, U., and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", [RFC 2574](#), April 1999.
- [RFC2575] Wijnen, B., Presuhn, R., and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", [RFC 2575](#), April 1999.
- [RFC2578] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC2662] Bathrick, G. and F. Ly "Definitions of Managed Objects for the ADSL Lines", May 1999.

[RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), June 2000.

11. Security Considerations

The following security matters should be considered when implementing this MIB.

1) Blocking unauthorized access to the ADSL MIB via the element management system is outside the scope of this document. It should be noted that access to the MIB permits the unauthorized entity to modify the profiles ([section 6.4](#)) such that both subscriber service and network operations can be interfered with. Subscriber service can be altered by modifying any of a number of service characteristics such as rate partitioning and maximum transmission rates. Network operations can be impacted by modification of notification thresholds such as Signal-to-Noise Ratio (SNR) margins.

2) There are a number of managed objects in this MIB that may be considered to contain sensitive information. In particular, the certain objects may be considered sensitive in many environments, since it would allow an intruder to obtain information about which vendor's equipment is in use on the network. Therefore, it may be important in some environments to control read access to these objects and possibly to even encrypt the values of these object when sending them over the network via SNMP. Not all versions of SNMP provide features for such a secure environment.

SNMPv1 by itself is such an insecure environment. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET (read) the objects in this MIB. It is recommended that the implementors consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model [RFC 2574](#) [21] and the View-based Access Control Model [RFC 2575](#) [23] is recommended.

It is then a customer/user responsibility to ensure that the SNMP entity giving access to an instance of this MIB, is properly configured to give access to those objects only to those principals (users) that have legitimate rights to access them.

3) The profile mechanism presented in this document requires specific attention. The implementor of this MIB has a choice of implementing either 'static' or 'dynamic' profiles. This decision must be consistent with the implementation of [RFC2662](#).

In the case of 'static' profiles, the elements of the profile are read-write as opposed to read-create when 'dynamic' profiles are implemented:

- adslConfProfileLineType,
 - adslAtucThreshold15MinFailedFastR,
 - adslAtucThreshold15MinSesL,
 - adslAtucThreshold15MinUasL,
- adslAturThreshold15MinSesL, and
- adslAturThreshold15MinUasL.

This decision also impacts the mechanics of the index, adslLineConfProfileDualLite. When 'static' profiles are implemented, its value is algorithmically set by the system and its value is based on the ifIndex, hence not guaranteed across system reboots. Similar to the handling of adslLineConfProfile [[RFC2662](#)], the implementor of this MIB must ensure that the profile object values associated with these indices are maintained across system reboots.

In the case of dynamic profiles, this object is set by the SNMP manager. The implementor of this MIB may want to provide view of the profile on a customer-by-customer standpoint, but should be cautious of the dynamic nature of these objects.

4) ADSL layer connectivity from the ATU-R will permit the subscriber to manipulate both the ADSL link directly and the ADSL overhead control channel(AOC)/embedded operations channel (EOC) for their own loop. For example, unchecked or unfiltered fluctuations initiated by the subscriber could generate sufficient notifications to potentially overwhelm either the management interface to the network or the element manager. Other attacks affecting the ATU-R portions of the MIB may also be possible.

12. Intellectual Property Notice

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in [BCP-11](#) [[RFC2028](#)]. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

Expires August 2002

[Page 34]

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

13. Authors' Addresses

Faye Ly
Pedestal Networks
3045 Park Boulevard
Palo Alto, CA 94306, USA

Phone: +1 650-475-1274
Fax: +1 650-688-3119
EMail: faye@pedestalnetworks.com

Gregory Bathrick
NOKIA High Speed Access Nodes
1310 Redwood Way,
Petaluma, CA 94954, USA

Phone: +1 707-793-7030
Fax: +1 707-792-0850
EMail: greg.bathrick@nokia.com

14. Full Copyright Statement

Copyright (C) The Internet Society (2002). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an

"AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

Table of Contents

1.	Status of this Memo	1
2.	Abstract	1
3.	The SNMP Network Management Framework	1
4.	Introduction	2
5.	Relationship of ADSL LINE EXTENSION MIB with standard MIBs.	3
6.	Conventions used in the MIB	3
7.	Conformance and Compliance	5
8.	Definitions	5
9.	Acknowledgments	25
10.	References	26
11.	Security Considerations	27
12.	Intellectual Property Notice	27
13.	Authors' Addresses	28
14.	Full Copyright Statement	29

