

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: November 29, 2010

E. Beili
Actelis Networks
M. Morgenstern
ECI Telecom
May 28, 2010

xDSL multi-pair bonding (G.Bond) MIB
draft-ietf-adslmib-gbond-mib-04.txt

Abstract

This document defines Management Information Base (MIB) module for use with network management protocols in TCP/IP-based internets. This document proposes an extension to the Interfaces Group MIB with a set of common objects for managing multi-pair bonded Digital Subscriber Line (xDSL) interfaces, defined in ITU-T recommendations G.998.1, G.998.2 and G.998.3. The MIB modules specific to each bonding technology are defined in GBOND-ATM-MIB, GBOND-ETH-MIB and GBOND-TDIM-MIB respectively.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 29, 2010.

Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	The Internet-Standard Management Framework	4
3.	The DSL Forum Management Framework for xDSL Bonding	4
4.	Relationship to Other MIB modules	4
4.1.	Relationship to Interfaces Group MIB module	5
4.1.1.	Layering Model	5
4.1.2.	xDSL Bonding	7
4.1.3.	Discovery Operation	7
4.1.4.	G.Bond ports initialization	9
4.1.5.	Usage of ifTable	10
4.2.	Relationship to xDSL MIB modules	11
5.	MIB Structure	11
5.1.	Overview	11
5.2.	Performance Monitoring	12
5.3.	Mapping of DSL Forum TR-159 Managed Objects	12
6.	xDSL Multi-pair Bonding MIB Definitions	16
7.	Security Considerations	60
8.	IANA Considerations	61
9.	Acknowledgments	61
10.	References	62
10.1.	Normative References	62
10.2.	Informative References	63

1. Introduction

The xDSL Multi-Pair Bonding, allows a service provider to provide high bandwidth services to business and residential customers over multiple xDSL lines, with greater speed and resiliency, than the service over a single xDSL line, bridging the gap between xDSL and fiber-based transport.

There are three xDSL Multi-Pair Bonding schemes, also known under collective name G.Bond:

- o The ATM-Based Multi-Pair Bonding, specified in ITU-T G.998.1 recommendation [[G.998.1](#)], which defines a method for bonding (or aggregating) of multiple xDSL lines (or individual bearer channels in multiple xDSL lines) into a single bi-directional logical link carrying an ATM stream. This specification can be viewed as an evolution of the legacy Inverse Multiplexing over ATM (IMA) technology [[af-phy-0086](#)], applied to xDSL with variable rates on each line/bearer channel.
- o The Ethernet-Based Multi-Pair Bonding, specified in ITU-T G.998.2 recommendation [[G.998.2](#)], which defines a method for bonding (or aggregating) of multiple xDSL lines (or individual bearer channels in multiple xDSL lines) into a single bi-directional logical link carrying an Ethernet stream. This specification can be viewed as IEEE 802.3-2005 [[802.3](#)] Clause 61 Physical Medium Entity (PME) Aggregation, generalized to work over any xDSL technology. (2Base-TL and 10Pass-TS interfaces defined by IEEE use G.SHDSL and VDSL technology respectively).
- o The Multi-pair bonding using time-division inverse multiplexing (TDIM), specified in ITU-T G.998.3 recommendation [[G.998.3](#)], which defines a method for bonding (or aggregating) of multiple xDSL lines into a single bi-directional logical link carrying a mix of various traffic streams (e.g., Ethernet, ATM, TDM).

Architecturally all three bonding schemes define a new "bonded" Transport Protocol Specific - Transmission Convergence (TPS-TC) sub-layer, stacked above multiple ATM-TC, Ethernet/PTM-TC or STM-TC (clear channel) sub-layers for the ATM, Ethernet or TDIM bonding respectively. Each underlying TPS-TC sub-layer represents a protocol specific gamma-interface to an xDSL line or an individual bearer channel of an xDSL line. Bonding of multiple bearer channels in the same xDSL line is not allowed.

All schemes allow bonding of up to 32 individual line/channel sub-layers with variable rates, providing common functionality for the configuration, initialization, operation and monitoring of the bonded

link.

This document defines a MIB module common to all 3 schemes. Additional managed objects, specific to each bonding technology, are defined in GBOND-ATM-MIB [[I-D.ietf-adslmib-gbond-atm-mib](#)], GBOND-ETH-MIB [[I-D.ietf-adslmib-gbond-eth-mib](#)] and GBOND-TDIM-MIB [[I-D.ietf-adslmib-gbond-tdim-mib](#)] modules.

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This document specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

3. The DSL Forum Management Framework for xDSL Bonding

This document makes use of the DSL Forum technical report Management Framework for xDSL Bonding [[TR-159](#)], defining a management model and a hierarchy of management objects for the bonded xDSL interfaces.

4. Relationship to Other MIB modules

This section outlines the relationship of the MIB modules defined in this document with other MIB modules described in the relevant RFCs. Specifically, the following MIB modules are discussed: Interfaces Group MIB (IF-MIB), Inverse Stack Table MIB (IF-INVERTED-STACK-MIB), Interface Stack Capability MIB (IF-CAP-STACK-MIB), G.Bond scheme specific modules: G.Bond/ATM (GBOND-ATM-MIB), G.Bond/Ethernet (GBOND-ETH-MIB) and G.Bond/TDIM (GBOND-TDIM-MIB), and DSL specific MIB modules: ADSL (ADSL-LINE-EXT-MIB), ADSL2 (ADSL2-LINE-MIB), SHDSL (HDSL2-SHDSL-LINE-MIB), VDSL (VDSL-LINE-MIB) and VDSL2 (VDSL2-LINE-MIB).

4.1. Relationship to Interfaces Group MIB module

A bonded xDSL port is a stacked (a.k.a. aggregated or bonded) interface and as such is managed using generic interface management objects defined in the IF-MIB [[RFC2863](#)].

The stack management, i.e., actual connection of the sub-layers to the top layer interface, is done via the ifStackTable, as defined in the IF-MIB [[RFC2863](#)] and its inverse ifInvStackTable, as defined in the IF-INVERTED-STACK-MIB [[RFC2864](#)].

The ifCapStackTable and its inverse ifInvCapStackTable defined in the IF-CAP-STACK-MIB [[RFC5066](#)], extend the stack management with an ability to describe possible connections or cross-connect capability, when a flexible cross-connect matrix is present between the interface layers.

4.1.1. Layering Model


A G.Bond interface can aggregate up to 32 channel sub-layers, with each channel representing an xDSL line or an xDSL bearer channel. For the purpose of brevity we will refer to the bonded interface as Generic Bonded Sub-layer (GBS) and to the channel sub-layer as Bonding Channel Entity (BCE).

A generic G.Bond device can have a number of GBS ports, each connected to a particular upper layer (e.g., Media Access Control (MAC) interface for G.998.2 scheme), while simultaneously cross-connected to a number of underlying BCEs, with a single GBS per BCE relationship.

A GBS port is represented in the Interface table (ifTable) as a separate interface with an ifType of g9981, g9982 or g9983 for a particular bonding scheme.

Each BCE in the aggregated GBS port is represented in the ifTable as a separate interface with an ifType relevant to a particular xDSL technology, e.g., shdsl(169) or vdsl(97). The ifType values are defined in [[IANAifType-MIB](#)].

The following figure shows the layering diagram and corresponding use of ifTable for the bonded xDSL interfaces:



BCE - Bonding Channel Entity
 GBS - Generic Bonded Sub-layer
 PMD - Physical Medium Dependent
 TPS-TC - Transport Protocol Specific - Transmission Convergence
 PMS-TC - Physical Media Specific - Transmission Convergence

Figure 1: Use of ifTable for bonded xDSL interfaces

The ifStackTable is indexed by the ifIndex values of the aggregated G.Bond port (GBS) and the BCEs connected to it. ifStackTable allows a Network Management application to determine which BCEs are connected to a particular GBS and change connections (if supported by the application). The ifInvStackTable, being an inverted version of the ifStackTable, provides an efficient means for a Network Management application to read a subset of the ifStackTable and thereby determine which GBS runs on top of a particular BCE.

The ifCapStackTable defined in the IF-CAP-STACK-MIB module, specifies for each higher-layer interface (e.g., GBS port) a list of lower-layer interfaces (e.g., BCEs), which can possibly be cross-connected to that higher-layer interface, determined by the cross-connect capability of the device. This table, modeled after ifStackTable, is read only, reflecting current cross-connect capability of a stacked interface, which can be dynamic in some implementations (e.g., if xDSL lines are located on a pluggable module and the module is pulled out). Note that BCE availability per GBS, described by ifCapStackTable, can be constrained by other parameters, for example by aggregation capacity of a GBS or by the BCE in question being already connected to another GBS. So, in order to ensure that a particular BCE can be connected to the GBS, all respective parameters (e.g., ifCapStackTable, ifStackTable and gBondCapacity) SHALL be inspected.

The ifInvCapStackTable, also defined in the IF-CAP-STACK-MIB module,

describes which higher-layer interfaces (e.g., GBS ports) can possibly be connected to a particular lower-layer interface (e.g., BCE), providing inverted mapping of ifCapStackTable. While it contains no additional information beyond that already contained in the ifCapStackTable, the ifInvCapStackTable has the ifIndex values in its INDEX clause in the reverse order, i.e., the lower-layer interface first, and the higher-layer interface second, providing an efficient means for a Network Management application to read a subset of the ifCapStackTable and thereby determine which interfaces can be connected to run on top of a particular interface.

4.1.2. xDSL Bonding

The G.998.x Bonding allows a number of BCEs to be aggregated onto a single logical GBS port, by splitting the incoming traffic into multiple streams, transmitting each stream over a specific BCE and combining the streams at the remote GBS port, preserving the original traffic order.

Big Ethernet frames MAY be fragmented before the transmission and reassembled at the remote end to minimize transportation delay.

The Bonding is OPTIONAL, meaning that a device with a single BCE MAY perform fragmentation and re-assembly if this function is supported by the device. The agent is REQUIRED to report on the Bonding capability for all types of G.Bond ports (ATM, Ethernet and TDIM).

The GBOND-MIB module allows a Network Management application to query Bonding capability and enable/disable it if supported. Note that enabling Bonding effectively turns on fragmentation and re-assembly, even on a single-BCE port.

4.1.3. Discovery Operation

The G.Bond ports may optionally support discovery operation, whereby BCEs, during initialization, exchange information about their respective aggregation groups (GBS), via xDSL handshake protocol. This information can then be used to detect copper misconnections or for an automatic assignment of the local BCEs into aggregation groups instead of a fixed pre-configuration.

The MIB module defined in this document allow a Network Management application to control G.Bond Discovery mechanism and query its results. Note that the Discovery mechanism can work only if Bonding is supported and enabled.

Two tables are used by the G.Bond Discovery mechanism: ifStackTable and ifCapStackTable. The following pseudo-code gives an example of

the Discovery and automatic BCE assignment for a generic multi-GBS G.Bond device, located at Central Office (CO), using objects defined in this MIB module, IF-CAP-STACK-MIB and IF-MIB modules [Note that automatic BCE assignment is only shown here for the purposes of the example. Fixed BCE pre-assignment, manual assignment or auto-assignment using an alternative internal algorithm may be chosen by a particular implementation]:

```
// Go over all GBS ports in the CO device
FOREACH gbs[i] IN CO_device
{ // Perform discovery and auto-assignment on GBS ports
  // with room for more Channels
  IF ( gbs[i].NumBCEs < gbs[i].BondCapacity )
  { // Assign a unique 6-octets local discovery code to the GBS
    // e.g., MAC address
    dc = gbs[i].DiscoveryCode = MAC[i];
    // Go over all disconnected Channels, which can
    // potentially be connected to the GBS
    FOREACH bce[j] IN ifCapStackTable[gbs[i]] AND
      NOT IN ifStackTable[gbs[i]] // not connected
    { // Try to grab the remote RT_device, by writing the value
      // of the local 6 Byte discovery code to the remote
      // discovery code register (via handshake mechanism).
      // This operation is atomic Set-if-Clear action, i.e., it
      // would succeed only if the remote discovery register was
      // zero. Read the remote discovery code register via Get
      // operation to see if the RT_device, attached via the BCE
      // is indeed marked as being the CO_device peer.
      bce[j].RemoteDiscoveryCode = dc; // Set-if-Clear
      r = bce[j].RemoteDiscoveryCode; // Get
      IF ( r == dc AND gbs[i].NumBCEs < gbs[i].BondCapacity )
      { // Remote RT_device connected via BCE[j] is/was a peer
        // for GBS[i] and there room for another BCE in the
        // GBS[i] aggregation group (max. Bonding capacity is
        // not reached yet).
        // Connect this BCE to the GBS (via ifStackTable,
        // ifInvStackTable being inverse of ifStackTable is
        // updated automatically, i.e., gbs[i] is auto-added
        // to ifInvStackTable[bce[j]])
        ADD bce[j] TO ifStackTable[gbs[i]];
        gbs[i].NumBCEs = gbs[i].NumBCEs + 1;
        // Discover all other disconnected BCEs,
        // attached to the same RT_device and connect them to
        // the GBS provided there is enough room for more BCEs.
        FOREACH bce[k] IN ifCapStackTable[gbs[i]] and
          NOT IN ifStackTable[gbs[i]]
        { // Get Remote Discovery Code from the BCE to see if
          // it belongs to a connected RT_device "grabbed" by
```



```
        // the CO_device.
        r = bce[k].RemoteDiscoveryCode;
        IF ( r == dc AND gbs[i].NumBCEs < gbs[i].BondCapacity)
        { // Physically connect the BCE to the GBS
          // (gbs[i] is auto-added TO ifInvStackTable[bce[k]])
          ADD bce[k] TO ifStackTable[gbs[i]];
          gbs[i].NumBCEs = gbs[i].NumBCEs + 1;
        }
      }
    }
  }
  // At this point we have discovered all local BCEs which
  // are physically connected to the same remote RT_device
  // and connected them to GBS[i]. Go to the next GBS.
  BREAK;
}
}
```

An SNMP Agent for a G.Bond device builds ifCapStackTable and its inverse ifInvCapStackTable on device initialization, according to the cross-connect capabilities of the device.

Adding a BCE to the ifStackTable row for a specific GBS, involves actual connection of the BCE to the GBS.

Note that GBS port does not have to be operationally 'down' for the connection to succeed. In fact, a dynamic BCE addition (and removal) MAY be implemented with an available BCE being initialized first (by setting its ifAdminStatus to 'up') and then added to an operationally 'up' GBS port, by modifying a respective ifStackTable (and respective ifInvStackTable) entry.

It is RECOMMENDED that a removal of the last operationally 'up' BCE from an operationally 'up' GBS would be rejected by the implementation, as this action would completely drop the link.

In addition to the standard handshake-based discovery described above, [\[G.998.2\]](#) defines an optional frame-based discovery and pair management. These frame-based methods are discussed in [\[I-D.ietf-adslmib-gbond-eth-mib\]](#).

4.1.4. G.Bond ports initialization

G.Bond ports being built on top of xDSL technology, require a lengthy initialization or 'training' process, before any data can pass. During this initialization both ends of a link (peers) work cooperatively to achieve required data rate on a particular copper pair. Sometimes, when the copper line is too long or the noise on

the line is too high, that 'training' process may fail to achieve a specific target rate with required characteristics.

The ifAdminStatus object from the IF-MIB, controls the desired state of a GBS with all the BCEs connected to it or of an individual BCE port. Setting this object to 'up' instructs a particular GBS or a BCE to start initialization process, which may take tens of seconds for G.Bond ports. The ifOperStatus object shows the operational state of an interface (extended by ifMauMediaAvailable object from MAU-MIB [[RFC4836](#)] for GBS and *Status object from a relevant line MIB for BCE interfaces).

A disconnected BCE may be initialized by changing the ifAdminState from 'down' to 'up'. Changing the ifAdminState to 'up' on the GBS initializes all BCEs connected to that particular GBS. Note that in case of bonding some interfaces may fail to initialize while others succeed. The GBS is considered operationally 'up' if at least one bonded BCE is operationally 'up'. When all BCEs connected to the GBS are 'down' the GBS SHALL be considered operationally 'lowerLayerDown'. The GBS SHALL be considered operationally 'notPresent' if it is not connected to any BCE. The GBS/BCE interface SHALL remain operationally 'down' during initialization.

4.1.5. Usage of ifTable

Both BCE and GBS interfaces are managed using interface specific management objects defined in the GBOND-MIB module and generic interface objects from the ifTable of IF-MIB, with all management table entries referenced by the interface index ifIndex.

The following table summarizes G.Bond specific interpretations for some of the ifTable objects specified by the mandatory ifGeneralInformationGroup:

IF-MIB object	G.Bond interpretation
ifIndex	Interface index. Note that each BCE and each GBS in the G.Bond PHY MUST have a unique index, as there some GBS and BCE specific attributes accessible only on the GBS or BCE level.
ifType	g9981, g9982 or g9982 for the ATM, Ethernet or TDIM GBS respectively, shdsl(169) for G.SHDSL BCE, vdsl(97) for VDSL BCE, etc.

ifSpeed	Operating data rate for the BCE. For the GBS it	
	is the sum of the current operating data rates of	
	all BCEs in the aggregation group, without the	
	encapsulation overhead and G.Bond overhead, but	
	accounting for the Inter-Frame Gaps (IFG). When a	
	GBS or a BCE is operating in an assymetrical	
	fashion (upstream data rate differs from the	
	downstream one) the lowest of the values is	
	shown.	
ifAdminStatus	Setting this object to 'up' instructs a	
	particular GBS (with all BCEs connected to it) or	
	a BCE to start initialization process	
ifOperStatus	a relevant *Status object from a particular line	
	MIB supplements the 'down' value of ifOperStatus	
	for BCEs.	

Table 1: G.Bond interpretation of IF-MIB objects

4.2. Relationship to xDSL MIB modules

Each xDSL technology is described in a relevant xDSL line MIB module: e.g., HDSL2-SHDSL-LINE-MIB [[RFC4319](#)] for G.SHDSL, ADSL-LINE-EXT-MIB [[RFC3440](#)] for ADSL, ADSL2-LINE-MIB [[RFC4706](#)] for ADSL2, VDSL-LINE-MIB [[RFC3728](#)] for VDSL or VDSL2-LINE-MIB [[RFC5650](#)] for VDSL2.

These MIBs are used to manage individual xDSL lines/channels (BCEs).

5. MIB Structure

5.1. Overview

The main management objects defined in the GBOND-MIB module are split into 2 groups, structured as recommended by [RFC 4181](#) [[RFC4181](#)]:

- o gBondPort - containing objects for configuration, capabilities, status, historical performance monitoring and notifications, common to all G.Bond ports (GBS).
- o gBondBce - containing a single common object for configuration of the remote discovery code per BCE. Note that the rest of the objects for BCE configuration, capabilities, status and notifications, is located in relevant xDSL line MIB modules as well as in the bonding scheme specific MIB modules.

5.2. Performance Monitoring

The OPTIONAL performance monitoring counters, thresholds and history buckets (interval-counters) defined in [TR-159] are implemented using the textual conventions defined in the HC-PerfHist-TC-MIB [RFC3705]. The HC-PerfHist-TC-MIB defines 64-bit versions of the textual conventions found in PerfHist-TC-MIB [RFC3593].

The agent SHOULD align the beginning of each interval to a fifteen minute boundary of a wall clock. Likewise, the beginning of each one day intervals SHOULD be aligned with the start of a day.

Counters are not reset when a GBS is reinitialized, but rather only when the agent is reset or reinitialized (or under specific request outside the scope of this MIB module).

5.3. Mapping of DSL Forum TR-159 Managed Objects

This section contains the mapping between relevant managed objects (attributes) defined in [TR-159] and managed objects defined in this document and in associated MIB modules, i.e., the IF-MIB [RFC2863].

+-----+-----+	+-----+-----+	+-----+-----+
G.Bond Managed Object	Corresponding SNMP Object	
+-----+-----+	+-----+-----+	+-----+-----+
oBondingGroup - Basic Package		
(Mandatory)		
+-----+-----+	+-----+-----+	+-----+-----+
aGroupID	ifIndex (IF-MIB)	
+-----+-----+	+-----+-----+	+-----+-----+
aGroupBondSchemesSupported	gBondSchemesSupported	
+-----+-----+	+-----+-----+	+-----+-----+
aGroupPeerBondSchemesSupported	gBondPeerSchemesSupported	
+-----+-----+	+-----+-----+	+-----+-----+
aGroupAdminBondScheme	gBondAdminScheme	
+-----+-----+	+-----+-----+	+-----+-----+
aGroupPeerAdminBondScheme	gBondPeerAdminScheme	
+-----+-----+	+-----+-----+	+-----+-----+
aGroupOperBondScheme	gBondOperScheme	
+-----+-----+	+-----+-----+	+-----+-----+
aGroupPeerOperBondScheme	gBondPeerOperScheme	
+-----+-----+	+-----+-----+	+-----+-----+
aGroupEnd	gBondPortSide	
+-----+-----+	+-----+-----+	+-----+-----+
aGroupOperState	ifOperStatus (IF-MIB)	
+-----+-----+	+-----+-----+	+-----+-----+
aGroupAdminState	ifAdminStatus (IF-MIB)	
+-----+-----+	+-----+-----+	+-----+-----+

+-----+-----+		
aGroupStatus	gBondFltStatus	
+-----+-----+		
aGroupCapacity	gBondCapacity	
+-----+-----+		
aGroupPeerCapacity	gBondPeerCapacity	
+-----+-----+		
aGroupNumChannels	gBondNumBCEs	
+-----+-----+		
aGroupName	ifName (IF-MIB)	
+-----+-----+		
aGroupDiscoveryCode	gBondDiscoveryCode	
+-----+-----+		
aGroupUpRate	gBondUpDataRate	
+-----+-----+		
aGroupDownRate	gBondDnDataRate	
+-----+-----+		
aGroupTargetUpRate	gBondTargetUpDataRate	
+-----+-----+		
aGroupTargetDownRate	gBondTargetDnDataRate	
+-----+-----+		
aGroupThreshLowUpRate	gBondThreshLowUpRate	
+-----+-----+		
aGroupThreshLowDownRate	gBondThreshLowDnRate	
+-----+-----+		
aGroupLowRateCrossingEnable	gBondLowRateCrossingEnable	
+-----+-----+		
nGroupLowUpRateCrossing	gBondLowUpRateCrossing	
+-----+-----+		
nGroupLowDownRateCrossing	gBondLowDnRateCrossing	
+-----+-----+		
aGroupLinkUpDownEnable	_EdNote: Currently IF-MIB	
	doesn't provide a control for	
	the linkUp/linkDown	
	notifications. Can we define a	
	control in one MIB module while	
	the notifications are in	
	another?_	
+-----+-----+		
nGroupLinkUp	linkDown (IF-MIB)	
+-----+-----+		
nGroupLinkDown	linkUp (IF-MIB)	
+-----+-----+		
oBondingGroup - PM Package		
(Optional)		
+-----+-----+		
aGroupPerfES	gBondPerfES	
+-----+-----+		

+-----+-----+		
aGroupPerfSES	gBondPerfSES	
+-----+-----+		
aGroupPerfUAS	gBondPerfUAS	
+-----+-----+		
aGroupPerf15MinValidIntervals	gBondPerf15MinValidIntervals	
+-----+-----+		
aGroupPerf15MinInvalidIntervals	gBondPerf15MinInvalidIntervals	
+-----+-----+		
aGroupPerfCurr15MinTimeElapsed	gBondPerfCurr15MinTimeElapsed	
+-----+-----+		
aGroupPerfCurr15MinES	gBondPerfCurr15MinES	
+-----+-----+		
aGroupPerfCurr15MinSES	gBondPerfCurr15MinSES	
+-----+-----+		
aGroupPerfCurr15MinUAS	gBondPerfCurr15MinUAS	
+-----+-----+		
aGroupPerfTcaEnable	gBondPerfTcaEnable	
+-----+-----+		
aGroupPerfThreshold15MinES	gBondPerfThreshold15MinES	
+-----+-----+		
aGroupPerfThreshold15MinSES	gBondPerfThreshold15MinSES	
+-----+-----+		
aGroupPerfThreshold15MinUAS	gBondPerfThreshold15MinUAS	
+-----+-----+		
nGroupPerfTca15MinES	gBondPerfTca15MinESCrossing	
+-----+-----+		
nGroupPerfTca15MinSES	gBondPerfTca15MinSESCrossing	
+-----+-----+		
nGroupPerfTca15MinUAS	gBondPerfTca15MinUASCrossing	
+-----+-----+		
aGroupPerf1DayValidIntervals	gBondPerf1DayValidIntervals	
+-----+-----+		
aGroupPerf1DayInvalidIntervals	gBondPerf1DayInvalidIntervals	
+-----+-----+		
aGroupPerfCurr1DayTimeElapsed	gBondPerfCurr1DayTimeElapsed	
+-----+-----+		
aGroupPerfCurr1DayES	gBondPerf1DayIntervalES	
+-----+-----+		
aGroupPerfCurr1DaySES	gBondPerf1DayIntervalSES	
+-----+-----+		
aGroupPerfCurr1DayUAS	gBondPerf1DayIntervalUAS	
+-----+-----+		
aGroupPerfThreshold1DayES	gBondPerfThreshold1DayES	
+-----+-----+		
aGroupPerfThreshold1DaySES	gBondPerfThreshold1DaySES	
+-----+-----+		
aGroupPerfThreshold1DayUAS	gBondPerfThreshold1DayUAS	

nGroupPerfTca1DayES	gBondPerfTca1DayESCrossing	
+-----+	+-----+	+-----+
nGroupPerfTca1DaySES	gBondPerfTca1DaySESCrossing	
+-----+	+-----+	+-----+
nGroupPerfTca1DayUAS	gBondPerfTca1DayUASCrossing	
+-----+	+-----+	+-----+
aGroupPerf15MinIntervalNumber	gBondPerf15MinIntervalIndex	
+-----+	+-----+	+-----+
aGroupPerf15MinIntervalValid	gBondPerf15MinIntervalValid	
+-----+	+-----+	+-----+
aGroupPerf15MinIntervalES	gBondPerf15MinIntervalES	
+-----+	+-----+	+-----+
aGroupPerf15MinIntervalSES	gBondPerf15MinIntervalSES	
+-----+	+-----+	+-----+
aGroupPerf15MinIntervalUAS	gBondPerf15MinIntervalUAS	
+-----+	+-----+	+-----+
aGroupPerf1DayIntervalNumber	gBondPerf1DayIntervalIndex	
+-----+	+-----+	+-----+
aGroupPerf1DayIntervalValid	gBondPerf1DayIntervalValid	
+-----+	+-----+	+-----+
aGroupPerf1DayIntervalMoniSecs	gBondPerf1DayIntervalMoniTime	
+-----+	+-----+	+-----+
aGroupPerf1DayIntervalES	gBondPerf1DayIntervalES	
+-----+	+-----+	+-----+
aGroupPerf1DayIntervalSES	gBondPerf1DayIntervalSES	
+-----+	+-----+	+-----+
aGroupPerf1DayIntervalUAS	gBondPerf1DayIntervalUAS	
+-----+	+-----+	+-----+
oLine - Basic Package		
(Mandatory)		
+-----+	+-----+	+-----+
aLineID	ifIndex (IF-MIB)	
+-----+	+-----+	+-----+
aLineType	ifType (IF-MIB)	
+-----+	+-----+	+-----+
aLineOperState	ifOperStatus (IF-MIB)	
+-----+	+-----+	+-----+
aLineStatus	*dsl*CurrStatus (*DSL-LINE-MIB)	
+-----+	+-----+	+-----+
aLineEnd	*dsl*Side (*DSL-LINE-MIB)	
+-----+	+-----+	+-----+
aLineAdminState	ifAdminStatus (IF-MIB)	
+-----+	+-----+	+-----+
aLineRemoteDiscoveryCode	gBondBceRemoteDiscoveryCode	
+-----+	+-----+	+-----+

aLineUpDownEnable	_EdNote: Currently IF-MIB	
	doesn't provide a control for	
	the linkUp/linkDown	
	notifications. Can we define a	
	control in one MIB module while	
	the notifications are in	
	another?_	
nLineUp	linkUp (IF-MIB)	
nLineDown	linkDown (IF-MIB)	
oChannel - Basic Package		
(Mandatory)		
aChannelID	ifIndex (IF-MIB)	
aChannelGroupID		
aChannelType	ifType (IF-MIB)	
aChannelOperState	ifOperStatus (IF-MIB)	
aChannelStatus	*dsl*CurrStatus	
	(*DSL-LINE-MIB),	
	xdsl2ChStatus*Status	
	(VDSL2-LINE-MIB)	

Table 2: Mapping of TR-159 Managed Objects

6. xDSL Multi-pair Bonding MIB Definitions

GBOND-MIB DEFINITIONS ::= BEGIN

```

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    NOTIFICATION-TYPE,
    mib-2,
    Unsigned32,
    Gauge32
    FROM SNMPv2-SMI
    TEXTUAL-CONVENTION,
    TruthValue,
    RowStatus,
    PhysAddress
    -- [RFC2578]
```



```
FROM SNMPv2-TC -- [RFC2579]
MODULE-COMPLIANCE,
OBJECT-GROUP,
NOTIFICATION-GROUP
FROM SNMPv2-CONF -- [RFC2580]
SnmpAdminString
FROM SNMP-FRAMEWORK-MIB -- [RFC3411]
ifIndex
FROM IF-MIB -- [RFC2863]
HCPerfCurrentCount,
HCPerfIntervalCount,
HCPerfIntervalThreshold,
HCPerfValidIntervals,
HCPerfInvalidIntervals,
HCPerfTimeElapsed,
HCPerfTotalCount
FROM HC-PerfHist-TC-MIB -- [RFC3705]
;
```

gBondMIB MODULE-IDENTITY

LAST-UPDATED "201005280000Z" -- May 28, 2010

ORGANIZATION "IETF ADSL MIB Working Group"

CONTACT-INFO

"WG charter:

<http://www.ietf.org/html.charters/adslmib-charter.html>

Mailing Lists:

General Discussion: adslmib@ietf.org

To Subscribe: adslmib-request@ietf.org

In Body: subscribe your_email_address

Chair: Menachem Dodge

Postal: ECI Telecom, Ltd.

30 Hasivim St.,

Petach-Tikva 49517

Israel

Phone: +972-3-926-8421

E-Mail: menachem.dodge@ecitele.com

Editor: Edward Beili

Postal: Actelis Networks, Inc.

25 Bazel St., P.O.B. 10173

Petach-Tikva 10173

Israel

Phone: +972-3-924-3491

E-Mail: edward.beili@actelis.com

Editor: Moti Morgenstern

Postal: ECI Telecom
30 Hasivim St.
Petach-Tikva 49517
Israel
Phone: +972-3-926-6258
EMail: moti.morgenstern@ecitele.com"

DESCRIPTION

"The objects in this MIB module are used to manage the multi-pair bonded xDSL Interfaces, defined in ITU-T recommendations G.998.1, G.998.2 and G.998.3.

This MIB module MUST be used in conjunction with a bonding scheme specific MIB module, that is, GBOND-ATM-MIB, GBOND-ETH-MIB or GBOND-TDIM-MIB.

The following references are used throughout this MIB module:

[G.998.1] refers to:

ITU-T Recommendation G.998.1: 'ATM-based multi-pair bonding', January 2005.

[G.998.2] refers to:

ITU-T Recommendation G.998.2: 'Ethernet-based multi-pair bonding', January 2005.

[G.998.3] refers to:

ITU-T Recommendation G.998.3: 'Multi-pair bonding using time-division inverse multiplexing', January 2005.

[TR-159] refers to:

Broadband Forum Technical Report: 'Management Framework for xDSL Bonding', December 2008.

Naming Conventions:

BCE - Bonding Channel Entity
BTU - Bonding Transmission Unit
CO - Central Office
CPE - Customer Premises Equipment
GBS - Generic Bonding Sublayer
PM - Performance Monitoring
SNR - Signal to Noise Ratio
TCA - Threshold Crossing Alert

Copyright (C) The IETF Trust (2009).

This version of this MIB module is part of RFC XXXX;
see the RFC itself for full legal notices."


```
REVISION      "201005280000Z"  -- May 28, 2010
DESCRIPTION    "Initial version, published as RFC XXXX."
```

```
-- EdNote: Replace XXXX with the actual RFC number &
-- remove this note
```

```
::= { mib-2 ZZZ }
```

```
-- EdNote: Replace ZZZ with a real OID once it is
-- allocated & remove this note.
```

```
-- Sections of the module
-- Structured as recommended by \[RFC4181\], Appendix D
```

```
gBondObjects      OBJECT IDENTIFIER ::= { gBondMIB 1 }
```

```
gBondConformance OBJECT IDENTIFIER ::= { gBondMIB 2 }
```

```
-- Groups in the module
```

```
gBondPort          OBJECT IDENTIFIER ::= { gBondObjects 1 }
```

```
gBondBce           OBJECT IDENTIFIER ::= { gBondObjects 2 }
```

```
-- Textual Conventions
```

```
GBondSchemeList ::= TEXTUAL-CONVENTION
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "This textual convention defines a bitmap of possible ITU-T
        G.998 (G.Bond) bonding schemes. Currently there are 3 bonding
        schemes defined: G.998.1, G.998.2 and G.998.3, identified by
        bit values g9981(1), g9982(2) and g9983(3), respectively.
        An additional value of unknown(0), can be returned as a result
        of GET operation, when an value of the object cannot be
        determined, for example a peer GBS cannot be reached or it
        does not support any kind of bonding."
```

```
    SYNTAX      BITS {
```

```
        unknown(0),
        g9981(1),
        g9982(2),
        g9983(3)
```

```
    }
```

```
GBondScheme ::= TEXTUAL-CONVENTION
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "This textual convention defines ITU-T G.998 bonding scheme"
```


values. Possible values are:

unknown(0) - undefined or unknown
g9981(1) - G.998.1 (G.Bond/ATM)
g9982(2) - G.998.2 (G.Bond/Ethernt)
g9983(3) - G.998.3 (G.Bond/TDIM)."

```
SYNTAX      INTEGER {  
    unknown(0),  
    g9981(1),  
    g9982(2),  
    g9983(3)  
}
```

GBondPerf1DayIntervalThreshold ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

DESCRIPTION

"This textual convention defines a range of values that may be set in a fault threshold alarm control for a 1-day interval. As the number of seconds in a 1-day interval numbers at most 86400, objects of this type may have a range of 0...86400, where the value of 0 disables the alarm."

SYNTAX Unsigned32 (0..86400)

-- Port Notifications Group

gBondPortNotifications OBJECT IDENTIFIER ::= { gBondPort 0 }

gBondLowUpRateCrossing NOTIFICATION-TYPE

OBJECTS {

-- ifIndex is not needed here since we are under specific GBS
gBondUpDataRate,
gBondThreshLowUpRate

}

STATUS current

DESCRIPTION

"This notification indicates that the G.Bond port' upstream data rate has reached/dropped below or exceeded the low upstream rate threshold, specified by gBondThreshLowUpRate.

This notification MAY be sent for the -0 subtype ports while the port is up, on the crossing event in both directions: from normal (rate is above the threshold) to low (rate equals the threshold or below it) and from low to normal. This notification is not applicable to the -R subtypes.

It is RECOMMENDED that a small debouncing period of 2.5 sec,

between the detection of the condition and notification, is implemented to prevent simultaneous LinkUp/LinkDown and gBondLowUpRateCrossing notifications to be sent.

The adaptive nature of the G.Bond technology allows the port to adapt itself to the changes in the copper environment, e.g., an impulse noise, alien crosstalk, or a micro-interruption may temporarily drop one or more BCEs in the aggregation group, causing a rate degradation of the aggregated G.Bond link. The dropped BCEs would then try to re-initialize, possibly at a lower rate than before, adjusting the rate to provide required target SNR margin.

Generation of this notification is controlled by the gBondLowRateCrossingEnable object.

This object maps to the TR-159 notification nGroupLowUpRateCrossing."

REFERENCE

"[[TR-159](#)] 5.5.1.24"
::= { gBondPortNotifications 1 }

gBondLowDnRateCrossing NOTIFICATION-TYPE

OBJECTS {

-- ifIndex is not needed here since we are under specific GBS
gBondDnDataRate,
gBondThreshLowDnRate

}

STATUS current

DESCRIPTION

"This notification indicates that the G.Bond port' downstream data rate has reached/dropped below or exceeded the low downstream rate threshold, specified by gBondThreshLowDnRate.

This notification MAY be sent for the -0 subtype ports while the port is up, on the crossing event in both directions: from normal (rate is above the threshold) to low (rate equals the threshold or below it) and from low to normal. This notification is not applicable to the -R subtypes.

It is RECOMMENDED that a small debouncing period of 2.5 sec, between the detection of the condition and notification, is implemented to prevent simultaneous LinkUp/LinkDown and gBondLowDnRateCrossing notifications to be sent.

The adaptive nature of the G.Bond technology allows the port

to adapt itself to the changes in the copper environment, e.g., an impulse noise, alien crosstalk, or a micro-interruption may temporarily drop one or more BCEs in the aggregation group, causing a rate degradation of the aggregated G.Bond link. The dropped BCEs would then try to re-initialize, possibly at a lower rate than before, adjusting the rate to provide required target SNR margin.

Generation of this notification is controlled by the gBondLowRateCrossingEnable object.

This object maps to the TR-159 notification nGroupLowDownRateCrossing."

REFERENCE

"[[TR-159](#)] 5.5.1.25"
::= { gBondPortNotifications 2}

gBondPerfTca15MinESCrossing NOTIFICATION-TYPE

OBJECTS {

-- ifIndex is not needed here since we are under specific GBS
gBondPerfCurr15MinES,
gBondPerfThreshold15MinES

}

STATUS current

DESCRIPTION

"This notification indicates that the Errored Seconds threshold, specified by gBondPerfThreshold15MinES, has been reached or exceeded for the GPS port.

Generation of this notification is controlled by gBondPerfTcaEnable and gBondPerfThreshold15MinES objects.

This object maps to the TR-159 notification nGroupPerfTca15MinES."

REFERENCE

"[[TR-159](#)] 5.5.1.42"
::= { gBondPortNotifications 3}

gBondPerfTca15MinSESCrossing NOTIFICATION-TYPE

OBJECTS {

-- ifIndex is not needed here since we are under specific GBS
gBondPerfCurr15MinSES,
gBondPerfThreshold15MinSES

}

STATUS current

DESCRIPTION

"This notification indicates that the Severely Errored Seconds threshold, specified by gBondPerfThreshold15MinSES, has been

reached or exceeded for the GPS port.

Generation of this notification is controlled by
gBondPerfTcaEnable and gBondPerfThreshold15MinSES objects.

This object maps to the TR-159 notification
nGroupPerfTca15MinSES."

REFERENCE

"[[TR-159](#)] 5.5.1.43"

::= { gBondPortNotifications 4}

gBondPerfTca15MinUASCrossing NOTIFICATION-TYPE

OBJECTS {

-- ifIndex is not needed here since we are under specific GBS
gBondPerfCurr15MinUAS,
gBondPerfThreshold15MinUAS

}

STATUS current

DESCRIPTION

"This notification indicates that the Unavailable Seconds
threshold, specified by gBondPerfThreshold15MinES, has been
reached or exceeded for the GPS port.

Generation of this notification is controlled by
gBondPerfTcaEnable and gBondPerfThreshold15MinUAS objects.

This object maps to the TR-159 notification
nGroupPerfTca15MinUAS."

REFERENCE

"[[TR-159](#)] 5.5.1.44"

::= { gBondPortNotifications 5}

gBondPerfTca1DayESCrossing NOTIFICATION-TYPE

OBJECTS {

-- ifIndex is not needed here since we are under specific GBS
gBondPerfCurr1DayES,
gBondPerfThreshold1DayES

}

STATUS current

DESCRIPTION

"This notification indicates that the Errored Seconds threshold,
specified by gBondPerfThreshold1DayES, has been reached or
exceeded for the GPS port.

Generation of this notification is controlled by
gBondPerfTcaEnable and gBondPerfThreshold1DayES objects.

This object maps to the TR-159 notification


```
    nGroupPerfTca1DayES."
REFERENCE
    "[TR-159] 5.5.1.54"
::= { gBondPortNotifications 6}

gBondPerfTca1DaySESCrossing NOTIFICATION-TYPE
OBJECTS {
    -- ifIndex is not needed here since we are under specific GBS
    gBondPerfCurr1DaySES,
    gBondPerfThreshold1DaySES
}
STATUS      current
DESCRIPTION
    "This notification indicates that the Severely Errored Seconds
    threshold, specified by gBondPerfThreshold1DaySES, has been
    reached or exceeded for the GPS port.

    Generation of this notification is controlled by
    gBondPerfTcaEnable and gBondPerfThreshold1DaySES objects.

    This object maps to the TR-159 notification
    nGroupPerfTca1DaySES."
REFERENCE
    "[TR-159] 5.5.1.55"
::= { gBondPortNotifications 7}

gBondPerfTca1DayUASCrossing NOTIFICATION-TYPE
OBJECTS {
    -- ifIndex is not needed here since we are under specific GBS
    gBondPerfCurr1DayUAS,
    gBondPerfThreshold1DayUAS
}
STATUS      current
DESCRIPTION
    "This notification indicates that the Unavailable Seconds
    threshold, specified by gBondPerfThreshold1DayUAS, has been
    reached or exceeded for the GPS port.

    Generation of this notification is controlled by
    gBondPerfTcaEnable and gBondPerfThreshold1DayUAS objects.

    This object maps to the TR-159 notification
    nGroupPerfTca1DayUAS."
REFERENCE
    "[TR-159] 5.5.1.56"
::= { gBondPortNotifications 8}

-- G.Bond Port (GBS) group
```


gBondPortConfTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondPortConfEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Table for Configuration of G.Bond GBS ports. Entries in this table MUST be maintained in a persistent manner"

::= { gBondPort 1 }

gBondPortConfEntry OBJECT-TYPE

SYNTAX GBondPortConfEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond Port Configuration table.

Each entry represents an G.Bond port indexed by the ifIndex.

Note that an G.Bond GBS port runs on top of a single

or multiple BCE port(s), which are also indexed by ifIndex."

INDEX { ifIndex }

::= { gBondPortConfTable 1 }

GBondPortConfEntry ::=

SEQUENCE {

gBondAdminScheme GBondScheme,

gBondPeerAdminScheme GBondScheme,

gBondDiscoveryCode PhysAddress,

gBondTargetUpDataRate Unsigned32,

gBondTargetDnDataRate Unsigned32,

gBondThreshLowUpRate Unsigned32,

gBondThreshLowDnRate Unsigned32,

gBondLowRateCrossingEnable TruthValue,

gBondPerfTcaConfProfile SnmpAdminString,

gBondPerfTcaEnable TruthValue

}

gBondAdminScheme OBJECT-TYPE

SYNTAX GBondScheme

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"A desired bonding scheme for a G.Bond GBS port.

The following values instruct the port to use corresponding bonding scheme if supported:

g9981(1) - instructs the port to use G.998.1 bonding

g9982(2) - instructs the port to use G.998.2 bonding

g9983(3) - instructs the port to use G.998.3 bonding

Changing of the gBondAdminScheme MUST be performed when the

link is Down. Attempts to change this object MUST be rejected (in case of SNMP with the error inconsistentValue), if the link is Up or Initializing. Attempts to change this object to an unsupported bonding scheme (see gBondSchemesSupported) SHALL be rejected (in case of SNMP with the error wrongValue).

This object MUST be maintained in a persistent manner.

This object maps to the TR-159 attribute
aGroupAdminBondScheme."

REFERENCE

"[[TR-159](#)] 5.5.1.6"
::= { gBondPortConfEntry 1 }

gBondPeerAdminScheme OBJECT-TYPE

SYNTAX GBondScheme

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"A desired bonding scheme for a peer (link partner) G.Bond port (GBS).

The following values instruct the peer port to use corresponding bonding scheme if supported:

- g9981(1) - instructs the port to use G.998.1 bonding
- g9982(2) - instructs the port to use G.998.2 bonding
- g9983(3) - instructs the port to use G.998.3 bonding

Changing of the gBondAdminScheme MUST be performed when the link is Down. Attempts to change this object MUST be rejected (in case of SNMP with the error inconsistentValue), if the link is Up or Initializing. Attempts to change this object to an unsupported bonding scheme (see gBondPeerSchemesSupported) SHALL be rejected (in case of SNMP with the error wrongValue).

This object MUST be maintained in a persistent manner.

This object maps to the TR-159 attribute
aGroupPeerAdminBondScheme."

REFERENCE

"[[TR-159](#)] 5.5.1.7"
::= { gBondPortConfEntry 2 }

gBondDiscoveryCode OBJECT-TYPE

SYNTAX PhysAddress (SIZE(6))

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"A Discovery Code of the G.Bond port (GBS).

A unique 6 octet long code used by the Discovery function. This object MUST be instantiated for the -0 subtype GBS before writing operations on the gBondBceRemoteDiscoveryCode (Set_if_Clear and Clear_if_Same) are performed by BCEs associated with the GBS.

The initial value of this object for -R subtype ports after reset is all zeroes. For -R subtype ports, the value of this object cannot be changed directly. This value may be changed as a result of writing operation on the gBondBceRemoteDiscoveryCode object of remote BCE of -0 subtype, connected to one of the local BCEs associated with the GBS.

Discovery MUST be performed when the link is Down. Attempts to change this object MUST be rejected (in case of SNMP with the error inconsistentValue), if the link is Up or Initializing.

This object maps to the TR-159 attribute aGroupDiscoveryCode."

REFERENCE

"[[TR-159](#)] 5.5.1.20; [[802.3](#)] 61.2.2.8.3, 61.2.2.8.4, 45.2.6.6.1, 45.2.6.8, 61A.2"
::= { gBondPortConfEntry 3 }

gBondTargetUpDataRate OBJECT-TYPE

SYNTAX Unsigned32(0|1..10000000)

UNITS "Kbps"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"A desired G.Bond port Data Rate in the upstream direction, in Kbps, to be achieved during initialization, under restrictions placed upon the member BCEs by their respective configuration settings.

This object represents a sum of individual BCE upstream data rates, modified to compensate for fragmentation and encapsulation overhead (e.g., for an Ethernet service, the target data rate of 10Mbps SHALL allow lossless transmission of full-duplex 10Mbps Ethernet frame stream with minimal inter-frame gap).

Note that the target upstream data rate may not be achieved during initialization (e.g., due to unavailability of required BCEs) or the initial bandwidth could deteriorate, so that the actual upstream data rate (gBondUpDataRate) could be less than gBondTargetUpDataRate.

The value is limited above by 10 Gbps, to accomodate very

high speed bonded xDSL interfaces (e.g. 32 x 100Mbps).

The value between 1 and 100000000 indicates that the total upstream data rate of the G.Bond port after initialization SHALL be equal to the target data rate or less, if the target upstream data rate cannot be achieved under the restrictions configured for BCEs. In case the copper environment allows to achieve higher upstream data rate than that specified by this object, the excess capability SHALL be either converted to additional SNR margin or reclaimed by minimizing transmit power.

The value of 0 means that the target data rate is not fixed and SHALL be set to the maximum attainable rate during initialization (Best Effort), under specified spectral restrictions and with desired SNR Margin per BCE.

This object is read-write for the -O subtype G.Bond ports and irrelevant for the -R subtypes.

Changing of the Target Upstream Data Rate MUST be performed when the link is Down. Attempts to change this object MUST be rejected (In case of SNMP with the error inconsistentValue), if the link is Up or Initializing.

This object MUST be maintained in a persistent manner.

This object maps to the TR-159 attribute
aGroupTargetUpRate."

REFERENCE

"[[TR-159](#)] 5.5.1.17"
::= { gBondPortConfEntry 4 }

gBondTargetDnDataRate OBJECT-TYPE

SYNTAX Unsigned32(0|1..100000000)

UNITS "Kbps"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"A desired G.Bond port Data Rate in the downstream direction, in Kbps, to be achieved during initialization, under restrictions placed upon the member BCEs by their respective configuration settings.

This object represents a sum of individual BCE downstream data rates, modified to compensate for fragmentation and encapsulation overhead (e.g., for an Ethernet service, the target data rate of 10Mbps SHALL allow lossless transmission of full-duplex 10Mbps Ethernet frame stream with minimal

inter-frame gap).

Note that the target downstream data rate may not be achieved during initialization (e.g., due to unavailability of required BCEs) or the initial bandwidth could deteriorate, so that the actual downstream data rate (gBondDnDataRate) could be less than gBondTargetDnDataRate.

The value is limited above by 10 Gbps, to accomodate very high speed bonded xDSL interfaces (e.g. 32 x 100Mbps).

The value between 1 and 100000000 indicates that the total downstream data rate of the G.Bond port after initialization SHALL be equal to the target data rate or less, if the target downstream data rate cannot be achieved under the restrictions configured for BCEs. In case the copper environment allows to achieve higher downstream data rate than that specified by this object, the excess capability SHALL be either converted to additional SNR margin or reclaimed by minimizing transmit power.

The value of 0 means that the target data rate is not fixed and SHALL be set to the maximum attainable rate during initialization (Best Effort), under specified spectral restrictions and with desired SNR Margin per BCE.

This object is read-write for the -O subtype G.Bond ports and irrelevant for the -R subtypes.

Changing of the Target Downstream Data Rate MUST be performed when the link is Down. Attempts to change this object MUST be rejected (In case of SNMP with the error inconsistentValue), if the link is Up or Initializing.

This object MUST be maintained in a persistent manner.

This object maps to the TR-159 attribute
aGroupTargetDownRate."

REFERENCE

"[[TR-159](#)] 5.5.1.18"

::= { gBondPortConfEntry 5 }

gBondThreshLowUpRate OBJECT-TYPE

SYNTAX Unsigned32(1..100000000)

UNITS "Kbps"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"This object configures the G.Bond port low upstream rate

crossing alarm threshold. When the current value of gBondUpDataRate for this port reaches/drops below or exceeds this threshold, an gBondLowUpRateCrossing notification MAY be generated if enabled by gBondLowRateCrossingEnable.

This object is read-write for the -O subtype G.Bond ports and irrelevant for the -R subtypes.

This object MUST be maintained in a persistent manner.

This object maps to the TR-159 attribute
aGroupthreshLowUpRate."

REFERENCE

"[[TR-159](#)] 5.5.1.21"
::= { gBondPortConfEntry 6 }

gBondThreshLowDnRate OBJECT-TYPE

SYNTAX Unsigned32(1..10000000)

UNITS "Kbps"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"This object configures the G.Bond port low downstream rate crossing alarm threshold. When the current value of gBondDnDataRate for this port reaches/drops below or exceeds this threshold, an gBondLowDnRateCrossing notification MAY be generated if enabled by gBondLowRateCrossingEnable.

This object is read-write for the -O subtype G.Bond ports and irrelevant for the -R subtypes.

This object MUST be maintained in a persistent manner.

This object maps to the TR-159 attribute
aGroupThreshDownUpRate."

REFERENCE

"[[TR-159](#)] 5.5.1.22"
::= { gBondPortConfEntry 7 }

gBondLowRateCrossingEnable OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Indicates whether gBondLowUpRateCrossing and gBondLowDnRateCrossing notifications should be generated for this interface.

Value of true(1) indicates that the notifications are enabled.
Value of false(2) indicates that the notifications are disabled.

This object is read-write for the -O subtype G.Bond ports and irrelevant for the -R subtypes.

This object MUST be maintained in a persistent manner.

This object maps to the TR-159 attribute
aGroupLowRateCrossingEnable."

REFERENCE

"[[TR-159](#)] 5.5.1.23"
::= { gBondPortConfEntry 8 }

gBondPerfTcaConfProfile OBJECT-TYPE

SYNTAX SnmpAdminString (SIZE(1..32))

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The value of this object is the index of the row in the GBS port Alarm Configuration Profile Table for Performance Monitoring Threshold Crossing Alerts - gBondPortAlarmConfProfileTable, which applies to this GBS port.

This object MUST be maintained in a persistent manner."

DEFVAL { "DEFVAL" }

::= { gBondPortConfEntry 9 }

gBondPerfTcaEnable OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Indicates whether gBondPerfTca*Crossing set of notifications should be generated for this interface.

Value of true(1) indicates that the notifications are enabled.
Value of false(2) indicates that the notifications are disabled.

This object MUST be maintained in a persistent manner.

This object maps to the TR-159 attribute aGroupPerfTcaEnable."

REFERENCE

"[[TR-159](#)] 5.5.1.38"
::= { gBondPortConfEntry 10 }

gBondPortCapabilityTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondPortCapabilityEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Table for Capabilities of G.Bond Ports. Entries in this table MUST be maintained in a persistent manner"

::= { gBondPort 2 }

gBondPortCapabilityEntry OBJECT-TYPE

SYNTAX GBondPortCapabilityEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond Port Capability table.
Each entry represents an G.Bond port indexed by the ifIndex.
Note that a G.Bond GBS port runs on top of a single
or multiple BCE port(s), which are also indexed by ifIndex."

INDEX { ifIndex }

::= { gBondPortCapabilityTable 1 }

GBondPortCapabilityEntry ::=

SEQUENCE {

gBondSchemesSupported GBondSchemeList,

gBondPeerSchemesSupported GBondSchemeList,

gBondCapacity Unsigned32,

gBondPeerCapacity Unsigned32

}

gBondSchemesSupported OBJECT-TYPE

SYNTAX GBondSchemeList

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Bonding Capability of the G.Bond port (GBS). This is a read-only bitmap of the possible bonding schemes supported by the GBS. The various bit-positions are:

g9981(1) - GBS is capable of G.998.1 bonding

g9982(2) - GBS is capable of G.998.2 bonding

g9983(3) - GBS is capable of G.998.3 bonding

Note that for ports supporting multiple bonding schemes the actual administrative scheme is set via gBondAdminScheme object. The current operating bonding scheme is reflected in the gBondOperScheme.

This object maps to the TR-159 attribute
aGroupBondSchemesSupported."

REFERENCE

"[[TR-159](#)] 5.5.1.2"
::= { gBondPortCapabilityEntry 1 }

gBondPeerSchemesSupported OBJECT-TYPE

SYNTAX GBondSchemeList

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Bonding Capability of the peer G.Bond port (GBS). This is a read-only bitmap of the possible bonding schemes supported by the link partner GBS. The various bit-positions are:

- unknown(0) - GBS does not support bonding or
the peer unit could not be reached.
- g9981(1) - GBS is capable of G.998.1 bonding
- g9982(2) - GBS is capable of G.998.2 bonding
- g9983(3) - GBS is capable of G.998.3 bonding

Note that for ports supporting multiple bonding schemes the actual administrative scheme is set via gBondPeerAdminScheme object. The current operating bonding scheme is reflected in the gBondPeerOperScheme.

This object maps to the TR-159 attribute
aGroupBondPeerSchemesSupported."

REFERENCE

"[[TR-159](#)] 5.5.1.3"
::= { gBondPortCapabilityEntry 2 }

gBondCapacity OBJECT-TYPE

SYNTAX Unsigned32 (1..32)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Number of BCEs that can be aggregated by the local GBS.
The number of BCEs currently assigned to a particular G.Bond port (gBondNumBCEs) is never greater than gBondCapacity.

This object maps to the TR-159 attribute aGroupCapacity."

REFERENCE

"[[TR-159](#)] 5.5.1.12"
::= { gBondPortCapabilityEntry 3 }

gBondPeerCapacity OBJECT-TYPE

SYNTAX Unsigned32 (0|1..32)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Number of BCEs that can be aggregated by the peer GBS port. Value of 0 is returned when peer Bonding Capacity is unknown (peer cannot be reached).

This object maps to the TR-159 attribute aGroupPeerCapacity."

REFERENCE

"[[TR-159](#)] 5.5.1.13"

::= { gBondPortCapabilityEntry 4 }

gBondPortStatusTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondPortStatusEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table provides overall status information of G.Bond ports, complementing the generic status information from the ifTable of IF-MIB. Additional status information about connected BCEs is available from the relevant line MIBs

This table contains live data from the equipment. As such, it is NOT persistent."

::= { gBondPort 3 }

gBondPortStatusEntry OBJECT-TYPE

SYNTAX GBondPortStatusEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond Port Status table. Each entry represents an G.Bond port indexed by the ifIndex. Note that an G.Bond GBS port runs on top of a single or multiple BCE port(s), which are also indexed by ifIndex."

INDEX { ifIndex }

::= { gBondPortStatusTable 1 }

GBondPortStatusEntry ::=

SEQUENCE {

gBondOperScheme GBondScheme,

gBondPeerOperScheme GBondScheme,

gBondUpDataRate Gauge32,

gBondDnDataRate Gauge32,

gBondFltStatus BITS,

gBondPortSide INTEGER,

gBondNumBCEs Unsigned32

}

gBondOperScheme OBJECT-TYPE

SYNTAX GBondScheme

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Current operating bonding scheme of a G.Bond port.

The possible values are:

g9981(1) - G.998.1 bonding

g9982(2) - G.998.2 bonding

g9983(3) - G.998.3 bonding

This object maps to the TR-159 attribute
aGroupOperBondScheme."

REFERENCE

"[[TR-159](#)] 5.5.1.4"

::= { gBondPortStatusEntry 1 }

gBondPeerOperScheme OBJECT-TYPE

SYNTAX GBondScheme

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Current operating bonding scheme of a G.Bond port link
partner.

The possible values are:

unknown(0) - peer cannot be reached due to the link
 state

g9981(1) - G.998.1 bonding

g9982(2) - G.998.2 bonding

g9983(3) - G.998.3 bonding

This object maps to the TR-159 attribute
aGroupPeerOperBondScheme."

REFERENCE

"[[TR-159](#)] 5.5.1.5"

::= { gBondPortStatusEntry 2 }

gBondUpDataRate OBJECT-TYPE

SYNTAX Gauge32

UNITS "bps"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A current G.Bond port operational Data Rate in the upstream
direction, in bps.

This object represents an estimation of the sum of individual
BCE upstream data rates, modified to compensate for
fragmentation and encapsulation overhead (e.g., for an
Ethernet service, the target data rate of 10Mbps SHALL allow

lossless transmission of full-duplex 10Mbps Ethernet frame stream with minimal inter-frame gap).

Note that for symmetrical interfaces `gBondUpDataRate == gBondDnDataRate == ifSpeed`.

This object maps to the TR-159 attribute `aGroupUpRate`."

REFERENCE

"[[TR-159](#)] 5.5.1.15"

::= { gBondPortStatusEntry 3 }

gBondDnDataRate OBJECT-TYPE

SYNTAX Gauge32

UNITS "bps"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A current G.Bond port operational Data Rate in the downstream direction, in bps.

This object represents an estimation of the sum of individual BCE downstream data rates, modified to compensate for fragmentation and encapsulation overhead (e.g., for an Ethernet service, the target data rate of 10Mbps SHALL allow lossless transmission of full-duplex 10Mbps Ethernet frame stream with minimal inter-frame gap).

Note that for symmetrical interfaces `gBondUpDataRate == gBondDnDataRate == ifSpeed`.

This object maps to the TR-159 attribute `aGroupDownRate`."

REFERENCE

"[[TR-159](#)] 5.5.1.16"

::= { gBondPortStatusEntry 4 }

gBondFltStatus OBJECT-TYPE

SYNTAX BITS {
noPeer(0),
peerPowerLoss(1),
peerBondSchemeMismatch(2),
bceSubTypeMismatch(3),
lowRate(4)
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"G.Bond (GBS) port Fault Status. This is a bitmap of possible conditions. The various bit positions are:

noPeer	- peer GBS cannot be reached (e.g., no BCEs attached, all BCEs are Down etc.).
peerPowerLoss	- peer GBS has indicated impending unit failure due to loss of local power ('Dying Gasp').
peerBondSchemeMismatch	- operating bonding scheme of a peer GBS is different from the local one.
bceSubTypeMismatch	- local BCEs in the aggregation group are not of the same sub-type, e.g., some BCEs in the local device are -0 while others are -R subtype.
lowRate	- gBondUpRate/gBondDnRate of the port has reached or dropped below gBondThreshLowUpRate/gBondThreshLowUpRate.

This object is intended to supplement ifOperStatus object in IF-MIB and ifMauMediaAvailable in MAU-MIB.

This object maps to the TR-159 attribute aGroupStatus."

REFERENCE

"[[TR-159](#)] 5.5.1.9; IF-MIB, ifOperStatus; MAU-MIB, ifMauMediaAvailable"
 ::= { gBondPortStatusEntry 5 }

gBondPortSide OBJECT-TYPE

```
SYNTAX      INTEGER {
    subscriber(1),
    office(2),
    unknown(3)
}
```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"G.Bond port mode of operation (subtype).

The value of 'subscriber' indicates the port is designated as '-R' subtype (all BCEs assigned to this port are of subtype '-R').

The value of the 'office' indicates that the port is designated as '-0' subtype (all BCEs assigned to this port are of subtype '-0').

The value of 'unknown' indicates that the port has no assigned BCEs yet or that the assigned BCEs are not of the same side (subTypeBCEMismatch).

This object maps to the TR-159 attribute aGroupEnd."

REFERENCE


```
"[TR-159] 5.5.1.11"
 ::= { gBondPortStatusEntry 6 }

gBondNumBCEs OBJECT-TYPE
    SYNTAX      Unsigned32 (0..32)
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "Number of BCEs that is currently aggregated by the local GBS
        (assigned to the G.Bond port using ifStackTable).
        This number is never greater than gBondCapacity.

        This object SHALL be automatically incremented or decremented
        when a BCE is added or deleted to/from the G.Bond port using
        ifStackTable.

        This object maps to the TR-159 attribute aGroupNumChannels"
    REFERENCE
        "[TR-159] 5.5.1.14"
 ::= { gBondPortStatusEntry 7 }

-- Performance Monitoring group

gBondPortPM OBJECT IDENTIFIER ::= { gBondPort 4 }

gBondPortPerfCurrTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF GBondPortPerfCurrEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "This table contains current Performance Monitoring (PM)
        information for a GBS port. This table contains live data from
        the equipment and as such is NOT persistent."
 ::= { gBondPortPM 1 }

gBondPortPerfCurrEntry OBJECT-TYPE
    SYNTAX      GBondPortPerfCurrEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "An entry in the G.Bond Port PM table.
        Each entry represents an G.Bond port indexed by the ifIndex.
        Note that a G.Bond GBS port runs on top of a single
        or multiple BCE port(s), which are also indexed by ifIndex."
    INDEX { ifIndex }
 ::= { gBondPortPerfCurrTable 1 }
```


GBondPortPerfCurrEntry ::=

```

SEQUENCE {
    gBondPerfES                HCPperfTotalCount,
    gBondPerfSES                HCPperfTotalCount,
    gBondPerfUAS                HCPperfTotalCount,
    gBondPerf15MinValidIntervals HCPperfValidIntervals,
    gBondPerf15MinInvalidIntervals HCPperfInvalidIntervals,
    gBondPerfCurr15MinTimeElapsed HCPperfTimeElapsed,
    gBondPerfCurr15MinES         HCPperfCurrentCount,
    gBondPerfCurr15MinSES        HCPperfCurrentCount,
    gBondPerfCurr15MinUAS        HCPperfCurrentCount,
    gBondPerf1DayValidIntervals  Unsigned32,
    gBondPerf1DayInvalidIntervals Unsigned32,
    gBondPerfCurr1DayTimeElapsed HCPperfTimeElapsed,
    gBondPerfCurr1DayES         HCPperfCurrentCount,
    gBondPerfCurr1DaySES        HCPperfCurrentCount,
    gBondPerfCurr1DayUAS        HCPperfCurrentCount
}

```

gBondPerfES OBJECT-TYPE

SYNTAX HCPperfTotalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Errored Seconds (ES) on the GBS since the BTU was last restarted.

An Errored Second for a G.998.x interface is defined as a count of 1-second intervals during which one or more GBS errors are declared. The errors are specific for each bonding scheme, e.g.

- lost cells for the ATM bonding;
- lost or discarded (due to an error or a buffer overflow) fragments for the Ethernet bonding;
- CRC4, CRC6 or CRC8 errors for the TDIM bonding

This object is inhibited during Unavailable Seconds (UAS).

This object maps to the TR-159 attribute aGroupPerfES."

REFERENCE

"[[TR-159](#)] 5.5.1.29"

::= { gBondPortPerfCurrEntry 1 }

gBondPerfSES OBJECT-TYPE

SYNTAX HCPperfTotalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Severely Errored Seconds (SES) on the GBS since the BTU was last restarted.

A Severely Errored Second for a G.998.x interface is defined as a count of 1-second intervals during which GBS errors cause at least 1% traffic loss of the nominal bonded link rate or at least 12ms for the TDM traffic. The exact definition is specific for each bonding scheme, e.g.

- 234 lost cells for the ATM bonding with 10Mbps nominal link rate
- 60 lost/discarded fragments for the Ethernet bonding with 10Mbps nominal link rate and fixed 192 Byte-long fragment size.
- 6 or more CRC4, one or more CRC6 or one or more CRC8 errors for the TDM bonding

This object is inhibited during Unavailable Seconds (UAS).

This object maps to the TR-159 attribute aGroupPerfSES."

REFERENCE

"[[TR-159](#)] 5.5.1.30"
::= { gBondPortPerfCurrEntry 2 }

gBondPerfUAS OBJECT-TYPE

SYNTAX HCPerfTotalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Unavailable Seconds (UAS) on the GBS since the BTU was last restarted.

An Unavailable Second for a G.998.x interface is defined as a count of 1-second intervals during which the bonded link is unavailable. The G.998.x link becomes unavailable at the onset of 10 contiguous SESSs. The 10 SESSs are included in the unavailable time. Once unavailable, the G.998.x line becomes available at the onset of 10 contiguous seconds with no SESSs. The 10 seconds with no SESSs are excluded from unavailable time.

This object maps to the TR-159 attribute aGroupPerfUAS."

REFERENCE

"[[TR-159](#)] 5.5.1.31"
::= { gBondPortPerfCurrEntry 3 }

gBondPerf15MinValidIntervals OBJECT-TYPE

SYNTAX HCPerfValidIntervals

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 15-minute intervals for which data was collected. The value of this object will be 96 or the maximum number of 15-minute history intervals collected by the

implementation unless the measurement was (re-)started recently, in which case the value will be the number of complete 15 minutes intervals for which there are at least some data. In certain cases it is possible that some intervals are unavailable. In this case, this object reports the maximum interval number for which data is available.

This object maps to the TR-159 attribute
aGroupPerf15MinInvalidIntervals."

REFERENCE

"[[TR-159](#)] 5.5.1.32"
::= { gBondPortPerfCurrEntry 4 }

gBondPerf15MinInvalidIntervals OBJECT-TYPE

SYNTAX HCPerfInvalidIntervals

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 15-minute intervals for which data was not always available. The value will typically be zero except in cases where the data for some intervals are not available.

This object maps to the TR-159 attribute
aGroupPerf15MinInvalidIntervals."

REFERENCE

"[[TR-159](#)] 5.5.1.33"
::= { gBondPortPerfCurrEntry 5 }

gBondPerfCurr15MinTimeElapsed OBJECT-TYPE

SYNTAX HCPerfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds that have elapsed since the beginning of the current 15-minute performance history interval.

This object maps to the TR-159 attribute
aGroupPerfCurr15MinTimeElapsed."

REFERENCE

"[[TR-159](#)] 5.5.1.34"
::= { gBondPortPerfCurrEntry 6 }

gBondPerfCurr15MinES OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Errored Seconds (ES) on the GBS in the

current 15-minute performance history interval.

This object maps to the TR-159 attribute aGroupPerfCurr15MinES."

REFERENCE

"[[TR-159](#)] 5.5.1.35"

::= { gBondPortPerfCurrEntry 7 }

gBondPerfCurr15MinSES OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Severely Errored Seconds (ES) on the GBS in the current 15-minute performance history interval.

This object maps to the TR-159 attribute aGroupPerfCurr15MinSES."

REFERENCE

"[[TR-159](#)] 5.5.1.36"

::= { gBondPortPerfCurrEntry 8 }

gBondPerfCurr15MinUAS OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Unavailable Seconds (UAS) on the GBS in the current 15-minute performance history interval.

This object maps to the TR-159 attribute aGroupPerfCurr15MinUAS."

REFERENCE

"[[TR-159](#)] 5.5.1.37"

::= { gBondPortPerfCurrEntry 9 }

gBondPerf1DayValidIntervals OBJECT-TYPE

SYNTAX Unsigned32 (0..7)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 1-day intervals for which data was collected. The value of this object will be 7 or the maximum number of 1-day history intervals collected by the implementation unless the measurement was (re-)started recently, in which case the value will be the number of complete 1-day intervals for which there are at least some data.

In certain cases it is possible that some intervals are unavailable. In this case, this object reports the maximum interval number for which data is available.

This object maps to the TR-159 attribute
aGroupPerf1DayValidIntervals."

REFERENCE

"[[TR-159](#)] 5.5.1.45"

::= { gBondPortPerfCurrEntry 10 }

gBondPerf1DayInvalidIntervals OBJECT-TYPE

SYNTAX Unsigned32 (0..7)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 1-day intervals for which data was
not always available. The value will typically be zero except in
cases where the data for some intervals are not available.

This object maps to the TR-159 attribute
aGroupPerf1DayInvalidIntervals."

REFERENCE

"[[TR-159](#)] 5.5.1.46"

::= { gBondPortPerfCurrEntry 11 }

gBondPerfCurr1DayTimeElapsed OBJECT-TYPE

SYNTAX HCPperfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds that have elapsed since the
beginning of the current 1-day performance history interval.

This object maps to the TR-159 attribute
aGroupPerfCurr1DayTimeElapsed."

REFERENCE

"[[TR-159](#)] 5.5.1.47"

::= { gBondPortPerfCurrEntry 12 }

gBondPerfCurr1DayES OBJECT-TYPE

SYNTAX HCPperfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Errored Seconds (ES) on the GBS in the
current 1-day performance history interval.

This object maps to the TR-159 attribute aGroupPerfCurr1DayES."

REFERENCE

"[[TR-159](#)] 5.5.1.48"

::= { gBondPortPerfCurrEntry 13 }

gBondPerfCurr1DaySES OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Severely Errored Seconds (ES) on the GBS in the current 1-day performance history interval.

This object maps to the TR-159 attribute aGroupPerfCurr1DaySES."

REFERENCE

"[[TR-159](#)] 5.5.1.49"

::= { gBondPortPerfCurrEntry 14 }

gBondPerfCurr1DayUAS OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Unavailable Seconds (UAS) on the GBS in the current 1-day performance history interval.

This object maps to the TR-159 attribute aGroupPerfCurr1DayUAS."

REFERENCE

"[[TR-159](#)] 5.5.1.50"

::= { gBondPortPerfCurrEntry 15 }

-- PM history: 15-min buckets

gBondPortPerf15MinTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondPortPerf15MinEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains historical 15-minute buckets of Performance Monitoring information for a GBS port (a row for each 15-minute interval, up to 96 intervals).

Entries in this table MUST be maintained in a persistent manner."

::= { gBondPortPM 2 }

gBondPortPerf15MinEntry OBJECT-TYPE

SYNTAX GBondPortPerf15MinEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond Port historical 15-minute PM table. Each entry represents performance monitoring data for a GBS port, indexed by ifIndex, collected during a particular 15-minute interval, indexed by gBondPerf15MinIntervalIndex."


```
INDEX { ifIndex, gBondPerf15MinIntervalIndex }  
 ::= { gBondPortPerf15MinTable 1 }
```

```
GBondPortPerf15MinEntry ::=
```

```
SEQUENCE {  
    gBondPerf15MinIntervalIndex      Unsigned32,  
    gBondPerf15MinIntervalMoniTime   HCPperfTimeElapsed,  
    gBondPerf15MinIntervalES         HCPperfIntervalCount,  
    gBondPerf15MinIntervalSES        HCPperfIntervalCount,  
    gBondPerf15MinIntervalUAS        HCPperfIntervalCount,  
    gBondPerf15MinIntervalValid      TruthValue  
}
```

```
gBondPerf15MinIntervalIndex OBJECT-TYPE
```

```
SYNTAX      Unsigned32 (1..96)
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

"Performance Data Interval number. 1 is the most recent previous interval; interval 96 is 24 hours ago. Intervals 2..96 are OPTIONAL.

This object maps to the TR-159 attribute aGroupPerf15MinIntervalNumber."

```
REFERENCE
```

"[[TR-159](#)] 5.5.1.57"

```
::= { gBondPortPerf15MinEntry 1 }
```

```
gBondPerf15MinIntervalMoniTime OBJECT-TYPE
```

```
SYNTAX      HCPperfTimeElapsed
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

```
DESCRIPTION
```

"A read-only count of seconds over which the performance data was actually monitored. This value will be the same as the interval duration (900 seconds), except in a situation where performance data could not be collected for any reason."

```
::= { gBondPortPerf15MinEntry 2 }
```

```
gBondPerf15MinIntervalES OBJECT-TYPE
```

```
SYNTAX      HCPperfIntervalCount
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

```
DESCRIPTION
```

"A read-only count of Errored Seconds (ES) on the GBS in the 15-minute performance history interval.

This object maps to the TR-159 attribute

aGroupPerf15MinIntervalES."

REFERENCE

"[[TR-159](#)] 5.5.1.59"

::= { gBondPortPerf15MinEntry 3 }

gBondPerf15MinIntervalsES OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Severely Errored Seconds (ES) on the GBS in the 15-minute performance history interval.

This object maps to the TR-159 attribute

aGroupPerf15MinIntervalsES."

REFERENCE

"[[TR-159](#)] 5.5.1.60"

::= { gBondPortPerf15MinEntry 4 }

gBondPerf15MinIntervalUAS OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Unavailable Seconds (UAS) on the GBS in the current 15-minute performance history interval.

This object maps to the TR-159 attribute aGroupPerfCurr15MinUAS."

REFERENCE

"[[TR-159](#)] 5.5.1.61"

::= { gBondPortPerf15MinEntry 5 }

gBondPerf15MinIntervalValid OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only object indicating whether or not this history bucket contains valid data. Valid bucket is reported as true(1) and invalid bucket as false(2).

If this history bucket is invalid the BTU-C MUST NOT produce notifications based upon the value of the counters in this bucket.

Note that an implementation may decide not to store invalid history buckets in its data base. In such case this object is not required as only valid history buckets are available while invalid history buckets are simply not in the data base.

This object maps to the TR-159 attribute
aGroupPerf15MinIntervalValid."

REFERENCE

"[[TR-159](#)] 5.5.1.58"

::= { gBondPortPerf15MinEntry 6 }

-- PM history: 1-day buckets

gBondPortPerf1DayTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondPortPerf1DayEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains historical 1-day buckets of Performance
Monitoring information for a GBS port (a row for each 1-day
interval, up to 7 intervals).

Entries in this table MUST be maintained in a persistent manner."

::= { gBondPortPM 3 }

gBondPortPerf1DayEntry OBJECT-TYPE

SYNTAX GBondPortPerf1DayEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond Port historical 1-day PM table.

Each entry represents performance monitoring data for a GBS port,
indexed by ifIndex, collected during a particular 1-day
interval, indexed by gBondPerf1DayIntervalIndex."

INDEX { ifIndex, gBondPerf1DayIntervalIndex }

::= { gBondPortPerf1DayTable 1 }

GBondPortPerf1DayEntry ::=

SEQUENCE {

gBondPerf1DayIntervalIndex	Unsigned32,
gBondPerf1DayIntervalMoniTime	HCPperfTimeElapsed,
gBondPerf1DayIntervales	HCPperfIntervalCount,
gBondPerf1DayIntervalesSES	HCPperfIntervalCount,
gBondPerf1DayIntervalUAS	HCPperfIntervalCount,
gBondPerf1DayIntervalValid	TruthValue

}

gBondPerf1DayIntervalIndex OBJECT-TYPE

SYNTAX Unsigned32 (1..7)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Performance Data Interval number. 1 is the most recent previous
interval; interval 7 is 24 hours ago.

Intervals 2..7 are OPTIONAL.

This object maps to the TR-159 attribute
aGroupPerf1DayIntervalNumber."

REFERENCE

"[[TR-159](#)] 5.5.1.62"

::= { gBondPortPerf1DayEntry 1 }

gBondPerf1DayIntervalMoniTime OBJECT-TYPE

SYNTAX HCPerfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds over which the performance data was actually monitored. This value will be the same as the interval duration (86400 seconds), except in a situation where performance data could not be collected for any reason.

This object maps to the TR-159 attribute
aGroupPerf1DayIntervalMoniSecs."

REFERENCE

"[[TR-159](#)] 5.5.1.64"

::= { gBondPortPerf1DayEntry 2 }

gBondPerf1DayIntervalES OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Errored Seconds (ES) on the GBS in the 1-day performance history interval.

This object maps to the TR-159 attribute
aGroupPerf1DayIntervalES."

REFERENCE

"[[TR-159](#)] 5.5.1.65"

::= { gBondPortPerf1DayEntry 3 }

gBondPerf1DayIntervalSES OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Severely Errored Seconds (ES) on the GBS in the 1-day performance history interval.

This object maps to the TR-159 attribute
aGroupPerf1DayIntervalSES."

REFERENCE

"[[TR-159](#)] 5.5.1.66"

::= { gBondPortPerf1DayEntry 4 }

gBondPerf1DayIntervalUAS OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of Unavailable Seconds (UAS) on the GBS in the current 1-day performance history interval.

This object maps to the TR-159 attribute aGroupPerfCurr1DayUAS."

REFERENCE

"[[TR-159](#)] 5.5.1.67"

::= { gBondPortPerf1DayEntry 5 }

gBondPerf1DayIntervalValid OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only object indicating whether or not this history bucket contains valid data. Valid bucket is reported as true(1) and invalid bucket as false(2).

If this history bucket is invalid the BTU-C MUST NOT produce notifications based upon the value of the counters in this bucket.

Note that an implementation may decide not to store invalid history buckets in its data base. In such case this object is not required as only valid history buckets are available while invalid history buckets are simply not in the data base.

This object maps to the TR-159 attribute aGroupPerf1DayIntervalValid."

REFERENCE

"[[TR-159](#)] 5.5.1.63"

::= { gBondPortPerf1DayEntry 6 }

-- Performance Monitoring TCA Configuration profile

gBondPortPerfTcaConfProfileTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondPortPerfTcaConfProfileEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table supports definitions of Performance Monitoring (PM)

Threshold Crossing Alerts (TCA) configuration profiles for GBS ports.

Entries in this table MUST be maintained in a persistent manner."

::= { gBondPortPM 4 }

gBondPortPerfTcaConfProfileEntry OBJECT-TYPE

SYNTAX GBondPortPerfTcaConfProfileEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the GBS PM TCA Configuration table.

Each entry corresponds to a single TCA configuration profile.

Each profile contains a set of parameters for setting alarm thresholds for various performance attributes monitored at GBS ports. Profiles may be created/deleted using the row creation/deletion mechanism via

gBondPerfTcaConfProfileRowStatus. If an active entry is referenced via gBondPerfTcaConfProfile, the entry MUST remain active until all references are removed.

A default profile with an index of 'DEFVAL', will always exist and its parameters will be set to vendor specific values, unless otherwise specified in this document."

INDEX { gBondPerfTcaConfProfileName }

::= { gBondPortPerfTcaConfProfileTable 1 }

GBondPortPerfTcaConfProfileEntry ::=

SEQUENCE {

gBondPerfTcaConfProfileName SnmpAdminString,

gBondPerfThreshold15MinES HCPperfIntervalThreshold,

gBondPerfThreshold15MinSES HCPperfIntervalThreshold,

gBondPerfThreshold15MinUAS HCPperfIntervalThreshold,

gBondPerfThreshold1DayES GBondPerf1DayIntervalThreshold,

gBondPerfThreshold1DaySES GBondPerf1DayIntervalThreshold,

gBondPerfThreshold1DayUAS GBondPerf1DayIntervalThreshold,

gBondPerfTcaConfProfileRowStatus RowStatus

}

gBondPerfTcaConfProfileName OBJECT-TYPE

SYNTAX SnmpAdminString (SIZE(1..32))

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This object is a unique index (name) associated with this GBS PM TCA profile."

::= { gBondPortPerfTcaConfProfileEntry 1 }

gBondPerfThreshold15MinES OBJECT-TYPE

SYNTAX HCPperfIntervalThreshold

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"A desired threshold for the number of Errored Seconds (ES) within any given 15-minute performance data collection interval. If the number of ESs in a particular 15-minute collection interval reaches or exceeds this value, a gBondPerfTca15MinESCrossing notification MAY be generated if enabled by gBondPerfTcaEnable. At most one notification can be sent per interval. Setting this attribute to zero (default) effectively disables gBondPerfTca15MinESCrossing notification.

This object maps to the TR-159 attribute
aGroupPerfThreshold15MinES."

REFERENCE

"[[TR-159](#)] 5.5.1.39"

::= { gBondPortPerfTcaConfProfileEntry 2 }

gBondPerfThreshold15MinSES OBJECT-TYPE

SYNTAX HCPerfIntervalThreshold

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"A desired threshold for the number of Severely Errored Seconds (SES) within any given 15-minute performance data collection interval. If the number of SESs in a particular 15-minute collection interval reaches or exceeds this value, a gBondPerfTca15MinSESCrossing notification MAY be generated if enabled by gBondPerfTcaEnable. At most one notification can be sent per interval. Setting this attribute to zero (default) effectively disables gBondPerfTca15MinSESCrossing notification.

This object maps to the TR-159 attribute
aGroupPerfThreshold15MinSES."

REFERENCE

"[[TR-159](#)] 5.5.1.40"

::= { gBondPortPerfTcaConfProfileEntry 3 }

gBondPerfThreshold15MinUAS OBJECT-TYPE

SYNTAX HCPerfIntervalThreshold

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"A desired threshold for the number of Unavailable Seconds (UAS) within any given 15-minute performance data collection interval.

If the number of UASs in a particular 15-minute collection interval reaches or exceeds this value, a gBondPerfTca15MinUASCrossing notification MAY be generated if enabled by gBondPerfTcaEnable.

At most one notification can be sent per interval.

Setting this attribute to zero (default) effectively disables gBondPerfTca15MinUASCrossing notification.

This object maps to the TR-159 attribute
aGroupPerfThreshold15MinUAS."

REFERENCE

"[[TR-159](#)] 5.5.1.41"

::= { gBondPortPerfTcaConfProfileEntry 4 }

gBondPerfThreshold1DayES OBJECT-TYPE

SYNTAX GBondPerf1DayIntervalThreshold

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"A desired threshold for the number of Errored Seconds (ES) within any given 1-day performance data collection interval. If the number of ESs in a particular 1-day collection interval reaches or exceeds this value, a gBondPerfTca1DayESCrossing notification MAY be generated if enabled by gBondPerfTcaEnable. At most one notification can be sent per interval. Setting this attribute to zero (default) effectively disables gBondPerfTca1DayESCrossing notification.

This object maps to the TR-159 attribute
aGroupPerfThreshold1DayES."

REFERENCE

"[[TR-159](#)] 5.5.1.51"

::= { gBondPortPerfTcaConfProfileEntry 5 }

gBondPerfThreshold1DaySES OBJECT-TYPE

SYNTAX GBondPerf1DayIntervalThreshold

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"A desired threshold for the number of Severely Errored Seconds (SES) within any given 1-day performance data collection interval. If the number of SESs in a particular 1-day collection interval reaches or exceeds this value, a gBondPerfTca1DaySESCrossing notification MAY be generated if enabled by gBondPerfTcaEnable. At most one notification can be sent per interval. Setting this attribute to zero (default) effectively disables gBondPerfTca1DaySESCrossing notification.

This object maps to the TR-159 attribute
aGroupPerfThreshold1DaySES."

REFERENCE

"[[TR-159](#)] 5.5.1.52"

::= { gBondPortPerfTcaConfProfileEntry 6 }

gBondPerfThreshold1DayUAS OBJECT-TYPE

SYNTAX GBondPerf1DayIntervalThreshold

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"A desired threshold for the number of Unavailable Seconds (UAS) within any given 1-day performance data collection interval. If the number of UASs in a particular 1-day collection interval reaches or exceeds this value, a gBondPerfTca1DayUASCrossing notification MAY be generated if enabled by gBondPerfTcaEnable. At most one notification can be sent per interval. Setting this attribute to zero (default) effectively disables gBondPerfTca1DayUASCrossing notification.

This object maps to the TR-159 attribute
aGroupPerfThreshold1DayUAS."

REFERENCE

"[[TR-159](#)] 5.5.1.53"

::= { gBondPortPerfTcaConfProfileEntry 7 }

gBondPerfTcaConfProfileRowStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object controls the creation, modification, or deletion of the associated entry in the gBondPortPerfTcaConfProfileTable per the semantics of RowStatus.

If an 'active' entry is referenced via gBondPerfTcaConfProfile instance(s), the entry MUST remain 'active'.

An 'active' entry SHALL NOT be modified. In order to modify an existing entry, it MUST be taken out of service (by setting this object to 'notInService'), modified, and set 'active' again."

::= { gBondPortPerfTcaConfProfileEntry 8 }

-- The BCE group

gBondBceConfTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondBceConfEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Table for Configuration of G.Bond common aspects for the Bonding Channel Entity (BCE) ports (modems/channels).

Entries in this table MUST be maintained in a persistent manner."

::= { gBondBce 1 }

gBondBceConfEntry OBJECT-TYPE

SYNTAX GBondBceConfEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond BCE Configuration table.

Each entry represents common aspects of a G.Bond BCE port indexed by the ifIndex. Note that an G.Bond BCE port can be stacked below a single GBS port, also indexed by ifIndex, possibly together with other BCE ports if GAF is enabled."

INDEX { ifIndex }

::= { gBondBceConfTable 1 }

GBondBceConfEntry ::=

SEQUENCE {

gBondBceRemoteDiscoveryCode PhysAddress

}

gBondBceRemoteDiscoveryCode OBJECT-TYPE

SYNTAX PhysAddress (SIZE(0|6))

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"A Remote Discovery Code of the BCE port at C0.

A 6 octet long Discovery Code of the peer GBS connected via the BCE.

Reading this object results in a Discovery Get operation. Setting this object to all zeroes results in a Discovery Clear_if_Same operation (the value of gBondDiscoveryCode at the peer GBS SHALL be the same as gBondDiscoveryCode of the local GBS associated with the BCE for the operation to succeed).

Writing a non-zero value to this object results in a Discovery Set_if_Clear operation.

A zero-length octet string SHALL be returned on an attempt to read this object when GAF aggregation is not enabled.

This object is irrelevant in BCE-R port subtypes (CPE side): in this case a zero length octet string SHALL be returned on an attempt to read this object, writing to this object SHALL be rejected.

Discovery MUST be performed when the link is Down. Attempts to change this object MUST be rejected (in case of SNMP with the error inconsistentValue), if the link is Up or Initializing.

This object maps to the TR-159 attribute
aLineRemoteDiscoveryCode."

REFERENCE

"[[TR-159](#)] 5.5.6.7"
::= { gBondBceConfEntry 1 }

--

-- Conformance Statements

--

gBondGroups OBJECT IDENTIFIER ::= { gBondConformance 1 }

gBondCompliances OBJECT IDENTIFIER ::= { gBondConformance 2 }

-- Object Groups

gBondBasicGroup OBJECT-GROUP

OBJECTS {

gBondOperScheme,
gBondUpDataRate,
gBondDnDataRate,
gBondTargetUpDataRate,
gBondTargetDnDataRate,
gBondOperScheme,
gBondCapacity,
gBondNumBCEs,
gBondPortSide,
gBondFltStatus

}

STATUS current

DESCRIPTION

"A collection of objects representing management information
common to all types of G.Bond ports."

::= { gBondGroups 1 }

gBondDiscoveryGroup OBJECT-GROUP

OBJECTS {

gBondPeerOperScheme,


```
    gBondPeerCapacity,
    gBondDiscoveryCode,
    gBondBceRemoteDiscoveryCode
}
STATUS      current
DESCRIPTION
    "A collection of objects supporting OPTIONAL G.Bond discovery
    in G.Bond ports."
::= { gBondGroups 2 }
```

gBondMultiSchemeGroup OBJECT-GROUP

```
OBJECTS {
    gBondSchemesSupported,
    gBondPeerSchemesSupported,
    gBondAdminScheme,
    gBondPeerAdminScheme
}
STATUS      current
DESCRIPTION
    "A collection of objects providing OPTIONAL management
    information for G.Bond ports supporting multiple bonding
    schemes."
::= { gBondGroups 3 }
```

gBondTcaConfGroup OBJECT-GROUP

```
OBJECTS {
    gBondThreshLowUpRate,
    gBondThreshLowDnRate,
    gBondLowRateCrossingEnable
}
STATUS      current
DESCRIPTION
    "A collection of objects required for configuration of alarm
    thresholds and notifications in G.Bond ports."
::= { gBondGroups 4 }
```

gBondTcaNotificationGroup NOTIFICATION-GROUP

```
NOTIFICATIONS {
    gBondLowUpRateCrossing,
    gBondLowDnRateCrossing
}
STATUS      current
DESCRIPTION
    "This group supports notifications of significant conditions
    (non-PM threshold crossing alerts) associated with G.Bond ports."
::= { gBondGroups 5 }
```

gBondPerfCurrGroup OBJECT-GROUP


```
OBJECTS {
    gBondPerfES,
    gBondPerfSES,
    gBondPerfUAS,
    gBondPerf15MinValidIntervals,
    gBondPerf15MinInvalidIntervals,
    gBondPerfCurr15MinTimeElapsed,
    gBondPerfCurr15MinES,
    gBondPerfCurr15MinSES,
    gBondPerfCurr15MinUAS,
    gBondPerf1DayValidIntervals,
    gBondPerf1DayInvalidIntervals,
    gBondPerfCurr1DayTimeElapsed,
    gBondPerfCurr1DayES,
    gBondPerfCurr1DaySES,
    gBondPerfCurr1DayUAS
}
STATUS          current
DESCRIPTION
    "A collection of objects supporting OPTIONAL current Performance
    Monitoring information for G.Bond ports."
::= { gBondGroups 6 }
```

gBondPerf15MinGroup OBJECT-GROUP

```
OBJECTS {
    gBondPerf15MinIntervalMoniTime,
    gBondPerf15MinIntervalES,
    gBondPerf15MinIntervalSES,
    gBondPerf15MinIntervalUAS,
    gBondPerf15MinIntervalValid
}
STATUS          current
DESCRIPTION
    "A collection of objects supporting OPTIONAL historical
    Performance Monitoring information for G.Bond ports, during
    previous 15-minute intervals ."
::= { gBondGroups 7 }
```

gBondPerf1DayGroup OBJECT-GROUP

```
OBJECTS {
    gBondPerf1DayIntervalMoniTime,
    gBondPerf1DayIntervalES,
    gBondPerf1DayIntervalSES,
    gBondPerf1DayIntervalUAS,
    gBondPerf1DayIntervalValid
}
STATUS          current
DESCRIPTION
```



```
"A collection of objects supporting OPTIONAL historical
Performance Monitoring information for G.Bond ports, during
previous 1-day intervals ."
 ::= { gBondGroups 8 }
```

gBondPerfTcaConfGroup OBJECT-GROUP

```
OBJECTS {
    gBondPerfTcaConfProfile,
    gBondPerfTcaEnable,
    gBondPerfThreshold15MinES,
    gBondPerfThreshold15MinSES,
    gBondPerfThreshold15MinUAS,
    gBondPerfThreshold1DayES,
    gBondPerfThreshold1DaySES,
    gBondPerfThreshold1DayUAS,
    gBondPerfTcaConfProfileRowStatus
}
STATUS      current
DESCRIPTION
    "A collection of objects required for configuration of
    Performance Monitoring Threshold Crossing Alert notifications
    in G.Bond ports."
 ::= { gBondGroups 9 }
```

gBondPerfTcaNotificationGroup NOTIFICATION-GROUP

```
NOTIFICATIONS {
    gBondPerfTca15MinESCrossing,
    gBondPerfTca15MinSESCrossing,
    gBondPerfTca15MinUASCrossing,
    gBondPerfTca1DayESCrossing,
    gBondPerfTca1DaySESCrossing,
    gBondPerfTca1DayUASCrossing
}
STATUS      current
DESCRIPTION
    "This group supports notifications of performance monitoring
    thresholds crossing alerts associated with G.Bond ports."
 ::= { gBondGroups 10 }
```

-- Compliance Statements

gBondCompliance MODULE-COMPLIANCE

```
STATUS      current
DESCRIPTION
    "The compliance statement for G.Bond interfaces.
    Compliance with the following external compliance statements
    is REQUIRED:
```


MIB Module	Compliance Statement
-----	-----
IF-MIB	ifCompliance3

Compliance with the following external compliance statements is OPTIONAL for implementations supporting bonding with flexible cross-connect between the GBS and BCE ports:

MIB Module	Compliance Statement
-----	-----
IF-INVERTED-STACK-MIB	ifInvCompliance
IF-CAP-STACK-MIB	ifCapStackCompliance"

```
MODULE -- this module
MANDATORY-GROUPS {
    gBondBasicGroup,
    gBondTcaConfGroup,
    gBondTcaNotificationGroup
}

GROUP          gBondDiscoveryGroup
DESCRIPTION
    "Support for this group is only required for implementations
    supporting G.Bond Discovery function."

GROUP          gBondMultiSchemeGroup
DESCRIPTION
    "Support for this group is only required for implementations
    supporting multiple bonding schemes."

GROUP          gBondPerfCurrGroup
DESCRIPTION
    "Support for this group is only required for implementations
    supporting Performance Monitoring."

GROUP          gBondPerf15MinGroup
DESCRIPTION
    "Support for this group is only required for implementations
    supporting historical Performance Monitoring."

GROUP          gBondPerf1DayGroup
DESCRIPTION
    "Support for this group is only required for implementations
    supporting historical Performance Monitoring."

GROUP          gBondPerfTcaConfGroup
DESCRIPTION
    "Support for this group is only required for implementations
```


supporting Performance Monitoring Threshold Crossing Alert notifications."

GROUP gBondPerfTcaNotificationGroup

DESCRIPTION

"Support for this group is only required for implementations supporting Performance Monitoring Threshold Crossing Alert notifications."

::= { gBondCompliances 1 }

END

7. Security Considerations

There is a number of managed objects defined in the GBOND-MIB module that have a MAX-ACCESS clause of read-write or read-create. Most objects are writeable only when the link is Down. Writing to these objects can have potentially disruptive effects on network operation, for example:

- o Changing of gBondAdminScheme MAY lead to a potential locking of the link, if the peer device does not support desired bonding scheme.
- o Changing of gBondDiscoveryCode, before the discovery operation, MAY lead to a wrongful discovery, for example when two CO ports are connected to the same multi-channel RT port, while both CO ports have the same Discovery register value.
- o Changing GBS configuration parameters (e.g., profile of a GBS via gBondAdminProfile) MAY lead to anything from link quality and rate degradation to a complete link initialization failure, as ability of an G.Bond port to support a particular configuration depends on the copper environment.
- o Activation of a specific line/channel MAY cause a severe degradation of service for another G.Bond port, whose channel(s) MAY be affected by the cross-talk from the newly activated channel.
- o Removal of a channel from an operationally 'up' G.Bond port, aggregating several channels, MAY cause port's rate degradation

The user of the GBOND-MIB module must therefore be aware that support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

The readable objects in the GBOND-MIB module (i.e., those with MAX-

ACCESS other than not-accessible) may be considered sensitive in some environments since, collectively, they provide information about the performance of network interfaces and can reveal some aspects of their configuration. In particular, since a bonded xDSL port can be comprised of multiple Unshielded Twisted Pair (UTP) voice grade copper, located in the same bundle with other pairs belonging to another operator/customer, it is theoretically possible to evasdrop to a G.Bond transmission, simply by "listening" to a cross-talk from the bonded pairs, especially if the parameters of the G.Bond link in question are known.

In such environments it is important to control also GET and NOTIFY access to these objects and possibly even to encrypt their values when sending them over the network via SNMP.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

8. IANA Considerations

Three new values of IANAifType: g9981, g9982 and g9982 SHALL be defined by the IANA [\[1\]](#) in the IANAifType-MIB module [\[IANAifType-MIB\]](#), before this document is published as an RFC.

Additionally, an object identifier for gBondMIB MODULE-IDENTITY SHALL be allocated by IANA in the MIB-2 transmission sub-tree, before this document is published.

9. Acknowledgments

This document was produced by the [\[ADSLMIB\]](#) working group.

[10.](#) References

[10.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), June 2000.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, [RFC 3411](#), December 2002.
- [RFC3705] Ray, B. and R. Abbi, "High Capacity Textual Conventions for MIB Modules Using Performance History Based on 15 Minute Intervals", [RFC 3705](#), February 2004.
- [TR-159] Beili, E. and M. Morgenstern, "Management Framework for xDSL Bonding", Broadband Forum technical report TR-159, December 2008.

10.2. Informative References

- [802.3] IEEE, "IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications", IEEE Std 802.3-2005, December 2005.
- [ADSLMIB] IETF, "ADSL MIB (adslmib) Charter", <<http://www.ietf.org/html.charters/adslmib-charter.html>>.
- [G.991.2] ITU-T, "Single-pair High-speed Digital Subscriber Line (SHDSL) transceivers", ITU-T Recommendation G.991.2, December 2003, <<http://www.itu.int/rec/T-REC-G.991.2/en>>.
- [G.993.1] ITU-T, "Very High speed Digital Subscriber Line transceivers", ITU-T Recommendation G.993.1, June 2004, <<http://www.itu.int/rec/T-REC-G.993.1/en>>.
- [G.998.1] ITU-T, "ATM-based multi-pair bonding", ITU-T Recommendation G.998.1, January 2005, <<http://www.itu.int/rec/T-REC-G.998.1/en>>.
- [G.998.2] ITU-T, "Ethernet-based multi-pair bonding", ITU-T Recommendation G.998.2, January 2005, <<http://www.itu.int/rec/T-REC-G.998.2/en>>.
- [G.998.3] ITU-T, "Multi-pair bonding using time-division inverse multiplexing", ITU-T Recommendation G.998.3,

- January 2005, <<http://www.itu.int/rec/T-REC-G.998.3/en>>.
- [I-D.ietf-adslmib-gbond-atm-mib] Beili, E., "ATM-based xDSL Bonded Interfaces MIB", [draft-ietf-adslmib-gbond-atm-mib-01](#) (work in progress), May 2010.
- [I-D.ietf-adslmib-gbond-eth-mib] Beili, E. and M. Morgenstern, "Ethernet-based xDSL Bonded Interfaces MIB", [draft-ietf-adslmib-gbond-eth-mib-02](#) (work in progress), May 2010.
- [I-D.ietf-adslmib-gbond-tdim-mib] Beili, E., "TDIM-based xDSL Bonded Interfaces MIB", [draft-ietf-adslmib-gbond-tdim-mib-03](#) (work in progress), May 2010.
- [IANAifType-MIB] Internet Assigned Numbers Authority (IANA), "IANAifType Textual Convention definition", <<http://www.iana.org/assignments/ianaiftype-mib>>.
- [RFC2864] McCloghrie, K. and G. Hanson, "The Inverted Stack Table Extension to the Interfaces Group MIB", [RFC 2864](#), June 2000.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.
- [RFC3440] Ly, F. and G. Bathrick, "Definitions of Extension Managed Objects for Asymmetric Digital Subscriber Lines", [RFC 3440](#), December 2002.
- [RFC3593] Tesink, K., "Textual Conventions for MIB Modules Using Performance History Based on 15 Minute Intervals", [RFC 3593](#), September 2003.

- [RFC3728] Ray, B. and R. Abbi, "Definitions of Managed Objects for Very High Speed Digital Subscriber Lines (VDSL)", [RFC 3728](#), February 2004.
- [RFC4181] Heard, C., "Guidelines for Authors and Reviewers of MIB Documents", [BCP 111](#), [RFC 4181](#), September 2005.
- [RFC4319] Sikes, C., Ray, B., and R. Abbi, "Definitions of Managed Objects for High Bit-Rate DSL - 2nd generation (HDSL2) and Single-Pair High-Speed Digital Subscriber Line (SHDSL) Lines", [RFC 4319](#), December 2005.
- [RFC4706] Morgenstern, M., Dodge, M., Baillie, S., and U. Bonollo, "Definitions of Managed Objects for Asymmetric Digital Subscriber Line 2 (ADSL2)", [RFC 4706](#), November 2006.
- [RFC4836] Beili, E., "Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs)", [RFC 4836](#), April 2007.
- [RFC5066] Beili, E., "Ethernet in the First Mile Copper (EFMCu) Interfaces MIB", [RFC 5066](#), November 2007.
- [RFC5650] Morgenstern, M., Baillie, S., and U. Bonollo, "Definitions of Managed Objects for Very High Speed Digital Subscriber Line 2 (VDSL2)", [RFC 5650](#), September 2009.
- [af-phy-0086] ATM Forum, "Inverse Multiplexing for ATM (IMA) Specification Version 1.1", ATM Forum specification af-pfy-0086.001, March 1999.

[1] <<http://www.iana.org/>>

Authors' Addresses

Edward Beili
Actelis Networks
25 Bazel St.
Petach-Tikva 49103
Israel

Phone: +972-3-924-3491
EMail: edward.beili@actelis.com

Moti Morgenstern
ECI Telecom
30 Hasivim St.
Petach-Tikva 49517
Israel

Phone: +972-3-926-6258
EMail: moti.morgenstern@ecitele.com

