

**xDSL multi-pair bonding using Time-Division Inverse Multiplexing
(G.Bond/TDIM) MIB
draft-ietf-adslmib-gbond-tdim-mib-06.txt**

Abstract

This document defines Management Information Base (MIB) module for use with network management protocols in TCP/IP based internets. This document proposes an extension to the GBOND-MIB module with a set of objects for managing multi-pair bonded xDSL interfaces using Time-Division Inverse Multiplexing (TDIM), defined in ITU-T recommendation G.998.3.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 27, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4](#).e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	The Internet-Standard Management Framework	3
3.	The Broadband Forum Management Framework for xDSL Bonding . .	3
4.	Relationship to other MIB modules	3
4.1.	Relationship to Interfaces Group MIB module	4
4.2.	Relationship to G.Bond MIB module	4
5.	MIB Structure	4
5.1.	Overview	4
5.2.	Link Protection Configuration	5
5.3.	Service Configuration	5
5.3.1.	Management of TDM Services and service drop priority during bandwidth degradation	6
5.3.2.	Service Notifications	6
5.4.	Performance Monitoring	6
5.5.	Mapping of Broadband Forum TR-159 and ITU-T G.998.3 Managed Objects	7
6.	G.Bond/TDIM MIB Definitions	8
7.	Security Considerations	49
8.	IANA Considerations	50
9.	Acknowledgments	50
10.	References	50
10.1.	Normative References	50
10.2.	Informative References	51

1. Introduction

The Multi-pair bonding using time-division inverse multiplexing (TDIM), a.k.a. G.Bond/TDIM, is specified in ITU-T G.998.3 recommendation [[G.998.3](#)], which defines a method for bonding (or aggregating) of multiple xDSL lines (or individual bearer channels in multiple xDSL lines) into a single bi-directional logical link, carrying a mix of various traffic streams, e.g. Ethernet, Asynchronous Transfer Mode (ATM), Time-Division Multiplexing (TDM).

The MIB module, defined in this document, provides G.Bond/TDIM-specific objects for the management of G.998.3 bonded interfaces, extending the common bonding objects specified in GBOND-MIB [[I-D.ietf-ads1mib-gbond-mib](#)] module.

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

3. The Broadband Forum Management Framework for xDSL Bonding

This document makes use of the Broadband Forum technical report Management Framework for xDSL Bonding [[TR-159](#)], defining a management model and a hierarchy of management objects for the bonded xDSL interfaces.

4. Relationship to other MIB modules

This section outlines the relationship of the MIB modules defined in this document with other MIB modules described in the relevant RFCs. Specifically, the following MIB modules are discussed: Interfaces Group MIB (IF-MIB) and G.Bond MIB (GBOND-MIB).

4.1. Relationship to Interfaces Group MIB module

A G.Bond/TDIM port is a private case of a Bonded multi-pair xDSL interface and as such is managed using generic interface management objects defined in the IF-MIB [[RFC2863](#)]. In particular an interface index (ifIndex) is used to index instances of G.Bond/TDIM ports, as well as xDSL lines/channels, in a managed system.

4.2. Relationship to G.Bond MIB module

GBOND-MIB [[I-D.ietf-adslmib-gbond-mib](#)] module defines management objects common for all Bonded multi-pair xDSL interfaces. In particular it describes the bonding management, bonded port and channel configuration, initialization sequence etc.

Both GBOND-MIB and GBOND-TDIM-MIB modules are REQUIRED to manage a G.Bond/TDIM port.

5. MIB Structure

5.1. Overview

All management objects defined in the GBOND-TDIM-MIB module are contained in a single group gBondTdimPort. This group is further split into 6 sub-groups, structured as recommended by [RFC 4181](#) [[RFC4181](#)]:

- o gBondTdimPortNotifications - containing notifications (TDIM Service Down/Up).
- o gBondTdimPortConfTable - containing objects for configuration of a G.Bond/TDIM port.
- o gBondTdimPortCapabilityTable - containing objects reflecting capability of a G.Bond/TDIM port.
- o gBondTdimPortStatusTable - containing objects providing overall status information of a G.Bond/TDIM port, complementing the generic status information from the ifTable of IF-MIB and gBondFltStatus of GBOND-MIB.
- o gBondTdimServiceTable - containing objects for configuration and status of the services in a G.Bond/TDIM port.
- o gBondTdimPM - containing objects for an OPTIONAL Historical Performance Monitoring (PM) of a G.Bond/TDIM port.

5.2. Link Protection Configuration

G.Bond/TDIM specification allows an optional Forward Error Correction (FEC) and Interleaver block, which, if supported and enabled, provides a degree of protection against micro-interruptions, alien noise, and even individual Bonding Channel Entity (BCE) failures, a.k.a. cut-line protection.

Management objects in the gBondTdimPortConfTable can be used to configure and query the FEC and Interleaver function of the G.Bond/TDIM port.

5.3. Service Configuration

Unlike the other two xDSL Multi-Pair Bonding schemes (G.Bond/ATM and G.Bond/Ethernet), which send the information required for reassembly of the fragmented data along with the data, G.Bond/TDIM is a synchronous scheme, requiring both ends to know the data distribution tables before any actual data transfer can happen.

Management objects in the gBondTdimPortConfTable (gBondTdimAdminServices), gBondTdimServiceTable and gBondTdimOperServiceTable can be used to configure and query the configuration of services transported via the G.Bond/TDIM link. The services may be configured independently of the link state (i.e. in- and out-of-service), as G.998.3 communicates changes in the service configuration via specific Bonding Communication Channel (BCC) messages, switching both ends of the link to the new configuration synchronously.

There can be up to 60 active services defined on a G.Bond/TDIM link. This MIB module provides an ability to define up to 255 services via the gBondTdimServiceTable, with each row representing a possible service, and then set the actual service configuration using the gBondTdimAdminServices object (a byte-vector of service indices), listing the active services in order of their position in the G.Bond/TDIM frame. This design allows one to easily modify service drop priority, which directly corresponds to the service position.

The actual list of services is provided via read-only gBondTdimOperServiceTable, where each entry's index corresponds to the service position, starting from index 1 for the first entry, 2 for the second entry etc., providing an easy service navigation for a management application using GET-NEXT (instead of counting bytes in the gBondTdimAdminServices object).

The service configuration can only be changed on a BTU-C side.

When configuring the services, please bear in mind that the sum of all the services' bandwidth SHOULD be less or equal to the target data rate of the bonded link. Note that G.Bond/TDIM links are symmetrical, i.e. their upstream data rate equals to the downstream data rate.

5.3.1. Management of TDM Services and service drop priority during bandwidth degradation

G.Bond/TDIM protocol provides an ability to map TDM services into the TDIM bonded link directly, without any additional overhead. It addresses only structure-agnostic TDM transport, disregarding any structure that may be imposed on these streams, in particular the structure imposed by the standard TDM framing [[G.704](#)].

During bandwidth degradation services with a lower priority are impaired or dropped first. Synchronous services (fractional DS1/E1, clear channel E1/T1, T3/E3, clock) positioned in the beginning of the G.Bond/TDIM frame, have higher priority than asynchronous services (Ethernet, ATM, GFP encapsulated), positioned farther away. Within the services of the same type, those with lower position (index) have higher priority.

5.3.2. Service Notifications

This MIB module provides specific Up/Down notifications (gBondTdimServiceUp/gBondTdimServiceDown) for each of the configured services. During bandwidth degradation a number of services may be suspended (dropped) simultaneously, according to their drop priority (position in the service list). Please note that it is possible for a higher priority service to be dropped before a lower priority one. For example, suppose there are two services configured on a 2 Mbps G.Bond/TDIM link: a T1 service (gBondTdimServiceType with a value of ds1, with a bandwidth requirement of 1.5 Mbps) and an Ethernet service with a size of 0.5 Mbps. When the actual link bandwidth is reduced to 1.4 Mbps, the T1 service with a gBondTdimServicePosition value of 1 would be dropped, while the Ethernet service with a gBondTdimServicePosition value of 2 would remain up.

5.4. Performance Monitoring

The OPTIONAL performance monitoring counters, thresholds and history buckets (interval-counters), similar to those defined in [[TR-159](#)] are implemented using the textual conventions defined in the HC-PerfHist-TC-MIB [[RFC3705](#)]. The HC-PerfHist-TC-MIB defines 64-bit versions of the textual conventions found in PerfHist-TC-MIB [[RFC3593](#)].

The agent SHOULD align the beginning of each interval to a fifteen

minute boundary of a wall clock. Likewise, the beginning of each one day intervals SHOULD be aligned with the start of a day.

Counters are not reset when a G.Bond TDIM port is reinitialized, but rather only when the agent is reset or reinitialized (or under specific request outside the scope of this MIB module).

5.5. Mapping of Broadband Forum TR-159 and ITU-T G.998.3 Managed Objects

This section contains the mapping between relevant managed objects (attributes) defined in [TR-159] and managed objects defined in this document. Note that all management objects defined in [G.998.3] have corresponding objects in [TR-159].

+-----+-----+	+-----+-----+	+-----+-----+
TR-159 Managed Object	Corresponding SNMP Object	
+-----+-----+	+-----+-----+	+-----+-----+
oBondTDIM - Basic Package		
(Mandatory)		
+-----+-----+	+-----+-----+	+-----+-----+
aCRC4Errors	gBondTdimCrc4Errors	
+-----+-----+	+-----+-----+	+-----+-----+
aCRC6Errors	gBondTdimCrc6Errors	
+-----+-----+	+-----+-----+	+-----+-----+
aCRC8Errors	gBondTdimCrc8Errors	
+-----+-----+	+-----+-----+	+-----+-----+
aFECSupported	gBondTdimFecSupported	
+-----+-----+	+-----+-----+	+-----+-----+
oBondTDIM - FEC Package		
(Optional)		
+-----+-----+	+-----+-----+	+-----+-----+
aFECAdminState	gBondTdimFecAdminState	
+-----+-----+	+-----+-----+	+-----+-----+
aFECOperState	gBondTdimFecOperState	
+-----+-----+	+-----+-----+	+-----+-----+
aFECWordSize	gBondTdimFecWordSize	
+-----+-----+	+-----+-----+	+-----+-----+
aFECRedundancySize	gBondTdimFecRedundancySize	
+-----+-----+	+-----+-----+	+-----+-----+
aFECInterleaverType	gBondTdimFecInterleaverType	
+-----+-----+	+-----+-----+	+-----+-----+
aFECInterleaverDepth	gBondTdimFecInterleaverDepth	
+-----+-----+	+-----+-----+	+-----+-----+
aFECMaxWordSize	gBondTdimFecMaxWordSize	
+-----+-----+	+-----+-----+	+-----+-----+
aFECMaxRedundancySize	gBondTdimFecMaxRedundancySize	
+-----+-----+	+-----+-----+	+-----+-----+

aFECInterleaverTypesSupport	gBondTdimFecInterleaverTypeSupporte	
ed	d	
aFECMaxInterleaverDepth	gBondTdimFecMaxInterleaverDepth	
oTDIMService - Basic		
Package (Mandatory)		
aServiceID	gBondTdimServicePosition	
aServiceIfIdx	gBondTdimServiceIfIdx	
aServiceType	gBondTdimServiceType	
aServiceSize	gBondTdimServiceSize	
aServiceOperState	gBondTdimServiceOperState	
aServiceUpDownEnable	gBondTdimServiceUpDownEnable	
nServiceUp	gBondTdimServiceUp	
nServiceDown	gBondTdimServiceDown	

Table 1: Mapping of TR-159 Managed Objects

6. G.Bond/TDIM MIB Definitions

GBOND-TDIM-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY,
OBJECT-TYPE,
NOTIFICATION-TYPE,
mib-2,
Unsigned32,
Counter32

FROM SNMPv2-SMI -- [[RFC2578](#)]

TEXTUAL-CONVENTION,
RowStatus,
TruthValue

FROM SNMPv2-TC -- [[RFC2579](#)]

MODULE-COMPLIANCE,
OBJECT-GROUP,
NOTIFICATION-GROUP
FROM SNMPv2-CONF

-- [[RFC2580](#)]


```
ifIndex,
InterfaceIndex
  FROM IF-MIB          -- [RFC2863]
HCPperfCurrentCount,
HCPperfIntervalCount,
HCPperfValidIntervals,
HCPperfInvalidIntervals,
HCPperfTimeElapsed
  FROM HC-PerfHist-TC-MIB -- [RFC3705]
;
```

gBondTdimMIB MODULE-IDENTITY

LAST-UPDATED "201105260000Z" -- May 26, 2011

ORGANIZATION "IETF ADSL MIB Working Group"

CONTACT-INFO

"WG charter:

<http://www.ietf.org/html.charters/adslmib-charter.html>

Mailing Lists:

General Discussion: adslmib@ietf.org

To Subscribe: adslmib-request@ietf.org

In Body: subscribe your_email_address

Chair: Menachem Dodge

Postal: ECI Telecom, Ltd.

30 Hasivim St.,

Petach-Tikva 4951169

Israel

Phone: +972-3-926-8421

E-Mail: menachem.dodge@ecitele.com

Editor: Edward Beili

Postal: Actelis Networks, Inc.

25 Bazel St., P.O.B. 10173

Petach-Tikva 49103

Israel

Phone: +972-3-924-3491

E-Mail: edward.beili@actelis.com

DESCRIPTION

"The objects in this MIB module are used to manage the multi-pair bonded xDSL Interfaces using time-division inverse multiplexing (TDIM), defined in ITU-T recommendation G.998.3 (G.Bond/TDIM).

This MIB module MUST be used in conjunction with GBOND-MIB module, common to all G.Bond technologies.

The following references are used throughout this MIB module:

[G.998.3] refers to:

ITU-T Recommendation G.998.3: 'Multi-pair bonding using time-division inverse multiplexing', January 2005.

[TR-159] refers to:

Broadband Forum Technical Report: 'Management Framework for xDSL Bonding', December 2008.

Naming Conventions:

BCE - Bonding Channel Entity
CO - Central Office
CPE - Customer Premises Equipment
GBS - Generic Bonding Sublayer
GBS-C - Generic Bonded Sub-layer, CO side
GBS-R - Generic Bonded Sub-layer, RT (or CPE) side
SNR - Signal to Noise Ratio

Copyright (C) The IETF Trust (2011).

This version of this MIB module is part of RFC YYYY;
see the RFC itself for full legal notices."

REVISION "201105260000Z" -- May 26, 2011

DESCRIPTION "Initial version, published as RFC YYYY."

-- EdNote: Replace YYYY with the actual RFC number &
-- remove this note

::= { mib-2 ZZZ }

-- EdNote: Replace ZZZ with a real OID once it is
-- allocated & remove this note.

-- Sections of the module

-- Structured as recommended by [\[RFC4181\]](#), [Appendix D](#)

gBondTdimObjects OBJECT IDENTIFIER ::= { gBondTdimMIB 1 }

gBondTdimConformance OBJECT IDENTIFIER ::= { gBondTdimMIB 2 }

-- Groups in the module

gBondTdimPort OBJECT IDENTIFIER ::= { gBondTdimObjects 1 }

-- Textual Conventions

GBondTdimServiceIndex ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"
STATUS current
DESCRIPTION
"A unique value, greater than zero, for each Service defined
in the managed G.Bond/TDIM port.
It is RECOMMENDED that values are assigned contiguously
starting from 1. The value for each Service MUST remain
constant at least from one re-initialization of the entity's
network management system to the next re-initialization."
SYNTAX Unsigned32 (1..255)

GBondTdimServiceIndexList ::= TEXTUAL-CONVENTION

DISPLAY-HINT "1d:"
STATUS current
DESCRIPTION
"This textual convention represents a continuous ordered list of
all the services defined for the managed G.Bond/TDIM port.
The value of this object is a concatenation of zero or more (up
to 60) octets, where each octet contains an 8-bit
GBondTdimServiceIndex value, identifying a particular service.
An octet's position reflects the associated service position
and its priority in the G.Bond/TDIM frame, with 1st octet being
the 1st service of highest priority.

A zero-length octet string is object-specific and MUST
therefore be defined as part of the description of any object
that uses this syntax. Examples of the usage of a zero-length
value might include situations where an object using this
textual convention is irrelevant for a specific G.Bond/TDIM port
type or that no services have been defined for this port."
SYNTAX OCTET STRING (SIZE(0..60))

GBondTdimServiceOrderIndex ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"
STATUS current
DESCRIPTION
"A unique value, greater than zero, for each Service defined
in the managed G.Bond/TDIM port, showing its relative position
inside the G.Bond/TDIM frame."
SYNTAX Unsigned32 (1..60)

-- Port Notifications Group

gBondTdimPortNotifications OBJECT IDENTIFIER
::= { gBondTdimPort 0 }

gBondTdimServiceUp NOTIFICATION-TYPE
OBJECTS {


```
-- ifIndex is not needed here since we are under specific GBS
gBondTdimServicePosition,
gBondTdimServiceIfIdx,
gBondTdimServiceOperState
}
```

STATUS current

DESCRIPTION

"This notification indicates that a service indicated by the gBondTdimServicePosition (mapped to a particular interface indicated by the gBondTdimServiceIfIdx) in a particular G.Bond/TDIM port' is passing traffic.

This notification MAY be send for the G.Bond/TDIM port, while the port is Up, when the gBondTdimServiceOperState object has left the Down state.

Generation of this notification is controlled by the gBondTdimServiceUpDownEnable object.

This object maps to the TR-159 notification nServiceUp."

REFERENCE

"[[TR-159](#)] 5.5.5.7"

::= { gBondTdimPortNotifications 1 }

gBondTdimServiceDown NOTIFICATION-TYPE

OBJECTS {

```
-- ifIndex is not needed here since we are under specific GBS
gBondTdimServicePosition,
gBondTdimServiceIfIdx,
gBondTdimServiceOperState
}
```

STATUS current

DESCRIPTION

"This notification indicates that a service indicated by the gBondTdimServicePosition (mapped to a particular interface indicated by the gBondTdimServiceIfIdx) in a particular G.Bond/TDIM port has stopped passing the traffic.

This notification MAY be send for the G.Bond/TDIM port, while the port is Up, when the gBondTdimServiceOperState object has entered the Down state.

Generation of this notification is controlled by the gBondTdimServiceUpDownEnable object.

This object maps to the TR-159 notification nServiceDown."

REFERENCE

"[[TR-159](#)] 5.5.5.8"


```
::= { gBondTdimPortNotifications 2 }
```

```
-- G.Bond/TDIM Port group
```

```
gBondTdimPortConfTable OBJECT-TYPE
```

```
SYNTAX      SEQUENCE OF GBondTdimPortConfEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "Table for Configuration of G.Bond/TDIM ports. Entries in
    this table MUST be maintained in a persistent manner"
```

```
::= { gBondTdimPort 1 }
```

```
gBondTdimPortConfEntry OBJECT-TYPE
```

```
SYNTAX      GBondTdimPortConfEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "An entry in the G.Bond/TDIM Port Configuration table.
    Each entry represents an G.Bond/TDIM port indexed by the
    ifIndex. Additional configuration parameters are available
    via the gBondPortConfEntry of GBOND-MIB.
    Note that an G.Bond/TDIM port runs on top of a single or
    multiple BCE port(s), which are also indexed by ifIndex."
```

```
INDEX { ifIndex }
```

```
::= { gBondTdimPortConfTable 1 }
```

```
GBondTdimPortConfEntry ::=
```

```
SEQUENCE {
```

```
    gBondTdimFecAdminState      TruthValue,
```

```
    gBondTdimFecWordSize        Unsigned32,
```

```
    gBondTdimFecRedundancySize  Unsigned32,
```

```
    gBondTdimFecInterleaverType INTEGER,
```

```
    gBondTdimFecInterleaverDepth Unsigned32,
```

```
    gBondTdimAdminServices      GBondTdimServiceIndexList,
```

```
    gBondTdimServiceUpDownEnable TruthValue
```

```
}
```

```
gBondTdimFecAdminState OBJECT-TYPE
```

```
SYNTAX      TruthValue
```

```
MAX-ACCESS  read-write
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "A desired state of the OPTIONAL Forward Error Correction
    (FEC) function of the G.Bond/TDIM port."
```

```
    A value of 'false' indicates that the FEC function SHALL be
    disabled. A value of 'true' indicates that the FEC SHALL be
```


enabled, if supported by the G.Bond/TDIM port, as indicated by the gBondTdimFecSupported object.

The gBondTdimFecOperState object indicates current operational state of the FEC function.

For the GBS-R ports, the value of this object cannot be changed directly. This value may be changed as a result of writing operation on the gBondTdimFecSupported object of a remote GBS-C.

Modifications of this object MUST be performed when the link is Down.

Attempts to change this object MUST be rejected, if the link is Up or Initializing or if it is an GBS-R.

This object MUST be maintained in a persistent manner.

This object maps to TR-159/G.998.3 attribute aFECAdminState."

REFERENCE

"[[TR-159](#)] 5.5.4.5; [[G.998.3](#)] [Appendix II](#), B-X"
::= { gBondTdimPortConfEntry 1 }

gBondTdimFecWordSize OBJECT-TYPE

SYNTAX Unsigned32(0|20..255)

UNITS "octets"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"A FEC code word size in octets for the G.Bond/TDIM ports supporting FEC function.

This object is read-write for the GBS-C ports and read-only for the GBS-R.

A value of zero SHALL be returned if the FEC is disabled (via gBondTdimFecAdminState) or not supported.

Changing of the FEC code word size MUST be performed when the FEC enabled link is Down. Attempts to change this object MUST be rejected, if the link is Up or Initializing or the FEC function is disabled/not supported.

This object MUST be maintained in a persistent manner.

This object maps to TR-159/G.998.3 attribute aFECWordSize."

REFERENCE

"[[TR-159](#)] 5.5.4.7; [[G.998.3](#)] [Appendix II](#), B-XI"
::= { gBondTdimPortConfEntry 2 }

gBondTdimFecRedundancySize OBJECT-TYPE

SYNTAX Unsigned32(0|2|4|8|16|20)

UNITS "octets"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"A FEC redundancy word size in octets for the G.Bond/TDIM ports supporting FEC function.

This object is read-write for the GBS-C ports and read-only for the GBS-R.

A value of zero SHALL be returned if the FEC is disabled (via gBondTdimFecAdminState) or not supported.

Changing of the FEC redundancy word size MUST be performed when the FEC enabled link is Down. Attempts to change this object MUST be rejected, if the link is Up or Initializing or the FEC function is disabled/not supported.

This object MUST be maintained in a persistent manner.

This object maps to TR-159/G.998.3 attribute aFECRedundancySize."

REFERENCE

"[[TR-159](#)] 5.5.4.8; [[G.998.3](#)] [Appendix II](#), B-XII"

::= { gBondTdimPortConfEntry 3 }

gBondTdimFecInterleaverType OBJECT-TYPE

SYNTAX INTEGER {

none(0),

block(1),

convolution(2)

}

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"An Interleaver type for the G.Bond/TDIM ports supporting FEC function.

This object is read-write for the GBS-C ports and read-only for the GBS-R.

A value of none(0) SHALL be returned if the FEC is disabled (via gBondTdimFecAdminState) or not supported.

Changing of the Interleaver type MUST be performed when the FEC enabled link is Down. Attempts to change this object MUST

be rejected, if the link is Up or Initializing or the FEC function is disabled/not supported.

This object MUST be maintained in a persistent manner.

This object maps to TR-159/G.998.3 attribute aFECInterleaverType."

REFERENCE

"[[TR-159](#)] 5.5.4.9; [[G.998.3](#)] [Appendix II](#), B-XIII"
::= { gBondTdimPortConfEntry 4 }

gBondTdimFecInterleaverDepth OBJECT-TYPE

SYNTAX Unsigned32(0|1|2|3|4|6|8|12|16|24|32|48|96)

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"An Interleaver Depth for the G.Bond/TDIM ports supporting FEC function.

This object is read-write for the GBS-C ports and read-only for the GBS-R.

A value of zero SHALL be returned if the FEC is disabled (via gBondTdimFecAdminState) or not supported.

Changing of the Interleaver Depth MUST be performed when the FEC enabled link is Down. Attempts to change this object MUST be rejected, if the link is Up or Initializing or the FEC function is disabled/not supported.

This object MUST be maintained in a persistent manner.

This object maps to TR-159/G.998.3 attribute aFECInterleaverDepth."

REFERENCE

"[[TR-159](#)] 5.5.4.10; [[G.998.3](#)] [Appendix II](#), B-XIV"
::= { gBondTdimPortConfEntry 5 }

gBondTdimAdminServices OBJECT-TYPE

SYNTAX GBondTdimServiceIndexList

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Desired list of services for a G.Bond/TDIM port. This object is a list of pointers to entries in the gBondTdimServiceTable.

The value of this object is a continuous ordered list of up to 60 indices (gBondTdimServiceIdx) of the active services carried

via the G.Bond/TDIM link.

This object is writable and readable for the GBS-C ports.
It is irrelevant for the GBS-R ports - a zero-length octet string SHALL be returned on an attempt to read this object and an attempt to change this object MUST be rejected in this case.

Note that the current operational service list is available via the gBondTdimOperServiceTable object.

This object for a GBS-C port MAY be modified independently of the link's state, i.e. in- and out-of-service.
Attempts to set this object to a list with a member value that is not the value of the index for an active entry in the corresponding gBondTdimServiceTable table MUST be rejected.

This object MUST be maintained in a persistent manner."

REFERENCE

"[[G.998.3](#)] 10.2.3, 13.3.4.6-13.3.4.11"
::= { gBondTdimPortConfEntry 6 }

gBondTdimServiceUpDownEnable OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Indicates whether gBondTdimServiceUp and gBondTdimServiceDown notifications should be generated for this interface.

Value of true(1) indicates that the notifications are enabled.
Value of false(2) indicates that the notifications are disabled.

This object MUST be maintained in a persistent manner.

This object maps to the TR-159 attribute
aServiceUpDownEnable."

REFERENCE

"[[TR-159](#)] 5.5.5.6"
::= { gBondTdimPortConfEntry 7 }

gBondTdimPortCapabilityTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondTdimPortCapabilityEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Table for Capabilities of G.Bond/TDIM ports. Entries in this

table MUST be maintained in a persistent manner."
 ::= { gBondTdimPort 2 }

gBondTdimPortCapabilityEntry OBJECT-TYPE

SYNTAX GBondTdimPortCapabilityEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond/TDIM port Capability table.

Each entry represents an G.Bond/TDIM port indexed by the ifIndex. Additional capabilities are available via the gBondPortCapabilityEntry of GBOND-MIB.

Note that a G.Bond/TDIM port runs on top of a single or multiple BCE port(s), which are also indexed by ifIndex."

INDEX { ifIndex }

::= { gBondTdimPortCapabilityTable 1 }

GBondTdimPortCapabilityEntry ::=

SEQUENCE {

gBondTdimFecSupported TruthValue,

gBondTdimFecMaxWordSize Unsigned32,

gBondTdimFecMaxRedundancySize Unsigned32,

gBondTdimFecInterleaverTypeSupported INTEGER,

gBondTdimFecMaxInterleaverDepth Unsigned32

}

gBondTdimFecSupported OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"FEC and Interleaver Capability of the G.Bond/TDIM port.

This object has a value of true(1) when the port supports the FEC and Interleaver function.

A value of false(2) is returned when the port does not support the FEC and Interleaver function.

This object maps to the TR-159/G.998.3 attribute aFECSupported."

REFERENCE

"[[TR-159](#)] 5.5.4.4; [[G.998.3](#)] [Appendix II](#), B-VI"

::= { gBondTdimPortCapabilityEntry 1 }

gBondTdimFecMaxWordSize OBJECT-TYPE

SYNTAX Unsigned32(0|20..255)

UNITS "octets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A Maximum supported FEC code word size in octets for the G.Bond/TDIM ports with FEC function.

A value of zero SHALL be returned if the FEC is not supported.

This object partially maps to TR-159/G.998.3 attribute aFECWordSize"

REFERENCE

"[[TR-159](#)] 5.5.4.11; [[G.998.3](#)] [Appendix II](#), B-XI"
::= { gBondTdimPortCapabilityEntry 2 }

gBondTdimFecMaxRedundancySize OBJECT-TYPE

SYNTAX Unsigned32(0|2|4|8|16|20)

UNITS "octets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A Maximum supported FEC redundancy word size in octets for the G.Bond/TDIM ports with FEC function.

A value of zero SHALL be returned if the FEC is not supported.

This object maps to TR-159 attribute aFECMaxRedundancySize."

REFERENCE

"[[TR-159](#)] 5.5.4.12; [[G.998.3](#)] [Appendix II](#), B-XII"
::= { gBondTdimPortCapabilityEntry 3 }

gBondTdimFecInterleaverTypeSupported OBJECT-TYPE

SYNTAX INTEGER {

none(0),

block(1),

convolution(2),

blockConvolution(3)

}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Supported Interleaver types for the G.Bond/TDIM ports with FEC function.

Possible values are:

- none - the port does not support interleaving
- block - the port supports Block Interleaver
- convolution - the port supports Convolution Interleaver
- blockConvolution - the port supports both Block and Convolution Interleaver

This object partially maps to TR-159 attribute
aFECInterleaverTypesSupported."

REFERENCE

"[[TR-159](#)] 5.5.4.13; [[G.998.3](#)] [Appendix II](#), B-XIII"
::= { gBondTdimPortCapabilityEntry 4 }

gBondTdimFecMaxInterleaverDepth OBJECT-TYPE

SYNTAX Unsigned32(0|1|2|3|4|6|8|12|16|24|32|48|96)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A Maximum Interleaver Depth for the G.Bond/TDIM ports with
FEC function.

A value of zero SHALL be returned if the Interleaver is not
supported.

This object partially maps to TR-159 attribute
aFECMaxInterleaverDepth."

REFERENCE

"[[TR-159](#)] 5.5.4.14; [[G.998.3](#)] [Appendix II](#), B-XIV"
::= { gBondTdimPortCapabilityEntry 5 }

gBondTdimPortStatusTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondTdimPortStatusEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table provides overall status information of G.Bond
TDIM ports, complementing the generic status information from
the ifTable of IF-MIB and gBondFltStatus of GBOND-MIB.
Additional status information about connected BCEs is
available from the relevant line MIBs.

This table contains live data from the equipment. As such,
it is NOT persistent."

::= { gBondTdimPort 3 }

gBondTdimPortStatusEntry OBJECT-TYPE

SYNTAX GBondTdimPortStatusEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond/TDIM port Status table.
Each entry represents a G.Bond/TDIM port indexed by the
ifIndex.

Note that an G.Bond GBS port runs on top of a single

or multiple BCE port(s), which are also indexed by ifIndex."
 INDEX { ifIndex }
 ::= { gBondTdimPortStatusTable 1 }

gBondTdimPortStatusEntry ::=

```
SEQUENCE {
    gBondTdimFecOperState      TruthValue,
    gBondTdimFltStatus         BITS,
    gBondTdimCrc4Errors        Counter32,
    gBondTdimCrc6Errors        Counter32,
    gBondTdimCrc8Errors        Counter32
}
```

gBondTdimFecOperState OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only value, indicating current operational state of the OPTIONAL Forward Error Correction (FEC) function for the G.998.3 port.

A value of 'false' indicates that the FEC function is disabled. A value of 'true' indicates that the FEC function is enabled (and supported).

This object maps to TR-159 attribute aFECOperState."

REFERENCE

"[[TR-159](#)] 5.5.4.6"

::= { gBondTdimPortStatusEntry 1 }

gBondTdimFltStatus OBJECT-TYPE

SYNTAX BITS {

serviceDown(0),

wrongConfig(1)

}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"G.Bond/TDIM port Fault Status. This is a bitmap of possible conditions. The various bit positions are:

- serviceDown - at least one of the services defined for this aggregation group is down (due to low rate).
- wrongConfig - at least one BCE at the remote GBS-R is already connected to another GBS.

This object is intended to supplement ifOperStatus object in IF-MIB and gBondFltStatus in GBOND-MIB."

REFERENCE

"G.998.3 [Section 6.3](#);
IF-MIB, ifOperStatus; GBOND-MIB, gBondFltStatus"
::= { gBondTdimPortStatusEntry 2 }

gBondTdimCrc4Errors OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of CRC-4 errors (frame header error) on all pairs in the G.Bond/TDIM port. Simultaneous errors on M lines SHOULD be counted M times.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the value of ifCounterDiscontinuityTime, defined in IF-MIB.

This object maps to TR-159/G.998.3 attribute aCRC4Errors."

REFERENCE

"[[TR-159](#)] 5.5.4.1; [[G.998.3](#)] [Appendix II](#), B-VII"
::= { gBondTdimPortStatusEntry 3 }

gBondTdimCrc6Errors OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of CRC-6 errors (super-frame error) on all pairs in the G.Bond/TDIM port. Simultaneous errors on M lines SHOULD be counted 1 time.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the value of ifCounterDiscontinuityTime, defined in IF-MIB.

This object maps to TR-159/G.998.3 attribute aCRC6Errors."

REFERENCE

"[[TR-159](#)] 5.5.4.2; [[G.998.3](#)] [Appendix II](#), B-VIII"
::= { gBondTdimPortStatusEntry 4 }

gBondTdimCrc8Errors OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of CRC-8 errors (event/message error) on all pairs in the G.Bond/TDIM port. Simultaneous errors on M lines SHOULD be counted M times.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the value of ifCounterDiscontinuityTime, defined in IF-MIB.

This object maps to TR-159/G.998.3 attribute aCRC8Errors."

REFERENCE

"[[TR-159](#)] 5.5.4.3; [[G.998.3](#)] [Appendix II](#), B-IX"

::= { gBondTdimPortStatusEntry 5 }

gBondTdimOperServiceTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondTdimOperServiceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Table of the operational Services configured on a G.Bond/TDIM port. This table reflects current actual service configuration, set by the gBondTdimAdminServices object. The number of entries (services) in this table is therefore can vary between 0, when no services are configured, and 60, for the maximum number of services.

This table contains live data from the equipment. As such, it is NOT persistent."

::= { gBondTdimPort 4 }

gBondTdimOperServiceEntry OBJECT-TYPE

SYNTAX GBondTdimOperServiceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond/TDIM Port Operational Service table, containing the index of an active Service entry in the gBondTdimServiceTable. The entry is indexed by ifIndex, indicating corresponding G.Bond/TDIM port, and by gBondTdimServicePosition (1..60), indicating the corresponding service position in the G.Bond/TDIM frame."

INDEX { ifIndex, gBondTdimServicePosition }

::= { gBondTdimOperServiceTable 1 }

GBondTdimOperServiceEntry ::=

SEQUENCE {

gBondTdimServicePosition	GBondTdimServiceOrderIndex,
gBondTdimServiceOperIdx	GBondTdimServiceIndex,


```
    gBondTdimServiceOperState      INTEGER
  }
```

gBondTdimServicePosition OBJECT-TYPE

```
SYNTAX      GBondTdimServiceOrderIndex
MAX-ACCESS  read-only
STATUS      current
```

DESCRIPTION

"G.Bond/TDIM operational Service position - a unique index, indicating relative placement of the associated service pointed by gBondTdimServiceOperIdx, within the G.Bond/TDIM frame.

There can be up to 60 services defined over TDIM bonded facility. Services with lower indices have higher priority in case of bandwidth degradation.

The value of gBondTdimServicePosition for the first gBondTdimOperServiceEntry is always 1, incrementing sequentially for each consecutive entry, i.e. 2 for the second entry, 3 for the third etc.

This objects maps to TR-159/G.998.3 attribute aServiceID."

REFERENCE

"[[TR-159](#)] 5.5.5.1; [[G.998.3](#)] [Appendix II](#), C-I"

::= { gBondTdimOperServiceEntry 1 }

gBondTdimServiceOperIdx OBJECT-TYPE

```
SYNTAX      GBondTdimServiceIndex
MAX-ACCESS  read-only
STATUS      current
```

DESCRIPTION

"G.Bond/TDIM operational Service index - a read-only pointer to an existing entry in the gBondTdimServiceTable (value of gBondTdimServiceIdx), describing a particular service."

::= { gBondTdimOperServiceEntry 2 }

gBondTdimServiceOperState OBJECT-TYPE

```
SYNTAX      INTEGER {
    up(1),
    down(2)
}
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

DESCRIPTION

"G.Bond/TDIM Service Operational State.

Possible values are:

up - Service is up passing traffic.

down - Service is down, due to a variety of reasons, e.g. G.Bond/TDIM port is down, current link bandwidth is too low to support a particular service, etc.

This objects maps to TR-159 attribute aServiceOperState."

REFERENCE

"[[TR-159](#)] 5.5.5.5"

::= { gBondTdimOperServiceEntry 3 }

gBondTdimServiceTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondTdimServiceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Table of possible Services for a G.Bond/TDIM ports.

Entries in this table MUST be maintained in a persistent manner"

::= { gBondTdimPort 5 }

gBondTdimServiceEntry OBJECT-TYPE

SYNTAX GBondTdimServiceEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond/TDIM Port Service table, containing the management information applicable to a particular Service, indexed by the gBondTdimServiceIdx, on a G.Bond/TDIM port, indexed by the ifIndex."

INDEX { ifIndex, gBondTdimServiceIdx }

::= { gBondTdimServiceTable 1 }

GBondTdimServiceEntry ::=

SEQUENCE {

gBondTdimServiceIdx GBondTdimServiceIndex,

gBondTdimServiceIfIdx InterfaceIndex,

gBondTdimServiceType INTEGER,

gBondTdimServiceSize Unsigned32,

gBondTdimServiceRowStatus RowStatus

}

gBondTdimServiceIdx OBJECT-TYPE

SYNTAX GBondTdimServiceIndex

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"G.Bond/TDIM Service index - a unique index associated with

a particular service entry."
::= { gBondTdimServiceEntry 1 }

gBondTdimServiceIfIdx OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"This is a unique index within the ifTable. It represents the interface index of a service to be transmitted over the G.Bond/TDIM service instance.

This objects maps to TR-159 attribute aServiceIfIndex."

REFERENCE

"[[TR-159](#)] 5.5.5.2"

::= { gBondTdimServiceEntry 2 }

gBondTdimServiceType OBJECT-TYPE

SYNTAX INTEGER {

ds1(0),

e1(1),

nxds0(2),

nx0(3),

ds3(4),

e3(5),

clock(6),

ethernet(7),

atm(8),

gfpNoFCS(9),

gfp(10)

}

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"G.Bond/TDIM Service Type.

Possible values are:

ds1	- Clear Channel DS1 (synchronous)
e1	- Clear Channel E1 (synchronous)
nxds0	- Fractional DS1 (synchronous)
nx0	- Fractional E1 (synchronous)
ds3	- DS3 (synchronous)
e3	- E3 (synchronous)
clock	- Clock transfer (synchronous)
ethernet	- Ethernet (asynchronous)
atm	- ATM (asynchronous)
gfpNoFCS	- GFP encapsulated without FCS (asynchronous)
gfp	- GFP encapsulated with FCS (asynchronous)

For the GBS-R ports, the value of this object cannot be changed directly. This value may be changed as a result of writing operation on the gBondTdimServiceType object of a remote GBS-C.

Attempts to change this object MUST be rejected for the GBS-R ports.

This object MUST be maintained in a persistent manner.

This object maps to TR-159/G.998.3 attribute aServiceType."

REFERENCE

"[[TR-159](#)] 5.5.5.3; [[G.998.3](#)] [Appendix II](#), C-II"
::= { gBondTdimServiceEntry 3 }

gBondTdimServiceSize OBJECT-TYPE

SYNTAX Unsigned32(0|20..255)

UNITS "octets"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Service size in octets per bonding sub-block for a specific service identified by gBondTdimServiceIdx.

For TDM (synchronous) services with variable size e.g. fractional DS1/E1 - this object represents the number of DS0/E0 channels.

For asynchronous services (Ethernet, ATM, GFPnoFCS or GFP) - this object represents max. number of octets.

For non-fractional TDM services, i.e. DS1, E1, DS3, E3 and Clock, the value of this object MUST be 0.

A GET operation returns current value.

A SET operation, allowed on GBS-C ports, changes the service size to the indicated value. If the service type is a fixed rate synchronous service (gBondTdimServiceType is nxds0, nxe0, ds1, e1, ds3, e3 or clock), the operation MUST be rejected.

This object MUST be maintained in a persistent manner.

This object maps to TR-159/G.998.3 attribute aServiceSize."

REFERENCE

"[[TR-159](#)] 5.5.5.4; [[G.998.3](#)] [Appendix II](#), C-III"
::= { gBondTdimServiceEntry 4 }

gBondTdimServiceRowStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object controls the creation, modification, or deletion of the associated entry in the gBondTdimServiceTable per the semantics of RowStatus.

If an 'active' entry is referenced via gBondTdimServiceOperIdx or gBondTdimAdminServices instance or indexes a gBondTdimServicePerf*Entry, the entry MUST remain 'active'.

An 'active' entry SHALL NOT be modified. In order to modify an existing entry, it MUST be taken out of service (by setting this object to 'notInService'), modified, and set 'active' again."

::= { gBondTdimServiceEntry 5 }

-- Performance Monitoring group

gBondTdimPM OBJECT IDENTIFIER ::= { gBondTdimPort 6 }

gBondTdimPortPerfCurrTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondTdimPortPerfCurrEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains current Performance Monitoring information for a G.Bond/TDIM port. This table contains live data from the equipment and as such is NOT persistent."

::= { gBondTdimPM 1 }

gBondTdimPortPerfCurrEntry OBJECT-TYPE

SYNTAX GBondTdimPortPerfCurrEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond/TDIM Port PM table.
Each entry represents a G.Bond/TDIM port indexed by the ifIndex."

INDEX { ifIndex }

::= { gBondTdimPortPerfCurrTable 1 }

GBondTdimPortPerfCurrEntry ::=

SEQUENCE {

gBondTdimPortPerf15MinValidIntervals HCPperfValidIntervals,


```

gBondTdimPortPerf15MinInvalidIntervals HCPperfInvalidIntervals,
gBondTdimPortPerfCurr15MinTimeElapsed  HCPperfTimeElapsed,
gBondTdimPortPerfCurr15MinCrc4s         HCPperfCurrentCount,
gBondTdimPortPerfCurr15MinCrc6s         HCPperfCurrentCount,
gBondTdimPortPerfCurr15MinCrc8s         HCPperfCurrentCount,
gBondTdimPortPerf1DayValidIntervals     Unsigned32,
gBondTdimPortPerf1DayInvalidIntervals   Unsigned32,
gBondTdimPortPerfCurr1DayTimeElapsed     HCPperfTimeElapsed,
gBondTdimPortPerfCurr1DayCrc4s           HCPperfCurrentCount,
gBondTdimPortPerfCurr1DayCrc6s           HCPperfCurrentCount,
gBondTdimPortPerfCurr1DayCrc8s           HCPperfCurrentCount
}

```

gBondTdimPortPerf15MinValidIntervals OBJECT-TYPE

SYNTAX HCPperfValidIntervals

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 15-minute intervals for which the performance data was collected. The value of this object will be 96 or the maximum number of 15-minute history intervals collected by the implementation unless the measurement was (re-)started recently, in which case the value will be the number of complete 15 minutes intervals for which there are at least some data.

In certain cases it is possible that some intervals are unavailable. In this case, this object reports the maximum interval number for which data is available.

This object partially maps to the TR-159 attribute aGroupPerf15MinValidIntervals."

REFERENCE

"[[TR-159](#)] 5.5.1.32"

::= { gBondTdimPortPerfCurrEntry 1 }

gBondTdimPortPerf15MinInvalidIntervals OBJECT-TYPE

SYNTAX HCPperfInvalidIntervals

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 15-minute intervals for which the performance data was not always available. The value will typically be zero except in cases where the data for some intervals are not available.

This object partially maps to the TR-159 attribute aGroupPerf15MinInvalidIntervals."

REFERENCE

"[[TR-159](#)] 5.5.1.33"

::= { gBondTdimPortPerfCurrEntry 2 }

gBondTdimPortPerfCurr15MinTimeElapsed OBJECT-TYPE

SYNTAX HCPerfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds that have elapsed since the beginning of the current 15-minute performance interval.

This object partially maps to the TR-159 attribute aGroupPerfCurr15MinTimeElapsed."

REFERENCE

"[[TR-159](#)] 5.5.1.34"

::= { gBondTdimPortPerfCurrEntry 3 }

gBondTdimPortPerfCurr15MinCrc4s OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-4 errors (frame header errors) on all active pairs in the G.Bond/TDIM port during the current 15-minute performance interval.

Simultaneous errors on M lines SHOULD be counted M times.

Note that the total number of CRC-4 errors is indicated by the gBondTdimCrc4Errors object.

This object is inhibited during Severely Errored Seconds (SES) or Unavailable Seconds (UAS)."

REFERENCE

"[[TR-159](#)] 5.5.4.1"

::= { gBondTdimPortPerfCurrEntry 4 }

gBondTdimPortPerfCurr15MinCrc6s OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-6 errors (super-frame errors) on all active pairs in the G.Bond/TDIM port during the current 15-minute performance interval.

Simultaneous errors on M lines SHOULD be counted 1 time.

Note that the total number of CRC-6 errors is indicated by the gBondTdimCrc6Errors object.

This object is inhibited during Unavailable Seconds (UAS)."

REFERENCE

"[[TR-159](#)] 5.5.4.2"

::= { gBondTdimPortPerfCurrEntry 5}

gBondTdimPortPerfCurr15MinCrc8s OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-8 errors (event/message errors) on all active pairs in the G.Bond/TDIM port during the current 15-minute performance interval. Simultaneous errors on M lines SHOULD be counted M times.

Note that the total number of CRC-8 errors is indicated by the gBondTdimCrc8Errors object.

This object is inhibited during Unavailable Seconds (UAS)."

REFERENCE

"[[TR-159](#)] 5.5.4.3"

::= { gBondTdimPortPerfCurrEntry 6}

gBondTdimPortPerf1DayValidIntervals OBJECT-TYPE

SYNTAX Unsigned32 (0..7)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 1-day intervals for which data was collected. The value of this object will be 7 or the maximum number of 1-day history intervals collected by the implementation unless the measurement was (re-)started recently, in which case the value will be the number of complete 1-day intervals for which there are at least some data. In certain cases it is possible that some intervals are unavailable. In this case, this object reports the maximum interval number for which data is available."

REFERENCE

"[[TR-159](#)] 5.5.1.45"

::= { gBondTdimPortPerfCurrEntry 7 }

gBondTdimPortPerf1DayInvalidIntervals OBJECT-TYPE

SYNTAX Unsigned32 (0..7)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 1-day intervals for which data was not always available. The value will typically be zero except in

cases where the data for some intervals are not available."

REFERENCE

"[[TR-159](#)] 5.5.1.46"

::= { gBondTdimPortPerfCurrEntry 8 }

gBondTdimPortPerfCurr1DayTimeElapsed OBJECT-TYPE

SYNTAX HCPperfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds that have elapsed since the beginning of the current 1-day performance interval."

REFERENCE

"[[TR-159](#)] 5.5.1.47"

::= { gBondTdimPortPerfCurrEntry 9 }

gBondTdimPortPerfCurr1DayCrc4s OBJECT-TYPE

SYNTAX HCPperfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-4 errors on the G.Bond/TDIM port in the current 1-day performance interval."

This object is inhibited during Severely Errored Seconds (SES) and Unavailable Seconds (UAS)."

::= { gBondTdimPortPerfCurrEntry 10 }

gBondTdimPortPerfCurr1DayCrc6s OBJECT-TYPE

SYNTAX HCPperfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-6 errors on the G.Bond/TDIM port in the current 1-day performance interval."

This object is inhibited during Unavailable Seconds (UAS)."

::= { gBondTdimPortPerfCurrEntry 11 }

gBondTdimPortPerfCurr1DayCrc8s OBJECT-TYPE

SYNTAX HCPperfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-8 on the G.Bond/TDIM port in the current 1-day performance interval."

This object is inhibited during Unavailable Seconds (UAS)."


```
 ::= { gBondTdimPortPerfCurrEntry 12 }
```

```
-- Port PM history: 15-min buckets
```

```
gBondTdimPortPerf15MinTable OBJECT-TYPE
```

```
SYNTAX      SEQUENCE OF GBondTdimPortPerf15MinEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"This table contains historical 15-minute buckets of Performance
Monitoring information for a G.Bond/TDIM port (a row for each
15-minute interval, up to 96 intervals).
```

```
Entries in this table MUST be maintained in a persistent manner."
```

```
 ::= { gBondTdimPM 2 }
```

```
gBondTdimPortPerf15MinEntry OBJECT-TYPE
```

```
SYNTAX      GBondTdimPortPerf15MinEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"An entry in the G.Bond/TDIM Port historical 15-minute PM table.
Each entry represents performance monitoring data for a G.Bond
TDIM port, indexed by ifIndex, collected during a particular
15-minute interval, indexed by
gBondTdimPortPerf15MinIntervalIndex."
```

```
INDEX { ifIndex, gBondTdimPortPerf15MinIntervalIndex }
```

```
 ::= { gBondTdimPortPerf15MinTable 1 }
```

```
GBondTdimPortPerf15MinEntry ::=
```

```
SEQUENCE {
```

gBondTdimPortPerf15MinIntervalIndex	Unsigned32,
gBondTdimPortPerf15MinIntervalMoniTime	HCPperfTimeElapsed,
gBondTdimPortPerf15MinIntervalCrc4s	HCPperfIntervalCount,
gBondTdimPortPerf15MinIntervalCrc6s	HCPperfIntervalCount,
gBondTdimPortPerf15MinIntervalCrc8s	HCPperfIntervalCount,
gBondTdimPortPerf15MinIntervalValid	TruthValue

```
}
```

```
gBondTdimPortPerf15MinIntervalIndex OBJECT-TYPE
```

```
SYNTAX      Unsigned32 (1..96)
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"Performance Data Interval number. 1 is the most recent previous
interval; interval 96 is 24 hours ago.
Intervals 2..96 are OPTIONAL.
```

```
This object partially maps to the TR-159 attribute
```


aGroupPerf15MinIntervalNumber."

REFERENCE

"[[TR-159](#)] 5.5.1.57"

::= { gBondTdimPortPerf15MinEntry 1 }

gBondTdimPortPerf15MinIntervalMoniTime OBJECT-TYPE

SYNTAX HCPerfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds over which the performance data was actually monitored. This value will be the same as the interval duration (900 seconds), except in a situation where performance data could not be collected for any reason."

::= { gBondTdimPortPerf15MinEntry 2 }

gBondTdimPortPerf15MinIntervalCrc4s OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-4 errors on the G.Bond/TDIM port during the 15-minute performance history interval."

This object is inhibited during Severely Errored Seconds (SES) and Unavailable Seconds (UAS)."

::= { gBondTdimPortPerf15MinEntry 3 }

gBondTdimPortPerf15MinIntervalCrc6s OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-6 errors on the G.Bond/TDIM port during the 15-minute performance history interval."

This object is inhibited during Unavailable Seconds (UAS)."

::= { gBondTdimPortPerf15MinEntry 4 }

gBondTdimPortPerf15MinIntervalCrc8s OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-8 errors on the G.Bond/TDIM port during the current 15-minute performance interval."

This object is inhibited during Unavailable Seconds (UAS)."


```
::= { gBondTdimPortPerf15MinEntry 5 }
```

gBondTdimPortPerf15MinIntervalValid OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only object indicating whether or not this history bucket contains valid data. Valid bucket is reported as true(1) and invalid bucket as false(2).

If this history bucket is invalid the BTU-C MUST NOT produce notifications based upon the value of the counters in this bucket.

Note that an implementation may decide not to store invalid history buckets in its data base. In such case this object is not required as only valid history buckets are available while invalid history buckets are simply not in the data base.

This object partially maps to the TR-159 attribute aGroupPerf15MinIntervalValid."

REFERENCE

"[[TR-159](#)] 5.5.1.58"

```
::= { gBondTdimPortPerf15MinEntry 6 }
```

-- Port PM history: 1-day buckets

gBondTdimPortPerf1DayTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondTdimPortPerf1DayEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains historical 1-day buckets of Performance Monitoring information for a G.Bond/TDIM port (a row for each 1-day interval, up to 7 intervals).

Entries in this table MUST be maintained in a persistent manner."

```
::= { gBondTdimPM 3 }
```

gBondTdimPortPerf1DayEntry OBJECT-TYPE

SYNTAX GBondTdimPortPerf1DayEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond/TDIM port historical 1-day PM table.

Each entry represents performance monitoring data for such port, indexed by ifIndex, collected during a particular 1-day interval, indexed by gBondTdimPortPerf1DayIntervalIndex."

INDEX { ifIndex, gBondTdimPortPerf1DayIntervalIndex }

```
::= { gBondTdimPortPerf1DayTable 1 }
```


GBondTdimPortPerf1DayEntry ::=

```
SEQUENCE {
    gBondTdimPortPerf1DayIntervalIndex      Unsigned32,
    gBondTdimPortPerf1DayIntervalMoniTime    HCPperfTimeElapsed,
    gBondTdimPortPerf1DayIntervalCrc4s      HCPperfIntervalCount,
    gBondTdimPortPerf1DayIntervalCrc6s      HCPperfIntervalCount,
    gBondTdimPortPerf1DayIntervalCrc8s      HCPperfIntervalCount,
    gBondTdimPortPerf1DayIntervalValid      TruthValue
}
```

gBondTdimPortPerf1DayIntervalIndex OBJECT-TYPE

SYNTAX Unsigned32 (1..7)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Performance Data Interval number. 1 is the most recent previous interval; interval 7 is 7 days ago. Intervals 2..7 are OPTIONAL.

This object partially maps to the TR-159 attribute aGroupPerf1DayIntervalNumber."

REFERENCE

"[[TR-159](#)] 5.5.1.62"

::= { gBondTdimPortPerf1DayEntry 1 }

gBondTdimPortPerf1DayIntervalMoniTime OBJECT-TYPE

SYNTAX HCPperfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds over which the performance data was actually monitored. This value will be the same as the interval duration (86400 seconds), except in a situation where performance data could not be collected for any reason.

This object partially maps to the TR-159 attribute aGroupPerf1DayIntervalMoniSecs."

REFERENCE

"[[TR-159](#)] 5.5.1.64"

::= { gBondTdimPortPerf1DayEntry 2 }

gBondTdimPortPerf1DayIntervalCrc4s OBJECT-TYPE

SYNTAX HCPperfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-4 errors on the G.Bond/TDIM port during the 1-day performance history interval.

This object is inhibited during Severely Errored Seconds (SES) and Unavailable Seconds (UAS)."
::= { gBondTdimPortPerf1DayEntry 3 }

gBondTdimPortPerf1DayIntervalCrc6s OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-6 errors on the G.Bond/TDIM port during the 1-day performance history interval.

This object is inhibited during Unavailable Seconds (UAS)."
::= { gBondTdimPortPerf1DayEntry 4 }

gBondTdimPortPerf1DayIntervalCrc8s OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of CRC-6 errors on the G.Bond/TDIM port during the current 1-day performance interval.

This object is inhibited during Unavailable Seconds (UAS)."
::= { gBondTdimPortPerf1DayEntry 5 }

gBondTdimPortPerf1DayIntervalValid OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only object indicating whether or not this history bucket contains valid data. Valid bucket is reported as true(1) and invalid bucket as false(2).

If this history bucket is invalid the BTU-C MUST NOT produce notifications based upon the value of the counters in this bucket.

Note that an implementation may decide not to store invalid history buckets in its data base. In such case this object is not required as only valid history buckets are available while invalid history buckets are simply not in the data base.

This object partially maps to the TR-159 attribute aGroupPerf1DayIntervalValid."

REFERENCE

"[[TR-159](#)] 5.5.1.63"

::= { gBondTdimPortPerf1DayEntry 6 }

-- Services PM

gBondTdimServicePerfCurrTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondTdimServicePerfCurrEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains current Performance Monitoring information for the services of a G.Bond/TDIM port.

This table contains live data from the equipment and as such is NOT persistent."

::= { gBondTdimPM 4 }

gBondTdimServicePerfCurrEntry OBJECT-TYPE

SYNTAX GBondTdimServicePerfCurrEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond/TDIM Services PM table.

Each entry represents a service, indexed by the gBondTdimServiceIdx, in a G.Bond/TDIM port, indexed by the ifIndex."

INDEX { ifIndex, gBondTdimServiceIdx }

::= { gBondTdimServicePerfCurrTable 1 }

GBondTdimServicePerfCurrEntry ::=

SEQUENCE {

gBondTdimServicePerf15MinValidIntervals HCPperfValidIntervals,

gBondTdimServicePerf15MinInvalidIntervals HCPperfInvalidIntervals,

gBondTdimServicePerfCurr15MinTimeElapsed HCPperfTimeElapsed,

gBondTdimServicePerfCurr15MinDowns HCPperfCurrentCount,

gBondTdimServicePerf1DayValidIntervals Unsigned32,

gBondTdimServicePerf1DayInvalidIntervals Unsigned32,

gBondTdimServicePerfCurr1DayTimeElapsed HCPperfTimeElapsed,

gBondTdimServicePerfCurr1DayDowns HCPperfCurrentCount

}

gBondTdimServicePerf15MinValidIntervals OBJECT-TYPE

SYNTAX HCPperfValidIntervals

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 15-minute intervals for which the performance data was collected. The value of this object will be 96 or the maximum number of 15-minute history intervals collected by the implementation unless the measurement was (re-)started recently, in which case the value will be the number of complete 15 minutes intervals for which there are at

least some data.

In certain cases it is possible that some intervals are unavailable. In this case, this object reports the maximum interval number for which data is available.

This object partially maps to the TR-159 attribute aGroupPerf15MinValidIntervals."

REFERENCE

"[[TR-159](#)] 5.5.1.32"

::= { gBondTdimServicePerfCurrEntry 1 }

gBondTdimServicePerf15MinInvalidIntervals OBJECT-TYPE

SYNTAX HCPerfInvalidIntervals

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 15-minute intervals for which the performance data was not always available. The value will typically be zero except in cases where the data for some intervals are not available.

This object partially maps to the TR-159 attribute aGroupPerf15MinInvalidIntervals."

REFERENCE

"[[TR-159](#)] 5.5.1.33"

::= { gBondTdimServicePerfCurrEntry 2 }

gBondTdimServicePerfCurr15MinTimeElapsed OBJECT-TYPE

SYNTAX HCPerfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds that have elapsed since the beginning of the current 15-minute performance interval.

This object partially maps to the TR-159 attribute aGroupPerfCurr15MinTimeElapsed."

REFERENCE

"[[TR-159](#)] 5.5.1.34"

::= { gBondTdimServicePerfCurrEntry 3 }

gBondTdimServicePerfCurr15MinDowns OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds in the current 15-minute performance interval, during which a particular TDIM

Service was 'down', as indicated by the gBondTdimServiceOperState object.

This object is inhibited during Unavailable Seconds (UAS)."
::= { gBondTdimServicePerfCurrEntry 4 }

gBondTdimServicePerf1DayValidIntervals OBJECT-TYPE

SYNTAX Unsigned32 (0..7)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 1-day performance history intervals for which the data was collected. The value of this object will be 7 or the maximum number of 1-day history intervals collected by the implementation unless the measurement was (re-)started recently, in which case the value will be the number of complete 1-day intervals for which there are at least some data. In certain cases it is possible that some intervals are unavailable. In this case, this object reports the maximum interval number for which data is available."

REFERENCE

"[[TR-159](#)] 5.5.1.45"

::= { gBondTdimServicePerfCurrEntry 5 }

gBondTdimServicePerf1DayInvalidIntervals OBJECT-TYPE

SYNTAX Unsigned32 (0..7)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only number of 1-day performance history intervals for which the performance data was not always available. The value will typically be zero except in cases where the data for some intervals are not available."

REFERENCE

"[[TR-159](#)] 5.5.1.46"

::= { gBondTdimServicePerfCurrEntry 6 }

gBondTdimServicePerfCurr1DayTimeElapsed OBJECT-TYPE

SYNTAX HCPerfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds that have elapsed since the beginning of the current 1-day performance interval."

REFERENCE

"[[TR-159](#)] 5.5.1.47"

::= { gBondTdimServicePerfCurrEntry 7 }

gBondTdimServicePerfCurr1DayDowns OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds in the current 1-day performance interval, during which a particular TDIM Service was 'down', as indicated by the gBondTdimServiceOperState object.

This object is inhibited during Unavailable Seconds (UAS)."

```
::= { gBondTdimServicePerfCurrEntry 8 }
```

-- Service PM history: 15-min buckets

gBondTdimServicePerf15MinTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondTdimServicePerf15MinEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains historical 15-minute buckets of Performance Monitoring information for the Services of a G.Bond/TDIM port (a multi-dimensional row for each 15-minute interval, up to 96 intervals).

Entries in this table MUST be maintained in a persistent manner."

```
::= { gBondTdimPM 5 }
```

gBondTdimServicePerf15MinEntry OBJECT-TYPE

SYNTAX GBondTdimServicePerf15MinEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond/TDIM Services historical 15-minute PM table.

Each entry represents performance monitoring data for a particular Service, indexed by gBondTdimServiceIdx, in a G.Bond TDIM port, indexed by ifIndex, collected during a particular 15-minute interval, indexed by gBondTdimServicePerf15MinIntervalIndex."

```
INDEX { ifIndex, gBondTdimServiceIdx,
        gBondTdimServicePerf15MinIntervalIndex }
```

```
::= { gBondTdimServicePerf15MinTable 1 }
```

GBondTdimServicePerf15MinEntry ::=

```
SEQUENCE {
```

```
    gBondTdimServicePerf15MinIntervalIndex    Unsigned32,
    gBondTdimServicePerf15MinIntervalMoniTime  HCPerfTimeElapsed,
    gBondTdimServicePerf15MinIntervalDowns     HCPerfIntervalCount,
```



```
    gBondTdimServicePerf15MinIntervalValid    TruthValue
  }
```

gBondTdimServicePerf15MinIntervalIndex OBJECT-TYPE

SYNTAX Unsigned32 (1..96)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Performance Data Interval number. 1 is the most recent previous interval; interval 96 is 24 hours ago. Intervals 2..96 are OPTIONAL.

This object partially maps to the TR-159 attribute aGroupPerf15MinIntervalNumber."

REFERENCE

"[[TR-159](#)] 5.5.1.57"

::= { gBondTdimServicePerf15MinEntry 1 }

gBondTdimServicePerf15MinIntervalMoniTime OBJECT-TYPE

SYNTAX HCPperfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds over which the performance data was actually monitored. This value will be the same as the interval duration (900 seconds), except in a situation where performance data could not be collected for any reason."

::= { gBondTdimServicePerf15MinEntry 2 }

gBondTdimServicePerf15MinIntervalDowns OBJECT-TYPE

SYNTAX HCPperfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds in the 15-minute performance history interval, during which a particular TDIM Service was 'down', as indicated by the gBondTdimServiceOperState object.

This object is inhibited during Unavailable Seconds (UAS)."

::= { gBondTdimServicePerf15MinEntry 3 }

gBondTdimServicePerf15MinIntervalValid OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only object indicating whether or not this history bucket contains valid data. Valid bucket is reported as true(1)

and invalid bucket as false(2).

If this history bucket is invalid the BTU-C MUST NOT produce notifications based upon the value of the counters in this bucket.

Note that an implementation may decide not to store invalid history buckets in its data base. In such case this object is not required as only valid history buckets are available while invalid history buckets are simply not in the data base.

This object partially maps to the TR-159 attribute
aGroupPerf15MinIntervalValid."

REFERENCE

"[[TR-159](#)] 5.5.1.58"

::= { gBondTdimServicePerf15MinEntry 4 }

-- Service PM history: 1-day buckets

gBondTdimServicePerf1DayTable OBJECT-TYPE

SYNTAX SEQUENCE OF GBondTdimServicePerf1DayEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains historical 1-day buckets of Performance Monitoring information for the Services of a G.Bond/TDIM port (a multi-dimensional row for each 1-day interval, up to 7 intervals).

Entries in this table MUST be maintained in a persistent manner."

::= { gBondTdimPM 6 }

gBondTdimServicePerf1DayEntry OBJECT-TYPE

SYNTAX GBondTdimServicePerf1DayEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the G.Bond/TDIM Service historical 1-day PM table.

Each entry represents performance monitoring data for a particular Service, indexed by gBondTdimServiceIdx, defined in a G.Bond/TDIM port, indexed by ifIndex, collected during a particular 1-day interval, indexed by gBondTdimServicePerf1DayIntervalIndex."

INDEX { ifIndex, gBondTdimServiceIdx,
gBondTdimServicePerf1DayIntervalIndex }

::= { gBondTdimServicePerf1DayTable 1 }

GBondTdimServicePerf1DayEntry ::=

SEQUENCE {

gBondTdimServicePerf1DayIntervalIndex Unsigned32,

gBondTdimServicePerf1DayIntervalMoniTime HCPperfTimeElapsed,


```
gBondTdimServicePerf1DayIntervalDowns      HCPperfIntervalCount,  
gBondTdimServicePerf1DayIntervalValid      TruthValue  
}
```

gBondTdimServicePerf1DayIntervalIndex OBJECT-TYPE

SYNTAX Unsigned32 (1..7)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Performance Data Interval number. 1 is the most recent previous interval; interval 7 is 7 days ago. Intervals 2..7 are OPTIONAL.

This object partially maps to the TR-159 attribute aGroupPerf1DayIntervalNumber."

REFERENCE

"[[TR-159](#)] 5.5.1.62"

::= { gBondTdimServicePerf1DayEntry 1 }

gBondTdimServicePerf1DayIntervalMoniTime OBJECT-TYPE

SYNTAX HCPperfTimeElapsed

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds over which the performance data was actually monitored. This value will be the same as the interval duration (86400 seconds), except in a situation where performance data could not be collected for any reason.

This object partially maps to the TR-159 attribute aGroupPerf1DayIntervalMoniSecs."

REFERENCE

"[[TR-159](#)] 5.5.1.64"

::= { gBondTdimServicePerf1DayEntry 2 }

gBondTdimServicePerf1DayIntervalDowns OBJECT-TYPE

SYNTAX HCPperfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only count of seconds in the 1-day performance history interval, during which a particular TDIM Service was 'down', as indicated by the gBondTdimServiceOperState object.

This object is inhibited during Unavailable Seconds (UAS)."

::= { gBondTdimServicePerf1DayEntry 3 }

gBondTdimServicePerf1DayIntervalValid OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A read-only object indicating whether or not this history bucket contains valid data. Valid bucket is reported as true(1) and invalid bucket as false(2).

If this history bucket is invalid the BTU-C MUST NOT produce notifications based upon the value of the counters in this bucket.

Note that an implementation may decide not to store invalid history buckets in its data base. In such case this object is not required as only valid history buckets are available while invalid history buckets are simply not in the data base.

This object partially maps to the TR-159 attribute aGroupPerf1DayIntervalValid."

REFERENCE

"[[TR-159](#)] 5.5.1.63"

::= { gBondTdimServicePerf1DayEntry 4 }

--

-- Conformance Statements

--

gBondTdimGroups OBJECT IDENTIFIER

::= { gBondTdimConformance 1 }

gBondTdimCompliances OBJECT IDENTIFIER

::= { gBondTdimConformance 2 }

-- Object Groups

gBondTdimBasicGroup OBJECT-GROUP

OBJECTS {

gBondTdimAdminServices,
gBondTdimCrc4Errors,
gBondTdimCrc6Errors,
gBondTdimCrc8Errors,
gBondTdimFecSupported,
gBondTdimServicePosition,
gBondTdimServiceOperIdx,
gBondTdimServiceOperState,
gBondTdimServiceIfIdx,
gBondTdimServiceType,
gBondTdimServiceSize,
gBondTdimServiceRowStatus,


```
    gBondTdimFltStatus
  }
  STATUS      current
  DESCRIPTION
    "A collection of objects representing management information
    for G.Bond/TDIM ports."
  ::= { gBondTdimGroups 1 }

gBondTdimFecGroup OBJECT-GROUP
  OBJECTS {
    gBondTdimFecSupported,
    gBondTdimFecAdminState,
    gBondTdimFecOperState,
    gBondTdimFecWordSize,
    gBondTdimFecRedundancySize,
    gBondTdimFecInterleaverType,
    gBondTdimFecInterleaverDepth,
    gBondTdimFecMaxWordSize,
    gBondTdimFecMaxRedundancySize,
    gBondTdimFecInterleaverTypeSupported,
    gBondTdimFecMaxInterleaverDepth
  }
  STATUS      current
  DESCRIPTION
    "A collection of objects supporting OPTIONAL Forward Error
    Correction (FEC) and Interleaver function in G.Bond/TDIM
    ports."
  ::= { gBondTdimGroups 2 }

gBondTdimAlarmConfGroup OBJECT-GROUP
  OBJECTS {
    gBondTdimServiceUpDownEnable
  }
  STATUS      current
  DESCRIPTION
    "A collection of objects required for configuration of alarm
    thresholds and notifications in G.Bond/TDIM ports."
  ::= { gBondTdimGroups 3 }

gBondTdimNotificationGroup NOTIFICATION-GROUP
  NOTIFICATIONS {
    gBondTdimServiceUp,
    gBondTdimServiceDown
  }
  STATUS      current
  DESCRIPTION
    "This group supports notifications of significant conditions
    associated with G.Bond/TDIM ports."
```



```
::= { gBondTdimGroups 4 }
```

```
gBondTdimPerfCurrGroup OBJECT-GROUP
```

```
OBJECTS {
    gBondTdimPortPerf15MinValidIntervals,
    gBondTdimPortPerf15MinInvalidIntervals,
    gBondTdimPortPerfCurr15MinTimeElapsed,
    gBondTdimPortPerfCurr15MinCrc4s,
    gBondTdimPortPerfCurr15MinCrc6s,
    gBondTdimPortPerfCurr15MinCrc8s,
    gBondTdimPortPerf1DayValidIntervals,
    gBondTdimPortPerf1DayInvalidIntervals,
    gBondTdimPortPerfCurr1DayTimeElapsed,
    gBondTdimPortPerfCurr1DayCrc4s,
    gBondTdimPortPerfCurr1DayCrc6s,
    gBondTdimPortPerfCurr1DayCrc8s,
    gBondTdimServicePerf15MinValidIntervals,
    gBondTdimServicePerf15MinInvalidIntervals,
    gBondTdimServicePerfCurr15MinTimeElapsed,
    gBondTdimServicePerfCurr15MinDowns,
    gBondTdimServicePerf1DayValidIntervals,
    gBondTdimServicePerf1DayInvalidIntervals,
    gBondTdimServicePerfCurr1DayTimeElapsed,
    gBondTdimServicePerfCurr1DayDowns
}
```

```
STATUS          current
```

```
DESCRIPTION
```

```
"A collection of objects supporting OPTIONAL current Performance
Monitoring information for G.Bond/TDIM ports."
```

```
::= { gBondTdimGroups 5 }
```

```
gBondTdimPerf15MinGroup OBJECT-GROUP
```

```
OBJECTS {
    gBondTdimPortPerf15MinIntervalMoniTime,
    gBondTdimPortPerf15MinIntervalCrc4s,
    gBondTdimPortPerf15MinIntervalCrc6s,
    gBondTdimPortPerf15MinIntervalCrc8s,
    gBondTdimPortPerf15MinIntervalValid,
    gBondTdimServicePerf15MinIntervalMoniTime,
    gBondTdimServicePerf15MinIntervalDowns,
    gBondTdimServicePerf15MinIntervalValid
}
```

```
STATUS          current
```

```
DESCRIPTION
```

```
"A collection of objects supporting OPTIONAL historical
Performance Monitoring information for G.Bond/TDIM ports, during
previous 15-minute intervals ."
```

```
::= { gBondTdimGroups 6 }
```


gBondTdimPerf1DayGroup OBJECT-GROUP

OBJECTS {

gBondTdimPortPerf1DayIntervalMoniTime,
gBondTdimPortPerf1DayIntervalCrc4s,
gBondTdimPortPerf1DayIntervalCrc6s,
gBondTdimPortPerf1DayIntervalCrc8s,
gBondTdimPortPerf1DayIntervalValid,
gBondTdimServicePerf1DayIntervalMoniTime,
gBondTdimServicePerf1DayIntervalDowns,
gBondTdimServicePerf1DayIntervalValid

}

STATUS current

DESCRIPTION

"A collection of objects supporting OPTIONAL historical
Performance Monitoring information for G.Bond/TDIM ports, during
previous 1-day intervals ."

::= { gBondTdimGroups 7 }

-- Compliance Statements

gBondTdimCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"The compliance statement for G.Bond/TDIM interfaces.
Compliance with the following external compliance statements
is REQUIRED:

MIB Module	Compliance Statement
IF-MIB	ifCompliance3
GBOND-MIB	gBondCompliance"

MODULE -- this module

MANDATORY-GROUPS {

gBondTdimBasicGroup,
gBondTdimAlarmConfGroup,
gBondTdimNotificationGroup

}

GROUP gBondTdimFecGroup

DESCRIPTION

"Support for this group is only required for implementations
supporting G.Bond FEC and Interleaver function."

GROUP gBondTdimPerfCurrGroup

DESCRIPTION

"Support for this group is only required for implementations
supporting Performance Monitoring."


```
GROUP          gBondTdimPerf15MinGroup
```

```
DESCRIPTION
```

```
"Support for this group is only required for implementations
supporting historical Performance Monitoring."
```

```
GROUP          gBondTdimPerf1DayGroup
```

```
DESCRIPTION
```

```
"Support for this group is only required for implementations
supporting historical Performance Monitoring."
```

```
::= { gBondTdimCompliances 1 }
```

```
END
```

7. Security Considerations

There is a number of managed objects defined in the GBOND-TDIM-MIB module that have a MAX-ACCESS clause of read-write or read-create. Most objects are writable only when the link is down. Writing to these objects can have potentially disruptive effects on network operation, for example:

- o Changing of gBondTdimAdminServices object MAY lead to a potential service disruption, by changing a particular service' position (therefore changing its drop priority) or even removing the service from the link altogether.
- o Changing of gBondTdimServiceTable configuration parameters (e.g. gBondTdimServiceType or gBondTdimServiceSize) MAY lead to a potential service impairment, for example a TDM service would be dropped if there is not enough actual bandwidth on the bonded link to support this service.
- o Changing of gBondTdimPortConfTable configuration parameters (e.g. gBondTdimFecAdminState) MAY lead to anything from link quality and rate degradation to a complete link initialization failure.

The user of the GBOND-TDIM-MIB module must therefore be aware that support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

The readable objects in the GBOND-TDIM-MIB module (i.e., those with MAX-ACCESS other than not-accessible) may be considered sensitive in some environments since, collectively, they provide information about the performance of network interfaces and can reveal some aspects of their configuration.

In such environments it is important to control also GET and NOTIFY access to these objects and possibly even to encrypt their values

when sending them over the network via SNMP.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

[8.](#) IANA Considerations

An object identifier for gBondTdimMIB MODULE-IDENTITY SHALL be allocated by IANA [[1](#)] in the MIB-2 transmission sub-tree, before this document is published as an RFC.

[9.](#) Acknowledgments

This document was produced by the [[ADSLMIB](#)] working group.

[10.](#) References

[10.1.](#) Normative References

- | | |
|------------------------------|--|
| [G.998.3] | ITU-T, "Multi-pair bonding using time-division inverse multiplexing", ITU-T Recommendation G.998.3, January 2005, < http://www.itu.int/rec/T-REC-G.998.3/en >. |
| [I-D.ietf-adslmib-gbond-mib] | Beili, E. and M. Morgenstern, "xDSL multi-pair bonding (G.Bond) MIB", draft-ietf-adslmib-gbond-mib-07 (work in progress), May 2011. |
| [RFC2119] | Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", |

[BCP 14](#), [RFC 2119](#), March 1997.

- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), June 2000.
- [RFC3705] Ray, B. and R. Abbi, "High Capacity Textual Conventions for MIB Modules Using Performance History Based on 15 Minute Intervals", [RFC 3705](#), February 2004.
- [TR-159] Beili, E. and M. Morgenstern, "Management Framework for xDSL Bonding", Broadband Forum technical report TR-159, December 2008.

[10.2.](#) Informative References

- [ADSLMIB] IETF, "ADSL MIB (adslmib) Charter", <<http://www.ietf.org/html.charters/adslmib-charter.html>>.
- [G.704] ITU-T, "Synchronous frame structures used at 1544, 6312, 2048, 8448 and 44736 Kbit/s hierarchical levels.", ITU-T Recommendation G.704, October 1998, <<http://www.itu.int/rec/T-REC-G.704/en>>.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and

Applicability Statements for Internet-
Standard Management Framework",
[RFC 3410](#), December 2002.

[RFC3593]

Tesink, K., "Textual Conventions for
MIB Modules Using Performance History
Based on 15 Minute Intervals",
[RFC 3593](#), September 2003.

[RFC4181]

Heard, C., "Guidelines for Authors and
Reviewers of MIB Documents", [BCP 111](#),
[RFC 4181](#), September 2005.

URIs

[1] <<http://www.iana.org/>>

Author's Address

Edward Beili
Actelis Networks
25 Bazel St.
Petach-Tikva 49103
Israel

Phone: +972-3-924-3491
EMail: edward.beili@actelis.com

