

ALTO WG
Internet-Draft
Intended status: Standards Track
Expires: December 31, 2018

W. Roome
Nokia Bell Labs
S. Chen
Tongji University
S. Randriamasy
Nokia Bell Labs
Y. Yang
Yale University
J. Zhang
Tongji University
June 29, 2018

Unified Properties for the ALTO Protocol
draft-ietf-alto-unified-props-new-04

Abstract

This document extends the Application-Layer Traffic Optimization (ALTO) Protocol [[RFC7285](#)] by generalizing the concept of "endpoint properties" to domains of other entities, and by presenting those properties as maps, similar to the network and cost maps in ALTO.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 31, 2018.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Definitions and Concepts	4
2.1.	Entity	4
2.2.	Entity Domain	5
2.3.	Domain Name	5
2.4.	Entity Address	5
2.5.	Property Name	6
2.6.	Hierarchy and Inheritance	6
2.7.	Relationship with Other ALTO Resources	6
3.	Entity Domains	7
3.1.	Internet Address Domains	7
3.1.1.	IPv4 Domain	7
3.1.2.	IPv6 Domain	8
3.1.3.	Hierarchy and Inheritance of ipv4/ipv6 Domains	8
3.1.4.	Relationship to Network Maps	9
3.2.	PID Domain	10
3.2.1.	Domain Name	10
3.2.2.	Domain-Specific Entity Addresses	10
3.2.3.	Hierarchy and Inheritance	10
3.2.4.	Relationship To Internet Addresses Domains	10
3.3.	Internet Address Properties vs. PID Properties	10
4.	Property Map Resource	11
4.1.	Media Type	11
4.2.	HTTP Method	11
4.3.	Accept Input Parameters	11
4.4.	Capabilities	11
4.5.	Uses	12
4.6.	Response	12
5.	Filtered Property Map Resource	13
5.1.	Media Type	13
5.2.	HTTP Method	13

5.3.	Accept Input Parameters	13
5.4.	Capabilities	14
5.5.	Uses	14
5.6.	Response	14
6.	Impact on Legacy ALTO Servers and ALTO Clients	14
6.1.	Impact on Endpoint Property Service	15
6.2.	Impact on Resource-Specific Properties	15
6.3.	Impact on the pid Property	15
6.4.	Impact on Other Properties	16
7.	Examples	16
7.1.	Network Map	16
7.2.	Property Definitions	16
7.3.	Information Resource Directory (IRD)	16
7.4.	Property Map Example	18
7.5.	Filtered Property Map Example #1	19
7.6.	Filtered Property Map Example #2	20
7.7.	Filtered Property Map Example #3	21
7.8.	Filtered Property Map Example #4	22
8.	Security Considerations	24
9.	IANA Considerations	24
9.1.	application/alto-* Media Types	24
9.2.	ALTO Entity Domain Registry	25
9.2.1.	Consistency Procedure between ALTO Address Type Registry and ALTO Entity Domain Registry	26
9.2.2.	ALTO Entity Domain Registration Process	27
9.3.	ALTO Endpoint Property Type Registry	28
10.	References	28
10.1.	Normative References	28
10.2.	Informative References	29
	Authors' Addresses	29

1. Introduction

The ALTO protocol [[RFC7285](#)] introduced the concept of "properties" attached to "endpoint addresses", and defined the Endpoint Property Service (EPS) to allow clients to retrieve those properties. While useful, the EPS, as defined in [[RFC7285](#)], has at least two limitations.

First, it only allows properties to be associated with a particular domain of entities, namely individual IP addresses. It is reasonable to think that collections of endpoints, as defined by CIDRs [[RFC4632](#)] or PIDs, may also have properties. The EPS cannot be extended to new entity domains. Instead, new services, with new request and response messages, would have to be defined for each new entity domain.

Second, the EPS is only defined as a POST-mode service. Clients must request the properties for an explicit set of addresses. By

contrast, [\[RFC7285\]](#) defines a GET-mode Cost Map resource which returns all available costs, so a client can get a full set of costs once, and then processes costs lookup without querying the ALTO server. [\[RFC7285\]](#) does not define an equivalent service for endpoint properties. At first a map might seem impractical, because it could require enumerating the property value for every possible endpoint. But in practice, it is highly unlikely that properties will be defined for every address. It is much more likely that properties will only be defined for a subset of addresses, and that subset would be small enough to enumerate. This is particularly true if blocks of addresses with a common prefix (e.g., a CIDR) have the same value for a property. Furthermore, entities in other domains may very well be enumerable.

This document proposes a new approach to retrieve ALTO properties. Specifically, it defines two new resource types, namely Property Maps (see [Section 4](#)) and Filtered Property Maps (see [Section 5](#)). The former are GET-mode resources which return the property values for all entities in a domain, and are analogous to the ALTO's Network Maps and Cost Maps. The latter are POST-mode resources which return the values for a set of properties and entities requested by the client, and are analogous to the ALTO's Filtered Network Maps and Filtered Cost Maps.

Additionally, this document introduces ALTO Entity Domains, where entities extend the concept of endpoints to objects that may be endpoints as defined in [\[RFC7285\]](#) but also, for example, PIDs, Abstract Network Elements as defined in [\[I-D.ietf-alto-path-vector\]](#) or cells. As a consequence, ALTO Entity Domains are a super-set of ALTO Address Types and their relation is specified in [Section 9.2.1](#).

Entity domains and property names are extensible. New entity domains can be defined without revising the messages defined in this document, in the same way that new cost metrics and new endpoint properties can be defined without revising the messages defined by the ALTO protocol.

This proposal would subsume the Endpoint Property Service defined in [\[RFC7285\]](#), although that service may be retained for legacy clients (see [Section 6](#)).

2. Definitions and Concepts

2.1. Entity

The entity is an extended concept of the endpoint defined in [Section 2.1 of \[RFC7285\]](#). An entity is an object with a (possibly

empty) set of properties. Every entity is in a domain, such as the IPv4 and IPv6 domains, and has a unique address.

2.2. Entity Domain

An entity domain is a family of entities. Two examples are the Internet address and PID domain (see [Section 3.1](#) and [Section 3.2](#)) that this document will define.

2.3. Domain Name

Each entity domain has a unique name. A domain name MUST be no more than 32 characters, and MUST NOT contain characters other than US-ASCII alphanumeric characters (U+0030-U+0039, U+0041-U+005A, and U+0061-U+007A), hyphen ("-", U+002D), and low line ("_", U+005F). For example, the names "ipv4" and "ipv6" identify objects in the Internet address domain (see [Section 3.1](#)).

The type `DomainName` is used in this document to denote a JSON string with a domain name in this format.

Domain names MUST be registered with the IANA, and the format of the entity addresses in that entity domain, as well as any hierarchical or inheritance rules for those entities, MUST be specified at the same time.

2.4. Entity Address

Each entity has a unique address of the format:

`domain-name : domain-specific-entity-address`

Examples from the IP domain include individual addresses such as "ipv4:192.0.2.14" and "ipv6:2001:db8::12", as well as address blocks such as "ipv4:192.0.2.0/26" and "ipv6:2001:db8::1/48".

The type `EntityAddr` is used in this document to denote a JSON string with an entity address in this format.

The format of the second part of an entity address depends on the entity domain, and MUST be specified when registering a new entity domain. Addresses MAY be hierarchical, and properties MAY be inherited based on that hierarchy. Again, the rules defining any hierarchy or inheritance MUST be defined when the entity domain is registered.

Note that an entity address MAY have different textual representations, for a given entity domain. For example, the strings

"ipv6:2001:db8::1" and "ipv6:2001:db8:0:0:0:0:0:1" refer to the same entity.

2.5. Property Name

The space of property names associated with entities defined by this document is the same as, and is shared with, the endpoint property names defined by [RFC7285]. Thus entity property names are as defined in [Section 10.8.2](#) of that document, and must be registered with the "ALTO Endpoint Property Type Registry" defined in [Section 9.3](#) of that document. The type `PropertyName` denotes a JSON string with a property name in this format.

This document defines uniform property names specified in a single property name space rather than being scoped by a specific entity domain, although some properties may only be applicable for particular entity domains. This design decision is to enforce a design so that similar properties are named similarly. The interpretation of the value of a property, however, may depend on the entity domain. For example, suppose the "geo-location" property is defined as the coordinates of a point, encoded as (say) "latitude longitude [altitude]." When applied to an entity that represents a specific host computer, such as an Internet address, the property defines the host's location. When applied to an entity that represents a set of computers, such as a CIDR, the property would be the location of the center of that set. If it is necessary to represent the bounding box of a set of hosts, another property, such as "geo-region", should be defined.

2.6. Hierarchy and Inheritance

Entities in a given domain MAY form hierarchy based on entity address. Each entity domain MUST define its own hierarchy and inheritance rules when registered. The hierarchy and inheritance rule makes it possible for an entity to inherit a property value from another entity in the same domain. If and only if the property of an entity is undefined, the hierarchy and inheritance rules are applied.

2.7. Relationship with Other ALTO Resources

[RFC7285] recognizes that some properties MAY be specific to another ALTO resource, such as a network map. Accordingly [RFC7285] defines the concept of "resource-specific endpoint properties" (see [Section 10.8.1](#)), and indicates that dependency by prefixing the property name with the ID of the resource on which it depends. That document defines one resource-specific property, namely the "pid" property, whose value is the name of the PID containing that endpoint in the associated network map.

This document takes a different approach. Instead of defining the dependency by qualifying the property name, this document attaches the dependency to the entity domains. Thus all properties of a specific entity domain depend on the same resource, the properties of another entity domain may depend on another resource. For example, entities in the PID domain depend on a network map.

The "uses" field in an IRD entry defines the dependencies of a property map resource, and the "dependent-vtags" field in a property map response defines the dependencies of that map. These fields are defined in Sections [9.1.5](#) and [11.1](#) of [\[RFC7285\]](#), respectively.

The "uses" field in an IRD entry MUST NOT include two dependent resources with the same media type. This is similar to how [\[RFC7285\]](#) handles dependencies between cost maps and network maps. Recall that cost maps present the costs between PIDs, and PID names depend on a network map. If an ALTO server provides the "routingcost" metric for the network maps "net1" and "net2", then the server defines two separate cost maps, one for "net1" and the other for "net2".

According to [\[RFC7285\]](#), a legacy ALTO server with two network maps, with resource IDs "net1" and "net2", could offer a single Endpoint Property Service for the two properties "net1.pid" and "net2.pid". An ALTO server which supports the extensions defined in this document, would, instead, offer two different Property Maps for the "pid" property, one depending on "net1", the other on "net2".

[3.](#) Entity Domains

This document defines the following entity domains. For the definition of each entity domain, it includes the following template: domain name, domain-specific addresses, and hierarchy and inheritance semantics.

[3.1.](#) Internet Address Domains

The document defines two entity domains (IPv4 and IPv6) for Internet addresses. Both entity domains include individual addresses and blocks of addresses.

[3.1.1.](#) IPv4 Domain

[3.1.1.1.](#) Domain Name

ipv4

3.1.1.2. Domain-Specific Entity Addresses

Individual addresses are strings as specified by the IPv4Addresses rule of [Section 3.2.2 of \[RFC3986\]](#). Blocks of addresses are prefix-match strings as specified in [Section 3.1 of \[RFC4632\]](#). For the purpose of defining properties, an individual Internet address and the corresponding full-length prefix are considered aliases for the same entity. Thus "ipv4:192.0.2.0" and "ipv4:192.0.2.0/32" are equivalent.

3.1.2. IPv6 Domain

3.1.2.1. Domain Name

ipv6

3.1.2.2. Domain-Specific Entity Addresses

Individual addresses are strings as specified by [Section 4 of \[RFC5952\]](#). Blocks of addresses are prefix-match strings as specified in [Section 7 of \[RFC5952\]](#). For the purpose of defining properties, an individual Internet address and the corresponding 128-bit prefix are considered aliases for the same entity. That is, "ipv6:2001:db8::1" and "ipv6:2001:db8::1/128" are equivalent, and have the same set of properties.

3.1.3. Hierarchy and Inheritance of ipv4/ipv6 Domains

Both entity domains allow property values to be inherited. Specifically, if a property P is not defined for a specific Internet address I, but P is defined for some block C which prefix-matches I, then the address I inherits the value of P defined for block C. If more than one such block defines a value for P, I inherits the value of P in the block with the longest prefix. It is important to notice that this longest prefix rule will ensure no multiple inheritance, and hence no ambiguity.

Address blocks can also inherit properties: if property P is not defined for a block C, but is defined for some block C' which prefix-matches C, and C' has a shorter mask than C, then block C inherits the property from C'. If there are several such blocks C', C inherits from the block with the longest prefix.

As an example, suppose that a server defines the property P for the following entities:


```
ipv4:192.0.2.0/26: P=v1
ipv4:192.0.2.0/28: P=v2
ipv4:192.0.2.0/30: P=v3
ipv4:192.0.2.0:    P=v4
```

Figure 1: Defined Property Values.

Then the following entities have the indicated values:

```
ipv4:192.0.2.0:    P=v4
ipv4:192.0.2.1:    P=v3
ipv4:192.0.2.16:   P=v1
ipv4:192.0.2.32:   P=v1
ipv4:192.0.2.64:   (not defined)
ipv4:192.0.2.0/32: P=v4
ipv4:192.0.2.0/31: P=v3
ipv4:192.0.2.0/29: P=v2
ipv4:192.0.2.0/27: P=v1
ipv4:192.0.2.0/25: (not defined)
```

Figure 2: Inherited Property Values.

An ALTO Server MAY explicitly indicate a property as not having a value for a particular entity. That is, a server MAY say that property A of entity X is "defined to have no value", instead of "undefined". To indicate "no value", a server MAY perform different behaviours:

- o If that entity would inherit a value for that property, then the ALTO server MUST return a "null" value for that property. In this case, the ALTO client MUST recognize a "null" value as "no value" and "do not apply the inheritance rules for this property."
- o If the entity would not inherit a value, then the ALTO server MAY return "null" or just omit the property. In this case, the ALTO client cannot infer the value for this property of this entity from the Inheritance rules. So the client MUST interpret this property has no value.

If the ALTO Server does not define any properties for an entity, then the server MAY omit that entity from the response.

3.1.4. Relationship to Network Maps

An Internet address domain MAY be associated with an ALTO network map resource. Logically, there is a map of Internet address entities to property values for each network map defined by the ALTO server, plus an additional property map for Internet address entities which are

not associated with a network map. So, if there are n network maps, the server can provide $n+1$ maps of Internet address entities to property values. These maps are separate from each other. The prefixes in the property map do not have to correspond to the prefixes defining the network map's PIDs. For example, the property map for a network map MAY assign properties to "ipv4:192.0.2.0/24" even if that prefix is not associated with any PID in the network map.

3.2. PID Domain

The PID domain associates property values with the PIDs in a network map. Accordingly, this entity domain always depends on a network map.

3.2.1. Domain Name

pid

3.2.2. Domain-Specific Entity Addresses

The entity addresses are the PID names of the associated network map.

3.2.3. Hierarchy and Inheritance

There is no hierarchy or inheritance for properties associated with PIDs.

3.2.4. Relationship To Internet Addresses Domains

The PID domain and the Internet address domains are completely independent; the properties associated with a PID have no relation to the properties associated with the prefixes or endpoint addresses in that PID. An ALTO server MAY choose to assign some or all properties of a PID to the prefixes in that PID.

For example, suppose "PID1" consists of the prefix "ipv4:192.0.2.0/24", and has the property "P" with value "v1". The Internet address entities "ipv4:192.0.2.0" and "ipv4:192.0.2.0/24", in the IPv4 domain MAY have a value for the property "P", and if they do, it is not necessarily "v1".

3.3. Internet Address Properties vs. PID Properties

Because the Internet address and PID domains are completely separate, the question may arise as to which entity domain is the best for a property. In general, the Internet address domain is RECOMMENDED for

properties that are closely related to the Internet address, or are associated with, and inherited through, blocks of addresses.

The PID domain is RECOMMENDED for properties that arise from the definition of the PID, rather than from the Internet address prefixes in that PID.

For example, because Internet addresses are allocated to service providers by blocks of prefixes, an "ISP" property would be best associated with the Internet address domain. On the other hand, a property that explains why a PID was formed, or how it relates a provider's network, would best be associated with the PID domain.

[4.](#) Property Map Resource

A Property Map returns the properties defined for all entities in one or more domains.

[Section 7.4](#) gives an example of a property map request and its response.

[4.1.](#) Media Type

The media type of an ALTO Property Map resource is "application/alto-propmap+json".

[4.2.](#) HTTP Method

An ALTO Property Map resource is requested using the HTTP GET method.

[4.3.](#) Accept Input Parameters

None.

[4.4.](#) Capabilities

The capabilities are defined by an object of type PropertyMapCapabilities:

```
object {  
  DomainName entity-domain-types<1..*>;  
  PropertyName prop-types<1..*>;  
} PropertyMapCapabilities;
```

where "entity-domain-types" is an array with the domains of the entities in this property map, and "prop-types" is an array with the names of the properties returned for entities in those domains.

[4.5.](#) Uses

An array with the resource ID(s) of resource(s) with which the entity domains in this map are associated. In most cases, this array will have at most one ID, for example, for a network map resource. However, the "uses" field MUST NOT contain two resources of the same resource type. For example, if a property map depends on network map resource, the "uses" field MUST include exactly one network map resource.

[4.6.](#) Response

If the entity domains in this property map depend on other resources, the "dependent-vtags" field in the "meta" field of the response MUST be an array that includes the version tags of those resources. The data component of a Property Map response is named "property-map", which is a JSON object of type PropertyMapData, where:

```
object {
  PropertyMapData property-map;
} InfoResourceProperties : ResponseEntityBase;

object-map {
  EntityAddr -> EntityProps;
} PropertyMapData;

object {
  PropertyName -> JSONValue;
} EntityProps;
```

The ResponseEntityBase type is defined in [Section 8.4 of \[RFC7285\]](#).

Specifically, a PropertyMapData object has one member for each entity in the Property Map. The entity's properties are encoded in the corresponding EntityProps object. EntityProps encodes one name/value pair for each property, where the property names are encoded as strings of type PropertyName. A protocol implementation SHOULD assume that the property value is either a JSONString or a JSON "null" value, and fail to parse if it is not, unless the implementation is using an extension to this document that indicates when and how property values of other data types are signaled.

For each entity in the Property Map, the ALTO Server returns the value defined for each of the properties specified in this resource's "capabilities" list. For efficiency, the ALTO Server SHOULD omit property values that are inherited rather than explicitly defined; if a client needs inherited values, the client SHOULD use the entity domain's inheritance rules to deduce those values.

[5.](#) Filtered Property Map Resource

A Filtered Property Map returns the values of a set of properties for a set of entities selected by the client.

[Section 7.5](#), [Section 7.6](#) and [Section 7.7](#) give examples of filtered property map requests and responses.

[5.1.](#) Media Type

The media type of an ALTO Property Map resource is "application/alto-propmap+json".

[5.2.](#) HTTP Method

An ALTO Filtered Property Map resource is requested using the HTTP POST method.

[5.3.](#) Accept Input Parameters

The input parameters for a Filtered Property Map request are supplied in the entity body of the POST request. This document specifies the input parameters with a data format indicated by the media type "application/alto-propmapparams+json", which is a JSON object of type `ReqFilteredPropertyMap`:

```
object {  
  EntityAddr      entities<1..*>;  
  PropertyName    properties<1..*>;  
} ReqFilteredPropertyMap;
```

with fields:

entities: List of entity addresses for which the specified properties are to be returned. The ALTO server MUST interpret entries appearing multiple times as if they appeared only once. The domain of each entity MUST be included in the list of entity domains in this resource's "capabilities" field (see [Section 5.4](#)).

properties: List of properties to be returned for each entity. Each specified property MUST be included in the list of properties in this resource's "capabilities" field (see [Section 5.4](#)). The ALTO server MUST interpret entries appearing multiple times as if they appeared only once.

Note that the "entities" and "properties" fields MUST have at least one entry each.

5.4. Capabilities

The capabilities are defined by an object of type `PropertyMapCapabilities`, as defined in [Section 4.4](#).

5.5. Uses

An array with the resource ID(s) of resource(s) with which the entity domains in this map are associated. In most cases, this array will have at most one ID, and it will be for a network map resource.

5.6. Response

The response is the same as for the property map (see [Section 4.6](#)), except that it only includes the entities and properties requested by the client.

Also, the Filtered Property Map response MUST include all inherited property values for the specified entities (unlike the Full Property Map, the Filtered Property Map response does not include enough information for the client to calculate the inherited values).

If an entity in "entities" in the request is invalid, the ALTO server MUST return an "E_INVALID_FIELD_VALUE" error defined in [Section 8.5.2 of \[RFC7285\]](#). An entity can be invalid if the domain of the entity is not defined in the IRD for this service or the entity address is an invalid address of the entity domain. On the other hand, a valid entity address is not an error, even if the server does not define a value for a requested property. In this case, the server MUST omit that property from the response for only that entity. If a request contains a property in "properties" and the property is not specified in the IRD for the service, the ALTO server MUST return an "E_INVALID_FIELD_VALUE" error defined in [Section 8.5.2 of \[RFC7285\]](#). The "value" of the error message SHOULD indicate the wrong property.

If the ALTO server does not define a requested property's value for a particular entity, then it MUST omit that property from the response for only that endpoint.

If the ALTO server does not support a requested entity's domain, then it MUST return an E_INVALID_FIELD_VALUE error defined in [Section 8.5.2 of \[RFC7285\]](#).

6. Impact on Legacy ALTO Servers and ALTO Clients

6.1. Impact on Endpoint Property Service

The Property Maps defined in this document provide the same functionality as the Endpoint Property Service (EPS) defined in [Section 11.4 of \[RFC7285\]](#). Accordingly, it is RECOMMENDED that the EPS be deprecated in favor of Property Maps. However, ALTO servers MAY provide an EPS for the benefit of legacy clients.

6.2. Impact on Resource-Specific Properties

[Section 10.8 of \[RFC7285\]](#) defines two categories of endpoint properties: "resource-specific" and "global". Resource-specific property names are prefixed with the ID of the resource they depend upon, while global property names have no such prefix. The property map resources defined in this document do not distinguish between those two types of properties. Instead, if there is a dependency, it is indicated by the "uses" capability of a property map, and is shared by all properties and entity domains in that map. Accordingly, it is RECOMMENDED that resource-specific endpoint properties be deprecated, and no new resource-specific endpoint properties be defined.

6.3. Impact on the pid Property

[Section 7.1.1 of \[RFC7285\]](#) defines the resource-specific endpoint property name "pid", whose value is the name of the PID containing that endpoint. For compatibility with legacy clients, an ALTO server which provides the "pid" property via the Endpoint Property Service MUST use that definition, and that syntax, in the EPS resource.

However, when used with Property Maps, this document amends the definition of the "pid" property as follows.

First, the name of the property is simply "pid"; the name is not prefixed with the resource ID of a network map. The "uses" capability of the property map resource indicates the associated network map. This implies that a property map can only return the "pid" property for one network map; if an ALTO server provides several network maps, it MUST provide a property map resource for each one.

Second, a client MAY request the "pid" property for a block of addresses. An ALTO server determines the value of "pid" for an address block C as follows. Let CS be the set of all address blocks in the network map. If C is in CS, then the value of "pid" is the name of the PID associated with C. Otherwise, find the longest block C' in CS such that C' prefix-matches C, but is shorter than C. If

there is such a block C', the value of "pid" is the name of the PID associated with C'. If not, then "pid" has no value for block C.

Note that although an ALTO server MAY provide a GET-mode property map resource which returns the entire map for the "pid" property, there is no need to do so, because that map is simply the inverse of the network map.

6.4. Impact on Other Properties

In general, there should be little or no impact on other previously defined properties. The only consideration is that properties can now be defined on blocks of addresses, rather than just individual addresses, which might change the semantics of a property.

7. Examples

7.1. Network Map

The examples in this section use a very simple default network map:

```
defaultpid:  ipv4:0.0.0.0/0  ipv6:::0/0
pid1:         ipv4:192.0.2.0/25
pid2:         ipv4:192.0.2.0/28  ipv4:192.0.2.16/28
```

Figure 3: Example Network Map

7.2. Property Definitions

The examples in this section use four additional properties, "ISP", "ASN", "country" and "state", with the following values:

	ISP	ASN	country	state
ipv4:192.0.2.0/24:	BitsRus	-	us	-
ipv4:192.0.2.0/28:	-	12345	-	NJ
ipv4:192.0.2.16/28:	-	12345	-	CT
ipv4:192.0.2.0:	-	-	-	PA

Figure 4: Example Property Values

7.3. Information Resource Directory (IRD)

The following IRD defines the relevant resources of the ALTO server. It provides two Property Map resources, one for the "ISP" and "ASN" properties, and another for the "country" and "state" properties. The server could have provided a Property Map resource for all four properties, but did not, presumably because the organization that

runs the ALTO server believes any given client is not interested in all four properties.

The server provides two Filtered Property Maps. The first returns all four properties, and the second just returns the "pid" property for the default network map.

The Filtered Property Maps for the "ISP", "ASN", "country" and "state" properties do not depend on the default network map (it does not have a "uses" capability), because the definitions of those properties do not depend on the default network map. The Filtered Property Map for the "pid" property does have a "uses" capability for the default network map, because that defines the values of the "pid" property.

Note that for legacy clients, the ALTO server provides an Endpoint Property Service for the "pid" property for the default network map.

```
"meta": { ... },
"resources" : {
  "default-network-map" : {
    "uri" : "http://alto.example.com/networkmap",
    "media-type" : "application/alto-networkmap+json"
  },
  .... property map resources ....
  "country-state-property-map" : {
    "uri" : "http://alto.example.com/propmap/full/inet-cs",
    "media-type" : "application/alto-propmap+json",
    "capabilities" : {
      "entity-domain-types": [ "ipv4", "ipv6" ],
      "prop-types" : [ "country", "state" ]
    }
  },
  "isp-asn-property-map" : {
    "uri" : "http://alto.example.com/propmap/full/inet-ia",
    "media-type" : "application/alto-propmap+json",
    "capabilities" : {
      "entity-domain-types": [ "ipv4", "ipv6" ],
      "prop-types" : [ "ISP", "ASN" ]
    }
  },
  "iacs-property-map" : {
    "uri" : "http://alto.example.com/propmap/lookup/inet-iacs",
    "media-type" : "application/alto-propmap+json",
    "accepts" : "application/alto-propmapparams+json",
    "capabilities" : {
      "entity-domain-types": [ "ipv4", "ipv6" ],
      "prop-types" : [ "ISP", "ASN", "country", "state" ]
    }
  }
}
```



```
    }
  },
  "pid-property-map" : {
    "uri" : "http://alto.example.com/propmap/lookup/pid",
    "media-type" : "application/alto-propmap+json",
    "accepts" : "application/alto-propmapparams+json",
    "uses" : [ "default-network-map" ]
    "capabilities" : {
      "entity-domain-types" : [ "ipv4", "ipv6" ],
      "prop-types" : [ "pid" ]
    }
  },
  "location-property-map": {
    "uri": "http://alto.exmaple.com/propmap/location",
    "media-type": "application/alto-propmap+json",
    "accepts": "application/alto-propmapparams+json",
    "uses" : [ "default-network-map" ],
    "capabilities": {
      "domain-types": [ "pid" ],
      "prop-types": [ "country", "state" ]
    }
  },
  "legacy-pid-property" : {
    "uri" : "http://alto.example.com/legacy/eps-pid",
    "media-type" : "application/alto-endpointprop+json",
    "accepts" : "application/alto-endpointpropparams+json",
    "capabilities" : {
      "prop-types" : [ "default-network-map.pid" ]
    }
  }
}
```

Figure 5: Example IRD

[7.4.](#) Property Map Example

The following example uses the properties and IRD defined above to retrieve a property map for entities with the "ISP" and "ASN" properties. Note that the response does not include the entity "ipv4:192.0.2.0", because it does not have a value for either of those properties. Also note that the entities "ipv4:192.0.2.0/28" and "ipv4:192.0.2.16/28" are refinements of "ipv4:192.0.2.0/24", and hence inherit its value for "ISP" property. But because that value is inherited, it is not explicitly listed in the property map.


```
GET /propmap/full/inet-ia HTTP/1.1
Host: alto.example.com
Accept: application/alto-propmap+json,application/alto-error+json
```

```
HTTP/1.1 200 OK
Content-Length: ###
Content-Type: application/alto-propmap+json
```

```
{
  "property-map": {
    "ipv4:192.0.2.0/24":  {"ISP": "BitsRus"},
    "ipv4:192.0.2.0/28":  {"ASN": "12345"},
    "ipv4:192.0.2.16/28": {"ASN": "12345"}
  }
}
```

[7.5.](#) **Filtered Property Map Example #1**

The following example uses the Filtered Property Map resource to request the "ISP", "ASN" and "state" properties for several IPv4 addresses. Note that the value of "state" for "ipv4:192.0.2.0" is the only explicitly defined property; the other values are all derived by the inheritance rules for Internet address entities.


```
POST /propmap/lookup/inet-iacs HTTP/1.1
Host: alto.example.com
Accept: application/alto-propmap+json,application/alto-error+json
Content-Length: ###
Content-Type: application/alto-propmapparams+json
```

```
{
  "entities" : [ "ipv4:192.0.2.0",
                 "ipv4:192.0.2.1",
                 "ipv4:192.0.2.17" ],
  "properties" : [ "ISP", "ASN", "state" ]
}
```

```
HTTP/1.1 200 OK
Content-Length: ###
Content-Type: application/alto-propmap+json
```

```
{
  "property-map": {
    "ipv4:192.0.2.0":
      {"ISP": "BitsRus", "ASN": "12345", "state": "PA"},
    "ipv4:192.0.2.1":
      {"ISP": "BitsRus", "ASN": "12345", "state": "NJ"},
    "ipv4:192.0.2.17":
      {"ISP": "BitsRus", "ASN": "12345", "state": "CT"}
  }
}
```

7.6. Filtered Property Map Example #2

The following example uses the Filtered Property Map resource to request the "ASN", "country" and "state" properties for several IPv4 prefixes. Note that none of the returned property values is explicitly defined; all values are derived by the inheritance rules for Internet address entities.

Also note the "ASN" property has the value "12345" for both the blocks "ipv4:192.0.2.0/28" and "ipv4:192.0.2.16/28", so every address in the block "ipv4:192.0.2.0/27" has that property value. However the block "ipv4:192.0.2.0/27" itself does not have a value for "ASN": address blocks cannot inherit properties from blocks with longer prefixes, even if every such block has the same value.


```
POST /propmap/lookup/inet-iacs HTTP/1.1
Host: alto.example.com
Accept: application/alto-propmap+json,application/alto-error+json
Content-Length: ###
Content-Type: application/alto-propmapparams+json
```

```
{
  "entities" : [ "ipv4:192.0.2.0/26",
                 "ipv4:192.0.2.0/27",
                 "ipv4:192.0.2.0/28" ],
  "properties" : [ "ASN", "country", "state" ]
}
```

```
HTTP/1.1 200 OK
Content-Length: ###
Content-Type: application/alto-propmap+json
```

```
{
  "property-map": {
    "ipv4:192.0.2.0/26": {"country": "us"},
    "ipv4:192.0.2.0/27": {"country": "us"},
    "ipv4:192.0.2.0/28": {"ASN": "12345",
                          "country": "us",
                          "state": "NJ"}
  }
}
```

[7.7.](#) Filtered Property Map Example #3

The following example uses the Filtered Property Map resource to request the "pid" property for several IPv4 addresses and prefixes.

Note that the value of "pid" for the prefix "ipv4:192.0.2.0/26" is "pid1", even though all addresses in that block are in "pid2", because "ipv4:192.0.2.0/25" is the longest prefix in the network map which prefix-matches "ipv4:192.0.2.0/26", and that prefix is in "pid1".


```
POST /propmap/lookup/pid HTTP/1.1
Host: alto.example.com
Accept: application/alto-propmap+json,application/alto-error+json
Content-Length: ###
Content-Type: application/alto-propmapparams+json
```

```
{
  "entities" : [
    "ipv4:192.0.2.0",
    "ipv4:192.0.2.16",
    "ipv4:192.0.2.64",
    "ipv4:192.0.2.128",
    "ipv4:192.0.2.0/26",
    "ipv4:192.0.2.0/30" ],
  "properties" : [ "pid" ]
}
```

```
HTTP/1.1 200 OK
Content-Length: ###
Content-Type: application/alto-propmap+json
```

```
{
  "meta" : {
    "dependent-vtags" : [
      {"resource-id": "default-network-map",
       "tag": "7915dc0290c2705481c491a2b4ffbec482b3cf62"}
    ]
  },
  "property-map": {
    "ipv4:192.0.2.0": {"pid": "pid2"},
    "ipv4:192.0.2.16": {"pid": "pid2"},
    "ipv4:192.0.2.64": {"pid": "pid1"},
    "ipv4:192.0.2.128": {"pid": "defaultpid"},
    "ipv4:192.0.2.0/26": {"pid": "pid1"},
    "ipv4:192.0.2.0/30": {"pid": "pid2"}
  }
}
```

[7.8.](#) Filtered Property Map Example #4

The following example uses the Filtered Property Map resource to request the "country" and "state" property for several PIDs defined in "default-network-map".


```
POST /propmap/lookup/location HTTP/1.1
Host: alto.example.com
Accept: application/alto-propmap+json,application/alto-error+json
Content-Length: ###
Content-Type: application/alto-propmapparams+json
```

```
{
  "entities" : ["pid:pid3",
                "pid:pid4",
                "pid:pid5",
                "pid:pid6",
                "pid:pid7"],
  "properties" : [ "country", "state" ]
}
```

```
HTTP/1.1 200 OK
Content-Length: ###
Content-Type: application/alto-propmap+json
```

```
{
  "meta" : {
    "dependent-vtags" : [
      {"resource-id": "default-network-map",
       "tag": "7915dc0290c2705481c491a2b4ffbec482b3cf62"}
    ]
  },
  "property-map": {
    "pid:pid3": {
      "country": "us",
      "state": "CA"
    },
    "pid:pid4": {
      "country": "us",
      "state": "CT"
    },
    "pid:pid5": {
      "country": "ca",
      "state": "QC"
    },
    "pid:pid6": {
      "country": "ca",
      "state": "NT"
    },
    "pid:pid7": {
      "country": "fr"
    }
  }
}
```


8. Security Considerations

As discussed in [Section 15 of \[RFC7285\]](#), properties MAY have sensitive customer-specific information. If this is the case, an ALTO Server MAY limit access to those properties by providing several different Property Maps. For non-sensitive properties, the ALTO Server would provide a URI which accepts requests from any client. Sensitive properties, on the other hand, would only be available via a secure URI which would require client authentication.

Also, while technically this document does not introduce any security risks not inherent in the Endpoint Property Service defined by [\[RFC7285\]](#), the GET-mode property map resource defined in this document does make it easier for a client to download large numbers of property values. Accordingly, an ALTO Server SHOULD limit GET-mode Property Maps to properties which do not contain sensitive data.

9. IANA Considerations

This document defines additional application/alto-* media types, and extends the ALTO endpoint property registry.

9.1. application/alto-* Media Types

This document registers two additional ALTO media types, listed in Table 1.

Type	Subtype	Specification
application	alto-propmap+json	Section 4.1
application	alto-propmapparams+json	Section 5.3

Table 1: Additional ALTO Media Types.

Type name: application

Subtype name: This document registers multiple subtypes, as listed in Table 1.

Required parameters: n/a

Optional parameters: n/a

Encoding considerations: Encoding considerations are identical to those specified for the "application/json" media type. See [\[RFC7159\]](#).

Security considerations: Security considerations related to the generation and consumption of ALTO Protocol messages are discussed in [Section 15 of \[RFC7285\]](#).

Interoperability considerations: This document specifies formats of conforming messages and the interpretation thereof.

Published specification: This document is the specification for these media types; see Table 1 for the section documenting each media type.

Applications that use this media type: ALTO servers and ALTO clients either stand alone or are embedded within other applications.

Additional information:

Magic number(s): n/a

File extension(s): This document uses the mime type to refer to protocol messages and thus does not require a file extension.

Macintosh file type code(s): n/a

Person & email address to contact for further information: See Authors' Addresses section.

Intended usage: COMMON

Restrictions on usage: n/a

Author: See Authors' Addresses section.

Change controller: Internet Engineering Task Force
(mailto:iesg@ietf.org).

[9.2.](#) ALTO Entity Domain Registry

This document requests IANA to create and maintain the "ALTO Entity Domain Registry", listed in Table 2.

Identifier	Entity Address Encoding	Hierarchy & Inheritance
ipv4	See Section 3.1.1	See Section 3.1.3
ipv6	See Section 3.1.2	See Section 3.1.3
pid	See Section 3.2	None

Table 2: ALTO Entity Domains.

This registry serves two purposes. First, it ensures uniqueness of identifiers referring to ALTO entity domains. Second, it states the requirements for allocated entity domains.

9.2.1. Consistency Procedure between ALTO Address Type Registry and ALTO Entity Domain Registry

One potential issue of introducing the "ALTO Entity Domain Registry" is its relationship with the "ALTO Address Types Registry" already defined in [Section 14.4 of \[RFC7285\]](#). In particular, the entity address of an entity domain registered in the "ALTO Entity Domain Registry" MAY match an address type defined in "ALTO Address Type Registry". It is necessary to precisely define and guarantee the consistency between "ALTO Address Type Registry" and "ALTO Entity Domain Registry".

We define that the ALTO Entity Domain Registry is consistent with ALTO Address Type Registry if two conditions are satisfied:

- o When an address type is already or able to be registered in the ALTO Address Type Registry [[RFC7285](#)], the same identifier MUST be used when a corresponding entity domain is registered in the ALTO Entity Domain Registry.
- o If an ALTO entity domain has the same identifier as an ALTO address type, their addresses encoding MUST be compatible.

To achieve this consistency, the following items MUST be checked before registering a new ALTO entity domain in a future document:

- o Whether the ALTO Address Type Registry contains an address type that can be used as an entity address for the candidate domain identifier. This has been done for the identifiers "ipv4" and "ipv6" in Table 2.
- o Whether the candidate entity address of the entity domain is able to be an endpoint address, as defined in Sections [2.1](#) and [2.2](#) of [[RFC7285](#)].

When a new ALTO entity domain is registered, the consistency with the ALTO Address Type Registry MUST be ensured by the following procedure:

- o test: Do corresponding entity addresses match a known "network" address type?
 - * if yes: (e.g., cell, MAC or socket addresses)
 - + test: Is such an address type present in the ALTO Address Type Registry?
 - if yes: Set the new ALTO entity domain identifier to be the found ALTO address type identifier.
 - if no: Define a new ALTO entity domain identifier and use it to register a new address type in the ALTO Address Type Registry following [Section 14.4 of \[RFC7285\]](#).
 - + Use the new ALTO entity domain identifier to register a new ALTO entity domain in the ALTO Entity Domain Registry following [Section 9.2.2](#) of this document.
 - * if no (e.g., pid name, ane name or country code): Proceed with the ALTO Entity Domain registration as described in [Section 9.2.2](#).

[9.2.2](#). ALTO Entity Domain Registration Process

New ALTO entity domains are assigned after IETF Review [[RFC5226](#)] to ensure that proper documentation regarding the new ALTO entity domains and their security considerations has been provided. RFCs defining new entity domains SHOULD indicate how an entity in a registered domain is encoded as an EntityAddr, and, if applicable, the rules defining the entity hierarchy and property inheritance. Updates and deletions of ALTO entity domains follow the same procedure.

Registered ALTO entity domain identifiers MUST conform to the syntactical requirements specified in [Section 2.3](#). Identifiers are to be recorded and displayed as strings.

Requests to the IANA to add a new value to the registry MUST include the following information:

- o Identifier: The name of the desired ALTO entity domain.

- o Entity Address Encoding: The procedure for encoding the address of an entity of the registered type as an EntityAddr (see [Section 2.4](#)). If corresponding entity addresses of an entity domain match a known "network" address type, the Entity Address Encoding of this domain identifier MUST include both Address Encoding and Prefix Encoding of the same identifier registered in the ALTO Address Type Registry [[RFC7285](#)]. For the purpose of defining properties, an individual entity address and the corresponding full-length prefix MUST be considered aliases for the same entity.
- o Hierarchy: If the entities form a hierarchy, the procedure for determining that hierarchy.
- o Inheritance: If entities can inherit property values from other entities, the procedure for determining that inheritance.
- o Security Considerations: In some usage scenarios, entity addresses carried in ALTO Protocol messages MAY reveal information about an ALTO client or an ALTO service provider. Applications and ALTO service providers using addresses of the registered type SHOULD be made aware of how (or if) the addressing scheme relates to private information and network proximity.

This specification requests registration of the identifiers "ipv4", "ipv6" and "pid", as shown in Table 2.

[9.3.](#) ALTO Endpoint Property Type Registry

The ALTO Endpoint Property Type Registry was created by [[RFC7285](#)]. If possible, the name of that registry SHOULD be changed to "ALTO Entity Property Type Registry", to indicate that it is not restricted to Endpoint Properties. If it is not feasible to change the name, the description MUST be amended to indicate that it registers properties in all entity domains, rather than just the Internet address domain.

[10.](#) References

[10.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC4632] Fuller, V. and T. Li, "Classless Inter-domain Routing (CIDR): The Internet Address Assignment and Aggregation Plan", [BCP 122](#), [RFC 4632](#), DOI 10.17487/RFC4632, August 2006, <<https://www.rfc-editor.org/info/rfc4632>>.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [RFC 5226](#), DOI 10.17487/RFC5226, May 2008, <<https://www.rfc-editor.org/info/rfc5226>>.
- [RFC5952] Kawamura, S. and M. Kawashima, "A Recommendation for IPv6 Address Text Representation", [RFC 5952](#), DOI 10.17487/RFC5952, August 2010, <<https://www.rfc-editor.org/info/rfc5952>>.
- [RFC7159] Bray, T., Ed., "The JavaScript Object Notation (JSON) Data Interchange Format", [RFC 7159](#), DOI 10.17487/RFC7159, March 2014, <<https://www.rfc-editor.org/info/rfc7159>>.
- [RFC7285] Alimi, R., Ed., Penno, R., Ed., Yang, Y., Ed., Kiesel, S., Previdi, S., Roome, W., Shalunov, S., and R. Woundy, "Application-Layer Traffic Optimization (ALTO) Protocol", [RFC 7285](#), DOI 10.17487/RFC7285, September 2014, <<https://www.rfc-editor.org/info/rfc7285>>.

10.2. Informative References

- [I-D.ietf-alto-path-vector]
Bernstein, G., Chen, S., Gao, K., Lee, Y., Roome, W., Scharf, M., Yang, Y., and J. Zhang, "ALTO Extension: Path Vector Cost Type", [draft-ietf-alto-path-vector-03](#) (work in progress), March 2018.

Authors' Addresses

Wendy Roome
Nokia Bell Labs (Retired)
124 Burlington Rd
Murray Hill, NJ 07974
USA

Phone: +1-908-464-6975
Email: wendy@wdroome.com

Shiwei Dawn Chen
Tongji University
4800 Caoan Road
Shanghai 201804
China

Email: dawn_chen_f@hotmail.com

Sabine Randriamasy
Nokia Bell Labs
Route de Villejust
NOZAY 91460
FRANCE

Email: Sabine.Randriamasy@nokia-bell-labs.com

Y. Richard Yang
Yale University
51 Prospect Street
New Haven, CT 06511
USA

Phone: +1-203-432-6400
Email: yry@cs.yale.edu

Jingxuan Jensen Zhang
Tongji University
4800 Caoan Road
Shanghai 201804
China

Email: jingxuan.n.zhang@gmail.com

