

ANIMA Working Group
Internet-Draft
Intended status: Standards Track
Expires: 15 July 2022

K. Watsen
Juniper Networks
M. Richardson
Sandelman Software
M. Pritikin
Cisco Systems
T. Eckert
Q. Ma
Huawei
January 2022

A Voucher Artifact for Bootstrapping Protocols draft-ietf-anima-rfc8366bis-00

Abstract

This document defines a strategy to securely assign a pledge to an owner using an artifact signed, directly or indirectly, by the pledge's manufacturer. This artifact is known as a "voucher".

This document defines an artifact format as a YANG-defined JSON document that has been signed using a Cryptographic Message Syntax (CMS) structure. Other YANG-derived formats are possible. The voucher artifact is normally generated by the pledge's manufacturer (i.e., the Manufacturer Authorized Signing Authority (MASA)).

This document only defines the voucher artifact, leaving it to other documents to describe specialized protocols for accessing it.

Discussion Venues

This note is to be removed before publishing as an RFC.

Discussion of this document takes place on the Autonomic Networking Integrated Model and Approach Working Group mailing list (anima@ietf.org), which is archived at <https://mailarchive.ietf.org/arch/browse/anima/>.

Source for this draft and an issue tracker can be found at <https://github.com/anima-wg/voucher>.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Draft

Voucher Artifact

January 2022

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 5 July 2022.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Table of Contents

1.	Introduction	3
2.	Terminology	3
3.	Requirements Language	5
4.	Survey of Voucher Types	5
5.	Voucher Artifact	7
5.1.	Tree Diagram	7
5.2.	Examples	8
5.3.	YANG Module	9
5.3.1.	"iana-voucher-assertion-type" Module	9
5.3.2.	"ietf-voucher" Module	11
5.4.	CMS Format Voucher Artifact	15
6.	Design Considerations	16
6.1.	Renewals Instead of Revocations	16
6.2.	Voucher Per Pledge	17
7.	Security Considerations	17

7.1.	Clock Sensitivity	18
7.2.	Protect Voucher PKI in HSM	18
7.3.	Test Domain Certificate Validity When Signing	18
7.4.	YANG Module Security Considerations	18
8.	IANA Considerations	19

8.1.	The IETF XML Registry	20
8.2.	The YANG Module Names Registry	20
8.3.	The Media Types Registry	21
8.4.	The SMI Security for S/MIME CMS Content Type Registry	22
9.	References	22
9.1.	Normative References	22
9.2.	Informative References	23
	Acknowledgements	24
	Authors' Addresses	25

[1.](#) Introduction

This document defines a strategy to securely assign a candidate device (pledge) to an owner using an artifact signed, directly or indirectly, by the pledge's manufacturer, i.e., the Manufacturer Authorized Signing Authority (MASA). This artifact is known as the "voucher".

The voucher artifact is a JSON [[RFC8259](#)] document that conforms with a data model described by YANG [[RFC7950](#)], is encoded using the rules defined in [[RFC8259](#)], and is signed using (by default) a CMS structure [[RFC5652](#)].

The primary purpose of a voucher is to securely convey a certificate, the "pinned-domain-cert", that a pledge can use to authenticate subsequent interactions. A voucher may be useful in several contexts, but the driving motivation herein is to support secure bootstrapping mechanisms. Assigning ownership is important to bootstrapping mechanisms so that the pledge can authenticate the network that is trying to take control of it.

The lifetimes of vouchers may vary. In some bootstrapping protocols, the vouchers may include a nonce restricting them to a single use, whereas the vouchers in other bootstrapping protocols may have an indicated lifetime. In order to support long lifetimes, this document recommends using short lifetimes with programmatic renewal,

see [Section 6.1](#).

This document only defines the voucher artifact, leaving it to other documents to describe specialized protocols for accessing it. Some bootstrapping protocols using the voucher artifact defined in this document include: [[ZERO-TOUCH](#)], [[SECUREJOIN](#)], and [[BRSKI](#)]).

2. Terminology

This document uses the following terms:

Artifact: Used throughout to represent the voucher as instantiated

in the form of a signed structure.

Domain: The set of entities or infrastructure under common administrative control. The goal of the bootstrapping protocol is to enable a pledge to discover and join a domain.

Imprint: The process where a device obtains the cryptographic key material to identify and trust future interactions with a network. This term is taken from Konrad Lorenz's work in biology with new ducklings: "during a critical period, the duckling would assume that anything that looks like a mother duck is in fact their mother" [[Stajano99theresurrecting](#)]. An equivalent for a device is to obtain the fingerprint of the network's root certification authority certificate. A device that imprints on an attacker suffers a similar fate to a duckling that imprints on a hungry wolf. Imprinting is a term from psychology and ethology, as described in [[imprinting](#)].

Join Registrar (and Coordinator): A representative of the domain that is configured, perhaps autonomically, to decide whether a new device is allowed to join the domain. The administrator of the domain interfaces with a join registrar (and Coordinator) to control this process. Typically, a join registrar is "inside" its domain. For simplicity, this document often refers to this as just "registrar".

MASA (Manufacturer Authorized Signing Authority): The entity that, for the purpose of this document, signs the vouchers for a manufacturer's pledges. In some bootstrapping protocols, the MASA

may have an Internet presence and be integral to the bootstrapping process, whereas in other protocols the MASA may be an offline service that has no active role in the bootstrapping process.

Owner: The entity that controls the private key of the "pinned-domain-cert" certificate conveyed by the voucher.

Pledge: The prospective device attempting to find and securely join a domain. When shipped, it only trusts authorized representatives of the manufacturer.

Registrar: See join registrar.

TOFU (Trust on First Use): Where a pledge device makes no security decisions but rather simply trusts the first domain entity it is contacted by. Used similarly to [[RFC7435](#)]. This is also known as the "resurrecting duckling" model.

Voucher: A signed statement from the MASA service that indicates to

a pledge the cryptographic identity of the domain it should trust.

[3.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

[4.](#) Survey of Voucher Types

A voucher is a cryptographically protected statement to the pledge device authorizing a zero-touch "imprint" on the join registrar of the domain. The specific information a voucher provides is influenced by the bootstrapping use case.

The voucher can impart the following information to the join registrar and pledge:

Assertion Basis: Indicates the method that protects the imprint (this is distinct from the voucher signature that protects the

voucher itself). This might include manufacturer-asserted ownership verification, assured logging operations, or reliance on pledge endpoint behavior such as secure root of trust of measurement. The join registrar might use this information. Only some methods are normatively defined in this document. Other methods are left for future work.

Authentication of Join Registrar: Indicates how the pledge can authenticate the join registrar. This document defines a mechanism to pin the domain certificate. Pinning a symmetric key, a raw key, or "CN-ID" or "DNS-ID" information (as defined in [[RFC6125](#)]) is left for future work.

Anti-Replay Protections: Time- or nonce-based information to constrain the voucher to time periods or bootstrap attempts.

A number of bootstrapping scenarios can be met using differing combinations of this information. All scenarios address the primary threat of a Man-in-The-Middle (MiTM) registrar gaining control over the pledge device. The following combinations are "types" of vouchers:

Voucher Type	Assertion		Registrar ID		Validity	
	Log- ged	Veri- fied	Trust Anchor	CN-ID or DNS-ID	RTC	Nonce
Audit	X		X			X
Noncesless Audit	X		X		X	
Owner Audit	X	X	X		X	X
Owner ID		X	X	X	X	
Bearer out-of-scope	X		wildcard		optional	

-----|----|-----|-----|-----|

NOTE: All voucher types include a 'pledge ID serial-number'
(not shown here for space reasons).

Audit Voucher: An Audit Voucher is named after the logging assertion mechanisms that the registrar then "audits" to enforce local policy. The registrar mitigates a MiTM registrar by auditing that an unknown MiTM registrar does not appear in the log entries. This does not directly prevent the MiTM but provides a response mechanism that ensures the MiTM is unsuccessful. The advantage is that actual ownership knowledge is not required on the MASA service.

Nonceless Audit Voucher: An Audit Voucher without a validity period statement. Fundamentally, it is the same as an Audit Voucher except that it can be issued in advance to support network partitions or to provide a permanent voucher for remote deployments.

Ownership Audit Voucher: An Audit Voucher where the MASA service has verified the registrar as the authorized owner. The MASA service mitigates a MiTM registrar by refusing to generate Audit Vouchers for unauthorized registrars. The registrar uses audit techniques to supplement the MASA. This provides an ideal sharing of policy decisions and enforcement between the vendor and the owner.

Ownership ID Voucher: Named after inclusion of the pledge's CN-ID or DNS-ID within the voucher. The MASA service mitigates a MiTM registrar by identifying the specific registrar (via WebPKI) authorized to own the pledge.

Bearer Voucher: A Bearer Voucher is named after the inclusion of a

registrar ID wildcard. Because the registrar identity is not indicated, this voucher type must be treated as a secret and protected from exposure as any 'bearer' of the voucher can claim the pledge device. Publishing a nonceless bearer voucher effectively turns the specified pledge into a "TOFU" device with minimal mitigation against MiTM registrars. Bearer vouchers are out of scope.

[5.](#) Voucher Artifact

The voucher's primary purpose is to securely assign a pledge to an owner. The voucher informs the pledge which entity it should consider to be its owner.

This document defines a voucher that is a JSON-encoded instance of the YANG module defined in [Section 5.3](#) that has been, by default, CMS signed.

This format is described here as a practical basis for some uses (such as in NETCONF), but more to clearly indicate what vouchers look like in practice. This description also serves to validate the YANG data model.

Future work is expected to define new mappings of the voucher to Concise Binary Object Representation (CBOR) (from JSON) and to change the signature container from CMS to JSON Object Signing and Encryption (JOSE) or CBOR Object Signing and Encryption (COSE). XML or ASN.1 formats are also conceivable.

This document defines a media type and a filename extension for the CMS-encoded JSON type. Future documents on additional formats would define additional media types. Signaling is in the form of a MIME Content-Type, an HTTP Accept: header, or more mundane methods like use of a filename extension when a voucher is transferred on a USB key.

[5.1.](#) Tree Diagram

The following tree diagram illustrates a high-level view of a voucher document. The notation used in this diagram is described in [\[RFC8340\]](#). Each node in the diagram is fully described by the YANG module in [Section 5.3](#). Please review the YANG module for a detailed description of the voucher format.


```

grouping voucher-artifact-grouping
  +-- voucher
    +-- created-on                yang:date-and-time
    +-- expires-on?              yang:date-and-time
    +-- assertion                 ianavat:voucher-assertion
    +-- serial-number             string
    +-- idevid-issuer?            binary
    +-- pinned-domain-cert        binary
    +-- domain-cert-revocation-checks? boolean
    +-- nonce?                    binary
    +-- last-renewal-date?        yang:date-and-time

```

5.2. Examples

This section provides voucher examples for illustration purposes. These examples conform to the encoding rules defined in [[RFC8259](#)].

The following example illustrates an ephemeral voucher (uses a nonce). The MASA generated this voucher using the 'logged' assertion type, knowing that it would be suitable for the pledge making the request.

```

{
  "ietf-voucher:voucher": {
    "created-on": "2016-10-07T19:31:42Z",
    "assertion": "logged",
    "serial-number": "JADA123456789",
    "idevid-issuer": "base64encodedvalue==",
    "pinned-domain-cert": "base64encodedvalue==",
    "nonce": "base64encodedvalue=="
  }
}

```

The following example illustrates a non-ephemeral voucher (no nonce). While the voucher itself expires after two weeks, it presumably can be renewed for up to a year. The MASA generated this voucher using the 'verified' assertion type, which should satisfy all pledges.

```
{
  "ietf-voucher:voucher": {
    "created-on": "2016-10-07T19:31:42Z",
    "expires-on": "2016-10-21T19:31:42Z",
    "assertion": "verified",
    "serial-number": "JADA123456789",
    "idevid-issuer": "base64encodedvalue==",
    "pinned-domain-cert": "base64encodedvalue==",
    "domain-cert-revocation-checks": "true",
    "last-renewal-date": "2017-10-07T19:31:42Z"
  }
}
```

[5.3.](#) YANG Module

[5.3.1.](#) "iana-voucher-assertion-type" Module

Following is a YANG [[RFC7950](#)] module formally describing the voucher's assertion type.

<CODE BEGINS>

```
module iana-voucher-assertion-type {
  namespace "urn:ietf:params:xml:ns:yang:iana-voucher-assertion-type";
  prefix ianavat;

  organization
    "IANA";
  contact
    "Internet Assigned Numbers Authority
    Postal: ICANN
      12025 Waterfront Drive, Suite 300
      Los Angeles, CA 90094-2536
      United States of America
    Tel:      +1 310 301 5800
    <mailto:iana@iana.org>";
  description
    "This YANG module defines a YANG enumeration type for IANA
    -registered voucher assertion type. This YANG module is
    maintained by IANA and reflects the 'voucher assertion types'
    registry. The latest revision of this YANG module can be
    obtained from the IANA web site. Request for new enumerations
    should be made to IANA via email(iana@iana.org).
```

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as

described in [BCP 14](#) ([RFC 2119](#)) ([RFC 8174](#)) when, and only when, they appear in all capitals, as shown here.

Copyright (c) 2018 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXX; see the RFC itself for full legal notices.";

```
revision 2021-07-04 {
  description
    "Initial version";
  reference "RFC XXXX: Voucher Artifact for Bootstrapping Protocols";
}

typedef voucher-assertion {
  type enumeration {
    enum verified {
      value 0;
      description
        "Indicates that the ownership has been positively verified
        by the MASA (e.g., through sales channel integration).";
    }
    enum logged {
      value 1;
      description
        "Indicates that the voucher has been issued after
        minimal verification of ownership or control. The
        issuance has been logged for detection of
        potential security issues (e.g., recipients of
        vouchers might verify for themselves that unexpected
        vouchers are not in the log). This is similar to
        unsecured trust-on-first-use principles but with the
        logging providing a basis for detecting unexpected
        events.";
```

```

}
enum proximity {
    value 2;
    description
        "Indicates that the voucher has been issued after
        the MASA verified a proximity proof provided by the
        device and target domain. The issuance has been logged
        for detection of potential security issues. This is
        stronger than just logging, because it requires some

```

```

        verification that the pledge and owner are
        in communication but is still dependent on analysis of
        the logs to detect unexpected events.";
    }
    enum agent-proximity {
        value 3;
        description
            "Indicates that the voucher has been issued after the
            MASA...support of asynchronous enrollment in BRSKI";
    }
}
description "Indicates what kind of ownership is being asserted by voucher"
}
}
<CODE ENDS>

```

[5.3.2.](#) "ietf-voucher" Module

The revised ietf-voucher YANG module imports the typedef defined in "iana-voucher-assertion-type" YANG module specified in this document.

```

<CODE BEGINS>
module ietf-voucher {
    yang-version 1.1;
    namespace "urn:ietf:params:xml:ns:yang:ietf-voucher";
    prefix vch;

    import ietf-yang-types {
        prefix yang;
        reference "RFC 6991: Common YANG Data Types";
    }
    import ietf-restconf {

```

```

prefix rc;
description
    "This import statement is only present to access
    the yang-data extension defined in RFC 8040.";
reference "RFC 8040: RESTCONF Protocol";
}

import iana-voucher-assertion-type {
    prefix ianavat;
    reference "RFCZZZZ: Voucher Profile for Bootstrapping Protocols";
}

organization
    "IETF ANIMA Working Group";
contact
    "WG Web:    <https://datatracker.ietf.org/wg/anima/>"

```

Watsen, et al.

Expires 15 July 2022

[Page 11]

Internet-Draft

Voucher Artifact

January 2022

```

WG List:  <mailto:anima@ietf.org>
Author:   Kent Watsen
          <mailto:kwatsen@juniper.net>
Author:   Max Pritikin
          <mailto:pritikin@cisco.com>
Author:   Michael Richardson
          <mailto:mcr+ietf@sandelman.ca>
Author:   Toerless Eckert
          <mailto:tte+ietf@cs.fau.de>";

```

description

"This module defines the format for a voucher, which is produced by a pledge's manufacturer or delegate (MASA) to securely assign a pledge to an 'owner', so that the pledge may establish a secure connection to the owner's network infrastructure.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in [BCP 14 \(RFC 2119\)](#) ([RFC 8174](#)) when, and only when, they appear in all capitals, as shown here.

Copyright (c) 2018 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without

modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of [RFC 8366](#); see the RFC itself for full legal notices.";

```
revision 2021-07-04 {
  description
    "updated to support new assertion enumerated type";
  reference "RFC ZZZZ Voucher Profile for Bootstrapping Protocols";
}

// Top-level statement
rc:yang-data voucher-artifact {
  uses voucher-artifact-grouping;
}

// Grouping defined for future augmentations

grouping voucher-artifact-grouping {
  description
```

```
"Grouping to allow reuse/extensions in future work.";
container voucher {
  description
    "A voucher assigns a pledge to an owner (pinned-domain-cert).";
  leaf created-on {
    type yang:date-and-time;
    mandatory true;
    description
      "A value indicating the date this voucher was created. This
       node is primarily for human consumption and auditing. Future
       work MAY create verification requirements based on this
       node.";
  }
  leaf expires-on {
    type yang:date-and-time;
    must 'not(.. /nonce)';
    description
      "A value indicating when this voucher expires. The node is
```

optional as not all pledges support expirations, such as pledges lacking a reliable clock.

If this field exists, then the pledges MUST ensure that the expires-on time has not yet passed. A pledge without an accurate clock cannot meet this requirement.

The expires-on value MUST NOT exceed the expiration date of any of the listed 'pinned-domain-cert' certificates.";

```
}
leaf assertion {
  type ianavat:voucher-assertion;
  mandatory true;
  description
    "The assertion is a statement from the MASA regarding how
    the owner was verified. This statement enables pledges
    to support more detailed policy checks. Pledges MUST
    ensure that the assertion provided is acceptable, per
    local policy, before processing the voucher.";
}
leaf serial-number {
  type string;
  mandatory true;
  description
    "The serial-number of the hardware. When processing a
    voucher, a pledge MUST ensure that its serial-number
    matches this value. If no match occurs, then the
    pledge MUST NOT process this voucher.";
}
leaf idevid-issuer {
```

```
type binary;
description
  "The Authority Key Identifier OCTET STRING (as defined in
  Section 4.2.1.1 of RFC 5280) from the pledge's IDevID
  certificate. Optional since some serial-numbers are
  already unique within the scope of a MASA.
  Inclusion of the statistically unique key identifier
  ensures statistically unique identification of the hardware.
  When processing a voucher, a pledge MUST ensure that its
  IDevID Authority Key Identifier matches this value. If no
  match occurs, then the pledge MUST NOT process this voucher.
```

```

        When issuing a voucher, the MASA MUST ensure that this field
        is populated for serial-numbers that are not otherwise unique
        within the scope of the MASA.";
    }
    leaf pinned-domain-cert {
        type binary;
        mandatory true;
        description
            "An X.509 v3 certificate structure, as specified by RFC 5280,
            using Distinguished Encoding Rules (DER) encoding, as defined
            in ITU-T X.690.

            This certificate is used by a pledge to trust a Public Key
            Infrastructure in order to verify a domain certificate
            supplied to the pledge separately by the bootstrapping
            protocol. The domain certificate MUST have this certificate
            somewhere in its chain of certificates. This certificate
            MAY be an end-entity certificate, including a self-signed
            entity.";
        reference
            "RFC 5280:
            Internet X.509 Public Key Infrastructure Certificate
            and Certificate Revocation List (CRL) Profile.
            ITU-T X.690:
            Information technology - ASN.1 encoding rules:
            Specification of Basic Encoding Rules (BER),
            Canonical Encoding Rules (CER) and Distinguished
            Encoding Rules (DER).";
    }
    leaf domain-cert-revocation-checks {
        type boolean;
        description
            "A processing instruction to the pledge that it MUST (true)
            or MUST NOT (false) verify the revocation status for the
            pinned domain certificate. If this field is not set, then
            normal PKIX behavior applies to validation of the domain

```

```

        certificate.";
    }
    leaf nonce {
        type binary {

```



```

        length "8..32";
    }
    must 'not(..../expires-on)';
    description
        "A value that can be used by a pledge in some bootstrapping
        protocols to enable anti-replay protection. This node is
        optional because it is not used by all bootstrapping
        protocols.

        When present, the pledge MUST compare the provided nonce
        value with another value that the pledge randomly generated
        and sent to a bootstrap server in an earlier bootstrapping
        message. If the values do not match, then the pledge MUST
        NOT process this voucher.";
    }
    leaf last-renewal-date {
        type yang:date-and-time;
        must '..../expires-on';
        description
            "The date that the MASA projects to be the last date it
            will renew a voucher on. This field is merely informative; it
            is not processed by pledges.

            Circumstances may occur after a voucher is generated that
            may alter a voucher's validity period. For instance, a
            vendor may associate validity periods with support contracts,
            which may be terminated or extended over time.";
    }
} // end voucher
} // end voucher-grouping
}
<CODE ENDS>

```

[5.4.](#) CMS Format Voucher Artifact

The IETF evolution of PKCS#7 is CMS [[RFC5652](#)]. A CMS-signed voucher, the default type, contains a ContentInfo structure with the voucher content. An eContentType of 40 indicates that the content is a JSON-encoded voucher.

The signing structure is a CMS SignedData structure, as specified by [Section 5.1 of \[RFC5652\]](#), encoded using ASN.1 Distinguished Encoding Rules (DER), as specified in ITU-T X.690 [[ITU-T.X690.2015](#)].

To facilitate interoperability, [Section 8.3](#) in this document registers the media type "application/voucher-cms+json" and the filename extension ".vcj".

The CMS structure MUST contain a 'signerInfo' structure, as described in [Section 5.1 of \[RFC5652\]](#), containing the signature generated over the content using a private key trusted by the recipient. Normally, the recipient is the pledge and the signer is the MASA. Another possible use could be as a "signed voucher request" format originating from the pledge or registrar toward the MASA. Within this document, the signer is assumed to be the MASA.

Note that [Section 5.1 of \[RFC5652\]](#) includes a discussion about how to validate a CMS object, which is really a PKCS7 object (cmsVersion=1). Intermediate systems (such the Bootstrapping Remote Secure Key Infrastructures [[BRSKI](#)] registrar) that might need to evaluate the voucher in flight MUST be prepared for such an older format. No signaling is necessary, as the manufacturer knows the capabilities of the pledge and will use an appropriate format voucher for each pledge.

The CMS structure SHOULD also contain all of the certificates leading up to and including the signer's trust anchor certificate known to the recipient. The inclusion of the trust anchor is unusual in many applications, but third parties cannot accurately audit the transaction without it.

The CMS structure MAY also contain revocation objects for any intermediate certificate authorities (CAs) between the voucher issuer and the trust anchor known to the recipient. However, the use of CRLs and other validity mechanisms is discouraged, as the pledge is unlikely to be able to perform online checks and is unlikely to have a trusted clock source. As described below, the use of short-lived vouchers and/or a pledge-provided nonce provides a freshness guarantee.

[6.](#) Design Considerations

[6.1.](#) Renewals Instead of Revocations

The lifetimes of vouchers may vary. In some bootstrapping protocols, the vouchers may be created and consumed immediately, whereas in other bootstrapping solutions, there may be a significant time delay between when a voucher is created and when it is consumed. In cases when there is a time delay, there is a need for the pledge to ensure that the assertions made when the voucher was created are still valid.

A revocation artifact is generally used to verify the continued validity of an assertion such as a PKIX certificate, web token, or a "voucher". With this approach, a potentially long-lived assertion is paired with a reasonably fresh revocation status check to ensure that the assertion is still valid. However, this approach increases solution complexity, as it introduces the need for additional protocols and code paths to distribute and process the revocations.

Addressing the shortcomings of revocations, this document recommends instead the use of lightweight renewals of short-lived non-revocable vouchers. That is, rather than issue a long-lived voucher, where the 'expires-on' leaf is set to some distant date, the expectation is for the MASA to instead issue a short-lived voucher, where the 'expires-on' leaf is set to a relatively near date, along with a promise (reflected in the 'last-renewal-date' field) to reissue the voucher again when needed. Importantly, while issuing the initial voucher may incur heavyweight verification checks ("Are you who you say you are?" "Does the pledge actually belong to you?"), reissuing the voucher should be a lightweight process, as it ostensibly only updates the voucher's validity period. With this approach, there is only the one artifact, and only one code path is needed to process it; there is no possibility of a pledge choosing to skip the revocation status check because, for instance, the OCSP Responder is not reachable.

While this document recommends issuing short-lived vouchers, the voucher artifact does not restrict the ability to create long-lived voucher, if required; however, no revocation method is described.

Note that a voucher may be signed by a chain of intermediate CAs leading up to the trust anchor certificate known by the pledge. Even though the voucher itself is not revocable, it may still be revoked, per se, if one of the intermediate CA certificates is revoked.

[6.2.](#) Voucher Per Pledge

The solution described herein originally enabled a single voucher to apply to many pledges, using lists of regular expressions to represent ranges of serial-numbers. However, it was determined that blocking the renewal of a voucher that applied to many devices would

be excessive when only the ownership for a single pledge needed to be blocked. Thus, the voucher format now only supports a single serial-number to be listed.

[7.](#) Security Considerations

Watsen, et al.

Expires 15 July 2022

[Page 17]

Internet-Draft

Voucher Artifact

January 2022

[7.1.](#) Clock Sensitivity

An attacker could use an expired voucher to gain control over a device that has no understanding of time. The device cannot trust NTP as a time reference, as an attacker could control the NTP stream.

There are three things to defend against this: 1) devices are required to verify that the expires-on field has not yet passed, 2) devices without access to time can use nonces to get ephemeral vouchers, and 3) vouchers without expiration times may be used, which will appear in the audit log, informing the security decision.

This document defines a voucher format that contains time values for expirations, which require an accurate clock in order to be processed correctly. Vendors planning on issuing vouchers with expiration values must ensure that devices have an accurate clock when shipped from manufacturing facilities and take steps to prevent clock tampering. If it is not possible to ensure clock accuracy, then vouchers with expirations should not be issued.

[7.2.](#) Protect Voucher PKI in HSM

Pursuant the recommendation made in [Section 6.1](#) for the MASA to be deployed as an online voucher signing service, it is RECOMMENDED that the MASA's private key used for signing vouchers is protected by a hardware security module (HSM).

[7.3.](#) Test Domain Certificate Validity When Signing

If a domain certificate is compromised, then any outstanding vouchers for that domain could be used by the attacker. The domain administrator is clearly expected to initiate revocation of any domain identity certificates (as is normal in PKI solutions).

Similarly, they are expected to contact the MASA to indicate that an outstanding (presumably short lifetime) voucher should be blocked from automated renewal. Protocols for voucher distribution are RECOMMENDED to check for revocation of domain identity certificates before the signing of vouchers.

[7.4.](#) YANG Module Security Considerations

The YANG module specified in this document defines the schema for data that is subsequently encapsulated by a CMS signed-data content type, as described in [Section 5 of \[RFC5652\]](#). As such, all of the YANG modeled data is protected from modification.

Implementations should be aware that the signed data is only protected from external modification; the data is still visible. This potential disclosure of information doesn't affect security so much as privacy. In particular, adversaries can glean information such as which devices belong to which organizations and which CRL Distribution Point and/or OCSP Responder URLs are accessed to validate the vouchers. When privacy is important, the CMS signed-data content type SHOULD be encrypted, either by conveying it via a mutually authenticated secure transport protocol (e.g., TLS [\[RFC5246\]](#)) or by encapsulating the signed-data content type with an enveloped-data content type ([Section 6 of \[RFC5652\]](#)), though details for how to do this are outside the scope of this document.

The use of YANG to define data structures, via the 'yang-data' statement, is relatively new and distinct from the traditional use of YANG to define an API accessed by network management protocols such as NETCONF [\[RFC6241\]](#) and RESTCONF [\[RFC8040\]](#). For this reason, these guidelines do not follow template described by Section 3.7 of [\[YANG-GUIDE\]](#).

[8.](#) IANA Considerations

This section deals with actions and processes necessary for IANA to undertake to maintain the "iana-voucher-assertion-type" YANG module. The iana-voucher-assertion-type YANG module is intended to reflect the "voucher assertion types" registry in [TBD].

IANA is asked to create the "iana-voucher-assertion-type YANG module" registry.

Voucher assertion types must not be directly added to the iana-voucher-type YANG module. They must instead be added to the "voucher assertion types" registry.

Whenever a new enumerated type is added to the "voucher assertion types" registry, IANA must also update the "ietf-voucher-assertion-type" YANG module and add a new "enum" statement to the "voucher-assertion-type" type. The assigned name defined by the "enum" statement SHALL be the same as the mnemonic name of the new assertion type. The following substatements to the "enum" statement SHALL be defined:

"value": Use the decimal value from the registry.

"status": Include only if a class or type registration has been deprecated or obsoleted. IANA "deprecated" maps to YANG status "deprecated", and IANA "obsolete" maps to YANG status "obsolete".

"description": Replicate the corresponding information from the registry, namely the full name of the new assertion type.

"reference": Replicate the reference(s) from the registry.

Each time the "iana-voucher-assertion-type" YANG module is updated, a new "revision" statement SHALL be added before the existing "revision" statements. IANA has added this note to the "voucher assertion types" registries:

When this registry is modified, the YANG module "iana-voucher-assertion-type" must be updated as defined in [RFCXXXX]. The "Reference" text in the "voucher assertion types" registry has been updated as follows: OLD: | [[RFC8366](#)] NEW: | [[RFC8366](#)][RFCXXX]

[8.1](#). The IETF XML Registry

This document registers two URIs in the "IETF XML Registry" [[RFC3688](#)].

IANA has registered the following:

URI: urn:ietf:params:xml:ns:yang:ietf-voucher
Registrant Contact: The ANIMA WG of the IETF.
XML: N/A, the requested URI is an XML namespace.

IANA is asked to register a second URI as follows:

URI: urn:ietf:params:xml:ns:yang:iana-voucher-assertion-type
Registrant Contact: The ANIMA WG of the IETF.
XML: N/A, the requested URI is an XML namespace.

[8.2.](#) The YANG Module Names Registry

This document registers two YANG module in the "YANG Module Names" registry [[RFC6020](#)].

IANA is asked to registrar the following:

name: ietf-voucher
namespace: urn:ietf:params:xml:ns:yang:ietf-voucher
prefix: vch

reference: :[RFC 8366](#)

IANA is asked to register a second YANG module as follows:

name: iana-voucher-assertion-type

namespace: urn:ietf:params:xml:ns:yang:iana-voucher-assertion-type
prefix: ianavat
reference: RFC XXXX

[8.3.](#) The Media Types Registry

This document requests IANA to update the following "Media Types" entry to point to the RFC number that will be assigned to this document:

Type name: application

Subtype name: voucher-cms+json

Required parameters: none

Optional parameters: none

Encoding considerations: CMS-signed JSON vouchers are ASN.1/DER encoded.

Security considerations: See [Section 7](#)

Interoperability considerations: The format is designed to be broadly interoperable.

Published specification: [RFC 8366](#)

Applications that use this media type: ANIMA, 6tisch, and NETCONF zero-touch imprinting systems.

Fragment identifier considerations: none

Additional information: Deprecated alias names for this type: none

Magic number(s): None

File extension(s): .vcj

Macintosh file type code(s): none

Person and email address to contact for further information: IETF ANIMA WG

Intended usage: LIMITED

Restrictions on usage: NONE

[8.4.](#) The SMI Security for S/MIME CMS Content Type Registry

This document requests IANA to update this registered OID in the "SMI Security for S/MIME CMS Content Type (1.2.840.113549.1.9.16.1)" registry to point to the RFC number to be assigned to this document:

Decimal	Description	References
40	id-ct-animaJSONVoucher	RFC 8366

Table 1

[9.](#) References

[9.1.](#) Normative References

- [ITU-T.X690.2015]
International Telecommunication Union, "Information Technology - ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)", ITU-T Recommendation X.690, ISO/IEC 8825-1, August 2015,
<<https://www.itu.int/rec/T-REC-X.690/>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997,
<<https://www.rfc-editor.org/rfc/rfc2119>>.
- [RFC5652] Housley, R., "Cryptographic Message Syntax (CMS)", STD 70, [RFC 5652](#), DOI 10.17487/RFC5652, September 2009,
<<https://www.rfc-editor.org/rfc/rfc5652>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010,
<<https://www.rfc-editor.org/rfc/rfc6020>>.

- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/rfc/rfc7950>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/rfc/rfc8174>>.
- [RFC8259] Bray, T., Ed., "The JavaScript Object Notation (JSON) Data Interchange Format", STD 90, [RFC 8259](#), DOI 10.17487/RFC8259, December 2017, <<https://www.rfc-editor.org/rfc/rfc8259>>.

9.2. Informative References

- [BRSKI] Pritikin, M., Richardson, M., Eckert, T., Behringer, M., and K. Watsen, "Bootstrapping Remote Secure Key Infrastructure (BRSKI)", [RFC 8995](#), DOI 10.17487/RFC8995, May 2021, <<https://www.rfc-editor.org/rfc/rfc8995>>.
- [imprinting] Wikipedia, "Wikipedia article: Imprinting", February 2018, <[https://en.wikipedia.org/w/index.php?title=Imprinting_\(psychology\)&oldid=825757556](https://en.wikipedia.org/w/index.php?title=Imprinting_(psychology)&oldid=825757556)>.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/rfc/rfc3688>>.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), DOI 10.17487/RFC5246, August 2008, <<https://www.rfc-editor.org/rfc/rfc5246>>.
- [RFC6125] Saint-Andre, P. and J. Hodges, "Representation and Verification of Domain-Based Application Service Identity within Internet Public Key Infrastructure Using X.509 (PKIX) Certificates in the Context of Transport Layer Security (TLS)", [RFC 6125](#), DOI 10.17487/RFC6125, March 2011, <<https://www.rfc-editor.org/rfc/rfc6125>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/rfc/rfc6241>>.

Internet-Draft

Voucher Artifact

January 2022

- [RFC6838] Freed, N., Klensin, J., and T. Hansen, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 6838](#), DOI 10.17487/RFC6838, January 2013, <<https://www.rfc-editor.org/rfc/rfc6838>>.
- [RFC7435] Dukhovni, V., "Opportunistic Security: Some Protection Most of the Time", [RFC 7435](#), DOI 10.17487/RFC7435, December 2014, <<https://www.rfc-editor.org/rfc/rfc7435>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/rfc/rfc8040>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/rfc/rfc8340>>.
- [SECUREJOIN]
Richardson, M., "6tisch Secure Join protocol", Work in Progress, Internet-Draft, [draft-ietf-6tisch-dtsecurity-secure-join-01](#), 25 February 2017, <<https://datatracker.ietf.org/doc/html/draft-ietf-6tisch-dtsecurity-secure-join-01>>.
- [Stajano99theresurrecting]
Stajano, F. and R. Anderson, "The Resurrecting Duckling: Security Issues for Ad-Hoc Wireless Networks", 1999, <<http://www.cl.cam.ac.uk/research/dtg/www/files/publications/public/files/tr.1999.2.pdf>>.
- [YANG-GUIDE]
Bierman, A., "Guidelines for Authors and Reviewers of Documents Containing YANG Data Models", [BCP 216](#), [RFC 8407](#), DOI 10.17487/RFC8407, October 2018, <<https://www.rfc-editor.org/rfc/rfc8407>>.
- [ZERO-TOUCH]
Watsen, K., Farrer, I., and M. Abrahamsson, "Secure Zero Touch Provisioning (SZTP)", [RFC 8572](#), DOI 10.17487/RFC8572, April 2019, <<https://www.rfc-editor.org/rfc/rfc8572>>.

Acknowledgements

The authors would like to thank for following for lively discussions on list and in the halls (ordered by last name): William Atwood, Toerless Eckert, and Sheng Jiang.

Watsen, et al.

Expires 15 July 2022

[Page 24]

Internet-Draft

Voucher Artifact

January 2022

Russ Housley provided the upgrade from PKCS7 to CMS ([RFC 5652](#)) along with the detailed CMS structure diagram.

Authors' Addresses

Kent Watsen
Juniper Networks

Email: kwatsen@juniper.net

Michael C. Richardson
Sandelman Software

Email: mcr+iETF@sandelman.ca
URI: <http://www.sandelman.ca/>

Max Pritikin
Cisco Systems

Email: pritikin@cisco.com

Toerless Eckert
Futurewei Technologies Inc.
2330 Central Expy
Santa Clara, 95050
United States of America

Email: tte+iETF@cs.fau.de

Qiufang Ma
Huawei

101 Software Avenue, Yuhua District
Nanjing
210012
China

Email: maqiufang1@huawei.com