

Network Working Group  
INTERNET-DRAFT  
Obsoletes: RFC [1778](#)

M. Wahl  
Critical Angle Inc.  
A. Coulbeck  
Isode Limited  
T. Howes  
Netscape Communications Corp.  
S. Kille  
Isode Limited  
6 June 1997

Intended Category: Standards Track

**Lightweight Directory Access Protocol (v3):  
Attribute Syntax Definitions**  
<[draft-ietf-asid-ldapv3-attributes-05.txt](#)>

## **[1.](#) Status of this Memo**

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

To learn the current status of any Internet-Draft, please check the "lidl-abstracts.txt" listing contained in the Internet-Drafts Shadow Directories on ds.internic.net (US East Coast), nic.nordu.net (Europe), ftp.isi.edu (US West Coast), or munnari.oz.au (Pacific Rim).

## **[2.](#) Abstract**

The Lightweight Directory Access Protocol (LDAP) [[1](#)] requires that the contents of AttributeValue fields in protocol elements be octet strings. This document defines a set of syntaxes for LDAPv3, and the rules by which attribute values of these syntaxes are represented as octet strings for transmission in the LDAP protocol. The syntaxes defined in this document are referenced by this and other documents that define attribute types. This document also defines the set of attribute types which LDAP servers should support.

## **[3.](#) Overview**

This document defines the framework for developing schemas for directories accessible via the Lightweight Directory Access Protocol.

Schema is the collection of attribute type definitions, object class definitions and other information which a server uses to determine how to match a filter or attribute value assertion (in a compare operation) against the attributes of an entry, and whether to permit

add and modify operations.

[Section 4](#) states the general requirements and notations for attribute types, object classes, syntax and matching rule definitions.

Wahl, Coulbeck, Howes, Kille      LDAPv3 Attribute Syntax Defns.      Page 1

INTERNET-DRAFT      [draft-ietf-asid-ldapv3-attributes-05.txt](#)      June 1997

[Section 5](#) lists attributes, [section 6](#) syntaxes and [section 7](#) object classes.

Additional documents define schemas for representing real-world objects as directory entries.

#### [4. General Issues](#)

This document describes encodings used in an Internet protocol.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [4].

##### [4.1. Common Encoding Aspects](#)

For the purposes of defining the encoding rules for attribute syntaxes, the following BNF definitions will be used. They are based on the BNF styles of [RFC 822](#) [13].

a            = "a" / "b" / "c" / "d" / "e" / "f" / "g" / "h" / "i" /  
              "j" / "k" / "l" / "m" / "n" / "o" / "p" / "q" / "r" /  
              "s" / "t" / "u" / "v" / "w" / "x" / "y" / "z" / "A" /  
              "B" / "C" / "D" / "E" / "F" / "G" / "H" / "I" / "J" /  
              "K" / "L" / "M" / "N" / "O" / "P" / "Q" / "R" / "S" /  
              "T" / "U" / "V" / "W" / "X" / "Y" / "Z"

d            = "0" / "1" / "2" / "3" / "4" /  
              "5" / "6" / "7" / "8" / "9"

hex-digit    = d / "a" / "b" / "c" / "d" / "e" / "f" /  
              "A" / "B" / "C" / "D" / "E" / "F"

k            = a / d / "-"

p            = a / d / "\"" / "(" / ")" / "+" / "," /  
              "." / "/" / ":" / "?" / " "

letterstring = 1\*a

numericstring = 1\*d

```

anhstring      = 1*k

keystring      = a [ anhstring ]

printablestring = 1*p

space          = 1*" "

whsp           = [ space ]

utf8           = <any sequence of octets formed from the UTF-8 [9]
                  transformation of a character from ISO10646 [10]>

```

Wahl, Coulbeck, Howes, Kille    LDAPv3 Attribute Syntax Defns.    Page 2

INTERNET-DRAFT    [draft-ietf-asid-ldapv3-attributes-05.txt](#)    June 1997

```

dstring        = 1*utf8

qdstring       = whsp "'" dstring "'" whsp

qdstringlist   = ( qdstringlist qdstring ) / ""

qdstrings      = qdstring / ( whsp "(" qdstringlist ")" whsp )

```

In the following BNF for the string representation of OBJECT IDENTIFIERS, descr is the syntactic representation of an object descriptor, which consists of letters and digits, starting with a letter. An OBJECT IDENTIFIER in the numericoid format should not have leading zeroes (e.g. "0.9.3" is permitted but "0.09.3" should not be generated).

When encoding values in syntax, the descr encoding option SHOULD be used in preference to the numericoid. An object descriptor is a more readable alias for a number OBJECT IDENTIFIER, and these (where assigned and known by the implementation) SHOULD be used in preference to numeric oids to the greatest extent possible. Examples of object descriptors in LDAP are attribute type, object class and matching rule names.

```

oid            = descr / numericoid

descr          = keystring

numericoid     = numericstring *( "." numericstring )

woid           = whsp oid whsp

; set of oids of either form
oids           = woid / ( "(" oidlist ")" )

```

```

oidlist          = woid *( "$" woid )

; object descriptors used as schema element names
qdescrs          = qdescr / ( whsp "(" qdescrlist ")" whsp )

qdescrlist       = ( qdescrlist qdescr ) / ""

qdescr           = whsp "'" descr "'" whsp

```

## 4.2. Attribute Types

The attribute types are described by sample values for the subschema "attributeTypes" attribute, which is written in the AttributeTypeDescription syntax. While lines have been folded for readability, the values transferred in protocol would not contain newlines.

The AttributeTypeDescription is encoded according to the following BNF, and the productions for oid, qdescrs and qdstring are given in [section 4.1](#). Implementors should note that future versions of this document may have expanded this BNF to include additional terms.

Wahl,Coulbeck,Howes,Kille LDAPv3 Attribute Syntax Defns. Page 3

INTERNET-DRAFT [draft-ietf-asid-ldapv3-attributes-05.txt](#) June 1997

```

AttributeTypeDescription = "(" whsp
    numericoid whsp          ; AttributeType identifier
    [ "NAME" qdescrs ]       ; name used in AttributeType
    [ "DESC" qdstring ]      ; description
    [ "OBSOLETE" whsp ]
    [ "SUP" woid ]           ; derived from this other
                             ; AttributeType
    [ "EQUALITY" woid        ; Matching Rule name
    [ "ORDERING" woid        ; Matching Rule name
    [ "SUBSTR" woid ]        ; Matching Rule name
    [ "SYNTAX" whsp numericoid whsp ] ; see section 4.2
    [ "SINGLE-VALUE" whsp ]   ; default multi-valued
    [ "COLLECTIVE" whsp ]    ; default not collective
    [ "NO-USER-MODIFICATION" whsp ]; default user modifiable
    [ "USAGE" whsp AttributeUsage ]; default user applications
    whsp ")"

AttributeUsage =
    "userApplications" /
    "directoryOperation" /
    "distributedOperation" / ; DSA-shared
    "dSAOperation"          ; DSA-specific, value depends on server

```

Servers are not required to provide the same or any text in the description part of the subschema values they maintain. Servers SHOULD provide at least one of the "SUP" and "SYNTAX" fields

for each AttributeTypeDescription.

Servers SHOULD implement all the attribute types referenced in [section 5](#). Servers MUST be able to evaluate presence filters, SHOULD be able to perform equality matching of values of all user attributes known to the server, and MAY be able to perform matching with the other kinds of filters. If a server allows values of an attribute of a particular type to be added or removed over protocol, the server MUST be able to perform equality matching of values of that attribute, but need not perform any additional validity checks on attribute values.

Servers MAY recognize additional names and attributes not listed in this document, and if they do so, SHOULD publish the definitions of the types in the attributeTypes attribute of their subschema entries.

AttributeDescriptions can be used as the value in a NAME part of an AttributeTypeDescription. Note that these are case insensitive.

Note that the AttributeTypeDescription does not list the matching rules which can be used with that attribute type in an extensibleMatch search filter. This is done using the matchingRuleUse attribute described in [section 4.4](#).

## **[4.2. Syntaxes](#)**

This section defines general requirements for LDAP attribute value syntax encodings. All documents defining attribute syntax encodings for use with LDAP are expected to conform to these requirements.

The encoding rules defined for a given attribute syntax must produce octet strings. To the greatest extent possible, encoded octet strings should be usable in their native encoded form for display purposes. In particular, encoding rules for attribute syntaxes defining non-binary values should produce strings that can be displayed with little or no translation by clients implementing LDAP. There are a few cases (e.g. audio) however, when it is not sensible to produce a printable representation, and clients MUST NOT assume that an unrecognized syntax is a string representation.

In encodings where an arbitrary string is used as part of a larger production (other than a Distinguished Name), a backslash quoting

mechanism is used to encode the following separator symbol character (such as "'", "\$" or "#") if it should occur in that string. The backslash is followed by a pair of hexadecimal digits representing the next character. A backslash itself in the string which forms part of a larger syntax is always transmitted as '\5C' or '\5c'.

Syntaxes are also defined for matching rules whose assertion value syntax is different from the attribute value syntax.

#### **4.2.1 Binary Transfer of Values**

This encoding format is used if the binary encoding is requested by the client for an attribute, or if the attribute syntax name is "1.3.6.1.4.1.1466.115.121.1.5". The value, an instance of the ASN.1 AttributeValue type, is BER-encoded, subject to the restrictions of section 5.1 of [1], and this sequence of octets is used as the value. (E.g. the first byte inside the OCTET STRING wrapper is a tag byte. However the OCTET STRING is still encoded in primitive form.)

All servers MUST implement this form for both generating attribute values in search responses, and parsing attribute values in add, compare and modify requests, if the attribute type is recognized and the attribute syntax name is that of Binary. Clients which request that all attributes be returned from entries MUST be prepared to receive values in binary (e.g. userCertificate), and SHOULD NOT simply display binary or unrecognized values to users.

#### **4.2.2. Syntax Object Identifiers**

Syntaxes for use with LDAP are named by OBJECT IDENTIFIERS, which are dotted-decimal strings. These are not intended to be displayed to users.

The following table lists some of the syntaxes that have been defined for LDAP thus far. The H-R column suggests whether a value in that syntax would likely be a human readable string. Clients and servers need not implement all the syntaxes listed here, and MAY implement other syntaxes.

Other documents may define additional syntaxes. However, the definition of additional arbitrary syntaxes is strongly deprecated since it will hinder interoperability: today's client and server implementations generally do not have the ability to dynamically

recognize new syntaxes. In most cases attributes will be defined with the syntax for directory strings.

Value being represented	H-R OBJECT IDENTIFIER
=====	=====
ACI Item	N 1.3.6.1.4.1.1466.115.121.1.1
Access Point	Y 1.3.6.1.4.1.1466.115.121.1.2
Attribute Type Description	Y 1.3.6.1.4.1.1466.115.121.1.3
Audio	N 1.3.6.1.4.1.1466.115.121.1.4
Binary	N 1.3.6.1.4.1.1466.115.121.1.5
Bit String	Y 1.3.6.1.4.1.1466.115.121.1.6
Boolean	Y 1.3.6.1.4.1.1466.115.121.1.7
Certificate	N 1.3.6.1.4.1.1466.115.121.1.8
Certificate List	N 1.3.6.1.4.1.1466.115.121.1.9
Certificate Pair	N 1.3.6.1.4.1.1466.115.121.1.10
Country String	Y 1.3.6.1.4.1.1466.115.121.1.11
DN	Y 1.3.6.1.4.1.1466.115.121.1.12
Data Quality Syntax	Y 1.3.6.1.4.1.1466.115.121.1.13
Delivery Method	Y 1.3.6.1.4.1.1466.115.121.1.14
Directory String	Y 1.3.6.1.4.1.1466.115.121.1.15
DIT Content Rule Description	Y 1.3.6.1.4.1.1466.115.121.1.16
DIT Structure Rule Description	Y 1.3.6.1.4.1.1466.115.121.1.17
DL Submit Permission	Y 1.3.6.1.4.1.1466.115.121.1.18
DSA Quality Syntax	Y 1.3.6.1.4.1.1466.115.121.1.19
DSE Type	Y 1.3.6.1.4.1.1466.115.121.1.20
Enhanced Guide	Y 1.3.6.1.4.1.1466.115.121.1.21
Facsimile Telephone Number	Y 1.3.6.1.4.1.1466.115.121.1.22
Fax	N 1.3.6.1.4.1.1466.115.121.1.23
Generalized Time	Y 1.3.6.1.4.1.1466.115.121.1.24
Guide	Y 1.3.6.1.4.1.1466.115.121.1.25
IA5 String	Y 1.3.6.1.4.1.1466.115.121.1.26
INTEGER	Y 1.3.6.1.4.1.1466.115.121.1.27
JPEG	N 1.3.6.1.4.1.1466.115.121.1.28
LDAP Syntax Description	Y 1.3.6.1.4.1.1466.115.121.1.54
Master And Shadow Access Points	Y 1.3.6.1.4.1.1466.115.121.1.29
Matching Rule Description	Y 1.3.6.1.4.1.1466.115.121.1.30
Matching Rule Use Description	Y 1.3.6.1.4.1.1466.115.121.1.31
Mail Preference	Y 1.3.6.1.4.1.1466.115.121.1.32
MHS OR Address	Y 1.3.6.1.4.1.1466.115.121.1.33
Name And Optional UID	Y 1.3.6.1.4.1.1466.115.121.1.34
Name Form Description	Y 1.3.6.1.4.1.1466.115.121.1.35
Numeric String	Y 1.3.6.1.4.1.1466.115.121.1.36

Object Class Description	Y 1.3.6.1.4.1.1466.115.121.1.37
--------------------------	---------------------------------

OID	Y	1.3.6.1.4.1.1466.115.121.1.38
Other Mailbox	Y	1.3.6.1.4.1.1466.115.121.1.39
Password	Y	1.3.6.1.4.1.1466.115.121.1.40
Postal Address	Y	1.3.6.1.4.1.1466.115.121.1.41
Protocol Information	Y	1.3.6.1.4.1.1466.115.121.1.42
Presentation Address	Y	1.3.6.1.4.1.1466.115.121.1.43
Printable String	Y	1.3.6.1.4.1.1466.115.121.1.44
Subtree Specification	Y	1.3.6.1.4.1.1466.115.121.1.45
Supplier Information	Y	1.3.6.1.4.1.1466.115.121.1.46
Supplier Or Consumer	Y	1.3.6.1.4.1.1466.115.121.1.47
Supplier And Consumer	Y	1.3.6.1.4.1.1466.115.121.1.48
Supported Algorithm	N	1.3.6.1.4.1.1466.115.121.1.49
Telephone Number	Y	1.3.6.1.4.1.1466.115.121.1.50
Teletex Terminal Identifier	Y	1.3.6.1.4.1.1466.115.121.1.51
Telex Number	Y	1.3.6.1.4.1.1466.115.121.1.52
UTC Time	Y	1.3.6.1.4.1.1466.115.121.1.53

A suggested minimum upper bound on the number of characters in value with a string-based syntax, or the number of bytes in a value for all other syntaxes, may be indicated by appending this bound count inside of curly braces following the syntax name's OBJECT IDENTIFIER. This bound is not part of the syntax name itself. For instance, "1.3.6.4.1.1466.0{64}" suggests that server implementations should allow the string to be 64 characters long, although they may allow longer strings. Note that a single character of the Directory String syntax may be encoded in more than one byte since UTF-8 is a variable-length encoding.

#### **4.2.3. Syntax Description**

The following BNF may be used to associate a short description with a syntax OBJECT IDENTIFIER. Implementors should note that future versions of this document may expand this definition to include additional terms.

```
SyntaxDescription = "(" whsp
    numericoid whsp
    [ "DESC" qdstring ]
    whsp ")"
```

#### **4.3. Object Classes**

The format for representation of object classes is defined in X.501 [3]. In general every entry will contain an abstract class ("top" or "alias"), at least one structural object class, and zero or more auxiliary object classes. Whether an object class is abstract, structural or auxiliary is defined when the object class identifier is assigned. An object class definition should not be changed without having a new identifier assigned to it.

Object class descriptions are written according to the following BNF.

Implementors should note that future versions of this document may expand this definition to include additional terms.

Wahl, Coulbeck, Howes, Kille LDAPv3 Attribute Syntax Defns. Page 7

INTERNET-DRAFT [draft-ietf-asid-ldapv3-attributes-05.txt](#) June 1997

```
ObjectClassDescription = "(" whsp
    numericoid whsp      ; ObjectClass identifier
    [ "NAME" qdescrs ]
    [ "DESC" qdstring ]
    [ "OBSOLETE" whsp ]
    [ "SUP" oids ]       ; Superior ObjectClasses
    [ ( "ABSTRACT" / "STRUCTURAL" / "AUXILIARY" ) whsp ]
                        ; default structural
    [ "MUST" oids ]      ; AttributeTypes
    [ "MAY" oids ]       ; AttributeTypes
whsp ")"
```

These are described as sample values for the subschema "objectClasses" attribute for a server which implements the LDAP schema. While lines have been folded for readability, the values transferred in protocol would not contain newlines.

Servers SHOULD implement all the object classes referenced in [section 7](#), except for extensibleObject, which is optional.

Servers MAY implement additional object classes not listed in this document, and if they do so, SHOULD publish the definitions of the classes in the objectClasses attribute of their subschema entries. Later documents may define additional object classes.

#### **[4.4. Matching Rules](#)**

Matching rules are used by servers to compare attribute values against assertion values when performing Search and Compare operations. They are also used to identify the value to be added or deleted when modifying entries, and are used when comparing a purported distinguished name with the name of an entry.

Most of the attributes given in this document will have an equality matching rule defined.

Matching rule descriptions are written according to the following BNF. Implementors should note that future versions of this document may have expanded this BNF to include additional terms.

```
MatchingRuleDescription = "(" whsp
    numericoid whsp      ; MatchingRule identifier
    [ "NAME" qdescrs ]
    [ "DESC" qdstring ]
```

```
[ "OBSOLETE" whsp ]
"SYNTAX" numericoid
whsp ")"
```

Values of the matchingRuleUse list the attributes which are suitable for use with an extensible matching rule.

Wahl, Coulbeck, Howes, Kille LDAPv3 Attribute Syntax Defns. Page 8

INTERNET-DRAFT [draft-ietf-asid-ldapv3-attributes-05.txt](#) June 1997

```
MatchingRuleUseDescription = "(" whsp
    numericoid whsp ; MatchingRule identifier
    [ "NAME" qdescrs ]
    [ "DESC" qdstring ]
    [ "OBSOLETE" ]
    "APPLIES" oids ; AttributeType identifiers
whsp ")"
```

Servers which support matching rules and the extensibleMatch SHOULD implement all the matching rules in [section 8](#).

Servers MAY implement additional matching rules not listed in this document, and if they do so, SHOULD publish the definitions of the matching rules in the matchingRules attribute of their subschema entries. If the server supports the extensibleMatch, then the server SHOULD publish the relationship between the matching rules and attributes in the matchingRuleUse attribute.

For example, a server which implements a privately-defined matching rule for performing sound-alike matches on Directory String-valued attributes would include the following in the subschema entry (1.2.3.4.5 is an example, the OID of an actual matching rule would be different):

```
matchingRule: ( 1.2.3.4.5 NAME 'soundAlikeMatch'
    SYNTAX '1.3.6.1.4.1.1466.115.121.1.15' )
```

If this matching rule could be used with the attributes 2.5.4.41 and 2.5.4.15, the following would also be present:

```
matchingRuleUse: ( 1.2.3.4.5 APPLIES (2.5.4.41 $ 2.5.4.15) )
```

A client could then make use of this matching rule by sending a search operation in which the filter is of the extensibleMatch choice, the matchingRule field is "soundAlikeMatch", and the type field is

"2.5.4.41" of "2.5.4.15".

## **5. Attribute Types**

All LDAP server implementations MUST recognize the attribute types defined in this section. These types are based on definitions in X.501(93) [3].

Servers SHOULD also recognize all the attributes from section 5 of [12].

### **5.1. Standard Operational Attributes**

Servers MUST maintain values of these attributes in accordance with the definitions in X.501(93).

Wahl, Coulbeck, Howes, Kille    LDAPv3 Attribute Syntax Defns.    Page 9

INTERNET-DRAFT    [draft-ietf-asid-ldapv3-attributes-05.txt](#)    June 1997

#### **5.1.1. createTimestamp**

This attribute SHOULD appear in entries which were created using the Add operation.

```
( 2.5.18.1 NAME 'createTimestamp' EQUALITY generalizedTimeMatch
  ORDERING generalizedTimeOrderingMatch
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.24'
  SINGLE-VALUE NO-USER-MODIFICATION USAGE directoryOperation )
```

#### **5.1.2. modifyTimestamp**

This attribute SHOULD appear in entries which have been modified using the Modify operation.

```
( 2.5.18.2 NAME 'modifyTimestamp' EQUALITY generalizedTimeMatch
  ORDERING generalizedTimeOrderingMatch
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.24'
  SINGLE-VALUE NO-USER-MODIFICATION USAGE directoryOperation )
```

#### **5.1.3. creatorsName**

This attribute SHOULD appear in entries which were created using the Add operation.

```
( 2.5.18.3 NAME 'creatorsName' EQUALITY distinguishedNameMatch
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.12'
  SINGLE-VALUE NO-USER-MODIFICATION USAGE directoryOperation )
```

#### **5.1.4. modifiersName**

This attribute SHOULD appear in entries which have been modified using the Modify operation.

```
( 2.5.18.4 NAME 'modifiersName' EQUALITY distinguishedNameMatch
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.12'
  SINGLE-VALUE NO-USER-MODIFICATION USAGE directoryOperation )
```

#### **5.1.5. subschemaSubentry**

The value of this attribute is the name of a subschema entry (or subentry if the server is based on X.500(93)) in which the server makes available attributes specifying the schema.

```
( 2.5.18.10 NAME 'subschemaSubentry'
  EQUALITY distinguishedNameMatch
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.12' NO-USER-MODIFICATION
  SINGLE-VALUE USAGE directoryOperation )
```

Wahl, Coulbeck, Howes, Kille    LDAPv3 Attribute Syntax Defns.    Page 10

INTERNET-DRAFT    [draft-ietf-asid-ldapv3-attributes-05.txt](#)    June 1997

#### **5.1.6. attributeTypes**

This attribute is typically located in the subschema entry.

```
( 2.5.21.5 NAME 'attributeTypes'
  EQUALITY objectIdentifierFirstComponentMatch
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.3' USAGE directoryOperation )
```

#### **5.1.7. objectClasses**

This attribute is typically located in the subschema entry.

```
( 2.5.21.6 NAME 'objectClasses'
  EQUALITY objectIdentifierFirstComponentMatch
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.37' USAGE directoryOperation )
```

#### **5.1.8. matchingRules**

This attribute is typically located in the subschema entry.

```
( 2.5.21.4 NAME 'matchingRules'
  EQUALITY objectIdentifierFirstComponentMatch
```

```
SYNTAX '1.3.6.1.4.1.1466.115.121.1.30' USAGE directoryOperation )
```

#### **5.1.9. matchingRuleUse**

This attribute is typically located in the subschema entry.

```
( 2.5.21.8 NAME 'matchingRuleUse'  
  EQUALITY objectIdentifierFirstComponentMatch  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.31' USAGE directoryOperation )
```

### **5.2. LDAP Operational Attributes**

These attributes are only present in the root DSE (see [1] and [3]).

Servers MUST recognize these attribute names, but it is not required that a server provide values for these attributes, when the attribute corresponds to a feature which the server does not implement.

#### **5.2.1. namingContexts**

The values of this attribute correspond to naming contexts which this server masters or shadows. If the server does not master any information (e.g. it is an LDAP gateway to a public X.500 directory) this attribute will be absent. If the server believes it contains the entire directory, the attribute will have a single value, and that value will be the empty string (indicating the null DN of the root). This attribute will allow a client to choose suitable base objects for searching when it has contacted a server.

```
( 1.3.6.1.4.1.1466.101.120.5 NAME 'namingContexts'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.12' USAGE dSAOperation )
```

Wahl, Coulbeck, Howes, Kille    LDAPv3 Attribute Syntax Defns.    Page 11

INTERNET-DRAFT    [draft-ietf-asid-ldapv3-attributes-05.txt](https://datatracker.ietf.org/doc/draft-ietf-asid-ldapv3-attributes-05.txt)    June 1997

#### **5.2.2. altServer**

The values of this attribute are URLs of other servers which may be contacted when this server becomes unavailable. If the server does not know of any other servers which could be used this attribute will be absent. Clients may cache this information in case their preferred LDAP server later becomes unavailable.

```
( 1.3.6.1.4.1.1466.101.120.6 NAME 'altServer'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.26' USAGE dSAOperation )
```

#### **5.2.3. supportedExtension**

The values of this attribute are OBJECT IDENTIFIERS identifying the

supported extended operations which the server supports.

If the server does not support any extensions this attribute will be absent.

```
( 1.3.6.1.4.1.1466.101.120.7 NAME 'supportedExtension'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.38' USAGE dSAOperation )
```

#### **5.2.4. supportedControl**

The values of this attribute are the OBJECT IDENTIFIERS identifying controls which the server supports. If the server does not support any controls, this attribute will be absent.

```
( 1.3.6.1.4.1.1466.101.120.13 NAME 'supportedControl'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.38' USAGE dSAOperation )
```

#### **5.2.5. supportedSASLMechanisms**

The values of this attribute are the names of supported SASL mechanisms which the server supports. If the server does not support any mechanisms this attribute will be absent.

```
( 1.3.6.1.4.1.1466.101.120.14 NAME 'supportedSASLMechanisms'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.15' USAGE dSAOperation )
```

#### **5.2.6. supportedLDAPVersion**

The values of this attribute are the versions of the LDAP protocol which the server implements.

```
( 1.3.6.1.4.1.1466.101.120.15 NAME 'supportedLDAPVersion'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.27' USAGE dSAOperation )
```

### **5.3. LDAP Subschema Attribute**

This attribute is typically located in the subschema entry.

#### **5.3.1. ldapSyntaxes**

Servers MAY use this attribute to list the syntaxes which are implemented. Each value corresponds to one syntax.

```
( 1.3.6.1.4.1.1466.101.120.16 NAME 'ldapSyntaxes'  
  EQUALITY objectIdentifierFirstComponentMatch
```

```
SYNTAX '1.3.6.1.4.1.1466.115.121.1.54' USAGE directoryOperation )
```

## **6. Syntaxes**

Servers SHOULD recognize all the syntaxes described in this section. Each syntax begins with a sample value of the ldapSyntaxes attribute which defines the OBJECT IDENTIFIER of the syntax. The descriptions of syntax names are not carried in protocol, and are not guaranteed to be unique.

### **6.1. Attribute Type Description**

```
( 1.3.6.1.4.1.1466.115.121.1.3 DESC 'Attribute Type Description' )
```

Values in this syntax are encoded according to the BNF given at the start of [section 4.2](#). For example,

```
( 2.5.4.0 NAME 'objectClass'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.38' )
```

### **6.2. Binary**

```
( 1.3.6.1.4.1.1466.115.121.1.5 DESC 'Binary' )
```

Values in this syntax are encoded as described in [section 4.2.1](#).

### **6.3. Bit String**

```
( 1.3.6.1.4.1.1466.115.121.1.6 DESC 'Bit String' )
```

Values in this syntax are encoded according to the following BNF:

```
bitstring = "'" *binary-digit "'"B"
```

```
binary-digit = "0" / "1"
```

Example:

```
'0101111101'B
```

### **6.4. Boolean**

```
( 1.3.6.1.4.1.1466.115.121.1.7 DESC 'Boolean' )
```

Values in this syntax are encoded according to the following BNF:

```
boolean = "TRUE" / "FALSE"
```

Boolean values have an encoding of "TRUE" if they are logically true, and have an encoding of "FALSE" otherwise.

#### **6.5. Certificate**

( 1.3.6.1.4.1.1466.115.121.1.8 DESC 'Certificate' )

Because of the changes from X.509(1988) and X.509(1993) and additional changes to the ASN.1 definition to support certificate extensions, no string representation is defined, and values in this syntax MUST only be transferred using the binary encoding, by requesting or returning the attributes with descriptions "userCertificate;binary" or "caCertificate;binary". The BNF notation in [RFC 1778](#) for "User Certificate" is not recommended to be used.

#### **6.6. Certificate List**

( 1.3.6.1.4.1.1466.115.121.1.9 DESC 'Certificate List' )

Because of the incompatibility of the X.509(1988) and X.509(1993) definitions of revocation lists, values in this syntax MUST only be transferred using a binary encoding, by requesting or returning the attributes with descriptions "certificateRevocationList;binary" or "authorityRevocationList;binary". The BNF notation in [RFC 1778](#) for "Authority Revocation List" is not recommended to be used.

#### **6.7. Certificate Pair**

( 1.3.6.1.4.1.1466.115.121.1.10 DESC 'Certificate Pair' )

Because the Certificate is being carried in binary, values in this syntax MUST only be transferred using a binary encoding, by requesting or returning the attribute description "crossCertificatePair;binary". The BNF notation in [RFC 1778](#) for "Certificate Pair" is not recommended to be used.

#### **6.8. Country String**

( 1.3.6.1.4.1.1466.115.121.1.11 DESC 'Country String' )

A value in this syntax is encoded the same as a value of Directory String syntax. Note that this syntax is limited to values of exactly two printable string characters.

CountryString = p p

Example:

US

## **6.9. DN**

( 1.3.6.1.4.1.1466.115.121.1.12 DESC 'DN' )

Values in the Distinguished Name syntax are encoded to have the representation defined in [5]. Note that this representation is not reversible to an ASN.1 encoding used in X.500 for Distinguished Names, as the CHOICE of any DirectoryString element in an RDN is no longer known.

Examples (from [5]):

```
CN=Steve Kille,O=Isode Limited,C=GB
OU=Sales+CN=J. Smith,O=Widget Inc.,C=US
CN=L. Eagle,O=Sue\, Grabbit and Runn,C=GB
CN=Before\0DAfter,O=Test,C=GB
1.3.6.1.4.1.1466.0=#04024869,O=Test,C=GB
SN=Lu\C4\8Di\C4\87
```

## **6.10. Directory String**

( 1.3.6.1.4.1.1466.115.121.1.15 DESC 'Directory String' )

A string in this syntax is encoded in the UTF-8 form of ISO 10646 (a superset of Unicode). Servers and clients MUST be prepared to receive encodings of arbitrary Unicode characters, including characters not presently assigned to any character set.

For characters in the PrintableString form, the value is encoded as the string value itself.

If it is of the TeletexString form, then the characters are transliterated to their equivalents in UniversalString, and encoded in UTF-8 [9].

If it is of the UniversalString or BMPString forms [10], UTF-8 is used to encode them.

Note: the form of DirectoryString is not indicated in protocol unless the attribute value is carried in binary. Servers which convert to DAP MUST choose an appropriate form. Servers MUST NOT reject values merely because they contain legal Unicode characters outside of the range of printable ASCII.

Example:

This is a string of DirectoryString containing #!%#@

Wahl, Coulbeck, Howes, Kille LDAPv3 Attribute Syntax Defns. Page 15

INTERNET-DRAFT [draft-ietf-asid-ldapv3-attributes-05.txt](#) June 1997

#### **6.11. DIT Content Rule Description**

( 1.3.6.1.4.1.1466.115.121.1.16 DESC 'DIT Content Rule Description' )

Values in this syntax are encoded according to the following BNF.  
Implementors should note that future versions of this document  
may have expanded this BNF to include additional terms.

```
DITContentRuleDescription = "("  
    numericoid ; Structural ObjectClass identifier  
    [ "NAME" qdescrs ]  
    [ "DESC" qdstring ]  
    [ "OBSOLETE" ]  
    [ "AUX" oids ] ; Auxiliary ObjectClasses  
    [ "MUST" oids ] ; AttributeType identifiers  
    [ "MAY" oids ] ; AttributeType identifiers  
    [ "NOT" oids ] ; AttributeType identifiers  
    ")"
```

#### **6.12. Facsimile Telephone Number**

( 1.3.6.1.4.1.1466.115.121.1.22 DESC 'Facsimile Telephone Number' )

Values in this syntax are encoded according to the following BNF:

```
fax-number = printablestring [ "$" faxparameters ]  
  
faxparameters = faxparm / ( faxparm "$" faxparameters )  
  
faxparm = "twoDimensional" / "fineResolution" /  
    "unlimitedLength" /  
    "b4Length" / "a3Width" / "b4Width" / "uncompressed"
```

In the above, the first printablestring is the actual fax number,  
and the faxparm tokens represent fax parameters.

#### **6.13. Fax**

( 1.3.6.1.4.1.1466.115.121.1.23 DESC 'Fax' )

Values in this syntax are encoded as if they were octet strings containing Group 3 Fax images as defined in [7].

#### **6.14. Generalized Time**

( 1.3.6.1.4.1.1466.115.121.1.24 DESC 'Generalized Time' )

Values in this syntax are encoded as printable strings, represented as specified in X.208. Note that the time zone must be specified. It is strongly recommended that GMT time be used. For example,

199412161032Z

Wahl, Coulbeck, Howes, Kille    LDAPv3 Attribute Syntax Defns.    Page 16

INTERNET-DRAFT    [draft-ietf-asid-ldapv3-attributes-05.txt](#)    June 1997

#### **6.15. IA5 String**

( 1.3.6.1.4.1.1466.115.121.1.26 DESC 'IA5 String' )

The encoding of a value in this syntax is the string value itself.

#### **6.16. INTEGER**

( 1.3.6.1.4.1.1466.115.121.1.27 DESC 'INTEGER' )

Values in this syntax are encoded as the decimal representation of their values, with each decimal digit represented by the its character equivalent. So the number 1321 is represented by the character string "1321".

#### **6.17. JPEG**

( 1.3.6.1.4.1.1466.115.121.1.28 DESC 'JPEG' )

Values in this syntax are encoded as strings containing JPEG images in the JPEG File Interchange Format (JFIF), as described in [8].

#### **6.18. Matching Rule Description**

( 1.3.6.1.4.1.1466.115.121.1.30 DESC 'Matching Rule Description' )

Values of type matchingRules are encoded as strings according to the BNF given in [section 4.4](#).

#### **6.19. Matching Rule Use Description**

( 1.3.6.1.4.1.1466.115.121.1.31 DESC 'Matching Rule Use Description' )

Values of type `matchingRuleUse` are encoded as strings according to the BNF given in [section 4.4](#).

#### **6.20. MHS OR Address**

( 1.3.6.1.4.1.1466.115.121.1.33 DESC 'MHS OR Address' )

Values in this syntax are encoded as strings, according to the format defined in [\[11\]](#).

#### **6.21. Name And Optional UID**

( 1.3.6.1.4.1.1466.115.121.1.34 DESC 'Name And Optional UID' )

Values in this syntax are encoded according to the following BNF:

```
NameAndOptionalUID = DistinguishedName [ "#" bitstring ]
```

Although the '#' character may occur in a string representation of a distinguished name, no additional special quoting is done.

This syntax has been added subsequent to [RFC 1778](#).

Wahl, Coulbeck, Howes, Kille    LDAPv3 Attribute Syntax Defns.    Page 17

INTERNET-DRAFT    [draft-ietf-asid-ldapv3-attributes-05.txt](#)    June 1997

Example:

```
1.3.6.1.4.1.1466.0=#04024869,0=Test,C=GB#'0101'B
```

#### **6.22. Name Form Description**

( 1.3.6.1.4.1.1466.115.121.1.35 DESC 'Name Form Description' )

Values in this syntax are encoded according to the following BNF. Implementors should note that future versions of this document may have expanded this BNF to include additional terms.

```
NameFormDescription = "(" whsp
    numericoid whsp ; NameForm identifier
    [ "NAME" qdescrs ]
    [ "DESC" qdstring ]
    [ "OBSOLETE" whsp ]
    "OC" woid          ; Structural ObjectClass
    "MUST" oids         ; AttributeTypes
    [ "MAY" oids ]     ; AttributeTypes
whsp ")"
```

### **6.23. Numeric String**

```
( 1.3.6.1.4.1.1466.115.121.1.36 DESC 'Numeric String' )
```

The encoding of a string in this syntax is the string value itself.  
Example:

```
1997
```

### **6.24. Object Class Description**

```
( 1.3.6.1.4.1.1466.115.121.1.37 DESC 'Object Class Description' )
```

Values in this syntax are encoded according to the BNF in [section 4.3](#).

### **6.25. OID**

```
( 1.3.6.1.4.1.1466.115.121.1.38 DESC 'OID' )
```

Values in the Object Identifier syntax are encoded according to the BNF in [section 4.1](#) for "oid".

Example:

```
1.2.3.4  
cn
```

### **6.26. Other Mailbox**

```
( 1.3.6.1.4.1.1466.115.121.1.39 DESC 'Other Mailbox' )
```

Values in this syntax are encoded according to the following BNF:

```
otherMailbox = mailbox-type "$" mailbox  
  
mailbox-type = printablestring  
  
mailbox = <an encoded IA5 String>
```

In the above, mailbox-type represents the type of mail system in which the mailbox resides, for example "MCIMail"; and mailbox is the actual mailbox in the mail system defined by mailbox-type.

### **6.27. Postal Address**

```
( 1.3.6.1.4.1.1466.115.121.1.41 DESC 'Postal Address' )
```

Values in this syntax are encoded according to the following BNF:

```
postal-address = dstring *( "$" dstring )
```

In the above, each dstring component of a postal address value is encoded as a value of type Directory String syntax. Backslashes and dollar characters, if they occur in the component, are quoted as described in [section 4.2](#).

Example:

```
1234 Main St.$Anytown, CA 12345$USA  
\241,000,000 Sweepstakes$PO Box 1000000$Anytown, CA 12345$USA
```

### **6.28. Presentation Address**

```
( 1.3.6.1.4.1.1466.115.121.1.43 DESC 'Presentation Address' )
```

Values in this syntax are encoded with the representation described in [RFC 1278](#) [6].

### **6.29. Printable String**

```
( 1.3.6.1.4.1.1466.115.121.1.44 DESC 'Printable String' )
```

The encoding of a value in this syntax is the string value itself. PrintableString is limited to the characters in production p of [section 4.1](#).

Example:

```
This is a PrintableString
```

### **6.30. Telephone Number**

```
( 1.3.6.1.4.1.1466.115.121.1.50 DESC 'Telephone Number' )
```

Values in this syntax are encoded as if they were Printable String types. Telephone numbers are recommended in X.520 to be in international form.

Example:

```
+1 512 305 0280
```

### **6.31. UTC Time**

```
( 1.3.6.1.4.1.1466.115.121.1.53 DESC 'UTC Time' )
```

Values in this syntax are encoded as if they were printable strings with the strings containing a UTCTime value. This is historical; new attribute definitions SHOULD use GeneralizedTime instead.

### **6.32. LDAP Syntax Description**

```
( 1.3.6.1.4.1.1466.115.121.1.54 DESC 'LDAP Syntax Description' )
```

Values in this syntax are encoded according to the BNF in [section 4.2.3](#).

## **7. Object Classes**

Servers SHOULD recognize all the names of standard classes from section 7 of [\[12\]](#).

### **7.1. Extensible Object Class**

The extensibleObject object class, if present in an entry, permits that entry to optionally hold any attribute. The MAY attribute list of this class is implicitly the set of all attributes.

```
( 1.3.6.1.4.1.1466.101.120.111 NAME 'extensibleObject'  
  SUP top AUXILIARY )
```

The mandatory attributes of the other object classes of this entry are still required to be present.

Note that not all servers will implement this object class, and those which do not will reject requests to add entries which contain this object class, or modify an entry to add this object class.

## **8. Matching Rules**

Servers which implement the extensibleMatch filter SHOULD allow all the matching rules listed in this section to be used in the extensibleMatch. In general these servers SHOULD allow matching rules to be used with all attribute types known to the server, when the assertion syntax of the matching rule is the same as the value syntax of the attribute.

Servers MAY implement additional matching rules.

### **8.1. Matching Rules used in Equality Filters**

Servers SHOULD be capable of performing the following matching rules.

For all these rules, the assertion syntax is the same as the value syntax.

```
( 2.5.13.0 NAME 'objectIdentifierMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.38' )
```

```
( 2.5.13.1 NAME 'distinguishedNameMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.12' )
```

```
( 2.5.13.2 NAME 'caseIgnoreMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.15' )
```

```
( 2.5.13.8 NAME 'numericStringMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.36' )
```

```
( 2.5.13.11 NAME 'caseIgnoreListMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.41' )
```

```
( 2.5.13.14 NAME 'integerMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.27' )
```

```
( 2.5.13.16 NAME 'bitStringMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.6' )
```

```
( 2.5.13.20 NAME 'telephoneNumberMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.50' )
```

```
( 2.5.13.22 NAME 'presentationAddressMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.43' )
```

```
( 2.5.13.23 NAME 'uniqueMemberMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.34' )
```

```
( 2.5.13.24 NAME 'protocolInformationMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.42' )
```

```
( 2.5.13.27 NAME 'generalizedTimeMatch'  
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.24' )
```

```
( 1.3.6.1.4.1.1466.109.114.1 NAME 'caseExactIA5Match'
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.26' )
```

```
( 1.3.6.1.4.1.1466.109.114.2 NAME 'caseIgnoreIA5Match'
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.26' )
```

When performing the caseIgnoreMatch, caseIgnoreListMatch, telephoneNumberMatch, caseExactIA5Match and caseIgnoreIA5Match, multiple adjoining whitespace characters are treated the same as an individual space, and leading and trailing whitespace is ignored.

## **8.2. Matching Rules used in Inequality Filters**

Servers SHOULD be capable of performing the following matching rules, which are used in greaterOrEqual and lessOrEqual filters.

```
( 2.5.13.28 NAME 'generalizedTimeOrderingMatch'
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.24' )
```

```
( 2.5.13.3 NAME 'caseIgnoreOrderingMatch'
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.15' )
```

## **8.3. Matching Rules for Subschema Attributes**

Servers which allow subschema entries to be modified by clients MUST support the following matching rule, as it is the equality matching rule for several of the subschema attributes.

```
( 2.5.13.30 NAME 'objectIdentifierFirstComponentMatch'
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.38' )
```

Implementors should note that the assertion syntax of this matching rule, an OID, is different from the value syntax of attributes for which this is the equality matching rule.

## **9. Security Considerations**

### **9.1. Disclosure**

Attributes of directory entries are used to provide descriptive information about the real-world objects they represent, which can be people, organizations or devices. Most countries have privacy laws regarding the publication of information about people.

### **9.2. Use of Attribute Values in Security Applications**

The transformations of an AttributeValue value from its X.501 form to an LDAP string representation are not always reversible back to the same BER or DER form. An example of a situation which requires the DER form of a distinguished name is the verification of an X.509 certificate.

Wahl, Coulbeck, Howes, Kille    LDAPv3 Attribute Syntax Defns.    Page 22

INTERNET-DRAFT    [draft-ietf-asid-ldapv3-attributes-05.txt](#)    June 1997

For example, a distinguished name consisting of one RDN with one AVA, in which the type is commonName and the value is of the TeletexString choice with the letters 'Sam' would be represented in LDAP as the string CN=Sam. Another distinguished name in which the value is still 'Sam' but of the PrintableString choice would have the same representation CN=Sam.

Applications which require the reconstruction of the DER form of the value SHOULD NOT use the string representation of attribute syntaxes when converting a value to LDAP format. Instead it SHOULD use the Binary syntax.

## **10. Acknowledgements**

This document is based substantially on [RFC 1778](#), written by Tim Howes, Steve Kille, Wengyik Yeong and Colin Robbins.

Many of the attribute syntax encodings defined in this and related documents are adapted from those used in the QUIPU and the IC R3 X.500 implementations. The contributions of the authors of both these implementations in the specification of syntaxes are gratefully acknowledged.

## **11. Authors Addresses**

Mark Wahl  
Critical Angle Inc.  
4815 West Braker Lane #502-385  
Austin, TX 78759  
USA

EMail: [M.Wahl@critical-angle.com](mailto:M.Wahl@critical-angle.com)

Andy Coulbeck  
Isode Limited  
The Dome, The Square  
Richmond TW9 1DT  
United Kingdom

Phone: +44 181-332-9091  
EMail: A.Coulbeck@isode.com

Tim Howes  
Netscape Communications Corp.  
501 E. Middlefield Rd  
Mountain View, CA 94043  
USA

Phone: +1 415 254-1900  
EMail: howes@netscape.com

Wahl, Coulbeck, Howes, Kille LDAPv3 Attribute Syntax Defns. Page 23

INTERNET-DRAFT [draft-ietf-asid-ldapv3-attributes-05.txt](#) June 1997

Steve Kille  
Isode Limited  
The Dome, The Square  
Richmond  
TW9 1DT  
UK

Phone: +44-181-332-9091  
EMail: S.Kille@isode.com

## **[12. Bibliography](#)**

- [1] M. Wahl, T. Howes, S. Kille, "Lightweight Directory Access Protocol (Version 3)", INTERNET-DRAFT  
<[draft-ietf-asid-ldapv3-protocol-05.txt](#)>, June 1997.
- [2] The Directory: Selected Attribute Types. ITU-T Recommendation X.520, 1993.
- [3] The Directory: Models. ITU-T Recommendation X.501, 1993.
- [4] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#).
- [5] M. Wahl, S. Kille, "A UTF-8 String Representation of Distinguished Names", INTERNET-DRAFT  
<[draft-ietf-asid-ldapv3-dn-03.txt](#)>, April 1997.
- [6] S. Kille, "A String Representation for Presentation Addresses", [RFC 1278](#), University College London, November 1991.

- [7] Terminal Equipment and Protocols for Telematic Services - Standardization of Group 3 facsimile apparatus for document transmission. CCITT, Recommendation T.4.
- [8] JPEG File Interchange Format (Version 1.02). Eric Hamilton, C-Cube Microsystems, Milpitas, CA, September 1, 1992.
- [9] F. Yergeau, "UTF-8, a transformation format of Unicode and ISO 10646", [RFC 2044](#), October 1996.
- [10] Universal Multiple-Octet Coded Character Set (UCS) - Architecture and Basic Multilingual Plane, ISO/IEC 10646-1 : 1993 (With amendments).
- [11] S. Hardcastle-Kille, "Mapping between X.400(1988) / ISO 10021 and [RFC 822](#)", [RFC 1327](#), May 1992.
- [12] M. Wahl, "X.500(93) User Schema for use with LDAP", INTERNET-DRAFT <[draft-ietf-asid-ldapv3schema-x500-01.txt](#)>, June 1997.
- [13] D. Crocker, "Standard of the Format of ARPA-Internet Text Messages", STD 11, [RFC 822](#), August 1982.

<[draft-ietf-asid-ldapv3-attributes-05.txt](#)> Expires: November 1997

Wahl, Coulbeck, Howes, Kille    LDAPv3 Attribute Syntax Defns.    Page 24