

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: March 28, 2011

X. Marjou  
A. Sollaud  
France Telecom Orange  
September 24, 2010

**Application Mechanism for keeping alive the Network Address Translator  
(NAT) mappings associated to RTP flows.  
draft-ietf-avt-app-rtp-keepalive-09**

**Abstract**

This document lists the different mechanisms that enable applications using Real-time Transport Protocol (RTP) to maintain their RTP Network Address Translator (NAT) mappings alive. It also makes a recommendation for a preferred mechanism. This document is not applicable to Interactive Connectivity Establishment (ICE) agents.

**Status of this Memo**

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 28, 2011.

**Copyright Notice**

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as

described in the Simplified BSD License.

## Table of Contents

|                       |   |                    |
|-----------------------|---|--------------------|
| <a href="#">1.</a>    | Introduction . . . . .                                      | <a href="#">3</a>  |
| <a href="#">2.</a>    | Terminology . . . . .                                       | <a href="#">4</a>  |
| <a href="#">3.</a>    | Requirements . . . . .                                      | <a href="#">4</a>  |
| <a href="#">4.</a>    | List of Alternatives for Performing RTP Keepalive . . . . . | <a href="#">5</a>  |
| <a href="#">4.1.</a>  | Transport Packet of 0-byte . . . . .                        | <a href="#">5</a>  |
| <a href="#">4.2.</a>  | RTP Packet with Comfort Noise Payload . . . . .             | <a href="#">5</a>  |
| <a href="#">4.3.</a>  | RTCP Packets Multiplexed with RTP Packets . . . . .         | <a href="#">6</a>  |
| <a href="#">4.4.</a>  | STUN Indication Packet . . . . .                            | <a href="#">6</a>  |
| <a href="#">4.5.</a>  | RTP Packet with Incorrect Version Number . . . . .          | <a href="#">6</a>  |
| <a href="#">4.6.</a>  | RTP Packet with Unknown Payload Type . . . . .              | <a href="#">6</a>  |
| <a href="#">5.</a>    | Recommended Solution for Keepalive Mechanism . . . . .      | <a href="#">7</a>  |
| <a href="#">6.</a>    | Media Format Exceptions . . . . .                           | <a href="#">7</a>  |
| <a href="#">7.</a>    | Timing and Transport Considerations . . . . .               | <a href="#">7</a>  |
| <a href="#">8.</a>    | Security Considerations . . . . .                           | <a href="#">8</a>  |
| <a href="#">9.</a>    | IANA Considerations . . . . .                               | <a href="#">8</a>  |
| <a href="#">10.</a>   | Acknowledgements . . . . .                                  | <a href="#">8</a>  |
| <a href="#">11.</a>   | References . . . . .  | <a href="#">8</a>  |
| <a href="#">11.1.</a> | Normative references . . . . .                              | <a href="#">8</a>  |
| <a href="#">11.2.</a> | Informative references . . . . .                            | <a href="#">9</a>  |
|                       | Authors' Addresses . . . . .                                | <a href="#">10</a> |



## 1. Introduction

Documents [[RFC4787](#)] and [[RFC5382](#)] describe Network Address Translator (NAT) behaviors and point out that two key aspects of NAT are mappings (a.k.a. bindings) and keeping them refreshed. This introduces a derived requirement for applications engaged in a multimedia session involving NAT traversal: they need to generate a minimum of flow activity in order to create NAT mappings and maintain them.

When applied to applications using the real-time transport protocol (RTP) [[RFC3550](#)], the RTP media stream packets themselves normally fulfill this requirement. However there exist some cases where RTP does not generate the minimum required flow activity.

The examples are:

- o In some RTP usages, such as the Session Initiation Protocol (SIP) [[RFC3550](#)], agents can negotiate a unidirectional media stream by using the Session Description Protocol (SDP) [[RFC4566](#)] "recvonly" attribute on one agent and "sendonly" on the peer, as defined in [[RFC3264](#)]. [[RFC3264](#)] directs implementations not to transmit media on the receiving agent. In case the agent receiving the media is located in the private side of a NAT, it will never receive RTP packets from the public peer if the NAT mapping has not been created.
- o Similarly, a bidirectional media stream can be "put on hold". This is accomplished by using the SDP "sendonly" or "inactive" attributes. Again [[RFC3264](#)] directs implementations to cease transmission of media in these cases. However, doing so may cause NAT bindings to timeout, and media won't be able to come off hold.
- o Some RTP payload formats, such as the payload format for text conversation [[RFC4103](#)], may send packets so infrequently that the interval exceeds the NAT binding timeouts.

To solve these problems, an agent therefore needs to periodically send keepalive data within the outgoing RTP session of an RTP media stream regardless of whether the media stream is currently inactive, sendonly, recvonly or sendrecv, and regardless of the presence or value of the bandwidth attribute.

It is important to note that the above examples also require the agents to use symmetric RTP [[RFC4961](#)] in addition to RTP keepalive.

This document first states the requirements that must be supported to perform RTP keepalives ([Section 3](#)). In a second step, the document



reports the different mechanisms to overcome this problem ([Section 4](#)). [Section 5](#) finally states the recommended solution for RTP keepalive.

This document is not applicable to Interactive Connectivity Establishment (ICE) [[RFC5245](#)] agents. Indeed, the ICE protocol together with Session Traversal Utilities for NAT (STUN) [[RFC5389](#)] and Traversal Using Relays around NAT (TURN) [[RFC5766](#)] solve the overall Network Address Translator (NAT) traversal mechanism of media streams. In the context of RTP media streams, some agents may not require all ICE functionalities and may only need a keepalive mechanism. This document thus applies to such agents, and does not apply to agents implementing ICE.

The scope of the draft is also limited to RTP flows. In particular, this document does not address keepalive activity related to:

- o Session signaling flows, such as the Session Initiation Protocol (SIP).
- o RTP Control Protocol (RTCP) flows.  
Recall that [[RFC3550](#)] recommends a minimum interval of 5 seconds and that "on hold" procedures of [[RFC3264](#)] do not impact RTCP transmissions. Therefore, when in use, there is always some RTCP flow activity.

Note that if a given media uses a codec that already integrates a keepalive mechanism, no additional keepalive mechanism is required at the RTP level.

As mentionned in [Section 3.5 of \[RFC5405\]](#) "It is important to note that keep-alive messages are NOT RECOMMENDED for general use -- they are unnecessary for many applications and can consume significant amounts of system and network resources."

## **[2.](#) Terminology**

In this document, the key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

## **[3.](#) Requirements**

This section outlines the key requirements that need to be satisfied in order to provide RTP media keepalive.



- REQ-1 Some data is sent periodically within the outgoing RTP session for the whole duration of the RTP media stream.
- REQ-2 Any type of transport (e.g. UDP, TCP) MUST be supported.
- REQ-3 Any media type (e.g. audio, video, text) MUST be supported.
- REQ-4 Any media format (e.g. G.711, H.263) MUST be supported.
- REQ-5 Session signaling protocols SHOULD NOT be impacted.
- REQ-6 Impacts on existing software SHOULD be minimized.
- REQ-7 Remote peer SHOULD NOT be impacted.
- REQ-8 The support for RTP keepalive SHOULD be described in the SDP.
- REQ-9 The solution SHOULD cover the integration with RTCP.

#### **4. List of Alternatives for Performing RTP Keepalive**

This section lists, in no particular order, some alternatives that can be used to perform a keepalive message within RTP media streams.

##### **4.1. Transport Packet of 0-byte**

The application sends an empty transport packet (e.g. UDP packet, DCCP packet).

Cons:

- o This alternative is specific to each transport protocol.

##### **4.2. RTP Packet with Comfort Noise Payload**

The application sends an RTP packet with a comfort-noise payload [[RFC3389](#)].

Cons:

- o This alternative is limited to audio formats only.
- o Comfort Noise needs to be supported by the remote peer.
- o Comfort Noise needs to be signalled in SDP offer/answer.
- o The peer is likely to render comfort noise at the other side, so the content of the payload (the noise level) needs to be carefully chosen.





#### **4.3. RTCP Packets Multiplexed with RTP Packets**

The application sends RTCP packets in the RTP media path itself (i.e. same tuples for both RTP and RTCP packets) [[RFC5761](#)]. RTCP packets therefore maintain the NAT mappings open.

Cons:

- o Multiplexing RTP and RTCP must be supported by the remote peer.
- o Some RTCP monitoring tools expect that RTCP packets are not multiplexed.

#### **4.4. STUN Indication Packet**

The application sends a STUN [[RFC5389](#)] Binding Indication packet as specified in ICE [[RFC5245](#)].

Thanks to the RTP validity check, STUN packets will be ignored by the RTP stack.

Cons:

- o The sending agent needs to support STUN.

#### **4.5. RTP Packet with Incorrect Version Number**

The application sends an RTP packet with an incorrect version number, which value is zero.

Based on RTP specification [[RFC3550](#)], the peer should perform a header validity check, and therefore ignore these types of packet.

Cons:

- o Only four version numbers are possible. Using one of them for RTP keepalive would be wasteful.
- o [[RFC4566](#)] and [[RFC3264](#)] mandate not to send media with inactive and recvonly attributes, however this is mitigated as no real media is sent with this mechanism.

#### **4.6. RTP Packet with Unknown Payload Type**

The application sends an RTP packet of 0 length with a dynamic payload type that has not been negotiated by the peers (e.g. not negotiated within the SDP offer/answer, and thus not mapped to any media format).

The sequence number is incremented by one for each packet, as it is sent within the same RTP session as the actual media. The timestamp contains the same value a media packet would have at this time. The marker bit is not significant for the keepalive packets and is thus



set to zero.

The SSRC is the same as for the media for which keepalive is sent.

Normally the peer will ignore this packet, as RTP [[RFC3550](#)] states that "a receiver MUST ignore packets with payload types that it does not understand".

Cons:

- o [[RFC4566](#)] and [[RFC3264](#)] mandate not to send media with inactive and recvonly attributes, however this is mitigated as no real media is sent with this mechanism.
- o [[RFC3550](#)] does not preclude examination of received packets by the peer in an attempt to determine if it is under attack.
- o The statement "RTP Packet with Unknown Payload Type" of [RFC3550](#) is not always observed in real life.

## **5. Recommended Solution for Keepalive Mechanism**

The RECOMMENDED mechanism is the "RTCP packets multiplexed with RTP packets" ([Section 4.3](#)). This mechanism is desirable because it reduces the number of ports when RTP and RTCP are used. It also has the advantage of taking into account RTCP aspects, which is not the case of other mechanisms.

Other mechanisms ([Section 4.1](#), [Section 4.2](#), [Section 4.4](#), [Section 4.5](#), [Section 4.6](#)) are NOT RECOMMENDED.

## **6. Media Format Exceptions**

When a given media format does not allow the keepalive solution recommended in [Section 5](#), an alternative mechanism SHOULD be defined in the payload format specification for this media format.

## **7. Timing and Transport Considerations**

An application supporting this specification MUST transmit either keepalive packets or media packets at least once every  $T_r$  seconds during the whole duration of the media session.

$T_r$  has different value according to the transport protocol

For UDP, the minimum RECOMMENDED  $T_r$  value is 15 seconds, and  $T_r$  SHOULD be configurable to larger values.



For TCP, the recommended Tr value is 7200 seconds.

When using the "RTCP packets multiplexed with RTP packets" solution for keepalive, Tr MUST comply with the RTCP timing rules of [\[RFC3550\]](#).

Keepalive packets within a particular RTP session MUST use the tuple (source IP address, source TCP/UDP ports, target IP address, target TCP/UDP Port) of the regular RTP packets.

The agent SHOULD only send RTP keepalive when it does not send regular RTP packets.

## **[8.](#) Security Considerations**

The RTP keepalive packets are sent on the same path as regular RTP media packets and may be perceived as an attack by a peer. However, [\[RFC3550\]](#) mandates a peer to "ignore packets with payload types that it does not understand". A peer that does not understand the keepalive message will thus appropriately drop the received packets.

## **[9.](#) IANA Considerations**

None.

## **[10.](#) Acknowledgements**

Jonathan Rosenberg provided the major inputs for this draft via the ICE specification. In addition, thanks to Alfred E. Heggstad, Colin Perkins, Dan Wing, Gunnar Hellstrom, Hadriel Kaplan, Magnus Westerlund, Randell Jesup, Remi Denis-Courmont, Robert Sparks, and Steve Casner for their useful inputs and comments.

## **[11.](#) References**

### **[11.1.](#) Normative references**

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, [RFC 3550](#), July 2003.



- [RFC4961] Wing, D., "Symmetric RTP / RTP Control Protocol (RTCP)", [BCP 131](#), [RFC 4961](#), July 2007.
- [RFC5405] Eggert, L. and G. Fairhurst, "Unicast UDP Usage Guidelines for Application Designers", [BCP 145](#), [RFC 5405](#), November 2008.
- [RFC5761] Perkins, C. and M. Westerlund, "Multiplexing RTP Data and Control Packets on a Single Port", [RFC 5761](#), April 2010.

### **11.2. Informative references**

- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.
- [RFC3264] Rosenberg, J. and H. Schulzrinne, "An Offer/Answer Model with Session Description Protocol (SDP)", [RFC 3264](#), June 2002.
- [RFC3389] Zopf, R., "Real-time Transport Protocol (RTP) Payload for Comfort Noise (CN)", [RFC 3389](#), September 2002.
- [RFC4103] Hellstrom, G. and P. Jones, "RTP Payload for Text Conversation", [RFC 4103](#), June 2005.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), July 2006.
- [RFC4787] Audet, F. and C. Jennings, "Network Address Translation (NAT) Behavioral Requirements for Unicast UDP", [BCP 127](#), [RFC 4787](#), January 2007.
- [RFC5245] Rosenberg, J., "Interactive Connectivity Establishment (ICE): A Protocol for Network Address Translator (NAT) Traversal for Offer/Answer Protocols", [RFC 5245](#), April 2010.
- [RFC5382] Guha, S., Biswas, K., Ford, B., Sivakumar, S., and P. Srisuresh, "NAT Behavioral Requirements for TCP", [BCP 142](#), [RFC 5382](#), October 2008.
- [RFC5389] Rosenberg, J., Mahy, R., Matthews, P., and D. Wing, "Session Traversal Utilities for NAT (STUN)", [RFC 5389](#), October 2008.
- [RFC5766] Mahy, R., Matthews, P., and J. Rosenberg, "Traversal Using





Relays around NAT (TURN): Relay Extensions to Session  
Traversal Utilities for NAT (STUN)", [RFC 5766](#), April 2010.

Authors' Addresses

Xavier Marjou  
France Telecom Orange  
2, avenue Pierre Marzin  
Lannion 22307  
France

Email: [xavier.marjou@orange-ftgroup.com](mailto:xavier.marjou@orange-ftgroup.com)

Aurelien Sollaud  
France Telecom Orange  
2, avenue Pierre Marzin  
Lannion 22307  
France

Email: [aurelien.sollaud@orange-ftgroup.com](mailto:aurelien.sollaud@orange-ftgroup.com)

