Network Working Group INTERNET-DRAFT Obsoletes: <u>3119</u> Category: Standards Track Expires: February 28, 2008 Ross Finlayson Live Networks, Inc. August 28, 2007

A More Loss-Tolerant RTP Payload Format for MP3 Audio <<u>draft-ietf-avt-rfc3119bis-05.txt</u>>

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with <u>Section 6 of</u> BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress.

The list of current Internet-Drafts can be accessed at http://www.ietf.org/ietf/lid-abstracts.txt

The list of Internet-Draft Shadow Directories can be accessed at http://www.ietf.org/shadow.html

Abstract

This document describes a RTP (Real-Time Protocol) payload format for transporting MPEG (Moving Picture Experts Group) 1 or 2, layer III audio (commonly known as "MP3"). This format is an alternative to that described in <u>RFC 2250</u>, and performs better if there is packet loss. (This document updates (and obsoletes) <u>RFC 3119</u>, correcting typographical errors in the "SDP usage" section and pseudo-code appendices.)

Table of Contents

- 1. Terminology
- 2. Introduction
- 3. The Structure of MP3 Frames
- 4. A New Payload Format
 - 4.1 ADU frames
 - 4.2 ADU descriptors
 - 4.3 Packing rules

4.4 RTP header fields 4.5 Handling received data 5. Handling Multiple MPEG Audio Layers 6. Frame Packetizing and Depacketizing 7. ADU Frame Interleaving 8. IANA Considerations 9. SDP usage 10. Security Considerations 11. Acknowledgements 12. Normative References 13. Author's Address 14. IPR Notice 15. Copyright Notice Appendix A. Translating Between "MP3 Frames" and "ADU Frames" A.1 Converting a sequence of "MP3 Frames" to a sequence of "ADU Frames": A.2 Converting a sequence of "ADU Frames" to a sequence of "MP3 Frames":

<u>Appendix B</u>: Interleaving and Deinterleaving

B.1 Interleaving a sequence of "ADU Frames":

B.2 Deinterleaving a sequence of (interleaved) "ADU Frames":

<u>1</u>. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in <u>RFC 2119</u> [<u>1</u>].

2. Introduction

While the RTP payload format defined in RFC 2250 [2] is generally applicable to all forms of MPEG audio or video, it is sub-optimal for MPEG-1 or 2, layer III audio (commonly known as "MP3"). The reason for this is that an MP3 frame is not a true "Application Data Unit" it contains a back-pointer to data in earlier frames, and so cannot be decoded independently of these earlier frames. Because RFC 2250 defines that packet boundaries coincide with frame boundaries, it handles packet loss inefficiently when carrying MP3 data. The loss of an MP3 frame will render some data in previous (or future) frames useless, even if they are received without loss.

In this document we define an alternative RTP payload format for MP3 audio. This format uses a data-preserving rearrangement of the original MPEG frames, so that packet boundaries now coincide with true MP3 "Application Data Units", which can also (optionally) be rearranged in an interleaving pattern. This new format is therefore more data-efficient than <u>RFC 2250</u> in the face of packet loss.

3. The Structure of MP3 Frames

In this section we give a brief overview of the structure of a MP3 frame. (For more detailed description, see the MPEG-1 audio $[\underline{3}]$ and MPEG-2 audio $[\underline{4}]$ specifications.)

Each MPEG audio frame begins with a 4-byte header. Information defined by this header includes:

- Whether the audio is MPEG-1 or MPEG-2.
- Whether the audio is layer I, II, or III. (The remainder of this document assumes layer III, i.e., "MP3" frames)
- Whether the audio is mono or stereo.
- Whether or not there is a 2-byte CRC field following the header.
- (indirectly) The size of the frame.

The following structures appear after the header:

- (optionally) A 2-byte CRC field
- A "side info" structure. This has the following length:
 - 32 bytes for MPEG-1 stereo
 - 17 bytes for MPEG-1 mono, or for MPEG-2 stereo
 - 9 bytes for MPEG-2 mono
- Encoded audio data, plus optional ancillary data (filling out the rest of the frame)

For the purpose of this document, the "side info" structure is the most important, because it defines the location and size of the "Application Data Unit" (ADU) that an MP3 decoder will process. In particular, the "side info" structure defines:

- "main_data_begin": This is a back-pointer (in bytes) to the start of the ADU. The back-pointer is counted from the beginning of the frame, and counts only encoded audio data and any ancillary data (i.e., ignoring any header, CRC, or "side info" fields).

An MP3 decoder processes each ADU independently. The ADUs will generally vary in length, but their average length will, of course, be that of the of the MP3 frames (minus the length of the header, CRC, and "side info" fields). (In MPEG literature, this ADU is sometimes referred to as a "bit reservoir".)

<u>4</u>. A New Payload Format

As noted in [5], a payload format should be designed so that packet boundaries coincide with "codec frame boundaries" - i.e., with ADUS. In the <u>RFC 2250</u> payload format for MPEG audio [2], each RTP packet payload contains MP3 frames. In this new payload format for MP3 audio, however, each RTP packet payload contains "ADU frames", each preceded by an "ADU descriptor".

4.1 ADU frames

An "ADU frame" is defined as:

- The 4-byte MPEG header (the same as the original MP3 frame, except that the first 11 bits are (optionally) replaced by an "Interleaving Sequence Number", as described in section 7 below)
- The optional 2-byte CRC field (the same as the original MP3 frame)
- The "side info" structure (the same as the original MP3 frame)
- The complete sequence of encoded audio data (and any ancillary data) for the ADU (i.e., running from the start of this MP3 frame's "main_data_begin" back-pointer, up to the start of the next MP3 frame's back-pointer)

4.2 ADU descriptors

Within each RTP packet payload, each "ADU frame" is preceded by a 1 or 2-byte "ADU descriptor", which gives the size of the ADU, and indicates whether or not this packet's data is a continuation of the previous packet's data. (This occurs only when a single "ADU descriptor"+"ADU frame" is too large to fit within a RTP packet.)

An ADU descriptor consists of the following fields

- "C": Continuation flag (1 bit): 1 if the data following the ADU descriptor is a continuation of an ADU frame that was too large to fit within a single RTP packet; 0 otherwise.
- "T": Descriptor Type flag (1 bit):
 0 if this is a 1-byte ADU descriptor;
 1 if this is a 2-byte ADU descriptor.
- "ADU size" (6 or 14 bits):

The size (in bytes) of the ADU frame that will follow this ADU descriptor (i.e., NOT including the size of the descriptor itself). A 2-byte ADU descriptor (with a 14-bit "ADU size" field) is used for ADU frame sizes of 64 bytes or more. For smaller ADU frame sizes, senders MAY alternatively use a 1-byte ADU descriptor (with a 6-bit "ADU size" field). Receivers MUST be able to accept an ADU descriptor of either size.

Thus, a 1-byte ADU descriptor is formatted as follows:

and a 2-byte ADU descriptor is formatted as follows:

0

1

4.3 Packing rules

Each RTP packet payload begins with a "ADU descriptor", followed by "ADU frame" data. Normally, this "ADU descriptor"+"ADU frame" will fit completely within the RTP packet. In this case, more than one successive "ADU descriptor"+"ADU frame" MAY be packed into a single RTP packet, provided that they all fit completely.

If, however, a single "ADU descriptor"+"ADU frame" is too large to fit within an RTP packet, then the "ADU frame" is split across two or more successive RTP packets. Each such packet begins with an ADU descriptor. The first packet's descriptor has a "C" (continuation) flag of 0; the following packets' descriptors each have a "C" flag of 1. Each descriptor, in this case, has the same "ADU size" value: the size of the entire "ADU frame" (not just the portion that will fit within a single RTP packet). Each such packet (even the last one) contains only one "ADU descriptor".

4.4 RTP header fields

- Payload Type: The (static) payload type 14 that was defined for MPEG audio [6] MUST NOT be used. Instead, a different, dynamic payload type MUST be used - i.e., one in the range [96..127].
- M bit: This payload format defines no use for this bit. Senders SHOULD set this bit to zero in each outgoing packet.

Timestamp: This is a 32-bit 90 kHz timestamp, representing the presentation time of the first ADU packed within the packet.

4.5 Handling received data

Note that no information is lost by converting a sequence of MP3 frames to a corresponding sequence of "ADU frames", so a receiving RTP implementation can either feed the ADU frames directly to an appropriately modified MP3 decoder, or convert them back into a sequence of MP3 frames, as described in <u>appendix A.2</u> below.

5. Handling Multiple MPEG Audio Layers

The RTP payload format described here is intended only for MPEG-1 or 2, layer III audio ("MP3"). In contrast, layer I and layer II frames are self-contained, without a back-pointer to earlier frames. However, it is possible (although unusual) for a sequence of audio frames to consist of a mixture of layer III frames and layer I or II frames. When such a sequence is transmitted, only layer III frames are converted to ADUs; layer I or II frames are sent 'as is' (except for the prepending of an "ADU descriptor"). Similarly, the receiver of a sequence of frames - using this payload format - leaves layer I and II frames untouched (after removing the prepended "ADU descriptor), but converts layer III frames from "ADU frames" to regular MP3 frames. (Recall that each frame's layer is identified from its 4-byte MPEG header.)

If you are transmitting a stream consisting *only* of layer I or layer II frames (i.e., without any MP3 data), then there is no benefit to using this payload format, *unless* you are using the interleaving mechanism described in <u>section 7</u> below.

<u>6</u>. Frame Packetizing and Depacketizing

The transmission of a sequence of MP3 frames takes the following steps:

MP3 frames -1-> ADU frames -2-> interleaved ADU frames -3-> RTP packets

Step 1, the conversion of a sequence of MP3 frames to a corresponding sequence of ADU frames, takes place as described in sections $\underline{3}$ and 4.1 above. (Note also the pseudo-code in <u>appendix A.1</u>.)

Step 2 is the reordering of the sequence of ADU frames in an (optional) interleaving pattern, prior to packetization, as described in <u>section 7</u> below. (Note also the pseudo-code in <u>appendix B.1</u>.) Interleaving helps reduce the effect of packet loss, by distributing consecutive ADU frames over non-consecutive packets. (Note that because of the back-pointer in MP3 frames, interleaving can be applied - in general - only to ADU frames. Thus, interleaving was not possible for RFC 2250.)

Step 3 is the packetizing of a sequence of (interleaved) ADU frames into RTP packets - as described in <u>section 4.3</u> above. Each packet's RTP timestamp is the presentation time of the first ADU that is packed within it. Note that, if interleaving was done in step 2, the RTP timestamps on outgoing packets will not necessarily be monotonically nondecreasing.

Similarly, a sequence of received RTP packets is handled as follows:

RTP packets -4-> RTP packets ordered by RTP sequence number -5-> interleaved ADU frames -6-> ADU frames -7-> MP3 frames Step 4 is the usual sorting of incoming RTP packets using the RTP sequence number.

Step 5 is the depacketizing of ADU frames from RTP packets - i.e., the reverse of step 3. As part of this process, a receiver uses the "C" (continuation) flag in the ADU descriptor to notice when an ADU frame is split over more than one packet (and to discard the ADU frame entirely if one of these packets is lost).

Step 6 is the rearranging of the sequence of ADU frames back to its original order (except for ADU frames missing due to packet loss), as described in section 7 below. (Note also the pseudo-code in appendix B.2.)

Step 7 is the conversion of the sequence of ADU frames into a corresponding sequence of MP3 frames - i.e., the reverse of step 1. (Note also the pseudo-code in <u>appendix A.2</u>.) With an appropriately modified MP3 decoder, an implementation may omit this step; instead, it could feed ADU frames directly to the (modified) MP3 decoder.

7. ADU Frame Interleaving

In MPEG audio frames (MPEG-1 or 2; all layers) the high-order 11 bits of the 4-byte MPEG header ('syncword') are always all-one (i.e., 0xFFE). When reordering a sequence of ADU frames for transmission, we reuse these 11 bits as an "Interleaving Sequence Number" (ISN). (Upon reception, they are replaced with 0xFFE once again.)

The structure of the ISN is (a,b), where:

-	a ==	bits	0-7:	8-bit	Interleave	Index	(within	Cycle)
-	b ==	bits	8-10:	3-bit	Interleave	Cycle	Count	

I.e., the 4-byte MPEG header is reused as follows:

(1,0) (3,0) (5,0) (7,0) (0,0) (2,0) (4,0) (6,0) (1,1) (3,1) (5,1) etc.

So, in this example, a sequence of ADU frames f0 f1 f2 f3 f4 f5 f6 f7 f8 f9 (etc.) would get reordered, in step 2, into:

(1,0)f1 (3,0)f3 (5,0)f5 (7,0)f7 (0,0)f0 (2,0)f2 (4,0)f4 (6,0)f6 (1,1)f9 (3,1)f11 (5,1)f13 (etc.)

and the reverse reordering (along with replacement of the 0xFFE) would occur upon reception.

The reason for breaking the ISN into "Interleave Cycle Count" and "Interleave Index" (rather than just treating it as a single 11-bit counter) is to give receivers a way of knowing when an ADU frame should be 'released' to the ADU->MP3 conversion process (step 7 above), rather than waiting for more interleaved ADU frames to arrive. E.g., in the example above, when the receiver sees a frame with ISN (<something>,1), it knows that it can release all previously-seen frames with ISN (<something>,0), even if some other (<something>,0) frames remain missing due to packet loss. A 8-bit Interleave Index allows interleave cycles of size up to 256.

The choice of an interleaving order can be made independently of RTP packetization. Thus, a simple implementation could choose an interleaving order first, reorder the ADU frames accordingly (step 2), then simply pack them sequentially into RTP packets (step 3). However, the size of ADU frames - and thus the number of ADU frames that will fit in each RTP packet - will typically vary in size, so a more optimal implementation would combine steps 2 and 3, by choosing an interleaving order that better reflected the number of ADU frames packed within each RTP packet.

Each receiving implementation of this payload format MUST recognize the ISN and be able to perform deinterleaving of incoming ADU frames (step 6). However, a sending implementation of this payload format MAY choose not to perform interleaving - i.e., by omitting step 2. In this case, the high-order 11 bits in each 4-byte MPEG header would remain at 0xFFE. Receiving implementations would thus see a sequence of identical ISNs (all 0xFFE). They would handle this in the same way as if the Interleave Cycle Count changed with each ADU frame, by simply releasing the sequence of incoming ADU frames sequentially to the ADU->MP3 conversion process (step 7), without reordering. (Note also the pseudo-code in appendix B.2.)

8. IANA Considerations

[Note to RFC Editor: Please replace "XXXX" with this document's RFC number, when it is assigned.]

Media type name: audio

Media subtype: mpa-robust Required parameters: none Optional parameters: none Encoding considerations: This type is defined only for transfer via RTP, as specified in "RFC XXXX". Security considerations: See the "Security Considerations" section of "RFC XXXX". Interoperability considerations: This encoding is incompatible with both the "audio/mpa" and "audio/mpeg" media types. Published specification: The ISO/IEC MPEG-1 [3] and MPEG-2 [4] audio specifications, and "RFC XXXX". Applications which use this media type: Audio streaming tools (transmitting and receiving) Additional information: none Person & email address to contact for further information: Ross Finlayson finlayson (at) live555.com Intended usage: COMMON Author/Change controller: Author: Ross Finlayson Change controller: IETF AVT Working Group

9. SDP usage

When conveying information by SDP [7], the encoding name SHALL be "mpa-robust" (the same as the media subtype). An example of the media representation in SDP is:

m=audio 49000 RTP/AVP 121
a=rtpmap:121 mpa-robust/90000

10. Security Considerations

If a session using this payload format is being encrypted, and

interleaving is being used, then the sender SHOULD ensure that any change of encryption key coincides with a start of a new interleave cycle. Apart from this, the security considerations for this payload format are identical to those noted for <u>RFC 2250</u> [2].

<u>11</u>. Acknowledgements

The suggestion of adding an interleaving option (using the first bits of the MPEG 'syncword' - which would otherwise be all-ones - as an interleaving index) is due to Dave Singer and Stefan Gewinner. In addition, Dave Singer provided valuable feedback that helped clarify and improve the description of this payload format. Feedback from Chris Sloan led to the addition of an "ADU descriptor" preceding each ADU frame in the RTP packet.

<u>12</u>. Normative References

- [1] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", <u>BCP 14</u>, <u>RFC 2119</u>, March 1997.
- [2] Hoffman, D., Fernando, G., Goyal, V. and M. Civanlar, "RTP Payload Format for MPEG1/MPEG2 Video", <u>RFC 2250</u>, January 1998.
- [3] ISO/IEC International Standard 11172-3; "Coding of moving pictures and associated audio for digital storage media up to about 1,5 Mbits/s - Part 3: Audio", 1993.
- [4] ISO/IEC International Standard 13818-3; "Generic coding of moving pictures and associated audio information - Part 3: Audio", 1998.
- [5] Handley, M., "Guidelines for Writers of RTP Payload Format Specifications", <u>BCP 36</u>, <u>RFC 2736</u>, December 1999.
- [6] Schulzrinne, H., S. Casner, "RTP Profile for Audio and Video Conferences with Minimal Control", <u>RFC 3551</u>, July 2003.
- [7] Handley, M., Jacobson, V. and C. Perkins, "SDP: Session Description Protocol", <u>RFC 4566</u>, July 2006.

13. Author's Address

Ross Finlayson, Live Networks, Inc. 650 Castro St., suite 120-196 Mountain View, CA 94041

EMail: finlayson (at) live555.com WWW: <u>http://www.live555.com/</u>

14. IPR Notice

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in <u>BCP 78</u> and <u>BCP 79</u>.

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at http://www.ietf.org/ipr.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

15. Copyright Notice

Copyright (C) The IETF Trust (2007).

This document is subject to the rights, licenses and restrictions contained in $\frac{BCP}{78}$, and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Appendix A. Translating Between "MP3 Frames" and "ADU Frames"

The following 'pseudo code' describes how a sender using this payload format can translate a sequence of regular "MP3 Frames" to "ADU Frames", and how a receiver can perform the reverse translation: from "ADU Frames" to "MP3 Frames".

We first define the following abstract data structures:

- "Segment": A record that represents either a "MP3 Frame" or an "ADU Frame". It consists of the following fields:
 - "header": the 4-byte MPEG header
 - "headerSize": a constant (== 4)
 - "sideInfo": the 'side info' structure, *including* the optional
 2-byte CRC field, if present
 - "sideInfoSize": the size (in bytes) of the above structure
 - "frameData": the remaining data in this frame
 - "frameDataSize": the size (in bytes) of the above data
 - "backpointer": the value (expressed in bytes) of the backpointer for this frame
 - "aduDataSize": the size (in bytes) of the ADU associated with this frame. (If the frame is already an "ADU Frame", then aduDataSize == frameDataSize)
 - "mp3FrameSize": the total size (in bytes) that this frame would have if it were a regular "MP3 Frame". (If it is already a "MP3 Frame", then mp3FrameSize == headerSize + sideInfoSize + frameDataSize) Note that this size can be derived completely from "header".
- "SegmentQueue": A FIFO queue of "Segment"s, with operations
 - void enqueue(Segment)
 - Segment dequeue()
 - Boolean isEmpty()
 - Segment head()
 - Segment tail()
 - Segment previous(Segment): returns the segment prior to a given one
 - Segment next(Segment): returns the segment after a given one
 - unsigned totalDataSize(): returns the sum of the "frameDataSize" fields of each entry in the queue

```
A.1 Converting a sequence of "MP3 Frames" to a sequence of "ADU Frames":
```

```
// We now have enough data to generate the ADU for the most
         // recently enqueued frame (i.e., the tail of the queue).
         // (The earlier frames in the queue - if any - must be
         // discarded, as we don't have enough data to generate
         // their ADUs.)
         Segment tailFrame = pendingMP3Frames.tail();
         // Output the header and side info:
         output(tailFrame.header);
         output(tailFrame.sideInfo);
         // Go back to the frame that contains the start of our ADU data:
         int offset = 0;
         Segment curFrame = tailFrame;
         int prevBytes = tailFrame.backpointer;
         while (prevBytes > 0) {
                 curFrame = pendingMP3Frames.previous(curFrame);
                 int dataHere = curFrame.frameDataSize;
                 if (dataHere < prevBytes) {</pre>
                         prevBytes -= dataHere;
                 } else {
                         offset = dataHere - prevBytes;
                         break;
                 }
         }
         // Dequeue any frames that we no longer need:
         while (pendingMP3Frames.head() != curFrame) {
                 pendingMP3Frames.dequeue();
         }
         // Output, from the remaining frames, the ADU data that we want:
         int bytesToUse = tailFrame.aduDataSize;
         while (bytesToUse > 0) {
                 int dataHere = curFrame.frameDataSize - offset;
                 int bytesUsedHere
                         = dataHere < bytesToUse ? dataHere : bytesToUse;</pre>
                 output("bytesUsedHere" bytes from curFrame.frameData,
                         starting from "offset");
                 bytesToUse -= bytesUsedHere;
                 offset = 0;
                 curFrame = pendingMP3Frames.next(curFrame);
         }
A.2 Converting a sequence of "ADU Frames" to a sequence of "MP3 Frames":
```

```
SegmentQueue pendingADUFrames; // initially empty
while (1) {
```

}

```
while (needToGetAnADU()) {
                 Segment newADU = 'the next ADU Frame';
                 pendingADUFrames.enqueue(newADU);
                 insertDummyADUsIfNecessary();
         }
         generateFrameFromHeadADU();
}
Boolean needToGetAnADU() {
         // Checks whether we need to enqueue one or more new ADUs before
         // we have enough data to generate a frame for the head ADU.
         Boolean needToEnqueue = True;
         if (!pendingADUFrames.isEmpty()) {
                 Segment curADU = pendingADUFrames.head();
                 int endOfHeadFrame = curADU.mp3FrameSize
                         - curADU.headerSize - curADU.sideInfoSize;
                 int frameOffset = 0;
                 while (1) {
                         int endOfData = frameOffset
                                 - curADU.backpointer +
                                   curADU.aduDataSize;
                         if (endOfData >= endOfHeadFrame) {
                                 // We have enough data to generate a
                                 // frame.
                                 needToEnqueue = False;
                                 break;
                         }
                         frameOffset += curADU.mp3FrameSize
                                 - curADU.headerSize
                                 - curADU.sideInfoSize;
                         if (curADU == pendingADUFrames.tail()) break;
                         curADU = pendingADUFrames.next(curADU);
                 }
         }
     return needToEnqueue;
}
void generateFrameFromHeadADU() {
         Segment curADU = pendingADUFrames.head();
         // Output the header and side info:
         output(curADU.header);
         output(curADU.sideInfo);
         // Begin by zeroing out the rest of the frame, in case the ADU
         // data doesn't fill it in completely:
```

```
int endOfHeadFrame = curADU.mp3FrameSize
                 - curADU.headerSize - curADU.sideInfoSize;
         output("endOfHeadFrame" zero bytes);
         // Fill in the frame with appropriate ADU data from this and
         // subsequent ADUs:
         int frameOffset = 0;
         int toOffset = 0;
         while (toOffset < endOfHeadFrame) {</pre>
                 int startOfData = frameOffset - curADU.backpointer;
                 if (startOfData > endOfHeadFrame) {
                         break; // no more ADUs are needed
                 }
                 int endOfData = startOfData + curADU.aduDataSize;
                 if (endOfData > endOfHeadFrame) {
                         endOfData = endOfHeadFrame;
                 }
                 int fromOffset;
                 if (startOfData <= toOffset) {</pre>
                         fromOffset = toOffset - startOfData;
                         startOfData = toOffset;
                         if (endOfData < startOfData) {</pre>
                                 endOfData = startOfData;
                         }
                 } else {
                         fromOffset = 0;
                         // leave some zero bytes beforehand:
                         toOffset = startOfData;
                 }
                 int bytesUsedHere = endOfData - startOfData;
                 output(starting at offset "toOffset, "bytesUsedHere"
                         bytes from "&curADU.frameData[fromOffset]");
                 toOffset += bytesUsedHere;
                 frameOffset += curADU.mp3FrameSize
                         - curADU.headerSize - curADU.sideInfoSize;
                 curADU = pendingADUFrames.next(curADU);
         }
         pendingADUFrames.dequeue();
void insertDummyADUsIfNecessary() {
         // The tail segment (ADU) is assumed to have been recently
         // enqueued. If its backpointer would overlap the data
         // of the previous ADU, then we need to insert one or more
         // empty, 'dummy' ADUs ahead of it. (This situation should
```

}

```
// occur only if an intermediate ADU was missing - e.g., due
// to packet loss.)
while (1) {
        Segment tailADU = pendingADUFrames.tail();
        int prevADUend; // relative to the start of the tail ADU
        if (pendingADUFrames.head() != tailADU) {
                // there is a previous ADU
                Segment prevADU
                        = pendingADUFrames.previous(tailADU);
                prevADUend
                        = prevADU.mp3FrameSize +
                          prevADU.backpointer
                          - prevADU.headerSize
                          - prevADU.sideInfoSize;
                if (prevADU.aduDataSize > prevADUend) {
                        // this shouldn't happen if the previous
                        // ADU was well-formed
                        prevADUend = 0;
                } else {
                        prevADUend -= prevADU.aduDataSize;
                }
        } else {
                prevADUend = 0;
        }
        if (tailADU.backpointer > prevADUend) {
           // Insert a 'dummy' ADU in front of the tail.
           // This ADU can have the same "header" (and thus
           // "mp3FrameSize") as the tail ADU, but should
           // have a "backpointer" of "prevADUend", and
           // an "aduDataSize" of zero. The simplest
           // way to do this is to copy the "sideInfo" from
           // the tail ADU, replace the value of
           // "main_data_begin" with "prevADUend", and set
           // all of the "part2_3_length" fields to zero.
        } else {
                break; // no more dummy ADUs need to be inserted
        }
}
```

Appendix B: Interleaving and Deinterleaving

}

The following 'pseudo code' describes how a sender can reorder a sequence of "ADU Frames" according to an interleaving pattern (step 2), and how a receiver can perform the reverse reordering (step 6).

<u>B.1</u> Interleaving a sequence of "ADU Frames":

We first define the following abstract data structures:

- "interleaveCycleSize": an integer in the range [1..256] "interleaveCycle": an array, of size "interleaveCycleSize",
 containing some permutation of the integers from the set [0 ..
 interleaveCycleSize-1]
 e.g., if "interleaveCycleSize" == 8, "interleaveCycle" might
 contain: 1,3,5,7,0,2,4,6
- "inverseInterleaveCycle": an array containing the inverse of the permutation in "interleaveCycle" - i.e., such that interleaveCycle[inverseInterleaveCycle[i]] == i
- "ii": the current Interleave Index (initially 0)
- "icc": the current Interleave Cycle Count (initially 0)
- "aduFrameBuffer": an array, of size "interleaveCycleSize", of ADU Frames that are awaiting packetization

```
while (1) {
```

```
}
```

B.2 Deinterleaving a sequence of (interleaved) "ADU Frames":

We first define the following abstract data structures:

- "ii": the Interleave Index from the current incoming ADU frame
- "icc": the Interleave Cycle Count from the current incoming ADU frame
- "iiLastSeen": the most recently seen Interleave Index (initially, some integer *not* in the range [0..255])
- "iccLastSeen": the most recently seen Interleave Cycle Count (initially, some integer *not* in the range [0..7])
- "aduFrameBuffer": an array, of size 256, of (pointers to) ADU Frames that have just been depacketized (initially, all entries are NULL)

```
while (1) {
```

aduFrame = the next ADU frame from the depacketizing step;

```
(ii,icc) = "the high-order 11 bits of aduFrame's MPEG header";
         "the high-order 11 bits of aduFrame's MPEG header" = 0xFFE;
                 // Note: Be sure to leave the remaining 21 bits as is
         if (icc != iccLastSeen || ii == iiLastSeen) {
                 // We've started a new interleave cycle
                 // (or interleaving was not used). Release all
                 // pending ADU frames to the ADU->MP3 conversion step:
                 for (int i = 0; i < 256; ++i) {
                         if (aduFrameBuffer[i] != NULL) {
                                 release aduFrameBuffer[i];
                                 aduFrameBuffer[i] = NULL;
                         }
                 }
         }
         iiLastSeen = ii;
         iccLastSeen = icc;
         aduFrameBuffer[ii] = aduFrame;
Expires: February 28, 2008
```

}