

Audio/Video Transport Working
Group
Internet-Draft
Intended status: Standards Track
Expires: August 29, 2009

G. Hunt
BT
A. Clark
Telchemy
February 25, 2009

RTCP XR Report Block for Concealed Seconds metric Reporting
draft-ietf-avt-rtcp-xr-concsec-01.txt

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on August 29, 2009.

Copyright Notice

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents in effect on the date of publication of this document (<http://trustee.ietf.org/license-info>). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

Internet-Draft

RTCP XR Concealed Seconds

February 2009

Abstract

This document defines an RTCP XR Report Block that allows the reporting of Concealed Seconds metrics primarily for audio applications of RTP.

Table of Contents

- [1. Introduction](#) [3](#)
- [1.1. Concealed Seconds Block](#) [3](#)
- [1.2. RTCP and RTCP XR Reports](#) [3](#)
- [1.3. Performance Metrics Framework](#) [3](#)
- [1.4. Applicability](#) [4](#)
- [2. Concealed Seconds Metrics Block](#) [5](#)
- [2.1. Report Block Structure](#) [5](#)
- 2.2. Definition of Fields in Concealed Seconds Metrics Block . 5
- [3. SDP Signaling](#) [10](#)
- [4. IANA Considerations](#) [11](#)
- [4.1. New RTCP XR Block Type value](#) [11](#)
- [4.2. New RTCP XR SDP Parameter](#) [11](#)
- [4.3. Contact information for registrations](#) [11](#)
- [5. Security Considerations](#) [12](#)
- [6. Contributors](#) [13](#)
- [7. Changes from previous version](#) [14](#)
- [8. References](#) [15](#)
- [8.1. Normative References](#) [15](#)
- [8.2. Informative References](#) [15](#)
- Authors' Addresses [16](#)

Internet-Draft

RTCP XR Concealed Seconds

February 2009

[1.](#) Introduction

[1.1.](#) Concealed Seconds Block

This draft defines a new block type to augment those defined in [\[RFC3611\]](#), for use primarily in audio applications of RTP.

At any instant, the audio output at a receiver may be classified as either 'normal' or 'concealed'. 'Normal' refers to playout of audio payload received from the remote end, and also includes locally generated signals such as announcements, tones and comfort noise. Concealment refers to playout of locally-generated signals used to mask the impact of network impairments such as lost packets or to reduce the audibility of jitter buffer adaptations.

The new block type provides metrics for concealment. Specifically, the first metric (Unimpaired Seconds) reports the number of whole seconds occupied only with normal playout of data which the receiver obtained from the sender's stream. The second metric (Concealed Seconds) reports the number of whole seconds during which the receiver played out any locally-generated media data. A third metric (Severely Concealed Seconds) reports the number of whole seconds during which the receiver played out locally-generated data for more than SCS Threshold (ms).

The metric belongs to the class of transport-related terminal metrics defined in [\[MONARCH\]](#) (work in progress).

Instances of this Metrics Block refer by tag to the separate auxiliary Measurement Identity block [\[MEASIDENT\]](#) which contains information such as the SSRC of the measured stream, and RTP sequence numbers and time intervals indicating the span of the report.

[1.2.](#) RTCP and RTCP XR Reports

The use of RTCP for reporting is defined in [\[RFC3550\]](#). [\[RFC3611\]](#)

defined an extensible structure for reporting using an RTCP Extended Report (XR). This draft defines a new Extended Report block that MUST be used as defined in [[RFC3550](#)] and [[RFC3611](#)].

[1.3.](#) Performance Metrics Framework

The Performance Metrics Framework [[PMOLFRAME](#)] provides guidance on the definition and specification of performance metrics. Metrics described in this draft either reference external definitions or define metrics generally in accordance with the guidelines in [[PMOLFRAME](#)].

[1.4.](#) Applicability

This metric is primarily applicable to audio applications of RTP. The reason for this restriction is that, for many video codecs, packet data may contain occasional complete reference pictures, and otherwise consists of data specifying picture changes relative to a complete reference picture. Loss of an RTP video media packet could degrade the user experience for a variable amount of time between the time of loss and the next complete reference picture. In contrast, in the audio case the degradation almost always persists for a predictable period of time from the loss of the packet, which might be simply the duration of the audio data encoded in the lost packet. However if a useful Concealed Seconds metric can be defined for an RTP video application, either in general or for a specific type of video codec, the Concealed Seconds and Severely Concealed Seconds metrics and the metric block type defined here MAY be used.

[2.](#) Concealed Seconds Metrics Block

This sub-block provides a description of potentially audible impairments due to lost and discarded packets at the endpoint, expressed on a time basis analogous to a traditional PSTN T1/E1 errored seconds metric.

The following metrics are based on successive one second intervals as declared by a local clock. This local clock does NOT need to be synchronized to any external time reference. The starting time of this clock is unspecified. Note that this implies that the same loss pattern could result in slightly different count values, depending on where the losses occur relative to the particular one-second demarcation points. For example, two loss events occurring 50ms apart could result in either one concealed second or two, depending on the particular 1000 ms boundaries used.

The seconds in this sub-block are not necessarily calendar seconds. At the tail end of a call, periods of time of less than 1000ms shall be incorporated into these counts if they exceed 500ms and shall be disregarded if they are less than 500ms.

2.1. Report Block Structure




Figure 1: Report Block Structure

2.2. Definition of Fields in Concealed Seconds Metrics Block

block type (BT): 8 bits

A Concealed Seconds Metrics Report Block is identified by the constant NCS.

[Note to RFC Editor: please replace NCS with the IANA provided RTCP XR block type for this block.]

Interval Metric flag (I): 1 bit

This field is used to indicate whether the Concealed Seconds metric block is an Interval or a Cumulative report, that is, whether the reported values apply to the most recent measurement interval duration between successive metrics reports (I=1) (the Interval Duration) or to the accumulation period characteristic of cumulative measurements (I=0) (the Cumulative Duration). Numerical values for both these intervals are provided in the Measurement Identifier block referenced by the tag field below.

Measurement Identifier association (tag): 3 bits

This field is used to identify the Measurement Identifier block [[MEASIDENT](#)] which describes this measurement. The relevant

Measurement Identifier block has the same tag value as the Concealed Seconds Metrics block. Note that there may be more than one Measurement Identifier block per RTCP packet.

Packet Loss Concealment Method (plc): 2 bits

This field is used to identify the packet loss concealment method in use at the receiver, according to the following code:

bits 0-3

- 0 = silence insertion
- 1 = simple replay, no attenuation
- 2 = simple replay, with attenuation
- 3 = enhanced
- Other values reserved

Reserved (rsv): 2 bits

These bits are reserved. They SHOULD be set to zero by senders and MUST be ignored by receivers.

block length: 16 bits

The length of this report block in 32-bit words, minus one. For the Concealed Seconds block, the block length is equal to 3.

Unimpaired Seconds: 32 bits

A count of the number of unimpaired Seconds that have occurred.

An unimpaired Second is defined as a continuous period of 1000ms during which no frame loss or discard due to late arrival has

occurred. Every second in a call must be classified as either OK or Concealed.

Normal playout of comfort noise or other silence concealment signal during periods of talker silence, if VAD is used, shall be counted as unimpaired seconds.

If the measured value exceeds 0xFFFFFFFF, the value 0xFFFFFFFF

SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFFFFFF SHOULD be reported.

Concealed Seconds: 32 bits

A count of the number of Concealed Seconds that have occurred.

A Concealed Second is defined as a continuous period of 1000ms during which any frame loss or discard due to late arrival has occurred.

Equivalently, a concealed second is one in which some Loss-type concealment has occurred. Buffer adjustment-type concealment SHALL not cause Concealed Seconds to be incremented, with the following exception. An implementation MAY cause Concealed Seconds to be incremented for 'emergency' buffer adjustments made during talkspurts.

Loss-type concealment is reactive insertion or deletion of samples in the audio playout stream due to effective frame loss at the audio decoder. "Effective frame loss" is the event in which a frame of coded audio is simply not present at the audio decoder when required. In this case, substitute audio samples are generally formed, at the decoder or elsewhere, to reduce audible impairment.

Buffer Adjustment-type concealment is proactive or controlled insertion or deletion of samples in the audio playout stream due to jitter buffer adaptation, re-sizing or re-centering decisions within the endpoint.

Because this insertion is controlled, rather than occurring randomly in response to losses, it is typically less audible than loss-type concealment. For example, jitter buffer adaptation events may be constrained to occur during periods of talker silence, in which case only silence duration is affected, or sophisticated time-stretching methods for insertion/deletion

during favorable periods in active speech may be employed. For

these reasons, buffer adjustment-type concealment MAY be exempted from inclusion in calculations of Concealed Seconds and Severely Concealed Seconds.

However, an implementation SHOULD include buffer-type concealment in counts of Concealed Seconds and Severely Concealed Seconds if the event occurs at an 'inopportune' moment, with an emergency or large, immediate adaptation during active speech, or for unsophisticated adaptation during speech without regard for the underlying signal, in which cases the assumption of low-audibility cannot hold. In other words, jitter buffer adaptation events which may be presumed to be audible SHOULD be included in Concealed Seconds and Severely Concealed Seconds counts.

Concealment events which cannot be classified as Buffer Adjustment- type MUST be classified as Loss-type.

For clarification, the count of Concealed Seconds MUST include the count of Severely Concealed Seconds.

If the measured value exceeds 0xFFFFFFFF, the value 0xFFFFFFFF SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFFFFFF SHOULD be reported.

Severely Concealed Seconds: 16 bits

A count of the number of Severely Concealed Seconds.

A Severely Concealed Second is defined as a non-overlapping period of 1000 ms during which the cumulative amount of time that has been subject to frame loss or discard due to late arrival, exceeds the SCS Threshold.

If the measured value exceeds 0xFFFF, the value 0xFFFF SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFF SHOULD be reported.

RESERVED: 8 bits

These bits are reserved. They SHOULD be set to zero by senders and MUST be ignored by receivers.

SCS Threshold: 8 bits

The SCS Threshold defines the amount of time corresponding to lost or discarded frames that must occur within a one second period in order for the second to be classified as a Severely Concealed Second. This is expressed in milliseconds and hence can represent a range of 0.1 to 25.5 percent loss or discard.

A default threshold of 50ms (5% effective frame loss per second) is suggested.

3. SDP Signaling

[RFC3611] defines the use of SDP (Session Description Protocol) [RFC4566] for signaling the use of XR blocks. XR blocks MAY be used without prior signaling.

This section augments the SDP [RFC4566] attribute "rtcp-xr" defined in [RFC3611] by providing an additional value of "xr-format" to signal the use of the report block defined in this document.

The SDP attribute for the block has an additional optional parameter, "thresh", used to supply a value for the SCS Threshold parameter. If this parameter is present, the RTP system receiving the SDP SHOULD use this value for the current session. If the parameter is not present, the RTP system SHOULD use a locally configured value.

```
rtcp-xr-attrib = "a=" "rtcp-xr" ":" [xr-format *(SP xr-format)] CRLF
```

(defined in [RFC3611])

```
xr-format = xr-format / xr-conc-sec-block
```

```
xr-conc-sec-block = "conc-sec" ["=" thresh]
```

```
thresh      = 1*DIGIT           ; threshold for SCS (ms)
DIGIT       = %x30-39
```

[4.](#) IANA Considerations

New block types for RTCP XR are subject to IANA registration. For general guidelines on IANA considerations for RTCP XR, refer to [\[RFC3611\]](#).

[4.1.](#) New RTCP XR Block Type value

This document assigns the block type value NCS in the IANA "RTCP XR Block Type Registry" to the "Concealed Seconds Metrics Block".

[Note to RFC Editor: please replace NCS with the IANA provided RTCP XR block type for this block.]

[4.2.](#) New RTCP XR SDP Parameter

This document also registers a new parameter "conc-sec" in the "RTCP XR SDP Parameters Registry".

[4.3.](#) Contact information for registrations

The contact information for the registrations is:

Geoff Hunt (geoff.hunt@bt.com)

Orion 2 PP3, Adastral Park, Martlesham Heath, Ipswich IP5 3RE, United Kingdom

5. Security Considerations

It is believed that this proposed RTCP XR report block introduces no new security considerations beyond those described in [[RFC3611](#)]. This block does not provide per-packet statistics so the risk to confidentiality documented in [Section 7](#), paragraph 3 of [[RFC3611](#)] does not apply.

[6.](#) Contributors

The authors gratefully acknowledge the comments and contributions made by Bruce Adams, Philip Arden, Amit Arora, Bob Biskner, Kevin Connor, Claus Dahm, Randy Ethier, Roni Even, Jim Frauenthal, Albert Higashi, Tom Hock, Shane Holthaus, Paul Jones, Rajesh Kumar, Keith Lantz, Mohamed Mostafa, Amy Pendleton, Colin Perkins, Mike Ramalho, Ravi Raviraj, Albrecht Schwarz, Tom Taylor, and Hideaki Yamada.

7. Changes from previous version

Intro: Added "such as lost packets" as example to clarify concealment in Intro, and text in [Section 2.2](#), to meet Roni Even's request for a definition of concealment (post 5-Dec-2008)

Intro, Applicability: Removed editor's note about metrics for concealment in video. Added text based on Roni Even's and Randall Jessup's posts of 5-Dec-2008 and 19-Dec-2008, explaining difficulty of applying Concealed Seconds to video but stating that metric MAY be used for video if a useful Concealed Seconds metric may be defined.

Extended and clarified IANA considerations section.

Changed SDP tag for block to "conc-sec".

Hunt & Clark

Expires August 29, 2009

[Page 14]

Internet-Draft

RTCP XR Concealed Seconds

February 2009

[8.](#) References

[8.1.](#) Normative References

[MEASIDENT]

Hunt, G., "RTCP XR Measurement Identifier Block",
ID [draft-ietf-avt-rtcp-xr-measid-01](#), February 2009.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), [BCP 14](#), March 1997.

[RFC3550] Schulzrinne, H., "RTP: A Transport Protocol for Real-Time Applications", [RFC 3550](#), July 2003.

[RFC3611] Friedman, T., "RTP Control Protocol Extended Reports (RTCP XR)", [RFC 3611](#), November 2003.

[RFC4566] Handley, M., "SDP: Session Description Protocol",
[RFC 4566](#), July 2006.

8.2. Informative References

[MONARCH] Hunt, G., "Monitoring Architectures for RTP",
ID [draft-hunt-avt-monarch-01](#), August 2008.

[PMOLFRAME]

Clark, A., "Framework for Performance Metric Development",
ID [draft-ietf-pmol-metrics-framework-00](#), July 2008.

Authors' Addresses

Geoff Hunt
BT
Orion 2 PP3
Adastral Park
Martlesham Heath
Ipswich, Suffolk IP5 3RE
United Kingdom

Phone: +44 1473 651704
Email: geoff.hunt@bt.com

Alan Clark
Telchemy Incorporated
2905 Premiere Parkway, Suite 280
Duluth, GA 30097
USA

Email: alan.d.clark@telchemy.com

