

Audio/Video Working Group
Internet-Draft
Expires: April 22, 2006

Alan Clark
Telchemy
Amy Pendleton
Nortel
October 2005

**RTP Control Protocol Extended Reports (RTCP XR)
VoIP Metrics Management Information Base
draft-ietf-avt-rtcp-xr-mib-03.txt**

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on April 22, 2006.

This document is a product of the Audio-Visual Transport (AVT) working group of the Internet Engineering Task Force. Comments are solicited and should be addressed to the working group's mailing list at avt@ietf.org and/or the authors.

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines objects for managing Real-Time Transport Control Protocol Extended Reports (RTCP XR) VoIP Metrics ([RFC3611](#)).

Clark

Expires April 2006

[Page 1]

Table of Contents

1. The Network Management Framework	2
2. Overview	3
2.1 Components	3
2.2 Applicability of the MIB to RTP System Implementations	3
2.3 Relationship to the RTP MIB.....	3
2.4 Relationship to the RAQMOM Architecture.....	3
2.5 The Structure of the RTCP XR MIB	4
2.6 Application to multi-party and multicast calls	4
3 Definitions	5
4. Security Considerations	42
5. IANA Considerations	42
5. Acknowledgements	42
6. Intellectual Property	43
7. Normative References	43
9. Informative References	43
8. Authors' Addresses	44
9. Full Copyright Statement	44

[1. The Internet-Standard Management Framework](#)

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

[2. Overview](#)

An "RTP System" may be a host end-system that runs an application program that sends or receives RTP data packets, or it may be an intermediate-system that forwards RTP packets. RTP Control Protocol (RTCP) packets are sent by senders and receivers to convey information about RTP packet transmission and reception [[RFC3550](#)]. RTCP Extended Report (XR) [[RFC3611](#)] packets are sent by receivers to convey additional information about certain types of RTP packet reception.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#).

2.1 Components

The RTCP XR MIB is structured around "Session", "Source", "Destination" and "Receiver" conceptual abstractions.

Clark

Expires April 2006

[Page 2]

2.1.1 An RTP Session is an association of two or more participants communicating with RTP. For each participant, the session is defined by a particular pair of destination transport addresses (one network address plus a port pair for RTP and RTCP). The destination transport addresses may be common for all participants, as in the case of IP multicast, or may be different for each, as in the case of individual unicast addresses plus a common port pair," as defined in [section 3 of \[RFC3550\]](#).

2.1.2 A "Sender" is identified within an RTP session by a 32-bit numeric "Synchronization Source," or "SSRC", value and is "...the source of a stream of RTP packets" as defined in [section 3 of \[RFC3550\]](#). The sender is also a source of RTCP Sender Report packets as specified in [section 6 of \[RFC3550\]](#).

2.1.3 A "Receiver" of a "stream of RTP packets" can be a unicast or multicast Receiver as described in 2.1.1, above. An RTP Receiver has an SSRC value that is unique to the session. An RTP Receiver is a source of RTCP Receiver Reports as specified in [section 6 of \[RFC3550\]](#) and RTCP XR VoIP Metrics Reports as specified in [section 4.7 of \[RFC3611\]](#).

[2.2](#) Applicability of the MIB to RTP System Implementations

The RTCP XR MIB may be used in RTP Host Systems (end systems), see [section 3 of \[RFC3550\]](#), that are supporting Voice over IP (VoIP host systems) or in intermediate systems.

2.2.1 VoIP host Systems are end-systems that may use the RTCP XR MIB to collect RTP Voice over IP session data that the host is sending or receiving; these data may be used by a network manager to detect and diagnose faults that occur over the lifetime of a VoIP session as in a "help-desk" scenario.

2.2.2 Monitors of RTP Voice over IP sessions may be third-party or may be located in the RTP host. Monitors may use the RTCP XR MIB to collect Voice over IP session statistical data; these data may be used by a network manager for planning and other network-management purposes. A Monitor may use the RTCP XR MIB to collect data to permit a network manager to diagnose faults in VoIP sessions.

[2.3](#) Relationship to the RTP MIB

The RTP MIB defines a session table, sender and receiver tables and inverse tables to support fast location of session information.

The RTP MIB Version 2 [draft TBD] has a session table that is identical to the session table in the RTCP XR MIB. This is intended to allow implementations that support both the RTP MIB V2 and the RTCP XR MIB to use a common session table.

[2.4](#) Relationship to the RAQMON Architecture

The Real-time Application QoS monitoring (RAQMON) Framework [xxx]

Clark

Expires April 2006

[Page 3]

defines an architecture that extends the Remote Monitoring (RMON) family of applications for monitoring of application QoS in real time, and an extensible data model with objects carried between RAQMON data sources and RAQMON collectors. The RAQMON work is more generic, and complementary in concept to RTCP-XR, covering a wider range of applications running concurrently, while RTCP-XR focuses on in-depth QoS monitoring of media traffic in VoIP.

The Real-time Application QoS Monitoring (RAQMON) MIB is defined by [xxx] and runs on RAQMON collectors. A performance monitoring application may query (i) RAQMON collectors for RAQMON MIB information about the QoS parameters of multiple concurrent applications (ii) end-points and gateways for in-depth RTCP-XR information about the media QoS of VoIP or (iii) both.

2.5 The Structure of the RTCP XR MIB

There are four tables in the RTCP XR MIB

The `rtcpXrSessionIDTable` contains identifying information about each session and about the source and destination.

The `rtcpXrBasicParametersTable` contains basic packet loss, discard and delay related parameters about a session.

The `rtcpXrVoiceQualityMetricSTable` contains information about the call quality of a session

The `rtcpXrHistoryTable` contains aggregate information about a group of sessions.

2.6 Application to multi-party and multicast calls

The RTCP XR MIB may be applied to multi-party calls. The Session table is defined in terms of uni-directional RTP streams from a source to a destination.

For a multi-party IP-IP conference call in which parties are directly interconnected in a mesh network, a row should be created in the session table for each such interconnection.

For a multi-party call in which parties are interconnected via a bridge function and RTP streams are literally or logically terminated at the bridge, a row should be created in the session table for the RTP sessions established to and from each endpoint and the bridge.

For a multicast call in which RTP sessions are terminated in logical IP addresses from they are redistributed, a row in the session table should be created for the source to multicast

address RTP session.

Clark

Expires April 2006

[Page 4]

RTCPXR-MIB DEFINITIONS ::= BEGIN

IMPORTS

mib-2, MODULE-IDENTITY, NOTIFICATION-TYPE,
OBJECT-TYPE, Unsigned32, Integer32,
Gauge32, Counter32 FROM SNMPv2-SMI
OBJECT-GROUP, MODULE-COMPLIANCE,
NOTIFICATION-GROUP FROM SNMPv2-CONF
TEXTUAL-CONVENTION, RowPointer, DateAndTime
FROM SNMPv2-TC
SnmAdminString FROM SNMP-FRAMEWORK-MIB
InetAddressType, InetAddress,
InetPortNumber FROM INET-ADDRESS-MIB
ItuPerceivedSeverity FROM ITU-ALARM-TC-MIB;

rtcpXrMIB MODULE-IDENTITY

LAST-UPDATED "200510230000Z"

ORGANIZATION

"IETF AVT Working Group"

CONTACT-INFO

"IETF AVT Working Group
Chairs: Colin Perkins, Magnus Westerlund
Working Group Email: avt@ietf.org

Editors: Alan Clark
Telchemy
Email: alan@telchemy.com

Amy Pendleton
Nortel
Email: aspen@nortel.com

DESCRIPTION

"RTCP Extended Reports MIB
Copyright (c) The Internet Society (2005)
This version of the MIB module is part of
RFC nnnn and is based on [RFC3611](#)."

REVISION "200510230000Z"

DESCRIPTION

"Initial version, published as RFC nnnn"

-- RFC Ed: replace nnnn (2 occurrences) with the actual RFC number and
-- remove this notice

::= { mib-2 mmm }

-- IANA: need assignment of a mib-2 OID for this MIB
-- RFC Ed: replace mmm with IANA assigned number and remove this note

--

-- RTCP Extended Reports - Voice over IP Metrics
--
-- Description
-- This MIB module provides basic voice quality monitoring

Clark

Expires April 2006

[Page 5]

```
-- capabilities for Voice-over-packet systems. The MIB contains
-- 4 tables of information:-
--     a table of call records with session identifying information
--     a table of basic parameters for each session
--     a table of call quality metrics for each session
--     a table of aggregate statistics for groups of calls

--
-- TEXTUAL CONVENTIONS
--
```

```
LeveldB ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS      current
DESCRIPTION
    "Represents a signal level in decibels (dB)."
```

```
SYNTAX      Integer32 (-120..120|127)
```

```
Rfactor ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS      current
DESCRIPTION
    "Call or transmission quality expressed as an
    R factor in the range 0 to 120. A value of
    127 shall be interpreted as NULL or unsupported."
```

```
REFERENCE
    "ITU-T G.107"
```

```
SYNTAX      Unsigned32 (0..120|127)
```

```
ScaledMOSscore ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS      current
DESCRIPTION
    "Call or transmission quality expressed as a
    MOS score scaled by 10. MOS is typically represented
    as a 1.0 to 5.0 score with a single decimal place and
    hence in this representation as 10 to 50. A value of
    127 shall be interpreted as NULL or unsupported."
```

```
REFERENCE
    "ITU-T P.800"
```

```
SYNTAX      Integer32 (10..50|127)
```

```
Percentage ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS      current
DESCRIPTION
    "Percentage expressed as a rounded integer."
```

```
SYNTAX      Unsigned32 (0..100)
```

--
-- OBJECTS
--

rtcpXrEvents OBJECT IDENTIFIER ::= { rtcpXrMIB 0 }

Clark Expires April 2006 [Page 6]

```
rtcpXrMIBObjects OBJECT IDENTIFIER ::= { rtcpXrMIB 1 }
rtcpXrConformance OBJECT IDENTIFIER ::= { rtcpXrMIB 2 }
```

```
--
-- Table of Session Identifying information
--
```

```
rtcpXrSessionIDTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RtcpXrSessionIDEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Table of information about RTP Sessions for which RTCP XR
        parameters and metrics are available. "
    ::= { rtcpXrMIBObjects 1 }
```

```
rtcpXrSessionIDEntry OBJECT-TYPE
    SYNTAX RtcpXrSessionIDEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "An entry in the table of call records. A row in this table
        is created for each RTP session endpoint participating."
    INDEX { rtcpXrSessionIDCallState, rtcpXrSessionIDIndex }
    ::= { rtcpXrSessionIDTable 1 }
```

```
RtcpXrSessionIDEntry ::= SEQUENCE {
    rtcpXrSessionIDCallState          INTEGER,
    rtcpXrSessionIDIndex              Unsigned32,
    rtcpXrSessionIDSessionIdentifier OCTET STRING,
    rtcpXrSessionIDStartTime          DateAndTime,
    rtcpXrSessionIDStopTime           DateAndTime,
    rtcpXrSessionIDSourceIPType       InetAddressType,
    rtcpXrSessionIDSourceIPAddress     InetAddress,
    rtcpXrSessionIDSourceRTPport       InetPortNumber,
    rtcpXrSessionIDSourceRTCPport      InetPortNumber,
    rtcpXrSessionIDDestIPType         InetAddressType,
    rtcpXrSessionIDDestIPAddress       InetAddress,
    rtcpXrSessionIDDestRTPport        InetPortNumber,
    rtcpXrSessionIDDestRTCPport       InetPortNumber,
    rtcpXrSessionIDSrceIdenType       INTEGER,
    rtcpXrSessionIDSrceIdentifier      OCTET STRING,
    rtcpXrSessionIDDestIdenType       INTEGER,
    rtcpXrSessionIDDestIdentifier      OCTET STRING,
    rtcpXrSessionIDMeasurePt          INTEGER,
    rtcpXrSessionIDMeasurePtID        OCTET STRING,
    rtcpXrSessionIDReverseSession     RowPointer,
    rtcpXrSessionIDAltMeasurePt       RowPointer
}
```

```
rtcpXrSessionIDCallState OBJECT-TYPE
    SYNTAX INTEGER { active(1),
                    completed(2)
                    }

```

Clark

Expires April 2006

[Page 7]

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Index for this session within the Session ID table. The value of this parameter shall be 2 if the session is complete or inactive and 1 if the session is still active."

::= { rtcpXrSessionIDEntry 1 }

rtcpXrSessionIDIndex OBJECT-TYPE

SYNTAX Unsigned32 (0..4294967295)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Index for this session within the Session ID table."

::= { rtcpXrSessionIDEntry 2 }

rtcpXrSessionIDSessionIdentifier OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(0..128))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Unique identifier for this session. A billing record correlation identifier should be used if available, otherwise an identifier such as SSRC can be used."

::= { rtcpXrSessionIDEntry 3 }

rtcpXrSessionIDStartTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Call start time for this call. If the start time is not known then this represents the earliest known time associated with the call."

::= { rtcpXrSessionIDEntry 4 }

rtcpXrSessionIDStopTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Call stop time for this call. If the call is still active then this shall have the value 0. If the call is complete but the time is unknown then this shall have the value of the latest time associated with the call."

::= { rtcpXrSessionIDEntry 5 }

rtcpXrSessionIDSourceIPtype OBJECT-TYPE

SYNTAX InetAddressType
MAX-ACCESS read-only
STATUS current
DESCRIPTION

Clark

Expires April 2006

[Page 8]

```
    "IP address type for the originating IP endpoint for this
    RTP stream."
 ::= { rtcpXrSessionIDEntry 6 }
```

rtcpXrSessionIDSourceIPAddress OBJECT-TYPE

```
    SYNTAX InetAddress
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "IP address for the originating IP endpoint for this
        RTP stream."
 ::= { rtcpXrSessionIDEntry 7 }
```

rtcpXrSessionIDSourceRTPport OBJECT-TYPE

```
    SYNTAX InetPortNumber
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Source UDP port for RTP. A value of 0 indicates
        an unknown port number."
 ::= { rtcpXrSessionIDEntry 8 }
```

rtcpXrSessionIDSourceRTCPport OBJECT-TYPE

```
    SYNTAX InetPortNumber
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Source UDP port for RTCP. A value of 0 indicates
        an unknown port number."
 ::= { rtcpXrSessionIDEntry 9 }
```

rtcpXrSessionIDDestIPtype OBJECT-TYPE

```
    SYNTAX InetAddressType
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Destination IP address type for this session."
 ::= { rtcpXrSessionIDEntry 10 }
```

rtcpXrSessionIDDestIPAddress OBJECT-TYPE

```
    SYNTAX InetAddress
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Destination IP address for this session."
 ::= { rtcpXrSessionIDEntry 11 }
```

rtcpXrSessionIDDestRTPport OBJECT-TYPE

```
    SYNTAX InetPortNumber
```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Destination UDP port for RTP. A value of 0 indicates
an unknown port number."

::= { rtcpXrSessionIDEntry 12 }

Clark

Expires April 2006

[Page 9]

```
rtcpXrSessionIDDestRTCPport OBJECT-TYPE
    SYNTAX InetPortNumber
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Destination UDP port for RTCP. A value of 0 indicates
        an unknown port number."
    ::= { rtcpXrSessionIDEntry 13 }

rtcpXrSessionIDSrceIdenType OBJECT-TYPE
    SYNTAX INTEGER {dialedNumber (1),
                    urlID (2),
                    other (3) }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Defines the type of address in parameter
        rtcpXrSessionIDSourceIdentifier"
    ::= { rtcpXrSessionIDEntry 14 }

rtcpXrSessionIDSrceIdentifier OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE(0..128))
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Alternate identifier to the IP address. This can be E.164,
        DN, or URL."
    ::= { rtcpXrSessionIDEntry 15 }

rtcpXrSessionIDDestIdenType OBJECT-TYPE
    SYNTAX INTEGER {dialedNumber (1),
                    urlID (2),
                    other (3) }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Defines the type of address in parameter
        rtcpXrSessionIDDestIdentifier."
    ::= { rtcpXrSessionIDEntry 16 }

rtcpXrSessionIDDestIdentifier OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE(0..128))
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Alternate identifier to the IP address. This can be E.164,
        DN, or URL."
    ::= { rtcpXrSessionIDEntry 17 }
```

```
rtcpXrSessionIDMeasurePt OBJECT-TYPE
    SYNTAX INTEGER {      localEndpoint (1),
                           remoteEndpoint (2),
                           midStream (3)
    }
```

Clark

Expires April 2006

[Page 10]

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Place that these metrics were measured - this endpoint, remote endpoint (i.e. reported through XR), or midstream. If this MIB is supported in a midstream device (e.g. probe) then data from the IP endpoint reported to this device using [RFC3611](#) would be described as 'remoteEndpoint' and data measured locally would be described as 'midStream'. If this MIB is supported in an IP endpoint then the metrics obtained from measurement of the incoming stream would be 'localEndpoint' and those reported via [RFC3611](#) from the remote end would be 'remoteEndpoint'. This MIB could therefore report both remote and local data if located in an IP endpoint or both remote and midstream data if located in a probe, router or other mid-network device."

::= { rtcpXrSessionIDEntry 18 }

rtcpXrSessionIDMeasurePtID OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(0..128))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Information describing the identity of the endpoint that measured the data in this row. If the data was measured locally then this would be the identity of this system, if measured remotely and reported via [RFC3611](#) then this would be the identity of the remote measurement point, if known. Expressed as IP address in 1.1.1.1 notation or as a descriptive name."

::= { rtcpXrSessionIDEntry 19 }

rtcpXrSessionIDReverseSession OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A pointer to the corresponding entry in this table for the reverse direction of transmission. For example, if this row contained locally measured metrics for the A->B direction of transmission then the reverse session would be the row containing locally measured metrics for the B->A direction of transmission."

::= { rtcpXrSessionIDEntry 20 }

rtcpXrSessionIDAltMeasurePt OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A pointer to the corresponding entry in this table for alternate measurement point data. For example, if this MIB was located in a midstream devices and this row

Clark

Expires April 2006

[Page 11]

contained metrics measured midstream then the alternate measurement point would refer to the metrics reported by the remote endpoint, and vice versa."

```
::= { rtcpXrSessionIDEntry 21 }
```

```
--
```

```
-- Table of basic call parameters
```

```
--
```

```
rtcpXrBaseParamTable OBJECT-TYPE
```

```
    SYNTAX SEQUENCE OF RtcpXrBaseParamEntry
```

```
    MAX-ACCESS not-accessible
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "Table of basic parameters related to RTP sessions in
         the Session table. "
```

```
::= { rtcpXrMIBObjects 2 }
```

```
rtcpXrBaseParamEntry OBJECT-TYPE
```

```
    SYNTAX RtcpXrBaseParamEntry
```

```
    MAX-ACCESS not-accessible
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "An entry in the table of basic parameters. A row in this table
         is created for each RTP session endpoint participating."
```

```
    INDEX { rtcpXrSessionIDCallState, rtcpXrSessionIDIndex }
```

```
::= { rtcpXrBaseParamTable 1 }
```

```
RtcpXrBaseParamEntry ::= SEQUENCE {
```

rtcpXrBaseParamCodecType	OCTET STRING,
rtcpXrBaseParamCodecBitRate	Unsigned32,
rtcpXrBaseParamFrameDuration	Unsigned32,
rtcpXrBaseParamFramesPerPacket	Unsigned32,
rtcpXrBaseParamSampleRate	Unsigned32,
rtcpXrBaseParamDurationMs	Counter32,
rtcpXrBaseParamNetworkLossRate	Percentage,
rtcpXrBaseParamAvgDiscardRate	Percentage,
rtcpXrBaseParamBurstLossDensity	Percentage,
rtcpXrBaseParamBurstLenMs	Gauge32,
rtcpXrBaseParamGapLossDensity	Percentage,
rtcpXrBaseParamGapLenMs	Gauge32,
rtcpXrBaseParamAvgOWDelay	Gauge32,
rtcpXrBaseParamAvgEndSysDelay	Gauge32,
rtcpXrBaseParamNoiseLeveldBm	LeveldB,
rtcpXrBaseParamSignalLeveldBm	LeveldB,
rtcpXrBaseParamLocalRERLdB	LeveldB,
rtcpXrBaseParamRemoteRERLdB	LeveldB,
rtcpXrBaseParamPlcType	INTEGER,

rtcpXrBaseParamJBuffAdaptMode	INTEGER,
rtcpXrBaseParamJBuffAdaptRate	Unsigned32,
rtcpXrBaseParamJBuffAverageDelay	Gauge32,
rtcpXrBaseParamJBuffMaximumDelay	Gauge32,
rtcpXrBaseParamJBuffAbsMaxDelay	Gauge32,
rtcpXrBaseParamJitterLevel	Gauge32
}	

rtcpXrBaseParamCodecType OBJECT-TYPE
SYNTAX OCTET STRING (SIZE(0..32))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Codec type used on this call. The format used shall be
 ITU-T G.7xx, GSM FR, GSM EFR, GSM HR, AMR, AMR WB, iLBC
 or similar. For example 'ITU G.729A'. It is recommended
 that Codecs are described in consistently with SDP."
 ::= { rtcpXrBaseParamEntry 1 }

rtcpXrBaseParamCodecBitRate OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Codec rate in use at the time this data was captured
 expressed in bits per second. For example G.711 would
 have the rate 64000 and G.729 would have the rate 8000."
 ::= { rtcpXrBaseParamEntry 2 }

rtcpXrBaseParamFrameDuration OBJECT-TYPE
SYNTAX Unsigned32 (0..16384)
UNITS "sample clock ticks"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Companion information to Codec type. This represents the
 duration of the time interval represented by a frame, which
 is generally equivalent to the nominal spacing of frames.
 This is expressed in sample clock ticks as defined under
 rtxpXrSampleRate.
 This parameter may be equated to the SDP ptime parameter
 which is expressed in milliseconds (however which cannot
 represent certain Codec types, e.g. those with 2.5mS
 frames)."
 ::= { rtcpXrBaseParamEntry 3 }

rtcpXrBaseParamFramesPerPacket OBJECT-TYPE
SYNTAX Unsigned32 (0..65535)
UNITS "frames per packet"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Number of Codec frames contained in a single IP packet in
 this RTP stream at the time of sampling. The duration of
 speech per IP packet is the product of Frame Duration and
 Frames Per Packet. This may vary during a call."
 ::= { rtcpXrBaseParamEntry 4 }

rtcpXrBaseParamSampleRate OBJECT-TYPE
SYNTAX Unsigned32 (0..16777215)
UNITS "samples per second"
MAX-ACCESS read-only

Clark

Expires April 2006

[Page 13]

STATUS current

DESCRIPTION

"Companion information to Codec type. This represents the rate at which media was sampled (e.g. 8000 for narrowband voice, 16000 for wideband voice)."

::= { rtcpXrBaseParamEntry 5 }

rtcpXrBaseParamDurationMs OBJECT-TYPE

SYNTAX Counter32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Current duration of call in milliseconds if still active, duration of call in milliseconds if complete."

::= { rtcpXrBaseParamEntry 6 }

rtcpXrBaseParamNetworkLossRate OBJECT-TYPE

SYNTAX Percentage

UNITS "percent"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Average rate of network packet loss."

REFERENCE

"See [RFC3611 Section 4.7.](#)"

::= { rtcpXrBaseParamEntry 7 }

rtcpXrBaseParamAvgDiscardRate OBJECT-TYPE

SYNTAX Percentage

UNITS "percent"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Average rate of discards due to jitter."

REFERENCE

"See [RFC3611 Section 4.7.](#)"

::= { rtcpXrBaseParamEntry 8 }

rtcpXrBaseParamBurstLossDensity OBJECT-TYPE

SYNTAX Percentage

UNITS "percent"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Density of loss and discarded packets during burst periods."

REFERENCE

"See [RFC3611 Section 4.7.](#)"

::= { rtcpXrBaseParamEntry 9 }

rtcpXrBaseParamBurstLenMs OBJECT-TYPE
SYNTAX Gauge32
UNITS "milliseconds"
MAX-ACCESS read-only

Clark

Expires April 2006

[Page 14]

STATUS current
DESCRIPTION
 "Average length of bursts in milliseconds."
REFERENCE
 "See [RFC3611 Section 4.7.](#)"
::= { rtcpXrBaseParamEntry 10 }

rtcpXrBaseParamGapLossDensity OBJECT-TYPE
SYNTAX Percentage
UNITS "percent"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Density of loss and discarded packets during gap periods."
REFERENCE
 "See [RFC3611 Section 4.7.](#)"
::= { rtcpXrBaseParamEntry 11 }

rtcpXrBaseParamGapLenMs OBJECT-TYPE
SYNTAX Gauge32
UNITS "milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Average length of gaps in milliseconds."
REFERENCE
 "See [RFC3611 Section 4.7.](#)"
::= { rtcpXrBaseParamEntry 12 }

rtcpXrBaseParamAvgOWDelay OBJECT-TYPE
SYNTAX Gauge32
UNITS "milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Average (symmetric) one way RTCP delay on call. A value of zero indicates that this value has not yet been determined."
REFERENCE
 "See [RFC3611 Section 4.7.](#)"
::= { rtcpXrBaseParamEntry 13 }

rtcpXrBaseParamAvgEndSysDelay OBJECT-TYPE
SYNTAX Gauge32
UNITS "milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Average end system delay on call. A value of zero may indicate that this value has not yet been determined."

REFERENCE

"See [RFC3611 Section 4.7.](#)"
::= { rtcpXrBaseParamEntry 14 }

Clark

Expires April 2006

[Page 15]

rtcpXrBaseParamNoiseLeveldBm OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm0"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Measured received silent period noise level in dBm.
A value of 127 indicates that this parameter is not available.

In midpoint applications this parameter may not be available. If this is a midstream device and call quality metrics were calculated using the value of this parameter reported from the endpoint in an RTCP XR payload then the value used in this calculation MAY be reported."

REFERENCE

"See [RFC3611 Section 4.7](#)."

::= { rtcpXrBaseParamEntry 15 }

rtcpXrBaseParamSignalLeveldBm OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm0"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Measured received signal level during talkspurts in dBm.
A value of 127 indicates that this parameter is not available.

In midpoint applications this parameter may not be available. If this is a midstream device and call quality metrics were calculated using the value of this parameter reported from the endpoint in an RTCP XR payload then the value used in this calculation MAY be reported."

REFERENCE

"See [RFC3611 Section 4.7](#)."

::= { rtcpXrBaseParamEntry 16 }

rtcpXrBaseParamLocalRERLdB OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Residual Echo Return Loss measured at this endpoint, or at the terminating endpoint of this RTP session. This relates to the echo level from the network beyond the terminating endpoint and may be interpreted as either line echo in the case of a gateway or acoustic echo in the

case of a handset.

Note that this echo affects conversational quality as perceived by the user at the originating end of this RTP session.

A value of 127 indicates that this parameter is not

available.

In midpoint applications this parameter may not be available. If this is a midstream device and call quality metrics were calculated using the value of this parameter reported from the endpoint in an RTCP XR payload then the value used in this calculation MAY be reported."

REFERENCE

"See [RFC3611 Section 4.7](#)."

::= { rtcpXrBaseParamEntry 17 }

rtcpXrBaseParamRemoteRERLdB OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Residual Echo Return Loss measured at originating endpoint of this RTP session (i.e. the remote endpoint if this MIB is implemented in an endpoint).

Note that this affects the conversational quality metrics reported by the terminating (this) endpoint, hence is useful in understanding what has affected the reported call quality metrics

A value of 127 indicates that this parameter is not available.

In midpoint applications this parameter may not be available. If this is a midstream device and call quality metrics were calculated using the value of this parameter reported from the endpoint in an RTCP XR payload then the value used in this calculation MAY be reported."

REFERENCE

"See [RFC3611 Section 4.7](#)."

::= { rtcpXrBaseParamEntry 18 }

rtcpXrBaseParamPlcType OBJECT-TYPE

SYNTAX INTEGER { disabled(1),
enhanced(2),
standard(3),
unspecified (4)}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Defines type of packet loss concealment used on this call."

REFERENCE

"See [RFC3611 Section 4.7](#)."

::= { rtcpXrBaseParamEntry 19 }

```
rtcpXrBaseParamJBuffAdaptMode OBJECT-TYPE
    SYNTAX INTEGER { reserved (1),
                    nonAdaptive (2),
                    adaptive (3),
                    unknown (4) }
```

Clark

Expires April 2006

[Page 17]

MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Defines if jitter buffer is in fixed or adaptive mode."
REFERENCE
 "See [RFC3611 Section 4.7.](#)"
::= { rtcpXrBaseParamEntry 20 }

rtcpXrBaseParamJBuffAdaptRate OBJECT-TYPE
SYNTAX Unsigned32 (0..15)
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Estimated adaptation rate of jitter buffer."
REFERENCE
 "See [RFC3611 Section 4.7.](#)"
::= { rtcpXrBaseParamEntry 21 }

rtcpXrBaseParamJBuffAverageDelay OBJECT-TYPE
SYNTAX Gauge32
UNITS "milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Average size of jitter buffer in mS."
REFERENCE
 "See [RFC3611 Section 4.7.](#)"
::= { rtcpXrBaseParamEntry 22 }

rtcpXrBaseParamJBuffMaximumDelay OBJECT-TYPE
SYNTAX Gauge32
UNITS "milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Maximum delay through jitter buffer at current size in mS."
REFERENCE
 "See [RFC3611 Section 4.7.](#)"
::= { rtcpXrBaseParamEntry 23 }

rtcpXrBaseParamJBuffAbsMaxDelay OBJECT-TYPE
SYNTAX Gauge32
UNITS "milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "Absolute maximum size jitter buffer can reach in mS."
REFERENCE
 "See [RFC3611 Section 4.7.](#)"

```
::= { rtcpXrBaseParamEntry 24 }
```

```
rtcpXrBaseParamJitterLevel OBJECT-TYPE  
    SYNTAX Gauge32  
    UNITS "milliseconds"
```

Clark

Expires April 2006

[Page 18]

```

MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Average jitter level measured according to RFC3550 and
    represented in terms of milliseconds."
REFERENCE
    "See RFC3550 Section 6.4."
::= { rtcpXrBaseParamEntry 25 }

```

```

--
-- Table of Call Quality Metrics
--

```

```

rtcpXrCallQualityTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RtcpXrCallQualityEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Table of voice quality metrics. A row is created
        in this table for each row in the Session table."
    ::= { rtcpXrMIBObjects 3 }

```

```

rtcpXrCallQualityEntry OBJECT-TYPE
    SYNTAX RtcpXrCallQualityEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "An entry in the table of voice quality metrics. A row in
        this table is created for each row in the Session
        table."
    INDEX { rtcpXrSessionIDCallState, rtcpXrSessionIDIndex }
    ::= { rtcpXrCallQualityTable 1 }

```

```

RtcpXrCallQualityEntry ::= SEQUENCE {
    rtcpXrCallQualityRCQ                Rfactor,
    rtcpXrCallQualityRLQ                Rfactor,
    rtcpXrCallQualityExternalRCQ       Rfactor,
    rtcpXrCallQualityMOSCQ             ScaledMOSscore,
    rtcpXrCallQualityMOSLQ             ScaledMOSscore,
    rtcpXrCallQualityRLQestAlgorithm   OCTET STRING,
    rtcpXrCallQualityRCQestAlgorithm   OCTET STRING,
    rtcpXrCallQualityMOSLQestAlgorithm OCTET STRING,
    rtcpXrCallQualityMOSCQestAlgorithm OCTET STRING
}

```

```

rtcpXrCallQualityRCQ OBJECT-TYPE
    SYNTAX Rfactor
    UNITS "R factor"

```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Conversational quality R factor for this call. This value
SHOULD be calculated using ITU G.107 (The E Model) or

Clark

Expires April 2006

[Page 19]

extended versions thereof."
REFERENCE
"See [RFC3611 Section 4.7](#)."
::= { rtcpXrCallQualityEntry 1 }

rtcpXrCallQualityRLQ OBJECT-TYPE
SYNTAX Rfactor
UNITS "R factor"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Listening quality R factor for this call. This value
SHOULD be calculated using ITU G.107 (The E Model) or
extended versions thereof."
::= { rtcpXrCallQualityEntry 2 }

rtcpXrCallQualityExternalRCQ OBJECT-TYPE
SYNTAX Rfactor
UNITS "R factor"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"External R factor for this call. This value
SHOULD be calculated using ITU G.107 (The E Model) or
extended versions thereof.
The External R factor relates to the quality of an
incoming voice from another network segment. For example
if a conference bridge terminates and re-creates voice
streams then an R factor would be calculated at the bridge
for the endpoint A to bridge segment and relayed to the
subsequent bridge to endpoint B as an External R factor.
This allows endpoint B to estimate the end-to-end call
quality."
::= { rtcpXrCallQualityEntry 3 }

rtcpXrCallQualityMOSCQ OBJECT-TYPE
SYNTAX ScaledMOSscore
UNITS "MOS x 10"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Estimated conversational quality MOS for this call
expressed in MOS x 10 (e.g. 41 = MOS of 4.1). This value
MAY be calculated by converting the R-CQ value to a MOS."
REFERENCE
"See [RFC3611 Section 4.7](#)."
::= { rtcpXrCallQualityEntry 4 }

rtcpXrCallQualityMOSLQ OBJECT-TYPE

SYNTAX ScaledMOSscore
UNITS "MOS x 10"
MAX-ACCESS read-only
STATUS current
DESCRIPTION

Clark

Expires April 2006

[Page 20]

"Estimated listening quality MOS for this call
expressed in MOS x 10 (e.g. 41 = MOS of 4.1). This value
MAY be calculated by converting the R-CQ value to a MOS."

REFERENCE

"See [RFC3611 Section 4.7](#)."

::= { rtcpXrCallQualityEntry 5 }

rtcpXrCallQualityRLQestAlgorithm OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(0..128))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Call quality algorithm used to determine R-LQ factors.
For example, 'ITU-T G.107' for the ITU G.107
E model or 'ETSI TS101329-5E' for ETSI
TS 101 329-5 Annex E."

::= { rtcpXrCallQualityEntry 6 }

rtcpXrCallQualityRCQestAlgorithm OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(0..128))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Call quality algorithm used to determine R-CQ factors.
For example, 'ITU-T G.107' for the ITU G.107
E model or 'ETSI TS101329-5E' for ETSI
TS 101 329-5 Annex E."

::= { rtcpXrCallQualityEntry 7 }

rtcpXrCallQualityMOSLQestAlgorithm OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(0..128))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Call quality algorithm used to determine MOS-LQ scores.
If any localized parameter scaling is used
(for example Japan's TTC MOS scaling) then this
MUST also be reported."

::= { rtcpXrCallQualityEntry 8 }

rtcpXrCallQualityMOSCQestAlgorithm OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(0..128))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Call quality algorithm used to determine MOS-CQ scores.
If any localized parameter scaling is used
(for example Japan's TTC MOS scaling) then this
MUST also be reported."

```
::= { rtcpXrCallQualityEntry 9 }
```

```
--
```

```
-- History Table
```

```
--
```

Clark

Expires April 2006

[Page 21]

--

rtcpXrHistoryTable OBJECT-TYPE

SYNTAX SEQUENCE OF RtcpXrHistoryEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Table of aggregate measurement data for groups
of RTP sessions. A group may be a flow or any
other logical association of streams."

::= { rtcpXrMIBObjects 4 }

rtcpXrHistoryEntry OBJECT-TYPE

SYNTAX RtcpXrHistoryEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in the table of call history records."

INDEX { rtcpXrHistoryIndex }

::= { rtcpXrHistoryTable 1 }

RtcpXrHistoryEntry ::= SEQUENCE {

rtcpXrHistoryIndex	Unsigned32,
rtcpXrHistoryGroupName	OCTET STRING,
rtcpXrHistoryStartTime	DateAndTime,
rtcpXrHistoryStopTime	DateAndTime,
rtcpXrHistoryNumOfSessions	Counter32,
rtcpXrHistoryMinDurationMs	Gauge32,
rtcpXrHistoryMaxDurationMs	Gauge32,
rtcpXrHistoryAvgDurationMs	Gauge32,
rtcpXrHistoryMaxNetworkLossRate	Percentage,
rtcpXrHistoryAvgNetworkLossRate	Percentage,
rtcpXrHistoryMaxDiscardRate	Percentage,
rtcpXrHistoryAvgDiscardRate	Percentage,
rtcpXrHistoryMaxBurstLossDensity	Percentage,
rtcpXrHistoryAvgBurstLossDensity	Percentage,
rtcpXrHistoryMinBurstLenMs	Gauge32,
rtcpXrHistoryMaxBurstLenMs	Gauge32,
rtcpXrHistoryAvgBurstLenMs	Gauge32,
rtcpXrHistoryMaxGapLossDensity	Percentage,
rtcpXrHistoryAvgGapLossDensity	Percentage,
rtcpXrHistoryMinGapLenMs	Gauge32,
rtcpXrHistoryMaxGapLenMs	Gauge32,
rtcpXrHistoryAvgGapLenMs	Gauge32,
rtcpXrHistoryMinOneWayDelay	Gauge32,
rtcpXrHistoryMaxOneWayDelay	Gauge32,
rtcpXrHistoryAvgOneWayDelay	Gauge32,
rtcpXrHistoryOneWayDelayCount	Counter32,
rtcpXrHistoryMinEndSystemDelay	Gauge32,

rtcpXrHistoryMaxEndSystemDelay
rtcpXrHistoryAvgEndSystemDelay
rtcpXrHistoryEndSystemDelayCount
rtcpXrHistoryMinJitterLevel
rtcpXrHistoryMaxJitterLevel

Gauge32,
Gauge32,
Counter32,
Gauge32,
Gauge32,

Clark

Expires April 2006

[Page 22]

```

rtcpXrHistoryAvgJitterLevel      Gauge32,
rtcpXrHistoryMinNoiseLeveldBm    LeveldB,
rtcpXrHistoryMaxNoiseLeveldBm    LeveldB,
rtcpXrHistoryAvgNoiseLeveldBm    LeveldB,
rtcpXrHistoryNoiseLevelCount     Counter32,
rtcpXrHistoryMinSignalLeveldBm    LeveldB,
rtcpXrHistoryMaxSignalLeveldBm    LeveldB,
rtcpXrHistoryAvgSignalLeveldBm    LeveldB,
rtcpXrHistorySignalLevelCount     Counter32,
rtcpXrHistoryMinLocalRERLdB       LeveldB,
rtcpXrHistoryMaxLocalRERLdB       LeveldB,
rtcpXrHistoryAvgLocalRERLdB       LeveldB,
rtcpXrHistoryLocalRERLCount       Counter32,
rtcpXrHistoryMinRemoteRERLdB      LeveldB,
rtcpXrHistoryMaxRemoteRERLdB      LeveldB,
rtcpXrHistoryAvgRemoteRERLdB      LeveldB,
rtcpXrHistoryRemoteRERLCount      Counter32,
rtcpXrHistoryMinRCQ               Rfactor,
rtcpXrHistoryMaxRCQ               Rfactor,
rtcpXrHistoryAvgRCQ               Rfactor,
rtcpXrHistoryRCQCount             Counter32,
rtcpXrHistoryMinRLQ               Rfactor,
rtcpXrHistoryMaxRLQ               Rfactor,
rtcpXrHistoryAvgRLQ               Rfactor,
rtcpXrHistoryRLQCount             Counter32,
rtcpXrHistoryMinMOSQC             ScaledMOSscore,
rtcpXrHistoryMaxMOSQC             ScaledMOSscore,
rtcpXrHistoryAvgMOSQC             ScaledMOSscore,
rtcpXrHistoryMOSQCCount           Counter32,
rtcpXrHistoryMinMOSLQ             ScaledMOSscore,
rtcpXrHistoryMaxMOSLQ             ScaledMOSscore,
rtcpXrHistoryAvgMOSLQ             ScaledMOSscore,
rtcpXrHistoryMOSLQCount           Counter32,
rtcpXrHistoryCQAlgorithm          OCTET STRING,
rtcpXrHistoryReset                INTEGER
}

```

```

rtcpXrHistoryIndex OBJECT-TYPE
    SYNTAX Unsigned32 (0..4294967295)
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Index for this set of aggregate data."
    ::= { rtcpXrHistoryEntry 1 }

```

```

rtcpXrHistoryGroupName OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE(0..128))
    MAX-ACCESS read-write

```

STATUS current

DESCRIPTION

"Name of this set of aggregate data. Examples may include a flow, an interface or some other logical grouping of RTP sessions."

::= { rtcpXrHistoryEntry 2 }

Clark

Expires April 2006

[Page 23]

rtcpXrHistoryStartTime OBJECT-TYPE
SYNTAX DateAndTime
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Time at which this history was reset or started."
::= {rtcpXrHistoryEntry 3 }

rtcpXrHistoryStopTime OBJECT-TYPE
SYNTAX DateAndTime
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Time at which this history was stopped."
::= {rtcpXrHistoryEntry 4 }

rtcpXrHistoryNumOfSessions OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Number of calls included in this history."
::= {rtcpXrHistoryEntry 5 }

rtcpXrHistoryMinDurationMs OBJECT-TYPE
SYNTAX Gauge32
UNITS "milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Minimum duration of calls."
::= {rtcpXrHistoryEntry 6 }

rtcpXrHistoryMaxDurationMs OBJECT-TYPE
SYNTAX Gauge32
UNITS "milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Maximum duration of calls."
::= {rtcpXrHistoryEntry 7 }

rtcpXrHistoryAvgDurationMs OBJECT-TYPE
SYNTAX Gauge32
UNITS "milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Average duration of calls within this history."

```
::= {rtcpXrHistoryEntry 8 }
```

```
rtcpXrHistoryMaxNetworkLossRate OBJECT-TYPE  
    SYNTAX Percentage  
    UNITS "percent"  
    MAX-ACCESS read-only
```

Clark

Expires April 2006

[Page 24]

STATUS current

DESCRIPTION

"Maximum loss rate occurring on any call in this history."

::= {rtcpXrHistoryEntry 9 }

rtcpXrHistoryAvgNetworkLossRate OBJECT-TYPE

SYNTAX Percentage

UNITS "percent"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean for all calls in this history of the individual
per call packet loss rate."

::= {rtcpXrHistoryEntry 10 }

rtcpXrHistoryMaxDiscardRate OBJECT-TYPE

SYNTAX Percentage

UNITS "percent"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum discard rate occurring on any call in this history."

::= {rtcpXrHistoryEntry 11 }

rtcpXrHistoryAvgDiscardRate OBJECT-TYPE

SYNTAX Percentage

UNITS "percent"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean for all calls in this history of the individual
per call packet discard rate."

::= {rtcpXrHistoryEntry 12 }

rtcpXrHistoryMaxBurstLossDensity OBJECT-TYPE

SYNTAX Percentage

UNITS "percent"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call average burst densities for any
call in this history. A value of 0 shall be reported if
no bursts were reported."

::= {rtcpXrHistoryEntry 13 }

rtcpXrHistoryAvgBurstLossDensity OBJECT-TYPE

SYNTAX Percentage

UNITS "percent"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean for all calls in this history of the individual
per call burst density. A value of 0 shall be reported if
no bursts were reported."

::= {rtcpXrHistoryEntry 14 }

Clark

Expires April 2006

[Page 25]

rtcpXrHistoryMinBurstLenMs OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call burst length for all calls in this history for which a burst length was reported. A value of 0 shall be reported if no bursts were present."

::= {rtcpXrHistoryEntry 15 }

rtcpXrHistoryMaxBurstLenMs OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call burst length for all calls in this history for which a burst length was reported. A value of 0 shall be reported if no bursts were present."

::= {rtcpXrHistoryEntry 16 }

rtcpXrHistoryAvgBurstLenMs OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call burst length for all calls in this history for which a burst length was reported. A value of 0 shall be reported if no bursts were present."

::= {rtcpXrHistoryEntry 17 }

rtcpXrHistoryMaxGapLossDensity OBJECT-TYPE

SYNTAX Percentage

UNITS "percent"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call gap density for all calls in this history for which a gap density was reported. A value of 0 shall be reported if no gaps were present."

::= {rtcpXrHistoryEntry 18 }

rtcpXrHistoryAvgGapLossDensity OBJECT-TYPE

SYNTAX Percentage

UNITS "percent"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call gap density for all calls in this history for which a gap density was reported. A value of 0 shall be reported if no gaps were present."
::= {rtcpXrHistoryEntry 19 }

Clark

Expires April 2006

[Page 26]

rtcpXrHistoryMinGapLenMs OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call gap length for all calls in this history for which a gap length was reported. A value of 0 shall be reported if no gaps were present."

::= {rtcpXrHistoryEntry 20 }

rtcpXrHistoryMaxGapLenMs OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call gap length for all calls in this history for which a gap length was reported. A value of 0 shall be reported if no gaps were present."

::= {rtcpXrHistoryEntry 21 }

rtcpXrHistoryAvgGapLenMs OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call gap length for all calls in this history for which a gap length was reported. A value of 0 shall be reported if no gaps were present."

::= {rtcpXrHistoryEntry 22 }

rtcpXrHistoryMinOneWayDelay OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call OW Delays for all calls in this history for which a Delay was reported. A value of 0 shall be reported if no Delay values were reported."

::= {rtcpXrHistoryEntry 23 }

rtcpXrHistoryMaxOneWayDelay OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call OW Delays for all calls in this history for which a Delay was reported. A value of 0 shall be reported if no Delay values were reported."
::= {rtcpXrHistoryEntry 24 }

Clark

Expires April 2006

[Page 27]

rtcpXrHistoryAvgOneWayDelay OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call OW Delays for all calls in this history for which a Delay was reported. A value of 0 shall be reported if no Delay values were reported."

::= {rtcpXrHistoryEntry 25 }

rtcpXrHistoryOneWayDelayCount OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Number of sessions included in the One Way Delay history values (as Delay may not be available on all calls."

::= {rtcpXrHistoryEntry 26 }

rtcpXrHistoryMinEndSystemDelay OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call ES Delays for all calls in this history for which an ES Delay was reported."

::= {rtcpXrHistoryEntry 27 }

rtcpXrHistoryMaxEndSystemDelay OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call ES Delays for all calls in this history for which an ES Delay was reported."

::= {rtcpXrHistoryEntry 28 }

rtcpXrHistoryAvgEndSystemDelay OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call ES Delays for all calls in this history for which an ES Delay was reported."

::= {rtcpXrHistoryEntry 29 }

rtcpXrHistoryEndSystemDelayCount OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only

Clark

Expires April 2006

[Page 28]

STATUS current

DESCRIPTION

"Number of sessions included in the End System
Delay history values (as End System Delay
may not be available on all calls."

::= {rtcpXrHistoryEntry 30 }

rtcpXrHistoryMinJitterLevel OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call jitter for all calls in this
history for which a jitter value was reported."

::= {rtcpXrHistoryEntry 31 }

rtcpXrHistoryMaxJitterLevel OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call jitter for all calls in this
history for which a jitter value was reported."

::= {rtcpXrHistoryEntry 32 }

rtcpXrHistoryAvgJitterLevel OBJECT-TYPE

SYNTAX Gauge32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call jitter for all calls in this
history for which a jitter value was reported."

::= {rtcpXrHistoryEntry 33 }

rtcpXrHistoryMinNoiseLeveldBm OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm0"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call Noise Level for all calls in this
history for which a Noise Level value was reported."

::= {rtcpXrHistoryEntry 34 }

rtcpXrHistoryMaxNoiseLeveldBm OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm0"
MAX-ACCESS read-only
STATUS current
DESCRIPTION

Clark

Expires April 2006

[Page 29]

"Maximum of the per-call Noise Level for all calls in this history for which a Noise Level value was reported."
::= {rtcpXrHistoryEntry 35 }

rtcpXrHistoryAvgNoiseLeveldBm OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm0"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call Noise Level for all calls in this history for which a Noise Level value was reported."
::= {rtcpXrHistoryEntry 36 }

rtcpXrHistoryNoiseLevelCount OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Number of sessions included in the Noise Level history values (as Noise Level is an optional parameter and may not be present on all calls."
::= {rtcpXrHistoryEntry 37 }

rtcpXrHistoryMinSignalLeveldBm OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm0"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call Signal Level for all calls in this history for which a Signal Level value was reported."
::= {rtcpXrHistoryEntry 38 }

rtcpXrHistoryMaxSignalLeveldBm OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm0"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call Signal Level for all calls in this history for which a Signal Level value was reported."
::= {rtcpXrHistoryEntry 39 }

rtcpXrHistoryAvgSignalLeveldBm OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm0"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call Signal Level for all calls in this
history for which a Signal Level value was reported."
::= {rtcpXrHistoryEntry 40 }

Clark

Expires April 2006

[Page 30]

rtcpXrHistorySignalLevelCount OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Number of sessions included in the Signal Level history values (as Signal Level is an optional parameter and may not be present on all calls."

::= {rtcpXrHistoryEntry 41 }

rtcpXrHistoryMinLocalRERLdB OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call local RERL for all calls in this history for which a local RERL value was reported."

::= {rtcpXrHistoryEntry 42 }

rtcpXrHistoryMaxLocalRERLdB OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call local RERL for all calls in this history for which a local RERL value was reported."

::= {rtcpXrHistoryEntry 43 }

rtcpXrHistoryAvgLocalRERLdB OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call local RERL for all calls in this history for which a local RERL value was reported."

::= {rtcpXrHistoryEntry 44 }

rtcpXrHistoryLocalRERLCount OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Number of sessions included in the Local RERL history values (as Local RERL is an optional parameter and may not be present on all calls."

::= {rtcpXrHistoryEntry 45 }

rtcpXrHistoryMinRemoteRERLdB OBJECT-TYPE
SYNTAX LeveldB
UNITS "dBm"
MAX-ACCESS read-only

Clark

Expires April 2006

[Page 31]

STATUS current

DESCRIPTION

"Minimum of the per-call remote RERL for all calls in this history for which a remote RERL value was reported."

::= {rtcpXrHistoryEntry 46 }

rtcpXrHistoryMaxRemoteRERLdB OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call remote RERL for all calls in this history for which a remote RERL value was reported."

::= {rtcpXrHistoryEntry 47 }

rtcpXrHistoryAvgRemoteRERLdB OBJECT-TYPE

SYNTAX LeveldB

UNITS "dBm"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call remote RERL for all calls in this history for which a remote RERL value was reported."

::= {rtcpXrHistoryEntry 48 }

rtcpXrHistoryRemoteRERLCount OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Number of sessions included in the Remote RERL history values (as Remote RERL is an optional parameter and may not be present on all calls.)"

::= {rtcpXrHistoryEntry 49 }

rtcpXrHistoryMinRCQ OBJECT-TYPE

SYNTAX Rfactor

UNITS "R factor"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call R-CQ for all calls in this history for which an R-CQ value was reported."

::= {rtcpXrHistoryEntry 50 }

rtcpXrHistoryMaxRCQ OBJECT-TYPE

SYNTAX Rfactor

UNITS "R factor"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call R-CQ for all calls in this
history for which an R-CQ value was reported."

::= {rtcpXrHistoryEntry 51 }

Clark

Expires April 2006

[Page 32]

rtcpXrHistoryAvgRCQ OBJECT-TYPE

SYNTAX Rfactor

UNITS "R factor"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call R-CQ for all calls in this history for which an R-CQ value was reported."

::= {rtcpXrHistoryEntry 52 }

rtcpXrHistoryRCQCount OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Number of sessions included in the R CQ history values (as R CQ is an optional parameter and may not be present on all calls."

::= {rtcpXrHistoryEntry 53 }

rtcpXrHistoryMinRLQ OBJECT-TYPE

SYNTAX Rfactor

UNITS "R factor"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call R-LQ for all calls in this history for which an R-LQ value was reported."

::= {rtcpXrHistoryEntry 54 }

rtcpXrHistoryMaxRLQ OBJECT-TYPE

SYNTAX Rfactor

UNITS "R factor"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Maximum of the per-call R-LQ for all calls in this history for which an R-LQ value was reported."

::= {rtcpXrHistoryEntry 55 }

rtcpXrHistoryAvgRLQ OBJECT-TYPE

SYNTAX Rfactor

UNITS "R factor"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Mean of the per-call R-LQ for all calls in this history for which an R-LQ value was reported."

::= {rtcpXrHistoryEntry 56 }

rtcpXrHistoryRLQCount OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION

Clark

Expires April 2006

[Page 33]

"Number of sessions included in the R LQ history values (as R LQ is an optional parameter and may not be present on all calls."
 ::= {rtcpXrHistoryEntry 57 }

rtcpXrHistoryMinMOS CQ OBJECT-TYPE
SYNTAX ScaledMOSscore
UNITS "MOS x 10"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Minimum of the per-call MOS-CQ for all calls in this history for which a MOS-CQ value was reported."
 ::= {rtcpXrHistoryEntry 58 }

rtcpXrHistoryMaxMOS CQ OBJECT-TYPE
SYNTAX ScaledMOSscore
UNITS "MOS x 10"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Maximum of the per-call MOS-CQ for all calls in this history for which a MOS-CQ value was reported."
 ::= {rtcpXrHistoryEntry 59 }

rtcpXrHistoryAvgMOS CQ OBJECT-TYPE
SYNTAX ScaledMOSscore
UNITS "MOS x 10"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Mean of the per-call MOS-CQ for all calls in this history for which a MOS-CQ value was reported."
 ::= {rtcpXrHistoryEntry 60 }

rtcpXrHistoryMOS CQ Count OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Number of sessions included in the MOS CQ history values (as MOS CQ is an optional parameter and may not be present on all calls."
 ::= {rtcpXrHistoryEntry 61 }

rtcpXrHistoryMinMOS LQ OBJECT-TYPE
SYNTAX ScaledMOSscore
UNITS "MOS x 10"
MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Minimum of the per-call MOS-LQ for all calls in this
history for which a MOS-LQ value was reported."
::= {rtcpXrHistoryEntry 62 }

Clark

Expires April 2006

[Page 34]

rtcpXrHistoryMaxMOSLQ OBJECT-TYPE
SYNTAX ScaledMOSscore
UNITS "MOS x 10"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Maximum of the per-call MOS-LQ for all calls in this
history for which a MOS-LQ value was reported."
::= {rtcpXrHistoryEntry 63 }

rtcpXrHistoryAvgMOSLQ OBJECT-TYPE
SYNTAX ScaledMOSscore
UNITS "MOS x 10"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Mean of the per-call MOS-LQ for all calls in this
history for which a MOS-LQ value was reported."
::= {rtcpXrHistoryEntry 64 }

rtcpXrHistoryMOSLQCount OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Number of sessions included in the MOS LQ
history values (as MOS LQ is an optional
parameter and may not be present on all calls."
::= {rtcpXrHistoryEntry 65 }

rtcpXrHistoryCQAlgorithm OBJECT-TYPE
SYNTAX OCTET STRING (SIZE(0..32))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Call quality algorithm used - if consistent
for all calls in this history."
::= {rtcpXrHistoryEntry 66 }

rtcpXrHistoryReset OBJECT-TYPE
SYNTAX INTEGER { running (1),
stop (2),
reset (3)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Status of this row in the history table.
Writing a value of 2 to this object MUST cause

history updates to be stopped for this row. Writing a value of 3 to this object MUST cause the history row to be reset.
Reads MUST return a value of 1 if the row is still being updated or 2 if the row update has stopped."
::= {rtcpXrHistoryEntry 67 }

Clark

Expires April 2006

[Page 35]

--
-- Notifications
--

rtcpXrVoipThresholdViolation NOTIFICATION-TYPE
 OBJECTS { rtcpXrVoipAlertSeverity, rtcpXrVoipAlertType,
 rtcpXrVoipAlertInfoType, rtcpXrVoipAlertPointer }
 STATUS current
 DESCRIPTION
 "Notification that voice quality has changed
 Sent immediately when the condition is detected."
 ::= { rtcpXrEvents 1 }

rtcpXrEventParam OBJECT IDENTIFIER ::= { rtcpXrEvents 2 }

rtcpXrVoipAlertType OBJECT-TYPE
 SYNTAX SnmpAdminString
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "Text description of the type of alert. Where possible,
 this parameter should be populated with the correct
 rtcpXrVoipEntry or rtcpXrVoipHistory description."
 ::= { rtcpXrEventParam 1 }

rtcpXrVoipAlertInfoType OBJECT-TYPE
 SYNTAX INTEGER { adminStringOnly (1),
 sessionPointer (2),
 historyPointer (3)
 }
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "Indicates the type of information returned in the
 rtcpXrVoipAlertInfo parameter."
 ::= { rtcpXrEventParam 2 }

rtcpXrVoipAlertPointer OBJECT-TYPE
 SYNTAX RowPointer
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "Pointer to the table of call session information to
 identify the specific call that triggered the alert."
 ::= { rtcpXrEventParam 3 }

rtcpXrVoipAlertSeverity OBJECT-TYPE
 SYNTAX ItuPerceivedSeverity

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The severity of the alert as defined in ITU-T X.733 and
[RFC3877](#)."

Clark

Expires April 2006

[Page 36]

REFERENCE

"See Alarm MIB - [RFC3877](#)."

::= { rtcpXrEventParam 4 }

--

-- MODULE GROUPS

--

-- There are four types of RTCP XR VoIP Metrics System.

--

-- RTCP XR VOIP Metrics Systems MUST implement one of the four
-- identified types of system and SHOULD NOT implement the
-- rtcpXrMinimalCompliance system, which is included only
-- for reasons of compatibility with [RFC3611](#)'s minimal
-- requirements.

--

rtcpXrCompliances OBJECT IDENTIFIER ::= { rtcpXrConformance 1 }

rtcpXrGroups OBJECT IDENTIFIER ::= { rtcpXrConformance 2 }

rtcpXrFullMetricsCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"Describes the requirements for conformance to the
rtcpXr MIB for VoIP devices that support basic
reporting."

MODULE -- this module

MANDATORY-GROUPS { rtcpXrSessionIDGroup,
rtcpXrBaseParamGroup,
rtcpXrCallQualityGroup
}

::= { rtcpXrCompliances 1 }

rtcpXrMetricsAlertsCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"Describes the requirements for conformance to the
rtcpXr MIB for VoIP devices that support reporting
and alerts."

MODULE -- this module

MANDATORY-GROUPS { rtcpXrSessionIDGroup,
rtcpXrBaseParamGroup,
rtcpXrCallQualityGroup,
rtcpXrNotificationParmsGroup,
rtcpXrNotificationsGroup
}

::= { rtcpXrCompliances 2 }

rtcpXrMetricsHistoryCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"Describes the requirements for conformance to the
rtcpXr MIB for VoIP devices that support reporting,

Clark

Expires April 2006

[Page 37]

```
        call history and alerts."
MODULE -- this module
MANDATORY-GROUPS { rtcpXrSessionIDGroup,
                    rtcpXrBaseParamGroup,
                    rtcpXrCallQualityGroup,
                    rtcpXrMIBHistoryGroup,
                    rtcpXrNotificationParmsGroup,
                    rtcpXrNotificationsGroup }
 ::= { rtcpXrCompliances 3 }

rtcpXrHistoryCompliance MODULE-COMPLIANCE
STATUS current
DESCRIPTION
    "Describes the requirements for conformance to the
    rtcpXr MIB for VoIP devices that support only
    call history."
MODULE -- this module
MANDATORY-GROUPS { rtcpXrMIBHistoryGroup
                    }
 ::= { rtcpXrCompliances 4 }

rtcpXrMinimalCompliance MODULE-COMPLIANCE
STATUS current
DESCRIPTION
    "Describes the minimal requirements for conformance to
    the rtcpXr MIB - NOT RECOMMENDED."
MODULE -- this module
MANDATORY-GROUPS { rtcpXrSessionIDGroup,
                    rtcpXrBaseParamGroup
                    }
 ::= { rtcpXrCompliances 5 }

rtcpXrSessionIDGroup OBJECT-GROUP
OBJECTS {
    rtcpXrSessionIDSessionIdentifier,
    rtcpXrSessionIDStartTime,
    rtcpXrSessionIDStopTime,
    rtcpXrSessionIDSourceIPtype,
    rtcpXrSessionIDSourceIPaddress,
    rtcpXrSessionIDSourceRTPport,
    rtcpXrSessionIDSourceRTPport,
    rtcpXrSessionIDDestIPtype,
    rtcpXrSessionIDDestIPaddress,
    rtcpXrSessionIDDestRTPport,
    rtcpXrSessionIDDestRTPport,
    rtcpXrSessionIDDestIdentifier,
    rtcpXrSessionIDDestIdentType,
    rtcpXrSessionIDSrceIdentifier,
    rtcpXrSessionIDSrceIdentType,
```

```
rtcpXrSessionIDMeasurePt,  
rtcpXrSessionIDMeasurePtID,  
rtcpXrSessionIDReverseSession,  
rtcpXrSessionIDAltMeasurePt  
}
```

Clark

Expires April 2006

[Page 38]

STATUS current

DESCRIPTION

"Session ID objects used in rtcpXr VoIP Metrics MIB"

::= { rtcpXrGroups 1 }

rtcpXrBaseParamGroup OBJECT-GROUP

OBJECTS {

rtcpXrBaseParamCodecType,
rtcpXrBaseParamCodecBitRate,
rtcpXrBaseParamFrameDuration,
rtcpXrBaseParamFramesPerPacket,
rtcpXrBaseParamSampleRate,
rtcpXrBaseParamDurationMs,
rtcpXrBaseParamNetworkLossRate,
rtcpXrBaseParamAvgDiscardRate,
rtcpXrBaseParamBurstLossDensity,
rtcpXrBaseParamBurstLenMs,
rtcpXrBaseParamGapLossDensity,
rtcpXrBaseParamGapLenMs,
rtcpXrBaseParamAvgOWDelay,
rtcpXrBaseParamAvgEndSysDelay,
rtcpXrBaseParamNoiseLeveldBm,
rtcpXrBaseParamSignalLeveldBm,
rtcpXrBaseParamLocalRERLdB,
rtcpXrBaseParamRemoteRERLdB,
rtcpXrBaseParamPlcType,
rtcpXrBaseParamJBuffAdaptMode,
rtcpXrBaseParamJBuffAdaptRate,
rtcpXrBaseParamJBuffAverageDelay,
rtcpXrBaseParamJBuffMaximumDelay,
rtcpXrBaseParamJBuffAbsMaxDelay,
rtcpXrBaseParamJitterLevel
}

STATUS current

DESCRIPTION

"Objects used in rtcpXr VoIP Metrics MIB"

::= { rtcpXrGroups 2 }

rtcpXrCallQualityGroup OBJECT-GROUP

OBJECTS {

rtcpXrCallQualityRCQ,
rtcpXrCallQualityRLQ,
rtcpXrCallQualityExternalRCQ,
rtcpXrCallQualityMOSQ,
rtcpXrCallQualityMOSLQ,
rtcpXrCallQualityRLQestAlgorithm,
rtcpXrCallQualityRCQestAlgorithm,
rtcpXrCallQualityMOSLQestAlgorithm,
rtcpXrCallQualityMOSQestAlgorithm

```
    }  
STATUS current  
DESCRIPTION  
    "Call quality objects used in rtcpXr VoIP Metrics MIB"  
 ::= { rtcpXrGroups 3 }
```

Clark

Expires April 2006

[Page 39]

```
rtcpXrMIBHistoryGroup OBJECT-GROUP
  OBJECTS {
    rtcpXrHistoryGroupName,
    rtcpXrHistoryStartTime,
    rtcpXrHistoryStopTime,
    rtcpXrHistoryNumOfSessions,
    rtcpXrHistoryMinDurationMs,
    rtcpXrHistoryMaxDurationMs,
    rtcpXrHistoryAvgDurationMs,
    rtcpXrHistoryMaxNetworkLossRate,
    rtcpXrHistoryAvgNetworkLossRate,
    rtcpXrHistoryMaxDiscardRate,
    rtcpXrHistoryAvgDiscardRate,
    rtcpXrHistoryMaxBurstLossDensity,
    rtcpXrHistoryAvgBurstLossDensity,
    rtcpXrHistoryMinBurstLenMs,
    rtcpXrHistoryMaxBurstLenMs,
    rtcpXrHistoryAvgBurstLenMs,
    rtcpXrHistoryMaxGapLossDensity,
    rtcpXrHistoryAvgGapLossDensity,
    rtcpXrHistoryMinGapLenMs,
    rtcpXrHistoryMaxGapLenMs,
    rtcpXrHistoryAvgGapLenMs,
    rtcpXrHistoryMinOneWayDelay,
    rtcpXrHistoryMaxOneWayDelay,
    rtcpXrHistoryAvgOneWayDelay,
    rtcpXrHistoryOneWayDelayCount,
    rtcpXrHistoryMinEndSystemDelay,
    rtcpXrHistoryMaxEndSystemDelay,
    rtcpXrHistoryAvgEndSystemDelay,
    rtcpXrHistoryEndSystemDelayCount,
    rtcpXrHistoryAvgJitterLevel,
    rtcpXrHistoryMinJitterLevel,
    rtcpXrHistoryMaxJitterLevel,
    rtcpXrHistoryMinNoiseLeveldBm,
    rtcpXrHistoryMaxNoiseLeveldBm,
    rtcpXrHistoryAvgNoiseLeveldBm,
    rtcpXrHistoryNoiseLevelCount,
    rtcpXrHistoryMinSignalLeveldBm,
    rtcpXrHistoryMaxSignalLeveldBm,
    rtcpXrHistoryAvgSignalLeveldBm,
    rtcpXrHistorySignalLevelCount,
    rtcpXrHistoryMinLocalRERLDdB,
    rtcpXrHistoryMaxLocalRERLDdB,
    rtcpXrHistoryAvgLocalRERLDdB,
    rtcpXrHistoryLocalRERLCount,
    rtcpXrHistoryMinRemoteRERLDdB,
    rtcpXrHistoryMaxRemoteRERLDdB,
    rtcpXrHistoryAvgRemoteRERLDdB,
```

rtcpXrHistoryRemoteRERLCount,
rtcpXrHistoryMinRCQ,
rtcpXrHistoryMaxRCQ,
rtcpXrHistoryAvgRCQ,
rtcpXrHistoryRCQCount,

Clark

Expires April 2006

[Page 40]

```
        rtcpXrHistoryMinRLQ,
        rtcpXrHistoryMaxRLQ,
        rtcpXrHistoryAvgRLQ,
        rtcpXrHistoryRLQCount,
        rtcpXrHistoryMinMOSCQ,
        rtcpXrHistoryMaxMOSCQ,
        rtcpXrHistoryAvgMOSCQ,
        rtcpXrHistoryMOSCQCount,
        rtcpXrHistoryMinMOSLQ,
        rtcpXrHistoryMaxMOSLQ,
        rtcpXrHistoryAvgMOSLQ,
        rtcpXrHistoryMOSLQCount,
        rtcpXrHistoryCQAlgorithm,
        rtcpXrHistoryReset
    }
STATUS current
DESCRIPTION
    "Objects used in rtcpXr VoIP History MIB"
 ::= { rtcpXrGroups 4 }

rtcpXrNotificationParmsGroup OBJECT-GROUP
    OBJECTS {
        rtcpXrVoipAlertSeverity,
        rtcpXrVoipAlertType,
        rtcpXrVoipAlertInfoType,
        rtcpXrVoipAlertPointer
    }
STATUS current
DESCRIPTION
    "Notification parameters emitted by a rtcpXr endpoint."
 ::= { rtcpXrGroups 5 }

rtcpXrNotificationsGroup NOTIFICATION-GROUP
    NOTIFICATIONS {
        rtcpXrVoipThresholdViolation
    }
STATUS current
DESCRIPTION
    "Notifications emitted by a rtcpXr endpoint."
 ::= { rtcpXrGroups 6 }
```

END

Clark

Expires April 2006

[Page 41]

4. Security Considerations

Certain MIB objects contain endpoint identifying information:

```
rtcpXrSessionIDSourceIPAddress  
rtcpXrSessionIDDestIPAddress  
rtcpXrSessionIDSrcIdentifier  
rtcpXrSessionIDDestIdentifier
```

Unauthorized exposure of these objects may lead to disclosure of the addresses of the participants in applications, or information about the traffic patterns of the applications, which may be considered sensitive in certain environments.

Access to `rtcpXrHistoryReset` can result in resetting the table of aggregate call quality information, which results in the loss of useful management data.

It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt their values when sending them over the network via SNMP.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

5. IANA Considerations

An OID within the `mib-2` tree is requested, following which this note may be deleted.

6. Acknowledgements

The authors would like to acknowledge the input and advice provided by Dan Romascanu, Rajesh Kumar. Kim Curran and Shane Holthaus.

Clark

Expires April 2006

[Page 42]

7. Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

8. Normative References

- [RFC3550] Shulzrinne, H., Casner, S., Frederick, R. and V. Jacobson, "RTP: A Transport Protocol for real-time applications," [RFC 3550](#), July 2003.
- [RFC3611] Friedman, T., Caceres, R., Clark, A., "RTP Control Protocol Reporting Extensions (RTCP XR)," [RFC 3611](#), [October/November] 2003
- [RFC2578] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), December 1999.
- [RFC2579] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), December 1999.
- [RFC2580] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), December 1999.

9. Informative References

[RFC3410] Case, J., Mundy, R., Partain, D. and Stewart, B.,
"Introduction and Applicability Statements for Internet
Standard Management Framework", [RFC 3410](#), December 2002

Clark

Expires April 2006

[Page 43]

8. Authors' Addresses

Alan Clark
Telchemy Incorporated
3360 Martins Farm Road, Ste 200
Suwanee, Georgia 30024
U.S.A.

Email: alan@telchemy.com

Amy Pendleton
Nortel
2380 Performance Drive
Richardson, Texas 75081
U.S.A.

Email: aspen@nortel.com

9. Full Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

Clark

Expires April 2006

[Page 44]

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

