

AVTCORE
Internet-Draft
Updates: [3550](#), [4585](#) (if approved)
Intended status: Standards Track
Expires: November 29, 2014

J. Lennox
Vidyo
M. Westerlund
Ericsson
Q. Wu
Huawei
C. Perkins
University of Glasgow
May 28, 2014

Sending Multiple Media Streams in a Single RTP Session **draft-ietf-avtccore-rtp-multi-stream-04**

Abstract

This document expands and clarifies the behavior of the Real-Time Transport Protocol (RTP) endpoints when they are using multiple synchronization sources (SSRCs), e.g. for sending multiple media streams, in a single RTP session. In particular, issues involving RTCP Control Protocol (RTCP) messages are described.

This document updates [RFC 3550](#) in regards to handling of multiple SSRCs per endpoint in RTP sessions. It also updates [RFC 4585](#) to update and clarify the calculation of the timeout of SSRCs and the inclusion of feedback messages.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 29, 2014.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Terminology	3
3.	Use Cases For Multi-Stream Endpoints	4
3.1.	Multiple-Capturer Endpoints	4
3.2.	Multi-Media Sessions	4
3.3.	Multi-Stream Mixers	4
3.4.	Multiple SSRCs for a Single Media Source	5
4.	Multi-Stream Endpoint RTP Media Recommendations	5
5.	Multi-Stream Endpoint RTCP Recommendations	5
5.1.	RTCP Reporting Requirement	5
5.2.	Initial Reporting Interval	6
5.3.	Compound RTCP Packets	6
5.3.1.	Maintaining AVG_RTCP_SIZE	7
5.3.2.	Scheduling RTCP with Multiple Reporting SSRCs	8
5.4.	RTP/AVPF Feedback Packets	10
5.4.1.	The SSRC Used	10
5.4.2.	Scheduling a Feedback Packet	11
6.	RTCP Considerations for Streams with Disparate Rates	12
6.1.	Timing out SSRCs	13
6.1.1.	AVPF T_rr_interval Behavior	13
6.1.2.	Avoiding Pre-mature Timeout	14
6.1.3.	AVP and AVPF Interoperability	15
6.1.4.	Specified Behavior	16
6.2.	Tuning RTCP transmissions	17
6.2.1.	RTP/AVP and RTP/SAVP	17
6.2.2.	RT/AVPF and RTP/SAVPF	18
7.	Security Considerations	19
8.	Open Issues	20
9.	IANA Considerations	20
10.	References	20
10.1.	Normative References	20

10.2.	Informative References	21
Appendix A.	Changes From Earlier Versions	22
A.1.	Changes From WG Draft -02	22
A.2.	Changes From WG Draft -01	22
A.3.	Changes From WG Draft -00	22
A.4.	Changes From Individual Draft -02	23
A.5.	Changes From Individual Draft -01	23
A.6.	Changes From Individual Draft -00	23
Authors' Addresses	24

[1.](#) Introduction

At the time The Real-Time Transport Protocol (RTP) [[RFC3550](#)] was originally written, and for quite some time after, endpoints in RTP sessions typically only transmitted a single media stream, and thus used a single synchronization source (SSRC) per RTP session, where separate RTP sessions were typically used for each distinct media type.

Recently, however, a number of scenarios have emerged (discussed further in [Section 3](#)) in which endpoints wish to send multiple RTP media streams, distinguished by distinct RTP synchronization source (SSRC) identifiers, in a single RTP session. Although RTP's initial design did consider such scenarios, the specification was not consistently written with such use cases in mind. The specifications are thus somewhat unclear.

The purpose of this document is to expand and clarify [[RFC3550](#)]'s language for these use cases. The authors believe this does not result in any major normative changes to the RTP specification, however this document defines how the RTP specification is to be interpreted. In these cases, this document updates [RFC3550](#). The document also updates [RFC 4585](#) in regards to the timeout of inactive SSRCs as specified in [Section 6.1](#) to resolve problematic behavior as well as clarifying the inclusion of feedback messages.

The document starts with terminology and some use cases where multiple sources will occur. This is followed by RTP and RTCP recommendations to resolve issues. Next are security considerations and remaining open issues.

[2.](#) Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)] and indicate requirement levels for compliant implementations.

3. Use Cases For Multi-Stream Endpoints

This section discusses several use cases that have motivated the development of endpoints that send RTP data using multiple SSRCs in a single RTP session.

3.1. Multiple-Capturer Endpoints

The most straightforward motivation for an endpoint to send multiple RTP streams in a session is the scenario where an endpoint has multiple capture devices, and thus media sources, of the same media type and characteristics. For example, telepresence endpoints, of the type described by the CLUE Telepresence Framework [[I-D.ietf-clue-framework](#)], often have multiple cameras or microphones covering various areas of a room.

3.2. Multi-Media Sessions

Recent work has been done in RTP [[I-D.ietf-avtcore-multi-media-rtp-session](#)] and SDP [[I-D.ietf-mmusic-sdp-bundle-negotiation](#)] to update RTP's historical assumption that media sources of different media types would always be sent on different RTP sessions. In this work, a single endpoint's audio and video RTP media streams (for example) are instead sent in a single RTP session.

3.3. Multi-Stream Mixers

There are several RTP topologies which can involve a central device that itself generates multiple RTP media streams in a session.

One example is a mixer providing centralized compositing for a multi-capture scenario like that described in [Section 3.1](#). In this case, the centralized node is behaving much like a multi-capturer endpoint, generating several similar and related sources.

More complicated is the Selective Forwarding Middlebox, see Section 3.7 of [[I-D.ietf-avtcore-rtp-topologies-update](#)]. This is a middlebox that receives media streams from several endpoints, and then selectively forwards modified versions of some of the streams toward the other endpoints it is connected to. Toward one destination, a separate media source appears in the session for every other source connected to the middlebox, "projected" from the original streams, but at any given time many of them can appear to be inactive (and thus are receivers, not senders, in RTP). This sort of device is closer to being an RTP mixer than an RTP translator, in that it terminates RTCP reporting about the mixed streams, and it can re-write SSRCs, timestamps, and sequence numbers, as well as the

contents of the RTP payloads, and can turn sources on and off at will without appearing to be generating packet loss. Each projected stream will typically preserve its original RTCP source description (SDES) information.

3.4. Multiple SSRCs for a Single Media Source

There are also several cases where a single media source results in the usage of multiple SSRCs within the same RTP session. Transport robustification tools like RTP Retransmission [[RFC4588](#)] result in multiple SSRCs, one with source data, and another with the repair data. Scalable encoders and their RTP payload formats, like H.264's extension for Scalable Video Coding(SVC) [[RFC6190](#)] can be transmitted in a configuration where the scalable layers are distributed over multiple SSRCs within the same session, to enable RTP packet stream level (SSRC) selection and routing in conferencing middleboxes.

4. Multi-Stream Endpoint RTP Media Recommendations

While an endpoint MUST (of course) stay within its share of the available session bandwidth, as determined by signalling and congestion control, this need not be applied independently or uniformly to each media stream and its SSRCs. In particular, session bandwidth MAY be reallocated among an endpoint's SSRCs, for example by varying the bandwidth use of a variable-rate codec, or changing the codec used by the media stream, up to the constraints of the session's negotiated (or declared) codecs. This includes enabling or disabling media streams and their redundancy streams as more or less bandwidth becomes available.

5. Multi-Stream Endpoint RTCP Recommendations

This section contains a number of different RTCP clarifications or recommendations that enables more efficient and simpler behavior without loss of functionality.

The RTP Control Protocol (RTCP) is defined in [Section 6 of \[RFC3550\]](#), but it is largely documented in terms of "participants". In many cases, the specification's recommendations for "participants" are to be interpreted as applying to individual SSRCs, rather than to endpoints. This section describes several concrete cases where this applies.

5.1. RTCP Reporting Requirement

For each of an endpoint's SSRCs, whether or not they are currently sending media, SR/RR and SDP packets MUST be sent at least once per RTCP report interval. (For discussion of the content of SR or RR

packets' reception statistic reports, see
[[I-D.ietf-avtcore-rtp-multi-stream-optimisation](#)].)

5.2. Initial Reporting Interval

When a new SSRC is added to a unicast session, the sentence in [[RFC3550](#)]'s [Section 6.2](#) applies: "For unicast sessions ... the delay before sending the initial compound RTCP packet MAY be zero." This applies to individual SSRCs as well. Thus, endpoints MAY send an initial RTCP packet for an SSRC immediately upon adding it to a unicast session.

This allowance also applies, as written, when initially joining a unicast session. However, in this case some caution needs to be exercised if the end-point or mixer has a large number of sources (SSRCs) as this can create a significant burst. How big an issue this is depends on the number of sources for which the initial SR or RR packets and Session Description CNAME items are to be sent, in relation to the RTCP bandwidth.

(tbd: Maybe some recommendation here? The aim in restricting this to unicast sessions was to avoid this burst of traffic, which the usual RTCP timing and reconsideration rules will prevent.)

5.3. Compound RTCP Packets

[Section 6.1 in \[RFC3550\]](#) gives the following advice to RTP translators and mixers:

"It is RECOMMENDED that translators and mixers combine individual RTCP packets from the multiple sources they are forwarding into one compound packet whenever feasible in order to amortize the packet overhead (see [Section 7](#)). An example RTCP compound packet as might be produced by a mixer is shown in Fig. 1. If the overall length of a compound packet would exceed the MTU of the network path, it SHOULD be segmented into multiple shorter compound packets to be transmitted in separate packets of the underlying protocol. This does not impair the RTCP bandwidth estimation because each compound packet represents at least one distinct participant. Note that each of the compound packets MUST begin with an SR or RR packet."

Note: To avoid confusion, an RTCP packet is an individual item, such as a Sender Report (SR), Receiver Report (RR), Source Description (SDS), Goodbye (BYE), Application Defined (APP), Feedback [[RFC4585](#)] or Extended Report (XR) [[RFC3611](#)] packet. A compound packet is the combination of two or more such RTCP

packets where the first packet has to be an SR or an RR packet, and which contains a SDES packet containing an CNAME item.

The above results in compound RTCP packets that contain multiple SR or RR packets from different sources (SSRCs) as well as any of the other packet types. There are no restrictions on the order in which the packets can occur within the compound packet, except the regular compound rule, i.e., starting with an SR or RR.

This advice applies to multi-media-stream endpoints as well, with the same restrictions and considerations. (Note, however, that the last sentence does not apply to AVPF [[RFC4585](#)] or SAVPF [[RFC5124](#)] feedback packets if Reduced-Size RTCP [[RFC5506](#)] is in use.)

5.3.1. Maintaining AVG_RTCP_SIZE

When multiple local SSRCs are sending their RTCP packets in the same compound packet, this obviously results in larger RTCP compound packets. This will have an affect on the value of the average RTCP packet size metering (avg_rtcp_size) that is done for the purpose of RTCP transmission scheduling calculation. This section discusses the impact of this and provide recommendations with how to deal with it.

This section will use the concept of an 'RTCP Compound Packet' to represent not just proper RTCP compound packets, i.e. ones that start with an SR or RR RTCP packet and include at least one SDES CNAME item. For the purpose of the below calculation, other valid lower layer datagram units an RTCP implementation can send or receive, independently if they are an aggregate or not of RTCP packets are also considered. This especially includes Reduced-Size RTCP packets [[RFC5506](#)].

The RTCP packet scheduling algorithm that is defined in RTP [[RFC3550](#)] deals with individual SSRCs. These SSRCs transmit their set of RTCP packets at each scheduled interval. Thus, to maintain this per-SSRC property of the scheduling, the avg_rtcp_size needs to be updated with per-SSRC average RTCP compound packet sizes. The avg_rtcp_size value SHALL be updated for each received or sent RTCP compound packet with the total size (including packet overhead such as IP/UDP) divided by the number of reporting SSRCs. The number of reporting SSRCs SHALL be determined by counting the number of different SSRCs that are the source of Sender Report (SR) or Receiver Report (RR) RTCP packets within the compound. A non-compound RTCP packet, i.e. it contains no SR or RR RTCP packets at all -- as can happen with Reduced-Size RTCP packets [[RFC5506](#)] -- the SSRC count SHALL be considered to be 1.

Note: The above makes it possible to amortize the packet overhead between the number of SSRCs sharing a RTCP compound packet.

For an RTCP end-point that doesn't follow the above rule, and instead uses the full RTCP compound packet size as input, the average RTCP reporting interval will be scaled up (i.e. become longer) with a factor that is proportional to the number of SSRCs sourcing RTCP packets in an RTCP compound packet as well as the set of SSRCs being aggregated in proportion to the total number of participants. This factor can quite easily become larger than 5, e.g. with an 1500 byte MTU and an average per-SSRC sum of RTCP packets of 240 bytes, the MTU will fit 6 packets. If the receiver end-point has a single SSRC and all other endpoints fill their MTU fully, the factor will be close to 6. If the RTCP configuration is such that the transmission interval is bandwidth limited, rather than any type of minimal interval limitation (T_{min} or T_{RR_INT}), then the other end-points will likely time out this SSRC due to it using an regular RTCP interval is more than 5 times the rest of the endpoints.

5.3.2. Scheduling RTCP with Multiple Reporting SSRCs

When implementing RTCP packet scheduling for cases where multiple reporting SSRCs are aggregating their RTCP packets in the same compound packet there are a number of challenges. First of all, we have the goal of not changing the general properties of the RTCP packet transmissions, which include the general inter-packet distribution, and the behavior for dealing with flash joins as well as other dynamic events.

The below specified mechanism deals with:

- o That one can't have a-priori knowledge about which RTCP packets are to be sent, or their size, prior to generating the packets. In which case, the time from generation to transmission ought to be as short as possible to minimize the information that becomes stale.
- o That one has an MTU limit, that one ought to avoid exceeding, as that requires lower-layer fragmentation (e.g., IP fragmentation) which impacts the packets' probability of reaching the receiver(s).

Schedule all the endpoint's local SSRCs individually for transmission using the regular calculation of T_n for the profile being used. Each time a SSRC's T_n timer expires, do the regular reconsideration. If the reconsideration indicates that an RTCP packet is to be sent:

1. Consider if an additional SSRC can be added. That consideration is done by picking the SSRC which has the T_n value closest in time to now (T_c).
2. Calculate how much space for RTCP packets would be needed to add that SSRC.
3. If the considered SSRC's RTCP Packets fit within the lower layer datagram's Maximum Transmission Unit, taking the necessary protocol headers into account and the consumed space by prior SSRCs, then add that SSRC's RTCP packets to the compound packet and go again to Step 1.
4. If the considered SSRC's RTCP Packets will not fit within the compound packet, then transmit the generated compound packet.
5. Update the RTCP Parameters for each SSRC that has been included in the sent RTCP packet. The T_p value for each SSRC MUST be updated as follows:

For the first SSRC: As this SSRC was the one that was reconsidered the t_p value is set to the t_c as defined in RTP [[RFC3550](#)].

For any additional SSRC: The t_p value SHALL be set to the transmission time this SSRC would have had it not been aggregated and given the current existing session context. This value is derived by taking this SSRC's T_n value and performing reconsideration and updating t_n until $t_p + T \leq t_n$. Then set t_p to this t_n value.

6. For the sent SSRCs calculate new t_n values based on the updated parameters and reschedule the timers.

Reverse reconsideration needs to be performed as specified in RTP [[RFC3550](#)]. It is important to note that under the above algorithm when performing reconsideration, the value of t_p can actually be larger than t_c . However, that still has the desired effect of proportionally pulling the t_p value towards t_c (as well as t_n) as the group size shrinks in direct proportion the reduced group size.

The above algorithm has been shown in simulations to maintain the inter-RTCP-packet transmission distribution for the SSRCs and consume the same amount of bandwidth as non-aggregated packets in RTP sessions with static sets of participants. With this algorithm the actual transmission interval for any SSRC triggering an RTCP compound packet transmission is following the regular transmission rules. It also handles the cases where the number of SSRCs that can be included

in an aggregated packet varies. An SSRC that previously was aggregated and fails to fit in a packet still has its own transmission scheduled according to normal rules. Thus, it will trigger a transmission in due time, or the SSRC will be included in another aggregate.

The algorithm's behavior under SSRC group size changes is under investigation. However, it is expected to be well behaved based on the following analyses.

RTP sessions where the number of SSRC are growing: When the group size is growing, the T_d values grow in proportion to the number of new SSRCs in the group. The reconsideration when the timer for the t_n expires, that SSRC will reconsider the transmission and with a certain probability reschedule the t_n timer. This part of the reconsideration algorithm is only impacted by the above algorithm by having t_p values that are in the future instead of set to the time of the actual last transmission at the time of updating t_p . Thus the scheduling causes in worst case a plateau effect for that SSRC. That effect depends on how far into the future t_p can advance.

RTP sessions where the number of SSRC are shrinking: When the group shrinks, reverse reconsideration moves the t_p and t_n values towards t_c proportionally to the number of SSRCs that leave the session compared to the total number of participants when they left. Thus the also group size reductions need to be handled.

In general the potential issue that might exist depends on how far into the future the t_p value can drift compared to the actual packet transmissions that occur. That drift can only occur for an SSRC that never is the trigger for RTCP packet transmission and always gets aggregated and where the calculated packet transmission interval randomly occurs so that $t_n - t_p$ for this SSRC is on average larger than the ones that gets transmitted.

5.4. RTP/AVPF Feedback Packets

This section discusses the transmission of RTP/AVPF feedback packets when the transmitting endpoint has multiple SSRCs.

5.4.1. The SSRC Used

When an RTP endpoint has multiple SSRCs, it can make certain choices on which SSRC to use as the source of an RTCP Feedback Packet. This sub-section discusses some considerations of this.

- o The media type of the media the SSRC transmits is actually not a relevant factor when considering if an SSRC can transmit a particular Feedback message.
- o Feedback messages which are Notification or Indications regarding the endpoint's own RTP packet stream need to be sent using the SSRC transmitting the media it relates to. This also includes notifications that are related to a received request or command.
- o The SSRC used to send feedback messages has a role as either a media sender or a receiver. The bandwidth pools can be different for SSRCs that are senders and receivers. Thus feedback messages that expect to be more frequent can be sent from an SSRC that has the better possibility of sending frequent RTCP compound packets or reduced size packets. This also affects the consideration if the SSRC can be used in immediate mode or not.
- o Some Feedback Types requires consistency in the sender. For example TMMBR, if one sets a limitation, the same SSRC needs to be the one that increases it. Others can simply benefit from having this property.

Note that the source of the feedback RTCP packet does not need to be any of the sources (SSRC) including SR/RR packets in a compound packet. For Reduced-Size RTCP [[RFC5506](#)] the aggregation of feedback messages from multiple sources are not limited, beyond the consideration in [Section 4.2.2 of \[RFC5506\]](#).

5.4.2. Scheduling a Feedback Packet

When an SSRC has a need to transmit a feedback packet in early mode it follows the scheduling rules defined in [Section 3.5](#) in RTP/AVPF [[RFC4585](#)]. When following these rules the following clarifications need to be taken into account:

- o That a session is considered to be point-to-point or multiparty not based on the number of SSRCs, but the number of endpoints directly seen in the RTP session by the endpoint. tbd: Clarify what is considered to "see" an endpoint?
- o Note that when checking if there is already a scheduled compound RTCP packet containing feedback messages (Step 2 in [Section 3.5.2](#)), that check is done considering all local SSRCs.

TBD: The above does not allow an SSRC that is unable to send either an early or regular RTCP packet with the feedback message within the `T_max_fb_delay` to trigger another SSRC to send an early packet to which it could piggyback. Nor does it allow feedback to piggyback on

even regular RTCP packet transmissions that occur within $T_{\text{max_fb_delay}}$. A question is if either of these behaviours ought to be allowed.

The latter appears simple and straight forward. Instead of discarding a FB message in step 4a: alternative 2, one could place such messages in a cache with a discard time equal to $T_{\text{max_fb_delay}}$, and in case any of the SSRCs schedule an RTCP packet for transmission within that time, it includes this message.

The former case can have more widespread impact on the application, and possibly also on the RTCP bandwidth consumption as it allows for more massive bursts of RTCP packets. Still, on a time scale of a regular reporting interval, it ought to have no effect on the RTCP bandwidth as the extra feedback messages increase the `avg_rtcp_size`.

6. RTCP Considerations for Streams with Disparate Rates

It is possible for a single RTP session to carry streams of greatly differing bandwidth. There are two scenarios where this can occur. The first is when a single RTP session carries multiple flows of the same media type, but with very different quality; for example a video switching multi-point conference unit might send a full rate high-definition video stream of the active speaker but only thumbnails for the other participants, all sent in a single RTP session. The second scenario occurs when audio and video flows are sent in a single RTP session, as discussed in [\[I-D.ietf-avtcore-multi-media-rtp-session\]](#).

An RTP session has a single set of parameters that configure the session bandwidth, the RTCP sender and receiver fractions (e.g., via the SDP "b=RR:" and "b=RS:" lines), and the parameters of the RTP/AVPF profile [\[RFC4585\]](#) (e.g., `trr-int`) if that profile (or its secure extension, RTP/SAVPF [\[RFC5124\]](#)) is used. As a consequence, the RTCP reporting interval will be the same for every SSRC in an RTP session. This uniform RTCP reporting interval can result in RTCP reports being sent more often than is considered desirable for a particular media type. For example, if an audio flow is multiplexed with a high quality video flow where the session bandwidth is configured to match the video bandwidth, this can result in the RTCP packets having a greater bandwidth allocation than the audio data rate. If the reduced minimum RTCP interval described in [Section 6.2 of \[RFC3550\]](#) is used in the session, which might be appropriate for video where rapid feedback is wanted, the audio sources could be expected to send RTCP packets more often than they send audio data packets. This is most likely undesirable, and while the mismatch can be reduced through careful tuning of the RTCP parameters, particularly `trr_int` in RTP/AVPF sessions, it is inherent in the design of the RTCP timing

rules, and affects all RTP sessions containing flows with mismatched bandwidth.

Having multiple media types in one RTP session also results in more SSRCs being present in this RTP session. This increasing the amount of cross reporting between the SSRCs. From an RTCP perspective, two RTP sessions with half the number of SSRCs in each will be slightly more efficient. If someone needs either the higher efficiency due to the lesser number of SSRCs or the fact that one can't tailor RTCP usage per media type, they need to use independent RTP sessions.

When it comes to configuring RTCP the need for regular periodic reporting needs to be weighted against any feedback or control messages being sent. Applications using RTP/AVPF or RTP/SAVPF are RECOMMENDED to consider setting the trr-int parameter to a value suitable for the application's needs, thus potentially reducing the need for regular reporting and thus releasing more bandwidth for use for feedback or control.

Another aspect of an RTP session with multiple media types is that the RTCP packets, RTCP Feedback Messages, or RTCP XR metrics used might not be applicable to all media types. Instead, all RTP/RTCP endpoints need to correlate the media type of the SSRC being referenced in a message or packet and only use those that apply to that particular SSRC and its media type. Signalling solutions might have shortcomings when it comes to indicating that a particular set of RTCP reports or feedback messages only apply to a particular media type within an RTP session.

6.1. Timing out SSRCs

This section discusses issues around timing out SSRCs. After the discussion, clarified and mandated behavior for SSRC timeout is specified.

6.1.1. AVPF T_rr_interval Behavior

The RTP/AVPF profile includes a mechanism for suppressing regular RTCP reporting from being sent unnecessarily frequently if sufficient RTCP bandwidth is configured. This mechanism is defined in [Section 3.5.3 of \[RFC4585\]](#), and can be summarized as follows: if less than a randomized T_rr_interval value has passed since the last regular report, and no feedback messages need to be sent, then the RTCP regular report is suppressed. The randomization is done by a linear randomizer in the interval 0.5 to 1.5 times T_rr_interval. The randomized T_rr_interval is recalculated after every transmitted regular packet, i.e when t_rr_last was updated. The benefit of the suppression mechanism is that it avoids wasting bandwidth when there

is nothing requiring frequent RTCP transmissions, but still allows utilization of the configured bandwidth when feedback is needed.

Unfortunately this suppression mechanism has some behaviors that are less than ideal. First of all, the randomized $T_{rr_interval}$ is distributed over a larger range than the actual transmission interval for RTCP would be if $T_{rr_interval}$ and T_d had the same value. The reconsideration mechanism and its compensation factor result in the actual RTCP transmission intervals for a T_d having a distribution that is exponentially growing more likely with higher values, and is bounded to the interval $[0.5/1.21828, 1.5/1.21828]*T_d$, i.e. with a T_d value of 5 s [2.052, 6.156]. In comparison, the suppression acts in an interval that is 0.5 to 1.5 times the $T_{rr_interval}$, i.e. for $T_{rr_interval} = 5$ s this is [2.5, 7.5].

The effect of the above is that the time period between two RTCP packets when using $T_{rr_interval}$ suppression can become very long compared to the average input values. The longest time interval between one transmitted regular RTCP compound packet and the next when $T_{rr_interval}$ suppression is being used are: First the maximum $T_{rr_interval}$, i.e. $1.5*T_{rr_interval}$. Assuming that the last suppressed packet would have been sent at $1.5*T_{rr_interval}$, the maximum interval until a packet can be sent under the regular scheduling is $1.5/1.21828*T_d$. Thus, the maximum time in total is $1.5*T_{rr_interval} + 1.5/1.21828*T_d$.

If T_d and $T_{rr_interval}$ have the same value, i.e. the minimal interval desired ($T_{rr_interval}$) and the actual average interval specified by the RTCP scheduling algorithm (T_d) are the same, one might expect that RTCP packets would be sent according to the regular mechanism. Instead, this algorithm results in the RTCP packets being sent anywhere from $0.5*T_d$ to $\sim 2.731*T_d$. The probability distribution over that time is also non-trivial in its shape, somewhat similar to a saw tooth.

Thus, we recommend that the AVPF regular transmission mechanism is revised in the future. This issue also has further implications as discussed in the next section.

6.1.2. Avoiding Pre-mature Timeout

In RTP/AVP [RFC3550] the timeout behavior is simple and is 5 times T_d , where T_d is calculated with a T_{min} value of 5 seconds. In other words, if the RTCP bandwidth allowed for an RTCP interval more frequent than every 5 seconds on average, then timeout happened after $5*T_d = 25$ seconds of no activity from the SSRC (RTP or RTCP), otherwise it was 5 average reporting intervals.

RTP/AVPF [RFC4585] introduced two different behaviors depending on the value of `T_rr_interval`. When `T_rr_interval` was 0, it defaulted to the same `Td` calculation in RTP/AVP [RFC3550]. However, when `T_rr_interval` is non-zero the `Tmin` value become `T_rr_interval` in that calculation, most likely to enable speed up the detection of timed out SSRCs. However, using a non-zero `T_rr_interval` has two consequences for RTP's behavior.

First, the number of actually sent RTCP packets for an SSRC that currently is not an active RTP sender can become very low due to the issue discussed above in [Section 6.1.1](#). As the RTCP packet interval can be as long as $2.73 \cdot Td$, then during a $5 \cdot Td$ time period an endpoint may in fact transmit only a single RTCP packet. The long intervals result in fewer RTCP packets, to a point where a one or two packet losses in RTCP result in timing out an SSRC.

Second, the change also increased RTP/AVPF's brittleness to both packet loss and configuration errors. In many cases, when one desires to use RTP/AVPF for its feedback, one will ensure that RTCP is configured for more frequent transmissions on average than every 5 seconds. Thus, many more RTP and RTCP packets can be transmitted during the time interval. Lets consider an implementation that would follow the AVP or AVPF with `T_rr_interval` = 0 rules for timeout, also when `T_rr_interval` is not zero. In such a case when the configured value of the `T_rr_interval` is significantly smaller than 5 seconds, e.g. less than 1 second, then a difference between using 0.1 seconds and 0.6 seconds has no significant impact on when an SSRC will be timed out. However, such a configuration difference between two endpoints following [RFC 4585](#) will result in that the endpoint configured with `T_rr_interval` = 0.1 will frequently timeout SSRCs currently not sending RTP, from the endpoint configured with 0.6, as that is six times the `Td` value used by the endpoint configured with `T_rr_interval`=0.1, assuming sufficient bandwidth. For this reason such a change is implemented below in [Section 6.1.4](#).

6.1.3. AVP and AVPF Interoperability

If endpoints implementing the RTP/AVP and RTP/AVPF profiles (or their secure variants) are combined in a single RTP session, and the RTP/AVPF endpoints use a non-zero `T_rr_interval` that is significantly lower than 5 seconds, then there is a risk that the RTP/AVPF endpoints will prematurely timeout the RTP/AVP SSRCs due to their different RTCP timeout intervals. Conversely, if the RTP/AVPF endpoints use a `T_rr_interval` that is significant larger than 5 seconds, there is a risk that the RTP/AVP endpoints will timeout the RTP/AVPF SSRCs.

If such mixed RTP profiles are used, (though this is NOT RECOMMENDED), and the AVPF endpoint is not updated to follow this specification, then the RTP/AVPF session SHOULD use a non-zero `T_rr_interval` that is 4 seconds.

It might appear strange to use a `T_rr_interval` of 4 seconds. It might be intuitive that this value ought to be 5 seconds, as then both the RTP/AVP and RTP/AVPF would use the same timeout period. However, considering regular RTCP transmission and their packet intervals for RTP/AVPF its mean value will (with non-zero `T_rr_interval`) be larger than `T_rr_interval` due to the scheduling algorithm's behavior as discussed in [Section 6.1.1](#). Thus, to enable an equal amount of regular RTCP transmissions in each directions between RTP/AVP and RTP/AVPF endpoints, taking the altered timeout intervals into account, the optimal value is around four (4), where almost four transmissions will on average occur in each direction between the different profile types given an otherwise good configuration of parameters in regards to `T_rr_interval`. If the RTCP bandwidth parameters are selected so that T_d based on bandwidth is close to 4, i.e. close to `T_rr_interval` the risk increases that RTP/AVPF SSRCs will be timed out by RTP/AVP endpoints, as the RTP/AVPF SSRC might only manage two transmissions in the timeout period.

[6.1.4](#). Specified Behavior

The above considerations result in the following clarification and RTP/AVPF specification change.

All SSRCs used in an RTP session MUST use the same timeout behaviour to avoid premature timeouts. This will depend on the RTP profile and its configuration. The RTP specification provides several options that can influence the values used when calculating the time interval. To avoid interoperability issues when using this specification, this document makes several clarifications to the calculations.

For RTP/AVP, RTP/SAVP, RTP/AVPF, and RTP/SAVPF, the timeout interval SHALL be calculated using a multiplier of 5, i.e. the timeout interval becomes $5 \cdot T_d$. The T_d calculation SHALL be done using a T_{min} value of 5 seconds, not the reduced minimal interval even if used to calculate RTCP packet transmission intervals. This changes the behavior for the RTP/AVPF or RTP/SAVPF profiles when `T_rr_interval` $\neq 0$, a behavior defined in [Section 3.5.4 of RFC 4585](#), i.e. T_{min} in the T_d calculation is the `T_rr_interval`.

6.2. Tuning RTCP transmissions

This sub-section discusses what tuning can be done to reduce the downsides of the shared RTCP packet intervals. First, it is considered what possibilities exist for the RTP/AVP [[RFC3551](#)] profile, then what additional tools are provided by RTP/AVPF [[RFC4585](#)].

6.2.1. RTP/AVP and RTP/SAVP

When using the RTP/AVP or RTP/SAVP profiles the tuning one can do is very limited. The controls one has are limited to the RTCP bandwidth values and whether the minimum RTCP interval is scaled according to the bandwidth. As the scheduling algorithm includes both random factors and reconsideration, one can't simply calculate the expected average transmission interval using the formula for T_d . But it does indicate the important factors affecting the transmission interval, namely the RTCP bandwidth available for the role (Active Sender or Participant), the average RTCP packet size, and the number of SSRCs classified in the relevant role. Note that if the ratio of senders to total number of session participants is larger than the ratio of RTCP bandwidth for senders in relation to the total RTCP bandwidth, then senders and receivers are treated together.

Let's start with some basic observations:

- a. Unless the scaled minimum RTCP interval is used, then T_d prior to randomization and reconsideration can never be less than 5 seconds (assuming default T_{min} of 5 seconds).
- b. If the scaled minimum RTCP interval is used, T_d can become as low as 360 divided by RTP Session bandwidth in kilobits. In SDP the RTP session bandwidth is signalled using $b=AS$. An RTP Session bandwidth of 72 kbps results in T_{min} being 5 seconds. An RTP session bandwidth of 360 kbps of course gives a T_{min} of 1 second, and to achieve a T_{min} equal to once every frame for a 25 Hz video stream requires an RTP session bandwidth of 9 Mbps! (The use of the RTP/AVPF or RTP/SAVPF profile allows a smaller T_{min} , and hence more frequent RTCP reports, as discussed below).
- c. Let's calculate the number (n) of SSRCs in the RTP session that 5% of the session bandwidth can support to yield a T_d value equal to T_{min} with minimal scaling. For this calculation we have to make two assumptions. The first is that we will consider most or all SSRC being senders, resulting in everyone sharing the available bandwidth. Secondly we will select an average RTCP packet size. This packet will consist of an SR, containing ($n-1$) report blocks up to 31 report blocks, and an SDES item with at least a CNAME (17 bytes in size) in it. Such a basic packet will

be 800 bytes for $n \geq 32$. With these parameters, and as the bandwidth goes up the time interval is proportionally decreased (due to minimal scaling), thus all the example bandwidths 72 kbps, 360 kbps and 9 Mbps all support 9 SSRCS.

- d. The actual transmission interval for a T_d value is $[0.5 \cdot T_d / 1.21828, 1.5 \cdot T_d / 1.21828]$, which means that for $T_d = 5$ seconds, the interval is actually $[2.052, 6.156]$ and the distribution is not uniform, but rather exponentially-increasing. The probability for sending at time X , given it is within the interval, is probability of picking X in the interval times the probability to randomly picking a number that is $\leq X$ within the interval with an uniform probability distribution. This results in that the majority of the probability mass is above the T_d value.

To conclude, with RTP/AVP and RTP/SAVP the key limitation for small unicast sessions is going to be the T_{min} value. Thus the RTP session bandwidth configured in RTCP has to be sufficiently high to reach the reporting goals the application has following the rules for the scaled minimal RTCP interval.

6.2.2. RT/AVPF and RTP/SAVPF

When using RTP/AVPF or RTP/SAVPF we get a quite powerful additional tool, the setting of the $T_{rr_interval}$ which has several effects on the RTCP reporting. First of all as T_{min} is set to 0 after the initial transmission, the regular reporting interval is instead determined by the regular bandwidth based calculation and the $T_{rr_interval}$. This has the effect that we are no longer restricted by the minimal interval or even the scaling rule for the minimal rule. Instead the RTCP bandwidth and the $T_{rr_interval}$ are the governing factors.

Now it also becomes important to separate between the application's need for regular reports and RTCP feedback packet types. In both regular RTCP mode, as in Early RTCP Mode, the usage of the $T_{rr_interval}$ prevents regular RTCP packets, i.e. packets without any Feedback packets, to be sent more often than $T_{rr_interval}$. This value is applied to prevent any regular RTCP packet to be sent less than $T_{rr_interval}$ times a uniformly distributed random value from the interval $[0.5, 1.5]$ after the previous regular packet packet. The random value recalculated after each regular RTCP packet transmission.

So applications that have a use for feedback packets for some media streams, for example video streams, but don't want frequent regular reporting for audio, could configure the $T_{rr_interval}$ to a value so

that the regular reporting for both audio and video is at a level that is considered acceptable for the audio. They could then use feedback packets, which will include RTCP SR/RR packets, unless reduced-size RTCP feedback packets [[RFC5506](#)] are used, and can include other report information in addition to the feedback packet that needs to be sent. That way the available RTCP bandwidth can be focused for the use which provides the most utility for the application.

Using `T_rr_interval` still requires one to determine suitable values for the RTCP bandwidth value, in fact it might make it even more important, as this is more likely to affect the RTCP behaviour and performance than when using RTP/AVP, as there are fewer limitations affecting the RTCP transmission.

When using `T_rr_interval`, i.e. having it be non zero, there are configurations that have to be avoided. If the resulting `Td` value is smaller but close to `T_rr_interval` then the interval in which the actual regular RTCP packet transmission falls into becomes very large, from 0.5 times `T_rr_interval` up to 2.73 times the `T_rr_interval`. Therefore for configuration where one intends to have `Td` smaller than `T_rr_interval`, then `Td` is RECOMMENDED to be targeted at values less than 1/4th of `T_rr_interval` which results in that the range becomes $[0.5 * T_rr_interval, 1.81 * T_rr_interval]$.

With RTP/AVPF, using a `T_rr_interval` of 0 or with another low value significantly lower than `Td` still has utility, and different behaviour compared to RTP/AVP. This avoids the `Tmin` limitations of RTP/AVP, thus allowing more frequent regular RTCP reporting. In fact this will result that the RTCP traffic becomes as high as the configured values.

(tbd: a future version of this memo will include examples of how to choose RTCP parameters for common scenarios)

There exists no method within the specification for using different regular RTCP reporting intervals depending on the media type or individual media stream.

7. Security Considerations

In the secure RTP protocol (SRTP) [[RFC3711](#)], the cryptographic context of a compound SRTCP packet is the SSRC of the sender of the first RTCP (sub-)packet. This could matter in some cases, especially for keying mechanisms such as Mikey [[RFC3830](#)] which allow use of per-SSRC keying.

Other than that, the standard security considerations of RTP apply; sending multiple media streams from a single endpoint does not appear to have different security consequences than sending the same number of streams.

8. Open Issues

At this stage this document contains a number of open issues. The below list tries to summarize the issues:

1. Do we need to provide a recommendation for unicast session joiners with many sources to not use 0 initial minimal interval from bit-rate burst perspective?
2. RTCP parameters for common scenarios in [Section 6.2](#)?
3. Is scheduling algorithm working well with dynamic changes?
4. Are the scheduling algorithm changes impacting previous implementations in such a way that the report aggregation has to be agreed on, and thus needs to be considered as an optimization?
5. An open question is if any improvements or clarifications ought to be allowed regarding FB message scheduling in multi-SSRC endpoints.

9. IANA Considerations

No IANA actions needed.

10. References

10.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, [RFC 3550](#), July 2003.
- [RFC3711] Baugher, M., McGrew, D., Naslund, M., Carrara, E., and K. Norrman, "The Secure Real-time Transport Protocol (SRTP)", [RFC 3711](#), March 2004.

- [RFC4585] Ott, J., Wenger, S., Sato, N., Burmeister, C., and J. Rey, "Extended RTP Profile for Real-time Transport Control Protocol (RTCP)-Based Feedback (RTP/AVPF)", [RFC 4585](#), July 2006.
- [RFC5124] Ott, J. and E. Carrara, "Extended Secure RTP Profile for Real-time Transport Control Protocol (RTCP)-Based Feedback (RTP/SAVPF)", [RFC 5124](#), February 2008.
- [RFC5506] Johansson, I. and M. Westerlund, "Support for Reduced-Size Real-Time Transport Control Protocol (RTCP): Opportunities and Consequences", [RFC 5506](#), April 2009.

10.2. Informative References

- [I-D.ietf-avtcore-multi-media-rtp-session]
Westerlund, M., Perkins, C., and J. Lennox, "Sending Multiple Types of Media in a Single RTP Session", [draft-ietf-avtcore-multi-media-rtp-session-05](#) (work in progress), February 2014.
- [I-D.ietf-avtcore-rtp-multi-stream-optimisation]
Lennox, J., Westerlund, M., Wu, W., and C. Perkins, "Sending Multiple Media Streams in a Single RTP Session: Grouping RTCP Reception Statistics and Other Feedback", [draft-ietf-avtcore-rtp-multi-stream-optimisation-02](#) (work in progress), February 2014.
- [I-D.ietf-avtcore-rtp-topologies-update]
Westerlund, M. and S. Wenger, "RTP Topologies", [draft-ietf-avtcore-rtp-topologies-update-02](#) (work in progress), May 2014.
- [I-D.ietf-clue-framework]
Duckworth, M., Pepperell, A., and S. Wenger, "Framework for Telepresence Multi-Streams", [draft-ietf-clue-framework-15](#) (work in progress), May 2014.
- [I-D.ietf-mmusic-sdp-bundle-negotiation]
Holmberg, C., Alvestrand, H., and C. Jennings, "Negotiating Media Multiplexing Using the Session Description Protocol (SDP)", [draft-ietf-mmusic-sdp-bundle-negotiation-07](#) (work in progress), April 2014.
- [RFC3551] Schulzrinne, H. and S. Casner, "RTP Profile for Audio and Video Conferences with Minimal Control", STD 65, [RFC 3551](#), July 2003.

- [RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", [RFC 3611](#), November 2003.
- [RFC3830] Arkko, J., Carrara, E., Lindholm, F., Naslund, M., and K. Norrman, "MIKEY: Multimedia Internet KEYing", [RFC 3830](#), August 2004.
- [RFC4588] Rey, J., Leon, D., Miyazaki, A., Varsa, V., and R. Hakenberg, "RTP Retransmission Payload Format", [RFC 4588](#), July 2006.
- [RFC6190] Wenger, S., Wang, Y., Schierl, T., and A. Eleftheriadis, "RTP Payload Format for Scalable Video Coding", [RFC 6190](#), May 2011.

[Appendix A.](#) Changes From Earlier Versions

Note to the RFC-Editor: please remove this section prior to publication as an RFC.

[A.1.](#) Changes From WG Draft -02

- o Changed usage of Media Stream
- o Added Updates [RFC 4585](#)
- o Added rules for how to deal with RTCP when aggregating multiple SSRCs report in same compound packet:
 - * avg_rtcp_size calculation
 - * Scheduling rules to maintain timing
- o Started a section clarifying and discussing RTP/AVPF Feedback Packets and their scheduling.

[A.2.](#) Changes From WG Draft -01

- o None, a keep-alive version

[A.3.](#) Changes From WG Draft -00

- o Split the Reporting Group Extension from this draft into [draft-ietf-avtcore-rtp-multi-stream-optimization-00](#).
- o Added RTCP tuning considerations from [draft-ietf-avtcore-multi-media-rtp-session-02](#).

A.4. Changes From Individual Draft -02

- o Resubmitted as working group draft.
- o Updated references.

A.5. Changes From Individual Draft -01

- o Merged with [draft-wu-avtcore-multisrc-endpoint-adver](#).
- o Changed how Reporting Groups are indicated in RTCP, to make it clear which source(s) is the group's reporting sources.
- o Clarified the rules for when sources can be placed in the same reporting group.
- o Clarified that mixers and translators need to pass reporting group SDDES information if they are forwarding RR and SR traffic from members of a reporting group.

A.6. Changes From Individual Draft -00

- o Added the Reporting Group semantic to explicitly indicate which sources come from a single endpoint, rather than leaving it implicit.
- o Specified that Reporting Group semantics (as they now are) apply to AVPF and XR, as well as to RR/SR report blocks.
- o Added a description of the cascaded source-projecting mixer, along with a calculation of its RTCP overhead if reporting groups are not in use.
- o Gave some guidance on how the flexibility of RTCP randomization allows some freedom in RTCP multiplexing.
- o Clarified the language of several of the recommendations.
- o Added an open issue discussing how avg_rtcp_size ought to be calculated for multiplexed RTCP.
- o Added an open issue discussing how RTCP bandwidths are to be chosen for sessions where source bandwidths greatly differ.

Authors' Addresses

Jonathan Lennox
Vidyo, Inc.
433 Hackensack Avenue
Seventh Floor
Hackensack, NJ 07601
US

Email: jonathan@vidyo.com

Magnus Westerlund
Ericsson
Farogatan 6
SE-164 80 Kista
Sweden

Phone: +46 10 714 82 87

Email: magnus.westerlund@ericsson.com

Qin Wu
Huawei
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: sunseawq@huawei.com

Colin Perkins
University of Glasgow
School of Computing Science
Glasgow G12 8QQ
United Kingdom

Email: csp@csperkins.org

