

Babel Working Group
Internet-Draft
Intended status: Standards Track
Expires: 26 March 2022

M. Jethanandani
Kloud Services
B. Stark
AT&T
22 September 2021

YANG Data Model for Babel
draft-ietf-babel-yang-model-13

Abstract

This document defines a data model for the Babel routing protocol. The data model is defined using the YANG data modeling language.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14 \[RFC2119\]](#)[RFC8174] when, and only when, they appear in all capitals, as shown here.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 26 March 2022.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document.

Internet-Draft

Babel YANG model

September 2021

Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Note to RFC Editor	2
1.2.	Tree Diagram Annotations	3
2.	Babel Module	3
2.1.	Information Model	3
2.2.	Tree Diagram	3
2.3.	YANG Module	5
3.	IANA Considerations	32
3.1.	URI Registrations	32
3.2.	YANG Module Name Registration	32
4.	Security Considerations	32
5.	Acknowledgements	34
6.	References	34
6.1.	Normative References	34
6.2.	Informative References	35
Appendix A.	Tree Diagram and Example Configurations	36
A.1.	Complete Tree Diagram	36
A.2.	Statistics Gathering Enabled	38
A.3.	Automatic Detection of Properties	39
A.4.	Override Default Properties	41
A.5.	Configuring other Properties	42
	Authors' Addresses	43

[1.](#) Introduction

This document defines a data model for The Babel Routing Protocol [[RFC8966](#)]. The data model is defined using YANG 1.1 [[RFC7950](#)] and is Network Management Datastore Architecture (NDMA) [[RFC8342](#)] compatible. It is based on the Babel Information Model [[RFC9046](#)]. The data model only includes data nodes that are useful for managing Babel over IPv6.

[1.1.](#) Note to RFC Editor

Artwork in this document contains shorthand references to drafts in

progress. Please apply the following replacements and remove this note before publication.

- * "XXXX" --> the assigned RFC value for this draft both in this draft and in the YANG models under the revision statement.

- * Revision date in model, in the format 2021-09-20 needs to get updated with the date the draft gets approved. The date also needs to get reflected on the line with <CODE BEGINS>.

[1.2.](#) Tree Diagram Annotations

For a reference to the annotations used in tree diagrams included in this draft, please see YANG Tree Diagrams [[RFC8340](#)].

[2.](#) Babel Module

This document defines a YANG 1.1 [[RFC7950](#)] data model for the configuration and management of Babel. The YANG module is based on the Babel Information Model [[RFC9046](#)].

[2.1.](#) Information Model

There are a few things that should be noted between the Babel Information Model and this data module. The information model mandates the definition of some of the attributes, e.g., 'babel-implementation-version' or the 'babel-self-router-id'. These attributes are marked as read-only objects in the information module as well as in this data module. However, there is no way in the data module to mandate that a read-only attribute be present. It is up to the implementation of this data module to make sure that the attributes that are marked read-only and are mandatory are indeed present.

[2.2.](#) Tree Diagram

The following diagram illustrates a top level hierarchy of the model. In addition to the version implemented by this device, the model contains subtrees on 'constants', 'interfaces', 'mac-key-set', 'dtls', and 'routes'.

```
module: ietf-babel

augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol:
  +--rw babel!
    +--ro version?          string
    +--rw enable           boolean
    +--ro router-id?      binary
    +--ro seqno?          uint16
    +--rw statistics-enabled? boolean
    +--rw constants
      |   ...
    +--rw interfaces* [reference]
      |   ...
    +--rw mac-key-set* [name]
      |   ...
    +--rw dtls* [name]
      |   ...
    +--ro routes* [prefix]
      ...
```

The 'interfaces' subtree describes attributes such as the 'interface' object that is being referenced, the type of link, e.g., wired, wireless or tunnel, as enumerated by 'metric-algorithm' and 'split-horizon' and whether the interface is enabled or not.

The 'constants' subtree describes the UDP port used for sending and receiving Babel messages, and the multicast group used to send and receive announcements on IPv6.

The 'routes' subtree describes objects such as the prefix for which the route is advertised, a reference to the neighboring route, and 'next-hop' address.

Finally, for security two subtrees are defined to contain MAC keys and DTLS certificates. The 'mac-key-set' subtree contains keys used with the MAC security mechanism. The boolean flag 'default-apply' indicates whether the set of MAC keys is automatically applied to new interfaces. The 'dtls' subtree contains certificates used with DTLS security mechanism. Similar to the MAC mechanism, the boolean flag 'default-apply' indicates whether the set of DTLS certificates is automatically applied to new interfaces.

[2.3.](#) YANG Module

This YANG module augments the YANG Routing Management [[RFC8349](#)] module to provide a common framework for all routing subsystems. By augmenting the module it provides a common building block for routes, and Routing Information Bases (RIBs). It also has a reference to an interface defined by A YANG Data Model for Interface Management [[RFC8343](#)].

A router running Babel routing protocol can sometimes determine the parameters it needs to use for an interface based on the interface name. For example, it can detect that eth0 is a wired interface, and that wlan0 is a wireless interface. This is not true for a tunnel interface, where the link parameters need to be configured explicitly.

For a wired interface, it will assume 'two-out-of-three' for 'metric-algorithm', and 'split-horizon' set to true. On the other hand, for a wireless interface it will assume 'etx' for 'metric-algorithm', and 'split-horizon' set to false. However, if the wired link is connected to a wireless radio, the values can be overridden by setting 'metric-algorithm' to 'etx', and 'split-horizon' to false.

Similarly, an interface that is a metered 3G link, and used for fallback connectivity needs much higher default time constants, e.g., 'mcast-hello-interval', and 'update-interval', in order to avoid carrying control traffic as much as possible.

In addition to the modules used above, this module imports definitions from Common YANG Data Types [[RFC6991](#)], and references HMAC: Keyed-Hashing for Message Authentication [[RFC2104](#)], Using HMAC-SHA-256, HMAC-SHA-384, and HMAC-SHA-512 with IPsec [[RFC4868](#)], The Datagram Transport Layer Security (DTLS) Version 1.3 [[I-D.ietf-tls-dtls13](#)], The Blake2 Cryptographic Hash and Message Authentication Code (MAC) [[RFC7693](#)], Babel Information Model [[RFC9046](#)], The Babel Routing Protocol [[RFC8966](#)], YANG Data Types and Groupings for Cryptography [[I-D.ietf-netconf-crypto-types](#)], Network Configuration Access Control Model [[RFC8341](#)] and MAC Authentication for Babel [[RFC8967](#)].

```
<CODE BEGINS> file "ietf-babel@2021-09-20.yang"
module ietf-babel {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-babel";
  prefix babel;

  import ietf-yang-types {
    prefix yang;
    reference
```

```
    "RFC 6991: Common YANG Data Types.";
  }
  import ietf-inet-types {
    prefix inet;
    reference
      "RFC 6991: Common YANG Data Types.";
  }
  import ietf-interfaces {
    prefix if;
    reference
      "RFC 8343: A YANG Data Model for Interface Management";
  }
  import ietf-routing {
    prefix rt;
    reference
```

```
    "RFC 8349: YANG Routing Management";
}
import ietf-crypto-types {
  prefix ct;
  reference
    "I-D.ietf-netconf-crypto-types: YANG Data Types and Groupings
    for Cryptographay.";
}
import ietf-netconf-acm {
  prefix nacm;
  reference
    "RFC 8341: Network Configuration Access Control Model";
}

organization
  "IETF Babel routing protocol Working Group";

contact
  "WG Web: http://tools.ietf.org/wg/babel/
  WG List: babel@ietf.org

  Editor: Mahesh Jethanandani
          mjethanandani@gmail.com
  Editor: Barbara Stark
          bs7652@att.com";

description
  "This YANG module defines a model for the Babel routing
  protocol.

  The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL
  NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED',
  'MAY', and 'OPTIONAL' in this document are to be interpreted as
```

described in [BCP 14](#) ([RFC 2119](#)) ([RFC 8174](#)) when, and only when, they appear in all capitals, as shown here.

Copyright (c) 2021 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to

the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX (<https://www.rfc-editor.org/info/rfcXXXX>); see the RFC itself for full legal notices.";

```
revision 2021-09-20 {
  description
    "Initial version.";
  reference
    "RFC XXXX: Babel YANG Data Model.";
}

/*
 * Features
 */

feature two-out-of-three-supported {
  description
    "This implementation supports the '2-out-of-3'
    computation algorithm.";
}

feature etx-supported {
  description
    "This implementation supports the Expected Transmission Count
    (ETX) metric computation algorithm.";
}

feature mac-supported {
  description
    "This implementation supports MAC-based security.";
  reference
    "RFC 8967: MAC authentication for Babel Routing
    Protocol.";
}
```

```
feature dtls-supported {
```



```

description
  "This implementation supports DTLS based security.";
reference
  "RFC 8968: Babel Routing Protocol over Datagram
  Transport Layer Security.";
}

feature hmac-sha256-supported {
  description
    "This implementation supports the HMAC-SHA256 MAC algorithm.";
  reference
    "RFC 8967: MAC authentication for Babel Routing
    Protocol.";
}

feature blake2s-supported {
  description
    "This implementation supports BLAKE2s MAC algorithms.";
  reference
    "RFC 8967: MAC authentication for Babel Routing
    Protocol.";
}

feature x-509-supported {
  description
    "This implementation supports the X.509 certificate type.";
  reference
    "RFC 8968: Babel Routing Protocol over Datagram
    Transport Layer Security.";
}

feature raw-public-key-supported {
  description
    "This implementation supports the Raw Public Key certificate
    type.";
  reference
    "RFC 8968: Babel Routing Protocol over Datagram
    Transport Layer Security.";
}

/*
 * Identities
 */

identity metric-comp-algorithms {
  description
    "Base identity from which all Babel metric computation

```

```
        algorithms MUST be derived.";
    }

    identity two-out-of-three {
        if-feature "two-out-of-three-supported";
        base metric-comp-algorithms;
        description
            "2-out-of-3 algorithm.";
        reference
            "RFC 8966: The Babel Routing Protocol, Section A.2.1.";
    }

    identity etx {
        if-feature "etx-supported";
        base metric-comp-algorithms;
        description
            "Expected Transmission Count (ETX) metric computation
            algorithm.";
        reference
            "RFC 8966: The Babel Routing Protocol, Section A.2.2.";
    }

    /*
     * Babel MAC algorithms identities.
     */

    identity mac-algorithms {
        description
            "Base identity for all Babel MAC algorithms.";
    }

    identity hmac-sha256 {
        if-feature "mac-supported";
        if-feature "hmac-sha256-supported";
        base mac-algorithms;
        description
            "HMAC-SHA256 algorithm supported.";
        reference
            "RFC 4868: Using HMAC-SHA-256, HMAC-SHA-384, and HMAC-SHA-512
            with IPsec.";
    }

    identity blake2s {
        if-feature "mac-supported";
        if-feature "blake2s-supported";
        base mac-algorithms;
```

description

"BLAKE2s algorithms supported. Specifically, BLAKE2-128 is

```
        supported.";
    reference
        "RFC 7693: The BLAKE2 Cryptographic Hash and Message
        Authentication Code (MAC).";
}

/*
 * Babel Cert Types
 */

identity dtls-cert-types {
    description
        "Base identity for Babel DTLS certificate types.";
}

identity x-509 {
    if-feature "dtls-supported";
    if-feature "x-509-supported";
    base dtls-cert-types;
    description
        "X.509 certificate type.";
}

identity raw-public-key {
    if-feature "dtls-supported";
    if-feature "raw-public-key-supported";
    base dtls-cert-types;
    description
        "Raw Public Key certificate type.";
}

/*
 * Babel routing protocol identity.
 */

identity babel {
    base rt:routing-protocol;
    description
        "Babel routing protocol";
```

```
}

/*
 * Groupings
 */

grouping routes {
  list routes {
    key "prefix";
```

```
config false;

leaf prefix {
  type inet:ip-prefix;
  description
    "Prefix (expressed in ip-address/prefix-length format) for
    which this route is advertised.";
  reference
    "RFC 9046: Babel Information Model, Section 3.6.";
}

leaf router-id {
  type binary {
    length 8;
  }
  description
    "router-id of the source router for which this route is
    advertised.";
  reference
    "RFC 9046: Babel Information Model, Section 3.6.";
}

leaf neighbor {
  type leafref {
    path "/rt:routing/rt:control-plane-protocols/"
      + "rt:control-plane-protocol/babel/interfaces/"
      + "neighbor-objects/neighbor-address";
  }
  description
    "Reference to the neighbor-objects entry for the neighbor
    that advertised this route.";
  reference
```

```

    "RFC 9046: Babel Information Model, Section 3.6.";
}

leaf received-metric {
  type union {
    type enumeration {
      enum null {
        description
          "Route was not received from a neighbor.";
      }
    }
  }
  type uint16;
}
description
  "The metric with which this route was advertised by the
  neighbor, or maximum value (infinity) to indicate the

```

```

    route was recently retracted and is temporarily
    unreachable. This metric will be NULL if the
    route was not received from a neighbor but instead was
    injected through means external to the Babel routing
    protocol. At least one of calculated-metric or
    received-metric MUST be non-NULL.";
reference
  "RFC 9046: Babel Information Model, Section 3.6,
  RFC 8966: The Babel Routing Protocol, Section 2.1.";
}

leaf calculated-metric {
  type union {
    type enumeration {
      enum null {
        description
          "Route has not been calculated.";
      }
    }
  }
  type uint16;
}
description
  "A calculated metric for this route. How the metric is
  calculated is implementation-specific. Maximum value
  (infinity) indicates the route was recently retracted

```

```

        and is temporarily unreachable. At least one of
        calculated-metric or received-metric MUST be non-NULL.";
    reference
        "RFC 9046: Babel Information Model, Section 3.6,
        RFC 8966: The Babel Routing Protocol, Section 2.1.";
}

leaf seqno {
    type uint16;
    description
        "The sequence number with which this route was
        advertised.";
    reference
        "RFC 9046: Babel Information Model, Section 3.6.";
}

leaf next-hop {
    type union {
        type enumeration {
            enum null {
                description
                    "Route has no next-hop address.";
            }
        }
    }
}

```

```

    }
    type inet:ip-address;
}
description
    "The next-hop address of this route. This will be NULL
    if this route has no next-hop address.";
reference
    "RFC 9046: Babel Information Model, Section 3.6.";
}

leaf feasible {
    type boolean;
    description
        "A boolean flag indicating whether this route is
        feasible.";
    reference
        "RFC 9046: Babel Information Model, Section 3.6,
        RFC 8966, The Babel Routing Protocol, Section 3.5.1.";
}

```

```

    }

    leaf selected {
      type boolean;
      description
        "A boolean flag indicating whether this route is selected,
        i.e., whether it is currently being used for forwarding
        and is being advertised.";
      reference
        "RFC 9046: Babel Information Model, Section 3.6.";
    }
    description
      "A set of babel-route-obj objects. Contains routes known to
      this node.";
    reference
      "RFC 9046: Babel Information Model, Section 3.1.";
  }
  description
    "Common grouping for routing used in RIB.";
}

/*
 * Data model
 */

augment "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol" {
  when "derived-from-or-self(rt:type, 'babel')" {
    description
      "Augmentation is valid only when the instance of routing type

```

```

      is of type 'babel'.");
    }
    description
      "Augment the routing module to support a common structure
      between routing protocols.";
    reference
      "YANG Routing Management, RFC 8349, Lhotka & Lindem, March
      2018.";

    container babel {
      presence "A Babel container.";

```

```

description
  "Babel Information Objects.";
reference
  "RFC 9046: Babel Information Model, Section 3.";

leaf version {
  type string;
  config false;
  description
    "The name and version of this implementation of the Babel
    protocol.";
  reference
    "RFC 9046: Babel Information Model, Section 3.1.";
}

leaf enable {
  type boolean;
  mandatory true;
  description
    "When written, it configures whether the protocol should be
    enabled. A read from the <running> or <intended> datastore
    therefore indicates the configured administrative value of
    whether the protocol is enabled or not.

    A read from the <operational> datastore indicates whether
    the protocol is actually running or not, i.e. it indicates
    the operational state of the protocol.";
  reference
    "RFC 9046: Babel Information Model, Section 3.1.";
}

leaf router-id {
  type binary;
  must '../enable = "true"';
  config false;
  description
    "Every Babel speaker is assigned a router-id, which is an

```

arbitrary string of 8 octets that is assumed to be unique across the routing domain.

The router-id is valid only if the protocol is enabled,


```

        at which time a non-zero value is assigned.";
reference
    "RFC 9046: Babel Information Model, Section 3.1,
    RFC 8966: The Babel Routing Protocol,
        Section 3.";
}

leaf seqno {
    type uint16;
    config false;
    description
        "Sequence number included in route updates for routes
        originated by this node.";
reference
    "RFC 9046: Babel Information Model, Section 3.1.";
}

leaf statistics-enabled {
    type boolean;
    description
        "Indicates whether statistics collection is enabled (true)
        or disabled (false) on all interfaces. On transition to
        enabled, existing statistics values are not cleared and
        will be incremented as new packets are counted.";
}

container constants {
    description
        "Babel Constants object.";
reference
    "RFC 9046: Babel Information Model, Section 3.1.";

    leaf udp-port {
        type inet:port-number;
        default "6696";
        description
            "UDP port for sending and receiving Babel messages. The
            default port is 6696.";
reference
    "RFC 9046: Babel Information Model, Section 3.2.";
    }

    leaf mcast-group {
        type inet:ip-address;

```

```
    default "ff02::1:6";
    description
      "Multicast group for sending and receiving multicast
       announcements on IPv6.";
    reference
      "RFC 9046: Babel Information Model, Section 3.2.";
  }
}

list interfaces {
  key "reference";

  description
    "A set of Babel Interface objects.";
  reference
    "RFC 9046: Babel Information Model, Section 3.3.";

  leaf reference {
    type if:interface-ref;
    description
      "References the name of the interface over which Babel
       packets are sent and received.";
    reference
      "RFC 9046: Babel Information Model, Section 3.3.";
  }

  leaf enable {
    type boolean;
    default "true";
    description
      "If true, babel sends and receives messages on this
       interface. If false, babel messages received on this
       interface are ignored and none are sent.";
    reference
      "RFC 9046: Babel Information Model, Section 3.3.";
  }

  leaf metric-algorithm {
    type identityref {
      base metric-comp-algorithms;
    }
    mandatory true;
    description
      "Indicates the metric computation algorithm used on this
       interface. The value MUST be one of those identities
       based on 'metric-comp-algorithms'.";
    reference

```

"[RFC 9046](#): Babel Information Model, [Section 3.3](#).";

```
}

leaf split-horizon {
  type boolean;
  description
    "Indicates whether or not the split horizon optimization
     is used when calculating metrics on this interface.
     A value of true indicates the split horizon optimization
     is used.";
  reference
    "RFC 9046: Babel Information Model, Section 3.3.";
}

leaf mcast-hello-seqno {
  type uint16;
  config false;
  description
    "The current sequence number in use for multicast hellos
     sent on this interface.";
  reference
    "RFC 9046: Babel Information Model, Section 3.3.";
}

leaf mcast-hello-interval {
  type uint16;
  units "centiseconds";
  description
    "The current multicast hello interval in use for hellos
     sent on this interface.";
  reference
    "RFC 9046: Babel Information Model, Section 3.3.";
}

leaf update-interval {
  type uint16;
  units "centiseconds";
  description
    "The current update interval in use for this interface.
     Units are centiseconds.";
  reference
```

```
    "RFC 9046: Babel Information Model, Section 3.3.";
}

leaf mac-enable {
    type boolean;
    description
        "Indicates whether the MAC security mechanism is enabled
        (true) or disabled (false).";
}
```

```
    reference
        "RFC 9046: Babel Information Model, Section 3.3.";
}

leaf-list mac-key-sets {
    type leafref {
        path "../..//mac-key-set/name";
    }
    description
        "List of references to the MAC entries that apply
        to this interface. When an interface instance is
        created, all MAC instances with default-apply 'true'
        will be included in this list.";
    reference
        "RFC 9046: Babel Information Model, Section 3.3.";
}

leaf mac-verify {
    type boolean;
    description
        "A Boolean flag indicating whether MACs in
        incoming Babel packets are required to be present and
        are verified. If this parameter is 'true', incoming
        packets are required to have a valid MAC.";
    reference
        "RFC 9046: Babel Information Model, Section 3.3.";
}

leaf dtls-enable {
    type boolean;
    description
        "Indicates whether the DTLS security mechanism is enabled
        (true) or disabled (false).";
}
```

```

reference
  "RFC 9046: Babel Information Model, Section 3.3.";
}

leaf-list dtls-certs {
  type leafref {
    path "../..//dtls/name";
  }
  description
    "List of references to the dtls entries that apply to
    this interface.  When an interface instance
    is created, all dtls instances with default-apply
    'true' will be included in this list.";
  reference
    "RFC 9046: Babel Information Model, Section 3.3.";
}

```

```

}

leaf dtls-cached-info {
  type boolean;
  description
    "Indicates whether the cached_info extension is enabled.
    The extension is enabled for inclusion in ClientHello
    and ServerHello messages if the value is 'true'.";
  reference
    "RFC 9046: Babel Information Model, Section 3.3.
    RFC 8968: Babel Routing Protocol over
    Datagram Transport Layer Security, Appendix A.";
}

leaf-list dtls-cert-prefer {
  type leafref {
    path "../..//dtls/certs/type";
  }
  ordered-by user;
  description
    "List of supported certificate types, in order of
    preference. The values MUST be the 'type' attribute
    in the list 'certs' of the list 'dtls'
    (../..//dtls/certs/type). This list is used to populate
    the server_certificate_type extension in a ClientHello.
    Values that are present in at least one instance in the

```

```

        certs object under dtls of a referenced dtls instance
        and that have a non-empty private-key will be used to
        populate the client_certificate_type extension in a
        ClientHello.";
    reference
        "RFC 9046: Babel Information Model, Section 3.3
        RFC 8968: Babel Routing Protocol over
        Datagram Transport Layer Security, Appendix A.";
}

leaf packet-log-enable {
    type boolean;
    description
        "If true, logging of babel packets received on this
        interface is enabled; if false, babel packets are not
        logged.";
    reference
        "RFC 9046: Babel Information Model, Section 3.3.";
}

leaf packet-log {
    type inet:uri;

```

```

    config false;
    description
        "A reference or url link to a file that contains a
        timestamped log of packets received and sent on
        udp-port on this interface. The [libpcap] file
        format with .pcap file extension SHOULD be supported for
        packet log files. Logging is enabled / disabled by
        packet-log-enable.";
    reference
        "RFC 9046: Babel Information Model, Section 3.3.";
}

container statistics {
    config false;
    description
        "Statistics collection object for this interface.";
    reference
        "RFC 9046: Babel Information Model, Section 3.3.";
}

```

```

leaf discontinuity-time {
    type yang:date-and-time;
    mandatory true;
    description
        "The time on the most recent occasion at which any one
        or more of counters suffered a discontinuity. If no
        such discontinuities have occurred since the last
        re-initialization of the local management subsystem,
        then this node contains the time the local management
        subsystem re-initialized itself.";
}

leaf sent-mcast-hello {
    type yang:counter32;
    description
        "A count of the number of multicast Hello packets sent
        on this interface.";
    reference
        "RFC 9046: Babel Information Model, Section 3.4.";
}

leaf sent-mcast-update {
    type yang:counter32;
    description
        "A count of the number of multicast update packets sent
        on this interface.";
    reference
        "RFC 9046: Babel Information Model, Section 3.4.";
}

```

```

leaf sent-ucast-hello {
    type yang:counter32;
    description
        "A count of the number of unicast Hello packets sent
        on this interface.";
    reference
        "RFC 9046: Babel Information Model, Section 3.6.";
}

leaf sent-ucast-update {
    type yang:counter32;
    description

```

```

        "A count of the number of unicast update packets sent
        on this interface.";
    reference
        "RFC 9046: Babel Information Model, Section 3.6.";
}

leaf sent-ihu {
    type yang:counter32;
    description
        "A count of the number of IHU packets sent on this
        interface.";
    reference
        "RFC 9046: Babel Information Model, Section 3.6.";
}

leaf received-packets {
    type yang:counter32;
    description
        "A count of the number of Babel packets received on
        this interface.";
    reference
        "RFC 9046: Babel Information Model, Section 3.4.";
}

action reset {
    description
        "The information model [RFC 9046] defines reset
        action as a system-wide reset of Babel statistics.
        In YANG the reset action is associated with the
        container where the action is defined. In this case
        the action is associated with the statistics container
        inside an interface. The action will therefore
        reset statistics at an interface level.

        Implementations that want to support a system-wide
        reset of Babel statistics need to call this action

```

```

        for every instance of the interface.";
    input {
        leaf reset-at {
            type yang:date-and-time;

```



```

        description
            "The time when the reset was issued.";
    }
}

output {
    leaf reset-finished-at {
        type yang:date-and-time;
        description
            "The time when the reset finished.";
    }
}
}
}

list neighbor-objects {
    key "neighbor-address";
    config false;
    description
        "A set of Babel Neighbor Object.";
    reference
        "RFC 9046: Babel Information Model, Section 3.5.";

    leaf neighbor-address {
        type inet:ip-address;
        description
            "IPv4 or v6 address the neighbor sends packets from.";
        reference
            "RFC 9046: Babel Information Model, Section 3.5.";
    }

    leaf hello-mcast-history {
        type string;
        description
            "The multicast Hello history of whether or not the
            multicast Hello packets prior to exp-mcast-
            hello-seqno were received, with a '1' for the most
            recent Hello placed in the most significant bit and
            prior Hellos shifted right (with '0' bits placed
            between prior Hellos and most recent Hello for any
            not-received Hellos); represented as a string of
            utf-8 encoded hex digits. A bit that is set indicates
            that the corresponding Hello was received, and a bit

```

```

        that is cleared indicates that the corresponding Hello
        was not received.";
reference
    "RFC 9046: Babel Information Model, Section 3.5.";
}

leaf hello-ucast-history {
    type string;
    description
        "The unicast Hello history of whether or not the
        unicast Hello packets prior to exp-ucast-hello-seqno
        were received, with a '1' for the most
        recent Hello placed in the most significant bit and
        prior Hellos shifted right (with '0' bits placed
        between prior Hellos and most recent Hello for any
        not-received Hellos); represented as a string using
        utf-8 encoded hex digits where a '1' bit = Hello
        received and a '0' bit = Hello not received.";
reference
    "RFC 9046: Babel Information Model, Section 3.5.";
}

leaf txcost {
    type int32;
    default "0";
    description
        "Transmission cost value from the last IHU packet
        received from this neighbor, or maximum value
        (infinity) to indicate the IHU hold timer for this
        neighbor has expired description.";
reference
    "RFC 9046: Babel Information Model, Section 3.5.";
}

leaf exp-mcast-hello-seqno {
    type union {
        type enumeration {
            enum null {
                description
                    "Multicast Hello packets are not expected, or
                    processing of multicast packets is not
                    enabled.";
            }
        }
        type uint16;
    }
    description
        "Expected multicast Hello sequence number of next Hello

```

Internet-Draft

Babel YANG model

September 2021

```
        to be received from this neighbor; if multicast Hello
        packets are not expected, or processing of multicast
        packets is not enabled, this MUST be NULL.";
    reference
        "RFC 9046: Babel Information Model, Section 3.5.";
}

leaf exp-ucast-hello-seqno {
    type union {
        type enumeration {
            enum null {
                description
                    "Unicast Hello packets are not expected, or
                    processing of unicast packets is not enabled.";
            }
        }
        type uint16;
    }
    default null;
    description
        "Expected unicast Hello sequence number of next Hello
        to be received from this neighbor; if unicast Hello
        packets are not expected, or processing of unicast
        packets is not enabled, this MUST be NULL.";
    reference
        "RFC 9046: Babel Information Model, Section 3.5.";
}

leaf ucast-hello-seqno {
    type union {
        type enumeration {
            enum null {
                description
                    "Unicast Hello packets are not being sent.";
            }
        }
        type uint16;
    }
    default null;
    description
        "The current sequence number in use for unicast Hellos
        sent to this neighbor. If unicast Hellos are not being
```

```
        sent, this MUST be NULL.";
    reference
        "RFC 9046: Babel Information Model, Section 3.5.";
}

leaf ucast-hello-interval {
```

```
    type uint16;
    units "centiseconds";
    description
        "The current interval in use for unicast hellos sent to
        this neighbor. Units are centiseconds.";
    reference
        "RFC 9046: Babel Information Model, Section 3.5.";
}

leaf rxcost {
    type uint16;
    description
        "Reception cost calculated for this neighbor. This
        value is usually derived from the Hello history, which
        may be combined with other data, such as statistics
        maintained by the link layer. The rxcost is sent to a
        neighbor in each IHU.";
    reference
        "RFC 9046: Babel Information Model, Section 3.5.";
}

leaf cost {
    type int32;
    description
        "Link cost is computed from the values maintained in
        the neighbor table. The statistics kept in the
        neighbor table about the reception of Hellos, and the
        txcost computed from received IHU packets.";
    reference
        "RFC 9046: Babel Information Model, Section 3.5.";
}
}
}

list mac-key-set {
```

```
key "name";

description
  "A MAC key set object. If this object is implemented, it
  provides access to parameters related to the MAC security
  mechanism.";
reference
  "RFC 9046: Babel Information Model, Section 3.7.";

leaf name {
  type string;
  description
    "A string that uniquely identifies the MAC object.";
```

```
}

leaf default-apply {
  type boolean;
  description
    "A Boolean flag indicating whether this object
    instance is applied to all new interfaces, by default.
    If 'true', this instance is applied to new babel-
    interfaces instances at the time they are created,
    by including it in the mac-key-sets list under
    the interface. If 'false', this instance is not applied
    to new interface instances when they are created.";
  reference
    "RFC 9046: Babel Information Model, Section 3.7.";
}

list keys {
  key "name";
  min-elements 1;
  description
    "A set of keys objects.";
  reference
    "RFC 9046: Babel Information Model, Section 3.8.";

  leaf name {
    type string;
    description
      "A unique name for this MAC key that can be used to
```

```

        identify the key in this object instance, since the
        key value is not allowed to be read. This value can
        only be provided when this instance is created, and is
        not subsequently writable.";
reference
  "RFC 9046: Babel Information Model, Section 3.8.";
}

leaf use-send {
  type boolean;
  mandatory true;
  description
    "Indicates whether this key value is used to compute a
    MAC and include that MAC in the sent Babel packet. A
    MAC for sent packets is computed using this key if the
    value is 'true'. If the value is 'false', this key is
    not used to compute a MAC to include in sent Babel
    packets.";
reference
  "RFC 9046: Babel Information Model, Section 3.8.";
}

```

```

}

leaf use-verify {
  type boolean;
  mandatory true;
  description
    "Indicates whether this key value is used to verify
    incoming Babel packets. This key is used to verify
    incoming packets if the value is 'true'. If the value
    is 'false', no MAC is computed from this key for
    comparing an incoming packet.";
reference
  "RFC 9046: Babel Information Model, Section 3.8.";
}

leaf value {
  nacm:default-deny-all;
  type binary;
  mandatory true;
  description
    "The value of the MAC key."
}

```

This value is of a length suitable for the associated babel-mac-key-algorithm. If the algorithm is based on the HMAC construction [RFC2104], the length MUST be between 0 and an upper limit that is at least the size of the output length (where 'HMAC-SHA256' output length is 32 octets as described in [RFC4868]). Longer lengths MAY be supported but are not necessary if the management system has the ability to generate a suitably random value (e.g., by randomly generating a value or by using a key derivation technique as recommended in [RFC8967] Security Considerations). If the algorithm is 'BLAKE2s-128', the length MUST be between 0 and 32 bytes inclusive as specified by [RFC7693].";

reference

"RFC 9046: Babel Information Model, [Section 3.8](#),

[RFC 2104](#): HMAC: Keyed-Hashing for Message Authentication

[RFC 4868](#): Using HMAC-SHA-256, HMAC-SHA-384, and HMAC-SHA-512 with IPsec,

[RFC 7693](#): The BLAKE2 Cryptographic Hash and Message Authentication Code (MAC).

[RFC 8967](#): MAC Authentication for Babel.";

}

leaf algorithm {

```
type identityref {
  base mac-algorithms;
}
mandatory true;
description
  "The MAC algorithm used with this key. The
  value MUST be one of the identities
  listed with the base of 'mac-algorithms'.";
reference
  "RFC 9046: Babel Information Model, Section 3.8.";
}
```

```
action test {
  description
```

```
"An operation that allows the MAC key and MAC
algorithm to be tested to see if they produce an
expected outcome. Input to this operation are a
binary string and a calculated MAC (also in the
format of a binary string) for the binary string.
The implementation is expected to create a MAC over
the binary string using the value and algorithm.
The output of this operation is a binary indication
that the calculated MAC matched the input MAC (true)
or the MACs did not match (false).";
```

```
reference
```

```
"RFC 9046: Babel Information Model, Section 3.8.";
```

```
input {
```

```
  leaf test-string {
```

```
    type binary;
```

```
    mandatory true;
```

```
    description
```

```
      "Input to this operation is a binary string.
```

```
      The implementation is expected to create
```

```
      a MAC over this string using the value and
```

```
      the algorithm defined as part of the
```

```
      mac-key-set.";
```

```
    reference
```

```
      "RFC 9046: Babel Information Model, Section 3.8.";
```

```
  }
```

```
  leaf mac {
```

```
    type binary;
```

```
    mandatory true;
```

```
    description
```

```
      "Input to this operation includes a MAC.
```

```
      The implementation is expected to calculate a MAC
```

```
      over the string using the value and algorithm of
```

```
      this key object and compare its calculated MAC to
      this input MAC.";
```

```
    reference
```

```
      "RFC 9046: Babel Information Model, Section 3.8.";
```

```
  }
```

```
}
```



```

output {
  leaf indication {
    type boolean;
    mandatory true;
    description
      "The output of this operation is a binary
      indication that the calculated MAC matched the
      input MAC (true) or the MACs did not match
      (false).";
    reference
      "RFC 9046: Babel Information Model, Section 3.8.";
  }
}
}
}
}
}

```

```

list dtls {
  key "name";

  description
    "A dtls object. If this object is implemented,
    it provides access to parameters related to the DTLS
    security mechanism.";
  reference
    "RFC 9046: Babel Information Model, Section 3.9";

  leaf name {
    type string;
    description
      "A string that uniquely identifies a dtls object.";
  }

  leaf default-apply {
    type boolean;
    mandatory true;
    description
      "A Boolean flag indicating whether this object
      instance is applied to all new interfaces, by default.
      If 'true', this instance is applied to new interfaces
      instances at the time they are created, by including it

```

```

        in the dtls-certs list under the interface. If 'false',
        this instance is not applied to new interface
        instances when they are created.";
    reference
        "RFC 9046: Babel Information Model, Section 3.9.";
}

list certs {
    key "name";

    min-elements 1;
    description
        "A set of cert objects. This contains
        both certificates for this implementation to present
        for authentication, and to accept from others.
        Certificates with a non-empty private-key
        can be presented by this implementation for
        authentication.";
    reference
        "RFC 9046: Babel Information Model, Section 3.10.";

    leaf name {
        type string;
        description
            "A unique name for this certificate that can be
            used to identify the certificate in this object
            instance, since the value is too long to be useful
            for identification. This value MUST NOT be empty
            and can only be provided when this instance is created
            (i.e., it is not subsequently writable).";
        reference
            "RFC 9046: Babel Information Model, Section 3.10.";
    }

    leaf value {
        nacm:default-deny-write;
        type string;
        mandatory true;
        description
            "The certificate in PEM format [RFC7468]. This
            value can only be provided when this instance is
            created, and is not subsequently writable.";
        reference
            "RFC 9046: Babel Information Model, Section 3.10.";
    }

    leaf type {
        nacm:default-deny-write;

```

Internet-Draft

Babel YANG model

September 2021

```
    type identityref {
      base dtls-cert-types;
    }
    mandatory true;
    description
      "The certificate type of this object instance.
      The value MUST be the same as one of the
      identities listed with the base 'dtls-cert-types'.
      This value can only be provided when this
      instance is created, and is not subsequently
      writable.";
    reference
      "RFC 9046: Babel Information Model, Section 3.10.";
  }

  leaf private-key {
    nacm:default-deny-all;
    type binary;
    mandatory true;
    description
      "The value of the private key. If this is non-empty,
      this certificate can be used by this implementation to
      provide a certificate during DTLS handshaking.";
    reference
      "RFC 9046: Babel Information Model, Section 3.10.";
  }

  leaf algorithm {
    nacm:default-deny-write;
    type identityref {
      base ct:private-key-format;
    }
    mandatory true;
    description
      "Identifies the algorithm identity with which the
      private-key has been encoded. This value can only be
      provided when this instance is created, and is not
      subsequently writable.";
  }
}
uses routes;
}
```

```
}  
}  
<CODE ENDS>
```

[3.](#) IANA Considerations

This document registers a URI and a YANG module.

[3.1.](#) URI Registrations

URI: urn:ietf:params:xml:ns:yang:ietf-babel

[3.2.](#) YANG Module Name Registration

This document registers a YANG module in the YANG Module Names registry YANG [[RFC6020](#)].

Name:ietf-babel

Namespace: urn:ietf:params:xml:ns:yang:ietf-babel

prefix: babel

reference: RFC XXXX

[4.](#) Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocol such as NETCONF [[RFC6241](#)] or RESTCONF [[RFC8040](#)]. The lowest NETCONF layer is the secure transport layer and the mandatory-to-implement secure transport is SSH [[RFC6242](#)]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [[RFC8446](#)].

The NETCONF Access Control Model (NACM [[RFC8341](#)]) provides the means to restrict access for particular NETCONF users to a pre-configured subset of all available NETCONF protocol operations and content.

The security considerations outlined here are specific to the YANG data model, and do not cover security considerations of the Babel protocol or its security mechanisms in The Babel Routing Protocol [[RFC8966](#)], MAC Authentication for the Babel Routing Protocol [[RFC8967](#)], and Babel Routing Protocol over Data Transport Layer

Security [[RFC8968](#)]. Each of these has its own Security Considerations section for considerations that are specific to it.

There are a number of data nodes defined in the YANG module which are writable/created/deleted (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., <edit-config>) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability from a config true perspective:

'babel': This container includes an 'enable' parameter that can be used to enable or disable use of Babel on a router

'babel/constants': This container includes configuration parameters that can prevent reachability if misconfigured.

'babel/interfaces': This leaf-list has configuration parameters that can enable/disable security mechanisms and change performance characteristics of the Babel protocol. For example, enabling logging of packets and giving unintended access to the log files gives an attacker detailed knowledge of the network, and allows it to launch an attack on the traffic traversing the network device.

'babel/hmac' and 'babel/dtls': These contain security credentials that influence whether incoming packets are trusted, and whether outgoing packets are produced in a way such that the receiver will treat them as trusted.

Some of the readable data or config false nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability from a config false perspective:

'babel': Access to the information in the various nodes can disclose the network topology. Additionally, the routes used by a network device may be used to mount a subsequent attack on traffic traversing the network device.

'babel/hmac' and 'babel/dtls': These contain security credentials, including private credentials of the router; however it is required that these values not be readable.

Some of the RPC operations in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control access to these operations. These are the operations and their sensitivity/vulnerability from a RPC operation perspective:

This model defines two actions. Resetting the statistics within an interface container would be visible to any monitoring processes, which should be designed to account for the possibility of such a reset. The "test" action allows for validation that a MAC key and MAC algorithm have been properly configured. The MAC key is a sensitive piece of information, and it is important to prevent an attacker that does not know the MAC key from being able to determine the MAC value by trying different input parameters. The "test"

action has been designed to not reveal such information directly. Such information might also be revealed indirectly, due to side channels such as the time it takes to produce a response to the action. Implementations SHOULD use a constant-time comparison between the input mac and the locally generated MAC value for comparison, in order to avoid such side channel leakage.

[5.](#) Acknowledgements

Juliusz Chroboczek provided most of the example configurations for babel that are shown in the Appendix.

[6.](#) References

[6.1.](#) Normative References

[I-D.ietf-netconf-crypto-types]

Watsen, K., "YANG Data Types and Groupings for Cryptography", Work in Progress, Internet-Draft, [draft-ietf-netconf-crypto-types-21](#), 14 September 2021, <<https://www.ietf.org/archive/id/draft-ietf-netconf-crypto-types-21.txt>>.

[I-D.ietf-tls-dtls13]

Rescorla, E., Tschofenig, H., and N. Modadugu, "The Datagram Transport Layer Security (DTLS) Protocol Version 1.3", Work in Progress, Internet-Draft, [draft-ietf-tls-dtls13-43](https://www.ietf.org/internet-drafts/draft-ietf-tls-dtls13-43), 30 April 2021, <<https://www.ietf.org/internet-drafts/draft-ietf-tls-dtls13-43.txt>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC4868] Kelly, S. and S. Frankel, "Using HMAC-SHA-256, HMAC-SHA-384, and HMAC-SHA-512 with IPsec", [RFC 4868](#), DOI 10.17487/RFC4868, May 2007, <<https://www.rfc-editor.org/info/rfc4868>>.

[RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", [RFC 6991](#), DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.

[RFC7693] Saarinen, M.-J., Ed. and J.-P. Aumasson, "The BLAKE2 Cryptographic Hash and Message Authentication Code (MAC)", [RFC 7693](#), DOI 10.17487/RFC7693, November 2015, <<https://www.rfc-editor.org/info/rfc7693>>.

[RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

[RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.

[RFC8343] Bjorklund, M., "A YANG Data Model for Interface Management", [RFC 8343](#), DOI 10.17487/RFC8343, March 2018,

<<https://www.rfc-editor.org/info/rfc8343>>.

- [RFC8349] Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", [RFC 8349](#), DOI 10.17487/RFC8349, March 2018, <<https://www.rfc-editor.org/info/rfc8349>>.
- [RFC8966] Chroboczek, J. and D. Schinazi, "The Babel Routing Protocol", [RFC 8966](#), DOI 10.17487/RFC8966, January 2021, <<https://www.rfc-editor.org/info/rfc8966>>.
- [RFC8967] Do, C., Kołodziejak, W., and J. Chroboczek, "MAC Authentication for the Babel Routing Protocol", [RFC 8967](#), DOI 10.17487/RFC8967, January 2021, <<https://www.rfc-editor.org/info/rfc8967>>.
- [RFC8968] Decimo, A., Schinazi, D., and J. Chroboczek, "Babel Routing Protocol over Datagram Transport Layer Security", [RFC 8968](#), DOI 10.17487/RFC8968, January 2021, <<https://www.rfc-editor.org/info/rfc8968>>.
- [RFC9046] Stark, B. and M. Jethanandani, "Babel Information Model", [RFC 9046](#), DOI 10.17487/RFC9046, June 2021, <<https://www.rfc-editor.org/info/rfc9046>>.

6.2. Informative References

- [RFC2104] Krawczyk, H., Bellare, M., and R. Canetti, "HMAC: Keyed-Hashing for Message Authentication", [RFC 2104](#), DOI 10.17487/RFC2104, February 1997, <<https://www.rfc-editor.org/info/rfc2104>>.

- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011,

<<https://www.rfc-editor.org/info/rfc6241>>.

- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

[Appendix A](#). Tree Diagram and Example Configurations

This section is devoted to including a complete tree diagram and examples that demonstrate how Babel can be configured.

[A.1](#). Complete Tree Diagram

This section includes the complete tree diagram for the Babel YANG module.

```
module: ietf-babel

  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol:
      +--rw babel!
        +--ro version?                string
        +--rw enable                  boolean
```

```

+--ro seqno?                uint16
+--rw statistics-enabled?   boolean
+--rw constants
| +--rw udp-port?          inet:port-number
| +--rw mcast-group?       inet:ip-address
+--rw interfaces* [reference]
| +--rw reference          if:interface-ref
| +--rw enable?           boolean
| +--rw metric-algorithm   identityref
| +--rw split-horizon?     boolean
| +--ro mcast-hello-seqno? uint16
| +--rw mcast-hello-interval? uint16
| +--rw update-interval?   uint16
| +--rw mac-enable?       boolean
| +--rw mac-key-sets*     -> ../../mac-key-set/name
| +--rw mac-verify?       boolean
| +--rw dtls-enable?      boolean
| +--rw dtls-certs*       -> ../../dtls/name
| +--rw dtls-cached-info? boolean
| +--rw dtls-cert-prefer* -> ../../dtls/certs/type
| +--rw packet-log-enable? boolean
| +--ro packet-log?       inet:uri
| +--ro statistics
| | +--ro discontinuity-time yang:date-and-time
| | +--ro sent-mcast-hello?  yang:counter32
| | +--ro sent-mcast-update? yang:counter32
| | +--ro sent-ucast-hello?  yang:counter32
| | +--ro sent-ucast-update? yang:counter32
| | +--ro sent-ihu?          yang:counter32
| | +--ro received-packets?  yang:counter32
| | +---x reset
| |   +---w input
| |   | +---w reset-at?     yang:date-and-time
| |   +--ro output
| |     +--ro reset-finished-at? yang:date-and-time
+--ro neighbor-objects* [neighbor-address]
| +--ro neighbor-address     inet:ip-address
| +--ro hello-mcast-history? string
| +--ro hello-ucast-history? string
| +--ro txcost?              int32
| +--ro exp-mcast-hello-seqno? union
| +--ro exp-ucast-hello-seqno? union
| +--ro ucast-hello-seqno?   union
| +--ro ucast-hello-interval? uint16
| +--ro rxcost?              uint16
| +--ro cost?                int32
+--rw mac-key-set* [name]

```

```

| +--rw name                string
| +--rw default-apply?     boolean
| +--rw keys* [name]
|   +--rw name              string
|   +--rw use-send          boolean
|   +--rw use-verify        boolean
|   +--rw value              binary
|   +--rw algorithm          identityref
|   +---x test
|     +---w input
|       | +---w test-string  binary
|       | +---w mac           binary
|       +--ro output
|         +--ro indication   boolean
+--rw dtls* [name]
| +--rw name                string
| +--rw default-apply       boolean
| +--rw certs* [name]
|   +--rw name              string
|   +--rw value              string
|   +--rw type               identityref
|   +--rw private-key        binary
|   +--rw algorithm          identityref
+--ro routes* [prefix]
  +--ro prefix                inet:ip-prefix
  +--ro router-id?           binary
  +--ro neighbor?            leafref
  +--ro received-metric?     union
  +--ro calculated-metric?   union
  +--ro seqno?                uint16
  +--ro next-hop?            union
  +--ro feasible?            boolean
  +--ro selected?            boolean

```

[A.2. Statistics Gathering Enabled](#)

In this example, interface eth0 is being configured for routing protocol Babel, and statistics gathering is enabled. For security, HMAC-SHA256 is supported. Every sent Babel packets is signed with the key value provided, and every received Babel packet is verified with the same key value.

Internet-Draft

Babel YANG model

September 2021

```
<?xml version="1.0" encoding="UTF-8"?>
<interfaces xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces"
            xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">
  <interface>
    <name>eth0</name>
    <type>ianaift:ethernetCsmacd</type>
    <enabled>true</enabled>
  </interface>
</interfaces>
<routing
  xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
  <control-plane-protocols>
    <control-plane-protocol>
      <type
        xmlns:babel=
          "urn:ietf:params:xml:ns:yang:ietf-babel">babel:babel</type>
      <name>name:babel</name>
      <babel
        xmlns="urn:ietf:params:xml:ns:yang:ietf-babel">
        <enable>true</enable>
        <statistics-enabled>true</statistics-enabled>
        <interfaces>
          <reference>eth0</reference>
          <metric-algorithm>two-out-of-three</metric-algorithm>
          <split-horizon>true</split-horizon>
        </interfaces>
        <mac-key-set>
          <name>hmac-sha256</name>
          <keys>
            <name>hmac-sha256-keys</name>
            <use-send>true</use-send>
            <use-verify>true</use-verify>
            <value>base64encodedvalue==</value>
            <algorithm>hmac-sha256</algorithm>
          </keys>
        </mac-key-set>
      </babel>
    </control-plane-protocol>
  </control-plane-protocols>
```

```
</routing>
```

[A.3.](#) Automatic Detection of Properties

```
<!-- In this example, babeld is configured on two interfaces
```

```
    interface eth0
    interface wlan0
```

This says to run Babel on interfaces eth0 and wlan0. Babeld will automatically detect that eth0 is wired and wlan0 is wireless, and will configure the right parameters automatically.

```
-->
```

```
<?xml version="1.0" encoding="UTF-8"?>
<interfaces xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces"
            xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">
  <interface>
    <name>eth0</name>
    <type>ianaift:ethernetCsmacd</type>
    <enabled>true</enabled>
  </interface>
  <interface>
    <name>wlan0</name>
    <type>ianaift:ieee80211</type>
    <enabled>true</enabled>
  </interface>
</interfaces>
<routing
  xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
  <control-plane-protocols>
    <control-plane-protocol>
      <type
        xmlns:babel=
          "urn:ietf:params:xml:ns:yang:ietf-babel">babel:babel</type>
      <name>name:babel</name>
```

```

<babel
  xmlns="urn:ietf:params:xml:ns:yang:ietf-babel">
  <enable>true</enable>
  <interfaces>
    <reference>eth0</reference>
    <enable>true</enable>
    <metric-algorithm>two-out-of-three</metric-algorithm>
    <split-horizon>true</split-horizon>
  </interfaces>
  <interfaces>
    <reference>wlan0</reference>
    <enable>true</enable>
    <metric-algorithm>etx</metric-algorithm>
    <split-horizon>>false</split-horizon>
  </interfaces>
</babel>

```

```

  </control-plane-protocol>
</control-plane-protocols>
</routing>

```

[A.4.](#) Override Default Properties

<!-- In this example, babeld is configured on three interfaces

```

interface eth0
interface eth1 type wireless
interface tun0 type tunnel

```

Here, interface eth1 is an Ethernet bridged to a wireless radio, so babeld's autodetection fails, and the interface type needs to be configured manually. Tunnels are not detected automatically, so this needs to be specified.

This is equivalent to the following:

```

interface eth0 metric-algorithm 2-out-of-3 split-horizon true
interface eth1 metric-algorithm etx split-horizon false
interface tun0 metric-algorithm 2-out-of-3 split-horizon true
-->

```

```

<?xml version="1.0" encoding="UTF-8"?>

```

```

<interfaces xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces"
            xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">
  <interface>
    <name>eth0</name>
    <type>ianaift:ethernetCsmacd</type>
    <enabled>true</enabled>
  </interface>
  <interface>
    <name>eth1</name>
    <type>ianaift:ethernetCsmacd</type>
    <enabled>true</enabled>
  </interface>
  <interface>
    <name>tun0</name>
    <type>ianaift:tunnel</type>
    <enabled>true</enabled>
  </interface>
</interfaces>
<routing
  xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
  <control-plane-protocols>
    <control-plane-protocol>
      <type

```

```

      xmlns:babel=
        "urn:ietf:params:xml:ns:yang:ietf-babel">babel:babel</type>
    <name>name:babel</name>
    <babel
      xmlns="urn:ietf:params:xml:ns:yang:ietf-babel">
      <enable>true</enable>
      <interfaces>
        <reference>eth0</reference>
        <enable>true</enable>
        <metric-algorithm>two-out-of-three</metric-algorithm>
        <split-horizon>true</split-horizon>
      </interfaces>
      <interfaces>
        <reference>eth1</reference>
        <enable>true</enable>
        <metric-algorithm>etx</metric-algorithm>
        <split-horizon>>false</split-horizon>
      </interfaces>

```

```

    <interfaces>
      <reference>tun0</reference>
      <enable>>true</enable>
      <metric-algorithm>two-out-of-three</metric-algorithm>
      <split-horizon>>true</split-horizon>
    </interfaces>
  </babel>
</control-plane-protocol>
</control-plane-protocols>
</routing>

```

A.5. Configuring other Properties

<!-- In this example, two interfaces are configured for babeld

```

interface eth0
interface ppp0 hello-interval 30 update-interval 120

```

Here, ppp0 is a metered 3G link used for fallback connectivity. It runs with much higher than default time constants in order to avoid control traffic as much as possible.

-->

```

<?xml version="1.0" encoding="UTF-8"?>
<interfaces xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces"
  xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">
  <interface>
    <name>eth0</name>
    <type>ianaift:ethernetCsmacd</type>
    <enabled>>true</enabled>

```

```

</interface>
<interface>
  <name>ppp0</name>
  <type>ianaift:ppp</type>
  <enabled>>true</enabled>
</interface>
</interfaces>
<routing
  xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
  <control-plane-protocols>
    <control-plane-protocol>

```



```
<type
  xmlns:babel=
    "urn:ietf:params:xml:ns:yang:ietf-babel">babel:babel</type>
<name>name:babel</name>
<babel
  xmlns="urn:ietf:params:xml:ns:yang:ietf-babel">
  <enable>true</enable>
  <interfaces>
    <reference>eth0</reference>
    <enable>true</enable>
    <metric-algorithm>two-out-of-three</metric-algorithm>
    <split-horizon>true</split-horizon>
  </interfaces>
  <interfaces>
    <reference>ppp0</reference>
    <enable>true</enable>
    <mcast-hello-interval>30</mcast-hello-interval>
    <update-interval>120</update-interval>
    <metric-algorithm>two-out-of-three</metric-algorithm>
  </interfaces>
</babel>
</control-plane-protocol>
</control-plane-protocols>
</routing>
```

Authors' Addresses

Mahesh Jethanandani
Kloud Services
California
United States of America

Email: mjethanandani@gmail.com

Barbara Stark
AT&T
Atlanta, GA
United States of America

Email: barbara.stark@att.com