BESS Workgroup J. Rabadan, Ed. Internet Draft W. Henderickx S. Palislamovic Intended status: Standards Track Nokia A. Isaac J. Drake W. Lin Juniper A. Sajassi Cisco

Expires: March 17, 2017

September 13, 2016

IP Prefix Advertisement in EVPN draft-ietf-bess-evpn-prefix-advertisement-03

Abstract

EVPN provides a flexible control plane that allows intra-subnet connectivity in an IP/MPLS and/or an NVO-based network. In NVO networks, there is also a need for a dynamic and efficient intersubnet connectivity across Tenant Systems and End Devices that can be physical or virtual and may not support their own routing protocols. This document defines a new EVPN route type for the advertisement of IP Prefixes and explains some use-case examples where this new routetype is used.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

Rabadan et al. Expires March 17, 2017

[Page 1]

The list of current Internet-Drafts can be accessed at http://www.ietf.org/ietf/lid-abstracts.txt

The list of Internet-Draft Shadow Directories can be accessed at http://www.ietf.org/shadow.html

This Internet-Draft will expire on March 17, 2017.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>http://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

<u>3</u>
<u>4</u>
<u>4</u>
7
<u>8</u>
9
1
2
2
5
6
9
0
3
5
8
9
9
9
0
0
0

1. Terminology

GW IP: Gateway IP Address

IPL: IP address length

IRB: Integrated Routing and Bridging interface

ML: MAC address length

NVE: Network Virtualization Edge

TS: Tenant System

VA: Virtual Appliance

RT-2: EVPN route type 2, i.e. MAC/IP advertisement route

RT-5: EVPN route type 5, i.e. IP Prefix route

AC: Attachment Circuit

Overlay index: object used in the IP Prefix route, as described in this document. It can be an IP address in the tenant space or an ESI, and identifies a pointer yielded by the IP route lookup at the routing context importing the route. An overlay index always needs a recursive route resolution on the NVE receiving the IP Prefix route, so that the NVE knows to which egress NVE it needs to forward the packets.

Underlay next-hop: IP address sent by BGP along with any EVPN route, i.e. BGP next-hop. It identifies the NVE sending the route and it is used at the receiving NVE as the VXLAN destination VTEP or NVGRE destination end-point.

Ethernet NVO tunnel: it refers to Network Virtualization Overlay tunnels with Ethernet payload. Examples of this type of tunnels are VXLAN or nvGRE.

IP NVO tunnel: it refers to Network Virtualization Overlay tunnels

with IP payload (no MAC header in the payload). Examples of IP NVO tunnels are VXLAN GPE or MPLSoGRE (both with IP payload).

2. Introduction and problem statement

Inter-subnet connectivity is required for certain tenants within the Data Center. [EVPN-INTERSUBNET] defines some fairly common intersubnet forwarding scenarios where TSes can exchange packets with TSes located in remote subnets. In order to meet this requirement, [EVPN-INTERSUBNET] describes how MAC/IPs encoded in TS RT-2 routes are not only used to populate MAC-VRF and overlay ARP tables, but also IP-VRF tables with the encoded TS host routes (/32 or /128). In some cases, EVPN may advertise IP Prefixes and therefore provide aggregation in the IP-VRF tables, as opposed to program individual host routes. This document complements the scenarios described in [EVPN-INTERSUBNET] and defines how EVPN may be used to advertise IP Prefixes.

<u>Section 2.1</u> describes the inter-subnet connectivity requirements in Data Centers. <u>Section 2.2</u> explains why a new EVPN route type is required for IP Prefix advertisements. Once the need for a new EVPN route type is justified, sections <u>3</u>, <u>4</u> and <u>5</u> will describe this route type and how it is used in some specific use cases.

2.1 Inter-subnet connectivity requirements in Data Centers

[RFC7432] is used as the control plane for a Network Virtualization Overlay (NVO3) solution in Data Centers (DC), where Network Virtualization Edge (NVE) devices can be located in Hypervisors or TORs, as described in [<u>EVPN-OVERLAY</u>].

If we use the term Tenant System (TS) to designate a physical or virtual system identified by MAC and IP addresses, and connected to an EVPN instance, the following considerations apply:

- o The Tenant Systems may be Virtual Machines (VMs) that generate traffic from their own MAC and IP.
- o The Tenant Systems may be Virtual Appliance entities (VAs) that forward traffic to/from IP addresses of different End Devices seating behind them.
 - o These VAs can be firewalls, load balancers, NAT devices, other appliances or virtual gateways with virtual routing instances.
 - o These VAs do not have their own routing protocols and hence rely on the EVPN NVEs to advertise the routes on their behalf.

Rabadan et al. Expires March 17, 2017

[Page 4]

- o In all these cases, the VA will forward traffic to the Data Center using its own source MAC but the source IP will be the one associated to the End Device seating behind or a translated IP address (part of a public NAT pool) if the VA is performing NAT.
- o Note that the same IP address could exist behind two of these TS. One example of this would be certain appliance resiliency mechanisms, where a virtual IP or floating IP can be owned by one of the two VAs running the resiliency protocol (the master VA). VRRP is one particular example of this. Another example is multi-homed subnets, i.e. the same subnet is connected to two VAs.
- o Although these VAs provide IP connectivity to VMs and subnets behind them, they do not always have their own IP interface connected to the EVPN NVE, e.g. layer-2 firewalls are examples of VAs not supporting IP interfaces.

The following figure illustrates some of the examples described above.



Figure 1 DC inter-subnet use-cases

Where:

NVE1, NVE2, NVE3, NVE4, NVE5, DGW1 and DGW2 share the same EVI for a particular tenant. EVI-10 is comprised of the collection of MAC-VRF10 instances defined in all the NVEs. All the hosts connected to EVI-10 belong to the same IP subnet. The hosts connected to EVI-10 are listed below:

- o TS1 is a VM that generates/receives traffic from/to IP1, where IP1 belongs to the EVI-10 subnet.
- o TS2 and TS3 are Virtual Appliances (VA) that generate/receive traffic from/to the subnets and hosts seating behind them (SN1, SN2, SN3, IP4 and IP5). Their IP addresses (IP2 and IP3) belong to the EVI-10 subnet and they can also generate/receive traffic. When these VAs receive packets destined to their own MAC addresses (M2 and M3) they will route the packets to the

[Page 6]

proper subnet or host. These VAs do not support routing protocols to advertise the subnets connected to them and can move to a different server and NVE when the Cloud Management System decides to do so. These VAs may also support redundancy mechanisms for some subnets, similar to VRRP, where a floating IP is owned by the master VA and only the master VA forwards traffic to a given subnet. E.g.: vIP23 in figure 1 is a floating IP that can be owned by TS2 or TS3 depending on who the master is. Only the master will forward traffic to SN1.

- o Integrated Routing and Bridging interfaces IRB1, IRB2 and IRB3 have their own IP addresses that belong to the EVI-10 subnet too. These IRB interfaces connect the EVI-10 subnet to Virtual Routing and Forwarding (IP-VRF) instances that can route the traffic to other connected subnets for the same tenant (within the DC or at the other end of the WAN).
- o TS4 is a layer-2 VA that provides connectivity to subnets SN5, SN6 and SN7, but does not have an IP address itself in the EVI-10. TS4 is connected to a physical port on NVE5 assigned to Ethernet Segment Identifier 4.

All the above DC use cases require inter-subnet forwarding and therefore the individual host routes and subnets:

- a) MUST be advertised from the NVEs (since VAs and VMs do not run routing protocols) and
- b) MAY be associated to an overlay index that can be a VA IP address, a floating IP address or an ESI.

2.2 The requirement for a new EVPN route type

[RFC7432] defines a MAC/IP route (also referred as RT-2) where a MAC address can be advertised together with an IP address length (IPL) and IP address (IP). While a variable IPL might have been used to indicate the presence of an IP prefix in a route type 2, there are several specific use cases in which using this route type to deliver IP Prefixes is not suitable.

One example of such use cases is the "floating IP" example described in <u>section 2.1</u>. In this example we need to decouple the advertisement of the prefixes from the advertisement of the floating IP (vIP23 in figure 1) and MAC associated to it, otherwise the solution gets highly inefficient and does not scale.

E.g.: if we are advertising 1k prefixes from M2 (using RT-2) and the floating IP owner changes from M2 to M3, we would need to withdraw 1k

Rabadan et al. Expires March 17, 2017

[Page 7]

routes from M2 and re-advertise 1k routes from M3. However if we use a separate route type, we can advertise the 1k routes associated to the floating IP address (vIP23) and only one RT-2 for advertising the ownership of the floating IP, i.e. vIP23 and M2 in the route type 2. When the floating IP owner changes from M2 to M3, a single RT-2 withdraw/update is required to indicate the change. The remote DGW will not change any of the 1k prefixes associated to vIP23, but will only update the ARP resolution entry for vIP23 (now pointing at M3).

Other reasons to decouple the IP Prefix advertisement from the MAC/IP route are listed below:

- o Clean identification, operation of troubleshooting of IP Prefixes, not subject to interpretation and independent of the IPL and the IP value. E.g.: a default IP route 0.0.0.0/0 must always be easily and clearly distinguished from the absence of IP information.
- o MAC address information must not be compared by BGP when selecting two IP Prefix routes. If IP Prefixes were to be advertised using MAC/IP routes, the MAC information would always be present and part of the route key.
- o IP Prefix routes must not be subject to MAC/IP route procedures such as MAC mobility or aliasing. Prefixes advertised from two different ESIs do not mean mobility; MACs advertised from two different ESIs do mean mobility. Similarly load balancing for IP prefixes is achieved through IP mechanisms such as ECMP, and not through MAC route mechanisms such as aliasing.
- o NVEs that do not require processing IP Prefixes must have an easy way to identify an update with an IP Prefix and ignore it, rather than processing the MAC/IP route to find out only later that it carries a Prefix that must be ignored.

The following sections describe how EVPN is extended with a new route type for the advertisement of IP prefixes and how this route is used to address the current and future inter-subnet connectivity requirements existing in the Data Center.

3. The BGP EVPN IP Prefix route

The current BGP EVPN NLRI as defined in [RFC7432] is shown below:

~	
Route Type (1 octet)	
Length (1 octet)	-
Route Type specific (variable) +	- +

Where the route type field can contain one of the following specific values:

- + 1 Ethernet Auto-Discovery (A-D) route
- + 2 MAC/IP advertisement route
- + 3 Inclusive Multicast Route
- + 4 Ethernet Segment Route

This document defines an additional route type that will be used for the advertisement of IP Prefixes:

+ 5 - IP Prefix Route

The support for this new route type is OPTIONAL.

Since this new route type is OPTIONAL, an implementation not supporting it MUST ignore the route, based on the unknown route type value.

The detailed encoding of this route and associated procedures are described in the following sections.

3.1 IP Prefix Route encoding

An IP Prefix advertisement route NLRI consists of the following fields:

+-----+ RD (8 octets) +----+ [Ethernet Segment Identifier (10 octets)] +-----+ | Ethernet Tag ID (4 octets) +----+ | IP Prefix Length (1 octet) +----+ | IP Prefix (4 or 16 octets) +----+ GW IP Address (4 or 16 octets) +----+ | MPLS Label (3 octets) +----+

Where:

- o RD, Ethernet Tag ID and MPLS Label fields will be used as defined in [RFC7432] and [EVPN-OVERLAY].
- o The Ethernet Segment Identifier will be a non-zero 10-byte identifier if the ESI is used as an overlay index. It will be zero otherwise.
- o The IP Prefix Length can be set to a value between 0 and 32 (bits) for ipv4 and between 0 and 128 for ipv6.
- o The IP Prefix will be a 32 or 128-bit field (ipv4 or ipv6).
- o The GW IP (Gateway IP Address) will be a 32 or 128-bit field (ipv4 or ipv6), and will encode an overlay IP index for the IP Prefixes. The GW IP field SHOULD be zero if it is not used as an overlay index.
- o The MPLS Label field is encoded as 3 octets, where the highorder 20 bits contain the label value. The value SHOULD be null when the IP Prefix route is used for a recursive lookup resolution.
- o The total route length will indicate the type of prefix (ipv4 or ipv6) and the type of GW IP address (ipv4 or ipv6). Note that the IP Prefix + the GW IP should have a length of either 64 or 256 bits, but never 160 bits (ipv4 and ipv6 mixed values are not allowed).

The Eth-Tag ID, IP Prefix Length and IP Prefix will be part of the route key used by BGP to compare routes. The rest of the fields will

Rabadan et al.Expires March 17, 2017[Page 10]

not be part of the route key.

The route will contain a single overlay index at most, i.e. if the ESI field is different from zero, the GW IP field will be zero, and vice versa. The following table shows the different inter-subnet usecases described in this document and the corresponding coding of the overlay index in the route type 5 (RT-5). The IP-VRF-to-IP-VRF or IRB forwarding on NVEs case is a special use-case, where there may be no need for overlay index, since the actual next-hop is given by the BGP next-hop. When an overlay index is present in the RT-5, the receiving NVE will need to perform a recursive route resolution to find out to which egress NVE to forward the packets.

+-----+ | Overlay Index in the RT-5 BGP update | Use-case +-----+ | TS IP address | TS IP address| Overlay GW IP Address| Floating IP address| Overlay GW IP Address| "Bump in the wire"| ESI| IP-VRF-to-IP-VRF| Overlay GW IP, MAC or N/A +-----+

4. Benefits of using the EVPN IP Prefix route

This section clarifies the different functions accomplished by the EVPN RT-2 and RT-5 routes, and provides a list of benefits derived from using a separate route type for the advertisement of IP Prefixes in EVPN.

[RFC7432] describes the content of the BGP EVPN RT-2 specific NLRI, i.e. MAC/IP Advertisement Route, where the IP address length (IPL) and IP address (IP) of a specific advertised MAC are encoded. The subject of the MAC advertisement route is the MAC address (M) and MAC address length (ML) encoded in the route. The MAC mobility and other procedures are defined around that MAC address. The IP address information carries the host IP address required for the ARP resolution of the MAC according to [RFC7432] and the host route to be programmed in the IP-VRF [EVPN-INTERSUBNET].

The BGP EVPN route type 5 defined in this document, i.e. IP Prefix Advertisement route, decouples the advertisement of IP prefixes from the advertisement of any MAC address related to it. This brings some major benefits to NVO-based networks where certain inter-subnet forwarding scenarios are required. Some of those benefits are:

a) Upon receiving a route type 2 or type 5, an egress NVE can easily

Rabadan et al.Expires March 17, 2017[Page 11]

distinguish MACs and IPs from IP Prefixes. E.g. an IP prefix with IPL=32 being advertised from two different ingress NVEs (as RT-5) can be identified as such and be imported in the designated routing context as two ECMP routes, as opposed to two MACs competing for the same IP.

- b) Similarly, upon receiving a route, an ingress NVE not supporting processing of IP Prefixes can easily ignore the update, based on the route type.
- c) A MAC route includes the ML, M, IPL and IP in the route key that is used by BGP to compare routes, whereas for IP Prefix routes, only IPL and IP (as well as Ethernet Tag ID) are part of the route key. Advertised IP Prefixes are imported into the designated routing context, where there is no MAC information associated to IP routes. In the example illustrated in figure 1, subnet SN1 should be advertised by NVE2 and NVE3 and interpreted by DGW1 as the same route coming from two different next-hops, regardless of the MAC address associated to TS2 or TS3. This is easily accomplished in the RT-5 by including only the IP information in the route key.
- d) By decoupling the MAC from the IP Prefix advertisement procedures, we can leave the IP Prefix advertisements out of the MAC mobility procedures defined in [RFC7432] for MACs. In addition, this allows us to have an indirection mechanism for IP Prefixes advertised from a MAC/IP that can move between hypervisors. E.g. if there are 1,000 prefixes seating behind TS2 (figure 1), NVE2 will advertise all those prefixes in RT-5 routes associated to the overlay index IP2. Should TS2 move to a different NVE, a single MAC/IP advertisement route withdraw for the M2/IP2 route from NVE2 will invalidate the 1,000 prefixes, as opposed to have to wait for each individual prefix to be withdrawn. This may be easily accomplished by using IP Prefix routes that are not tied to a MAC address, and use a different MAC/IP route to advertise the location and resolution of the overlay index to a MAC address.

<u>5</u>. IP Prefix overlay index use-cases

The IP Prefix route can use a GW IP or an ESI as an overlay index as well as no overlay index whatsoever. This section describes some usecases for these index types.

<u>5.1</u> TS IP address overlay index use-case

The following figure illustrates an example of inter-subnet forwarding for subnets seating behind Virtual Appliances (on TS2 and TS3).

Rabadan et al.Expires March 17, 2017[Page 12]



Figure 2 TS IP address use-case

An example of inter-subnet forwarding between subnet SN1/24 and a subnet seating in the WAN is described below. NVE2, NVE3, DGW1 and DGW2 are running BGP EVPN. TS2 and TS3 do not support routing protocols, only a static route to forward the traffic to the WAN.

(1) NVE2 advertises the following BGP routes on behalf of TS2:

- o Route type 2 (MAC/IP route) containing: ML=48, M=M2, IPL=32, IP=IP2 and [RFC5512] BGP Encapsulation Extended Community with the corresponding Tunnel-type.
- o Route type 5 (IP Prefix route) containing: IPL=24, IP=SN1, ESI=0, GW IP address=IP2.

(2) NVE3 advertises the following BGP routes on behalf of TS3:

- o Route type 2 (MAC/IP route) containing: ML=48, M=M3, IPL=32, IP=IP3 (and BGP Encapsulation Extended Community).
- o Route type 5 (IP Prefix route) containing: IPL=24, IP=SN1, ESI=0, GW IP address=IP3.
- (3) DGW1 and DGW2 import both received routes based on the route-targets:
 - o Based on the MAC-VRF10 route-target in DGW1 and DGW2, the MAC/IP route is imported and M2 is added to the MAC-VRF10 along with its corresponding tunnel information. For instance, if VXLAN is used, the VTEP will be derived from the MAC/IP route BGP next-hop (underlay next-hop) and VNI from the MPLS Label1 field. IP2 - M2 is added to the ARP table.

Rabadan et al.Expires March 17, 2017[Page 13]

- o Based on the MAC-VRF10 route-target in DGW1 and DGW2, the IP Prefix route is also imported and SN1/24 is added to the IP-VRF with overlay index IP2 pointing at the local MAC-VRF10. Should ECMP be enabled in the IP-VRF, SN1/24 would also be added to the routing table with overlay index IP3.
- (4) When DGW1 receives a packet from the WAN with destination IPx, where IPx belongs to SN1/24:
 - o A destination IP lookup is performed on the DGW1 IP-VRF routing table and overlay index=IP2 is found. Since IP2 is an overlay index a recursive route resolution is required for IP2.
 - o IP2 is resolved to M2 in the ARP table, and M2 is resolved to the tunnel information given by the MAC-VRF FIB (e.g. remote VTEP and VNI for the VXLAN case).
 - o The IP packet destined to IPx is encapsulated with:
 - . Source inner MAC = IRB1 MAC.
 - . Destination inner MAC = M2.
 - . Tunnel information provided by the MAC-VRF (VNI, VTEP IPs and MACs for the VXLAN case).
- (5) When the packet arrives at NVE2:
 - o Based on the tunnel information (VNI for the VXLAN case), the MAC-VRF10 context is identified for a MAC lookup.
 - o Encapsulation is stripped-off and based on a MAC lookup (assuming MAC forwarding on the egress NVE), the packet is forwarded to TS2, where it will be properly routed.
- (6) Should TS2 move from NVE2 to NVE3, MAC Mobility procedures will be applied to the MAC route IP2/M2, as defined in [RFC7432]. Route type 5 prefixes are not subject to MAC mobility procedures, hence no changes in the DGW IP-VRF routing table will occur for TS2 mobility, i.e. all the prefixes will still be pointing at IP2 as overlay index. There is an indirection for e.g. SN1/24, which still points at overlay index IP2 in the routing table, but IP2 will be simply resolved to a different tunnel, based on the outcome of the MAC mobility procedures for the MAC/IP route IP2/M2.

```
Note that in the opposite direction, TS2 will send traffic based on
```

Rabadan et al.Expires March 17, 2017[Page 14]

its static-route next-hop information (IRB1 and/or IRB2), and regular EVPN procedures will be applied.

5.2 Floating IP overlay index use-case

Sometimes Tenant Systems (TS) work in active/standby mode where an upstream floating IP - owned by the active TS - is used as the overlay index to get to some subnets behind. This redundancy mode, already introduced in <u>section 2.1</u> and 2.2, is illustrated in Figure 3.

NVE2 DGW1 +----+ +-----+ +-----+ +---TS2(VA)--|(MAC-VRF10)|-| |----|(MAC-VRF10) | IP2/M2 +----+ | | | IRB1\ | <-+ (IP-VRF)|---+ +----+ _|_ vIP23 (floating) | VXLAN/ | SN1 () (WAN) | nvGRE | DGW2 +----+ (____) NVE3 <-+ |----|(MAC-VRF10) | | IP3/M3 +----+ | +---TS3(VA)--|(MAC-VRF10)|-| | IRB2\ | | +----+ (IP-VRF)|---+ +----+

Figure 3 Floating IP overlay index for redundant TS

In this example, assuming TS2 is the active TS and owns IP23:

- (1) NVE2 advertises the following BGP routes for TS2:
 - o Route type 2 (MAC/IP route) containing: ML=48, M=M2, IPL=32, IP=IP23 (and BGP Encapsulation Extended Community).
 - o Route type 5 (IP Prefix route) containing: IPL=24, IP=SN1, ESI=0, GW IP address=IP23.
- (2) NVE3 advertises the following BGP routes for TS3:
 - o Route type 5 (IP Prefix route) containing: IPL=24, IP=SN1, ESI=0, GW IP address=IP23.
- (3) DGW1 and DGW2 import both received routes based on the routetarget:
 - o M2 is added to the MAC-VRF10 FIB along with its corresponding tunnel information. For the VXLAN use case, the VTEP will be derived from the MAC/IP route BGP next-hop and VNI from the

Rabadan et al.Expires March 17, 2017[Page 15]

VNI/VSID field. IP23 - M2 is added to the ARP table.

- o SN1/24 is added to the IP-VRF in DGW1 and DGW2 with overlay index IP23 pointing at the local MAC-VRF10.
- (4) When DGW1 receives a packet from the WAN with destination IPx, where IPx belongs to SN1/24:
 - o A destination IP lookup is performed on the DGW1 IP-VRF routing table and overlay index=IP23 is found. Since IP23 is an overlay index, a recursive route resolution for IP23 is required.
 - o IP23 is resolved to M2 in the ARP table, and M2 is resolved to the tunnel information given by the MAC-VRF (remote VTEP and VNI for the VXLAN case).
 - o The IP packet destined to IPx is encapsulated with:
 - . Source inner MAC = IRB1 MAC.
 - . Destination inner MAC = M2.
 - . Tunnel information provided by the MAC-VRF FIB (VNI, VTEP IPs and MACs for the VXLAN case).
- (5) When the packet arrives at NVE2:
 - o Based on the tunnel information (VNI for the VXLAN case), the MAC-VRF10 context is identified for a MAC lookup.
 - o Encapsulation is stripped-off and based on a MAC lookup (assuming MAC forwarding on the egress NVE), the packet is forwarded to TS2, where it will be properly routed.
- (6) When the redundancy protocol running between TS2 and TS3 appoints TS3 as the new active TS for SN1, TS3 will now own the floating IP23 and will signal this new ownership (GARP message or similar). Upon receiving the new owner's notification, NVE3 will issue a route type 2 for M3-IP23. DGW1 and DGW2 will update their ARP tables with the new MAC resolving the floating IP. No changes are carried out in the IP-VRF routing table.

5.3 ESI overlay index ("Bump in the wire") use-case

Figure 5 illustrates an example of inter-subnet forwarding for an IP Prefix route that carries a subnet SN1 and uses an ESI as an overlay index (ESI23). In this use-case, TS2 and TS3 are layer-2 VA devices

Rabadan et al.Expires March 17, 2017[Page 16]

without any IP address that can be included as an overlay index in the GW IP field of the IP Prefix route. Their MAC addresses are M2 and M3 respectively and are connected to EVI-10. Note that IRB1 and IRB2 (in DGW1 and DGW2 respectively) have IP addresses in a subnet different than SN1.



Figure 5 ESI overlay index use-case

Since neither TS2 nor TS3 can run any routing protocol and have no IP address assigned, an ESI, i.e. ESI23, will be provisioned on the attachment ports of NVE2 and NVE3. This model supports VA redundancy in a similar way as the one described in section 5.2 for the floating IP overlay index use-case, only using the EVPN Ethernet A-D route instead of the MAC advertisement route to advertise the location of the overlay index. The procedure is explained below:

- (1) NVE2 advertises the following BGP routes for TS2:
 - o Route type 1 (Ethernet A-D route for EVI-10) containing: ESI=ESI23 and the corresponding tunnel information (VNI/VSID field), as well as the BGP Encapsulation Extended Community as per [EVPN-OVERLAY].
 - o Route type 5 (IP Prefix route) containing: IPL=24, IP=SN1, ESI=ESI23, GW IP address=0. The Router's MAC Extended Community defined in [EVPN-INTERSUBNET] is added and carries the MAC address (M2) associated to the TS behind which SN1 seats.
- (2) NVE3 advertises the following BGP routes for TS3:
 - o Route type 1 (Ethernet A-D route for EVI-10) containing: ESI=ESI23 and the corresponding tunnel information (VNI/VSID

Rabadan et al.Expires March 17, 2017[Page 17]

field), as well as the BGP Encapsulation Extended Community.

- o Route type 5 (IP Prefix route) containing: IPL=24, IP=SN1, ESI=23, GW IP address=0. The Router's MAC Extended Community is added and carries the MAC address (M3) associated to the TS behind which SN1 seats.
- (3) DGW1 and DGW2 import the received routes based on the routetarget:
 - o The tunnel information to get to ESI23 is installed in DGW1 and DGW2. For the VXLAN use case, the VTEP will be derived from the Ethernet A-D route BGP next-hop and VNI from the VNI/VSID field (see [EVPN-OVERLAY]).
 - o SN1/24 is added to the IP-VRF in DGW1 and DGW2 with overlay index ESI23.
- (4) When DGW1 receives a packet from the WAN with destination IPx, where IPx belongs to SN1/24:
 - o A destination IP lookup is performed on the DGW1 IP-VRF routing table and overlay index=ESI23 is found. Since ESI23 is an overlay index, a recursive route resolution is required to find the egress NVE where ESI23 resides.
 - o The IP packet destined to IPx is encapsulated with:
 - . Source inner MAC = IRB1 MAC.
 - . Destination inner MAC = M2 (this MAC will be obtained from the Router's MAC Extended Community received along with the RT-5 for SN1).
 - . Tunnel information for the NVO tunnel is provided by the Ethernet A-D route per-EVI for ESI23 (VNI and VTEP IP for the VXLAN case).
- (5) When the packet arrives at NVE2:
 - o Based on the tunnel demultiplexer information (VNI for the VXLAN case), the MAC-VRF10 context is identified for a MAC lookup (assuming MAC disposition model) or the VNI MAY directly identify the egress interface (for a label or VNI disposition model).
 - o Encapsulation is stripped-off and based on a MAC lookup (assuming MAC forwarding on the egress NVE) or a VNI lookup

Rabadan et al.Expires March 17, 2017[Page 18]

September 13, 2016

(in case of VNI forwarding), the packet is forwarded to TS2, where it will be forwarded to SN1.

(6) If the redundancy protocol running between TS2 and TS3 follows an active/standby model and there is a failure, appointing TS3 as the new active TS for SN1, TS3 will now own the connectivity to SN1 and will signal this new ownership. Upon receiving the new owner's notification, NVE3's AC will become active and issue a route type 1 for ESI23, whereas NVE2 will withdraw its Ethernet A-D route for ESI23. DGW1 and DGW2 will update their tunnel information to resolve ESI23. The destination inner MAC will be changed to M3.

5.4 IP-VRF-to-IP-VRF model

This use-case is similar to the scenario described in "IRB forwarding on NVEs for Tenant Systems" in [EVPN-INTERSUBNET], however the new requirement here is the advertisement of IP Prefixes as opposed to only host routes.

In the examples described in sections 5.1, 5.2 and 5.3, the MAC-VRF instance can connect IRB interfaces and any other Tenant Systems connected to it. EVPN provides connectivity for:

- 1. Traffic destined to the IRB IP interfaces as well as
- 2. Traffic destined to IP subnets seating behind the TS, e.g. SN1 or SN2.

In order to provide connectivity for (1), MAC/IP routes (RT-2) are needed so that IRB MACs and IPs can be distributed. Connectivity type (2) is accomplished by the exchange of IP Prefix routes (RT-5) for IPs and subnets seating behind certain overlay indexes, e.g. GW IP or ESI.

In some cases, IP Prefix routes may be advertised for subnets and IPs seating behind an IRB. We refer to this use-case as the "IP-VRF-to-IP-VRF" model.

[EVPN-INTERSUBNET] defines an asymmetric IRB model and a symmetric IRB model, based on the required lookups at the ingress and egress NVE: the asymmetric model requires an ip-lookup and a mac-lookup at the ingress NVE, whereas only a mac-lookup is needed at the egress NVE; the symmetric model requires ip and mac lookups at both, ingress and egress NVE. From that perspective, the IP-VRF-to-IP-VRF use-case described in this section is a symmetric IRB model. Note that in an IP-VRF-to-IP-VRF scenario, a PE may not be configured with any MAC-VRF for a given tenant, in which case it will only be doing IP

Rabadan et al.Expires March 17, 2017[Page 19]

lookups and forwarding for that tenant.

Based on the way the IP-VRFs are interconnected, there are three different IP-VRF-to-IP-VRF scenarios identified and described in this document:

- 1) Interface-less model
- 2) Interface-full with core-facing IRB model

3) Interface-full with unnumbered core-facing IRB model

5.4.1 Interface-less IP-VRF-to-IP-VRF model

Figure 6 will be used for the description of this model.



Figure 6 Interface-less IP-VRF-to-IP-VRF model

In this case, the requirements are the following:

- a) The NVEs and DGWs must provide connectivity between hosts in SN1, SN2, IP1 and hosts seating at the other end of the WAN.
- b) The IP-VRF instances in the NVE/DGWs are directly connected through NVO tunnels, and no IRBs and/or MAC-VRF instances are defined at the core.

Rabadan et al.Expires March 17, 2017[Page 20]

- c) The solution must provide layer-3 connectivity among the IP-VRFs for Ethernet NVO tunnels, for instance, VXLAN or nvGRE.
- d) The solution may provide layer-3 connectivity among the IP-VRFs for IP NVO tunnels, for example, VXLAN GPE (with IP payload).

In order to meet the above requirements, the EVPN route type 5 will be used to advertise the IP Prefixes, along with the Router's MAC Extended Community as defined in [EVPN-INTERSUBNET] if the advertising NVE/DGW uses Ethernet NVO tunnels. Each NVE/DGW will advertise an RT-5 for each of its prefixes with the following fields:

o RD as per [RFC7432].

- o Eth-Tag ID=0 assuming VLAN-based service.
- o IP address length and IP address, as explained in the previous sections.
- o GW IP address= SHOULD be set to 0.
- o ESI=0
- o MPLS label or VNI corresponding to the IP-VRF.

Each RT-5 will be sent with a route-target identifying the tenant (IP-VRF) and two BGP extended communities:

- o The first one is the BGP Encapsulation Extended Community, as per [<u>RFC5512</u>], identifying the tunnel type.
- o The second one is the Router's MAC Extended Community as per [EVPN-INTERSUBNET] containing the MAC address associated to the NVE advertising the route. This MAC address identifies the NVE/DGW and MAY be re-used for all the IP-VRFs in the NVE. The Router's MAC Extended Community MUST be sent if the route is associated to an Ethernet NVO tunnel, for instance, VXLAN. If the route is associated to an IP NVO tunnel, for instance VXLAN GPE with IP payload, the Router's MAC Extended Community SHOULD NOT be sent.

The following example illustrates the procedure to advertise and forward packets to SN1/24 (ipv4 prefix advertised from NVE1) for VXLAN tunnels:

(1) NVE1 advertises the following BGP route:

o Route type 5 (IP Prefix route) containing:

Rabadan et al.Expires March 17, 2017[Page 21]

- . IPL=24, IP=SN1, VNI=10.
- . GW IP= SHOULD be set to 0.
- . [<u>RFC5512</u>] BGP Encapsulation Extended Community with Tunneltype=VXLAN.
- . Router's MAC Extended Community that contains M1.
- . Route-target identifying the tenant (IP-VRF).
- (2) DGW1 imports the received routes from NVE1:
 - o DGW1 installs SN1/24 in the IP-VRF identified by the RT-5 route-target.
 - o Since GW IP=0 and the VNI is a valid value, DGW1 will use the VNI and next-hop of the RT-5, as well as the MAC address conveyed in the Router's MAC Extended Community (as inner destination MAC address) to encapsulate the routed IP packets.
- (3) When DGW1 receives a packet from the WAN with destination IPx, where IPx belongs to SN1/24:
 - o A destination IP lookup is performed on the DGW1 IP-VRF routing table. The lookup yields SN1/24.
 - o Since the RT-5 for SN1/24 had a GW IP=0 and a valid VNI and next-hop (used as destination VTEP), DGW1 will not need a recursive lookup to resolve the route.
 - o The IP packet destined to IPx is encapsulated with: Source inner MAC = DGW1 MAC, Destination inner MAC = M1, Source outer IP (source VTEP) = DGW1 IP, Destination outer IP (destination VTEP) = NVE1 IP.
- (4) When the packet arrives at NVE1:
 - o NVE1 will identify the IP-VRF for an IP-lookup based on the VNI.
 - o An IP lookup is performed in the routing context, where SN1 turns out to be a local subnet associated to MAC-VRF2. A subsequent lookup in the ARP table and the MAC-VRF FIB will provide the forwarding information for the packet in MAC-VRF2.

The implementation of this Interface-less model is REQUIRED.

Rabadan et al.Expires March 17, 2017[Page 22]

5.4.2 Interface-full IP-VRF-to-IP-VRF with core-facing IRB

Figure 7 will be used for the description of this model.



Figure 7 Interface-full with core-facing IRB model

In this model, the requirements are the following:

- a) As in <u>section 5.4.1</u>, the NVEs and DGWs must provide connectivity between hosts in SN1, SN2, IP1 and hosts seating at the other end of the WAN.
- b) However, the NVE/DGWs are now connected through Ethernet NVO tunnels terminated in core-MAC-VRF instances. The IP-VRFs use IRB interfaces for their connectivity to the core MAC-VRFs.
- c) Each core-facing IRB has an IP and a MAC address, where the IP address must be reachable from other NVEs or DGWs.
- d) The core EVI is composed of the NVE/DGW MAC-VRFs and may contain other MAC-VRFs without IRB interfaces. Those non-IRB MAC-VRFs will typically connect TSes that need layer-3 connectivity to remote subnets.
- e) The solution must provide layer-3 connectivity for Ethernet NVO tunnels, for instance, VXLAN or nvGRE.

EVPN type 5 routes will be used to advertise the IP Prefixes, whereas

Rabadan et al.Expires March 17, 2017[Page 23]

EVPN RT-2 routes will advertise the MAC/IP addresses of each corefacing IRB interface. Each NVE/DGW will advertise an RT-5 for each of its prefixes with the following fields:

- o RD as per [RFC7432].
- o Eth-Tag ID=0 assuming VLAN-based service.
- o IP address length and IP address, as explained in the previous sections.
- o GW IP address=IRB-IP (this is the overlay index that will be used for the recursive route resolution).

o ESI=0

o MPLS label or VNI corresponding to the IP-VRF. Note that the value SHOULD be zero since the RT-5 route requires a recursive lookup resolution to an RT-2 route. The MPLS label or VNI to be used when forwarding packets will be derived from the RT-2's MPLS Label1 field.

Each RT-5 will be sent with a route-target identifying the tenant (IP-VRF). The Router's MAC Extended Community SHOULD NOT be sent in this case.

The following example illustrates the procedure to advertise and forward packets to SN1/24 (ipv4 prefix advertised from NVE1) for VXLAN tunnels:

- (1) NVE1 advertises the following BGP routes:
 - o Route type 5 (IP Prefix route) containing:
 - . IPL=24, IP=SN1, VNI= SHOULD be set to 0.
 - . GW IP=IP1 (core-facing IRB's IP)
 - . Route-target identifying the tenant (IP-VRF).
 - o Route type 2 (MAC/IP route for the core-facing IRB) containing:
 - . ML=48, M=M1, IPL=32, IP=IP1, VNI=10.
 - . A [RFC5512] BGP Encapsulation Extended Community with Tunnel-type= VXLAN.

Rabadan et al.Expires March 17, 2017[Page 24]

- . Route-target identifying the tenant. This route-target MAY be the same as the one used with the RT-5.
- (2) DGW1 imports the received routes from NVE1:
 - o DGW1 installs SN1/24 in the IP-VRF identified by the RT-5 route-target.
 - . Since GW IP is different from zero, the GW IP (IP1) will be used as the overlay index for the recursive route resolution to the RT-2 carrying IP1.
- (3) When DGW1 receives a packet from the WAN with destination IPx, where IPx belongs to SN1/24:
 - o A destination IP lookup is performed on the DGW1 IP-VRF routing table. The lookup yields SN1/24, which is associated to the overlay index IP1. The forwarding information is derived from the RT-2 received for IP1.
 - o The IP packet destined to IPx is encapsulated with: Source inner MAC = M3, Destination inner MAC = M1, Source outer IP (source VTEP) = DGW1 IP, Destination outer IP (destination VTEP) = NVE1 IP.

(4) When the packet arrives at NVE1:

- o NVE1 will identify the IP-VRF for an IP-lookup based on the VNI and the inner MAC DA.
- o An IP lookup is performed in the routing context, where SN1 turns out to be a local subnet associated to MAC-VRF2. A subsequent lookup in the ARP table and the MAC-VRF FIB will provide the forwarding information for the packet in MAC-VRF2.

The implementation of the Interface-full with core-facing IRB model is REQUIRED.

5.4.3 Interface-full IP-VRF-to-IP-VRF with unnumbered core-facing IRB

Figure 8 will be used for the description of this model. Note that this model is similar to the one described in <u>section 5.4.2</u>, only without IP addresses on the core-facing IRB interfaces.

Rabadan et al.Expires March 17, 2017[Page 25]



Figure 8 Interface-full with unnumbered core-facing IRB model

- In this model, the requirements are the following:
- a) As in <u>section 5.4.1</u> and 5.4.2, the NVEs and DGWs must provide connectivity between hosts in SN1, SN2, IP1 and hosts seating at the other end of the WAN.
- b) As in section 5.4.2, the NVE/DGWs are connected through Ethernet NVO tunnels terminated in core-MAC-VRF instances. The IP-VRFs use IRB interfaces for their connectivity to the core MAC-VRFs.
- c) However, each core-facing IRB has a MAC address only, and no IP address (that is why the model refers to an 'unnumbered' corefacing IRB). In this model, there is no need to have IP reachability to the core-facing IRB interfaces themselves and there is a requirement to save IP addresses on those interfaces.
- d) As in section 5.4.2, the core EVI is composed of the NVE/DGW MAC-VRFs and may contain other MAC-VRFs.
- e) As in section 5.4.2, the solution must provide layer-3 connectivity for Ethernet NVO tunnels, for instance, VXLAN or nvGRE.

This model will also make use of the RT-5 recursive resolution. EVPN type 5 routes will advertise the IP Prefixes along with the Router's MAC Extended Community used for the recursive lookup, whereas EVPN RT-2 routes will advertise the MAC addresses of each core-facing IRB

Rabadan et al.Expires March 17, 2017[Page 26]

interface (this time without an IP). Each NVE/DGW will advertise an RT-5 for each of its prefixes with the following fields:

- o RD as per [RFC7432].
- o Eth-Tag ID=0 assuming VLAN-based service.
- o IP address length and IP address, as explained in the previous sections.
- o GW IP address= SHOULD be set to 0.
- o ESI=0
- o MPLS label or VNI corresponding to the IP-VRF. Note that the value SHOULD be zero since the RT-5 route requires a recursive lookup resolution to an RT-2 route. The MPLS label or VNI to be used when forwarding packets will be derived from the RT-2's MPLS Label1 field.

Each RT-5 will be sent with a route-target identifying the tenant (IP-VRF) and the Router's MAC Extended Community containing the MAC address associated to core-facing IRB interface. This MAC address MAY be re-used for all the IP-VRFs in the NVE.

The following example illustrates the procedure to advertise and forward packets to SN1/24 (ipv4 prefix advertised from NVE1) for VXLAN tunnels:

- (1) NVE1 advertises the following BGP routes:
 - o Route type 5 (IP Prefix route) containing:
 - . IPL=24, IP=SN1, VNI= SHOULD be set to 0.
 - . GW IP= SHOULD be set to 0.
 - . Router's MAC Extended Community containing M1 (this will be used for the recursive lookup to a RT-2).
 - . Route-target identifying the tenant (IP-VRF).
 - o Route type 2 (MAC route for the core-facing IRB) containing:
 - . ML=48, M=M1, IPL=0, VNI=10.
 - . A [<u>RFC5512</u>] BGP Encapsulation Extended Community with Tunnel-type=VXLAN.

- . Route-target identifying the tenant. This route-target MAY be the same as the one used with the RT-5.
- (2) DGW1 imports the received routes from NVE1:
 - o DGW1 installs SN1/24 in the IP-VRF identified by the RT-5 route-target.
 - . The MAC contained in the Router's MAC Extended Community sent along with the RT-5 (M1) will be used as the overlay index for the recursive route resolution to the RT-2 carrying M1.
- (3) When DGW1 receives a packet from the WAN with destination IPx, where IPx belongs to SN1/24:
 - o A destination IP lookup is performed on the DGW1 IP-VRF routing table. The lookup yields SN1/24, which is associated to the overlay index M1. The forwarding information is derived from the RT-2 received for M1.
 - o The IP packet destined to IPx is encapsulated with: Source inner MAC = M3, Destination inner MAC = M1, Source outer IP (source VTEP) = DGW1 IP, Destination outer IP (destination VTEP) = NVE1 IP.
- (4) When the packet arrives at NVE1:
 - o NVE1 will identify the IP-VRF for an IP-lookup based on the VNI and the inner MAC DA.
 - o An IP lookup is performed in the routing context, where SN1 turns out to be a local subnet associated to MAC-VRF2. A subsequent lookup in the ARP table and the MAC-VRF FIB will provide the forwarding information for the packet in MAC-VRF2.

The implementation of the Interface-full with unnumbered core-facing IRB model is OPTIONAL.

6. Conclusions

An EVPN route (type 5) for the advertisement of IP Prefixes is described in this document. This new route type has a differentiated role from the RT-2 route and addresses all the Data Center (or NVObased networks in general) inter-subnet connectivity scenarios in which an IP Prefix advertisement is required. Using this new RT-5, an IP Prefix may be advertised along with an overlay index that can be a

Rabadan et al.Expires March 17, 2017[Page 28]

Internet-Draft

GW IP address, a MAC or an ESI, or without an overlay index, in which case the BGP next-hop will point at the egress NVE and the MAC in the Router's MAC Extended Community will provide the inner MAC destination address to be used. As discussed throughout the document, the EVPN RT-2 does not meet the requirements for all the DC use cases, therefore this EVPN route type 5 is required.

The EVPN route type 5 decouples the IP Prefix advertisements from the MAC/IP route advertisements in EVPN, hence:

- a) Allows the clean and clear advertisements of ipv4 or ipv6 prefixes in an NLRI with no MAC addresses in the route key, so that only IP information is used in BGP route comparisons.
- b) Since the route type is different from the MAC/IP Advertisement route, the advertisement of prefixes will be excluded from all the procedures defined for the advertisement of VM MACs, e.g. MAC Mobility or aliasing. As a result of that, the current [<u>RFC7432</u>] procedures do not need to be modified.
- c) Allows a flexible implementation where the prefix can be linked to different types of overlay indexes: overlay IP address, overlay MAC addresses, overlay ESI, underlay IP next-hops, etc.
- d) An EVPN implementation not requiring IP Prefixes can simply discard them by looking at the route type value. An unknown route type MUST be ignored by the receiving NVE/PE.

7. Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC-2119 [RFC2119].

<u>8</u>. Security Considerations

The security considerations discussed in [<u>RFC7432</u>] apply to this document.

9. IANA Considerations

This document requests the allocation of value 5 in the "EVPN Route Types" registry defined by [RFC7432] and modification of the registry as follows:

ValueDescriptionReference5IP Prefix route[this document]]

Rabadan et al.Expires March 17, 2017[Page 29]

6-255 Unassigned

10. References

10.1 Normative References

[<u>RFC4364</u>]Rosen, E. and Y. Rekhter, "BGP/MPLS IP Virtual Private Networks (VPNs)", <u>RFC 4364</u>, DOI 10.17487/RFC4364, February 2006, <<u>http://www.rfc-editor.org/info/rfc4364</u>>.

[RFC7432]Sajassi, A., Ed., Aggarwal, R., Bitar, N., Isaac, A., Uttaro, J., Drake, J., and W. Henderickx, "BGP MPLS-Based Ethernet VPN", <u>RFC 7432</u>, DOI 10.17487/RFC7432, February 2015, <<u>http://www.rfc-</u> editor.org/info/rfc7432>.

<u>**10.2</u>** Informative References</u>

[EVPN-OVERLAY] Sajassi-Drake et al., "A Network Virtualization Overlay Solution using EVPN", <u>draft-ietf-bess-evpn-overlay-04.txt</u>, work in progress, June, 2016

[EVPN-INTERSUBNET] Sajassi et al., "IP Inter-Subnet Forwarding in EVPN", <u>draft-ietf-bess-evpn-inter-subnet-forwarding-01.txt</u>, work in progress, October, 2015

<u>11</u>. Acknowledgments

The authors would like to thank Mukul Katiyar for their valuable feedback and contributions. The following people also helped improving this document with their feedback: Tony Przygienda and Thomas Morin.

12. Contributors

In addition to the authors listed on the front page, the following co-authors have also contributed to this document:

Senthil Sathappan Florin Balus

<u>13</u>. Authors' Addresses

Jorge Rabadan (Editor) Nokia 777 E. Middlefield Road

Rabadan et al. Expires March 17, 2017 [Page 30]

Mountain View, CA 94043 USA Email: jorge.rabadan@nokia.com

Wim Henderickx Nokia Email: wim.henderickx@nokia.com

Aldrin Isaac Juniper Email: aisaac@juniper.net

Senad Palislamovic Nokia Email: senad.palislamovic@nokia.com

John E. Drake Juniper Email: jdrake@juniper.net

Ali Sajassi Cisco Email: sajassi@cisco.com

Wen Lin Juniper Email: wlin@juniper.net

Rabadan et al. Expires March 17, 2017 [Page 31]