

**BGP/MPLS Layer 3 VPN Multicast Management Information Base
draft-ietf-bess-mvpn-mib-10**

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects to configure and/or monitor Multicast communication over IP Virtual Private Networks (VPNs) supported by MultiProtocol Label Switching/Border Gateway Protocol (MPLS/BGP) on a Provider Edge router.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 12, 2019.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4](#).e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Terminology	2
2.	The Internet-Standard Management Framework	3
3.	MCAST-VPN-MIB	4
3.1.	Summary of MIB Module	4
3.2.	MIB Module Definitions	5
4.	Security Considerations	50
5.	IANA Considerations	53
6.	Acknowledgement	53
7.	References	53
7.1.	Normative References	54
7.2.	Informative References	56
	Author's Address	56

[1.](#) Introduction

[[RFC6513](#)], [[RFC6514](#)], and [[RFC6625](#)] specify procedures for supporting multicast in Border Gateway Protocol/MultiProtocol Label Switching (BGP/MPLS) Layer 3 (IP) Virtual Private Networks (VPNs). Throughout this document, we will use the term "Multicast VPN" (MVPN) [[RFC6513](#)] to refer to a BGP/MPLS IP VPN that supports multicast.

Provider Edge routers (PEs) attaching to a particular MVPN exchange customer multicast (C-multicast) routing information with neighboring PEs. In [[RFC6513](#)], two basic methods for exchanging C-multicast routing information are defined (1) Protocol Independent Multicast (PIM) [[RFC7761](#)] and (2) BGP.

In the rest of this document we will use the term "PIM-MVPN" to refer to the case where PIM is used for exchanging C-multicast routing information, and "BGP-MVPN" to refer to the case where BGP is used for exchanging C-multicast routing information.

This document describes managed objects to configure and/or monitor MVPNs. Most of the managed objects are common to both PIM-MVPN and BGP-MVPN, and some managed objects are BGP-MVPN specific.

[1.1.](#) Terminology

This document adopts the definitions, acronyms and mechanisms described in [[RFC4364](#)], [[RFC6513](#)], and [[RFC6514](#)]. Familiarity with Multicast, MPLS, Layer 3 (L3) VPN, MVPN concepts and/or mechanisms is

assumed. Some terms specifically related to this document are explained below.

An MVPN can be realized by using various kinds of transport mechanisms for forwarding a packet to all or a subset of PEs across service provider networks. Such transport mechanisms are referred to as provider tunnels (P-tunnels).

A "Provider Multicast Service Interface" (PMSI) [[RFC6513](#)] is a conceptual interface instantiated by a P-tunnel. A PE uses a PMSI to send customer multicast traffic to all or some PEs in the same VPN.

There are two kinds of PMSI: "Inclusive PMSI" (I-PMSI) and "Selective PMSI" (S-PMSI) [[RFC6513](#)]. An I-PMSI enables a PE attached to a particular MVPN to transmit a message to all PEs in the same MVPN. An S-PMSI enables a PE to transmit a message to a selected set of PEs in the same MVPN.

As described in [[RFC4382](#)], each PE maintains one default forwarding table and zero or more "Virtual Routing and Forwarding tables" (VRFs). Throughout this document, we will use the term "multicast VRF" (MVRF) to refer to a VRF that contains multicast routing information.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

3. MCAST-VPN-MIB

This document defines MCAST-VPN-MIB, a MIB module for monitoring and/or configuring MVPNs on PEs. This MIB module will be used in conjunction with MPLS-L3VPN-STD-MIB [[RFC4382](#)] and IPMCAST-MIB [[RFC5132](#)].

3.1. Summary of MIB Module

MCAST-VPN-MIB provides the following functionalities.

- o Monitoring attributes of MVPNs on a PE
- o Configuring timers and thresholds related to an MVPN on a PE
- o Notifying creation, deletion, and modification of MVRFs on a PE
- o Monitoring PMSI attributes
- o Monitoring statistics of advertisements exchanged by a PE
- o Monitoring routing information for multicast destinations
- o Monitoring next-hops for each multicast destination

To provide these functionalities, MCAST-VPN-MIB defines following tables.

- o mvpnGenericTable

This table contains generic information about MVPNs on a PE. Each entry in this table represents an instance of an MVPN on a PE and contains generic information related to the MVPN. For each entry in this table there MUST be a corresponding VRF in MPLS-L3VPN-STD-MIB [[RFC4382](#)].

- o mvpnBgpTable

This table contains information specific to BGP-MVPNs. Each BGP-MVPN on a PE will have an entry in this table.

- o mvpnPmsiTable

This table contains managed objects representing attribute information that is common to I-PMSIs and S-PMSIs on a PE.

- o mvpnSpmsiTable

This table contains managed objects representing attribute information specific to S-PMSIs. An S-PMSI represented in this table will have a corresponding entry in `mvpnPmsiTable`.

- o `mvpnAdvtStatsTable`

This table contains statistics pertaining to I-PMSI and S-PMSI advertisements sent/received.

- o `mvpnMrouteTable`

This table contains multicast routing information in MVRFs on a PE.

- o `mvpnMrouteNextHopTable`

This table contains information on the next-hops for routing IP multicast datagrams in MVPNs on a PE.

3.2. MIB Module Definitions

```
MCAST-VPN-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,  
    Counter32, Counter64, Gauge32, Unsigned32, TimeTicks,  
    mib-2
```

```
    FROM SNMPv2-SMI -- [RFC2578]
```

```
    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP  
    FROM SNMPv2-CONF -- [RFC2580]
```

```
    RowPointer, TimeStamp, DateAndTime  
    FROM SNMPv2-TC -- [RFC2579]
```

```
    InterfaceIndex, InterfaceIndexOrZero  
    FROM IF-MIB -- [RFC2863]
```

```
    InetAddress, InetAddressType, InetAddressPrefixLength  
    FROM INET-ADDRESS-MIB -- [RFC4001]
```

```
    mplsL3VpnVrfName, MplsL3VpnRouteDistinguisher  
    FROM MPLS-L3VPN-STD-MIB -- [RFC4382]
```

```
    IANAipRouteProtocol, IANAipMRouteProtocol  
    FROM IANA-RTPROTO-MIB -- [RTPROTO]
```

```
    L2L3VpnMcastProviderTunnelType
```



```
FROM L2L3-VPN-MCAST-TC-MIB;          -- [RFCXXXX]

-- RFC Ed.: replace XXXX with actual RFC number and remove this note

mvpnMIB MODULE-IDENTITY
  LAST-UPDATED "201808101200Z"  -- 10th August 2018 12:00:00 GMT
  ORGANIZATION "IETF BESS Working Group."
  CONTACT-INFO
    "
      Hiroshi Tsunoda
      Tohoku Institute of Technology
      35-1, Yagiyama Kasumi-cho
      Taihaku-ku, Sendai, 982-8577
      Japan
      Email: tsuno@m.ieice.org

      Comments and discussion to bess@ietf.org"

  DESCRIPTION
    "This MIB module contains managed object definitions to
    configure and/or monitor Multicast communication over IP
    Virtual Private Networks (VPNs) supported by MultiProtocol
    Label Switching/Border Gateway Protocol (MPLS/BGP) on a
    Provider Edge router (PE).
    Copyright (C) The Internet Society (2018).
    "

-- Revision history.

REVISION "201808101200Z"  -- 10th August, 2018
DESCRIPTION
  "Initial version, published as RFC YYYY."

-- RFC Ed. replace YYYY with the actual RFC number and
-- remove this note

 ::= { mib-2 AAAA }

-- IANA Reg.: Please assign a value for "AAAA" under the
-- 'mib-2' subtree and record the assignment in the SMI
-- Numbers registry.

-- RFC Ed.: When the above assignment has been made, please
-- remove the above note
-- replace "AAAA" here with the assigned value and
-- remove this note.

-- Top level components of this MIB module.
```



```
mvpnNotifications OBJECT IDENTIFIER ::= { mvpnMIB 0 }

-- scalars, tables
mvpnObjects          OBJECT IDENTIFIER ::= { mvpnMIB 1 }

-- conformance information
mvpnConformance     OBJECT IDENTIFIER ::= { mvpnMIB 2 }

-- mvpn Objects
mvpnScalars          OBJECT IDENTIFIER ::= { mvpnObjects 1 }

-- Scalar Objects

mvpnMvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS           current
    DESCRIPTION
        "The total number of Multicast Virtual Routing and
        Forwarding tables (MVRFs) that are present on
        this Provider Edge router (PE). This includes MVRFs
        for IPv4, IPv6, and mLDP C-Multicast.
        "
    ::= { mvpnScalars 1 }

mvpnV4Mvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS           current
    DESCRIPTION
        "The number of MVRFs for IPv4 C-Multicast on this PE.
        "
    ::= { mvpnScalars 2 }

mvpnV6Mvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS           current
    DESCRIPTION
        "The number of MVRFs for IPv6 C-Multicast on this PE.
        "
    ::= { mvpnScalars 3 }

mvpnMldpMvrfs OBJECT-TYPE
    SYNTAX          Gauge32
    MAX-ACCESS      read-only
    STATUS           current
    DESCRIPTION
```



```
    "The number of MVRFs on this PE that use BGP for
      exchanging Multipoint Label Distribution Protocol (mLDP)
      C-Multicast routing information.
    "
    ::= { mvpnScalars 4 }

mvpnPimV4Mvrfs OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The number of MVRFs on this PE that use Provider
          Independent Multicast (PIM) for exchanging IPv4
          C-Multicast routing information.
        "
    ::= { mvpnScalars 5 }

mvpnPimV6Mvrfs OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The number of MVRFs on this PE that use PIM for
          exchanging IPv6 C-Multicast routing information.
        "
    ::= { mvpnScalars 6 }

mvpnBgpV4Mvrfs OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The number of MVRFs on this PE that use BGP for
          exchanging IPv4 C-Multicast routing information.
        "
    ::= { mvpnScalars 7 }

mvpnBgpV6Mvrfs OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The number of MVRFs on this PE that use BGP for
          exchanging IPv6 C-Multicast routing information.
        "
    ::= { mvpnScalars 8 }

mvpnSPTunnelLimit OBJECT-TYPE
```


SYNTAX Unsigned32 (1..4294967295)
MAX-ACCESS read-write
STATUS current
DESCRIPTION
 "The maximum number of selective provider tunnels that
 this PE allows for a particular MVPN on this PE."
"

REFERENCE
 "[RFC6513, Section 13](#)"
::= { mvpnScalars 9 }

mvpnBgpCmcastRouteWithdrawalTimer OBJECT-TYPE

SYNTAX Unsigned32
UNITS "milliseconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
 "A configurable timer to control the delay
 of C-multicast route withdrawal advertisements."
"

REFERENCE
 "[RFC6514, Section 16.1.1](#)"
::= { mvpnScalars 10 }

mvpnBgpSrcSharedTreeJoinTimer OBJECT-TYPE

SYNTAX Unsigned32
UNITS "milliseconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
 "A configurable timer to control the delay
 of Source/Shared Tree Join C-multicast route
 advertisements."
"

REFERENCE
 "[RFC6514, Section 16.1.2](#)"
::= { mvpnScalars 11 }

-- Generic MVRP Information Table

mvpnGenericTable OBJECT-TYPE

SYNTAX SEQUENCE OF MvpnGenericEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "A conceptual table containing generic information about MVPNs
 on this PE."
"


```
::= { mvpnObjects 2 }
```

```
mvpnGenericEntry OBJECT-TYPE
```

```
SYNTAX      MvpnGenericEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"A conceptual row that represents an MVPN on this PE.
The MVPN represented by this entry will have one or more
corresponding P-Multicast Service Interfaces (PMSIs)
and a corresponding VRF in MPLS-L3VPN-STD-MIB [RFC4382].
"
```

```
INDEX {
```

```
    mplsL3VpnVrfName
```

```
}
```

```
::= { mvpnGenericTable 1 }
```

```
MvpnGenericEntry ::= SEQUENCE {
```

```
    mvpnGenMvrfLastAction      INTEGER,
```

```
    mvpnGenMvrfLastActionTime  DateAndTime,
```

```
    mvpnGenMvrfCreationTime    DateAndTime,
```

```
    mvpnGenCmcastRouteProtocol INTEGER,
```

```
    mvpnGenIpmsiInfo           RowPointer,
```

```
    mvpnGenInterAsPmsiInfo     RowPointer,
```

```
    mvpnGenUmhSelection        INTEGER,
```

```
    mvpnGenCustomerSiteType    INTEGER
```

```
}
```

```
mvpnGenMvrfLastAction OBJECT-TYPE
```

```
SYNTAX      INTEGER {
```

```
    createdMvrf          (1),
```

```
    deletedMvrf          (2),
```

```
    modifiedMvrfIpmsiConfig (3),
```

```
    modifiedMvrfSpmsiConfig (4)
```

```
}
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"This object describes the last action pertaining
to the MVPN represented by this entry.
```

```
The enumerated action types and the corresponding
descriptions are as follows:
```

```
    createdMvrf:
```

```
        MVRP was created for this MVPN on the PE.
```

```
    deletedMvrf:
```


MVRF for this MVPN was deleted from the PE.
 A conceptual row in this table will never have
 mvpnGenMvrfLastAction equal to deletedMvrf,
 because in that case the row itself will not exist
 in the table.
 This value for mvpnGenMvrfLastAction is defined
 solely for use in mvpnMvrfActionChange notification.

modifiedMvrfIpmsiConfig:
 an I-PMSI for this MVPN was configured, deleted or
 changed.

modifiedMvrfSpmsiConfig:
 an S-PMSI for this MVPN was configured, deleted or
 changed.

"

::= { mvpnGenericEntry 2 }

mvpnGenMvrfLastActionTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The timestamp when the last action, given in
 the corresponding mvpnGenMvrfLastAction object,
 was carried out.

"

::= { mvpnGenericEntry 3 }

mvpnGenMvrfCreationTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The timestamp when the MVRF was created for
 the MVPN represented by this entry.

"

::= { mvpnGenericEntry 4 }

mvpnGenCmcastRouteProtocol OBJECT-TYPE

SYNTAX INTEGER {
 pim (1),
 bgp (2)
 }

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The protocol used to signal C-multicast routing

information across the provider core for the MVPN represented by this entry.

The enumerated protocols and the corresponding descriptions are as follows:

pim : PIM (PIM-MVPN)
bgp : BGP (BGP-MVPN)

"

REFERENCE

["RFC6513, Section 5"](#)

::= { mvpnGenericEntry 5 }

mvpnGenIpmsiInfo OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A pointer to a conceptual row representing the corresponding I-PMSI in mvpnPmsiTable. If there is no I-PMSI for the MVPN represented by this entry, the value of this object will be zeroDotZero.

"

::= { mvpnGenericEntry 6 }

mvpnGenInterAsPmsiInfo OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A pointer to a conceptual row representing the corresponding segmented Inter-AS I-PMSI in mvpnPmsiTable. If there is no segmented Inter-AS I-PMSI for the MVPN, the value of this object will be zeroDotZero.

"

::= { mvpnGenericEntry 7 }

mvpnGenUmhSelection OBJECT-TYPE

SYNTAX INTEGER {
highestPeAddress (1),
cRootGroupHashing (2),
ucastUmhRoute (3)
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The Upstream Multicast Hop (UMH) selection method for the MVPN

represented by this entry.

The enumerated methods and the corresponding descriptions are as follows:

```

    highestPeAddress  : PE with the highest address
                        (see RFC6513, Section 5.1.3)
    cRootGroupHashing : hashing based on (c-root, c-group)
    ucastUmhRoute     : per unicast route towards c-root

```

"

REFERENCE

["RFC6513, Section 5.1"](#)

::= { mvpnGenericEntry 8 }

mvpnGenCustomerSiteType OBJECT-TYPE

```

SYNTAX      INTEGER {
                                senderReceiver (1),
                                receiverOnly   (2),
                                senderOnly     (3)
                            }

```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The type of the customer site, connected to the MVPN represented by this entry.

The enumerated types and the corresponding descriptions are as follows:

```

    senderReceiver : Site is both sender and receiver
    receiverOnly   : Site is receiver-only
    senderOnly     : Site is sender-only

```

"

REFERENCE

["RFC6513, Section 2.3"](#)

::= { mvpnGenericEntry 9 }

-- Generic BGP-MVPN table

mvpnBgpTable OBJECT-TYPE

SYNTAX SEQUENCE OF MvpnBgpEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A conceptual table that supplements mvpnGenericTable with BGP-MVPN specific information for BGP-MVPNs on this PE.

"

::= { mvpnObjects 3 }

mvpnBgpEntry OBJECT-TYPE

SYNTAX MvpnBgpEntry
 MAX-ACCESS not-accessible
 STATUS current

DESCRIPTION

"A conceptual row corresponding to a BGP-MVPN on this PE."
 "

INDEX {
 mplsL3VpnVrfName
 }

::= { mvpnBgpTable 1 }

MvpnBgpEntry ::= SEQUENCE {

 mvpnBgpMode INTEGER,
 mvpnBgpVrfRouteImportExtendedCommunity MplsL3VpnRouteDistinguisher,
 mvpnBgpSrcASEExtendedCommunity Unsigned32,
 mvpnBgpMsgRateLimit Unsigned32,
 mvpnBgpMaxSpmsiAdRoutes Unsigned32,
 mvpnBgpMaxSpmsiAdRouteFreq Unsigned32,
 mvpnBgpMaxSrcActiveAdRoutes Unsigned32,
 mvpnBgpMaxSrcActiveAdRouteFreq Unsigned32

}

mvpnBgpMode OBJECT-TYPE

SYNTAX INTEGER {
 other (0),
 rptSpt (1),
 sptOnly (2)
 }

MAX-ACCESS read-only
 STATUS current

DESCRIPTION

"The inter-site C-tree mode used by the BGP-MVPN represented by this entry.

 other : none of the following
 rptSpt : inter-site shared tree mode
 (Rendezvous Point Tree (RPT) and
 source-specific shortest-path tree (SPT))
 sptOnly : inter-site source-only tree mode

"

REFERENCE

"[RFC6513, Section 9.3.1](#)"

::= { mvpnBgpEntry 1 }

mvpnBgpVrfRouteImportExtendedCommunity OBJECT-TYPE

SYNTAX MplsL3VpnRouteDistinguisher
 MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The VRF Route Import Extended Community added by this PE to unicast VPN routes that it advertises for the BGP-MVPN corresponding to this entry.
"

REFERENCE

"[RFC6514, Section 7](#)
"

::= { mvpnBgpEntry 2 }

mvpnBgpSrcASExtendedCommunity OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The Source AS Extended Community added by this PE to the unicast VPN routes that it advertises for the BGP-MVPN represented by this entry.
"

REFERENCE

"[RFC6514, Section 6](#)
"

::= { mvpnBgpEntry 3 }

mvpnBgpMsgRateLimit OBJECT-TYPE

SYNTAX Unsigned32 (0..4294967295)

UNITS "messages per second"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The configurable upper bound for the rate of BGP C-multicast routing information message exchange between this PE and other PEs in the BGP-MVPN corresponding to this entry.
"

REFERENCE

"[RFC6514, Section 17](#)"

::= { mvpnBgpEntry 4 }

mvpnBgpMaxSpmsiAdRoutes OBJECT-TYPE

SYNTAX Unsigned32 (0..4294967295)

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The configurable upper bound for the number of S-PMSI A-D routes for the BGP-MVPN corresponding to this entry.
"

REFERENCE

["RFC6514, Section 17"](#)

::= { mvpnBgpEntry 5 }

mvpnBgpMaxSpmsiAdRouteFreq OBJECT-TYPE

SYNTAX Unsigned32 (0..4294967295)

UNITS "routes per second"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The configurable upper bound for the frequency of
S-PMSI A-D route generation for the BGP-MVPN corresponding
to this entry.

"

REFERENCE

["RFC6514, Section 17"](#)

::= { mvpnBgpEntry 6 }

mvpnBgpMaxSrcActiveAdRoutes OBJECT-TYPE

SYNTAX Unsigned32 (0..4294967295)

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The configurable upper bound for the number of
Source Active A-D routes for the BGP-MVPN corresponding
to this entry.

"

REFERENCE

["RFC6514, Section 17"](#)

::= { mvpnBgpEntry 7 }

mvpnBgpMaxSrcActiveAdRouteFreq OBJECT-TYPE

SYNTAX Unsigned32 (0..4294967295)

UNITS "routes per second"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The configurable upper bound for the frequency of Source
Active A-D route generation for the BGP-MVPN corresponding
to this entry.

"

REFERENCE

["RFC6514, Section 17"](#)

::= { mvpnBgpEntry 8 }

-- Table of PMSI information

mvpnPmsiTable OBJECT-TYPE

SYNTAX SEQUENCE OF MvpnPmsiEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "A conceptual table containing information related
 to PMSIs on this PE."
::= { mvpnObjects 4 }

mvpnPmsiEntry OBJECT-TYPE

SYNTAX MvpnPmsiEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "A conceptual row corresponding to a
 PMSI on this PE."
INDEX {
 mvpnPmsiTunnelIfIndex
 }
::= { mvpnPmsiTable 1 }

MvpnPmsiEntry ::= SEQUENCE {
 mvpnPmsiTunnelIfIndex InterfaceIndex,
 mvpnPmsiRD MplsL3VpnRouteDistinguisher,
 mvpnPmsiTunnelType L2L3VpnMcastProviderTunnelType,
 mvpnPmsiTunnelAttribute RowPointer,
 mvpnPmsiTunnelPimGroupAddrType InetAddressType,
 mvpnPmsiTunnelPimGroupAddr InetAddress,
 mvpnPmsiEncapsulationType INTEGER
}

mvpnPmsiTunnelIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
 "A unique value for this conceptual row. Its value
 will be the same as that of the ifIndex object instance
 for the corresponding PMSI in ifTable."
REFERENCE
 "[RFC2863](#) Sec. 3.1.5"
::= { mvpnPmsiEntry 1 }

mvpnPmsiRD OBJECT-TYPE

SYNTAX MplsL3VpnRouteDistinguisher

MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The Route Distinguisher for this I-PMSI."
 ::= { mvpnPmsiEntry 3 }

mvpnPmsiTunnelType OBJECT-TYPE

SYNTAX L2L3VpnMcastProviderTunnelType
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The type of tunnel used to
 instantiate the PMSI corresponding to this entry."
REFERENCE
 "[RFC6513](#), Sec. 2.6"
 ::= { mvpnPmsiEntry 4 }

mvpnPmsiTunnelAttribute OBJECT-TYPE

SYNTAX RowPointer
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "A pointer to a conceptual row representing
 the P-tunnel used by the PMSI in
 l2L3VpnMcastPmsiTunnelAttributeTable."
 ::= { mvpnPmsiEntry 5 }

mvpnPmsiTunnelPimGroupAddrType OBJECT-TYPE

SYNTAX InetAddressType
MAX-ACCESS read-only
STATUS current
DESCRIPTION
 "The InetAddressType of the mvpnPmsiTunnelPimGroupAddr object
 that follows.
 When the PMSI corresponding to this entry does not use
 the PIM provider tunnel, i.e.,
 the value of mvpnPmsiTunnelType is not one of
 pimSsm(3), pimAsm(4), or pimBidir(5),
 this object should be unknown(0)."
 ::= { mvpnPmsiEntry 6 }

mvpnPmsiTunnelPimGroupAddr OBJECT-TYPE

SYNTAX InetAddress
MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The tunnel address which is used by the PMSI corresponding to this entry.
When the PMSI corresponding to this entry does not use PIM provider tunnel, i.e., the value of mvpnPmsiTunnelType is not one of pimSsm(3), pimAsm(4), or pimBidir(5), this object should be a zero-length octet string.
"

::= { mvpnPmsiEntry 7 }

mvpnPmsiEncapsulationType OBJECT-TYPE

SYNTAX INTEGER {
greIp (1),
ipIp (2),
mpls (3)
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The encapsulation type used for sending packets through the PMSI corresponding to this entry.

The enumerated encapsulation types and the corresponding descriptions are as follows:

greIp : GRE (Generic Routing Encapsulation)
encapsulation [[RFC2784](#)]
ipIp : IP-in-IP encapsulation [[RFC2003](#)]
mpls : MPLS encapsulation [[RFC3032](#)]

"

REFERENCE

"[RFC2003](#)
[RFC2784](#)
[RFC3032](#)
[RFC6513](#), Sec. 12.1
"

"

::= { mvpnPmsiEntry 8 }

-- Table of S-PMSI specific information

mvpnSpmsiTable OBJECT-TYPE

SYNTAX SEQUENCE OF MvpnSpmsiEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A conceptual table containing information related


```

    to S-PMSIs on this PE.
    This table stores only S-PMSI specific attribute
    information. Generic PMSI attribute information of
    S-PMSIs is stored in mvpnPmsiTable.
    "
 ::= { mvpnObjects 5 }

mvpnSpmsiEntry OBJECT-TYPE
    SYNTAX      MvpnSpmsiEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "A conceptual row corresponding to an S-PMSI on this PE.
        Implementers need to be aware that if the total number of
        octets in mplsL3VpnVrfName, mvpnSpmsiCmcastGroupAddr and
        mvpnSpmsiCmcastSourceAddr exceeds 113, the OIDs of column
        instances in this row will have more than 128 sub-identifiers
        and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3.
        "
    INDEX      {
        mplsL3VpnVrfName,
        mvpnSpmsiCmcastGroupAddrType,
        mvpnSpmsiCmcastGroupAddr,
        mvpnSpmsiCmcastGroupPrefixLen,
        mvpnSpmsiCmcastSourceAddrType,
        mvpnSpmsiCmcastSourceAddr,
        mvpnSpmsiCmcastSourcePrefixLen
    }
 ::= { mvpnSpmsiTable 1 }

MvpnSpmsiEntry ::= SEQUENCE {
    mvpnSpmsiCmcastGroupAddrType  InetAddressType,
    mvpnSpmsiCmcastGroupAddr      InetAddress,
    mvpnSpmsiCmcastGroupPrefixLen  InetAddressPrefixLength,
    mvpnSpmsiCmcastSourceAddrType  InetAddressType,
    mvpnSpmsiCmcastSourceAddr      InetAddress,
    mvpnSpmsiCmcastSourcePrefixLen  InetAddressPrefixLength,
    mvpnSpmsiPmsiPointer           RowPointer
}

mvpnSpmsiCmcastGroupAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "The InetAddressType of the mvpnSpmsiCmcastGroupAddr object
        that follows.
        "

```



```
::= { mvpnSpmsiEntry 1 }
```

mvpnSpmsiCmcastGroupAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The group address of the C-flow assigned to the
S-PMSI corresponding to this entry."

REFERENCE

"[RFC6513](#), Sec. 3.1"

```
::= { mvpnSpmsiEntry 2 }
```

mvpnSpmsiCmcastGroupPrefixLen OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The prefix length of the corresponding
mvpnSpmsiCmcastGroupAddr object.
"

```
::= { mvpnSpmsiEntry 3 }
```

mvpnSpmsiCmcastSourceAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The InetAddressType of the mvpnSpmsiCmcastSourceAddr object
that follows.
"

```
::= { mvpnSpmsiEntry 4 }
```

mvpnSpmsiCmcastSourceAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The source address of the C-flow assigned to the
S-PMSI corresponding to this entry."

```
::= { mvpnSpmsiEntry 5 }
```

mvpnSpmsiCmcastSourcePrefixLen OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The prefix length of the corresponding


```
        mvpnSpmsiCmcastSourceAddr object.
    "
 ::= { mvpnSpmsiEntry 6 }

mvpnSpmsiPmsiPointer OBJECT-TYPE
    SYNTAX      RowPointer
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "A pointer to a conceptual row representing
        generic information of this S-PMSI in mvpnPmsiTable.
        "
    ::= { mvpnSpmsiEntry 7 }

-- Table of statistics pertaining to
-- advertisements sent/received

mvpnAdvtStatsTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF MvpnAdvtStatsEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A conceptual table containing statistics pertaining to
        I-PMSI and S-PMSI advertisements sent/received by this PE.
        "
    ::= { mvpnObjects 6 }

mvpnAdvtStatsEntry OBJECT-TYPE
    SYNTAX      MvpnAdvtStatsEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A conceptual row corresponding to statistics
        pertaining to advertisements sent/received
        for a particular MVPN on this PE.

        Implementers need to be aware that if the total number of
        octets in mplsL3VpnVrfName and mvpnAdvtPeerAddr exceeds 115,
        then OIDs of column instances in this row will have more than
        128 sub-identifiers and cannot be accessed using SNMPv1,
        SNMPv2c, or SNMPv3.
        "
    INDEX {
        mplsL3VpnVrfName,
        mvpnAdvtType,
        mvpnAdvtPeerAddrType,
        mvpnAdvtPeerAddr
    }
```



```
 ::= { mvpnAdvtStatsTable 1 }
```

```
MvpnAdvtStatsEntry ::= SEQUENCE {
    mvpnAdvtType                INTEGER,
    mvpnAdvtPeerAddrType        InetAddressType,
    mvpnAdvtPeerAddr            InetAddress,
    mvpnAdvtSent                Counter32,
    mvpnAdvtReceived            Counter32,
    mvpnAdvtReceivedError       Counter32,
    mvpnAdvtReceivedMalformedTunnelType Counter32,
    mvpnAdvtReceivedMalformedTunnelId Counter32,
    mvpnAdvtLastSentTime        DateAndTime,
    mvpnAdvtLastReceivedTime    DateAndTime,
    mvpnAdvtCounterDiscontinuityTime TimeStamp
}
```

```
mvpnAdvtType OBJECT-TYPE
```

```
SYNTAX          INTEGER {
                                intraAsIpmsi (0),
                                interAsIpmsi (1),
                                sPmsi        (2)
                            }
```

```
MAX-ACCESS      not-accessible
```

```
STATUS          current
```

```
DESCRIPTION
```

```
"The PMSI type.
```

```

    The enumerated PMSI types and corresponding
    descriptions are as follows:
```

```

    intraAsIpmsi : Intra-AS Inclusive PMSI
    interAsIpmsi : Inter-AS Inclusive PMSI
    sPmsi        : Selective PMSI
```

```
"
```

```
REFERENCE
```

```
"RFC6513, Sec. 3.2.1"
```

```
 ::= { mvpnAdvtStatsEntry 1 }
```

```
mvpnAdvtPeerAddrType OBJECT-TYPE
```

```
SYNTAX          InetAddressType
```

```
MAX-ACCESS      not-accessible
```

```
STATUS          current
```

```
DESCRIPTION
```

```
"The InetAddressType of the mvpnAdvtPeerAddr object
that follows.
```

```
"
```

```
 ::= { mvpnAdvtStatsEntry 2 }
```


mvpnAdvtPeerAddr OBJECT-TYPE
SYNTAX InetAddress
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The address of a peer PE that exchanges advertisement with
this PE."
::= { mvpnAdvtStatsEntry 3 }

mvpnAdvtSent OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of advertisements successfully
sent to the peer PE specified by the corresponding
mvpnAdvtPeerAddr.

Discontinuities in the value of this counter can
occur at re-initialization of the management system,
and at other times as indicated by the corresponding
mvpnAdvtCounterDiscontinuityTime object."
::= { mvpnAdvtStatsEntry 4 }

mvpnAdvtReceived OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of advertisements received from the peer PE
specified by the corresponding mvpnAdvtPeerAddr object.
This includes advertisements that were discarded.

Discontinuities in the value of this counter can
occur at re-initialization of the management system,
and at other times as indicated by the corresponding
mvpnAdvtCounterDiscontinuityTime object."
::= { mvpnAdvtStatsEntry 5 }

mvpnAdvtReceivedError OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of advertisements received from a peer PE,

specified by the corresponding mvpnAdvPeerAddr object, that were rejected due to error(s) in the advertisement. The value of this object includes the error cases counted in the corresponding mvpnAdvReceivedMalformedTunnelType and mvpnAdvReceivedMalformedTunnelId objects.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnAdvCounterDiscontinuityTime object.

"

::= { mvpnAdvStatsEntry 6 }

mvpnAdvReceivedMalformedTunnelType OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of advertisements received from the peer PE specified by the corresponding mvpnAdvPeerAddr object, that were rejected due to malformed Tunnel Type in the PMSI Tunnel attribute.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnAdvCounterDiscontinuityTime object.

"

REFERENCE

"[RFC6514](#) Sec.5"

::= { mvpnAdvStatsEntry 7 }

mvpnAdvReceivedMalformedTunnelId OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of advertisements received from the peer PE specified by the corresponding mvpnAdvPeerAddr object, that were rejected due to malformed Tunnel Identifier in the PMSI Tunnel attribute.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnAdvCounterDiscontinuityTime object.

"

REFERENCE

"[RFC6514](#) Sec.5"

::= { mvpnAdvtStatsEntry 8 }

mvpnAdvtLastSentTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The timestamp when the last advertisement was successfully sent by this PE.

If no advertisement has been sent since the last re-initialization of this PE, then this object will have a zero-length string.

"

::= { mvpnAdvtStatsEntry 9 }

mvpnAdvtLastReceivedTime OBJECT-TYPE

SYNTAX DateAndTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The timestamp when the last advertisement was successfully received from the peer PE specified by the corresponding mvpnAdvtPeerAddr object and processed by this PE.

If no advertisement has been received since the last re-initialization of this PE, then this object will have a zero-length string.

"

::= { mvpnAdvtStatsEntry 10 }

mvpnAdvtCounterDiscontinuityTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime on the most recent occasion at which any one or more of this application's counters, viz., counters with OID prefix

'mvpnAdvtSent' or

'mvpnAdvtReceived' or

'mvpnAdvtReceivedError' or

'mvpnAdvtReceivedMalformedTunnelType' or

'mvpnAdvtReceivedMalformedTunnelId' suffered a discontinuity.

If no such discontinuities have occurred since the last re-initialization of the local management subsystem, then this object will have a zero value.


```

    "
    ::= { mvpnAdvtStatsEntry 11 }

-- Table of multicast routes in an MVPN

mvpnMrouteTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF MvpnMrouteEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "A conceptual table containing multicast routing information
        corresponding to the MVRFs present on the PE.
        "
    ::= { mvpnObjects 7 }

mvpnMrouteEntry OBJECT-TYPE
    SYNTAX      MvpnMrouteEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "A conceptual row corresponding to a route for IP datagrams
        from a particular source and addressed to a particular IP
        multicast group address.

        Implementers need to be aware that if the total number of
        octets in mplsL3VpnVrfName, mvpnMrouteCmcastGroupAddr and
        mvpnMrouteCmcastSourceAddrs exceeds 113, the OIDs of column
        instances in this row will have more than 128 sub-identifiers
        and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3.
        "
    INDEX {
        mplsL3VpnVrfName,
        mvpnMrouteCmcastGroupAddrType,
        mvpnMrouteCmcastGroupAddr,
        mvpnMrouteCmcastGroupPrefixLength,
        mvpnMrouteCmcastSourceAddrType,
        mvpnMrouteCmcastSourceAddrs,
        mvpnMrouteCmcastSourcePrefixLength
    }
    ::= { mvpnMrouteTable 1 }

MvpnMrouteEntry ::= SEQUENCE {
    mvpnMrouteCmcastGroupAddrType      InetAddressType,
    mvpnMrouteCmcastGroupAddr          InetAddress,
    mvpnMrouteCmcastGroupPrefixLength  InetAddressPrefixLength,
    mvpnMrouteCmcastSourceAddrType     InetAddressType,
    mvpnMrouteCmcastSourceAddrs        InetAddress,
    mvpnMrouteCmcastSourcePrefixLength InetAddressPrefixLength,

```



```

mvpnMrouteUpstreamNeighborAddrType  InetAddressType,
mvpnMrouteUpstreamNeighborAddr      InetAddress,
mvpnMrouteInIfIndex                  InterfaceIndexOrZero,
mvpnMrouteExpiryTime                  TimeTicks,
mvpnMrouteProtocol                    IANAipMRouteProtocol,
mvpnMrouteRtProtocol                  IANAipRouteProtocol,
mvpnMrouteRtAddrType                  InetAddressType,
mvpnMrouteRtAddr                      InetAddress,
mvpnMrouteRtPrefixLength              InetAddressPrefixLength,
mvpnMrouteRtType                       INTEGER,
mvpnMrouteOctets                       Counter64,
mvpnMroutePkts                         Counter64,
mvpnMrouteTtlDroppedOctets            Counter64,
mvpnMrouteTtlDroppedPackets           Counter64,
mvpnMrouteDroppedInOctets             Counter64,
mvpnMrouteDroppedInPackets            Counter64,
mvpnMroutePmsiPointer                 RowPointer,
mvpnMrouteNumberOfLocalReplication    Unsigned32,
mvpnMrouteNumberOfRemoteReplication   Unsigned32,
mvpnMrouteCounterDiscontinuityTime    TimeStamp
}

```

mvpnMrouteCmcastGroupAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The InetAddressType of the mvpnMrouteCmcastGroupAddr object
that follows.

"

::= { mvpnMrouteEntry 1 }

mvpnMrouteCmcastGroupAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The IP multicast group address which, along with
the corresponding mvpnMrouteCmcastGroupPrefixLength object,
identifies destinations for which this entry contains
multicast routing information.

This address object is only significant up to
mvpnMrouteCmcastGroupPrefixLength bits. The remaining address
bits MUST be set to zero.

For addresses of type 'ipv4z' or 'ipv6z', the appended zone
index is significant even though it lies beyond the prefix

length. The use of these address types indicate that this forwarding state applies only within the given zone. Zone index zero is not valid in this table.

"

::= { mvpnMrouteEntry 2 }

mvpnMrouteCmcastGroupPrefixLength OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The length in bits of the mask which, along with the corresponding mvpnMrouteCmcastGroupAddr object, identifies destinations for which this entry contains multicast routing information.

If the corresponding InetAddressType is 'ipv4' or 'ipv4z', this object must be in the range 4..32.

If the corresponding InetAddressType is 'ipv6' or 'ipv6z', this object must be in the range 8..128.

"

::= { mvpnMrouteEntry 3 }

mvpnMrouteCmcastSourceAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The InetAddressType of the mvpnMrouteCmcastSourceAddrs object that follows.

A value of unknown(0) indicates a non-source-specific entry, corresponding to all sources in the group. Otherwise, the value MUST be the same as the value of mvpnMrouteCmcastGroupAddrType.

"

::= { mvpnMrouteEntry 4 }

mvpnMrouteCmcastSourceAddrs OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The network address which, along with the corresponding mvpnMrouteCmcastSourcePrefixLength object, identifies the sources for which this entry contains multicast routing information.

This address object is only significant up to
mvpnMrouteCmcastSourcePrefixLength bits.
The remaining address bits MUST be set to zero.

For addresses of type 'ipv4z' or 'ipv6z', the appended zone
index is significant even though it lies beyond the prefix
length. The use of these address types indicate that this
source address applies only within the given zone. Zone
index zero is not valid in this table.

"

::= { mvpnMrouteEntry 5 }

mvpnMrouteCmcastSourcePrefixLength OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The length in bits of the mask which, along with
the corresponding mvpnMrouteCmcastSourceAddr object,
identifies the sources for which this entry contains
multicast routing information.

If the corresponding InetAddressType is 'ipv4' or 'ipv4z',
this object must be in the range 4..32.

If the corresponding InetAddressType is 'ipv6' or 'ipv6z',
this object must be in the range 8..128.

If the corresponding InetAddressType is 'unknown',
this object must be zero.

"

::= { mvpnMrouteEntry 6 }

mvpnMrouteUpstreamNeighborAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The InetAddressType of the mvpnMrouteUpstreamNeighborAddr
object that follows.

A value of unknown(0) indicates that the upstream
neighbor is unknown, for example in BIDIR-PIM."

REFERENCE

"[RFC 5015](#)"

::= { mvpnMrouteEntry 7 }

mvpnMrouteUpstreamNeighborAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The address of the upstream neighbor (for example, Reverse Path Forwarding (RPF) neighbor) from which IP datagrams from these sources represented by this entry to this multicast address are received.
"

::= { mvpnMrouteEntry 8 }

mvpnMrouteInIfIndex OBJECT-TYPE

SYNTAX InterfaceIndexOrZero

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of ifIndex for the interface on which IP datagrams sent by these sources represented by this entry to this multicast address are received.

A value 0 indicates that datagrams are not subject to an incoming interface check, but may be accepted on multiple interfaces (for example, in BIDIR-PIM).

"

REFERENCE

"[RFC 5015](#)"

::= { mvpnMrouteEntry 9 }

mvpnMrouteExpiryTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The minimum amount of time remaining before this entry will be aged out. The value 0 indicates that the entry is not subject to aging. If the corresponding mvpnMrouteNextHopState object is pruned(1), this object represents the remaining time for the prune to expire after which the state will return to forwarding(2).

If the corresponding mvpnMrouteNextHopState object is forwarding(2), this object indicates the time after which this entry will be removed from the table.

"

::= { mvpnMrouteEntry 10 }

mvpnMrouteProtocol OBJECT-TYPE

SYNTAX IANAipMrouteProtocol

MAX-ACCESS read-only

STATUS current

DESCRIPTION


```
"The multicast routing protocol via which this multicast
  forwarding entry was learned.
"
 ::= { mvpnMrouteEntry 11 }

mvpnMrouterRtProtocol OBJECT-TYPE
    SYNTAX      IANAipRouteProtocol
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The routing protocol via which the route used to find the
          upstream or parent interface for this multicast forwarding
          entry was learned.
        "
    ::= { mvpnMrouteEntry 12 }

mvpnMrouterRtAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The InetAddressType of the mvpnMrouterRtAddr object
          that follows.
        "
    ::= { mvpnMrouteEntry 13 }

mvpnMrouterRtAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The address portion of the route used to find the upstream
          or parent interface for this multicast forwarding entry.

        This address object is only significant up to
        mvpnMrouterRtPrefixLength bits. The remaining address bits
        MUST be set to zero.

        For addresses of type 'ipv4z' or 'ipv6z', the appended zone
        index is significant even though it lies beyond the prefix
        length. The use of these address types indicate that this
        forwarding state applies only within the given zone. Zone
        index zero is not valid in this table.
        "
    ::= { mvpnMrouteEntry 14 }

mvpnMrouterRtPrefixLength OBJECT-TYPE
    SYNTAX      InetAddressPrefixLength
```


MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The length in bits of the mask associated with the route used to find the upstream or parent interface for this multicast forwarding entry.

If the corresponding InetAddressType is 'ipv4' or 'ipv4z', this object must be in the range 4..32.

If the corresponding InetAddressType is 'ipv6' or 'ipv6z', this object must be in the range 8..128.

"

::= { mvpnMrouteEntry 15 }

mvpnMrouteRtType OBJECT-TYPE

SYNTAX INTEGER {
 unicast (1),
 multicast (2)
 }

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The reason for placing the route in the (logical) multicast Routing Information Base (RIB).

The enumerated reasons and the corresponding descriptions are as follows:

unicast:

The route would normally be placed only in the unicast RIB, but was placed in the multicast RIB by local configuration, such as when running PIM over RIP.

multicast:

The route was explicitly added to the multicast RIB by the routing protocol, such as the Distance Vector Multicast Routing Protocol (DVMRP) or Multiprotocol BGP.

"

::= { mvpnMrouteEntry 16 }

mvpnMrouteOctets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of octets contained in IP datagrams that were received from sources represented by this entry and

addressed to this multicast group address, and which were forwarded by this router.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

::= { mvpnMrouteEntry 17 }

mvpnMroutePkts OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of packets routed using this multicast route entry.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

::= { mvpnMrouteEntry 18 }

mvpnMrouteTtlDroppedOctets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of octets contained in IP datagrams that this router has received from sources represented by this entry and addressed to this multicast group address, which were dropped due to Time To Live (TTL) issues. TTL issues occur when the TTL (IPv4) or Hop Limit (IPv6) of the incoming packet was decremented to zero, or to a value less than ipMcastInterfaceTtl of the corresponding interface.

The ipMcastInterfaceTtl object is defined in IPMCAST-MIB [[RFC5132](#)] and represents the datagram TTL threshold for the interface. Any IP multicast datagrams with a TTL (IPv4) or Hop Limit (IPv6) less than this threshold will not be forwarded out of the interface. The default value of 0 means all multicast packets are forwarded out of the interface. A value of 256 means that no multicast packets are forwarded out of the interface.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

REFERENCE

"[RFC5132](#), Sec. 6

"

::= { mvpnMrouteEntry 19 }

mvpnMrouteTtlDroppedPackets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of packets that this router has received from the sources represented by this entry and addressed to this multicast group address, which were dropped due to Time To Live (TTL) issues. TTL issues occur when the TTL (IPv4) or Hop Limit (IPv6) of the incoming packet was decremented to zero, or to a value less than ipMcastInterfaceTtl of the corresponding interface.

The ipMcastInterfaceTtl object is defined in IPMCAST-MIB [[RFC5132](#)] and represents the datagram TTL threshold for the interface. Any IP multicast datagrams with a TTL (IPv4) or Hop Limit (IPv6) less than this threshold will not be forwarded out of the interface. The default value of 0 means all multicast packets are forwarded out of the interface. A value of 256 means that no multicast packets are forwarded out of the interface.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

REFERENCE

"[RFC5132](#), Sec. 6

"

::= { mvpnMrouteEntry 20 }

mvpnMrouteDroppedInOctets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of octets contained in IP datagrams that this

router has received from sources represented by this entry and addressed to this multicast group address, which were dropped due to error(s).

The value of this object includes the octets counted in the corresponding mvpnMrouteTtlDroppedOctets object.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

::= { mvpnMrouteEntry 21 }

mvpnMrouteDroppedInPackets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of packets which this router has received from sources represented by this entry and addressed to this multicast group address, which were dropped due to error(s). The value of this object includes the number of octets counted in the corresponding mvpnMrouteTtlDroppedPackets object.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnMrouteCounterDiscontinuityTime object.

"

::= { mvpnMrouteEntry 22 }

mvpnMroutePmsiPointer OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A pointer to a conceptual row representing the corresponding I-PMSI in mvpnPmsiTable or S-PMSI in mvpnSpmsiTable, that this C-multicast route is using.

"

::= { mvpnMrouteEntry 23 }

mvpnMrouteNumberOfLocalReplication OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION


```
"Number of replications for local receivers.
For example, if an ingress PE needs to send traffic out of
N PE-CE interfaces, then mvpnMrouteNumberOfLocalReplication
is N.
"
::= { mvpnMrouteEntry 24 }

mvpnMrouteNumberOfRemoteReplication OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "Number of local replications for remote PEs. For example,
        if the number of remote PEs that need to receive traffic is N,
        then mvpnMrouteNumberOfRemoteReplication is N in case of
        Ingress Replication, but may be less than N in case of RSVP-TE
        or mLDP P2MP tunnels, depending on the actual number of
        replications the PE needs to do.
        "
    ::= { mvpnMrouteEntry 25 }

mvpnMrouteCounterDiscontinuityTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime on the most recent occasion
        at which any one or more of this application's
        counters, viz., counters with OID prefix
        'mvpnMrouteOctets' or 'mvpnMroutePkts' or
        'mvpnMrouteTtlDroppedOctets' or
        'mvpnMrouteTtlDroppedPackets' or
        'mvpnMrouteDroppedInOctets' or 'mvpnMrouteDroppedInPackets'
        suffered a discontinuity.
        If no such discontinuities have occurred since the
        last re-initialization of the local management
        subsystem, then this object will have a zero value.
        "
    ::= { mvpnMrouteEntry 26 }

-- Table of next hops for multicast routes in an MVPN

mvpnMrouteNextHopTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF MvpnMrouteNextHopEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "A conceptual table containing information on the
```


next-hops for routing IP multicast datagrams.
Each entry is one of a list of next-hops for
a set of sources sending to a multicast group
address.

"

::= { mvpnObjects 8 }

mvpnMrouteNextHopEntry OBJECT-TYPE

SYNTAX MvpnMrouteNextHopEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A conceptual row corresponding to a next-hop to which
IP multicast datagrams from a set of sources to
an IP multicast group address are routed.

Implementers need to be aware that if the total number of
octets in mplsL3VpnVrfName, mvpnMrouteNextHopGroupAddr,
mvpnMrouteNextHopSourceAddrs, and mvpnMrouteNextHopAddr
exceeds 111, the OIDs of column instances in this row
will have more than 128 sub-identifiers and cannot be
accessed using SNMPv1, SNMPv2c, or SNMPv3.

"

INDEX {
 mplsL3VpnVrfName,
 mvpnMrouteNextHopGroupAddrType,
 mvpnMrouteNextHopGroupAddr,
 mvpnMrouteNextHopGroupPrefixLength,
 mvpnMrouteNextHopSourceAddrType,
 mvpnMrouteNextHopSourceAddrs,
 mvpnMrouteNextHopSourcePrefixLength,
 mvpnMrouteNextHopIfIndex,
 mvpnMrouteNextHopAddrType,
 mvpnMrouteNextHopAddr
}

::= { mvpnMrouteNextHopTable 1 }

MvpnMrouteNextHopEntry ::= SEQUENCE {

mvpnMrouteNextHopGroupAddrType	InetAddressType,
mvpnMrouteNextHopGroupAddr	InetAddress,
mvpnMrouteNextHopGroupPrefixLength	InetAddressPrefixLength,
mvpnMrouteNextHopSourceAddrType	InetAddressType,
mvpnMrouteNextHopSourceAddrs	InetAddress,
mvpnMrouteNextHopSourcePrefixLength	InetAddressPrefixLength,
mvpnMrouteNextHopIfIndex	InterfaceIndex,
mvpnMrouteNextHopAddrType	InetAddressType,
mvpnMrouteNextHopAddr	InetAddress,
mvpnMrouteNextHopState	INTEGER,


```
    mvpnMrouteNextHopExpiryTime      TimeTicks,
    mvpnMrouteNextHopClosestMemberHops Unsigned32,
    mvpnMrouteNextHopProtocol        IANAipMRouteProtocol,
    mvpnMrouteNextHopOctets          Counter64,
    mvpnMrouteNextHopPkts            Counter64,
    mvpnMrouteNextHopCounterDiscontinuityTime TimeStamp
}

mvpnMrouteNextHopGroupAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The InetAddressType of the mvpnMrouteNextHopGroupAddr object
        that follows.
        "
    ::= { mvpnMrouteNextHopEntry 1 }

mvpnMrouteNextHopGroupAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The IP multicast group address which, along with
        the corresponding mvpnMrouteNextHopGroupPrefixLength object,
        identifies destinations for which this entry contains
        multicast forwarding information.

        This address object is only significant up to
        mvpnMrouteNextHopGroupPrefixLength bits. The remaining
        address bits MUST be set to zero.

        For addresses of type 'ipv4z' or 'ipv6z', the appended zone
        index is significant even though it lies beyond the prefix
        length. The use of these address types indicate that this
        forwarding state applies only within the given zone. Zone
        index zero is not valid in this table.
        "
    ::= { mvpnMrouteNextHopEntry 2 }

mvpnMrouteNextHopGroupPrefixLength OBJECT-TYPE
    SYNTAX      InetAddressPrefixLength
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The length in bits of the mask which, along with
        the corresponding mvpnMrouteGroupAddr object,
        identifies destinations for which this entry contains
```


multicast routing information.

If the corresponding InetAddressType is 'ipv4' or 'ipv4z', this object must be in the range 4..32.

If the corresponding InetAddressType is 'ipv6' or 'ipv6z', this object must be in the range 8..128.

"

::= { mvpnMrouteNextHopEntry 3 }

mvpnMrouteNextHopSourceAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The InetAddressType of mvpnMrouteNextHopSourceAddrs object that follows.

A value of unknown(0) indicates a non-source-specific entry, corresponding to all sources in the group. Otherwise, the value MUST be the same as the value of mvpnMrouteNextHopGroupAddrType."

::= { mvpnMrouteNextHopEntry 4 }

mvpnMrouteNextHopSourceAddrs OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The network address which, along with the corresponding mvpnMrouteNextHopSourcePrefixLength object, identifies the sources for which this entry specifies a next-hop.

This address object is only significant up to mvpnMrouteNextHopSourcePrefixLength bits. The remaining address bits MUST be set to zero.

For addresses of type 'ipv4z' or 'ipv6z', the appended zone index is significant even though it lies beyond the prefix length. The use of these address types indicate that this source address applies only within the given zone. Zone index zero is not valid in this table.

"

::= { mvpnMrouteNextHopEntry 5 }

mvpnMrouteNextHopSourcePrefixLength OBJECT-TYPE

SYNTAX InetAddressPrefixLength

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The length in bits of the mask which, along with the corresponding mvpnMrouteNextHopSourceAddrs object, identifies the sources for which this entry specifies a next-hop.

If the corresponding InetAddressType is 'ipv4' or 'ipv4z', this object must be in the range 4..32.

If the corresponding InetAddressType is 'ipv6' or 'ipv6z', this object must be in the range 8..128.

If the corresponding InetAddressType is 'unknown', this object must be zero.

"

::= { mvpnMrouteNextHopEntry 6 }

mvpnMrouteNextHopIfIndex OBJECT-TYPE

SYNTAX InterfaceIndex

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The ifIndex value of the outgoing interface for this next-hop.

"

::= { mvpnMrouteNextHopEntry 7 }

mvpnMrouteNextHopAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The InetAddressType of the mvpnMrouteNextHopAddr object that follows.

"

::= { mvpnMrouteNextHopEntry 8 }

mvpnMrouteNextHopAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The address of the next-hop specific to this entry. For most interfaces, this is identical to mvpnMrouteNextHopGroupAddr. Non-Broadcast Multi-Access (NBMA) interfaces, however, may have multiple next-hop addresses out of a single outgoing interface.

"

::= { mvpnMrouteNextHopEntry 9 }

mvpnMrouteNextHopState OBJECT-TYPE

```
SYNTAX      INTEGER {
                                pruned(1),
                                forwarding(2)
                        }
```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"An indication of whether the outgoing interface and next-hop represented by this entry is currently being used to forward IP datagrams.

The enumerated states and the corresponding descriptions are as follows:

pruned : this entry is not currently being used.
forwarding : this entry is currently being used.

"

::= { mvpnMrouteNextHopEntry 10 }

mvpnMrouteNextHopExpiryTime OBJECT-TYPE

```
SYNTAX      TimeTicks
```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The minimum amount of time remaining before this entry will be aged out. If mvpnMrouteNextHopState is pruned(1), this object represents the remaining time for the prune to expire after which the state will return to forwarding(2). If mvpnMrouteNextHopState is forwarding(2), this object indicates the time after which this entry will be removed from the table.

The value of 0 indicates that the entry is not subject to aging.

"

::= { mvpnMrouteNextHopEntry 11 }

mvpnMrouteNextHopClosestMemberHops OBJECT-TYPE

```
SYNTAX      Unsigned32 (0..256)
```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The minimum number of hops between this router and any member of this IP multicast group reached via this next-hop on the corresponding outgoing interface. Any IP multicast datagram for the group that has a TTL (IPv4) or Hop Count (IPv6) less than mvpnMrouteNextHopClosestMemberHops will

not be forwarded through this interface.

A value of 0 means all multicast datagrams are forwarded out of the interface. A value of 256 means that no multicast datagrams are forwarded out of the interface.

This is an optimization applied by multicast routing protocols that explicitly track hop counts to downstream listeners. Multicast protocols that are not aware of hop counts to downstream listeners set this object to 0.

"

::= { mvpnMrouteNextHopEntry 12 }

mvpnMrouteNextHopProtocol OBJECT-TYPE

SYNTAX IANAipMRouteProtocol

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The routing protocol via which this next-hop was learned."

::= { mvpnMrouteNextHopEntry 13 }

mvpnMrouteNextHopOctets OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of octets of multicast packets that have been forwarded using this route.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnMrouteNextHopCounterDiscontinuityTime object.

"

::= { mvpnMrouteNextHopEntry 14 }

mvpnMrouteNextHopPkts OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of packets which have been forwarded using this route.

Discontinuities in the value of this counter can occur at re-initialization of the management system, and at other times as indicated by the corresponding mvpnMrouteNextHopCounterDiscontinuityTime object.


```
"
 ::= { mvpnMrouteNextHopEntry 15 }

mvpnMrouteNextHopCounterDiscontinuityTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime on the most recent occasion
        at which any one or more of this application's
        counters, viz., counters with OID prefix
        'mvpnMrouteNextHopOctets' or 'mvpnMrouteNextHopPackets'
        suffered a discontinuity.
        If no such discontinuities have occurred since the
        last re-initialization of the local management
        subsystem, then this object will have a zero value.
        "
    ::= { mvpnMrouteNextHopEntry 16 }

-- MVPN Notifications

mvpnMvrfActionTaken NOTIFICATION-TYPE
    OBJECTS      {
        mvpnGenMvrfCreationTime,
        mvpnGenMvrfLastAction,
        mvpnGenMvrfLastActionTime,
        mvpnGenMvrfCreationTime,
        mvpnGenCmcastRouteProtocol,
        mvpnGenUmhSelection,
        mvpnGenCustomerSiteType
    }
    STATUS      current
    DESCRIPTION
        "mvpnMvrfActionTaken notifies about a change
        in a MVRF on the PE. The change itself will be given by
        mvpnGenMvrfLastAction.
        "
    ::= { mvpnNotifications 1 }

-- MVPN MIB Conformance Information

mvpnGroups      OBJECT IDENTIFIER ::= { mvpnConformance 1 }
mvpnCompliances OBJECT IDENTIFIER ::= { mvpnConformance 2 }

-- Compliance Statements

mvpnModuleFullCompliance MODULE-COMPLIANCE
    STATUS      current
```


DESCRIPTION

"Compliance statement for agents that provide full support
for the MCAST-VPN-MIB
"

MODULE -- this module

MANDATORY-GROUPS {
 mvpnScalarGroup,
 mvpnGenericGroup,
 mvpnPmsiGroup,
 mvpnAdvtStatsGroup,
 mvpnMrouteGroup,
 mvpnMrouteNextHopGroup,
 mvpnNotificationGroup
}

GROUP mvpnBgpScalarGroup

DESCRIPTION

"This group is mandatory for systems that support
BGP-MVPN.
"

GROUP mvpnBgpGroup

DESCRIPTION

"This group is mandatory for systems that support
BGP-MVPN.
"

::= { mvpnCompliances 1 }

mvpnModuleReadOnlyCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION "Compliance requirement for implementations that
only provide read-only support for MCAST-VPN-MIB.
Such devices can then be monitored but cannot be
configured using this MIB module.
"

MODULE -- this module

MANDATORY-GROUPS {
 mvpnScalarGroup,
 mvpnGenericGroup,
 mvpnPmsiGroup,
 mvpnAdvtStatsGroup,
 mvpnMrouteGroup,
 mvpnMrouteNextHopGroup,
 mvpnNotificationGroup
}

GROUP mvpnBgpScalarGroup

DESCRIPTION

"This group is mandatory for systems that support
BGP-MVPN.
"

GROUP mvpnBgpGroup

DESCRIPTION

"This group is mandatory for systems that support
BGP-MVPN.
"

OBJECT mvpnSPTunnelLimit

MIN-ACCESS read-only

DESCRIPTION "Write access is not required."

OBJECT mvpnBgpCmcastRouteWithdrawalTimer

MIN-ACCESS read-only

DESCRIPTION "Write access is not required."

OBJECT mvpnBgpSrcSharedTreeJoinTimer

MIN-ACCESS read-only

DESCRIPTION "Write access is not required."

OBJECT mvpnBgpMsgRateLimit

MIN-ACCESS read-only

DESCRIPTION "Write access is not required."

OBJECT mvpnBgpMaxSpmsiAdRoutes

MIN-ACCESS read-only

DESCRIPTION "Write access is not required."

OBJECT mvpnBgpMaxSpmsiAdRouteFreq

MIN-ACCESS read-only

DESCRIPTION "Write access is not required."

OBJECT mvpnBgpMaxSrcActiveAdRoutes

MIN-ACCESS read-only

DESCRIPTION "Write access is not required."

OBJECT mvpnBgpMaxSrcActiveAdRouteFreq

MIN-ACCESS read-only

DESCRIPTION "Write access is not required."

::= { mvpnCompliances 2 }

mvpnModuleAdvtStatsCompliance MODULE-COMPLIANCE

STATUS current


```
DESCRIPTION
    "Compliance statement for agents that support
      monitoring of the statistics pertaining to
      advertisements sent/received by a PE.
    "
MODULE -- this module
MANDATORY-GROUPS {
    mvpnAdvtStatsGroup
}

::= { mvpnCompliances 3 }

-- units of conformance

mvpnScalarGroup    OBJECT-GROUP
    OBJECTS {
        mvpnMvrfs,
        mvpnV4Mvrfs,
        mvpnV6Mvrfs,
        mvpnPimV4Mvrfs,
        mvpnPimV6Mvrfs,
        mvpnSPTunnelLimit
    }
    STATUS          current
    DESCRIPTION
        "These objects are used to monitor/manage
          global statistics and parameters.
        "
    ::= { mvpnGroups 1 }

mvpnBgpScalarGroup    OBJECT-GROUP
    OBJECTS {
        mvpnMldpMvrfs,
        mvpnBgpV4Mvrfs,
        mvpnBgpV6Mvrfs,
        mvpnBgpCmcastRouteWithdrawalTimer,
        mvpnBgpSrcSharedTreeJoinTimer
    }
    STATUS          current
    DESCRIPTION
        "These objects are used to monitor/manage
          BGP-MVPN specific global parameters.
        "
    ::= { mvpnGroups 2 }

mvpnGenericGroup    OBJECT-GROUP
    OBJECTS {
        mvpnGenMvrflLastAction,
```



```
        mvpnGenMvrfLastActionTime,
        mvpnGenMvrfCreationTime,
        mvpnGenCmcastRouteProtocol,
        mvpnGenIpmsiInfo,
        mvpnGenInterAsPmsiInfo,
        mvpnGenUmhSelection,
        mvpnGenCustomerSiteType
    }
    STATUS          current
    DESCRIPTION
        "These objects are used to monitor MVPNs on a PE.
        "
    ::= { mvpnGroups 3 }

mvpnBgpGroup      OBJECT-GROUP
    OBJECTS {
        mvpnBgpMode,
        mvpnBgpVrfRouteImportExtendedCommunity,
        mvpnBgpSrcASEExtendedCommunity,
        mvpnBgpMsgRateLimit,
        mvpnBgpMaxSpmsiAdRoutes,
        mvpnBgpMaxSpmsiAdRouteFreq,
        mvpnBgpMaxSrcActiveAdRoutes,
        mvpnBgpMaxSrcActiveAdRouteFreq
    }
    STATUS          current
    DESCRIPTION
        "These objects are used to monitor/manage
        the MVPN-wise BGP specific parameters.
        "
    ::= { mvpnGroups 4 }

mvpnPmsiGroup      OBJECT-GROUP
    OBJECTS {
        mvpnPmsiRD,
        mvpnPmsiTunnelType,
        mvpnPmsiTunnelAttribute,
        mvpnPmsiTunnelPimGroupAddrType,
        mvpnPmsiTunnelPimGroupAddr,
        mvpnPmsiEncapsulationType,
        mvpnSpmsiPmsiPointer
    }
    STATUS          current
    DESCRIPTION
        "These objects are used to monitor
        I-PMSIs and S-PMSIs tunnel on a PE.
        "
    ::= { mvpnGroups 5 }
```



```
mvpnAdvStatsGroup      OBJECT-GROUP
  OBJECTS {
    mvpnAdvSent,
    mvpnAdvReceived,
    mvpnAdvReceivedError,
    mvpnAdvReceivedMalformedTunnelType,
    mvpnAdvReceivedMalformedTunnelId,
    mvpnAdvLastSentTime,
    mvpnAdvLastReceivedTime,
    mvpnAdvCounterDiscontinuityTime
  }
  STATUS      current
  DESCRIPTION
    "These objects are used to monitor
    the statistics pertaining to I-PMSI and S-PMSI
    advertisements sent/received by a PE.
    "
  ::= { mvpnGroups 6 }

mvpnMrouteGroup        OBJECT-GROUP
  OBJECTS {
    mvpnMrouteUpstreamNeighborAddrType,
    mvpnMrouteUpstreamNeighborAddr,
    mvpnMrouteInIfIndex,
    mvpnMrouteExpiryTime,
    mvpnMrouteProtocol,
    mvpnMrouteRtProtocol,
    mvpnMrouteRtAddrType,
    mvpnMrouteRtAddr,
    mvpnMrouteRtPrefixLength,
    mvpnMrouteRtType,
    mvpnMrouteOctets,
    mvpnMroutePkts,
    mvpnMrouteTtlDroppedOctets,
    mvpnMrouteTtlDroppedPackets,
    mvpnMrouteDroppedInOctets,
    mvpnMrouteDroppedInPackets,
    mvpnMroutePmsiPointer,
    mvpnMrouteNumberOfLocalReplication,
    mvpnMrouteNumberOfRemoteReplication,
    mvpnMrouteCounterDiscontinuityTime
  }
  STATUS      current
  DESCRIPTION
    "These objects are used to monitor multicast routing
    information corresponding to the MVRFs on a PE.
    "
  ::= { mvpnGroups 7 }
```



```
mvpnMrouteNextHopGroup    OBJECT-GROUP
    OBJECTS {
        mvpnMrouteNextHopState,
        mvpnMrouteNextHopExpiryTime,
        mvpnMrouteNextHopClosestMemberHops,
        mvpnMrouteNextHopProtocol,
        mvpnMrouteNextHopOctets,
        mvpnMrouteNextHopPkts,
        mvpnMrouteNextHopCounterDiscontinuityTime
    }
    STATUS      current
    DESCRIPTION
        "These objects are used to monitor the information on
        next-hops for routing datagrams to MVPNs on a PE.
        "
    ::= { mvpnGroups 8 }

mvpnNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS {
        mvpnMvrfActionTaken
    }
    STATUS      current
    DESCRIPTION
        "Objects required for MVPN notifications."
    ::= { mvpnGroups 9 }

END
```

4. Security Considerations

This MIB module contains some read-only objects that may be deemed sensitive. It also contains some read-write objects, whose setting will change the device's MVPN related behavior. Appropriate security procedures related to SNMP in general but not specific to this MIB module need to be implemented by concerned operators.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection opens devices to attack. These are the tables and objects and their sensitivity/vulnerability:

- o mvpnSPTunnelLimit

The value of this object is used to control the maximum number of selective provider tunnels that a PE allows for a particular MVPN. Access to this object may be abused to impact the performance of

the PE or prevent the PE from having new selective provider tunnels.

- o mvpnBgpCmcastRouteWithdrawalTimer

The value of this object is used to control the delay for the advertisement of withdrawals of C-multicast routes. Access to this object may be abused to impact the performance of a PE.

- o mvpnBgpSrcSharedTreeJoinTimer

The value of this object is used to control the delay for the advertisement of Source/Shared Tree Join C-multicast routes. Access to this object may be abused to impact the propagation of C-multicast routing information.

- o mvpnBgpMsgRateLimit

The value of this object is used to control the upper bound for the rate of BGP C-multicast routing information message exchange among PEs. Access to this object may be abused to impact the performance of the PE or disrupt the C-multicast routing information message exchange using BGP.

- o mvpnBgpMaxSpmsiAdRoutes

The value of this object is used to control the upper bound for the number of S-PMSI A-D routes. Access to this object may be abused to impact the performance of the PE or prevent the PE from receiving S-PMSI A-D routes.

- o mvpnBgpMaxSpmsiAdRouteFreq

The value of this object is used to control the upper bound for the frequency of S-PMSI A-D route generation. Access to this object may be abused to impact the performance of the PE or prevent the PE from generating new S-PMSI A-D routes.

- o mvpnBgpMaxSrcActiveAdRoutes

The value of this object is used to control the upper bound for the number of Source Active A-D routes. Access to this object may be abused to impact the performance of the PE or prevent the PE from receiving Source Active A-D routes.

- o mvpnBgpMaxSrcActiveAdRouteFreq

The value of this object is used to control the upper bound for the frequency of Source Active A-D route generation. Access to this object may be abused to impact the performance of the PE or prevent the PE from generating new Source Active A-D routes.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- o The address-related objects in this MIB module may have impact on privacy and security. These objects may reveal the locations of senders and recipients.

- * mvpnPmsiTunnelPimGroupAddr
- * mvpnSpmsiCmcastGroupAddr
- * mvpnSpmsiCmcastSourceAddr
- * mvpnAdvtPeerAddr
- * mvpnMrouteCmcastGroupAddr
- * mvpnMrouteCmcastSourceAddrs
- * mvpnMrouteUpstreamNeighborAddr
- * mvpnMrouteNextHopGroupAddr
- * mvpnMrouteNextHopSourceAddrs
- * mvpnMrouteNextHopAddr

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations SHOULD provide the security features described by the SNMPv3 framework (see [[RFC3410](#)]), and implementations claiming compliance to the SNMPv3 standard MUST include full support for authentication and privacy via the User-based Security Model (USM) [[RFC3414](#)] with the AES cipher algorithm [[RFC3826](#)]. Implementations

MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

5. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
-----	-----
mvpnMIB	{ mib-2 AAAA }

Editor's Note (to be removed prior to publication): the IANA is requested to assign a value for "AAAA" under the 'mib-2' subtree and to record the assignment in the SMI Numbers registry. When the assignment has been made, the RFC Editor is asked to replace "AAAA" (here and in the MIB module) with the assigned value and to remove this note.

6. Acknowledgement

An earlier draft version of this document was coauthored by Zhaohui (Jeffrey) Zhang, Saud Asif, Andy Green, Sameer Gulrajani, and Pradeep G. Jain, based on an earlier draft written by Susheela Vaidya, Thomas D. Nadeau, and Harmen Van der Linde.

This document also borrows heavily from the design and descriptions of ipMcastRouteTable and ipMcastRouteNextHopTable from IPMCAST-MIB[RFC5132].

Glenn Mansfield Keeni did the MIB Doctor review and provided valuable comments.

7. References

7.1. Normative References

- [RFC2003] Perkins, C., "IP Encapsulation within IP", [RFC 2003](#), DOI 10.17487/RFC2003, October 1996, <<https://www.rfc-editor.org/info/rfc2003>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), DOI 10.17487/RFC2578, April 1999, <<https://www.rfc-editor.org/info/rfc2578>>.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), DOI 10.17487/RFC2579, April 1999, <<https://www.rfc-editor.org/info/rfc2579>>.
- [RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), DOI 10.17487/RFC2580, April 1999, <<https://www.rfc-editor.org/info/rfc2580>>.
- [RFC2784] Farinacci, D., Li, T., Hanks, S., Meyer, D., and P. Traina, "Generic Routing Encapsulation (GRE)", [RFC 2784](#), DOI 10.17487/RFC2784, March 2000, <<https://www.rfc-editor.org/info/rfc2784>>.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), DOI 10.17487/RFC2863, June 2000, <<https://www.rfc-editor.org/info/rfc2863>>.
- [RFC3032] Rosen, E., Tappan, D., Fedorkow, G., Rekhter, Y., Farinacci, D., Li, T., and A. Conta, "MPLS Label Stack Encoding", [RFC 3032](#), DOI 10.17487/RFC3032, January 2001, <<https://www.rfc-editor.org/info/rfc3032>>.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, [RFC 3414](#), DOI 10.17487/RFC3414, December 2002, <<https://www.rfc-editor.org/info/rfc3414>>.

- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", [RFC 3826](#), DOI 10.17487/[RFC3826](#), June 2004, <<https://www.rfc-editor.org/info/rfc3826>>.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), DOI 10.17487/RFC4001, February 2005, <<https://www.rfc-editor.org/info/rfc4001>>.
- [RFC4364] Rosen, E. and Y. Rekhter, "BGP/MPLS IP Virtual Private Networks (VPNs)", [RFC 4364](#), DOI 10.17487/RFC4364, February 2006, <<https://www.rfc-editor.org/info/rfc4364>>.
- [RFC4382] Nadeau, T., Ed. and H. van der Linde, Ed., "MPLS/BGP Layer 3 Virtual Private Network (VPN) Management Information Base", [RFC 4382](#), DOI 10.17487/RFC4382, February 2006, <<https://www.rfc-editor.org/info/rfc4382>>.
- [RFC5132] McWalter, D., Thaler, D., and A. Kessler, "IP Multicast MIB", [RFC 5132](#), DOI 10.17487/RFC5132, December 2007, <<https://www.rfc-editor.org/info/rfc5132>>.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", STD 78, [RFC 5591](#), DOI 10.17487/RFC5591, June 2009, <<https://www.rfc-editor.org/info/rfc5591>>.
- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", [RFC 5592](#), DOI 10.17487/RFC5592, June 2009, <<https://www.rfc-editor.org/info/rfc5592>>.
- [RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", STD 78, [RFC 6353](#), DOI 10.17487/RFC6353, July 2011, <<https://www.rfc-editor.org/info/rfc6353>>.
- [RFC6513] Rosen, E., Ed. and R. Aggarwal, Ed., "Multicast in MPLS/BGP IP VPNs", [RFC 6513](#), DOI 10.17487/RFC6513, February 2012, <<https://www.rfc-editor.org/info/rfc6513>>.
- [RFC6514] Aggarwal, R., Rosen, E., Morin, T., and Y. Rekhter, "BGP Encodings and Procedures for Multicast in MPLS/BGP IP VPNs", [RFC 6514](#), DOI 10.17487/RFC6514, February 2012, <<https://www.rfc-editor.org/info/rfc6514>>.

- [RFC6625] Rosen, E., Ed., Rekhter, Y., Ed., Hendrickx, W., and R. Qiu, "Wildcards in Multicast VPN Auto-Discovery Routes", [RFC 6625](#), DOI 10.17487/RFC6625, May 2012, <<https://www.rfc-editor.org/info/rfc6625>>.
- [RFC7761] Fenner, B., Handley, M., Holbrook, H., Kouvelas, I., Parekh, R., Zhang, Z., and L. Zheng, "Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol Specification (Revised)", STD 83, [RFC 7761](#), DOI 10.17487/RFC7761, March 2016, <<https://www.rfc-editor.org/info/rfc7761>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RTPROTO] IANA, "IP Route Protocol MIB", 2016, <<http://www.iana.org/assignments/ianaiprouteprotocol-mib>>.

7.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), DOI 10.17487/RFC3410, December 2002, <<https://www.rfc-editor.org/info/rfc3410>>.

Author's Address

Hiroshi Tsunoda
Tohoku Institute of Technology
35-1, Yagiyama Kasumi-cho, Taihaku-ku
Sendai 982-8577
Japan

Phone: +81-22-305-3411
Email: tsuno@m.ieice.org

