

BFD Working Group  
Standard Track

Thomas D. Nadeau  
Zafar Ali  
Cisco Systems, Inc.

Document: [draft-ietf-bfd-mib-01.txt](#)

Expires: January 2006

July 2005

Bidirectional Forwarding Detection Management Information Base  
draft-ietf-bfd-mib-01.txt

### Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

### Abstract

This draft defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects for modeling Bidirectional Forwarding Detection (BFD) protocol [[BFD](#)].

### Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

### SUMMARY

This draft defines Management Information Base (MIB) for

BFD Working Group

Expires January 2005

[Page 1]

---

Internet Draft

BFD-DRAFT-01-MIB

July 2004

Bidirectional Forwarding Detection (BFD) protocol [[BFD](#)].

#### RELATED REFERENCES

Please refer to the reference section.

#### Table of Contents

<a href="#">1.</a>	Introduction.....	<a href="#">2</a>
<a href="#">2.</a>	Terminology.....	<a href="#">3</a>
<a href="#">3.</a>	The Internet-Standard Management Framework.....	<a href="#">3</a>
<a href="#">3.</a>	Brief Description of MIB Objects.....	<a href="#">3</a>
<a href="#">3.1</a>	General Variables.....	<a href="#">3</a>
<a href="#">3.2</a>	Session Table (bfdSessionTable).....	<a href="#">3</a>
<a href="#">3.3</a>	Session Performance Table (bfdSessionPerfTable).....	<a href="#">3</a>
<a href="#">3.4</a>	Session Mapping Table (bfdSessMapTable).....	<a href="#">3</a>
<a href="#">4.</a>	BFD MIB Module Definitions.....	<a href="#">4</a>
<a href="#">5.</a>	Security Considerations.....	<a href="#">21</a>
<a href="#">6.</a>	Acknowledgements.....	<a href="#">22</a>
<a href="#">7.</a>	Reference.....	<a href="#">23</a>
<a href="#">7.1</a>	Normative References.....	<a href="#">23</a>
<a href="#">7.2</a>	Informative References.....	<a href="#">23</a>
<a href="#">8.</a>	Author's Addresses.....	<a href="#">23</a>
<a href="#">9.</a>	Full Copyright Statement.....	<a href="#">24</a>
<a href="#">10.</a>	IANA Considerations.....	<a href="#">41</a>
<a href="#">10.1.</a>	IANA Considerations for BFD-STD-MIB.....	<a href="#">41</a>
<a href="#">11.</a>	Intellectual Property Statement.....	<a href="#">41</a>

#### [1.](#) Introduction

This memo defines an portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects to configure and/or monitor Bi-Directional Forwarding Detection on devices supporting this feature.

This document adopts the definitions, acronyms and mechanisms described in [[BFD](#)], [[BFD-SHARED](#)] and [[BFD-LSP](#)]. Unless otherwise

stated, the mechanisms described therein will not be re-described here.

Comments should be made directly to the BFD mailing list at [rtg-bfd@ietf.org](mailto:rtg-bfd@ietf.org).

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

BFD Working Group Expires January 2005 [Page 2]

---

Internet Draft BFD-DRAFT-01-MIB July 2004

## [2.](#) Terminology

This document adopts the definitions, acronyms and mechanisms described in [\[BFD\]](#), [\[BFD-SHARED\]](#) and [\[BFD-LSP\]](#). Unless otherwise stated, the mechanisms described therein will not be re-described here.

## [3.](#) The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [\[RFC3410\]](#).

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [\[RFC2578\]](#), STD 58, [RFC 2579](#) [\[RFC2579\]](#) and STD 58, [RFC 2580](#) [\[RFC2580\]](#).

## [4.](#) Brief Description of MIB Objects

This section describes objects pertaining to BFD. The MIB objects are derived from the BFD document [\[BFD\]](#).

### [4.1](#) General Variables

The General Variables are used to identify parameters that are global to the BFD process.

#### [4.2](#) Session Table (bfdSessionTable)

The session table is used to identify a BFD session between a pair of nodes.

#### [4.3](#) Session Performance Table (bfdSessionPerfTable)

The session performance table is used for collecting BFD performance counts on a per session basis. This table is an AUGMENT to the bfdSessionTable.

#### [3.4](#) Session Mapping Table (bfdSessMapTable)

The BFD Session Mapping Table maps the complex indexing of the BFD sessions to the flat BFDIndex used in the BfdSessionTable.

BFD Working Group Expires January 2005 [Page 3]

---

Internet Draft BFD-DRAFT-01-MIB July 2004

## [5.](#) BFD MIB Module Definitions

```
BFD-DRAFT-01-MIB DEFINITIONS ::= BEGIN
    -- RFC-editor pls change BFD-DRAFT-*--MIB to
    -- BFD-STD-MIB
```

### IMPORTS

```
    MODULE-IDENTITY, OBJECT-TYPE,
    Unsigned32, Counter32, Counter64,
    NOTIFICATION-TYPE, mib-2
    FROM SNMPv2-SMI
```

```
    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
    FROM SNMPv2-CONF
```

```
    TEXTUAL-CONVENTION, TruthValue, RowStatus, StorageType,
    TimeStamp
    FROM SNMPv2-TC
```

```
    InetAddress, InetAddressType, InetPortNumber
    FROM INET-ADDRESS-MIB
```

;

bfdMIB MODULE-IDENTITY

LAST-UPDATED "200507221200Z" -- 04 July 2005 12:00:00 EST

ORGANIZATION "IETF"

CONTACT-INFO

" Thomas D. Nadeau  
Cisco Systems, Inc.  
Email: tnadeau@cisco.com

Zafar Ali  
Cisco Systems, Inc.  
Email: zali@cisco.com

"

DESCRIPTION

"Bidirectional Forwarding Management Information Base."

-- Revision history.

REVISION

"200507221200Z" -- 04 July 2005 12:00:00 EST

DESCRIPTION

"Initial version. Published as RFC xxxx." -- RFC-editor pls fill  
-- in xxx

::= { mib-2 XXX } -- assigned by IANA, see [section 18.1](#) for details

-- Top level components of this MIB module.

BFD Working Group

Expires January 2005

[Page 4]

---

Internet Draft

BFD-DRAFT-01-MIB

July 2004

bfdNotifications OBJECT IDENTIFIER ::= { bfdMIB 0 }

bfdObjects OBJECT IDENTIFIER ::= { bfdMIB 1 }

bfdConformance OBJECT IDENTIFIER ::= { bfdMIB 3 }

bfdScalarObjects OBJECT IDENTIFIER ::= { bfdObjects 1 }

-- Textual Conventions

BfdSessIndexTC ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current  
DESCRIPTION  
"An index used to uniquely identify BFD sessions."  
SYNTAX Unsigned32 (1..4294967295)

BfdInterval ::= TEXTUAL-CONVENTION  
STATUS current  
DESCRIPTION  
"The BFD interval delay in microseconds."  
SYNTAX Unsigned32 (1..4294967295)

BfdDiag ::= TEXTUAL-CONVENTION  
STATUS current  
DESCRIPTION  
"A common BFD diagnostic code."

SYNTAX INTEGER { noDiagnostic(1),  
controlDetectionTimeExpired(2),  
echoFunctionFailed(3),  
neighborSignaledSessionDown(4),  
forwardingPlaneReset(5),  
pathDown(6),  
concatenatedPathDown(7),  
administrativelyDown(8),  
reverseConcatenatedPathDown (9)  
}

-- BFD General Variables

-- These parameters apply globally to the Router's  
-- BFD Process.

bfdAdminStatus OBJECT-TYPE

SYNTAX INTEGER { enabled(1), disabled(2) }  
MAX-ACCESS read-write  
STATUS current  
DESCRIPTION

"The global administrative status of BFD in this router.  
The value 'enabled' denotes that the BFD Process is

```

        active on at least one interface; 'disabled' disables
        it on all interfaces."
    DEFVAL { enabled }
    ::= { bfdScalarObjects 1 }

bfdVersionNumber OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The current version number of the BFD protocol."
    REFERENCE
        " BFD Version 0 (draft-katz-ward-bfd-02.txt)"
    DEFVAL { 0 }
    ::= { bfdScalarObjects 3 }

-- BFD Session Table
-- The BFD Session Table specifies BFD session specific
-- information.

bfdSessTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF BfdSessEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The BFD Session Table describes the BFD sessions."
    REFERENCE
        "BFD Version 0 (draft-katz-ward-bfd-02.txt)"
    ::= { bfdObjects 2 }

bfdSessEntry OBJECT-TYPE
    SYNTAX      BfdSessEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The BFD Session Entry describes BFD session."
    INDEX { bfdSessIndex }
    ::= { bfdSessTable 1 }

BfdSessEntry ::= SEQUENCE {
    bfdSessIndex
                                BfdSessIndexTC,

```

```

bfdSessApplicationId      Unsigned32,
bfdSessDiscriminator      Unsigned32,
bfdSessRemoteDiscr       Unsigned32,
bfdSessUdpPort            InetPortNumber,
bfdSessState              INTEGER,
bfdSessRemoteHeardFlag    TruthValue,
bfdSessDiag               Unsigned32,
bfdSessOperMode           INTEGER,
bfdSessDemandModeDesiredFlag TruthValue,
bfdSessEchoFuncModeDesiredFlag TruthValue,
bfdSessControlPlanIndepFlag TruthValue,
bfdSessAddrType           InetAddressType,
bfdSessAddr               InetAddress,
bfdSessDesiredMinTxInterval BfdInterval,
bfdSessDesiredMinRxInterval BfdInterval,
bfdSessDesiredMinEchoRxInterval BfdInterval,
bfdSessDetectMult         Unsigned32,
bfdSessStorType           StorageType,
bfdSessRowStatus          RowStatus,
bfdSessAuthPresFlag       TruthValue,
bfdSessAuthenticationType INTEGER
}

```

```

bfdSessIndex OBJECT-TYPE
SYNTAX      BfdSessIndexTC
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "This object contains an index used to represent a
    unique BFD session on this device."
 ::= { bfdSessEntry 1 }

```

```

bfdSessApplicationId OBJECT-TYPE
SYNTAX      Unsigned32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "This object contains an index used to indicate
    a local application which owns or maintains this
    BFD session. For instance, the MPLS VPN process may
    maintain a subset of the total number of BFD
    sessions. This application ID provides a convenient
    way to segregate sessions by the applications which
    maintain them."
 ::= { bfdSessEntry 2 }

```

```

bfdSessDiscriminator      OBJECT-TYPE
SYNTAX      Unsigned32 (1..4294967295)

```



Internet Draft

BFD-DRAFT-01-MIB

July 2004

```
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "This object specifies the local discriminator for this BFD
    session, used to uniquely identify it."
 ::= { bfdSessEntry 3 }

bfdSessRemoteDiscr OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object specifies the session discriminator chosen
        by the remote system for this BFD session."
 ::= { bfdSessEntry 4 }

bfdSessUdpPort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The UDP Port for BFD. The default value is the
        well-known value for this port."
    REFERENCE
        "draft-katz-ward-bfd-02.txt and
        draft-raggarwa-mpls-bfd-00.txt"
    DEFVAL { 0 }
 ::= { bfdSessEntry 5 }

bfdSessState OBJECT-TYPE
    SYNTAX      INTEGER {
        adminDown(1),
        down(2),
        init(3),
        up(4)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The perceived state of the BFD session."
 ::= { bfdSessEntry 6 }
```

bfdSessRemoteHeardFlag OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object specifies status of BFD packet reception from

the remote system. Specifically, it is set to true(1) if the local system is actively receiving BFD packets from the remote system, and is set to false(0) if the local system has not received BFD packets recently (within the detection time) or if the local system is attempting to tear down the BFD session."

::= { bfdSessEntry 7 }

bfdSessDiag OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS accessible-for-notify

STATUS current

DESCRIPTION

"A diagnostic code specifying the local system's reason for the last transition of the session from up(1) to some other state."

::= { bfdSessEntry 8 }

bfdSessOperMode OBJECT-TYPE

SYNTAX INTEGER { asyncModeWEchoFun(1),  
asynchModeWOEchoFun(2),  
demandModeWEchoFunction(3),  
demandModeWOEchoFunction(4)  
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object specifies current operating mode that BFD session is operating in.

A value of AsyncModeWEchoFun(1) ...

A value of AsynchModeWOEchoFun(2) ...

A value of DemandModeWEchoFunction(3) ...

```
        A value of DemandModeWOEchoFunction(4) ...
"
 ::= { bfdSessEntry 9 }
```

bfdSessDemandModeDesiredFlag OBJECT-TYPE

```
SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
```

DESCRIPTION

```
"This object indicates that the local system's
desire to use Demand mode. Specifically, it is set
to true(1) if the local system wishes to use
Demand mode or false(0) if not"
```

```
DEFVAL { false }
 ::= { bfdSessEntry 10 }
```

bfdSessEchoFuncModeDesiredFlag OBJECT-TYPE

```
SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
```

DESCRIPTION

```
"This object indicates that the local system's
desire to use Echo mode. Specifically, it is set
to true(1) if the local system wishes to use
Echo mode or false(0) if not"
```

```
DEFVAL { false }
 ::= { bfdSessEntry 11 }
```

bfdSessControlPlanIndepFlag OBJECT-TYPE

```
SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
```

DESCRIPTION

```
"This object indicates that the local system's
ability to continue to function through a disruption of
the control plane. Specifically, it is set
to true(1) if the local system BFD implementation is
independent of the control plane. Otherwise, the
value is set to false(0)"
```

```
DEFVAL { false }
```

```
::= { bfdSessEntry 12 }
```

```
bfdSessAddrType OBJECT-TYPE
SYNTAX          InetAddressType
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "This object specifies IP address of the interface
    associated with this BFD session.

    Only values unknown(0), ipv4(1) or ipv6(2)
    have to be supported.

    A value of unknown(0) is allowed only when
    the outgoing interface is of type point-to-point, or
    when the BFD session is not associated with a specific
    interface.

    If any other unsupported values are attempted in a set
    operation, the agent MUST return an inconsistentValue
    error.
"
::= { bfdSessEntry 13 }
```

```
bfdSessAddr OBJECT-TYPE
SYNTAX          InetAddress
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "This object specifies IP address of the interface
    associated with this BFD session.
    It can also be used to enabled BFD on a specific
    interface. The value is set to zero when BFD session is not
    associated with a specific interface. "
::= { bfdSessEntry 14 }
```

```
bfdSessDesiredMinTxInterval OBJECT-TYPE
SYNTAX          BfdInterval
MAX-ACCESS      read-create
STATUS          current
```

DESCRIPTION

"This object specifies the minimum interval, in microseconds, that the local system would like to use when transmitting BFD Control packets."

::= { bfdSessEntry 15 }

bfdSessDesiredMinRxInterval OBJECT-TYPE

SYNTAX BfdInterval

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the minimum interval, in microseconds, between received BFD Control packets the local system is capable of supporting."

::= { bfdSessEntry 16 }

bfdSessDesiredMinEchoRxInterval OBJECT-TYPE

SYNTAX BfdInterval

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the minimum interval, in microseconds, between received BFD Echo packets that this system is capable of supporting."

::= { bfdSessEntry 17 }

bfdSessDetectMult OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the Detect time multiplier."  
::= { bfdSessEntry 18 }

bfdSessStorType OBJECT-TYPE

SYNTAX StorageType

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This variable indicates the storage type for this

object. Conceptual rows having the value 'permanent' need not allow write-access to any columnar objects in the row."  
 ::= { bfdSessEntry 19 }

bfdSessRowStatus OBJECT-TYPE

SYNTAX RowStatus  
MAX-ACCESS read-create  
STATUS current

DESCRIPTION

"This variable is used to create, modify, and/or delete a row in this table. When a row in this table has a row in the active(1) state, no objects in this row can be modified except the bfdSessRowStatus and bfdSessStorageType."

::= { bfdSessEntry 20 }

bfdSessAuthPresFlag OBJECT-TYPE

SYNTAX TruthValue  
MAX-ACCESS read-create  
STATUS current

DESCRIPTION

"This object indicates that the local system's desire to use Authentication. Specifically, it is set to true(1) if the local system wishes the session to be authenticated or false(0) if not"

DEFVAL { false }

::= { bfdSessEntry 21 }

bfdSessAuthenticationType OBJECT-TYPE

SYNTAX INTEGER { simplePassword(1),  
keyedMD5(2),  
meticulousKeyedMD5(3),  
keyedSHA1(4),  
meticulousKeyedSHA1(5)

}

MAX-ACCESS read-create  
STATUS current

DESCRIPTION

field is valid only when the Authentication Present bit is set"

::= { bfdSessEntry 22 }

-- BFD Session Performance Table

bfdSessPerfTable OBJECT-TYPE

SYNTAX SEQUENCE OF BfdSessPerfEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table specifies BFD Session performance counters."

::= { bfdObjects 3 }

bfdSessPerfEntry OBJECT-TYPE

SYNTAX BfdSessPerfEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An entry in this table is created by a BFD-enabled node for every BFD Session. bfdCounterDiscontinuityTime is used to indicate potential discontinuity for all counter objects in this table."

AUGMENTS { bfdSessEntry }

::= { bfdSessPerfTable 1 }

BfdSessPerfEntry ::= SEQUENCE {

bfdSessPerfPktIn Counter32,

bfdSessPerfPktOut Counter32,

bfdSessUpTime TimeStamp,

bfdSessPerfLastSessDownTime TimeStamp,

bfdSessPerfLastCommLostDiag BfdDiag,

bfdSessPerfSessUpCount Counter32,

bfdSessPerfDiscTime TimeStamp,

-- High Capacity Counters

bfdSessPerfPktInHC Counter64,

bfdSessPerfPktOutHC Counter64

}

-- Ed Note: should we add per-diag code counts here,

bfdSessPerfPktIn OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of BFD messages received for this BFD

---

```
session."
 ::= { bfdSessPerfEntry 1 }

bfdSessPerfPktOut OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of BFD messages sent for this BFD session."
 ::= { bfdSessPerfEntry 2 }

bfdSessUpTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime on the most recent occasion at which
         the session came up. If no such up event exists this object
         contains a zero value."
 ::= { bfdSessPerfEntry 3 }

bfdSessPerfLastSessDownTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime on the most recent occasion at which
         the last time communication was lost with the neighbor. If
         no such down event exist this object contains a zero value."
 ::= { bfdSessPerfEntry 4 }

bfdSessPerfLastCommLostDiag OBJECT-TYPE
    SYNTAX      BfdDiag
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The BFD diag code for the last time communication was lost
         with the neighbor. If no such down event exists this object
         contains a zero value."
 ::= { bfdSessPerfEntry 5 }

bfdSessPerfSessUpCount OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
```



DESCRIPTION

"The number of times this session has gone into the Up state since the router last rebooted."

BFD Working Group

Expires January 2005

[Page 14]

---

Internet Draft

BFD-DRAFT-01-MIB

July 2004

::= { bfdSessPerfEntry 6 }

bfdSessPerfDiscTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime on the most recent occasion at which any

one or more of the session counters suffered a discontinuity.

The relevant counters are the specific instances associated with this BFD session of any Counter32 object contained in the

BfdSessPerfTable. If no such discontinuities have occurred since the last re-initialization of the local management subsystem,

then this object contains a zero value."

::= { bfdSessPerfEntry 7 }

bfdSessPerfPktInHC OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This value represents the total number of BFD messages received for this BFD session. It MUST be equal to the least significant 32 bits of bfdSessPerfPktIn if bfdSessPerfPktInHC is supported according to the rules spelled out in [RFC2863](#)."

::= { bfdSessPerfEntry 8 }

bfdSessPerfPktOutHC OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This value represents the total number of total number of BFD messages transmitted for this BFD session. It MUST be equal to the least significant 32 bits of bfdSessPerfPktIn if bfdSessPerfPktOutHC is supported according to the rules spelled out in [RFC2863](#)."  
 ::= { bfdSessPerfEntry 9 }

-- BFD Session Mapping Table

BFD Working Group Expires January 2005 [Page 15]

---

Internet Draft BFD-DRAFT-01-MIB July 2004

bfdSessMapTable OBJECT-TYPE

SYNTAX SEQUENCE OF BfdSessMapEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The BFD Session Mapping Table maps the complex indexing of the BFD sessions to the flat BfdIndex used in the BfdSessionTable.

Implementors need to be aware that if the value of the bfdSessAddr (an OID) has more than 111 sub-identifiers, then OIDs of column instances in this table will have more than 128 sub-identifiers and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3.

"

REFERENCE

"BFD Version 0 ([draft-katz-ward-bfd-02.txt](#))"

::= { bfdObjects 4 }

bfdSessMapEntry OBJECT-TYPE

SYNTAX BfdSessMapEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The BFD Session Entry describes BFD session that is mapped to this index.

Implementors need to be aware that if the value of

the mplsInSegmentMapLabelPtrIndex (an OID) has more than 111 sub-identifiers, then OIDs of column instances in this table will have more than 128 sub-identifiers and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3."

```
INDEX { bfdSessApplicationId,  
        bfdSessDiscriminator,  
        bfdSessAddrType,  
        bfdSessAddr
```

```
}
```

```
::= { bfdSessMapTable 1 }
```

```
BfdSessMapEntry ::= SEQUENCE {  
    bfdSessMapBfdIndex          BfdSessIndexTC  
}
```

```
bfdSessMapBfdIndex OBJECT-TYPE  
SYNTAX          BfdSessIndexTC  
MAX-ACCESS      read-only
```

BFD Working Group

Expires January 2005

[Page 16]

---

Internet Draft

BFD-DRAFT-01-MIB

July 2004

```
STATUS          current
```

```
DESCRIPTION
```

```
"This object specifies the BfdIndex referred to by  
the indexes of this row. In essence, a mapping is  
provided between these indexes and the BfdSessTable."
```

```
::= { bfdSessMapEntry 1 }
```

```
-- Notification Configuration
```

```
bfdSessNotificationsEnable OBJECT-TYPE
```

```
SYNTAX          TruthValue
```

```
MAX-ACCESS      read-write
```

```
STATUS          current
```

```
DESCRIPTION
```

```
"If this object is set to true(1), then it enables  
the emission of bfdSessUp and bfdSessDown  
notifications; otherwise these notifications are not  
emitted."
```

```
REFERENCE
```

```
"See also RFC3413 for explanation that  
notifications are under the ultimate control of the
```

```
        MIB modules in this document."
DEFVAL { false }
 ::= { bfdScalarObjects 4 }
```

bfdSessUp NOTIFICATION-TYPE

```
OBJECTS      { bfdSessDiag, -- low range value
               bfdSessDiag -- high range value
}
```

```
}
```

```
STATUS      current
```

```
DESCRIPTION
```

"This notification is generated when the bfdSessState object for one or more contiguous entries in bfdSessTable are about to enter the up(2) state from some other state. The included values of bfdSessDiag MUST both be set equal to this new state (i.e: up(1)). The two instances of bfdSessDiag in this notification indicate the range of indexes that are affected. Note that all the indexes of the two ends of the range can be derived from the instance identifiers of these two objects. For the cases where a contiguous range of sessions have transitioned into the up(1) state at roughly the same time, the device SHOULD issue a single notification for each range of contiguous indexes in an effort to minimize the emission of a large number of notifications. If a notification has to be issued for just a single bfdSessEntry, then

```
        the instance identifier (and values) of the two
        bfdSessDiag objects MUST be the identical."
 ::= { bfdNotifications 1 }
```

bfdSessDown NOTIFICATION-TYPE

```
OBJECTS      { bfdSessDiag, -- low range value
               bfdSessDiag -- high range value
}
```

```
}
```

```
STATUS      current
```

```
DESCRIPTION
```

"This notification is generated when the bfdSessState object for one or more contiguous entries in bfdSessTable are about to enter the down(4)

or adminDown(5) states from some other state. The included values of bfdSessDiag MUST both be set equal to this new state (i.e: down(4) or adminDown(5)). The two instances of bfdSessDiag in this notification indicate the range of indexes that are affected. Note that all the indexes of the two ends of the range can be derived from the instance identifiers of these two objects. For cases where a contiguous range of sessions have transitioned into the down(4) or adminDown(5) states at roughly the same time, the device SHOULD issue a single notification for each range of contiguous indexes in an effort to minimize the emission of a large number of notifications. If a notification has to be issued for just a single bfdSessEntry, then the instance identifier (and values) of the two bfdSessDiag objects MUST be the identical."

```
::= { bfdNotifications 2 }
```

```
-- Ed Note: We need to add notification for changes  
-- when the two ends automatically negotiate to a new detection time  
-- value or when detection multiplier changes.  
-- Similarly, changes in the operating mode (bfdSessOperMode)  
-- also need to be notified.
```

```
-- Module compliance.
```

```
bfdGroups
```

```
  OBJECT IDENTIFIER ::= { bfdConformance 1 }
```

```
bfdCompliances
```

```
  OBJECT IDENTIFIER ::= { bfdConformance 2 }
```

```
-- Compliance requirement for fully compliant implementations.
```

```
bfdModuleFullCompliance MODULE-COMPLIANCE
```

STATUS current

DESCRIPTION "Compliance statement for agents that provide full support for BFD-MIB. Such devices can then be monitored and also be configured using this MIB module."

```

MODULE -- This module.
MANDATORY-GROUPS {
    bfdSessionGroup,
    bfdSessionPerfGroup,
    bfdSessionPerfHCGroup,
    bfdNotificationGroup
}

GROUP          bfdSessionPerfHCGroup
DESCRIPTION    "This group is mandatory for those bfdPerfTable
                entries for which any of the objects
                bfdSessPerfPktInHC or bfdSessPerfPktOutHC
                wraps around too quickly
                based on the criteria specified in RFC 2863 for
                high-capacity counters."

GROUP          bfdNotificationGroup
DESCRIPTION    "This group is only mandatory for those
                implementations which can efficiently implement
                the notifications contained in this group."

OBJECT         bfdSessAddrType
SYNTAX         InetAddressType { unknown(0), ipv4(1), ipv6(2) }
DESCRIPTION    "Only unknown(0), ipv4(1) and ipv6(2) support
                is required."

OBJECT         bfdSessAddr
SYNTAX         InetAddress (SIZE(0|4|16))
DESCRIPTION    "An implementation is only required to support
                unknown(0), ipv4(1) and ipv6(2) sizes."

 ::= { bfdCompliances 1 }

-- Read-Only Conformance TBD...

-- Units of conformance.

bfdSessionGroup OBJECT-GROUP
  OBJECTS {
    bfdSessNotificationsEnable,
    bfdAdminStatus,

```

```

        bfdVersionNumber,
        bfdSessApplicationId,
        bfdSessDiscriminator,
        bfdSessAddrType,
        bfdSessAddr,
        bfdSessRemoteDiscr,
        bfdSessUdpPort,
        bfdSessState,
        bfdSessRemoteHeardFlag,
        bfdSessDiag,
        bfdSessOperMode,
        bfdSessDemandModeDesiredFlag,
        bfdSessEchoFuncModeDesiredFlag,
        bfdSessControlPlanIndepFlag,
        bfdSessDesiredMinTxInterval,
        bfdSessDesiredMinRxInterval,
        bfdSessDesiredMinEchoRxInterval,
        bfdSessDetectMult,
        bfdSessStorType,
        bfdSessRowStatus,
        bfdSessMapBfdIndex,
        bfdSessAuthPresFlag,
        bfdSessAuthenticationType
    }
    STATUS current
    DESCRIPTION
        "Collection of objects needed for BFD sessions."
    ::= { bfdGroups 1 }

```

```

bfdSessionPerfGroup OBJECT-GROUP
    OBJECTS {
        bfdSessPerfPktIn,
        bfdSessPerfPktOut,
        bfdSessUpTime,
        bfdSessPerfLastSessDownTime,
        bfdSessPerfLastCommLostDiag,
        bfdSessPerfSessUpCount,
        bfdSessPerfDiscTime
    }
    STATUS current
    DESCRIPTION
        "Collection of objects needed to monitor the
        performance of BFD sessions."
    ::= { bfdGroups 2 }

```

```

bfdSessionPerfHCGroup OBJECT-GROUP
    OBJECTS {

```

Internet Draft

BFD-DRAFT-01-MIB

July 2004

```
        bfdSessPerfPktInHC,
        bfdSessPerfPktOutHC
    }
    STATUS current
    DESCRIPTION
        "Collection of objects needed to monitor the
        performance of BFD sessions for which the
        values of bfdSessPerfPktIn, bfdSessPerfPktOut
        wrap around too quickly."
    ::= { bfdGroups 3 }

bfdNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS {
        bfdSessUp,
        bfdSessDown
    }
    STATUS current
    DESCRIPTION
        "Set of notifications implemented in this
        module."
    ::= { bfdGroups 4 }

END
```

## 6. Security Considerations

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP.



SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure "for example by using IPsec", even then, there is no control as to who on the secure network is allowed to access and GET/SET "read/change/create/delete" the objects in these MIB modules.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework "see [\[RFC3410\], section 8](#)",

BFD Working Group

Expires January 2005

[Page 21]

---

Internet Draft

BFD-DRAFT-01-MIB

July 2004

including full support for the SNMPv3 cryptographic mechanisms "for authentication and privacy".

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module, is properly configured to give access to the objects only to those principals "users" that have legitimate rights to indeed GET or SET "change/create/delete" them.

## [7.](#) Acknowledgements

We would like to thank David Ward for his comments and suggestions.

## [8.](#) Reference

### [8.1](#) Normative References

- [BFD] Katz, D., and Ward, D., "Bidirectional Forwarding Detection", [draft-ietf-bfd-base-02.txt](#).
- [BFD-SHARED] Bidirectional Forwarding Detection over Shared Interfaces, work in progress.
- [BFD-LSP] Aggarwal, R., Kompella, K., T. D. Nadeau, and G. Swallow BFD For MPLS LSPs, [draft-ietf-bfd-mpls-01.txt](#).

### [8.2](#) Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D. and B. Stewart, "Introduction and Applicability Statements for

Internet-Standard Management Framework", [RFC 3410](#),  
December 2002.

[RFC3413] Levi, D., Meyer, P., Stewart, B.,  
"SNMP Applications", [RFC 3413](#), December 2002.

[RFC2434] Narten, T. and H. Alvestrand., "Guidelines for Writing  
an IANA Considerations Section in RFCs", [BCP 26](#), [RFC  
2434](#), October 1998.

## 9. Authors' Addresses

Thomas D. Nadeau  
Cisco Systems, Inc.  
300 Beaver Brook Road  
Boxboro, MA 01719

BFD Working Group Expires January 2005 [Page 22]

---

Internet Draft BFD-DRAFT-01-MIB July 2004

Phone: +1-978-936-1470

Email: [tnadeau@cisco.com](mailto:tnadeau@cisco.com)

Zafar Ali  
Cisco Systems Inc.  
100 South Main St. #200  
Ann Arbor, MI 48104, USA.  
Phone: +1-734-276-2459  
Email: [zali@cisco.com](mailto:zali@cisco.com)

## 10. Full Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## 11. IANA Considerations

There is one MIB module contained in this document. The following "IANA Considerations" subsection requests IANA for a new assignment under the mib-2 subtree. New assignments can only be made via a Standards Action as specified in [[RFC2434](#)].

### 11.1. IANA Considerations for BFD-STD-MIB

The IANA is requested to assign { mib-2 XXX } to the MPLS-L3VPN-STD-MIB module specified in this document.

## 12. Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

BFD Working Group	Expires January 2005	[Page 23]
-------------------	----------------------	-----------

---

Internet Draft	BFD-DRAFT-01-MIB	July 2004
----------------	------------------	-----------

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

