

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: May 25, 2014

T. Nadeau  
Juniper Networks  
Z. Ali  
N. Akiya  
Cisco Systems  
November 21, 2013

BFD Management Information Base  
draft-ietf-bfd-mib-16

## Abstract

This draft defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects for modeling Bidirectional Forwarding Detection (BFD) protocol.

## Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [RFC 2119](#) [[RFC2119](#)].

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 25, 2014.

## Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

Internet-Draft

BFD-STD-MIB

November 2013

This document is subject to [BCP 78](http://trustee.ietf.org/license-info) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	The Internet-Standard Management Framework . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">3.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">4.</a>	Brief Description of MIB Objects . . . . .	<a href="#">3</a>
<a href="#">4.1.</a>	General Variables . . . . .	<a href="#">3</a>
<a href="#">4.2.</a>	Session Table (bfdSessionTable) . . . . .	<a href="#">3</a>
<a href="#">4.3.</a>	Session Performance Table (bfdSessionPerfTable) . . . . .	<a href="#">3</a>
4.4.	BFD Session Discriminator Mapping Table (bfdSessDiscMapTable) . . . . .	<a href="#">3</a>
<a href="#">4.5.</a>	BFD Session IP Mapping Table (bfdSessIpMapTable) . . . . .	<a href="#">3</a>
<a href="#">5.</a>	BFD MIB Module Definitions . . . . .	<a href="#">4</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">34</a>
<a href="#">7.</a>	IANA Considerations . . . . .	<a href="#">36</a>
<a href="#">8.</a>	Acknowledgments . . . . .	<a href="#">36</a>
<a href="#">9.</a>	References . . . . .	<a href="#">36</a>
<a href="#">9.1.</a>	Normative References . . . . .	<a href="#">36</a>
<a href="#">9.2.</a>	Informative References . . . . .	<a href="#">37</a>

## [1.](#) The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#)

[\[RFC2580\]](#).

## 2. Introduction

Nadeau, et al.

Expires May 25, 2014

[Page 2]

---

Internet-Draft

BFD-STD-MIB

November 2013

This memo defines an portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects to configure and/or monitor Bi-Directional Forwarding Detection for [\[RFC5880\]](#), [\[RFC5881\]](#) and [\[RFC5883\]](#), BFD versions 0 and/or 1, on devices supporting this feature.

## 3. Terminology

This document adopts the definitions, acronyms and mechanisms described in [\[RFC5880\]](#), [\[RFC5881\]](#) and [\[RFC5883\]](#). Unless otherwise stated, the mechanisms described therein will not be re-described here.

## 4. Brief Description of MIB Objects

This section describes objects pertaining to BFD. The MIB objects are derived from [\[RFC5880\]](#), [\[RFC5881\]](#) and [\[RFC5883\]](#), and also include textual conventions defined in [\[I-D.ietf-bfd-tc-mib\]](#).

### 4.1. General Variables

The General Variables are used to identify parameters that are global to the BFD process.

### 4.2. Session Table (bfdSessionTable)

The session table is used to identify a BFD session between a pair of nodes.

### 4.3. Session Performance Table (bfdSessionPerfTable)

The session performance table is used for collecting BFD performance counters on a per session basis. This table is an AUGMENT to the bfdSessionTable.

#### [4.4.](#) BFD Session Discriminator Mapping Table (bfdSessDiscMapTable)

The BFD Session Discriminator Mapping Table maps a local discriminator value to associated BFD session's IANAbfdSessIndexTC used in the bfdSessionTable.

#### [4.5.](#) BFD Session IP Mapping Table (bfdSessIpMapTable)

The BFD Session IP Mapping Table maps, given bfdSessInterface, bfdSessSrcAddrType, bfdSessSrcAddr, bfdSessDstAddrType, and bfdSessDstAddr, to an associated BFD session's IANAbfdSessIndexTC used in the bfdSessionTable. This table SHOULD contains those BFD sessions that are of IP type.

### [5.](#) BFD MIB Module Definitions

This MIB module makes references to the following documents. [\[RFC2579\]](#), [\[RFC2580\]](#), [\[RFC2863\]](#), [\[RFC4001\]](#), and [\[RFC3413\]](#).

```
BFD-STD-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,  
        mib-2, Integer32, Unsigned32, Counter32, Counter64  
    FROM SNMPv2-SMI
```

```
    TruthValue, RowStatus, StorageType, TimeStamp  
    FROM SNMPv2-TC
```

```
    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP  
    FROM SNMPv2-CONF
```

```
    InterfaceIndexOrZero  
    FROM IF-MIB
```

```
    InetAddress, InetAddressType, InetPortNumber  
    FROM INET-ADDRESS-MIB
```

IANAbfdSessIndexTC, IANAbfdIntervalTC, IANAbfdMultiplierTC,  
IANAbfdDiagTC, IANAbfdSessTypeTC, IANAbfdSessOperModeTC,  
IANAbfdCtrlDestPortNumberTC, IANAbfdCtrlSourcePortNumberTC,  
IANAbfdSessStateTC, IANAbfdSessAuthenticationTypeTC,  
IANAbfdSessAuthenticationKeyTC  
FROM IANA-BFD-TC-STD-MIB;

bfdMIB MODULE-IDENTITY

LAST-UPDATED "201311211200Z" -- 21 Nov. 2013 12:00:00 EST  
ORGANIZATION "IETF Bidirectional Forwarding Detection  
Working Group"

CONTACT-INFO

"Thomas D. Nadeau  
Juniper Networks  
Email: tnadeau@lucidvision.com

Zafar Ali  
Cisco Systems, Inc.

Nadeau, et al.

Expires May 25, 2014

[Page 4]

---

Internet-Draft

BFD-STD-MIB

November 2013

Email: zali@cisco.com

Nobo Akiya  
Cisco Systems, Inc.  
Email: nobo@cisco.com

Comments about this document should be emailed directly  
to the BFD working group mailing list at  
rtg-bfd@ietf.org"

DESCRIPTION

"Bidirectional Forwarding Management Information Base."

REVISION "201311211200Z" -- 21 Nov. 2013 12:00:00 EST

DESCRIPTION

"Initial version. Published as RFC xxxx."

-- RFC Ed.: RFC-editor pls fill in xxxx

::= { mib-2 XXX }

-- RFC Ed.: assigned by IANA, see [section 7.1](#) for details

-- Top level components of this MIB module.

bfdNotifications OBJECT IDENTIFIER ::= { bfdMIB 0 }

```

bfdObjects      OBJECT IDENTIFIER ::= { bfdMIB 1 }

bfdConformance OBJECT IDENTIFIER ::= { bfdMIB 2 }

bfdScalarObjects OBJECT IDENTIFIER ::= { bfdObjects 1 }

-- BFD General Variables

-- These parameters apply globally to the Systems'
-- BFD Process.

bfdAdminStatus OBJECT-TYPE
    SYNTAX      INTEGER {
        enabled(1),
        disabled(2)
    }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The global administrative status of BFD in this device.
        The value 'enabled' denotes that the BFD Process is
        active on at least one interface; 'disabled' disables
        it on all interfaces."
    DEFVAL { enabled }
    ::= { bfdScalarObjects 1 }

```

```

bfdSessNotificationsEnable OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "If this object is set to true(1), then it enables
        the emission of bfdSessUp and bfdSessDown
        notifications; otherwise these notifications are not
        emitted."
    REFERENCE
        "See also RFC3413 for explanation that
        notifications are under the ultimate control of the
        MIB modules in this document."
    DEFVAL { false }
    ::= { bfdScalarObjects 2 }

```

-- BFD Session Table  
-- The BFD Session Table specifies BFD session specific  
-- information.

bfdSessTable OBJECT-TYPE  
SYNTAX SEQUENCE OF BfdSessEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"The BFD Session Table describes the BFD sessions."  
REFERENCE  
"Katz, D. and D. Ward, Bidirectional Forwarding  
Detection (BFD), [RFC 5880](#), June 2012."  
 ::= { bfdObjects 2 }

bfdSessEntry OBJECT-TYPE  
SYNTAX BfdSessEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"The BFD Session Entry describes BFD session."  
INDEX { bfdSessIndex }  
 ::= { bfdSessTable 1 }

BfdSessEntry ::= SEQUENCE {  
bfdSessIndex IANAbfdSessIndexTC,  
bfdSessVersionNumber Unsigned32,  
bfdSessType IANAbfdSessTypeTC,  
bfdSessDiscriminator Unsigned32,  
bfdSessRemoteDiscr Unsigned32,  
bfdSessDestinationUdpPort IANAbfdCtrlDestPortNumberTC,  
bfdSessSourceUdpPort IANAbfdCtrlSourcePortNumberTC,

bfdSessEchoSourceUdpPort InetPortNumber,  
bfdSessAdminStatus INTEGER,  
bfdSessState IANAbfdSessStateTC,  
bfdSessRemoteHeardFlag TruthValue,  
bfdSessDiag IANAbfdDiagTC,  
bfdSessOperMode IANAbfdSessOperModeTC,  
bfdSessDemandModeDesiredFlag TruthValue,  
bfdSessControlPlaneIndepFlag TruthValue,

```

bfdSessMultipointFlag      TruthValue,
bfdSessInterface           InterfaceIndexOrZero,
bfdSessSrcAddrType        InetAddressType,
bfdSessSrcAddr             InetAddress,
bfdSessDstAddrType        InetAddressType,
bfdSessDstAddr            InetAddress,
bfdSessGTSM               TruthValue,
bfdSessGTSMTTL            Unsigned32,
bfdSessDesiredMinTxInterval IANAbfdIntervalTC,
bfdSessReqMinRxInterval   IANAbfdIntervalTC,
bfdSessReqMinEchoRxInterval IANAbfdIntervalTC,
bfdSessDetectMult         IANAbfdMultiplierTC,
bfdSessNegotiatedInterval IANAbfdIntervalTC,
bfdSessNegotiatedEchoInterval IANAbfdIntervalTC,
bfdSessNegotiatedDetectMult IANAbfdMultiplierTC,
bfdSessAuthPresFlag       TruthValue,
bfdSessAuthenticationType IANAbfdSessAuthenticationTypeTC,
bfdSessAuthenticationKeyID Integer32,
bfdSessAuthenticationKey  IANAbfdSessAuthenticationKeyTC,
bfdSessStorageType        StorageType,
bfdSessRowStatus           RowStatus
}

```

bfdSessIndex OBJECT-TYPE

SYNTAX IANAbfdSessIndexTC

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This object contains an index used to represent a unique BFD session on this device."

::= { bfdSessEntry 1 }

bfdSessVersionNumber OBJECT-TYPE

SYNTAX Unsigned32 (0..7)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The version number of the BFD protocol that this session is running in. Write access is available for this object to provide ability to set desired version for this



REFERENCE

"Katz, D. and D. Ward, Bidirectional Forwarding Detection (BFD), [RFC 5880](#), June 2012."

DEFVAL { 1 }

::= { bfdSessEntry 2 }

bfdSessType OBJECT-TYPE

SYNTAX IANAbfdSessTypeTC

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the type of this BFD session."

::= { bfdSessEntry 3 }

bfdSessDiscriminator OBJECT-TYPE

SYNTAX Unsigned32 (1..4294967295)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the local discriminator for this BFD session, used to uniquely identify it."

::= { bfdSessEntry 4 }

bfdSessRemoteDiscr OBJECT-TYPE

SYNTAX Unsigned32 (0 | 1..4294967295)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object specifies the session discriminator chosen by the remote system for this BFD session. The value may be zero(0) if the remote discriminator is not yet known or if the session is in the down or adminDown(1) state."

REFERENCE

"[Section 6.8.6](#), from Katz, D. and D. Ward, Bidirectional Forwarding Detection (BFD), [RFC 5880](#), June 2012."

::= { bfdSessEntry 5 }

bfdSessDestinationUdpPort OBJECT-TYPE

SYNTAX IANAbfdCtrlDestPortNumberTC

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the destination UDP port number used for this BFD session's control packets. The value may be zero(0) if the session is in adminDown(1) state."

DEFVAL { 0 }

::= { bfdSessEntry 6 }

## bfdSessSourceUdpPort OBJECT-TYPE

SYNTAX IANAbfdCtrlSourcePortNumberTC

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"This object specifies the source UDP port number used for this BFD session's control packets. The value may be zero(0) if the session is in adminDown(1) state. Upon creation of a new BFD session via this MIB, the value of zero(0) specified would permit the implementation to choose its own source port number."

DEFVAL { 0 }

::= { bfdSessEntry 7 }

## bfdSessEchoSourceUdpPort OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"This object specifies the source UDP port number used for this BFD session's echo packets. The value may be zero(0) if the session is not running in the echo mode, or the session is in adminDown(1) state. Upon creation of a new BFD session via this MIB, the value of zero(0) would permit the implementation to choose its own source port number."

DEFVAL { 0 }

::= { bfdSessEntry 8 }

## bfdSessAdminStatus OBJECT-TYPE

SYNTAX INTEGER {  
stop(1),  
start(2)  
}

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"A transition from 'stop' to 'start' will start the BFD state machine for the session. The state machine will have an initial state of down. A transition from 'start' to 'stop' will cause the BFD session to be brought down to adminDown(1). Care should be used in providing write access to this object without adequate authentication."

DEFVAL { 2 }

::= { bfdSessEntry 9 }

bfdSessState OBJECT-TYPE

SYNTAX IANAbfdSessStateTC

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"BFD session state."

DEFVAL { 2 }

::= { bfdSessEntry 10 }

bfdSessRemoteHeardFlag OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object specifies status of BFD packet reception from the remote system. Specifically, it is set to true(1) if the local system is actively receiving BFD packets from the remote system, and is set to false(2) if the local system has not received BFD packets recently (within the detection time) or if the local system is attempting to tear down the BFD session."

REFERENCE

"Katz, D. and D. Ward, Bidirectional Forwarding Detection (BFD), [RFC 5880](#), June 2012."

DEFVAL { false }

::= { bfdSessEntry 11 }

bfdSessDiag OBJECT-TYPE

SYNTAX IANAbfdDiagTC

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A diagnostic code specifying the local system's reason for the last transition of the session from up(4) to some other state."

::= { bfdSessEntry 12 }

bfdSessOperMode OBJECT-TYPE

SYNTAX IANAbfdSessOperModeTC

MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
    "This object specifies current operating mode that BFD  
    session is operating in."  
 ::= { bfdSessEntry 13 }

bfdSessDemandModeDesiredFlag OBJECT-TYPE  
SYNTAX TruthValue

Nadeau, et al.

Expires May 25, 2014

[Page 10]

---

Internet-Draft

BFD-STD-MIB

November 2013

MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
    "This object indicates that the local system's  
    desire to use Demand mode. Specifically, it is set  
    to true(1) if the local system wishes to use  
    Demand mode or false(2) if not"  
DEFVAL { false }  
 ::= { bfdSessEntry 14 }

bfdSessControlPlaneIndepFlag OBJECT-TYPE

SYNTAX TruthValue  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
    "This object indicates that the local system's  
    ability to continue to function through a disruption of  
    the control plane. Specifically, it is set  
    to true(1) if the local system BFD implementation is  
    independent of the control plane. Otherwise, the  
    value is set to false(2)"  
DEFVAL { false }  
 ::= { bfdSessEntry 15 }

bfdSessMultipointFlag OBJECT-TYPE

SYNTAX TruthValue  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
    "This object indicates the Multipoint (M) bit for this  
    session. It is set to true(1) if Multipoint (M) bit is  
    set to 1. Otherwise, the value is set to false(2)"

```
DEFVAL { false }
 ::= { bfdSessEntry 16 }
```

bfdSessInterface OBJECT-TYPE

```
SYNTAX      InterfaceIndexOrZero
```

```
MAX-ACCESS  read-create
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"This object contains an interface index used to indicate
 the interface which this BFD session is running on. This
 value can be zero if there is no interface associated
 with this BFD session."
```

```
 ::= { bfdSessEntry 17 }
```

bfdSessSrcAddrType OBJECT-TYPE

```
SYNTAX      InetAddressType
```

```
MAX-ACCESS  read-create
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"This object specifies IP address type of the source IP
 address of this BFD session. Only values unknown(0),
 ipv4(1), ipv6(2), or ipv6z(4) have to be supported.
 The value of unknown(0) is allowed only when the session
 is singleHop(1) and the source IP address of this BFD
 session is derived from the outgoing interface, or when
 the BFD session is not associated with a specific
 interface. If any other unsupported values are attempted
 in a set operation, the agent MUST return an
 inconsistentValue error."
```

```
 ::= { bfdSessEntry 18 }
```

bfdSessSrcAddr OBJECT-TYPE

```
SYNTAX      InetAddress
```

```
MAX-ACCESS  read-create
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"This object specifies the source IP address of this BFD
 session."
```

```
 ::= { bfdSessEntry 19 }
```

bfdSessDstAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies IP address type of the neighboring IP address which is being monitored with this BFD session. Only values unknown(0), ipv4(1), ipv6(2), or ipv6z(4) have to be supported. The value of unknown(0) is allowed only when the session is singleHop(1) and the outgoing interface is of type point-to-point, or when the BFD session is not associated with a specific interface. If any other unsupported values are attempted in a set operation, the agent MUST return an inconsistentValue error."

::= { bfdSessEntry 20 }

bfdSessDstAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the neighboring IP address which is being monitored with this BFD session."

::= { bfdSessEntry 21 }

bfdSessGTSM OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Setting the value of this object to true(1) will enable GTSM protection of the BFD session. GTSM MUST be enabled on a singleHop(1) session if no authentication is in use."

REFERENCE

"[RFC5082](#), The Generalized TTL Security Mechanism (GTSM).  
[RFC5881, Section 5](#)"

DEFVAL { false }

::= { bfdSessEntry 22 }

bfdSessGTSM TTL OBJECT-TYPE

SYNTAX Unsigned32 (0..255)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object is valid only when bfdSessGTSM protection is enabled on the system. This object specifies the minimum allowed TTL for received BFD control packets. For singleHop(1) session, if GTSM protection is enabled, this object SHOULD be set to maximum TTL allowed for single hop. The value of zero(0) indicates that bfdSessGTSM is disabled."

REFERENCE

"[RFC5082](#), The Generalized TTL Security Mechanism (GTSM).  
[RFC5881, Section 5](#)"

DEFVAL { 0 }

::= { bfdSessEntry 23 }

bfdSessDesiredMinTxInterval OBJECT-TYPE

SYNTAX IANAbfdIntervalTC

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the minimum interval, in microseconds, that the local system would like to use when transmitting BFD Control packets. The value of zero(0) is reserved, and should not be used."

REFERENCE

"[Section 4.1](#) from Katz, D. and D. Ward, Bidirectional Forwarding Detection (BFD), [RFC 5880](#), June 2012."

::= { bfdSessEntry 24 }

bfdSessReqMinRxInterval OBJECT-TYPE

SYNTAX IANAbfdIntervalTC

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the minimum interval, in microseconds, between received BFD Control packets the local system is capable of supporting. The value of zero(0) can be specified when the transmitting system does not want the remote system to send any periodic BFD control packets."

REFERENCE

"[Section 4.1](#) from Katz, D. and D. Ward, Bidirectional

Forwarding Detection (BFD), [RFC 5880](#), June 2012."  
 ::= { bfdSessEntry 25 }

bfdSessReqMinEchoRxInterval OBJECT-TYPE

SYNTAX IANAbfdIntervalTC

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the minimum interval, in microseconds, between received BFD Echo packets that this system is capable of supporting. Value must be zero(0) if this is a multihop BFD session."

::= { bfdSessEntry 26 }

bfdSessDetectMult OBJECT-TYPE

SYNTAX IANAbfdMultiplierTC

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object specifies the Detect time multiplier."

::= { bfdSessEntry 27 }

bfdSessNegotiatedInterval OBJECT-TYPE

SYNTAX IANAbfdIntervalTC

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object specifies the negotiated interval, in microseconds, that the local system is transmitting BFD Control packets."

::= { bfdSessEntry 28 }

bfdSessNegotiatedEchoInterval OBJECT-TYPE

SYNTAX IANAbfdIntervalTC

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object specifies the negotiated interval, in microseconds, that the local system is transmitting BFD echo packets. Value is expected to be zero if the sessions is not running in echo mode."



```
::= { bfdSessEntry 29 }
```

bfdSessNegotiatedDetectMult OBJECT-TYPE

SYNTAX IANAbfdMultiplierTC

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object specifies the Detect time multiplier."

```
::= { bfdSessEntry 30 }
```

bfdSessAuthPresFlag OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object indicates that the local system's desire to use Authentication. Specifically, it is set to true(1) if the local system wishes the session to be authenticated or false(2) if not."

REFERENCE

"Sections [4.2](#) - [4.4](#) from Katz, D. and D. Ward, Bidirectional Forwarding Detection (BFD), [RFC 5880](#), June 2012."

DEFVAL { false }

```
::= { bfdSessEntry 31 }
```

bfdSessAuthenticationType OBJECT-TYPE

SYNTAX IANAbfdSessAuthenticationTypeTC

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The Authentication Type used for this BFD session. This field is valid only when the Authentication Present bit is set. Max-access to this object as well as other authentication related objects are set to read-create in order to support management of a single key ID at a time, key rotation is not handled. Key update in practice must be done by atomic update using a set containing all affected objects in the same varBindList or otherwise risk the session dropping. Value -1 indicates that no authentication is in use for this session."

REFERENCE

"Sections [4.2](#) - [4.4](#) from Katz, D. and D. Ward,

Bidirectional Forwarding Detection (BFD), [RFC 5880](#),  
June 2012."

DEFVAL { -1 }  
::= { bfdSessEntry 32 }

bfdSessAuthenticationKeyID OBJECT-TYPE  
SYNTAX Integer32 (-1 | 0..255)  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
"The authentication key ID in use for this session. This  
object permits multiple keys to be active simultaneously.  
When bfdSessAuthPresFlag is false(2), then the value  
of this object MUST be -1. The value -1 indicates that  
no Authentication Key ID will be present in the optional  
BFD Authentication Section."  
REFERENCE  
"Sections [4.2](#) - [4.4](#) from Katz, D. and D. Ward,  
Bidirectional Forwarding Detection (BFD), [RFC 5880](#),  
June 2012."  
DEFVAL { -1 }  
::= { bfdSessEntry 33 }

bfdSessAuthenticationKey OBJECT-TYPE  
SYNTAX IANAbfdSessAuthenticationKeyTC  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
"The authentication key. When the  
bfdSessAuthenticationType is simplePassword(1), the value  
of this object is the password present in the BFD packets.  
  
When the bfdSessAuthenticationType is one of the keyed  
authentication types, this value is used in the  
computation of the key present in the BFD authentication  
packet."  
REFERENCE  
"Sections [4.2](#) - [4.4](#) from Katz, D. and D. Ward,  
Bidirectional Forwarding Detection (BFD), [RFC 5880](#),  
June 2012."  
::= { bfdSessEntry 34 }

bfdSessStorageType OBJECT-TYPE  
SYNTAX StorageType  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION

"This variable indicates the storage type for this

object. Conceptual rows having the value  
'permanent' need not allow write-access to any  
columnar objects in the row."  
 ::= { bfdSessEntry 35 }

bfdSessRowStatus OBJECT-TYPE

SYNTAX RowStatus  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION

"This variable is used to create, modify, and/or  
delete a row in this table. When a row in this  
table has a row in the active(1) state, no  
objects in this row can be modified except the  
bfdSessRowStatus and bfdSessStorageType."

::= { bfdSessEntry 36 }

-- BFD Session Performance Table

bfdSessPerfTable OBJECT-TYPE

SYNTAX SEQUENCE OF BfdSessPerfEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"This table specifies BFD Session performance counters."

::= { bfdObjects 3 }

bfdSessPerfEntry OBJECT-TYPE

SYNTAX BfdSessPerfEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"An entry in this table is created by a BFD-enabled node  
for every BFD Session. bfdSessPerfDiscTime is used to  
indicate potential discontinuity for all counter objects  
in this table."

AUGMENTS { bfdSessEntry }  
 ::= { bfdSessPerfTable 1 }

BfdSessPerfEntry ::= SEQUENCE {

```

bfdSessPerfCtrlPktIn          Counter32,
bfdSessPerfCtrlPktOut        Counter32,
bfdSessPerfCtrlPktDrop       Counter32,
bfdSessPerfCtrlPktDropLastTime TimeStamp,
bfdSessPerfEchoPktIn         Counter32,
bfdSessPerfEchoPktOut        Counter32,
bfdSessPerfEchoPktDrop       Counter32,
bfdSessPerfEchoPktDropLastTime TimeStamp,

```

```

bfdSessUpTime                 TimeStamp,
bfdSessPerfLastSessDownTime   TimeStamp,
bfdSessPerfLastCommLostDiag   IANAbfdDiagTC,
bfdSessPerfSessUpCount        Counter32,
bfdSessPerfDiscTime           TimeStamp,

```

-- High Capacity Counters

```

bfdSessPerfCtrlPktInHC        Counter64,
bfdSessPerfCtrlPktOutHC       Counter64,
bfdSessPerfCtrlPktDropHC      Counter64,
bfdSessPerfEchoPktInHC        Counter64,
bfdSessPerfEchoPktOutHC       Counter64,
bfdSessPerfEchoPktDropHC      Counter64

```

}

bfdSessPerfCtrlPktIn OBJECT-TYPE

```

SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION

```

"The total number of BFD control messages received for this BFD session.

It MUST be equal to the least significant 32 bits of bfdSessPerfCtrlPktInHC if supported, and MUST do so with the rules spelled out in [RFC 2863](#)."

```
 ::= { bfdSessPerfEntry 1 }
```

bfdSessPerfCtrlPktOut OBJECT-TYPE

```

SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION

```

"The total number of BFD control messages sent for this BFD session.

It MUST be equal to the least significant 32 bits of bfdSessPerfCtrlPktOutHC if supported, and MUST do so with the rules spelled out in [RFC 2863](#)."

::= { bfdSessPerfEntry 2 }

bfdSessPerfCtrlPktDrop OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of BFD control messages received for this session yet dropped for being invalid.

It MUST be equal to the least significant 32 bits of bfdSessPerfCtrlPktDropHC if supported, and MUST do so with the rules spelled out in [RFC 2863](#)."

::= { bfdSessPerfEntry 3 }

bfdSessPerfCtrlPktDropLastTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime on the most recent occasion at which received BFD control message for this session was dropped. If no such up event exists, this object contains a zero value."

::= { bfdSessPerfEntry 4 }

bfdSessPerfEchoPktIn OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of BFD echo messages received for this BFD session.

It MUST be equal to the least significant 32 bits of bfdSessPerfEchoPktInHC if supported, and MUST do so

with the rules spelled out in [RFC 2863](#)."  
 ::= { bfdSessPerfEntry 5 }

bfdSessPerfEchoPktOut OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of BFD echo messages sent for this BFD session.

It MUST be equal to the least significant 32 bits of bfdSessPerfEchoPktOutHC if supported, and MUST do so with the rules spelled out in [RFC 2863](#)."

::= { bfdSessPerfEntry 6 }

bfdSessPerfEchoPktDrop OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of BFD echo messages received for this

session yet dropped for being invalid.

It MUST be equal to the least significant 32 bits of bfdSessPerfEchoPktDropHC if supported, and MUST do so with the rules spelled out in [RFC 2863](#)."

::= { bfdSessPerfEntry 7 }

bfdSessPerfEchoPktDropLastTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime on the most recent occasion at which received BFD echo message for this session was dropped. If no such up event exists, this object contains a zero value."

::= { bfdSessPerfEntry 8 }

bfdSessUpTime OBJECT-TYPE

SYNTAX       TimeStamp  
MAX-ACCESS read-only  
STATUS       current  
DESCRIPTION  
    "The value of sysUpTime on the most recent occasion at which  
    the session came up. If no such up event exists this object  
    contains a zero value."  
 ::= { bfdSessPerfEntry 9 }

bfdSessPerfLastSessDownTime OBJECT-TYPE

SYNTAX       TimeStamp  
MAX-ACCESS read-only  
STATUS       current  
DESCRIPTION  
    "The value of sysUpTime on the most recent occasion at  
    which the last time communication was lost with the  
    neighbor. If no such down event exist this object  
    contains a zero value."  
 ::= { bfdSessPerfEntry 10 }

bfdSessPerfLastCommLostDiag OBJECT-TYPE

SYNTAX       IANAbfdDiagTC  
MAX-ACCESS read-only  
STATUS       current  
DESCRIPTION  
    "The BFD diag code for the last time communication was lost  
    with the neighbor. If no such down event exists this object  
    contains a zero value."  
 ::= { bfdSessPerfEntry 11 }

bfdSessPerfSessUpCount OBJECT-TYPE

SYNTAX       Counter32  
MAX-ACCESS read-only  
STATUS       current  
DESCRIPTION  
    "The number of times this session has gone into the Up  
    state since the system last rebooted."  
 ::= { bfdSessPerfEntry 12 }

bfdSessPerfDiscTime OBJECT-TYPE

SYNTAX       TimeStamp  
MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime on the most recent occasion at which any one or more of the session counters suffered a discontinuity.

The relevant counters are the specific instances associated with this BFD session of any Counter32 object contained in the BfdSessPerfTable. If no such discontinuities have occurred since the last re-initialization of the local management subsystem, then this object contains a zero value."

::= { bfdSessPerfEntry 13 }

bfdSessPerfCtrlPktInHC OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This value represents the total number of BFD control messages received for this BFD session.

The least significant 32 bits MUST equal to bfdSessPerfCtrlPktIn, and MUST do so with the rules spelled out in [RFC 2863](#)."

::= { bfdSessPerfEntry 14 }

bfdSessPerfCtrlPktOutHC OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This value represents the total number of BFD control messages transmitted for this BFD session.

The least significant 32 bits MUST equal to

bfdSessPerfCtrlPktOut, and MUST do so with the rules spelled out in [RFC 2863](#)."

::= { bfdSessPerfEntry 15 }

bfdSessPerfCtrlPktDropHC OBJECT-TYPE



SYNTAX Counter64  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"This value represents the total number of BFD control messages received for this BFD session yet dropped for being invalid.  
  
The least significant 32 bits MUST equal to bfdSessPerfCtrlPktDrop, and MUST do so with the rules spelled out in [RFC 2863](#)."  
::= { bfdSessPerfEntry 16 }

bfdSessPerfEchoPktInHC OBJECT-TYPE

SYNTAX Counter64  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"This value represents the total number of BFD echo messages received for this BFD session.  
  
The least significant 32 bits MUST equal to bfdSessPerfEchoPktIn, and MUST do so with the rules spelled out in [RFC 2863](#)."  
::= { bfdSessPerfEntry 17 }

bfdSessPerfEchoPktOutHC OBJECT-TYPE

SYNTAX Counter64  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"This value represents the total number of BFD echo messages transmitted for this BFD session.  
  
The least significant 32 bits MUST equal to bfdSessPerfEchoPktOut, and MUST do so with the rules spelled out in [RFC 2863](#)."  
::= { bfdSessPerfEntry 18 }

bfdSessPerfEchoPktDropHC OBJECT-TYPE

SYNTAX Counter64  
MAX-ACCESS read-only  
STATUS current

DESCRIPTION

"This value represents the total number of BFD echo messages received for this BFD session yet dropped for being invalid.

The least significant 32 bits MUST equal to bfdSessPerfEchoPktDrop, and MUST do so with the rules spelled out in [RFC 2863](#)."

::= { bfdSessPerfEntry 19 }

-- BFD Session Discriminator Mapping Table

bfdSessDiscMapTable OBJECT-TYPE

SYNTAX SEQUENCE OF BfdSessDiscMapEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The BFD Session Discriminator Mapping Table maps a local discriminator value to associated BFD session's IANAbfdSessIndexTC used in the bfdSessionTable."

::= { bfdObjects 4 }

bfdSessDiscMapEntry OBJECT-TYPE

SYNTAX BfdSessDiscMapEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The BFD Session Discriminator Map Entry describes BFD session that is mapped to this IANAbfdSessIndexTC."

INDEX { bfdSessDiscriminator }

::= { bfdSessDiscMapTable 1 }

BfdSessDiscMapEntry ::= SEQUENCE {

bfdSessDiscMapIndex IANAbfdSessIndexTC,

bfdSessDiscMapStorageType StorageType,

bfdSessDiscMapRowStatus RowStatus

}

bfdSessDiscMapIndex OBJECT-TYPE

SYNTAX IANAbfdSessIndexTC

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object specifies the IANAbfdSessIndexTC referred to by the indices of this row. In essence, a mapping is provided between these indexes and the BfdSessTable."

::= { bfdSessDiscMapEntry 1 }

Internet-Draft

BFD-STD-MIB

November 2013

bfdSessDiscMapStorageType OBJECT-TYPE

SYNTAX StorageType

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This variable indicates the storage type for this object. Conceptual rows having the value 'permanent' need not allow write-access to any columnar objects in the row."

::= { bfdSessDiscMapEntry 2 }

bfdSessDiscMapRowStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This variable is used to create, modify, and/or delete a row in this table. When a row in this table has a row in the active(1) state, no objects in this row can be modified except the bfdSessDiscMapRowStatus and bfdSessDiscMapStorageType."

::= { bfdSessDiscMapEntry 3 }

-- BFD Session IP Mapping Table

bfdSessIpMapTable OBJECT-TYPE

SYNTAX SEQUENCE OF BfdSessIpMapEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The BFD Session IP Mapping Table maps given bfdSessInterface, bfdSessSrcAddrType, bfdSessSrcAddr, bfdSessDstAddrType and bfdSessDstAddr to an associated BFD session's IANAbfdSessIndexTC used in the bfdSessionTable."

::= { bfdObjects 5 }

bfdSessIpMapEntry OBJECT-TYPE

SYNTAX BfdSessIpMapEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The BFD Session IP Map Entry describes  
BFD session that is mapped to this IANAbfdSessIndexTC."  
INDEX {  
    bfdSessInterface,  
    bfdSessSrcAddrType,  
    bfdSessSrcAddr,

```
    bfdSessDstAddrType,  
    bfdSessDstAddr  
}  
 ::= { bfdSessIpMapTable 1 }  
  
BfdSessIpMapEntry ::= SEQUENCE {  
    bfdSessIpMapIndex          IANAbfdSessIndexTC,  
    bfdSessIpMapStorageType    StorageType,  
    bfdSessIpMapRowStatus      RowStatus  
}  
  
bfdSessIpMapIndex OBJECT-TYPE  
    SYNTAX      IANAbfdSessIndexTC  
    MAX-ACCESS  read-only  
    STATUS      current  
    DESCRIPTION  
        "This object specifies the IANAbfdSessIndexTC referred  
        to by the indexes of this row. In essence, a mapping is  
        provided between these indexes and the BfdSessTable."  
     ::= { bfdSessIpMapEntry 1 }  
  
bfdSessIpMapStorageType OBJECT-TYPE  
    SYNTAX      StorageType  
    MAX-ACCESS  read-create  
    STATUS      current  
    DESCRIPTION  
        "This variable indicates the storage type for this  
        object. Conceptual rows having the value  
        'permanent' need not allow write-access to any  
        columnar objects in the row."  
     ::= { bfdSessIpMapEntry 2 }  
  
bfdSessIpMapRowStatus OBJECT-TYPE  
    SYNTAX      RowStatus  
    MAX-ACCESS  read-create
```

```
STATUS      current
DESCRIPTION
    "This variable is used to create, modify, and/or
    delete a row in this table. When a row in this
    table has a row in the active(1) state, no
    objects in this row can be modified except the
    bfdSessIpMapRowStatus and bfdSessIpMapStorageType."
 ::= { bfdSessIpMapEntry 3 }
```

-- Notification Configuration

```
bfdSessUp NOTIFICATION-TYPE
OBJECTS {
```

```
    bfdSessDiag, -- low range value
    bfdSessDiag -- high range value
}
STATUS      current
DESCRIPTION
    "This notification is generated when the
    bfdSessState object for one or more contiguous
    entries in bfdSessTable are about to enter the up(4)
    state from some other state. The included values of
    bfdSessDiag MUST both be set equal to this
    new state (i.e: up(4)). The two instances of
    bfdSessDiag in this notification indicate the range
    of indexes that are affected. Note that all the indexes
    of the two ends of the range can be derived from the
    instance identifiers of these two objects. For the
    cases where a contiguous range of sessions
    have transitioned into the up(4) state at roughly
    the same time, the device SHOULD issue a single
    notification for each range of contiguous indexes in
    an effort to minimize the emission of a large number
    of notifications. If a notification has to be
    issued for just a single bfdSessEntry, then
    the instance identifier (and values) of the two
    bfdSessDiag objects MUST be the identical."
 ::= { bfdNotifications 1 }
```

```
bfdSessDown NOTIFICATION-TYPE
OBJECTS {
```

```

        bfdSessDiag, -- low range value
        bfdSessDiag -- high range value
    }
    STATUS current
    DESCRIPTION
        "This notification is generated when the
        bfdSessState object for one or more contiguous
        entries in bfdSessTable are about to enter the down(2)
        or adminDown(1) states from some other state. The included
        values of bfdSessDiag MUST both be set equal to this new
        state (i.e: down(2) or adminDown(1)). The two instances
        of bfdSessDiag in this notification indicate the range
        of indexes that are affected. Note that all the indexes
        of the two ends of the range can be derived from the
        instance identifiers of these two objects. For
        cases where a contiguous range of sessions
        have transitioned into the down(2) or adminDown(1) states
        at roughly the same time, the device SHOULD issue a single
        notification for each range of contiguous indexes in
        an effort to minimize the emission of a large number

```

```

        of notifications. If a notification has to be
        issued for just a single bfdSessEntry, then
        the instance identifier (and values) of the two
        bfdSessDiag objects MUST be the identical."
 ::= { bfdNotifications 2 }

-- Module compliance.

bfdGroups
    OBJECT IDENTIFIER ::= { bfdConformance 1 }

bfdCompliances
    OBJECT IDENTIFIER ::= { bfdConformance 2 }

-- Compliance requirement for fully compliant implementations.

bfdModuleFullCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "Compliance statement for agents that provide full
        support for the BFD-MIB module. Such devices can

```

then be monitored and also be configured using this MIB module."

MODULE -- This module.

```
MANDATORY-GROUPS {  
    bfdSessionGroup,  
    bfdSessionReadOnlyGroup,  
    bfdSessionPerfGroup,  
    bfdNotificationGroup  
}
```

```
GROUP          bfdSessionPerfHCGroup  
DESCRIPTION    "This group is mandatory for all systems that  
               are able to support the Counter64 date type."  
  
OBJECT         bfdSessSrcAddrType  
SYNTAX         InetAddressType { unknown(0), ipv4(1),  
                                ipv6(2), ipv6z(4) }  
DESCRIPTION    "Only unknown(0), ipv4(1), ipv6(2) and ipv6z(4)  
               support are required."  
  
OBJECT         bfdSessSrcAddr  
SYNTAX         InetAddress (SIZE (0|4|16|20))  
DESCRIPTION    "An implementation is only required to support  
               unknown(0), ipv4(1), ipv6(2) and ipv6z(4) sizes."
```

```
OBJECT         bfdSessDstAddrType  
SYNTAX         InetAddressType { unknown(0), ipv4(1),  
                                ipv6(2), ipv6z(4) }  
DESCRIPTION    "Only unknown(0), ipv4(1), ipv6(2) and ipv6z(4)  
               support are required."  
  
OBJECT         bfdSessDstAddr  
SYNTAX         InetAddress (SIZE (0|4|16|20))  
DESCRIPTION    "An implementation is only required to support  
               unknown(0), ipv4(1), ipv6(2) and ipv6z(4) sizes."  
  
OBJECT         bfdSessRowStatus  
SYNTAX         RowStatus { active(1), notInService(2) }  
WRITE-SYNTAX  RowStatus { active(1), notInService(2),
```

```
                createAndGo(4), destroy(6) }
DESCRIPTION    "Support for createAndWait and notReady is not
                required."
```

```
OBJECT         bfdSessDiscMapRowStatus
SYNTAX         RowStatus { active(1), notInService(2) }
WRITE-SYNTAX   RowStatus { active(1), notInService(2),
                createAndGo(4), destroy(6) }
DESCRIPTION    "Support for createAndWait and notReady is not
                required."
```

```
OBJECT         bfdSessIpMapRowStatus
SYNTAX         RowStatus { active(1), notInService(2) }
WRITE-SYNTAX   RowStatus { active(1), notInService(2),
                createAndGo(4), destroy(6) }
DESCRIPTION    "Support for createAndWait and notReady is not
                required."
```

```
::= { bfdCompliances 1 }
```

```
bfdModuleReadOnlyCompliance MODULE-COMPLIANCE
```

```
STATUS current
```

```
DESCRIPTION
```

```
    "Compliance requirement for implementations that only
    provide read-only support for BFD-MIB. Such devices
    can then be monitored but cannot be configured using
    this MIB module."
```

```
MODULE -- This module.
```

```
MANDATORY-GROUPS {
    bfdSessionGroup,
    bfdSessionReadOnlyGroup,
    bfdSessionPerfGroup,
```

```
    bfdNotificationGroup
}
```

```
GROUP         bfdSessionPerfHCGroup
DESCRIPTION    "This group is mandatory for all systems that
                are able to support the Counter64 date type."
```



OBJECT	bfdSessVersionNumber
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessType
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessDiscriminator
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessDestinationUdpPort
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessSourceUdpPort
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessEchoSourceUdpPort
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessAdminStatus
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessOperMode
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessDemandModeDesiredFlag
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessControlPlaneIndepFlag
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessMultipointFlag

MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessInterface
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessSrcAddrType
SYNTAX	InetAddressType { unknown(0), ipv4(1), ipv6(2), ipv6z(4) }
MIN-ACCESS	read-only
DESCRIPTION	"Only unknown(0), ipv4(1), ipv6(2) and ipv6z(4) support are required."
OBJECT	bfdSessSrcAddr
SYNTAX	InetAddress (SIZE (0 4 16 20))
MIN-ACCESS	read-only
DESCRIPTION	"An implementation is only required to support unknown(0), ipv4(1), ipv6(2) and ipv6z(4) sizes."
OBJECT	bfdSessDstAddrType
SYNTAX	InetAddressType { unknown(0), ipv4(1), ipv6(2), ipv6z(4) }
MIN-ACCESS	read-only
DESCRIPTION	"Only unknown(0), ipv4(1), ipv6(2) and ipv6z(4) support are required."
OBJECT	bfdSessDstAddr
SYNTAX	InetAddress (SIZE (0 4 16 20))
MIN-ACCESS	read-only
DESCRIPTION	"An implementation is only required to support unknown(0), ipv4(1), ipv6(2) and ipv6z(4) sizes."
OBJECT	bfdSessGTSM
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessGTSM TTL
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessDesiredMinTxInterval
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."
OBJECT	bfdSessReqMinRxInterval
MIN-ACCESS	read-only
DESCRIPTION	"Write access is not required."

Internet-Draft

BFD-STD-MIB

November 2013

OBJECT bfdSessReqMinEchoRxInterval  
MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

OBJECT bfdSessDetectMult  
MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

OBJECT bfdSessAuthPresFlag  
MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

OBJECT bfdSessAuthenticationType  
MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

OBJECT bfdSessAuthenticationKeyID  
MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

OBJECT bfdSessAuthenticationKey  
MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

OBJECT bfdSessStorageType  
MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

OBJECT bfdSessRowStatus  
SYNTAX RowStatus { active(1) }  
MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

OBJECT bfdSessDiscMapStorageType  
MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

OBJECT bfdSessDiscMapRowStatus  
SYNTAX RowStatus { active(1) }  
MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

OBJECT bfdSessIpMapStorageType

MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."  
  
OBJECT bfdSessIpMapRowStatus  
SYNTAX RowStatus { active(1) }

Nadeau, et al.

Expires May 25, 2014

[Page 31]

---

Internet-Draft

BFD-STD-MIB

November 2013

MIN-ACCESS read-only  
DESCRIPTION "Write access is not required."

::= { bfdCompliances 2 }

-- Units of conformance.

bfdSessionGroup OBJECT-GROUP  
OBJECTS {  
 bfdAdminStatus,  
 bfdSessNotificationsEnable,  
 bfdSessVersionNumber,  
 bfdSessType,  
 bfdSessDiscriminator,  
 bfdSessDestinationUdpPort,  
 bfdSessSourceUdpPort,  
 bfdSessEchoSourceUdpPort,  
 bfdSessAdminStatus,  
 bfdSessOperMode,  
 bfdSessDemandModeDesiredFlag,  
 bfdSessControlPlaneIndepFlag,  
 bfdSessMultipointFlag,  
 bfdSessInterface,  
 bfdSessSrcAddrType,  
 bfdSessSrcAddr,  
 bfdSessDstAddrType,  
 bfdSessDstAddr,  
 bfdSessGTSM,  
 bfdSessGTSM TTL,  
 bfdSessDesiredMinTxInterval,  
 bfdSessReqMinRxInterval,  
 bfdSessReqMinEchoRxInterval,  
 bfdSessDetectMult,  
 bfdSessAuthPresFlag,  
 bfdSessAuthenticationType,  
 bfdSessAuthenticationKeyID,

```
        bfdSessAuthenticationKey,
        bfdSessStorageType,
        bfdSessRowStatus,
        bfdSessDiscMapStorageType,
        bfdSessDiscMapRowStatus,
        bfdSessIpMapStorageType,
        bfdSessIpMapRowStatus
    }
    STATUS      current
    DESCRIPTION
        "Collection of objects needed for BFD sessions."
    ::= { bfdGroups 1 }
```

```
bfdSessionReadOnlyGroup OBJECT-GROUP
    OBJECTS {
        bfdSessRemoteDiscr,
        bfdSessState,
        bfdSessRemoteHeardFlag,
        bfdSessDiag,
        bfdSessNegotiatedInterval,
        bfdSessNegotiatedEchoInterval,
        bfdSessNegotiatedDetectMult,
        bfdSessDiscMapIndex,
        bfdSessIpMapIndex
    }
    STATUS      current
    DESCRIPTION
        "Collection of read-only objects needed for BFD sessions."
    ::= { bfdGroups 2 }
```

```
bfdSessionPerfGroup OBJECT-GROUP
    OBJECTS {
        bfdSessPerfCtrlPktIn,
        bfdSessPerfCtrlPktOut,
        bfdSessPerfCtrlPktDrop,
        bfdSessPerfCtrlPktDropLastTime,
        bfdSessPerfEchoPktIn,
        bfdSessPerfEchoPktOut,
        bfdSessPerfEchoPktDrop,
        bfdSessPerfEchoPktDropLastTime,
        bfdSessUpTime,
        bfdSessPerfLastSessDownTime,
```

```

        bfdSessPerfLastCommLostDiag,
        bfdSessPerfSessUpCount,
        bfdSessPerfDiscTime
    }
    STATUS      current
    DESCRIPTION
        "Collection of objects needed to monitor the
         performance of BFD sessions."
    ::= { bfdGroups 3 }

bfdSessionPerfHCGroup OBJECT-GROUP
OBJECTS {
    bfdSessPerfCtrlPktInHC,
    bfdSessPerfCtrlPktOutHC,
    bfdSessPerfCtrlPktDropHC,
    bfdSessPerfEchoPktInHC,
    bfdSessPerfEchoPktOutHC,
    bfdSessPerfEchoPktDropHC
}

```

```

    STATUS      current
    DESCRIPTION
        "Collection of objects needed to monitor the
         performance of BFD sessions for which the
         values of bfdSessPerfPktIn, bfdSessPerfPktOut
         wrap around too quickly."
    ::= { bfdGroups 4 }

bfdNotificationGroup NOTIFICATION-GROUP
NOTIFICATIONS {
    bfdSessUp,
    bfdSessDown
}
STATUS      current
DESCRIPTION
    "Set of notifications implemented in this
     module."
    ::= { bfdGroups 5 }

```

END

## [6.](#) Security Considerations

As BFD may be tied into the stability of the network infrastructure (such as routing protocols), the effects of an attack on a BFD session may be very serious. This ultimately has denial-of-service effects, as links may be declared to be down (or falsely declared to be up.) As such, improper manipulation of the objects represented by this MIB may result in denial of service to a large number of end-users.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

- o bfdSessAdminStatus - Improper change of bfdSessAdminStatus, from start to stop, can cause significant disruption of the connectivity to those portions of the Internet reached via the applicable remote BFD peer.

- o bfdSessDesiredMinTxInterval, bfdSessReqMinRxInterval, bfdSessReqMinEchoRxInterval, bfdSessDetectMult - Improper change of this object can cause connections to be disrupted for extremely long time periods when otherwise they would be restored in a relatively short period of time.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP.

- o The bfdSessTable may be used to directly configure BFD sessions. The bfdSessMapTable can be used indirectly in the same way.

Unauthorized access to objects in this table could result in disruption of traffic on the network. This is especially true if an unauthorized user configures enough tables to invoke a denial of service attack on the device where they are configured, or on a remote device where the sessions terminate.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- o The bfdSessPerfTable both allows access to the performance characteristics of BFD sessions. Network administrators not wishing to show this information should consider this table sensitive.

The bfdSessAuthenticationType, bfdSessAuthenticationKeyID, and bfdSessAuthenticationKey objects hold security methods and associated security keys of BFD sessions. These objects SHOULD be considered highly sensitive objects. In order for these sensitive information from being improperly accessed, implementers MAY wish to disallow read and create access to these objects.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure "for example by using IPsec", even then, there is no control as to who on the secure network is allowed to access and GET/SET "read/change/create/delete" the objects in these MIB modules.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\], section 8](#)), including full support for the SNMPv3 cryptographic mechanisms "for authentication and privacy".

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator



responsibility to ensure that the SNMP entity giving access to an instance of this MIB module, is properly configured to give access to the objects only to those principals "users" that have legitimate rights to indeed GET or SET "change/create/delete" them.

## 7. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor -----	OBJECT IDENTIFIER value -----
bfdMib	{ mib-2 XXX }

[RFC-Editor's Note (to be removed prior to publication): the IANA is requested to assign a value for "XXX" under the 'mib-2' subtree and to record the assignment in the SMI Numbers registry. When the assignment has been made, the RFC Editor is asked to replace "XXX" (here and in the MIB module) with the assigned value and to remove this note.]

## 8. Acknowledgments

Authors would like to thank David Ward, Jeffrey Haas, Reshad Rahman, David Toscano, Sylvain Masse, Mark Tooker, and Kiran Koushik Agrahara Sreenivasa for their comments and suggestions.

## 9. References

### 9.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIV2)", STD 58, [RFC 2578](#), April 1999.

Schoenwaelder, Ed., "Textual Conventions for SMIV2", STD 58, [RFC 2579](#), April 1999.

[RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIV2", STD 58, [RFC 2580](#), April 1999.

[RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", [RFC 5880](#), June 2010.

[RFC5881] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD) for IPv4 and IPv6 (Single Hop)", [RFC 5881](#), June 2010.

[RFC5883] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD) for Multihop Paths", [RFC 5883](#), June 2010.

[I-D.ietf-bfd-tc-mib]

Nadeau, T., Ali, Z., and N. Akiya, "Definitions of Textual Conventions (TCs) for Bidirectional Forwarding Detection (BFD) Management", [draft-ietf-bfd-tc-mib-03](#) (work in progress), November 2013.

## [9.2](#). Informative References

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.

[RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.

[RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), June 2000.

[RFC3413] Levi, D., Meyer, P., and B. Stewart, "Simple Network Management Protocol (SNMP) Applications", STD 62, [RFC 3413](#), December 2002.

## Authors' Addresses

Thomas D. Nadeau  
Juniper Networks

EMail: [tnadeau@juniper.net](mailto:tnadeau@juniper.net)

Zafar Ali  
Cisco Systems

EMail: [zali@cisco.com](mailto:zali@cisco.com)

Nobo Akiya  
Cisco Systems

EMail: [nobo@cisco.com](mailto:nobo@cisco.com)

