

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: 6 June 2022

E. Chen
Palo Alto Networks
N. Shen
Zededa
R. Raszuk
NTT Network Innovations
R. Rahman
3 December 2021

Unsolicited BFD for Sessionless Applications draft-ietf-bfd-unsolicited-09

Abstract

For operational simplification of "sessionless" applications using BFD, in this document we present procedures for "unsolicited BFD" that allow a BFD session to be initiated by only one side, and be established without explicit per-session configuration or registration by the other side (subject to certain per-interface or per-router policies).

We also introduce a new YANG module to configure and manage "unsolicited BFD". The YANG module in this document conforms to the Network Management Datastore Architecture (NMDA) [[RFC8342](#)].

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

Internet-Draft Unsolicited BFD for Sessionless Applicat December 2021

This Internet-Draft will expire on 6 June 2022.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Table of Contents

1.	Introduction	2
2.	Procedures for Unsolicited BFD	3
3.	State Variables	4
4.	YANG Data Model	5
4.1.	Unsolicited BFD Hierarchy	5
4.2.	Unsolicited BFD Module	6
5.	IANA Considerations	10
6.	Acknowledgments	10
7.	Security Considerations	10
7.1.	BFD Protocol Security Considerations	11
7.2.	YANG Module Security Considerations	11
8.	References	12
8.1.	Normative References	12
8.2.	Informative References	14
	Authors' Addresses	14

[1.](#) Introduction

The current implementation and deployment practice for BFD ([\[RFC5880\]](#) and [\[RFC5881\]](#)) usually requires BFD sessions be explicitly configured or registered on both sides. This requirement is not an issue when an application like BGP [\[RFC4271\]](#) has the concept of a "session" that involves both sides for its establishment. However, this requirement can be operationally challenging when the prerequisite "session" does not naturally exist between two endpoints in an application.

Simultaneous configuration and coordination may be required on both sides for BFD to take effect. For example:

Internet-Draft Unsolicited BFD for Sessionless Applicat December 2021

- * When BFD is used to keep track of the "liveness" of the nexthop of static routes. Although only one side may need the BFD functionality, currently both sides need to be involved in specific configuration and coordination and in some cases static routes are created unnecessarily just for BFD.
- * When BFD is used to keep track of the "liveness" of the third-party nexthop of BGP routes received from the Route Server [[RFC7947](#)] at an Internet Exchange Point (IXP). As the third-party nexthop is different from the peering address of the Route Server, for BFD to work, currently two routers peering with the Route Server need to have routes and nexthops from each other (although indirectly via the Router Server), and the nexthop of each router must be present at the same time. These issues are also discussed in [[I-D.ietf-idr-rs-bfd](#)].

Clearly it is beneficial and desirable to reduce or eliminate unnecessary configurations and coordination in these "sessionless" applications using BFD.

In this document we present procedures for "unsolicited BFD" that allow a BFD session to be initiated by only one side, and be established without explicit per-session configuration or registration by the other side (subject to certain per-interface or per-router policies).

With "unsolicited BFD" there is potential risk for excessive resource usage by BFD from "unexpected" remote systems. To mitigate such risks, several mechanisms are recommended in the Security Considerations section.

Compared to the "Seamless BFD" [[RFC7880](#)], this proposal involves only minor procedural enhancements to the widely deployed BFD itself. Thus we believe that this proposal is inherently simpler in the protocol itself and deployment. As an example, it does not require the exchange of BFD discriminators over an out-of-band channel before the BFD session bring-up.

When BGP Add-Path [[RFC7911](#)] is deployed at an IXP using the Route Server, multiple BGP paths (when exist) can be made available to the clients of the Router Server as described in [[RFC7947](#)]. The "unsolicited BFD" can be used in BGP route selection by these clients to eliminate paths with "inaccessible nexthops".

2. Procedures for Unsolicited BFD

With "unsolicited BFD", one side takes the "Active role" and the other side takes only the "Passive role" as described in [[RFC5880](#)].

On the passive side, the "unsolicited BFD" SHOULD be explicitly configured on an interface or globally (apply to all interfaces). The BFD parameters can be either per-interface or per-router based. It MAY also choose to use the parameters that the active side uses in its BFD Control packets. The "My Discriminator", however, MUST be chosen to allow multiple unsolicited BFD sessions.

The active side starts sending the BFD Control packets as specified in [[RFC5880](#)]. The passive side does not send BFD Control packets.

When the passive side receives a BFD Control packet from the active side with 0 as "Your Discriminator" and does not find an existing BFD session, the passive side MAY create a matching BFD session toward the active side, if permitted by local configuration.

It would then start sending the BFD Control packets and perform necessary procedure for bringing up, maintaining and tearing down the BFD session. If the BFD session fails to get established within certain specified time, or if an established BFD session goes down, the passive side would stop sending BFD Control packets and MAY delete the BFD session created until the BFD Control packets is initiated by the active side again.

When an Unsolicited BFD session goes down, an implementation MAY retain the session state for a period of time, which may be configurable. Retaining this state can be useful for operational purposes.

The "Passive role" may change to the "Active role" when a local

client registers for the same BFD session, and from the "Active role" to the "Passive role" when there is no longer any locally registered client for the BFD session.

[3.](#) State Variables

This document defines a new state variable called Unsolicited Role.

bfd.UnsolicitedRole

The operational mode of BFD interface when configured for unsolicited behaviour. Options can be either PASSIVE, ACTIVE or NULL (NULL - not initialized) for unsolicited BFD sessions. Default (not configured for unsolicited behaviour) MUST be set to NULL if present on the interface.

[4.](#) YANG Data Model

This section extends the YANG data model for BFD [[RFC9127](#)] to cover unsolicited BFD. We import [[RFC8349](#)] since the "bfd" container in [[RFC9127](#)] is under "control-plane-protocol".

[4.1.](#) Unsolicited BFD Hierarchy

Configuration for unsolicited BFD parameters for IP single-hop sessions can be done at 2 levels:

- * Globally, i.e. for all interfaces. This requires support for the "unsolicited-params-global" feature.
- * For specific interfaces. This requires support for the "unsolicited-params-per-interface" feature.

For operational data, a new "unsolicited" container has been added for BFD IP single-hop sessions.

The tree diagram below uses the graphical representation of data models, as defined in [[RFC8340](#)].

Internet-Draft Unsolicited BFD for Sessionless Applicat December 2021

module: ietf-bfd-unsolicited

```
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/bfd:bfd/bfd-ip-sh:ip-sh:
  +--rw unsolicited {bfd-unsol:unsolicited-params-global}?
    +--rw enabled? boolean
    +--rw local-multiplier? multiplier
    +--rw (interval-config-type)?
      +--:(tx-rx-intervals)
        | +--rw desired-min-tx-interval? uint32
        | +--rw required-min-rx-interval? uint32
      +--:(single-interval) {single-minimum-interval}?
        +--rw min-interval? uint32
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/bfd:bfd/bfd-ip-sh:ip-sh
```

```

        /bfd-ip-sh:interfaces:
+--rw unsolicited {bfd-unsol:unsolicited-params-per-interface}?
    +--rw enabled?                               boolean
    +--rw local-multiplier?                       multiplier
    +--rw (interval-config-type)?
        +--:(tx-rx-intervals)
            | +--rw desired-min-tx-interval?      uint32
            | +--rw required-min-rx-interval?     uint32
        +--:(single-interval) {single-minimum-interval}?
            +--rw min-interval?                   uint32
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/bfd:bfd/bfd-ip-sh:ip-sh
    /bfd-ip-sh:sessions/bfd-ip-sh:session:
+--ro unsolicited
    +--ro role?   bfd-unsol:unsolicited-role

```

[4.2.](#) Unsolicited BFD Module

```

<CODE BEGINS> file "ietf-bfd-unsolicited@2021-11-23.yang"
module ietf-bfd-unsolicited {

    yang-version 1.1;

    namespace "urn:ietf:params:xml:ns:yang:ietf-bfd-unsolicited";

    prefix "bfd-unsol";

    // RFC Ed.: replace occurrences of YYYY with actual RFC numbers
    // and remove this note

    import ietf-bfd-types {

```

```

        prefix "bfd-types";
        reference
            "RFC 9127: YANG Data Model for Bidirectional Forwarding Detection
            (BFD)";
    }

    import ietf-bfd {
        prefix "bfd";

```

```

reference
  "RFC 9127: YANG Data Model for Bidirectional Forwarding Detection
  (BFD)";
}

import ietf-bfd-ip-sh {
  prefix "bfd-ip-sh";
  reference
    "RFC 9127: YANG Data Model for Bidirectional Forwarding Detection
    (BFD)";
}

import ietf-routing {
  prefix "rt";
  reference
    "RFC 8349: A YANG Data Model for Routing Management
    (NMDA version)";
}

organization "IETF BFD Working Group";

contact
  "WG Web:  <https://datatracker.ietf.org/wg/bfd/>
  WG List:  <rtg-bfd@ietf.org>

  Editors:  Enke Chen (enchen@paloaltonetworks.com),
            Naiming Shen (naiming@zededa.com),
            Robert Raszuk (robert@raszuk.net),
            Reshad Rahman (reshad@yahoo.com)";

description
  "This module contains the YANG definition for BFD unsolicited
  as per RFC YYYY.

  Copyright (c) 2021 IETF Trust and the persons
  identified as authors of the code.  All rights reserved.

  Redistribution and use in source and binary forms, with or
  without modification, is permitted pursuant to, and subject
  to the license terms contained in, the Simplified BSD License

```


Relating to IETF Documents
(<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC YYYY; see the RFC itself for full legal notices.";

```
reference "RFC YYYY";

revision 2021-11-23 {
  description
    "Initial revision.";
  reference
    "RFC YYYY: Unsolicited BFD for Sessionless Applications.";
}

/*
 * Feature definitions
 */
feature unsolicited-params-global {
  description
    "This feature indicates that the server supports global
    parameters for unsolicited sessions.";
  reference
    "RFC YYYY: Unsolicited BFD for Sessionless Applications.";
}

feature unsolicited-params-per-interface {
  description
    "This feature indicates that the server supports per-interface
    parameters for unsolicited sessions.";
  reference
    "RFC YYYY: Unsolicited BFD for Sessionless Applications.";
}

/*
 * Type Definitions
 */
typedef unsolicited-role {
  type enumeration {
    enum unsolicited-active {
      description "Active role";
    }
    enum unsolicited-passive {
      description "Passive role";
    }
  }
  description "Unsolicited role";
}
```

```
}

/*
 * Augments
 */
augment "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol/bfd:bfd/bfd-ip-sh:ip-sh" {
    if-feature bfd-unsol:unsolicited-params-global;
    description
      "Augmentation for BFD unsolicited parameters";
    container unsolicited {
      description
        "BFD unsolicited top level container";
      leaf enabled {
        type boolean;
        default false;
        description
          "BFD unsolicited enabled globally for IP single-hop.";
      }
      uses bfd-types:base-cfg-parms;
    }
  }

augment "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol/bfd:bfd/bfd-ip-sh:ip-sh/"
  + "bfd-ip-sh:interfaces" {
    if-feature bfd-unsol:unsolicited-params-per-interface;
    description
      "Augmentation for BFD unsolicited on IP single-hop interface";
    container unsolicited {
      description
        "BFD IP single-hop interface unsolicited top level
        container";
      leaf enabled {
        type boolean;
        default false;
        description
          "BFD unsolicited enabled on this interface.";
      }
      uses bfd-types:base-cfg-parms;
    }
  }

augment "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol/bfd:bfd/bfd-ip-sh:ip-sh/"
  + "bfd-ip-sh:sessions/bfd-ip-sh:session" {
```

```
description
  "Augmentation for BFD unsolicited on IP single-hop session";
```

Internet-Draft Unsolicited BFD for Sessionless Applicat December 2021

```
    container unsolicited {
      config false;
      description
        "BFD IP single-hop session unsolicited top level container";
      leaf role {
        type bfd-unsol:unsolicited-role;
        description "Role.";
      }
    }
  }
}
<CODE ENDS>
```

[5.](#) IANA Considerations

This document registers the following namespace URI in the "IETF XML Registry" [[RFC3688](#)]:

URI: urn:ietf:params:xml:ns:yang:ietf-bfd-unsolicited

Registrant Contact: The IESG.

XML: N/A; the requested URI is an XML namespace.

This document registers the following YANG module in the "YANG Module Names" registry [[RFC6020](#)]:

Name: ietf-bfd-unsolicited

Namespace: urn:ietf:params:xml:ns:yang:ietf-bfd-unsolicited

Prefix: bfd-unsol

Reference: RFC YYYY

[6.](#) Acknowledgments

Authors would like to thank Acee Lindem, Greg Mirsky, Jeffrey Haas, Raj Chetan and Tom Petch for their review and valuable input.

[7.](#) Security Considerations

[7.1.](#) BFD Protocol Security Considerations

The same security considerations and protection measures as those described in [\[RFC5880\]](#) and [\[RFC5881\]](#) normatively apply to this document. With "unsolicited BFD" there is potential risk for excessive resource usage by BFD from "unexpected" remote systems. To mitigate such risks, the following measures are mandatory:

- * Limit the feature to specific interfaces, and to a single-hop BFD with "TTL=255" [\[RFC5082\]](#). For numbered interfaces, the source address of an incoming BFD packet should belong to the subnet of the interface on which the BFD packet is received. For unnumbered interfaces the above check should be aligned with routing protocol addresses running on such pair of interfaces.
- * Apply "policy" to allow BFD packets only from certain subnets or hosts.
- * Deploy the feature only in certain "trustworthy" environment, e.g., at an IXP, or between a provider and its customers.
- * Adjust BFD parameters as needed for the particular deployment and scale.
- * Use BFD authentication.

[7.2.](#) YANG Module Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [\[RFC6241\]](#) or RESTCONF [\[RFC8040\]](#). The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [\[RFC6242\]](#). The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [\[RFC8446\]](#).

The NETCONF access control model [[RFC8341](#)] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

/routing/control-plane-protocols/control-plane-protocol/bfd/ip-sh
/unsolicited:

- * data node "enabled" enables creation of unsolicited BFD IP single-hop sessions globally, i.e. on all interfaces. See [Section 7.1](#).
- * data nodes local-multiplier, desired-min-tx-interval, required-min-rx-interval and min-interval all impact the parameters of the unsolicited BFD IP single-hop sessions.

/routing/control-plane-protocols/control-plane-protocol/bfd/ip-sh
/interfaces/interface/unsolicited:

- * data node "enabled" enables creation of unsolicited BFD IP single-hop sessions on a specific interface. See [Section 7.1](#).
- * data nodes local-multiplier, desired-min-tx-interval, required-min-rx-interval and min-interval all impact the parameters of the unsolicited BFD IP single-hop sessions on the interface.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

/routing/control-plane-protocols/control-plane-protocol/bfd/ip-sh
/sessions/session/unsolicited: access to this information discloses the role of the local system in the creation of the unsolicited BFD session.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC5082] Gill, V., Heasley, J., Meyer, D., Savola, P., Ed., and C. Pignataro, "The Generalized TTL Security Mechanism (GTSM)", [RFC 5082](#), DOI 10.17487/RFC5082, October 2007, <<https://www.rfc-editor.org/info/rfc5082>>.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", [RFC 5880](#), DOI 10.17487/RFC5880, June 2010, <<https://www.rfc-editor.org/info/rfc5880>>.

- [RFC5881] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD) for IPv4 and IPv6 (Single Hop)", [RFC 5881](#), DOI 10.17487/RFC5881, June 2010, <<https://www.rfc-editor.org/info/rfc5881>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.

- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8349] Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", [RFC 8349](#), DOI 10.17487/RFC8349, March 2018, <<https://www.rfc-editor.org/info/rfc8349>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

- [RFC9127] Rahman, R., Ed., Zheng, L., Ed., Jethanandani, M., Ed., Pallagatti, S., and G. Mirsky, "YANG Data Model for Bidirectional Forwarding Detection (BFD)", [RFC 9127](#), DOI 10.17487/RFC9127, October 2021, <<https://www.rfc-editor.org/info/rfc9127>>.

[8.2](#). Informative References

- [I-D.ietf-idr-rs-bfd]
Bush, R., Haas, J., Scudder, J. G., Nipper, A., and C. Dietzel, "Making Route Servers Aware of Data Link Failures

at IXPs", Work in Progress, Internet-Draft, [draft-ietf-idr-rs-bfd-09](https://www.ietf.org/archive/id/draft-ietf-idr-rs-bfd-09), 21 September 2020,
<<https://www.ietf.org/archive/id/draft-ietf-idr-rs-bfd-09.txt>>.

- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](https://www.rfc-editor.org/info/rfc4271), DOI 10.17487/RFC4271, January 2006, <<https://www.rfc-editor.org/info/rfc4271>>.
- [RFC7880] Pignataro, C., Ward, D., Akiya, N., Bhatia, M., and S. Pallagatti, "Seamless Bidirectional Forwarding Detection (S-BFD)", [RFC 7880](https://www.rfc-editor.org/info/rfc7880), DOI 10.17487/RFC7880, July 2016, <<https://www.rfc-editor.org/info/rfc7880>>.
- [RFC7911] Walton, D., Retana, A., Chen, E., and J. Scudder, "Advertisement of Multiple Paths in BGP", [RFC 7911](https://www.rfc-editor.org/info/rfc7911), DOI 10.17487/RFC7911, July 2016, <<https://www.rfc-editor.org/info/rfc7911>>.
- [RFC7947] Jasinska, E., Hilliard, N., Raszuk, R., and N. Bakker, "Internet Exchange BGP Route Server", [RFC 7947](https://www.rfc-editor.org/info/rfc7947), DOI 10.17487/RFC7947, September 2016, <<https://www.rfc-editor.org/info/rfc7947>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](https://www.rfc-editor.org/info/rfc8342), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.

Authors' Addresses

Enke Chen
Palo Alto Networks

Email: enchen@paloaltonetworks.com

Chen, et al.

Expires 6 June 2022

[Page 14]

Internet-Draft Unsolicited BFD for Sessionless Applicat December 2021

Naiming Shen
Zededa

Email: naiming@zededa.com

Robert Raszuk
NTT Network Innovations
940 Stewart Dr
Sunnyvale, CA 94085
United States of America

Email: robert@raszuk.net

Reshad Rahman
Canada

Email: reshad@yahoo.com