BIER Z. Zhang

Internet-Draft
Updates: 8401,8444 (if approved)

Updates: <u>8401</u>,8444 (if approved)
Intended status: Standards Track

Expires: April 2, 2022

A. Przygienda
Juniper Networks
A. Dolganow
Individual
H. Bidgoli
Nokia
I. Wijnands
Individual
A. Gulko

Edward Jones Wealth Management September 29, 2021

# BIER Underlay Path Calculation Algorithm and Constraints draft-ietf-bier-bar-ipa-08

#### Abstract

This document specifies general rules for the interaction between the BIER Algorithm (BAR) and the IGP Algorithm (IPA) used for underlay path calculation. The semantics defined in this document update RFC8401, RFC8444, and draft-ietf-bier-ospfv3-extensions.

# Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in <a href="https://example.com/BCP14">BCP 14 [RFC2119]</a> [RFC8174] when, and only when, they appear in all capitals, as shown here.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of  $\underline{\mathsf{BCP}}\ 78$  and  $\underline{\mathsf{BCP}}\ 79$ .

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at https://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 2, 2022.

Internet-Draft bier-bar-ipa September 2021

# Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<a href="https://trustee.ietf.org/license-info">https://trustee.ietf.org/license-info</a>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

#### Table of Contents

<u>1</u> .	Introduction	<u>2</u>
<u>2</u> .	General Rules for the BAR and IPA fields	<u>3</u>
2.	<u>2.1</u> . When BAR Is Not Used	4
2.	<u>2.2</u> . Exceptions/Extensions to the General Rules	4
<u>3</u> .	Examples	4
<u>4</u> .	IANA Considerations	4
<u>5</u> .	Security Considerations	4
<u>6</u> .	Acknowledgements	4
	References	
<u>7.</u>	<u>7.1</u> . Normative References	<u>5</u>
<u>7.</u>	<u>7.2</u> . Informative References	5
Auth	chors' Addresses	5

# 1. Introduction

In the Bit Index Explicit Replication (BIER) architecture [RFC8279], packets with a BIER encapsulation header are forwarded to the neighbors on the underlay paths towards the BFERs. The paths are calculated in the underlay topology for each sub-domain following a calculation algorithm specific to the sub-domain. The topology or algorithm may be congruent with unicast. The algorithm could be a generic IGP algorithm (e.g. SPF) or could be a BIER specific one defined in the future.

This document specifies general rules for the interaction between the BIER Algorithm (BAR) and the IGP Algorithm (IPA) used for underlay path calculation. The semantics defined in this document update [RFC8401], [RFC8444], and [I-D.ietf-bier-ospfv3-extensions].

Zhang, et al. Expires April 2, 2022 [Page 2]

#### 2. General Rules for the BAR and IPA fields

For a particular sub-domain, all BIER Forwarding Routers (BFRs) MUST be provisioned with and signal the same BAR and IPA values. If a BFR discovers another BFR advertising different BAR or IPA value, it MUST treat the advertising router as incapable of supporting BIER (one way of handling incapable routers is documented in <a href="Section 6.9 of">Section 6.9 of</a> [RFC8279] and additional methods may be defined in the future).

Both BAR and IPA have both algorithm and constraints semantics. To generalize, we introduce the following terms:

o BC: BIER-specific Constraints

o BA: BIER-specific Algorithm

o RC: Generic Routing Constraints

o RA: Generic Routing Algorithm

o BCBA: BC + BA

o RCRA: RC + RA

A BAR value corresponds to a BCBA, and an IPA value corresponds to an RCRA. Any of the RC/BC/BA could be "NULL", which means there are no corresponding constraints or algorithm.

When a new BAR value is defined, its corresponding BC/BA semantics MUST be specified. For a new IGP Algorithm to be used as a BIER IPA, its RC/RA semantics MUST also be clearly specified.

For a particular topology X (which could be a default topology or non-default topology) that a sub-domain is associated with, a router calculates the underlay paths according to its provisioned BCBA and RCRA the following way:

- 1. Apply the BIER constraints, resulting in BC(X).
- 2. Apply the routing constraints, resulting in RC(BC(X)).
- 3. Select the algorithm AG as following:
  - A. If BA is NULL, AG is set to RA.
  - B. If BA is not NULL, AG is set to BA.
- 4. Run AG on RC(BC(X)).

#### 2.1. When BAR Is Not Used

The BIER Algorithm registry established by [RFC8401] and also used in [RFC8444] has value 0 for "No BIER specific algorithm is used". That translates to NULL BA and NULL BC. Following the rules defined above, the IPA value alone identifies the calculation algorithm and constraints to be used for a particular sub-domain when BAR is 0.

# 2.2. Exceptions/Extensions to the General Rules

Exceptions or extensions to the above general rules may be specified in the future for specific BAR and/or IPA values. When that happens, compatibility with defined BAR and/or IPA values and semantics need to be specified.

# Examples

As an example, one may define BAR=x with the semantics of "excluding BIER incapable routers". That BIER specific constraint can go with any IPA: whatever RCRA defined by the IPA is augmented with "excluding BIER incapable routers", i.e., BIER incapable routers are not put onto the candidate list during SPF calculation.

Note that if the BC and RC happen to conflict and lead to an empty topology, then no native BIER forwarding path will be found. That is a network design issue that an operator need to avoid when choosing BAR/IPA.

## 4. IANA Considerations

No IANA Consideration is requested in this document.

# 5. Security Considerations

This document does not change the security aspects as discussed in  $[\mbox{RFC8279}]$ .

## 6. Acknowledgements

The authors thank Alia Atlas, Eric Rosen, Senthil Dhanaraj and many others for their suggestions and comments. In particular, the BCBA/RCRA representation for the interaction rules is based on Alia's write-up.

#### 7. References

#### 7.1. Normative References

- [I-D.ietf-bier-ospfv3-extensions]

  Psenak, P., Nainar, N. K., and I. Wijnands, "OSPFv3

  Extensions for BIER", <u>draft-ietf-bier-ospfv3-extensions-04</u>

  (work in progress), May 2021.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
  Requirement Levels", BCP 14, RFC 2119,
  DOI 10.17487/RFC2119, March 1997,
  <a href="https://www.rfc-editor.org/info/rfc2119">https://www.rfc-editor.org/info/rfc2119</a>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC
  2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174,
  May 2017, <a href="https://www.rfc-editor.org/info/rfc8174">https://www.rfc-editor.org/info/rfc8174</a>>.
- [RFC8401] Ginsberg, L., Ed., Przygienda, T., Aldrin, S., and Z. Zhang, "Bit Index Explicit Replication (BIER) Support via IS-IS", RFC 8401, DOI 10.17487/RFC8401, June 2018, <a href="https://www.rfc-editor.org/info/rfc8401">https://www.rfc-editor.org/info/rfc8401</a>.
- [RFC8444] Psenak, P., Ed., Kumar, N., Wijnands, IJ., Dolganow, A., Przygienda, T., Zhang, J., and S. Aldrin, "OSPFv2 Extensions for Bit Index Explicit Replication (BIER)", RFC 8444, DOI 10.17487/RFC8444, November 2018, <a href="https://www.rfc-editor.org/info/rfc8444">https://www.rfc-editor.org/info/rfc8444</a>.

## 7.2. Informative References

- [RFC5120] Przygienda, T., Shen, N., and N. Sheth, "M-ISIS: Multi
   Topology (MT) Routing in Intermediate System to
   Intermediate Systems (IS-ISs)", RFC 5120,
   DOI 10.17487/RFC5120, February 2008,
   <a href="https://www.rfc-editor.org/info/rfc5120">https://www.rfc-editor.org/info/rfc5120</a>>.
- [RFC8279] Wijnands, IJ., Ed., Rosen, E., Ed., Dolganow, A.,
  Przygienda, T., and S. Aldrin, "Multicast Using Bit Index
  Explicit Replication (BIER)", RFC 8279,
  DOI 10.17487/RFC8279, November 2017,
  <a href="https://www.rfc-editor.org/info/rfc8279">https://www.rfc-editor.org/info/rfc8279</a>>.

Authors' Addresses

Zhaohui Zhang Juniper Networks

EMail: zzhang@juniper.net

Antoni Przygienda Juniper Networks

EMail: prz@juniper.net

Andrew Dolganow Individual

EMail: adolgano@gmail.com

Hooman Bidgoli Nokia

EMail: hooman.bidgoli@nokia.com

IJsbrand Wijnands Individual

EMail: ice@braindump.be

Arkadiy Gulko Edward Jones Wealth Management

EMail: arkadiy.gulko@edwardjones.com