

BIER
Internet-Draft
Updates: [8401](#), 8444 (if approved)
Intended status: Standards Track
Expires: August 5, 2022

Z. Zhang
A. Przygienda
Juniper Networks
A. Dolganow
Individual
H. Bidgoli
Nokia
I. Wijnands
Individual
A. Gulko
Edward Jones Wealth Management
February 1, 2022

BIER Underlay Path Calculation Algorithm and Constraints
draft-ietf-bier-bar-ipa-10

Abstract

This document specifies general rules for the interaction between the BIER Algorithm (BAR) and the IGP Algorithm (IPA) used for underlay path calculation. The semantics defined in this document update [RFC8401](#) and [RFC8444](#).

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 5, 2022.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Updated Definition for BAR and IPA Fields	3
3.	General Rules for the BAR and IPA Interaction	3
3.1.	When BAR Is Not Used	4
3.2.	Exceptions/Extensions to the General Rules	4
4.	Examples	4
5.	IANA Considerations	5
6.	Security Considerations	5
7.	Acknowledgements	5
8.	Normative References	5
	Authors' Addresses	6

[1.](#) Introduction

In the Bit Index Explicit Replication (BIER) architecture [[RFC8279](#)], packets with a BIER encapsulation header are forwarded to the neighbors on the underlay paths towards the BFERs. The paths are calculated in the underlay topology for each sub-domain following a calculation algorithm specific to the sub-domain. The topology or algorithm may be congruent with unicast. The algorithm could be a generic IGP algorithm (e.g. SPF) or could be a BIER specific one defined in the future.

This document specifies general rules for the interaction between the BIER Algorithm (BAR) and the IGP Algorithm (IPA) used for underlay path calculation. The semantics defined in this document update [[RFC8401](#)], [[RFC8444](#)].

2. Updated Definition for BAR and IPA Fields

The definition for the BAR and IPA fields in [\[RFC8401\]](#) and [\[RFC8441\]](#) are updated as following.

IPA: IGP Algorithm. Specifies a generic Routing Algorithm (RA) and related Routing Constraints (RC) to calculate underlay paths to reach other BFRs. Values are from the "IGP Algorithm Types" registry [\[RFC8665\]](#).

BAR: BIER Algorithm. Specifies a BIER-specific Algorithm (BA) and BIER-specific Constraints (BC) used to either modify, enhance, or replace the calculation of underlay paths to reach other BFRs as defined by the IPA value. Values are allocated from the "BIER Algorithm" registry [\[RFC8401\]](#).

When a BAR value is defined in a RFC or used in a deployment, the corresponding BA and BC semantics SHOULD be specified in the RFC or for the deployment. For an IGP Algorithm to be used as a BIER IPA, its RA and RC semantics SHOULD be specified in a RFC or for the deployment.

If a BAR value is not specified in a RFC but only privately used for a deployment, it MUST be within the "240-254 Experimental Use" range of the registry.

None of the components of the BAR or IPA can be unknown. If any of the components is not specified, it is interpreted as "NULL" algorithm or constraint. For example, the IGP Algorithm 0 defined in [\[RFC8665\]](#) is treated as having a NULL RC, i.e., no constraints.

3. General Rules for the BAR and IPA Interaction

For a particular sub-domain, all BIER Forwarding Routers (BFRs) MUST be provisioned with and signal the same BAR and IPA values. If a BFR discovers another BFR advertising different BAR or IPA value for a sub-domain, it MUST treat the advertising router as incapable of supporting BIER for that sub-domain (one way of handling incapable routers is documented in [Section 6.9 of \[RFC8279\]](#) and additional methods may be defined in the future).

For a particular topology X that a sub-domain is associated with, a router MUST calculate the underlay paths according to its BAR and IPA values in the following way:

1. Apply the BIER constraints, resulting in BC(X).
2. Apply the routing constraints, resulting in RC(BC(X)).

3. Select the algorithm AG as following:

- A. If BA is NULL, AG is set to RA.
- B. If BA is not NULL, AG is set to BA.

4. Run AG on RC(BC(X)).

It's possible that the resulting AG is not applicable to BIER, In that case, no BIER paths will be calculated and it is a network design issue that an operator needs to avoid when choosing BAR/IPA.

3.1. When BAR Is Not Used

BAR value 0 is defined as "No BIER-specific algorithm is used" [[RFC8401](#)]. This value indicates NULL BA and BC. Following the rules defined above, the IPA value alone identifies the calculation algorithm and constraints to be used for a particular sub-domain.

3.2. Exceptions/Extensions to the General Rules

Exceptions or extensions to the above general rules may be specified in the future for specific BAR and/or IPA values. When that happens, compatibility with defined BAR and/or IPA values and semantics need to be specified.

4. Examples

As an example, one may define a new BAR with a BIER specific constraint of "excluding BIER incapable routers". No BIER specific algorithm is specified, and the BIER specific constraint can go with any IPA - whatever RC defined by the IPA is augmented with "excluding BIER incapable routers", i.e., routers that do not support BIER are not considered when applying the IGP Algorithm.

If the BC and RC happen to conflict and lead to an empty topology, then no BIER forwarding path will be found. For example, the BC could be "exclude BIER-incapable routers" and the RC could be "include green links only". If all the green links are associated with BIER-incapable routers, it results in an empty topology. That is a network design issue that an operator needs to avoid when choosing BAR/IPA.

In another example, a BAR value can be specified to use Steiner Tree algorithm and used together with IPA 0 (which uses SPF algorithm). According to the general rules, the BIER specific algorithm takes precedence so SPF is not used.

5. IANA Considerations

No IANA Consideration is requested in this document.

6. Security Considerations

This document specifies general rules for the interaction between the BIER Algorithm (BAR) and the IGP Algorithm (IPA) used for underlay path calculation. It does not change the security aspects as discussed in [RFC8279], [RFC8401], [RFC8444].

7. Acknowledgements

The authors thank Alia Atlas, Eric Rosen, Senthil Dhanaraj and many others for their suggestions and comments. In particular, the BC/BA/RC/RA representation for the interaction rules is based on Alia's write-up.

8. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8279] Wijnands, IJ., Ed., Rosen, E., Ed., Dolganow, A., Przygienda, T., and S. Aldrin, "Multicast Using Bit Index Explicit Replication (BIER)", [RFC 8279](#), DOI 10.17487/RFC8279, November 2017, <<https://www.rfc-editor.org/info/rfc8279>>.
- [RFC8401] Ginsberg, L., Ed., Przygienda, T., Aldrin, S., and Z. Zhang, "Bit Index Explicit Replication (BIER) Support via IS-IS", [RFC 8401](#), DOI 10.17487/RFC8401, June 2018, <<https://www.rfc-editor.org/info/rfc8401>>.
- [RFC8444] Psenak, P., Ed., Kumar, N., Wijnands, IJ., Dolganow, A., Przygienda, T., Zhang, J., and S. Aldrin, "OSPFv2 Extensions for Bit Index Explicit Replication (BIER)", [RFC 8444](#), DOI 10.17487/RFC8444, November 2018, <<https://www.rfc-editor.org/info/rfc8444>>.

Authors' Addresses

Zhaohui Zhang
Juniper Networks

EMail: zzhang@juniper.net

Antoni Przygienda
Juniper Networks

EMail: prz@juniper.net

Andrew Dolganow
Individual

EMail: adolgano@gmail.com

Hooman Bidgoli
Nokia

EMail: hooman.bidgoli@nokia.com

IJsbrand Wijnands
Individual

EMail: ice@braindump.be

Arkadiy Gulko
Edward Jones Wealth Management

EMail: arkadiy.gulko@edwardjones.com

