

Networking Working Group
Internet-Draft
Intended status: Standards Track
Expires: April 11, 2019

Ran. Chen
Zheng. Zhang
ZTE Corporation
Vengada. Govindan
IJsbrand. Wijnands
Cisco
October 8, 2018

BGP Link-State extensions for BIER
draft-ietf-bier-bgp-ls-bier-ext-04

Abstract

Bit Index Explicit Replication (BIER) is an architecture that provides optimal multicast forwarding through a "BIER domain" without requiring intermediate routers to maintain any multicast related per-flow state. BIER also does not require any explicit tree-building protocol for its operation. A multicast data packet enters a BIER domain at a "Bit-Forwarding Ingress Router" (BFIR), and leaves the BIER domain at one or more "Bit-Forwarding Egress Routers" (BFERs). The BFIR router adds a BIER header to the packet. The BIER header contains a bitstring in which each bit represents exactly one BFER to forward the packet to. The set of BFERs to which the multicast packet needs to be forwarded is expressed by setting the bits that correspond to those routers in the BIER header.

This document specifies extensions to the BGP Link-state address-family in order to advertising BIER information.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 11, 2019.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](https://trustee.ietf.org/license-info) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Conventions used in this document	3
3.	BGP-LS Extensions for BIER	3
3.1.	The BIER TLV	3
3.2.	The BIER MPLS Encapsulation Sub-TLV	4
3.3.	The BIER-TE TLV	5
4.	IANA Considerations	5
5.	Security Considerations	6
6.	Acknowledgements	6
7.	Normative references	6
	Authors' Addresses	7

[1.](#) Introduction

Bit Index Explicit Replication (BIER) is an architecture that provides optimal multicast forwarding through a "BIER domain" without requiring intermediate routers to maintain any multicast related per-flow state. BIER also does not require any explicit tree-building protocol for its operation. A multicast data packet enters a BIER domain at a "Bit-Forwarding Ingress Router" (BFIR), and leaves the BIER domain at one or more "Bit-Forwarding Egress Routers" (BFERs). The BFIR router adds a BIER header to the packet. The BIER header contains a bitstring in which each bit represents exactly one BFER to forward the packet to. The set of BFERs to which the multicast packet needs to be forwarded is expressed by setting the bits that correspond to those routers in the BIER header.

This document specifies extensions to the BGP Link-state address-family in order to advertising BIER-specific. An external component (e.g., a controller) then can collect BIER information in the "northbound" direction within the BIER domain.

Reserved: MUST be 0 on transmission, ignored on reception. May be used in future versions.

BAR: A 1 octet field encoding the BIER Algorithm, used to calculate underlay paths to reach BFERs. Values are allocated from the "BIER Algorithms" registry which is defined in [[RFC8401](#)].

IPA: A 1 octet field encoding the IGP Algorithm, used to either modify, enhance, or replace the calculation of underlay paths to reach BFERs as defined by the BAR value. Values are from the IGP Algorithm registry.

Subdomain-id: Unique value identifying the BIER sub-domain, 1 octet.

MT-ID: Multi-Topology ID that identifies the topology that is associated with the BIER sub-domain. 1 octet.

BFR-id: A 2 octet field encoding the BFR-id, as documented in [[RFC8279](#)]. If the BFR-id is zero, it means, the advertising router is not advertising any BIER-id. In some environment, BFR-id can be configured by NMS, The BFR-id should be sent to a controller.

BS Length: A 1 octet field encoding the Bitstring length as per [[RFC8296](#)]

If the MT-ID value is outside of the values specified in [[RFC4915](#)], the BIER Sub-TLV MUST be ignored.

3.2. The BIER MPLS Encapsulation Sub-TLV

The BIER MPLS Encapsulation Sub-TLV is a sub-TLV of the BIER TLV. BIER MPLS Encapsulation Sub-TLV is used in order to advertise MPLS specific information used for BIER. It MUST appear multiple times in the BIER TLV as described in [[I-D.ietf-bier-ospf-bier-extensions](#)]

In some environment, each router allocates its labels, and advertises it to the controller. That solution is simpler as the controller does not need to deal with label allocation. If the controller has to deal with Label allocation, there needs to be a (global) range carved out such there are no conflicts. We can avoid all that by having the router allocate the BIER Label range and advertise it to the controller.

The following the BIER MPLS Encapsulation Sub-TLV is defined:

This document requests assigning code-points from the registry for the new Prefix Attribute TLV and Sub-TLV.

TLV Code Point	Description	Value defined
1158(recommend)	BIER	this document

Table 1: The new Prefix Attribute TLV

Sub-TLV Code Point	Description	Value
1 (recommend)	BIER MPLS Encapsulation	this document

Table 2: The new Prefix Attribute Sub-TLV

5. Security Considerations

Procedures and protocol extensions defined in this document do not affect the BGP security model. See [[RFC6952](#)] for details.

6. Acknowledgements

We would like to thank Peter Psenak (Cisco) for his comments and support of this work.

7. Normative references

[I-D.ietf-bier-ospf-bier-extensions]

Psenak, P., Kumar, N., Wijnands, I., Dolganow, A., Przygienda, T., Zhang, Z., and S. Aldrin, "OSPFv2 Extensions for BIER", [draft-ietf-bier-ospf-bier-extensions-18](#) (work in progress), June 2018.

[RFC3630] Katz, D., Kompella, K., and D. Yeung, "Traffic Engineering (TE) Extensions to OSPF Version 2", [RFC 3630](#), DOI 10.17487/RFC3630, September 2003, <<https://www.rfc-editor.org/info/rfc3630>>.

[RFC4915] Psenak, P., Mirtorabi, S., Roy, A., Nguyen, L., and P. Pillay-Esnault, "Multi-Topology (MT) Routing in OSPF", [RFC 4915](#), DOI 10.17487/RFC4915, June 2007, <<https://www.rfc-editor.org/info/rfc4915>>.

- [RFC6952] Jethanandani, M., Patel, K., and L. Zheng, "Analysis of BGP, LDP, PCEP, and MSDP Issues According to the Keying and Authentication for Routing Protocols (KARP) Design Guide", [RFC 6952](#), DOI 10.17487/RFC6952, May 2013, <<https://www.rfc-editor.org/info/rfc6952>>.
- [RFC7752] Gredler, H., Ed., Medved, J., Previdi, S., Farrel, A., and S. Ray, "North-Bound Distribution of Link-State and Traffic Engineering (TE) Information Using BGP", [RFC 7752](#), DOI 10.17487/RFC7752, March 2016, <<https://www.rfc-editor.org/info/rfc7752>>.
- [RFC8279] Wijnands, IJ., Ed., Rosen, E., Ed., Dolganow, A., Przygienda, T., and S. Aldrin, "Multicast Using Bit Index Explicit Replication (BIER)", [RFC 8279](#), DOI 10.17487/RFC8279, November 2017, <<https://www.rfc-editor.org/info/rfc8279>>.
- [RFC8296] Wijnands, IJ., Ed., Rosen, E., Ed., Dolganow, A., Tantsura, J., Aldrin, S., and I. Meilik, "Encapsulation for Bit Index Explicit Replication (BIER) in MPLS and Non-MPLS Networks", [RFC 8296](#), DOI 10.17487/RFC8296, January 2018, <<https://www.rfc-editor.org/info/rfc8296>>.
- [RFC8401] Ginsberg, L., Ed., Przygienda, T., Aldrin, S., and Z. Zhang, "Bit Index Explicit Replication (BIER) Support via IS-IS", [RFC 8401](#), DOI 10.17487/RFC8401, June 2018, <<https://www.rfc-editor.org/info/rfc8401>>.

Authors' Addresses

Ran Chen
ZTE Corporation
No.50 Software Avenue, Yuhuatai District
Nanjing, Jiangsu Province 210012
China

Phone: +86 025 88014636
Email: chen.ran@zte.com.cn

Zheng Zhang
ZTE Corporation
No.50 Software Avenue, Yuhuatai District
Nanjing, Jiangsu Province 210012
China

Email: zhang.zheng@zte.com.cn

Vengada Prasad Govindan
Cisco

Email: venggovi@cisco.com

IJsbrand Wijnands
Cisco
De Kleetlaan 6a
Diegem 1831
Belgium

Email: ice@cisco.com