

Benchmarking Working Group
Internet Draft
Intended status: Informational
Expires: January 2017

M. Georgescu
NAIST
G. Lencse
Szechenyi Istvan University
July 7, 2016

Benchmarking Methodology for IPv6 Transition Technologies
draft-ietf-bmwg-ipv6-tran-tech-benchmarking-02.txt

Abstract

There are benchmarking methodologies addressing the performance of network interconnect devices that are IPv4- or IPv6-capable, but the IPv6 transition technologies are outside of their scope. This document provides complementary guidelines for evaluating the performance of IPv6 transition technologies. More specifically, this document targets IPv6 transition technologies that employ encapsulation or translation mechanisms, as dual-stack nodes can be very well tested using the recommendations of [RFC2544](#) and [RFC5180](#). The methodology also includes a tentative metric for benchmarking load scalability.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on January 7, 2016.

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction.....	3
1.1.	IPv6 Transition Technologies.....	4
2.	Conventions used in this document.....	5
3.	Terminology.....	6
4.	Test Setup.....	6
4.1.	Single translation Transition Technologies.....	7
4.2.	Encapsulation/Double translation Transition Technologies..	7
5.	Test Traffic.....	8
5.1.	Frame Formats and Sizes.....	8
5.1.1.	Frame Sizes to Be Used over Ethernet.....	9
5.2.	Protocol Addresses.....	9
5.3.	Traffic Setup.....	9
6.	Modifiers.....	10
7.	Benchmarking Tests.....	10
7.1.	Throughput - [RFC2544].....	10
7.2.	Latency.....	10
7.3.	Packet Delay Variation.....	11
7.3.1.	PDV.....	12
7.3.2.	IPDV.....	12
7.4.	Frame Loss Rate - [RFC2544].....	13
7.5.	Back-to-back Frames - [RFC2544].....	13
7.6.	System Recovery - [RFC2544].....	13
7.7.	Reset - [RFC2544].....	13

8. Additional Benchmarking Tests for Stateful IPv6 Transition Technologies.....13

- 8.1. Concurrent TCP Connection Capacity -[RFC3511].....14
- 8.2. Maximum TCP Connection Establishment Rate -[RFC3511].....14

9. DNS Resolution Performance.....14

- 9.1. Test and Traffic Setup.....14
- 9.2. Benchmarking DNS Resolution Performance.....15
 - 9.2.1. Requirements for the Tester.....16

10. Scalability.....17

- 10.1. Test Setup.....17
 - 10.1.1. Single Translation Transition Technologies.....17
 - 10.1.2. Encapsulation/Double Translation Transition Technologies.....18
- 10.2. Benchmarking Performance Degradation.....18
 - 10.2.1. Network performance degradation with simultaneous load18
 - 10.2.2. Network performance degradation with incremental load19

11. NAT44 and NAT66.....20

12. Summarizing function and variation.....20

13. Security Considerations.....20

14. IANA Considerations.....21

15. References.....21

- 15.1. Normative References.....21
- 15.2. Informative References.....22

16. Acknowledgements.....23

[Appendix A](#). Theoretical Maximum Frame Rates.....25

1. Introduction

The methodologies described in [RFC2544] and [RFC5180] help vendors and network operators alike analyze the performance of IPv4 and IPv6-capable network devices. The methodology presented in [RFC2544] is mostly IP version independent, while [RFC5180] contains complementary recommendations, which are specific to the latest IP version, IPv6. However, [RFC5180] does not cover IPv6 transition technologies.

IPv6 is not backwards compatible, which means that IPv4-only nodes cannot directly communicate with IPv6-only nodes. To solve this issue, IPv6 transition technologies have been proposed and implemented.

This document presents benchmarking guidelines dedicated to IPv6 transition technologies. The benchmarking tests can provide insights about the performance of these technologies, which can act as useful feedback for developers, as well as for network operators going through the IPv6 transition process.

The document also includes an approach to quantify load scalability. Load scalability can be defined as a system's ability to gracefully accommodate higher loads. Because poor scalability usually leads to poor performance, the proposed approach is to quantify the load scalability by measuring the performance degradation created by a higher number of network flows.

1.1. IPv6 Transition Technologies

Two of the basic transition technologies, dual IP layer (also known as dual stack) and encapsulation are presented in [RFC4213]. IPv4/IPv6 Translation is presented in [RFC6144]. Most of the transition technologies employ at least one variation of these mechanisms. Some of the more complex ones (e.g. DSLite [RFC6333]) are using all three. In this context, a generic classification of the transition technologies can prove useful.

Tentatively, we can consider a production network transitioning to IPv6 as being constructed using the following IP domains:

- o Domain A: IPvX specific domain
- o Core domain: which may be IPvY specific or dual-stack(IPvX and IPvY)
- o Domain B: IPvX specific domain

Note: X,Y are part of the {4,6} set.

According to the technology used for the core domain traversal the transition technologies can be categorized as follows:

1. Single Translation: In this case, the production network is assumed to have only two domains, Domain A and the Core domain. The core domain is assumed to be IPvY specific. IPvX packets are translated to IPvY at the edge between Domain A and the Core domain.
2. Dual-stack: the core domain devices implement both IP protocols
3. Encapsulation: The production network is assumed to have all three domains, Domains A and B are IPvX specific, while the core domain is IPvY specific. An encapsulation mechanism is used to traverse the core domain. The IPvX packets are encapsulated to IPvY packets at the edge between Domain A and the Core domain. Subsequently, the IPvY packets are decapsulated at the edge between the Core domain and Domain B.

4. Double translation: The production network is assumed to have all three domains, Domains A and B are IPvX specific, while the core domain is IPvY specific. A translation mechanism is employed for the traversal of the core network. The IPvX packets are translated to IPvY packets at the edge between Domain A and the Core domain. Subsequently, the IPvY packets are translated back to IPvX at the edge between the Core domain and Domain B.

The performance of Dual-stack transition technologies can be fully evaluated using the benchmarking methodologies presented by [RFC2544] and [RFC5180]. Consequently, this document focuses on the other 3 categories: Single translation, Encapsulation and Double translation transition technologies.

Another important aspect by which the IPv6 transition technologies can be categorized is their use of stateful or stateless mapping algorithms. The technologies that use stateful mapping algorithms (e.g. Stateful NAT64 [RFC6146]) create dynamic correlations between IP addresses or {IP address, transport protocol, transport port number} tuples, which are stored in a state table. For ease of reference, the IPv6 transition technologies which employ stateful mapping algorithms will be called stateful IPv6 transition technologies. The efficiency with which the state table is managed can be an important performance indicator for these technologies. Hence, for the stateful IPv6 transition technologies additional benchmarking tests are RECOMMENDED.

Table 1 contains the generic categories as well as associations with some of the IPv6 transition technologies proposed in the IETF.

Table 1. IPv6 Transition Technologies Categories

	Generic category	IPv6 Transition Technology
1	Dual-stack	Dual IP Layer Operations [RFC4213]
2	Single translation	NAT64 [RFC6146], IVI [RFC6219]
3	Double translation	464XLAT [RFC6877], MAP-T [RFC7599]
4	Encapsulation	DSLite[RFC6333], MAP-E [RFC7597] Lightweight 4over6 [RFC7596] 6RD [RFC 5569]

2. Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

In this document, these words will appear with that interpretation only when in ALL CAPS. Lower case uses of these words are not to be interpreted as carrying [\[RFC2119\]](#) significance.

Although these terms are usually associated with protocol requirements, in this doc the terms are requirements for users and systems that intend to implement the test conditions and claim conformance with this specification.

3. Terminology

A number of terms used in this memo have been defined in other RFCs. Please refer to those RFCs for definitions, testing procedures and reporting formats.

Throughput (Benchmark) - [\[RFC2544\]](#)

Frame Loss Rate (Benchmark) - [\[RFC2544\]](#)

Back-to-back Frames (Benchmark) - [\[RFC2544\]](#)

System Recovery (Benchmark) - [\[RFC2544\]](#)

Reset (Benchmark) - [\[RFC6201\]](#)

Concurrent TCP Connection Capacity (Benchmark) - [\[RFC3511\]](#)

Maximum TCP Connection Establishment Rate (Benchmark) - [\[RFC3511\]](#)

4. Test Setup

The test environment setup options recommended for IPv6 transition technologies benchmarking are very similar to the ones presented in [Section 6 of \[RFC2544\]](#). In the case of the tester setup, the options presented in [\[RFC2544\]](#) and [\[RFC5180\]](#) can be applied here as well. However, the Device under test (DUT) setup options should be explained in the context of the targeted categories of IPv6 transition technologies: Single translation, Double translation and Encapsulation transition technologies.

Although both single tester and sender/receiver setups are applicable to this methodology, the single tester setup will be used to describe the DUT setup options.

For the test setups presented in this memo, dynamic routing SHOULD be employed. However, the presence of routing and management frames can represent unwanted background data that can affect the

benchmarking result. To that end, the procedures defined in [RFC2544] (Sections 11.2 and 11.3) related to routing and management frames SHOULD be used here as well. Moreover, the "Trial description" recommendations presented in [RFC2544] (Section 23) are valid for this memo as well.

In terms of route setup, the recommendations of [RFC2544] Section 13 are valid for this document as well assuming that an IPv6 version of the routing packets shown in appendix C.2.6.2 is used.

4.1. Single translation Transition Technologies

For the evaluation of Single translation transition technologies, a single DUT setup (see Figure 1) SHOULD be used. The DUT is responsible for translating the IPvX packets into IPvY packets. In this context, the tester device should be configured to support both IPvX and IPvY.




Figure 1. Test setup 1

4.2. Encapsulation/Double translation Transition Technologies

For evaluating the performance of Encapsulation and Double translation transition technologies, a dual DUT setup (see Figure 2) SHOULD be employed. The tester creates a network flow of IPvX packets. The first DUT is responsible for the encapsulation or translation of IPvX packets into IPvY packets. The IPvY packets are decapsulated/translated back to IPvX packets by the second DUT and forwarded to the tester.




Figure 2. Test setup 2

One of the limitations of the dual DUT setup is the inability to reflect asymmetries in behavior between the DUTs. Considering this, additional performance tests SHOULD be performed using the single DUT setup.

Note: For encapsulation IPv6 transition technologies, in the single DUT setup, in order to test the decapsulation efficiency, the tester SHOULD be able to send IPvX packets encapsulated as IPvY.

5. Test Traffic

The test traffic represents the experimental workload and SHOULD meet the requirements specified in this section. The requirements are dedicated to unicast IP traffic. Multicast IP traffic is outside of the scope of this document.

5.1. Frame Formats and Sizes

[RFC5180] describes the frame size requirements for two commonly used media types: Ethernet and SONET (Synchronous Optical Network). [RFC2544] covers also other media types, such as token ring and FDDI. The two documents can be referred for the dual-stack transition technologies. For the rest of the transition technologies the frame overhead introduced by translation or encapsulation MUST be considered.

The encapsulation/translation process generates different size frames on different segments of the test setup. For instance, the single translation transition technologies will create different frame sizes on the receiving segment of the test setup, as IPvX packets are translated to IPvY. This is not a problem if the bandwidth of the employed media is not exceeded. To prevent exceeding the limitations imposed by the media, the frame size overhead needs to be taken into account when calculating the maximum theoretical frame rates. The calculation method for the Ethernet, as

Internet-Draft IPv6 transition tech benchmarking July 2016
well as a calculation example are detailed in [Appendix A](#). The details of the media employed for the benchmarking tests MUST be noted in all test reports.

In the context of frame size overhead, MTU recommendations are needed in order to avoid frame loss due to MTU mismatch between the virtual encapsulation/translation interfaces and the physical network interface controllers (NICs). To avoid this situation, the larger MTU between the physical NICs and virtual encapsulation/translation interfaces SHOULD be set for all interfaces of the DUT and tester. To be more specific, the minimum IPv6 MTU size (1280 bytes) plus the encapsulation/translation overhead is the RECOMMENDED value for the physical interfaces as well as virtual ones.

5.1.1. Frame Sizes to Be Used over Ethernet

Based on the recommendations of [[RFC5180](#)], the following frame sizes SHOULD be used for benchmarking IPvX/IPvY traffic on Ethernet links: 64, 128, 256, 512, 1024, 1280, 1518, 1522, 2048, 4096, 8192 and 9216.

The theoretical maximum frame rates considering an example of frame overhead are presented in [Appendix A1](#).

5.2. Protocol Addresses

The selected protocol addresses should follow the recommendations of [[RFC5180](#)]([Section 5](#)) for IPv6 and [[RFC2544](#)]([Section 12](#)) for IPv4.

Note: testing traffic with extension headers might not be possible for the transition technologies, which employ translation. Proposed IPvX/IPvY translation algorithms such as IP/ICMP translation [[RFC6145](#)] do not support the use of extension headers.

5.3. Traffic Setup

Following the recommendations of [[RFC5180](#)], all tests described SHOULD be performed with bi-directional traffic. Uni-directional traffic tests MAY also be performed for a fine grained performance assessment.

Because of the simplicity of UDP, UDP measurements offer a more reliable basis for comparison than other transport layer protocols. Consequently, for the benchmarking tests described in [Section 6](#) of this document UDP traffic SHOULD be employed.

Internet-Draft IPv6 transition tech benchmarking July 2016
Considering that a transition technology could process both native IPv6 traffic and translated/encapsulated traffic, the following traffic setups are recommended:

- i) IPvX only traffic (where the IPvX traffic is to be translated/encapsulated by the DUT)
- ii) 90% IPvX traffic and 10% IPvY native traffic
- iii) 50% IPvX traffic and 50% IPvY native traffic
- iv) 10% IPvX traffic and 90% IPvY native traffic

Considering that the stateful transition technologies need to manage the state table for each connection, a connection-oriented transport layer protocol needs to be used with the test traffic. Consequently, TCP test traffic SHOULD be employed for the tests described in [Section 7](#) of this document.

6. Modifiers

The idea of testing under different operational conditions was first introduced in [[RFC2544](#)]([Section 11](#)) and represents an important aspect of benchmarking network elements, as it emulates to some extent the conditions of a production environment. [[RFC5180](#)] describes complementary testing conditions specific to IPv6. Their recommendations can be referred for IPv6 transition technologies testing as well.

7. Benchmarking Tests

The following sub-sections contain the list of all recommended benchmarking tests.

7.1. Throughput - [[RFC2544](#)]

7.2. Latency

Objective: To determine the latency. Typical latency is based on the definitions of latency from [[RFC1242](#)]. However, this memo provides a new measurement procedure.

Procedure: Similar to [[RFC2544](#)], the throughput for DUT at each of the listed frame sizes SHOULD be determined. Send a stream of frames at a particular frame size through the DUT at the determined throughput rate to a specific destination. The stream SHOULD be at least 120 seconds in duration.

Identifying tags SHOULD be included in at least 500 frames after 60 seconds. For each tagged frame, the time at which the frame was

fully transmitted (timestamp A) and the time at which the frame was received (timestamp B) MUST be recorded. The latency is timestamp B minus timestamp A as per the relevant definition from [RFC 1242](#), namely latency as defined for store and forward devices or latency as defined for bit forwarding devices.

From the resulted (at least 500) latencies, 2 quantities SHOULD be calculated. One is the typical latency, which SHOULD be calculated with the following formula:

$$TL = \text{Median}(Li)$$

Where: TL - the reported typical latency of the stream

Li - the latency for tagged frame i

The other measure is the worst case latency, which SHOULD be calculated with the following formula:

$$WCL = L99.9\text{thPercentile}$$

Where: WCL - The reported worst case latency

L99.9thPercentile - The 99.9th Percentile of the stream measured latencies

The test MUST be repeated at least 20 times with the reported value being the median of the recorded values.

Reporting Format: The report MUST state which definition of latency (from [RFC 1242](#)) was used for this test. The summarized latency results SHOULD be reported in the format of a table with a row for each of the tested frame sizes. There SHOULD be columns for the frame size, the rate at which the latency test was run for that frame size, for the media types tested, and for the resultant typical latency and worst case latency values for each type of data stream tested. To account for the variation, the 1st and 99th percentiles of the 20 iterations MAY be reported in two separated columns. For a fine grain analysis, the histogram (as exemplified in [\[RFC5481\] Section 4.4](#)) of one of the iterations MAY be displayed as well.

7.3. Packet Delay Variation

Considering two of the metrics presented in [\[RFC5481\]](#), Packet Delay Variation (PDV) and Inter Packet Delay Variation (IPDV), it is RECOMMENDED to measure PDV. For a fine grain analysis of delay variation, IPDV measurements MAY be performed as well.

7.3.1. PDV

Objective: To determine the Packet Delay Variation as defined in [[RFC5481](#)].

Procedure: As described by [[RFC2544](#)], first determine the throughput for the DUT at each of the listed frame sizes. Send a stream of frames at a particular frame size through the DUT at the determined throughput rate to a specific destination. The stream SHOULD be at least 60 seconds in duration. Measure the One-way delay as described by [[RFC3393](#)] for all frames in the stream. Calculate the PDV of the stream using the formula:

$$\text{PDV} = D_{99.9\text{thPercentile}} - D_{\text{min}}$$

Where: $D_{99.9\text{thPercentile}}$ - the 99.9th Percentile (as it was described in [[RFC5481](#)]) of the One-way delay for the stream

D_{min} - the minimum One-way delay in the stream

As recommended in [[RFC 2544](#)], the test MUST be repeated at least 20 times with the reported value being the median of the recorded values. Moreover, the 1st and 99th percentiles SHOULD be calculated to account for the variation of the dataset.

Reporting Format: The PDV results SHOULD be reported in a table with a row for each of the tested frame sizes and columns for the frame size and the applied frame rate for the tested media types. Two columns for the 1st and 99th percentile values MAY as well be displayed. Following the recommendations of [[RFC5481](#)], the RECOMMENDED units of measurement are milliseconds.

7.3.2. IPDV

Objective: To determine the Inter Packet Delay Variation as defined in [[RFC5481](#)].

Procedure: As described by [[RFC2544](#)], first determine the throughput for the DUT at each of the listed frame sizes. Send a stream of frames at a particular frame size through the DUT at the determined throughput rate to a specific destination. The stream SHOULD be at least 60 seconds in duration. Measure the One-way delay as described by [[RFC3393](#)] for all frames in the stream. Calculate the IPDV for each of the frames using the formula:

$$\text{IPDV}(i) = D(i) - D(i-1)$$

Where: $D(i)$ - the One-way delay of the i th frame in the stream

Given the nature of IPDV, reporting a single number might lead to over-summarization. In this context, the report for each measurement SHOULD include 3 values: Dmin, Dmed, and Dmax

Where: Dmin - the minimum One-way delay in the stream

Dmed - the median One-way delay of the stream

Dmax - the maximum One-way delay in the stream

As recommended in [[RFC 2544](#)], the test MUST be repeated at least 20 times. To summarize the 20 repetitions, for each of the 3 (Dmin, Dmed and Dmax) the median value SHOULD be reported.

Reporting format: The median for the 3 proposed values SHOULD be reported. The IPDV results SHOULD be reported in a table with a row for each of the tested frame sizes. The columns SHOULD include the frame size and associated frame rate for the tested media types and sub-columns for the three proposed reported values. Following the recommendations of [[RFC5481](#)], the RECOMMENDED units of measurement are milliseconds.

[7.4. Frame Loss Rate - \[\[RFC2544\]\(#\)\]](#)

[7.5. Back-to-back Frames - \[\[RFC2544\]\(#\)\]](#)

[7.6. System Recovery - \[\[RFC2544\]\(#\)\]](#)

[7.7. Reset - \[\[RFC2544\]\(#\)\]](#)

[8. Additional Benchmarking Tests for Stateful IPv6 Transition Technologies](#)

This section describes additional tests dedicated to the stateful IPv6 transition technologies. For the tests described in this section the DUT devices SHOULD follow the test setup and test parameters recommendations presented in [[RFC3511](#)] (Sections [4](#), [5](#)).

In addition to the IPv4/IPv6 transition function, a network node can have a firewall function. This document is targeting only the network devices that do not have a firewall function, as this function can be benchmarked using the recommendations of [[RFC3511](#)]. Consequently, only the tests described in [[RFC3511](#)] (Sections [5.2](#), [5.3](#)) are RECOMMENDED. Namely, the following additional tests SHOULD be performed:

8.1. Concurrent TCP Connection Capacity -[RFC3511]


8.2. Maximum TCP Connection Establishment Rate -[RFC3511]

9. DNS Resolution Performance

This section describes benchmarking tests dedicated to DNS64 (see [RFC6147]), used as DNS support for single translation technologies such as NAT64.

9.1. Test and Traffic Setup

The test setup follows the setup proposed for single translation IPv6 transition technologies in Figure 1.



The test traffic SHOULD follow the following steps.

1. Query for the AAAA record of a domain name (from client to DNS64 server)
2. Query for the AAAA record of the same domain name (from DNS64 server to authoritative DNS server)
3. Empty AAAA record answer (from authoritative DNS server to DNS64 server)
4. Query for the A record of the same domain name (from DNS64 server to authoritative DNS server)
5. Valid A record answer (from authoritative DNS server to DNS64 server)
6. Synthesized AAAA record answer (from DNS64 server to client)

The Tester plays the role of DNS client as well as authoritative DNS server. It MAY be realized as a single physical device, or alternatively, two physical devices MAY be used.

Please note that:

- If the DNS64 server implements caching and there is a cache hit then step 1 is followed by step 6 (and steps 2 through 5 are omitted).
- If the domain name has an AAAA record then it is returned in step 3 by the authoritative DNS server, steps 4 and 5 are omitted, and the DNS64 server does not synthesize an AAAA record, but returns the received AAAA record to the client.
- As for the IP version used between the tester and the DUT, IPv6 MUST be used between the client and the DNS64 server (as a DNS64 server provides service for an IPv6-only client), but either IPv4 or IPv6 MAY be used between the DNS64 server and the authoritative DNS server.

9.2. Benchmarking DNS Resolution Performance

Objective: To determine DNS64 performance by means of the number of successfully processed DNS requests per second.

Procedure: Send a specific number of DNS queries at a specific rate to the DUT and then count the replies received in time (within a predefined timeout period from the sending time of the corresponding query, having the default value 1 second) from the DUT. If the count of sent queries is equal to the count of received replies, the rate of the queries is raised and the test is rerun. If fewer replies are received than queries were sent, the rate of the queries is reduced and the test is rerun. The duration of the test SHOULD be at least 60 seconds to reduce the potential gain of a DNS64 server, which is able to exhibit higher performance by storing the requests and thus utilizing also the timeout time for answering them. For the same reason, no higher timeout time than 1 second SHOULD be used.

The number of processed DNS queries per second is the fastest rate at which the count of DNS replies sent by the DUT is equal to the number of DNS queries sent to it by the test equipment.

The test SHOULD be repeated at least 20 times and the median and 1st /99th percentiles of the number of processed DNS queries per second SHOULD be calculated.

Details and parameters:

1. Caching

First, all the DNS queries MUST contain different domain names (or

Internet-Draft IPv6 transition tech benchmarking July 2016
domain names MUST NOT be repeated before the cache of the DUT is exhausted). Then new tests MAY be executed with 10%, 20%, 30%, etc. domain names which are repeated (early enough to be still in the cache).

2. Existence of AAAA record

First, all the DNS queries MUST contain domain names which do not have an AAAA record and have exactly one A record. Then new tests MAY be executed with 10%, 20%, 30%, etc. domain names which have an AAAA record.

Please note that the two conditions above are orthogonal, thus all their combinations are possible and MAY be tested. The testing with 0% repeated DNS names and with 0% existing AAAA record is REQUIRED and the other combinations are OPTIONAL.

Reporting format: The primary result of the DNS64/DNS46 test is the average of the number of processed DNS queries per second measured with the above mentioned "0% + 0% combination". The average SHOULD be complemented with the margin of error to show the stability of the result. If optional tests are done, the median and the 1st and 99th percentiles MAY be presented in a two dimensional table where the dimensions are the proportion of the repeated domain names and the proportion of the DNS names having AAAA records. The two table headings SHOULD contain these percentage values. Alternatively, the results MAY be presented as the corresponding two dimensional graph, too. In this case the graph SHOULD show the median values with the percentiles as error bars. From both the table and the graph, one dimensional excerpts MAY be made at any given fixed percentage value of the other dimension. In this case, the fixed value MUST be given together with a one dimensional table or graph.

9.2.1. Requirements for the Tester

Before a Tester can be used for testing a DUT at rate r queries per second with t seconds timeout, it MUST perform a self-test in order to exclude the possibility that the poor performance of the Tester itself influences the results. For performing a self-test, the tester is looped back (leaving out DUT) and its authoritative DNS server subsystem is configured to be able to answer all the AAAA record queries. For passing the self-test, the Tester SHOULD be able to answer AAAA record queries at $2 \cdot (r + \delta)$ rate within $0.25 \cdot t$ timeout, where the value of δ is at least 0.1.

Explanation: When performing DNS64 testing, each AAAA record query may result in at most two queries sent by the DUT, the first one of them is for an AAAA record and the second one is for an A record (the are both sent when there is no cache hit and also no AAAA record exists). The parameters above guarantee that the

Internet-Draft IPv6 transition tech benchmarking July 2016
 authoritative DNS server subsystem of the DUT is able to answer the queries at the required frequency using up not more than the half of the timeout time.

Remark: a sample open-source test program, dns64perf++ is available from [Dns64perf]. It implements only the client part of the Tester and it should be used together with an authoritative DNS server implementation, e.g. BIND, NSD or YADIFA.

10. Scalability

Scalability has been often discussed; however, in the context of network devices, a formal definition or a measurement method has not yet been proposed. In this context, scalability can be defined as the ability of each transition technology to accommodate network growth. Poor scalability usually leads to poor performance. Considering this, scalability can be measured by quantifying the network performance degradation while the network grows.

The following subsections describe how the test setups can be modified to create network growth and how the associated performance degradation can be quantified.

10.1. Test Setup

The test setups defined in Section 3 have to be modified to create network growth.

10.1.1. Single Translation Transition Technologies

In the case of single translation transition technologies the network growth can be generated by increasing the number of network flows generated by the tester machine (see Figure 3).




Figure 3. Test setup 3

10.1.2. Encapsulation/Double Translation Transition Technologies

Similarly, for the encapsulation/double translation technologies a multi-flow setup is recommended. Considering a multipoint-to-point scenario, for most transition technologies, one of the edge nodes is designed to support more than one connecting devices. Hence, the recommended test setup is a n:1 design, where n is the number of client DUTs connected to the same server DUT (See Figure 4).




Figure 4. Test setup 4

This test setup can help to quantify the scalability of the server device. However, for testing the scalability of the client DUTs additional recommendations are needed.

For encapsulation transition technologies a m:n setup can be created, where m is the number of flows applied to the same client device and n the number of client devices connected to the same server device.

For the translation based transition technologies the client devices can be separately tested with n network flows using the test setup presented in Figure 3.

10.2. Benchmarking Performance Degradation

10.2.1. Network performance degradation with simultaneous load

Objective: To quantify the performance degradation introduced by n parallel and simultaneous network flows.

Procedure: First, the benchmarking tests presented in [Section 6](#) have to be performed for one network flow.

The same tests have to be repeated for n network flows, where the network flows are started simultaneously. The performance degradation of the X benchmarking dimension SHOULD be calculated as relative performance change between the 1-flow results and the n-flow results, using the following formula:

$$Xpd = \frac{X_n - X_1}{X_1} * 100, \text{ where: } X_1 - \text{result for 1-flow}$$

$$X_n - \text{result for n-flows}$$

As a guideline for the maximum number of flows n, the value can be deduced by measuring the Concurrent TCP Connection Capacity as described by [[RFC3511](#)], following the test setups specified by [Section 4](#).

Reporting Format: The performance degradation SHOULD be expressed as a percentage. The number of tested parallel flows n MUST be clearly specified. For each of the performed benchmarking tests, there SHOULD be a table containing a column for each frame size. The table SHOULD also state the applied frame rate.

[10.2.2. Network performance degradation with incremental load](#)

Objective: To quantify the performance degradation introduced by n parallel and incrementally started network flows.

Procedure: First, the benchmarking tests presented in [Section 6](#) have to be performed for one network flow.

The same tests have to be repeated for n network flows, where the network flows are started incrementally in succession, each after time T. In other words, if flow I is started at time x, flow i+1 will be started at time x+T. Considering the time T, the time duration of each iteration must be extended with the time necessary to start all the flows, namely (n-1)xT. The measurement for the first flow SHOULD be at least 60 seconds in duration.

The performance degradation of the X benchmarking dimension SHOULD be calculated as relative performance change between the 1-flow results and the n-flow results, using the following formula presented in [Section 9.2.1](#). Intermediary degradation points for 1/4*n, 1/2*n and 3/4*n MAY also be performed.

Reporting Format: The performance degradation SHOULD be expressed as a percentage. The number of tested parallel flows n MUST be clearly specified. For each of the performed benchmarking tests, there SHOULD be a table containing a column for each frame size. The table SHOULD also state the applied frame rate and time duration T , used as increment step between the network flows. The units of measurement for T SHOULD be seconds. A column for the intermediary degradation points MAY also be displayed.

11. NAT44 and NAT66

Although these technologies are not the primarily scope of this document, the benchmarking methodology associated with single translation technologies as defined in [Section 4.1](#) can be employed to benchmark NAT44 (as defined by [\[RFC2663\]](#) with the behavior described by [\[RFC7857\]](#)) implementations and NAT66 (as defined by [\[RFC6296\]](#)) implementations.

12. Summarizing function and variation

To ensure the stability of the benchmarking scores obtained using the tests presented in Sections [6-9](#), multiple test iterations are RECOMMENDED. Using a summarizing function (or measure of central tendency) can be a simple and effective way to compare the results obtained across different iterations. However, over-summarization is an unwanted effect of reporting a single number.

Measuring the variation (dispersion index) can be used to counter the over-summarization effect. Empirical data obtained following the proposed methodology can also offer insights on which summarizing function would fit better.

To that end, data presented in [\[ietf95pres\]](#) indicate the median as suitable summarizing function and the 1st and 99th percentiles as variation measures for DNS Resolution Performance and PDV. . The median and percentile calculation functions SHOULD follow the recommendations of [\[RFC2330\] Section 11.3](#).

For a fine grain analysis of the frequency distribution of the data, histograms or cumulative distribution function plots can be employed.

13. Security Considerations

Benchmarking activities as described in this memo are limited to technology characterization using controlled stimuli in a laboratory

Internet-Draft IPv6 transition tech benchmarking July 2016
environment, with dedicated address space and the constraints
specified in the sections above.

The benchmarking network topology will be an independent test setup and MUST NOT be connected to devices that may forward the test traffic into a production network, or misroute traffic to the test management network.

Further, benchmarking is performed on a "black-box" basis, relying solely on measurements observable external to the DUT/SUT. Special capabilities SHOULD NOT exist in the DUT/SUT specifically for benchmarking purposes. Any implications for network security arising from the DUT/SUT SHOULD be identical in the lab and in production networks.

14. IANA Considerations

The IANA has allocated the prefix 2001:0002::/48 [[RFC5180](#)] for IPv6 benchmarking. For IPv4 benchmarking, the 198.18.0.0/15 prefix was reserved, as described in [[RFC6890](#)]. The two ranges are sufficient for benchmarking IPv6 transition technologies.

15. References

15.1. Normative References

- [RFC1242] Bradner, S., "Benchmarking Terminology for Network Interconnection Devices", [RFC 1242](#), July 1991.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2330] Paxson, V., Almes, G., Mahdavi, J., and M. Mathis. "Framework for IP performance metrics." [RFC 2330](#), May 1998.
- [RFC2544] Bradner, S., and J. McQuaid, "Benchmarking Methodology for Network Interconnect Devices", [RFC 2544](#), March 1999.
- [RFC2647] Newman, D., "Benchmarking Terminology for Firewall Devices", [[RFC2647](#)], August 1999.
- [RFC3393] Demichelis, C. and P. Chimento, "IP Packet Delay Variation Metric for IP Performance Metrics (IPPM)", [RFC 3393](#), November 2002.
- [RFC3511] Hickman, B., Newman, D., Tadjudin, S. and T. Martin, "Benchmarking Methodology for Firewall Performance", [RFC 3511](#), April 2003.

- [[RFC5180](#)] Popoviciu, C., Hamza, A., Van de Velde, G., and D. Dugatkin, "IPv6 Benchmarking Methodology for Network Interconnect Devices", [RFC 5180](#), May 2008.
- [RFC5481] Morton, A., and B. Claise, "Packet Delay Variation Applicability Statement", [RFC 5481](#), March 2009.
- [RFC6201] Asati, R., Pignataro, C., Calabria, F. and C. Olvera, "Device Reset Characterization ", [RFC 6201](#), March 2011.

15.2. Informative References

- [RFC2663] Srisuresh, P., and M. Holdrege. "IP Network Address Translator (NAT) Terminology and Considerations", [RFC2663](#), August 1999.
- [RFC4213] Nordmark, E. and R. Gilligan, "Basic Transition Mechanisms for IPv6 Hosts and Routers", [RFC 4213](#), October 2005.
- [RFC5569] Despres, R., "IPv6 Rapid Deployment on IPv4 Infrastructures (6rd)", [RFC 5569](#), DOI 10.17487/RFC5569, January 2010, <<http://www.rfc-editor.org/info/rfc5569>>.
- [RFC6144] Baker, F., Li, X., Bao, C., and K. Yin, "Framework for IPv4/IPv6 Translation", [RFC 6144](#), April 2011.
- [RFC6145] Li, X., Bao, C., and F. Baker, "IP/ICMP Translation Algorithm", [RFC 6145](#), DOI 10.17487/RFC6145, April 2011, <<http://www.rfc-editor.org/info/rfc6145>>.
- [RFC6146] Bagnulo, M., Matthews, P., and I. van Beijnum, "Stateful NAT64: Network Address and Protocol Translation from IPv6 Clients to IPv4 Servers", [RFC 6146](#), DOI 10.17487/RFC6146, April 2011, <<http://www.rfc-editor.org/info/rfc6146>>.
- [RFC6219] Li, X., Bao, C., Chen, M., Zhang, H., and J. Wu, "The China Education and Research Network (CERNET) IVI Translation Design and Deployment for the IPv4/IPv6 Coexistence and Transition", [RFC 6219](#), DOI 10.17487/RFC6219, May 2011, <<http://www.rfc-editor.org/info/rfc6219>>.
- [RFC6296] Wasserman, M., and F. Baker. "IPv6-to-IPv6 network prefix translation." [RFC6296](#), June 2011.

- Internet-Draft IPv6 transition tech benchmarking July 2016
- [[RFC6333](#)] Durand, A., Droms, R., Woodyatt, J., and Y. Lee, "Dual-Stack Lite Broadband Deployments Following IPv4 Exhaustion", [RFC 6333](#), August 2011.
 - [RFC6877] Mawatari, M., Kawashima, M., and C. Byrne, "464XLAT: Combination of Stateful and Stateless Translation", [RFC 6877](#), DOI 10.17487/RFC6877, April 2013, <<http://www.rfc-editor.org/info/rfc6877>>.
 - [RFC6890] Cotton, M., Vegoda, L., Bonica, R., and B. Haberman, "Special-Purpose IP Address Registries", [BCP 153](#), [RFC6890](#), April 2013.
 - [RFC7596] Cui, Y., Sun, Q., Boucadair, M., Tsou, T., Lee, Y., and I. Farrer, "Lightweight 4over6: An Extension to the Dual-Stack Lite Architecture", [RFC 7596](#), DOI 10.17487/RFC7596, July 2015, <<http://www.rfc-editor.org/info/rfc7596>>.
 - [RFC7597] Troan, O., Ed., Dec, W., Li, X., Bao, C., Matsushima, S., Murakami, T., and T. Taylor, Ed., "Mapping of Address and Port with Encapsulation (MAP-E)", [RFC 7597](#), DOI 10.17487/RFC7597, July 2015, <<http://www.rfc-editor.org/info/rfc7597>>.
 - [RFC7599] Li, X., Bao, C., Dec, W., Ed., Troan, O., Matsushima, S., and T. Murakami, "Mapping of Address and Port using Translation (MAP-T)", [RFC 7599](#), DOI 10.17487/RFC7599, July 2015, <<http://www.rfc-editor.org/info/rfc7599>>.
 - [RFC7857] Penno, R., Perreault, S., Boucadair, M., Sivakumar, S., and K. Naito "Updates to Network Address Translation (NAT) Behavioral Requirements" [RFC 7857](#), April 2016.
 - [Dns64perf] Bakai, D., "A C++11 DNS64 performance tester", available: <https://github.com/bakaid/dns64perfpp>
 - [ietf95pres] Georgescu, M., "Benchmarking Methodology for IPv6 Transition Technologies", IETF 95, Buenos Aires, Argentina, April 2016, available: <https://www.ietf.org/proceedings/95/slides/slides-95-bmwg-2.pdf>

16. Acknowledgements

The authors would like to thank Youki Kadobayashi and Hiroaki Hazeyama for their constant feedback and support. The thanks should be extended to the NECOMA project members for their continuous

Internet-Draft IPv6 transition tech benchmarking July 2016
support. We would also like to thank Scott Bradner for the useful
suggestions. We also note that portions of text from Scott's
documents were used in this memo (e.g. Latency section). A big thank
you to Al Morton and Fred Baker for their detailed review of the
draft and very helpful suggestions. Other helpful comments and
suggestions were offered by Bhuvaneshwaran Vengainathan, Andrew
McGregor, Nalini Elkins, Kaname Nishizuka, Yasuhiro Ohara, Masataka
Mawatari, Kostas Pentikousis, Bela Almasi, Tim Chown, Paul Emmerich
and Stenio Fernandes. A special thank you to the RFC Editor Team for
their thorough editorial review and helpful suggestions. This
document was prepared using 2-Word-v2.0.template.dot.

[Appendix A.](#)

Theoretical Maximum Frame Rates

This appendix describes the recommended calculation formulas for the theoretical maximum frame rates to be employed over Ethernet as example media. The formula takes into account the frame size overhead created by the encapsulation or the translation process. For example, the 6in4 encapsulation described in [[RFC4213](#)] adds 20 bytes of overhead to each frame.

Considering X to be the frame size and O to be the frame size overhead created by the encapsulation on translation process, the maximum theoretical frame rate for Ethernet can be calculated using the following formula:

$$\frac{\text{Line Rate (bps)}}{(8\text{bits/byte}) \cdot (X+O+20)\text{bytes/frame}}$$

The calculation is based on the formula recommended by [RFC5180](#) in [Appendix A1](#). As an example, the frame rate recommended for testing a 6in4 implementation over 10Mb/s Ethernet with 64 bytes frames is:

$$\frac{10,000,000(\text{bps})}{(8\text{bits/byte}) \cdot (64+20+20)\text{bytes/frame}} = 12,019 \text{ fps}$$

The complete list of recommended frame rates for 6in4 encapsulation can be found in the following table:

Frame size (bytes)	10 Mb/s (fps)	100 Mb/s (fps)	1000 Mb/s (fps)	10000 Mb/s (fps)
64	12,019	120,192	1,201,923	12,019,231
128	7,440	74,405	744,048	7,440,476
256	4,223	42,230	422,297	4,222,973
512	2,264	22,645	226,449	2,264,493
1024	1,175	11,748	117,481	1,174,812
1280	947	9,470	94,697	946,970
1518	802	8,023	80,231	802,311
1522	800	8,003	80,026	800,256
2048	599	5,987	59,866	598,659
4096	302	3,022	30,222	302,224
8192	152	1,518	15,185	151,846
9216	135	1,350	13,505	135,048

Internet-Draft IPv6 transition tech benchmarking July 2016

Authors' Addresses

Marius Georgescu
Nara Institute of Science and Technology (NAIST)
Takayama 8916-5
Nara
Japan

Phone: +81 743 72 5216
Email: liviumarius-g@is.naist.jp

Gabor Lencse
Szechenyi Istvan University
Egyetem ter 1.
Gyor
Hungary

Phone: +36 20 775 8267
Email: lencse@sze.hu