

Internet Draft

Expires February 2006

[draft-ietf-bridge-rstpmib-08.txt](#)

V. Ngai

Enterasys Networks

E. Bell

3Com Corp.

August 2005

**Definitions of Managed Objects for Bridges
with Rapid Spanning Tree Protocol**

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Copyright Notice

Copyright (C) The Internet Society (2005). All Rights Reserved.

Abstract

This memo defines an SMIV2 MIB module for managing the Rapid Spanning Tree capability defined by the IEEE P802.1t and P802.1w amendments to IEEE Std 802.1D-1998 for bridging between Local Area Network (LAN) segments. The objects in this MIB are defined to apply both to transparent bridging and to bridges connected by subnetworks other than LAN segments.

Table of Contents

1	The Internet-Standard Management Framework	3
2	Overview	3
3	Relationship to IEEE 802.1t and 802.1w amendments	3
4	Relation to the BRIDGE-MIB	4
5	Definitions for RSTP-MIB	5
6	Acknowledgments	12
7	IANA Considerations	12
8	Security Considerations	12
9	Normative References	14
10	Informative References	15
11	Authors' Addresses	16
	Intellectual Property Statement	17
	Disclaimer of Validity	17
	Copyright Statement	17

1. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

2. Overview

This memo defines an SMIV2 MIB module for managing the Rapid Spanning Tree (RSTP) capability defined by the IEEE P802.1t [[802.1t](#)] and P802.1w [[802.1w](#)] amendments to IEEE Std 802.1D-1998 [[802.1D-1998](#)] for bridging between Local Area Network (LAN) segments. The objects in this MIB are defined to apply both to transparent bridging and to bridges connected by subnetworks other than LAN segments.

3. Relationship to IEEE 802.1t and 802.1w amendments

This document defines managed object for the Rapid Spanning Tree Protocol defined by the IEEE P802.1t and IEEE P802.1w amendments to 802.1d-1998.

RSTP-MIB Name	IEEE 802.1 Reference
dot1dStp	
dot1dStpVersion	(w) 17.16.1 ForceVersion
dot1dStpTxHoldCount	(w) 17.16.6 TxHoldCount
dot1dStpExtPortTable	
dot1dStpPortProtocolMigration	(w) 17.18.10 mcheck
dot1dStpPortAdminEdgePort	(t) 18.3.3 adminEdgePort
dot1dStpPortOperEdgePort	(t) 18.3.4 operEdgePort
dot1dStpPortAdminPointToPoint	(w) 6.4.3 adminPointToPointMAC
dot1dStpPortOperPointToPoint	(w) 6.4.3 operPointToPointMAC
dot1dStpPortAdminPathCost	(D) 8.5.5.3 Path Cost

Following are the references for the above objects in 802.1D-2004

[[802.1D-2004](#)].

RSTP-MIB Name	IEEE 802.1D-2004 Reference
dot1dStp	
dot1dStpVersion	17.13.4 ForceVersion
dot1dStpTxHoldCount	17.13.12 TxHoldCount
dot1dStpExtPortTable	
dot1dStpPortProtocolMigration	17.19.13 mcheck
dot1dStpPortAdminEdgePort	17.13.1 adminEdgePort
dot1dStpPortOperEdgePort	17.19.17 operEdgePort
dot1dStpPortAdminPointToPoint	6.4.3 adminPointToPointMAC
dot1dStpPortOperPointToPoint	6.4.3 operPointToPointMAC
dot1dStpPortAdminPathCost	17.13.11 Path Cost

4. Relation to the BRIDGE-MIB

The Original BRIDGE-MIB [[RFC1493](#)] has been updated in an SMIV2-compliant version [[RFC1493bis](#)]. Conformance statements have been added and some description and reference clauses have been updated. The interpretations of some objects were changed to accommodate IEEE 802.1t and 802.1w amendments.

The object dot1dStpPortPathCost32 was added to support IEEE 802.1t, and the permissible values of dot1dStpPriority and dot1dStpPortPriority have been clarified for bridges supporting IEEE 802.1t or IEEE 802.1w. The interpretation of dot1dStpTimeSinceTopologyChange has been clarified for bridges supporting the RSTP.

See the updated BRIDGE-MIB [[RFC1493bis](#)] for details.

The objects in the RSTP-MIB supplement those defined in the Bridge MIB [[RFC1493bis](#)].

5. Definitions for RSTP-MIB

```
RSTP-MIB DEFINITIONS ::= BEGIN
```

```
-- -----  
-- MIB for IEEE 802.1w Rapid Spanning Tree Protocol  
-- -----
```

IMPORTS

```
    MODULE-IDENTITY, OBJECT-TYPE, Integer32, mib-2  
        FROM SNMPv2-SMI  
    TruthValue  
        FROM SNMPv2-TC  
    MODULE-COMPLIANCE, OBJECT-GROUP  
        FROM SNMPv2-CONF  
    dot1dStp, dot1dStpPortEntry  
        FROM BRIDGE-MIB;
```

rstpMIB MODULE-IDENTITY

```
    LAST-UPDATED "200507290000Z"  
    ORGANIZATION "IETF Bridge MIB Working Group"  
    CONTACT-INFO  
        "Email: Bridge-mib@ietf.org"  
    DESCRIPTION  
        "The Bridge MIB Extension module for managing devices  
        that support the Rapid Spanning Tree Protocol defined  
        by IEEE 802.1w."  
    REVISION      "200507290000Z"
```

```
-- RFC Ed.: replace XXXX with RFC number and remove this note
```

```
    DESCRIPTION  
        "Copyright (C) The Internet Society (2005). The initial  
        version of this MIB module was published in RFC XXXX; for full  
        legal notices see the RFC itself. Supplementary information  
        may be available at:  
        http://www.ietf.org/copyrights/ianamib.html."
```

```
-- RFC Ed.: replace xxxx with IANA-assigned number and
```

```
--     remove this note
```

```
    ::= { mib-2 xxxx }
```

```
-- -----  
-- subtrees in the RSTP-MIB  
-- -----
```

```
rstpNotifications OBJECT IDENTIFIER ::= { rstpMIB 0 }  
rstpObjects        OBJECT IDENTIFIER ::= { rstpMIB 1 }  
rstpConformance    OBJECT IDENTIFIER ::= { rstpMIB 2 }
```



```
-- -----
-- Addition to the dot1dStp group
-- -----

dot1dStpVersion OBJECT-TYPE
    SYNTAX      INTEGER {
                    stpCompatible(0),
                    rstp(2)
                }
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "The version of Spanning Tree Protocol the bridge is
        currently running.  The value 'stpCompatible(0)'
        indicates the Spanning Tree Protocol specified in
        IEEE 802.1D-1998 and 'rstp(2)' indicates the Rapid
        Spanning Tree Protocol specified in IEEE 802.1w and
        clause 17 of 802.1D-2004.  The values are directly from
        the IEEE standard.  New values may be defined as future
        versions of the protocol become available.

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE
        "IEEE 802.1w clause 14.8.1, 17.12, 17.16.1"
    DEFVAL       { rstp }
    ::= { dot1dStp 16 }

dot1dStpTxHoldCount OBJECT-TYPE
    SYNTAX      Integer32 (1..10)
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "The value used by the Port Transmit state machine to limit
        the maximum transmission rate.

        The value of this object MUST be retained across
        reinitializations of the management system."

    REFERENCE
        "IEEE 802.1w clause 17.16.6"
    DEFVAL       { 3 }
    ::= { dot1dStp 17 }

--
-- { dot1dStp 18 } was used to represent dot1dStpPathCostDefault
```



```
-- in an internet-draft version of this MIB.  It has since been
-- obsoleted, and should not be used.
--
```

dot1dStpExtPortTable OBJECT-TYPE

SYNTAX SEQUENCE OF Dot1dStpExtPortEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A table that contains port-specific Rapid Spanning Tree information."

::= { dot1dStp 19 }

dot1dStpExtPortEntry OBJECT-TYPE

SYNTAX Dot1dStpExtPortEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A list of Rapid Spanning Tree information maintained by each port."

AUGMENTS { dot1dStpPortEntry }

::= { dot1dStpExtPortTable 1 }

Dot1dStpExtPortEntry ::=

SEQUENCE {

dot1dStpPortProtocolMigration

TruthValue,

dot1dStpPortAdminEdgePort

TruthValue,

dot1dStpPortOperEdgePort

TruthValue,

dot1dStpPortAdminPointToPoint

INTEGER,

dot1dStpPortOperPointToPoint

TruthValue,

dot1dStpPortAdminPathCost

Integer32

}

dot1dStpPortProtocolMigration OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"When operating in RSTP (version 2) mode, writing true(1) to this object forces this port to transmit RSTP BPDUs."

Any other operation on this object has no effect and it always returns false(2) when read."

REFERENCE

"IEEE 802.1w clause 14.8.2.4, 17.18.10, 17.26"
 ::= { dot1dStpExtPortEntry 1 }

dot1dStpPortAdminEdgePort OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The administrative value of the Edge Port parameter. A value of true(1) indicates that this port should be assumed as an edge-port and a value of false(2) indicates that this port should be assumed as a non-edge-port. Setting this object will also cause the corresponding instance of dot1dStpPortOperEdgePort to change to the same value. Note that even when this object's value is true, the value of the corresponding instance of dot1dStpPortOperEdgePort can be false if a BPDU has been received.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE

"IEEE 802.1t clause 14.8.2, 18.3.3"
 ::= { dot1dStpExtPortEntry 2 }

dot1dStpPortOperEdgePort OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The operational value of the Edge Port parameter. The object is initialized to the value of the corresponding instance of dot1dStpPortAdminEdgePort. When the corresponding instance of dot1dStpPortAdminEdgePort is set, this object will be changed as well. This object will also be changed to false on reception of a BPDU."

REFERENCE

"IEEE 802.1t clause 14.8.2, 18.3.4"
 ::= { dot1dStpExtPortEntry 3 }

dot1dStpPortAdminPointToPoint OBJECT-TYPE

SYNTAX INTEGER {


```
        forceTrue(0),
        forceFalse(1),
        auto(2)
    }
MAX-ACCESS    read-write
STATUS        current
DESCRIPTION
    "The administrative point-to-point status of the LAN segment
    attached to this port, using the enumeration values of the
    IEEE 802.1w clause. A value of forceTrue(0) indicates
    that this port should always be treated as if it is connected
    to a point-to-point link. A value of forceFalse(1) indicates
    that this port should be treated as having a shared media
    connection. A value of auto(2) indicates that this port is
    considered to have a point-to-point link if it is an Aggregator
    and all of its members are aggregatable, or if the MAC entity
    is configured for full duplex operation, either through
    auto-negotiation or by management means. Manipulating this
    object changes the underlying adminPortToPortMAC.

    The value of this object MUST be retained across
    reinitializations of the management system."
```

REFERENCE

```
    "IEEE 802.1w clause 6.4.3, 6.5, 14.8.2"
 ::= { dot1dStpExtPortEntry 4 }
```

dot1dStpPortOperPointToPoint OBJECT-TYPE

```
SYNTAX        TruthValue
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "The operational point-to-point status of the LAN segment
    attached to this port. It indicates whether a port is
    considered to have a point-to-point connection or not.
    If adminPointToPointMAC is set to auto(2), then the value
    of operPointToPointMAC is determined in accordance with the
    specific procedures defined for the MAC entity concerned,
    as defined in IEEE 802.1w clause 6.5. The value is
    determined dynamically; i.e., it is re-evaluated whenever
    the value of adminPointToPointMAC changes, and whenever
    the specific procedures defined for the MAC entity evaluate
    a change in its point-to-point status."
REFERENCE
    "IEEE 802.1w clause 6.4.3, 6.5, 14.8.2"
 ::= { dot1dStpExtPortEntry 5 }
```


dot1dStpPortAdminPathCost OBJECT-TYPE

SYNTAX Integer32 (0..200000000)

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The administratively assigned value for the contribution of this port to the path cost of paths towards the spanning tree root.

Writing a value of '0' assigns the automatically calculated default Path Cost value to the port. If the default Path Cost is being used, this object returns '0' when read.

This complements the object dot1dStpPortPathCost or dot1dStpPortPathCost32, which returns the operational value of the path cost.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE

"IEEE 802.1D-1998: [Section 8.5.5.3](#)"

::= { dot1dStpExtPortEntry 6 }

-- rstpMIB - Conformance Information

rstpGroups OBJECT IDENTIFIER ::= { rstpConformance 1 }

rstpCompliances OBJECT IDENTIFIER ::= { rstpConformance 2 }

-- Units of conformance

rstpBridgeGroup OBJECT-GROUP

OBJECTS {

dot1dStpVersion,

dot1dStpTxHoldCount

}

STATUS current

DESCRIPTION

"Rapid Spanning Tree information for the bridge."

::= { rstpGroups 1 }

rstpPortGroup OBJECT-GROUP


```
OBJECTS {
    dot1dStpPortProtocolMigration,
    dot1dStpPortAdminEdgePort,
    dot1dStpPortOperEdgePort,
    dot1dStpPortAdminPointToPoint,
    dot1dStpPortOperPointToPoint,
    dot1dStpPortAdminPathCost
}
STATUS      current
DESCRIPTION
    "Rapid Spanning Tree information for individual ports."
::= { rstpGroups 2 }
```

```
-- -----
-- Compliance statements
-- -----
```

```
rstpCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION
        "The compliance statement for device support of Rapid
        Spanning Tree Protocol (RSTP) bridging services."
    MODULE
        MANDATORY-GROUPS {
            rstpBridgeGroup,
            rstpPortGroup
        }
    ::= { rstpCompliances 1 }
```

```
END
```


6. Acknowledgments

This document was produced on behalf of the Bridge MIB Working Group in the Operations and Management area of the Internet Engineering Task Force.

The authors wish to thank the members of the Bridge MIB Working Group, especially Alex Ruzin, for their comments and suggestions which improved this effort.

7. IANA Considerations

This document requires an OID assignment to be made by IANA:

Descriptor	OBJECT IDENTIFIER value
-----	-----
rstpMIB	{ mib-2 xxxx }

8. Security Considerations

There are a number of management objects defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

Writable objects that could be misused to cause network delays and spanning tree instabilities include dot1dStpVersion, dot1dStpTxHoldCount, dot1dStpPortProtocolMigration, dot1dStpPortAdminEdgePort, and dot1dStpPortAdminPathCost.

dot1dStpVersion could be read by an attacker to identify environments containing applications or protocols which are potentially sensitive to RSTP mode.

dot1dStpPortAdminPointToPoint could be used to mislead an access control protocol, such as 802.1x, to believe that only one other system is attached to a LAN segment and to enable network access based on that assumption. This situation could permit potential man-in-the-middle attacks.

SNMPv1 by itself is not a secure environment. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [\[RFC3410\]](#), [section 8](#)), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy), and user-based access control.

9. Normative References

- [RFC2578] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M., and S. Waldbusser, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [802.1D-1998] "Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Common specifications - Part 3: Media Access Control (MAC) Bridges: Revision. This is a revision of ISO/IEC 10038: 1993, 802.1j-1992 and 802.6k-1992. It incorporates P802.11c, P802.1p and P802.12e." ISO/IEC 15802-3: 1998.
- [802.1D-2004] IEEE Project 802 Local and Metropolitan Area Networks, "IEEE Standard 802.1D-2004 MAC Bridges", 2004.
- [RFC1493] Decker, E., Langille, P., Rijssinghani, A. and K. McCloghrie, "Definitions of Managed Objects for Bridges", [RFC 1493](#), July 1993.
- [RFC1493bis] Bell, E. and Norseth, K., "Definitions of Managed Objects for Bridges", [draft-ietf-bridge-bridgemib-smiv2-10.txt](#), February 2005. NOTE TO RFC EDITOR: Replace the above ID reference with the appropriate RFC.
- [802.1t] IEEE 802.1t-2001, "(Amendment to IEEE Standard 802.1D) IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Common specifications - Part 3: Media Access Control (MAC) Bridges: Technical and Editorial Corrections".
- [802.1w] IEEE 802.1w-2001, "(Amendment to IEEE Standard 802.1D) IEEE Standard for Information technology--Telecommunications and information exchange between systems--Local and metropolitan area networks--Common Specifications--Part 3:

Media Access Control (MAC) Bridges: Rapid Reconfiguration".

10. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D. and B. Stewart,
"Introduction and Applicability Statements for Internet
Standard Management Framework", [RFC 3410](#), December 2002.

11. Authors' Addresses

Les Bell
3Com Europe Limited
eCom Centre, Boundary Way
Hemel Hempstead
Herts. HP2 7YU
UK

Phone: +44 1442 438025
Email: Les_Bell@3Com.com

Vivian Ngai
Enterasys Networks
2691 South Decker Lake Lane
Salt Lake City, UT 84119
USA

Phone: +1 801 556 5652
Email: vivian_ngai@acm.org

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005).

This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

