

Network Working Group  
Internet-Draft  
Updates: [5545](#) (if approved)  
Intended status: Standards Track  
Expires: 23 September 2022

M. Douglass  
Bedework  
22 March 2022

Support for iCalendar Relationships  
draft-ietf-calext-ical-relations-11

## Abstract

This specification updates the iCalendar RELATED-TO property defined in [RFC5545](#) by adding new relation types and introduces new iCalendar properties LINK, CONCEPT and REFID to allow better linking and grouping of iCalendar components and related data.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 23 September 2022.

## Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">1.1.</a>	Structured iCalendar relationships . . . . .	<a href="#">3</a>
<a href="#">1.2.</a>	Grouped iCalendar relationships . . . . .	<a href="#">3</a>
<a href="#">1.3.</a>	Concept relationships . . . . .	<a href="#">3</a>
<a href="#">1.4.</a>	Linked relationships . . . . .	<a href="#">4</a>
<a href="#">1.5.</a>	Caching and offline use . . . . .	<a href="#">5</a>
<a href="#">1.6.</a>	Conventions Used in This Document . . . . .	<a href="#">5</a>
<a href="#">2.</a>	LINK Property Reference Types . . . . .	<a href="#">5</a>
<a href="#">3.</a>	Link Relation Types . . . . .	<a href="#">6</a>
<a href="#">4.</a>	New temporal RELTYPE Parameter values . . . . .	<a href="#">6</a>
<a href="#">5.</a>	Additional New RELTYPE Parameter Values . . . . .	<a href="#">8</a>
<a href="#">6.</a>	New Property Parameters . . . . .	<a href="#">8</a>
<a href="#">6.1.</a>	Link Relation . . . . .	<a href="#">9</a>
<a href="#">6.2.</a>	Gap . . . . .	<a href="#">9</a>
<a href="#">7.</a>	New Value Data Types . . . . .	<a href="#">10</a>
<a href="#">8.</a>	New Properties . . . . .	<a href="#">11</a>
<a href="#">8.1.</a>	Concept . . . . .	<a href="#">11</a>
<a href="#">8.2.</a>	Link . . . . .	<a href="#">12</a>
<a href="#">8.3.</a>	Refid . . . . .	<a href="#">14</a>
<a href="#">9.</a>	Updates to <a href="#">RFC 5545</a> . . . . .	<a href="#">14</a>
<a href="#">9.1.</a>	RELATED-TO . . . . .	<a href="#">15</a>
<a href="#">10.</a>	Security Considerations . . . . .	<a href="#">17</a>
<a href="#">11.</a>	IANA Considerations . . . . .	<a href="#">17</a>
<a href="#">11.1.</a>	iCalendar Property Registrations . . . . .	<a href="#">17</a>
<a href="#">11.2.</a>	iCalendar Property Parameter Registrations . . . . .	<a href="#">18</a>
<a href="#">11.3.</a>	iCalendar Value Data Type Registrations . . . . .	<a href="#">18</a>
<a href="#">11.4.</a>	iCalendar RELTYPE Value Registrations . . . . .	<a href="#">19</a>
<a href="#">11.5.</a>	New Reference Type Registration . . . . .	<a href="#">19</a>
<a href="#">12.</a>	Acknowledgements . . . . .	<a href="#">20</a>
<a href="#">13.</a>	References . . . . .	<a href="#">20</a>
<a href="#">13.1.</a>	Informative References . . . . .	<a href="#">20</a>
<a href="#">13.2.</a>	Normative References . . . . .	<a href="#">20</a>
	Author's Address . . . . .	<a href="#">21</a>

[1.](#) Introduction

iCalendar entities defined in [\[RFC5545\]](#) often need to be related to each other or to associated meta-data. The specifications below support relationships of the following forms:

Structured iCalendar: iCalendar entities can be related to each

other in some structured way, for example as parent, sibling, before, after.

Grouped iCalendar: iCalendar entities can be related to each other

as a group. CATEGORIES are often used for this purpose but are problematic for application developers due to their lack of consistency and use as a free-form tag.

Linked: Entities can be linked to other entities such as vcards through a URI and associated REL and FMTTYPE parameters.

### [1.1.](#) Structured iCalendar relationships

The iCalendar [[RFC5545](#)] RELATED-TO property has no support for temporal relationships as used by project management tools.

The RELTYPE parameter is extended to take new values defining temporal relationships, a GAP parameter is defined to provide lead and lag values, and RELATED-TO is extended to allow URI values. These changes allow the RELATED-TO property to define a richer set of relationships useful for project management.

### [1.2.](#) Grouped iCalendar relationships

This specification defines a new REFID property which allows arbitrary groups of entities to be associated with the same key value.

REFID is used to identify a key allowing the association of components that are all related to the referring, aggregating component and the retrieval of components based on this key. For example, this may be used to identify the tasks associated with a given project without having to communicate the task structure of the project. A further example is the grouping of all sub-tasks associated with the delivery of a specific package in a package delivery system.

As such, the presence of a REFID property imparts no meaning to the component. It is merely a key to allow retrieval. This is distinct from categorisation which, while allowing grouping also adds meaning

to the component to which it is attached.

### 1.3. Concept relationships

The name CONCEPT is used by the Simple Knowledge Organization System defined in [[W3C.REC-skos-reference-20090818](#)]. The term "concept" more accurately defines what we often mean by a category. It's not the text string that is important but the meaning attached to it. For example, the term "football" can mean very different sports.

Douglass

Expires 23 September 2022

[Page 3]

---

Internet-Draft

iCalendar Relationships

March 2022

The introduction of CONCEPT allows a more structured approach to categorization, with the possibility of namespaced and path-like values. Unlike REFID the CONCEPT property imparts some meaning. It is assumed that the value of this property will reference a well defined category.

The current [[RFC5545](#)] CATEGORY property is used as a free form 'tagging' field. These values have some meaning to those who apply them but not necessarily to any consumer. As such it is difficult to establish formal relationships between components based on their category.

Rather than attempt to add semantics to the CATEGORY property it seems best to continue its usage as an informal tag and establish a new CONCEPT property with more constraints.

### 1.4. Linked relationships

The currently existing iCalendar standard [[RFC5545](#)] lacks a general purpose method for referencing additional, external information relating to calendar components.

This document proposes a method for referencing typed external information that can provide additional information about an iCalendar component. This new LINK property is closely aligned to [[RFC8288](#)] which defines the generic concept of Web Linking as well as its expression in the HTTP LINK header field.

The LINK property defines a typed reference or relation to external

meta-data or related resources. By providing type and format information as parameters, clients and servers are able to discover interesting references and make use of them, perhaps for indexing or the presentation of interesting links for the user.

Calendar components are often grouped into collections to represent a calendar or a series of tasks, for example [[RFC4791](#)]' (CalDAV) calendar collections.

It is also often necessary to reference calendar components in other collections. For example, a VEVENT might refer to a VTODO from which it was derived. The PARENT, SIBLING and CHILD relationships defined for the RELATED-TO property only allow for a UID which is inadequate for many purposes. Allowing other value types for those relationships may help but would cause backward compatibility issues. The LINK property can link components in different collections or even on different servers.

When publishing events it is useful to be able to refer back to the source of that information. The actual event may have been consumed from a feed or an ics file on a web site. A LINK property can provide a reference to the originator of the event.

Beyond the need to relate elements temporally, project management tools often need to be able to specify the relationships between the various events and tasks which make up a project. The LINK property provides such a mechanism.

The LINK property MUST NOT be treated as just another attachment. The ATTACH property defined in [[RFC5545](#)] has been extended by [[RFC8607](#)] to handle server-side management and stripping of inline data and to provide additional data about the attachment (size, filename etc).

Additionally clients may choose to handle attachments differently from the LINK property as attachments are often an integral part of the message - for example, the agenda.

#### [1.5](#). Caching and offline use

In general, the calendar entity should be self explanatory without the need to download referenced meta-data such as a web page.

However, to facilitate offline display the link type may identify important pieces of data which should be downloaded in advance.

## [1.6.](#) Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY" and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

The notation used in this memo to (re-)define iCalendar elements is the ABNF notation of [[RFC5234](#)] as used by [[RFC5545](#)]. Any syntax elements shown below that are not explicitly defined in this specification come from iCalendar [[RFC5545](#)].

## [2.](#) LINK Property Reference Types

The reference value in the LINK property defined below can take three forms specified by the VALUE parameter:

URI: This is a URI referring to the target.

UID: This allows for linking within a single collection of calendar components and the value MUST refer to another component within the same collection.

XML-REFERENCE: In an XML environment it may be necessary to refer to a fragment of an external XML artifact. This value is a URI with an XPointer anchor value. The XPointer is defined in [[W3C.WD-xptr-xpointer-20021219](#)] and its use as an anchor is defined in [[W3C.REC-xptr-framework-20030325](#)]

Note that UID references may need updating on import. An example, is data to be imported from a file containing VTOD0 and VEVENT components with a VTOD0 referring to VEVENT components by UID. When imported into a CalDAV system, the VTOD0 components are typically placed in a different collection from the VEVENT components. This

would require the UID reference to be replaced with a URI.

### 3. Link Relation Types

[RFC8288] defines two forms of relation type: registered and extension. Registered relation types are added to the Link Relations registry as specified in [Section 2.1.1 of \[RFC8288\]](#). Extension relation types, defined in [Section 2.1.2 of \[RFC8288\]](#), are specified as unique URIs that are not registered in the registry.

The relation types defined in [Section 6.1](#) will be registered with IANA in accordance with the specifications in [\[RFC8288\]](#).

### 4. New temporal RELTYPE Parameter values

This section defines the usual temporal relationships for use with the RELTYPE parameter defined in [Section 3.2.15 of \[RFC5545\]](#): FINISHTOSTART, FINISHTOFINISH, STARTTOFINISH or STARTTOSTART.

The [\[RFC5545\]](#) RELATED-TO property with one or more of these temporal relationships will be present in the predecessor entity and will refer to the successor entity.

The GAP parameter (see [Section 6.2](#)) specifies the lead (a negative value) or lag (a positive value) time between the predecessor and the successor.

In the description of each temporal relationship below we refer to Task-A, which contains and controls the relationship, and Task-B the target of the relationship. This is indicated by the direction of the arrow in the diagrams below.

Also each relationship may be modified by the addition of a GAP parameter to the relationship which applies to the targeted component.

RELTYPE=FINISHTOSTART: Task-B cannot start until Task-A finishes.  
For example, when painting is complete, carpet-laying can begin.

=====




Figure 1: Finish to start relationship

RELTYPE=FINISHTOFINISH: Task-B can only be completed after Task-A is finished. The related tasks may run in parallel before completion.

For example, in the development of two related pieces of software, e.g. the api and the implementation, the design of the implementation (B) cannot be completed until the design of the api (A) has been completed.




Figure 2: Finish to finish relationship

RELTYPE=STARTTOFINISH: The start of Task-A (which occurs after Task-B) controls the finish of Task-B. For example, ticket sales (Task-B) end after the game starts (Task-A).




Figure 3: Start to finish relationship



RELTYPE=STARTTOSTART: The start of Task-A triggers the start of Task-B, that is Task-B can start anytime after Task-A starts.




Figure 4: Start to start relationship

## 5. Additional New RELTYPE Parameter Values

This section defines the additional relationships below:

RELTYPE=FIRST: Indicates that the referenced calendar component is the first in a series the referencing calendar component is part of.

RELTYPE=NEXT: Indicates that the referenced calendar component is the next in a series the referencing calendar component is part of.

RELTYPE=DEPENDS-ON: Indicates that the current calendar component depends on the referenced calendar component in some manner. For example a task may be blocked waiting on the other, referenced, task.

RELTYPE=REFID: Establishes a reference from the current component to components with a REFID property which matches the value given in the associated RELATED-TO property.

RELTYPE=CONCEPT: Establishes a reference from the current component to components with a CONCEPT property which matches the value given in the associated RELATED-TO property.

Note that the relationship types of PARENT, CHILD and SIBLING establish a hierarchical relationship. The new types of FIRST and NEXT are an ordering relationship.

## 6. New Property Parameters

### [6.1.](#) Link Relation

Parameter name: LINKREL

Purpose: To specify the relationship of data referenced by a LINK property.

Format Definition: This parameter is defined by the following notation:

```
linkrelparam = "LINKREL" "="  
              ("SOURCE"      ; Link to source of this component  
              / DQUOTE uri DQUOTE  
              / iana-token)  ; Other IANA registered type
```

Description: This parameter MUST be specified on all LINK properties, and defines the type of reference. This allows programs consuming this data to automatically scan for references they support. There is no default relation type.

In addition to the value defined here any link relation in the link registry established by [\[RFC8288\]](#), or new link relations, may be used.

It is expected that link relation types seeing significant usage in calendaring will have the calendaring usage described in an RFC.

LINKREL=SOURCE: identifies the source of the event information.

Registration: These relation types are registered in [\[RFC8288\]](#)

### [6.2.](#) Gap

Parameter name: GAP

Purpose: To specify the length of the gap, positive or negative, between two components with a temporal relationship.

Format Definition: This parameter is defined by the following notation where dur-value is defined in [section 3.3.6 of \[RFC5545\]](#).  
:

```
gapparam      = "GAP" "=" dur-value
```

Description: This parameter MAY be specified on the RELATED-TO

property, and defines the duration of time between the predecessor and successor in an interval. When positive it defines the lag time between a task and its logical successor. When negative it defines the lead time.

An example of lag time might be if task A is "paint the room" and task B is "lay the carpets" then task A may be related to task B with RELTYPE=FINISHTOSTART with a gap of 1 day - long enough for the paint to dry.




Figure 5: Finish to start relationship with lag

For an example of lead time, in constructing a two storey building the electrical work must be done before painting. However the painter can move in to the first floor as the electricians move upstairs.




Figure 6: Finish to start relationship with lead

## [7.](#) New Value Data Types

This specification defines the following new value types to be used with the VALUE property parameter:

UID VALUE=UID indicates that the associated value is the UID for a component.

XML-REFERENCE VALUE=XML-REFERENCE indicates that the associated

value references an associated XML artifact and is a URI with an XPointer anchor value. The XPointer is defined in [\[W3C.WD-xptr-xpointer-20021219\]](#) and its use as an anchor is defined in [\[W3C.REC-xptr-framework-20030325\]](#).

## [8.](#) New Properties

### [8.1.](#) Concept

Property name: CONCEPT

Purpose: This property defines the formal categories for a calendar component.

Value type: URI

Property Parameters: IANA, and non-standard parameters can be specified on this property.

Conformance: This property can be specified zero or more times in any iCalendar component.

Description: This property is used to specify formal categories or classifications of the calendar component. The values are useful in searching for a calendar component of a particular type and category.

This categorization is distinct from the more informal "tagging" of components provided by the existing CATEGORIES property. It is expected that the value of the CONCEPT property will reference an external resource which provides information about the categorization.

In addition, a structured URI value allows for hierarchical categorization of events.

Possible category resources are the various proprietary systems, for example Library of Congress, or an open source of categorisation data.

Format Definition: This property is defined by the following notation:

```
concept          = "CONCEPT" conceptparam ":"  
                  uri CRLF
```

```
conceptparam = *(";" other-param)
```

Douglass

Expires 23 September 2022

[Page 11]

---

Internet-Draft

iCalendar Relationships

March 2022

Example: The following is an example of this property. It points to a server acting as the source for the calendar object.

```
CONCEPT:https://example.com/event-types/arts/music
```

## [8.2.](#) Link

Property name: LINK

Purpose: This property provides a reference to external information related to a component.

Value type: URI, UID or XML-REFERENCE

Property Parameters: The VALUE parameter is required. Non-standard, link relation type, format type, label and language parameters can also be specified on this property. The LABEL parameter is defined in [[RFC7986](#)].

Conformance: This property can be specified zero or more times in any iCalendar component.

Description: When used in a component the value of this property points to additional information related to the component. For example, it may reference the originating web server.

Format Definition: This property is defined by the following notation:

```
link          = "LINK" linkparam ":"
                ( uri / ; for VALUE=XML-REFERENCE
                  uri / ; for VALUE=URI
                  text ) ; for VALUE=UID
                CRLF

linkparam     = ; the elements herein may appear in any order,
                ; and the order is not significant.

                (";" "VALUE" "=" ("XML-REFERENCE" /
                                   "URI" /
                                   "UID"))
                1*(";" linkrelparam)
                1*(";" fmttypeparam)
                1*(";" labelparam)
                1*(";" languageparam)
                *(";" other-param)
```

This property is a serialisation of the model in [\[RFC8288\]](#), where the link target is carried in the property value, the link context is the containing calendar entity, and the link relation type and any target attributes are carried in iCalendar property parameters.

The LINK property parameters map to [\[RFC8288\]](#) attributes as follows:

**LABEL:** Maps to the "title" attribute defined in [section 3.4.1 of \[RFC8288\]](#).

**LANGUAGE:** Maps to the "hreflang" attribute defined in [section 3.4.1 of \[RFC8288\]](#).

**LINKREL:** Maps to the link relation type defined in [section 2.1 of \[RFC8288\]](#).

FMTTYPE: Maps to the "type" attribute defined in [section 3.4.1 of \[RFC8288\]](#).

There is no mapping for [\[RFC8288\]](#) "title\*", "anchor", "rev" or "media".

Example: The following is an example of this property which provides a reference to the source for the calendar object.

```
LINK;LINKREL=SOURCE;LABEL=Venue;VALUE=URI:
https://example.com/events
```

Example: The following is an example of this property which provides a reference to an entity from which this one was derived. The link relation is a vendor defined value.

```
LINK;LINKREL="https://example.com/linkrel/derivedFrom";
VALUE=URI:
https://example.com/tasks/01234567-abcd1234.ics
```

Example: The following is an example of this property which provides a reference to a fragment of an XML document. The link relation is a vendor defined value.

```
LINK;LINKREL="https://example.com/linkrel/costStructure";
VALUE=XML-REFERENCE:
https://example.com/xmlDocs/bidFramework.xml
#xpointer(descendant::CostStruc/range-to(
following::CostStrucEND[1]))
```

### [8.3.](#) Refid

Property name: REFID

Purpose: This property value acts as a key for associated iCalendar entities.

Value type: TEXT

Property Parameters: Non-standard parameters can be specified on this property.

Conformance: This property can be specified zero or more times in any iCalendar component.

Description: The value of this property is free-form text that creates an identifier for associated components. All components that use the same REFID value are associated through that value and can be located or retrieved as a group. For example, all of the events in a travel itinerary would have the same REFID value, so as to be grouped together.

Format Definition: This property is defined by the following notation:

```
refid      = "REFID" refidparam ":" text CRLF
```

```
refidparam = *(";" other-param)
```

The current link registry

Example: The following is an example of this property.

```
REFID:itinerary-2014-11-17
```

## 9. Updates to [RFC 5545](#)

This specification updates the RELATED-TO property defined in [Section 3.8.4.5 of \[RFC5545\]](#). The contents of [Section 9.1](#) replace that section.

The RELTYPE parameter is extended to take new values defining temporal relationships, a GAP parameter is defined to provide lead and lag values, and RELATED-TO is extended to allow URI values. These changes allow the RELATED-TO property to define a richer set of relationships useful for project management.

### 9.1. RELATED-TO

Property Name: RELATED-TO



**Purpose:** This property is used to represent a relationship or reference between one calendar component and another. The definition here extends the definition in [Section 3.8.4.5 of \[RFC5545\]](#) by allowing URI or UID values and a GAP parameter.

**Value Type:** URI, UID or TEXT

**Property Parameters:** Relationship type, IANA and non-standard property parameters can be specified on this property.

**Conformance:** This property MAY be specified in any iCalendar component.

**Description:** By default or when VALUE=UID is specified, the property value consists of the persistent, globally unique identifier of another calendar component. This value would be represented in a calendar component by the "UID" property.

By default, the property value points to another calendar component that has a PARENT relationship to the referencing object. The "RELTYPE" property parameter is used to either explicitly state the default PARENT relationship type to the referenced calendar component or to override the default PARENT relationship type and specify either a CHILD or SIBLING relationship or a temporal relationship.

The PARENT relationship indicates that the calendar component is a subordinate of the referenced calendar component. The CHILD relationship indicates that the calendar component is a superior of the referenced calendar component. The SIBLING relationship indicates that the calendar component is a peer of the referenced calendar component.

To preserve backwards compatibility the value type MUST be UID when the PARENT, SIBLING or CHILD relationships are specified.

The FINISHTOSTART, FINISHTOFINISH, STARTTOFINISH or STARTTOSTART relationships define temporal relationships as specified in the reltype parameter definition.

The FIRST and NEXT define ordering relationships between calendar components.

The DEPENDS-ON relationship indicates that the current calendar

component depends on the referenced calendar component in some manner. For example a task may be blocked waiting on the other, referenced, task.

The REFID and CONCEPT relationships establish a reference from the current component to the referenced component.

Changes to a calendar component referenced by this property can have an implicit impact on the related calendar component. For example, if a group event changes its start or end date or time, then the related, dependent events will need to have their start and end dates changed in a corresponding way. Similarly, if a PARENT calendar component is cancelled or deleted, then there is an implied impact to the related CHILD calendar components. This property is intended only to provide information on the relationship of calendar components.

Deletion of the target component, for example the target of a FIRST, NEXT or temporal relationship can result in broken links.

It is up to the target calendar system to maintain any property implications of these relationships.

**Format Definition:** This property is defined by the following notation:

```
related      = "RELATED-TO" relparam ":"
               ( text / ; for VALUE=UID
                 uri / ; for VALUE=URI
                 text ) ; for VALUE=TEXT or default
               CRLF

relparam     = ; the elements herein may appear in any order,
               ; and the order is not significant.
               [";" "VALUE" "=" ("UID" /
                                   "URI" /
                                   "TEXT")]
               [";" reltypeparam]
               [";" gapparam]
               *(";" other-param)
```

**Example:** The following are examples of this property.

Internet-Draft

iCalendar Relationships

March 2022

RELATED-TO:jsmith.part7.19960817T083000.xyzMail@example.com

RELATED-TO:19960401-080045-4000F192713-0052@example.com

RELATED-TO;VALUE=URI;RELTYPE=STARTTOFINISH:  
https://example.com/caldav/user/jb/cal/  
19960401-080045-4000F192713.ics

## [10.](#) Security Considerations

All of the security considerations of [section 7](#) of [\[RFC5545\]](#) apply to this specification.

Applications using the LINK property need to be aware of the risks entailed in using the URIs provided as values. See [section 7 of \[RFC3986\]](#) for a discussion of the security considerations relating to URIs.

In particular note [section 7.1](#) "Reliability and Consistency" of [\[RFC3986\]](#) which points out the lack of a stability guarantee for referenced resources.

When the value is an XML-REFERENCE type the targeted data is an XML document or portion thereof. Consumers need to be aware of the security issues related to XML processing - in particular those related to XML entities. See [\[RFC4918\]](#) - [Section 20.6](#). Additionally note that the reference may be invalid or become so over time.

The CONCEPT and redefined RELATED-TO property have the same issues in that values may be URIs.

Extremely large values for the GAP parameter may lead to unexpected behavior.

## [11.](#) IANA Considerations

### [11.1.](#) iCalendar Property Registrations

The following iCalendar property names have been added to the iCalendar Properties Registry defined in [Section 8.3.2 of \[RFC5545\]](#).

IANA has also added a reference to this document where the properties originally defined in [[RFC5545](#)] have been updated by this document.

Property	Status	Reference
CONCEPT	Current	<a href="#">Section 8.1</a>
LINK	Current	<a href="#">Section 8.2</a>
REFID	Current	<a href="#">Section 8.3</a>
RELATED-TO	Current	<a href="#">[RFC5545], Section 9.1</a>

Table 1

### [11.2.](#) iCalendar Property Parameter Registrations

The following iCalendar property parameter names have been added to the iCalendar Parameters Registry defined in [Section 8.3.3 of \[RFC5545\]](#).

Parameter	Status	Reference
GAP	Current	<a href="#">Section 6.2</a>
LINKREL	Current	<a href="#">Section 6.1</a>

Table 2

### [11.3.](#) iCalendar Value Data Type Registrations

The following iCalendar property parameter names have been added to

the iCalendar Value Data Types Registry defined in [Section 8.3.4 of \[RFC5545\]](#).

Value Data Type	Status	Reference
XML-REFERENCE	Current	<a href="#">Section 7</a>
UID	Current	<a href="#">Section 7</a>

Table 3

Douglass

Expires 23 September 2022

[Page 18]

Internet-Draft

iCalendar Relationships

March 2022

#### [11.4.](#) iCalendar RELTYPE Value Registrations

The following iCalendar "RELTYPE" values have been added to the iCalendar Relationship Types Registry defined in [Section 8.3.8 of \[RFC5545\]](#).

Relationship Type	Status	Reference
CONCEPT	Current	<a href="#">Section 5</a>
DEPENDS-ON	Current	<a href="#">Section 5</a>
FINISHTOFINISH	Current	<a href="#">Section 4</a>
FINISHTOSTART	Current	<a href="#">Section 4</a>
FIRST	Current	<a href="#">Section 5</a>
NEXT	Current	<a href="#">Section 5</a>
REFID	Current	<a href="#">Section 5</a>
STARTTOFINISH	Current	<a href="#">Section 4</a>
STARTTOSTART	Current	<a href="#">Section 4</a>

+-----+-----+-----+

Table 4

### [11.5.](#) New Reference Type Registration

The following link relation values have been added to the Reference Types Registry defined in [Section 6.2.2 of \[RFC8288\]](#).

=====	=====	=====
Name	Status	Reference
=====	=====	=====
SOURCE	Current	<a href="#">Section 6.1</a>
-----	-----	-----

Table 5

Douglass Expires 23 September 2022 [Page 19]

---

Internet-Draft iCalendar Relationships March 2022

## [12.](#) Acknowledgements

The author would like to thank the members of CalConnect, the Calendaring and Scheduling Consortium technical committees and the following individuals for contributing their ideas, support and comments:

Adrian Apthorp, Cyrus Daboo, Marten Gajda, Ken Murchison

The author would also like to thank CalConnect, the Calendaring and Scheduling Consortium for advice with this specification.

## [13.](#) References

### [13.1.](#) Informative References

[RFC4791] Daboo, C., Desruisseaux, B., and L. Dusseault, "Calendaring Extensions to WebDAV (CalDAV)", [RFC 4791](#), DOI 10.17487/RFC4791, March 2007,

<<https://www.rfc-editor.org/info/rfc4791>>.

- [RFC8607] Daboo, C., Quillaud, A., and K. Murchison, Ed., "Calendaring Extensions to WebDAV (CalDAV): Managed Attachments", [RFC 8607](#), DOI 10.17487/RFC8607, June 2019, <<https://www.rfc-editor.org/info/rfc8607>>.

### 13.2. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC4918] Dusseault, L., Ed., "HTTP Extensions for Web Distributed Authoring and Versioning (WebDAV)", [RFC 4918](#), DOI 10.17487/RFC4918, June 2007, <<https://www.rfc-editor.org/info/rfc4918>>.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), DOI 10.17487/RFC5234, January 2008, <<https://www.rfc-editor.org/info/rfc5234>>.

Douglass

Expires 23 September 2022

[Page 20]

---

Internet-Draft

iCalendar Relationships

March 2022

- [RFC5545] Desruisseaux, B., Ed., "Internet Calendaring and Scheduling Core Object Specification (iCalendar)", [RFC 5545](#), DOI 10.17487/RFC5545, September 2009, <<https://www.rfc-editor.org/info/rfc5545>>.
- [RFC7986] Daboo, C., "New Properties for iCalendar", [RFC 7986](#), DOI 10.17487/RFC7986, October 2016, <<https://www.rfc-editor.org/info/rfc7986>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

[RFC8288] Nottingham, M., "Web Linking", [RFC 8288](#),  
DOI 10.17487/RFC8288, October 2017,  
<<https://www.rfc-editor.org/info/rfc8288>>.

[W3C.REC-skos-reference-20090818]  
Miles, A. and S. Bechhofer, "SKOS Simple Knowledge  
Organization System Reference", World Wide Web Consortium  
Recommendation REC-skos-reference-20090818, 18 August  
2009,  
<<https://www.w3.org/TR/2009/REC-skos-reference-20090818>>.

[W3C.REC-xptr-framework-20030325]  
Grosso, P., Maler, E., Marsh, J., and N. Walsh, "XPointer  
Framework", World Wide Web Consortium Recommendation REC-  
xptr-framework-20030325, 25 March 2003,  
<<https://www.w3.org/TR/2003/REC-xptr-framework-20030325>>.

[W3C.WD-xptr-xpointer-20021219]  
DeRose, S., Daniel, R., and E. Maler, "XPointer xpointer()  
Scheme", World Wide Web Consortium WD WD-xptr-xpointer-  
20021219, 19 December 2002,  
<<http://www.w3.org/TR/2002/WD-xptr-xpointer-20021219>>.

#### Author's Address

Michael Douglass  
Bedework  
226 3rd Street  
Troy, NY 12180  
United States of America  
Email: [mdouglass@bedework.com](mailto:mdouglass@bedework.com)  
URI: <https://bedework.com>