

Calendaring extensions
Internet-Draft
Intended status: Standards Track
Expires: August 23, 2020

N. Jenkins
R. Stepanek
Fastmail
February 20, 2020

**JSCalendar: A JSON representation of calendar data
draft-ietf-calexext-jscalendar-24**

Abstract

This specification defines a data model and JSON representation of calendar data that can be used for storage and data exchange in a calendaring and scheduling environment. It aims to be an alternative and, over time, successor to the widely deployed iCalendar data format, and to be unambiguous, extendable, and simple to process. In contrast to the jCal format, which is also JSON-based, JSCalendar is not a direct mapping from iCalendar, but defines the data model independently and expands semantics where appropriate.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 23, 2020.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	4
1.1.	Motivation and Relation to iCalendar and jCal	5
1.2.	Notational Conventions	6
1.3.	Type Signatures	6
1.4.	Data Types	7
1.4.1.	Int	7
1.4.2.	UnsignedInt	7
1.4.3.	UTCDateTime	7
1.4.4.	LocalDateTime	7
1.4.5.	Duration	7
1.4.6.	SignedDuration	8
1.4.7.	Id	8
1.4.8.	PatchObject	9
1.4.9.	Time Zones	9
1.4.10.	Relation	9
2.	JSCalendar Objects	10
2.1.	JSEvent	10
2.2.	JSTask	11
2.3.	JSGroup	11
3.	Structure of JSCalendar Objects	11
3.1.	Normalization and Equivalence	11
3.2.	Vendor-specific Property Extensions and Values	12
4.	Common JSCalendar Properties	12
4.1.	Metadata Properties	12
4.1.1.	@type	12
4.1.2.	uid	13
4.1.3.	relatedTo	13
4.1.4.	prodId	13
4.1.5.	created	14
4.1.6.	updated	14
4.1.7.	sequence	14
4.1.8.	method	14
4.2.	What and Where Properties	14
4.2.1.	title	14
4.2.2.	description	15
4.2.3.	descriptionContentType	15
4.2.4.	showWithoutTime	15
4.2.5.	locations	15
4.2.6.	virtualLocations	17
4.2.7.	links	17
4.2.8.	locale	19
4.2.9.	keywords	19

4.2.10.	categories	19
4.2.11.	color	20
4.3.	Recurrence Properties	20
4.3.1.	recurrenceId	20
4.3.2.	recurrenceRules	20
4.3.3.	recurrenceOverrides	28
4.3.4.	excluded	30
4.4.	Sharing and Scheduling Properties	30
4.4.1.	priority	30
4.4.2.	freeBusyStatus	30
4.4.3.	privacy	30
4.4.4.	replyTo	32
4.4.5.	participants	32
4.5.	Alerts Properties	37
4.5.1.	useDefaultAlerts	37
4.5.2.	alerts	37
4.6.	Multilingual Properties	39
4.6.1.	localizations	39
4.7.	Time Zone Properties	40
4.7.1.	timeZone	40
4.7.2.	timeZones	40
5.	Type-specific JSCalendar Properties	43
5.1.	JSEvent Properties	43
5.1.1.	start	43
5.1.2.	duration	43
5.1.3.	status	43
5.2.	JSTask Properties	44
5.2.1.	due	44
5.2.2.	start	44
5.2.3.	estimatedDuration	44
5.2.4.	progress	44
5.2.5.	progressUpdated	45
5.3.	JSGroup Properties	45
5.3.1.	entries	46
5.3.2.	source	46
6.	Examples	46
6.1.	Simple event	46
6.2.	Simple task	47
6.3.	Simple group	47
6.4.	All-day event	48
6.5.	Task with a due date	48
6.6.	Event with end time-zone	49
6.7.	Floating-time event (with recurrence)	49
6.8.	Event with multiple locations and localization	50
6.9.	Recurring event with overrides	51
6.10.	Recurring event with participants	52
7.	Security Considerations	54
7.1.	Expanding Recurrences	54

7.2.	JSON Parsing	54
7.3.	URI Values	55
8.	IANA Considerations	55
8.1.	Media Type Registration	55
8.2.	Creation of "JSCalendar Properties" Registry	56
8.2.1.	Preliminary Community Review	57
8.2.2.	Submit Request to IANA	57
8.2.3.	Designated Expert Review	57
8.2.4.	Change Procedures	58
8.2.5.	JMAP Properties Registry Template	58
8.2.6.	Initial Contents for the JSCalendar Properties Registry	59
8.3.	Creation of "JSCalendar Types" Registry	66
8.3.1.	JMAP Types Registry Template	66
8.3.2.	Initial Contents for the JSCalendar Types Registry	66
8.4.	Creation of "JSCalendar Enum Values" Registry	68
8.4.1.	JMAP Enum Subregistry Creation Template	68
8.4.2.	JMAP Enum Subregistry Template	68
8.4.3.	Initial Contents for the JSCalendar Enum Registry	69
9.	Acknowledgments	73
10.	References	73
10.1.	Normative References	73
10.2.	Informative References	75
	Authors' Addresses	76

[1.](#) Introduction

This document defines a data model for calendar event and task objects, or groups of such objects, in electronic calendar applications and systems. It aims to be unambiguous, extendable and simple to process.

The key design considerations for this data model are as follows:

- o The attributes of the calendar entry represented must be described as simple key-value pairs. Simple events are simple to represent; complex events can be modelled accurately.
- o Wherever possible, there should be only one way to express the desired semantics, reducing complexity.
- o The data model should avoid ambiguities, which often lead to interoperability issues between implementations.
- o The data model should be compatible with the iCalendar data format [[RFC5545](#)] [[RFC7986](#)] and extensions, but the specification should add new attributes where the iCalendar format currently lacks expressivity, and drop seldom-used, obsolete, or redundant

properties. This means translation with no loss of semantics should be easy with most common iCalendar files.

- o Extensions, such as new properties and components, generally do not require updates to this document.

The representation of this data model is defined in the I-JSON format [[RFC7493](#)], which is a strict subset of the JavaScript Object Notation (JSON) Data Interchange Format [[RFC8259](#)]. Using JSON is mostly a pragmatic choice: its widespread use makes JSCalendar easier to adopt, and the ready availability of production-ready JSON implementations eliminates a whole category of parser-related interoperability issues, which iCalendar has often suffered from.

1.1. Motivation and Relation to iCalendar and jCal

The iCalendar data format [[RFC5545](#)], a widely deployed interchange format for calendaring and scheduling data, has served calendaring vendors for a long while, but contains some ambiguities and pitfalls that can not be overcome without backward-incompatible changes.

Sources of implementation errors include the following:

- o iCalendar defines various formats for local times, UTC time, and dates.
- o iCalendar requires custom time zone definitions within a single calendar component.
- o iCalendar's definition of recurrence rules is ambiguous and has resulted in differing understandings even between experienced calendar developers.
- o The iCalendar format itself causes interoperability issues due to misuse of CRLF-terminated strings, line continuations, and subtle differences among iCalendar parsers.

In recent years, many new products and services have appeared that wish to use a JSON representation of calendar data within their APIs. The JSON format for iCalendar data, jCal [[RFC7265](#)], is a direct mapping between iCalendar and JSON. In its effort to represent full iCalendar semantics, it inherits all the same pitfalls and uses a complicated JSON structure unlike most common JSON data representations.

As a consequence, since the standardization of jCal, the majority of implementations and service providers either kept using iCalendar, or came up with their own proprietary JSON representations, which are

incompatible with each other and often suffer from common pitfalls, such as storing event start times in UTC (which become incorrect if the timezone's rules change in the future). JSCalendar meets the demand for JSON-formatted calendar data that is free of such known problems and provides a standard representation as an alternative to the proprietary formats.

1.2. Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

The underlying format used for this specification is JSON. Consequently, the terms "object" and "array" as well as the four primitive types (strings, numbers, booleans, and null) are to be interpreted as described in [Section 1 of \[RFC8259\]](#).

Some examples in this document contain "partial" JSON documents used for illustrative purposes. In these examples, three periods "..." are used to indicate a portion of the document that has been removed for compactness.

1.3. Type Signatures

Type signatures are given for all JSON values in this document. The following conventions are used:

- o "" - The type is undefined (the value could be any type, although permitted values may be constrained by the context of this value).
- o "String" - The JSON string type.
- o "Number" - The JSON number type.
- o "Boolean" - The JSON boolean type.
- o "A[B]" - A JSON object where the keys are all of type "A", and the values are all of type "B".
- o "A[]" - An array of values of type "A".
- o "A|B" - The value is either of type "A" or of type "B".

Other types may also be given, with their representations defined elsewhere in this document.

1.4. Data Types

In addition to the standard JSON data types, the following data types are used in this specification:

1.4.1. Int

Where "Int" is given as a data type, it means an integer in the range $-2^{53}+1 \leq \text{value} \leq 2^{53}-1$, the safe range for integers stored in a floating-point double, represented as a JSON "Number".

1.4.2. UnsignedInt

Where "UnsignedInt" is given as a data type, it means an integer in the range $0 \leq \text{value} \leq 2^{53}-1$, represented as a JSON "Number".

1.4.3. UTCDateTime

This is a string in [[RFC3339](#)] "date-time" format, with the further restrictions that any letters MUST be in uppercase, the time component MUST be included and the time offset MUST be the character "Z". Fractional second values MUST NOT be included unless non-zero and MUST NOT have trailing zeros, to ensure there is only a single representation for each date-time.

For example "2010-10-10T10:10:10.003Z" is OK, but "2010-10-10T10:10:10.000Z" is invalid and MUST be encoded as "2010-10-10T10:10:10Z".

1.4.4. LocalDateTime

This is a date-time string with no time zone/offset information. It is otherwise in the same format as UTCDateTime, including fractional seconds. For example "2006-01-02T15:04:05" and "2006-01-02T15:04:05.003" are both valid. The time zone to associate the LocalDateTime with comes from an associated property, or if no time zone is associated it defines *floating time*. Floating date-times are not tied to any specific time zone. Instead, they occur in each time zone at the given wall-clock time (as opposed to the same instant point in time).

1.4.5. Duration

Where Duration is given as a type, it means a length of time represented by a subset of ISO8601 duration format, as specified by the following ABNF:


```
dur-secfrac = "." 1*DIGIT
dur-second  = 1*DIGIT [dur-secfrac] "S"
dur-minute  = 1*DIGIT "M" [dur-second]
dur-hour    = 1*DIGIT "H" [dur-minute]
dur-time    = "T" (dur-hour / dur-minute / dur-second)
dur-day     = 1*DIGIT "D"
dur-week    = 1*DIGIT "W"

duration    = "P" (dur-day [dur-time] / dur-time / dur-week)
```

In addition, the duration MUST NOT include fractional second values unless the fraction is non-zero.

1.4.6. SignedDuration

A SignedDuration represents a length of time that may be positive or negative and is typically used to express the offset of a point in time relative to an associated time. It is represented as a Duration, optionally preceded by a sign character. It is specified by the following ABNF:

```
signed-duration = ["+" / "-"] duration
```

A negative sign indicates a point in time at or before the associated time, a positive or no sign a time at or after the associated time.

1.4.7. Id

Where "Id" is given as a data type, it means a "String" of at least 1 and a maximum of 255 octets in size, and it MUST only contain characters from the "URL and Filename Safe" base64url alphabet, as defined in [Section 5 of \[RFC4648\]](#), excluding the pad character ("="). This means the allowed characters are the ASCII alphanumeric characters ("A-Za-z0-9"), hyphen ("-"), and underscore ("_").

Unless otherwise specified, Ids are arbitrary and only have meaning within the object where they are being used. Ids need not be unique among different objects. For example, two JSEvent objects might use the same ids in their respective "links" properties. Or within the same JSEvent object the same Id could appear in the "participants" and "alerts" properties. These situations do not imply any semantic connections among the objects.

Nevertheless, a UUID is typically a good choice.

1.4.8. PatchObject

A PatchObject is of type "String[*]", and represents an unordered set of patches on a JSON object. Each key is a path represented in a subset of JSON pointer format [[RFC6901](#)]. The paths have an implicit leading "/", so each key is prefixed with "/" before applying the JSON pointer evaluation algorithm.

A patch within a PatchObject is only valid if all of the following conditions apply:

1. The pointer MUST NOT insert/delete from an array; the array MUST be replaced in its entirety instead.
2. When evaluating a path, all parts prior to the last (i.e., the value after the final slash) MUST exist.
3. There MUST NOT be two patches in the PatchObject where the pointer of one is a prefix of the pointer of the other, e.g., "alerts/foo/offset" and "alerts".

The value associated with each pointer is either:

- o null: Remove the property at the given path from the patched object. If the property is not present in the object, this a no-op.
- o Anything else: Set the value for the property to this value (this may be a replacement or addition to the object being patched).

Implementations MUST reject in its entirety a PatchObject if any of its patches is invalid. Implementations MUST NOT apply partial patches.

1.4.9. Time Zones

By default, time zones in JSCalendar are identified by their names in the IANA Time Zone Database [[TZDB](#)], and the zone rules of the respective zone records apply.

Implementations MAY embed the definitions of custom time zones in the "timeZones" property (see [Section 4.7.2](#)).

1.4.10. Relation

A Relation object defines the relation to other objects, using a possibly empty set of relation types. The object that defines this

relation is the linking object, while the other object is the linked object. The Relation object has the following properties:

- o @type: "String" (mandatory)

Specifies the type of this object. This MUST be "Relation".

- o relation: "String[Boolean]" (optional, default: empty Object)

Describes how the linked object is related to the linking object. The relation is defined as a set of relation types. If empty, the relationship between the two objects is unspecified.

Keys in the set MUST be one of the following values, or specified in the property definition where the Relation object is used, or a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value:

- * "first": The linked object is the first in a series the linking object is part of.
- * "next": The linked object is the next in a series the linking object is part of.
- * "child": The linked object is a subpart of the linking object.
- * "parent": The linking object is a subpart of the linked object.

The value for each key in the set MUST be true.

2. JSCalendar Objects

This section describes the calendar object types specified by JSCalendar.

2.1. JSEvent

Media type: "application/jscalendar+json;type=jsevent"

A JSEvent represents a scheduled amount of time on a calendar, typically a meeting, appointment, reminder or anniversary. It is required to start at a certain point in time and typically has a non-zero duration. Multiple participants may partake in the event at multiple locations.

The @type ([Section 4.1.1](#)) property value MUST be "jsevent".

2.2. JSTask

Media type: "application/jscalendar+json;type=jstask"

A JSTask represents an action-item, assignment, to-do or work item. It may start and be due at certain points in time, may take some estimated time to complete, and may recur, none of which is required.

The @type ([Section 4.1.1](#)) property value MUST be "jstask".

2.3. JSGroup

Media type: "application/jscalendar+json;type=jsgroup"

A JSGroup is a collection of JSEvent ([Section 2.1](#)) and/or JSTask ([Section 2.2](#)) objects. Typically, objects are grouped by topic (e.g., by keywords) or calendar membership.

The @type ([Section 4.1.1](#)) property value MUST be "jsgroup".

3. Structure of JSCalendar Objects

A JSCalendar object is a JSON object, which MUST be valid I-JSON (a stricter subset of JSON), as specified in [[RFC8259](#)]. Property names and values are case-sensitive.

The object has a collection of properties, as specified in the following sections. Properties are specified as being either mandatory or optional. Optional properties may have a default value, if explicitly specified in the property definition.

3.1. Normalization and Equivalence

JSCalendar aims to provide unambiguous definitions for value types and properties, but does not define a general normalization or equivalence method for JSCalendar objects and types. This is because the notion of equivalence might range from byte-level equivalence to semantic equivalence, depending on the respective use case (for example, the CalDAV protocol [[RFC4791](#)] requires octet equivalence of the encoded calendar object to determine ETag equivalence).

Normalization of JSCalendar objects is hindered because of the following reasons:

- o Custom JSCalendar properties may contain arbitrary JSON values, including arrays. However, equivalence of arrays might or might not depend on the order of elements, depending on the respective property definition.

- o Several JSCalendar property values are defined as URIs and media types, but normalization of these types is inherently protocol- and scheme-specific, depending on the use-case of the equivalence definition (see [Section 6 of \[RFC3986\]](#)).

Considering this, the definition of equivalence and normalization is left to client and server implementations and to be negotiated by a calendar exchange protocol or defined elsewhere.

[3.2.](#) Vendor-specific Property Extensions and Values

Vendors MAY add additional properties to the calendar object to support their custom features. The names of these properties MUST be prefixed with a domain name controlled by the vendor to avoid conflict, e.g., "example.com/customprop".

Some JSCalendar properties allow vendor-specific value extensions. Such vendor-specific values MUST be prefixed with a domain name controlled by the vendor, e.g., "example.com/customrel".

Vendors are strongly encouraged to register any new property values or extensions that are useful to other systems as well, rather than use a vendor-specific prefix.

[4.](#) Common JSCalendar Properties

This section describes the properties that are common to the various JSCalendar object types. Specific JSCalendar object types may only support a subset of these properties. The object type definitions in [Section 5](#) describe the set of supported properties per type.

[4.1.](#) Metadata Properties

[4.1.1.](#) @type

Type: "String" (mandatory).

Specifies the type which this object represents. This MUST be one of the following values:

- o "jsevent": a JSCalendar event ([Section 2.1](#)).
- o "jstask": a JSCalendar task ([Section 2.2](#)).
- o "jsgroup": a JSCalendar group ([Section 2.3](#)).

4.1.2. uid

Type: "String" (mandatory).

A globally unique identifier, used to associate the object as the same across different systems, calendars and views. The value of this property MUST be unique across all JSCalendar objects, even if they are of different type. [\[RFC4122\]](#) describes a range of established algorithms to generate universally unique identifiers (UUID). UUID version 4, described in [Section 4.4 of \[RFC4122\]](#), is RECOMMENDED.

For compatibility with [\[RFC5545\]](#) UUIDs, implementations MUST be able to receive and persist values of at least 255 octets for this property, but they MUST NOT truncate values in the middle of a UTF-8 multi-octet sequence.

4.1.3. relatedTo

Type: "String[Relation]" (optional).

Relates the object to other JSCalendar objects. This is represented as a map of the UUIDs of the related objects to information about the relation.

If an object is split to make a "this and future" change to a recurrence, the original object MUST be truncated to end at the previous occurrence before this split, and a new object created to represent all the occurrences after the split. A "next" relation MUST be set on the original object's relatedTo property for the UUID of the new object. A "first" relation for the UUID of the first object in the series MUST be set on the new object. Clients can then follow these UUIDs to get the complete set of objects if the user wishes to modify them all at once.

4.1.4. prodId

Type: "String" (optional).

The identifier for the product that last updated the JSCalendar object. This should be set whenever the data in the object is modified (i.e., whenever the "updated" property is set).

The vendor of the implementation SHOULD ensure that this is a globally unique identifier, using some technique such as an FPI value, as defined in [\[ISO.9070.1991\]](#). It MUST only use characters of an iCalendar TEXT data value (see [Section 3.3.11 of \[RFC5545\]](#)).

This property SHOULD NOT be used to alter the interpretation of a JSCalendar object beyond the semantics specified in this document. For example, it is not to be used to further the understanding of non-standard properties, a practice that is known to cause long-term interoperability problems.

[4.1.5.](#) created

Type: "UTCDateTime" (optional).

The date and time this object was initially created.

[4.1.6.](#) updated

Type: "UTCDateTime" (mandatory).

The date and time the data in this object was last modified (or its creation date/time if not modified since).

[4.1.7.](#) sequence

Type: "UnsignedInt" (optional, default: 0).

Initially zero, this MUST be incremented by one every time a change is made to the object, except if the change only modifies the "participants" property (see [Section 4.4.5](#)).

This is used as part of iTIP [[RFC5546](#)] to know which version of the object a scheduling message relates to.

[4.1.8.](#) method

Type: "String" (optional).

The iTIP [[RFC5546](#)] method, in lowercase. This MUST only be present if the JSCalendar object represents an iTIP scheduling message.

[4.2.](#) What and Where Properties

[4.2.1.](#) title

Type: "String" (optional, default: empty String).

A short summary of the object.

4.2.2. description

Type: "String" (optional, default: empty String).

A longer-form text description of the object. The content is formatted according to the "descriptionContentType" property.

4.2.3. descriptionContentType

Type: "String" (optional, default: "text/plain").

Describes the media type [[RFC6838](#)] of the contents of the "description" property. Media types MUST be sub-types of type "text", and SHOULD be "text/plain" or "text/html" [[MIME](#)]. They MAY include parameters and the "charset" parameter value MUST be "utf-8", if specified. Descriptions of type "text/html" MAY contain "cid" URLs [[RFC2392](#)] to reference links in the calendar object by use of the "cid" property of the Link object.

4.2.4. showWithoutTime

Type: "Boolean" (optional, default: false).

Indicates that the time is not important to display to the user when rendering this calendar object. An example of this is an event that conceptually occurs all day or across multiple days, such as "New Year's Day" or "Italy Vacation". While the time component is important for free-busy calculations and checking for scheduling clashes, calendars may choose to omit displaying it and/or display the object separately to other objects to enhance the user's view of their schedule.

Such events are also commonly known as "all-day" events.

4.2.5. locations

Type: "Id[Location]" (optional).

A map of location ids to Location objects, representing locations associated with the object.

A Location object has the following properties. It MUST have at least one property other than the "relativeTo" property.

- o @type: "String" (mandatory)

Specifies the type of this object. This MUST be "Location".

- o name: "String" (optional)

The human-readable name of the location.

- o description: "String" (optional)

Human-readable, plain-text instructions for accessing this location. This may be an address, set of directions, door access code, etc.

- o locationTypes: "String[Boolean]" (optional)

A set of one or more location types that describe this location. All types MUST be from the Location Types Registry as defined in [\[RFC4589\]](#). The set is represented as a map, with the keys being the location types. The value for each key in the map MUST be true.

- o relativeTo: "String" (optional)

Specifies the relation between this location and the time of the JSCalendar object. This is primarily to allow events representing travel to specify the location of departure (at the start of the event) and location of arrival (at the end); this is particularly important if these locations are in different time zones, as a client may wish to highlight this information for the user.

This MUST be one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value. Any value the client or server doesn't understand should be treated the same as if this property is omitted.

- * "start": The event/task described by this JSCalendar object occurs at this location at the time the event/task starts.
- * "end": The event/task described by this JSCalendar object occurs at this location at the time the event/task ends.

- o timeZone: "String" (optional)

A time zone for this location. See also [Section 1.4.9](#).

- o coordinates: "String" (optional)

A "geo:" URI [\[RFC5870\]](#) for the location.

- o linkIds: "Id[Boolean]" (optional)

A set of link ids for links to alternative representations of this location. Each key in the set MUST be the id of a Link object defined in the "links" property of this calendar object. The value for each key in the set MUST be true. If there are no links, this MUST be omitted (rather than specified as an empty set).

For example, an alternative representation could be in vCard format.

4.2.6. virtualLocations

Type: "Id[VirtualLocation]" (optional).

A map of ids to VirtualLocation objects, representing virtual locations, such as video conferences or chat rooms, associated with the object.

A VirtualLocation object has the following properties.

- o @type: "String" (mandatory)

Specifies the type of this object. This MUST be "VirtualLocation".

- o name: "String" (optional, default: empty String)

The human-readable name of the virtual location.

- o description: "String" (optional)

Human-readable plain-text instructions for accessing this location. This may be an address, set of directions, door access code, etc.

- o uri: "String" (mandatory)

A URI that represents how to connect to this virtual location.

This may be a telephone number (represented using the "tel:" scheme, e.g., "tel:+1-555-555-555") for a teleconference, a web address for online chat, or any custom URI.

4.2.7. links

Type: "Id[Link]" (optional).

A map of link ids to Link objects, representing external resources associated with the object.

A Link object has the following properties:

- o @type: "String" (mandatory)

Specifies the type of this object. This MUST be "Link".

- o href: "String" (mandatory)

A URI from which the resource may be fetched.

This MAY be a "data:" URL [[RFC2397](#)], but it is recommended that the file be hosted on a server to avoid embedding arbitrarily large data in JSCalendar object instances.

- o cid: "String" (optional)

This MUST be a valid "content-id" value according to the definition of [Section 2 in \[RFC2392\]](#). The value MUST be unique within this Link object but has no meaning beyond that. It MAY be different from the link id for this Link object.

- o contentType: "String" (optional)

The media type [[RFC6838](#)] of the resource, if known.

- o size: "UnsignedInt" (optional)

The size, in octets, of the resource when fully decoded (i.e., the number of octets in the file the user would download), if known.

- o rel: "String" (optional)

Identifies the relation of the linked resource to the object. If set, the value MUST be a relation type from the IANA registry [[LINKRELS](#)], as established in [[RFC8288](#)].

Links with a rel of "enclosure" SHOULD be considered by the client as attachments for download.

Links with a rel of "describedby" SHOULD be considered by the client to be an alternative representation of the description.

Links with a rel of "icon" SHOULD be considered by the client to be an image that it may use when presenting the calendar data to a

user. The "display" property may be set to indicate the purpose of this image.

o display: "String" (optional)

Describes the intended purpose of a link to an image. If set, the "rel" property MUST be set to "icon". The value MUST be one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value:

- * "badge": an image meant to be displayed alongside the title of the object.
- * "graphic": a full image replacement for the object itself.
- * "fullsize": an image that is used to enhance the object.
- * "thumbnail": a smaller variant of "fullsize" to be used when space for the image is constrained.

o title: "String" (optional)

A human-readable plain-text description of the resource.

4.2.8. locale

Type: "String" (optional).

The language tag as defined in [[RFC5646](#)] that best describes the locale used for the text in the calendar object, if known.

4.2.9. keywords

Type: "String[Boolean]" (optional).

A set of keywords or tags that relate to the object. The set is represented as a map, with the keys being the keywords. The value for each key in the map MUST be true.

4.2.10. categories

Type: "String[Boolean]" (optional).

A set of categories that relate to the calendar object. The set is represented as a map, with the keys being the categories specified as URIs. The value for each key in the map MUST be true.

In contrast to keywords, categories typically are structured. For example, a vendor owning the domain "example.com" might define the categories "http://example.com/categories/sports/american-football" and "http://example.com/categories/music/r-b".

4.2.11. color

Type: "String" (optional).

A color clients MAY use when displaying this calendar object. The value is a color name taken from the set of names defined in [Section 4.3](#) of CSS Color Module Level 3 [[COLORS](#)], or an RGB value in hexadecimal notation, as defined in [Section 4.2.1](#) of CSS Color Module Level 3.

4.3. Recurrence Properties

Some events and tasks occur at regular or irregular intervals. Rather than having to copy the data for every occurrence there can be a master event with a recurrence rule, and/or overrides that add extra dates or exceptions to the rule.

4.3.1. recurrenceId

Type: "LocalDateTime" (optional).

If present, this JSCalendar object represents one occurrence of a recurring JSCalendar object. If present the "recurrenceRules" and "recurrenceOverrides" properties MUST NOT be present.

The value is a date-time either produced by the "recurrenceRules" of the master event, or added as a key to the "recurrenceOverrides" property of the master event.

4.3.2. recurrenceRules

Type: "RecurrenceRule[]" (optional).

Defines a set of recurrence rules (repeating patterns) for recurring calendar objects.

A JSEvent recurs by applying the recurrence rules to the "start" date-time.

A JSTask recurs by applying the recurrence rules to the "start" date-time, if defined, otherwise it recurs by the "due" date-time, if defined. If the task defines neither a "start" nor "due" date-time, it MUST NOT define a "recurrenceRules" property.

If multiple recurrence rules are given, each rule is to be applied and then the union of the results used, ignoring any duplicates.

A `RecurrenceRule` object is a JSON object mapping of a `RECUR` value type in iCalendar [\[RFC5545\]](#) [\[RFC7529\]](#) and has the same semantics. It has the following properties:

- o `@type: "String"` (mandatory)

Specifies the type of this object. This MUST be `"RecurrenceRule"`.

- o `frequency: "String"` (mandatory)

The time span covered by each iteration of this recurrence rule (see [Section 4.3.2.1](#) for full semantics). This MUST be one of the following values:

- * `"yearly"`
- * `"monthly"`
- * `"weekly"`
- * `"daily"`
- * `"hourly"`
- * `"minutely"`
- * `"secondly"`

This is the `FREQ` part from iCalendar, converted to lowercase.

- o `interval: "UnsignedInt"` (optional, default: 1)

The interval of iteration periods at which the recurrence repeats. If included, it MUST be an integer ≥ 1 .

This is the `INTERVAL` part from iCalendar.

- o `rscale: "String"` (optional, default: `"gregorian"`)

The calendar system in which this recurrence rule operates, in lowercase. This MUST be either a CLDR-registered calendar system name [\[CLDR\]](#), or a vendor-specific value.

This is the `RSCALE` part from iCalendar `RSCALE` [\[RFC7529\]](#), converted to lowercase.

- o skip: "String" (optional, default: "omit")

The behaviour to use when the expansion of the recurrence produces invalid dates. This property only has an effect if the frequency is "yearly" or "monthly". It MUST be one of the following values:

- * "omit"
- * "backward"
- * "forward"

This is the SKIP part from iCalendar RSCALE [[RFC7529](#)], converted to lowercase.

- o firstDayOfWeek: "String" (optional, default: "mo")

The day on which the week is considered to start, represented as a lowercase abbreviated two-letter English day of the week. If included, it MUST be one of the following values:

- * "mo"
- * "tu"
- * "we"
- * "th"
- * "fr"
- * "sa"
- * "su"

This is the WKST part from iCalendar.

- o byDay: "NDay[]" (optional)

Days of the week on which to repeat. An *NDay* object has the following properties:

- * day: "String" (mandatory)

A day of the week on which to repeat; the allowed values are the same as for the "firstDayOfWeek" RecurrenceRule property.

This is the day-of-the-week of the BYDAY part in iCalendar, converted to lowercase.

* nthOfPeriod: "Int" (optional)

If present, rather than representing every occurrence of the weekday defined in the "day" property, it represents only a specific instance within the recurrence period. The value can be positive or negative, but MUST NOT be zero. A negative integer means nth-last of period.

This is the ordinal part of the BYDAY value in iCalendar (e.g., 1 or -3).

o byMonthDay: "Int[]" (optional)

Days of the month on which to repeat. Valid values are between 1 and the maximum number of days any month may have in the calendar given by the "rscale" property, and the negative values of these numbers. For example, in the Gregorian calendar valid values are 1 to 31 and -31 to -1. Negative values offset from the end of the month. The array MUST have at least one entry if included.

This is the BYMONTHDAY part in iCalendar.

o byMonth: "String[]" (optional)

The months in which to repeat. Each entry is a string representation of a number, starting from "1" for the first month in the calendar (e.g., "1" means January with the Gregorian calendar), with an optional "L" suffix (see [RFC7529](#)) for leap months (this MUST be uppercase, e.g., "3L"). The array MUST have at least one entry if included.

This is the BYMONTH part from iCalendar.

o byYearDay: "Int[]" (optional)

The days of the year on which to repeat. Valid values are between 1 and the maximum number of days any year may have in the calendar given by the "rscale" property, and the negative values of these numbers. For example, in the Gregorian calendar valid values are 1 to 366 and -366 to -1. Negative values offset from the end of the year. The array MUST have at least one entry if included.

This is the BYYEARDAY part from iCalendar.

o byWeekNo: "Int[]" (optional)

Weeks of the year in which to repeat. Valid values are between 1 and the maximum number of weeks any year may have in the calendar given by the "rscale" property, and the negative values of these numbers. For example, in the Gregorian calendar valid values are 1 to 53 and -53 to -1. The array **MUST** have at least one entry if included.

This is the BYWEEKNO part from iCalendar.

- o byHour: "UnsignedInt[]" (optional)

The hours of the day in which to repeat. Valid values are 0 to 23. The array **MUST** have at least one entry if included. This is the BYHOUR part from iCalendar.

- o byMinute: "UnsignedInt[]" (optional)

The minutes of the hour in which to repeat. Valid values are 0 to 59. The array **MUST** have at least one entry if included.

This is the BYMINUTE part from iCalendar.

- o bySecond: "UnsignedInt[]" (optional)

The seconds of the minute in which to repeat. Valid values are 0 to 60. The array **MUST** have at least one entry if included.

This is the BYSECOND part from iCalendar.

- o bySetPosition: "Int[]" (optional)

The occurrences within the recurrence interval to include in the final results. Negative values offset from the end of the list of occurrences. The array **MUST** have at least one entry if included. This is the BYSETPOS part from iCalendar.

- o count: "UnsignedInt" (optional)

The number of occurrences at which to range-bound the recurrence. This **MUST NOT** be included if an "until" property is specified.

This is the COUNT part from iCalendar.

- o until: "LocalDateTime" (optional)

The date-time at which to finish recurring. The last occurrence is on or before this date-time. This **MUST NOT** be included if a "count" property is specified. Note: if not specified otherwise

for a specific JSCalendar object, this date is to be interpreted in the time zone specified in the JSCalendar object's "timeZone" property.

This is the UNTIL part from iCalendar.

4.3.2.1. Interpreting recurrence rules

A recurrence rule specifies a set of date-times for recurring calendar objects. A recurrence rule has the following semantics. Note, wherever "year", "month" or "day of month" is used, this is within the calendar system given by the "rscale" property, which defaults to "gregorian" if omitted.

1. A set of candidates is generated. This is every second within a period defined by the frequency property value:

- * "yearly": every second from midnight on the 1st day of a year (inclusive) to midnight the 1st day of the following year (exclusive).

If skip is not "omit", the calendar system has leap months and there is a byMonth property, generate candidates for the leap months even if they don't occur in this year.

If skip is not "omit" and there is a byMonthDay property, presume each month has the maximum number of days any month may have in this calendar system when generating candidates, even if it's more than this month actually has.

- * "monthly": every second from midnight on the 1st day of a month (inclusive) to midnight on the 1st of the following month (exclusive).

If skip is not "omit" and there is a byMonthDay property, presume the month has the maximum number of days any month may have in this calendar system when generating candidates, even if it's more than this month actually has.

- * "weekly": every second from midnight (inclusive) on the first day of the week (as defined by the firstDayOfWeek property, or Monday if omitted), to midnight 7 days later (exclusive).
- * "daily": every second from midnight at the start of the day (inclusive) to midnight at the end of the day (exclusive).
- * "hourly": every second from the beginning of the hour (inclusive) to the beginning of the next hour (exclusive).

- * "minutely": every second from the beginning of the minute (inclusive) to the beginning of the next minute (exclusive).
 - * "secondly": the second itself, only.
2. Each date-time candidate is compared against all of the byX properties of the rule except bySetPosition. If any property in the rule does not match the date-time, it is eliminated. Each byX property is an array; the date-time matches the property if it matches any of the values in the array. The properties have the following semantics:
- * byMonth: the date-time is in the given month.
 - * byWeekNo: the date-time is in the nth week of the year. Negative numbers mean the nth last week of the year. This corresponds to weeks according to week numbering as defined in ISO.8601.2004, with a week defined as a seven day period, starting on the firstDayOfWeek property value or Monday if omitted. Week number one of the calendar year is the first week that contains at least four days in that calendar year.

If the date-time is not valid (this may happen when generating candidates with a skip property in effect), it is always eliminated by this property.
 - * byYearDay: the date-time is on the nth day of year. Negative numbers mean the nth last day of the year.

If the date-time is not valid (this may happen when generating candidates with a skip property in effect), it is always eliminated by this property.
 - * byMonthDay: the date-time is on the given day of the month. Negative numbers mean the nth last day of the month.
 - * byDay: the date-time is on the given day of the week. If the day is prefixed by a number, it is the nth occurrence of that day of the week within the month (if frequency is monthly) or year (if frequency is yearly). Negative numbers means nth last occurrence within that period.
 - * byHour: the date-time has the given hour value.
 - * byMinute: the date-time has the given minute value.
 - * bySecond: the date-time has the given second value.

If a skip property is defined and is not "omit", there may be candidates that do not correspond to valid dates (e.g., 31st February in the Gregorian calendar). In this case, the properties MUST be considered in the order above and:

1. After applying the byMonth filter, if the candidate's month is invalid for the given year, increment it (if skip is "forward") or decrement it (if skip is "backward") until a valid month is found, incrementing/decrementing the year as well if passing through the beginning/end of the year. This only applies to calendar systems with leap months.
2. After applying the byMonthDay filter, if the day of the month is invalid for the given month and year, change the date to the first day of the next month (if skip is "forward") or the last day of the current month (if skip is "backward").
3. If any valid date produced after applying the skip is already a candidate, eliminate the duplicate. (For example after adjusting, 30th February and 31st February would both become the same "real" date, so one is eliminated as a duplicate.)
3. If a bySetPosition property is included, this is now applied to the ordered list of remaining dates. This property specifies the indexes of date-times to keep; all others should be eliminated. Negative numbers are indexes from the end of the list, with -1 being the last item.
4. Any date-times before the start date of the event are eliminated (see below for why this might be needed).
5. If a skip property is included and is not "omit", eliminate any date-times that have already been produced by previous iterations of the algorithm. (This is not possible if skip is "omit".)
6. If further dates are required (we have not reached the until date, or count limit) skip the next (interval - 1) sets of candidates, then continue from step 1.

When determining the set of occurrence dates for an event or task, the following extra rules must be applied:

1. The initial date-time to which the rule is applied (the "start" date-time for events; the "start" or "due" date-time for tasks) is always the first occurrence in the expansion (and is counted if the recurrence is limited by a "count" property), even if it would normally not match the rule.

2. The first set of candidates to consider is that which would contain the initial date-time. This means the first set may include candidates before the initial date-time; such candidates are eliminated from the results in step (4) as outlined before.
3. The following properties MUST be implicitly added to the rule under the given conditions:
 - * If frequency is not "secondly" and no bySecond property: Add a bySecond property with the sole value being the seconds value of the initial date-time.
 - * If frequency is not "secondly" or "minutely", and no byMinute property: Add a byMinute property with the sole value being the minutes value of the initial date-time.
 - * If frequency is not "secondly", "minutely" or "hourly" and no byHour property: Add a byHour property with the sole value being the hours value of the initial date-time.
 - * If frequency is "weekly" and no byDay property: Add a byDay property with the sole value being the day-of-the-week of the initial date-time.
 - * If frequency is "monthly" and no byDay property and no byMonthDay property: Add a byMonthDay property with the sole value being the day-of-the-month of the initial date-time.
 - * If frequency is "yearly" and no byYearDay property:
 - + If there are no byMonth or byWeekNo properties, and either there is a byMonthDay property or there is no byDay property: Add a byMonth property with the sole value being the month of the initial date-time.
 - + If there is no byMonthDay, byWeekNo or byDay properties: Add a byMonthDay property with the sole value being the day-of-the-month of the initial date-time.
 - + If there is a byWeekNo property and no byMonthDay or byDay properties: Add a byDay property with the sole value being the day-of-the-week of the initial date-time.

4.3.3. recurrenceOverrides

Type: "LocalDateTime[PatchObject]" (optional).

A map of the recurrence ids (the date-time produced by the recurrence rule) to an object of patches to apply to the generated occurrence object.

If the recurrence id does not match a date-time from the recurrence rule (or no rule is specified), it is to be treated as an additional occurrence (like an RDATE from iCalendar). The patch object may often be empty in this case.

If the patch object defines the "excluded" property value to be true, then the recurring calendar object does not occur at the recurrence id date-time (like an EXDATE from iCalendar). Such a patch object MUST NOT patch any other property.

By default, an occurrence inherits all properties from the main object except the start (or due) date-time, which is shifted to match the recurrence id LocalDateTime. However, individual properties of the occurrence can be modified by a patch, or multiple patches. It is valid to patch the "start" property value, and this patch takes precedence over the value generated from the recurrence id. Both the recurrence id as well as the patched "start" date-time may occur before the original JSCalendar object's "start" or "due" date.

A pointer in the PatchObject MUST be ignored if it starts with one of the following prefixes:

- o @type
- o method
- o privacy
- o prodId
- o recurrenceId
- o recurrenceOverrides
- o recurrenceRules
- o relatedTo
- o replyTo
- o uid

[4.3.4.](#) **excluded**

Type: "Boolean" (optional, default: false).

Defines if this object is an overridden, excluded instance of a recurring JSCalendar object (see [Section 4.3.3](#)). If this property value is true, this calendar object instance **MUST** be removed from the occurrence expansion. The absence of this property or its default value false indicates that this instance **MUST** be included in the occurrence expansion.

[4.4.](#) **Sharing and Scheduling Properties**

[4.4.1.](#) **priority**

Type: "Int" (optional, default: 0).

Specifies a priority for the calendar object. This may be used as part of scheduling systems to help resolve conflicts for a time period.

The priority is specified as an integer in the range 0 to 9. A value of 0 specifies an undefined priority. A value of 1 is the highest priority. A value of 2 is the second highest priority. Subsequent numbers specify a decreasing ordinal priority. A value of 9 is the lowest priority. Other integer values are reserved for future use.

[4.4.2.](#) **freeBusyStatus**

Type: "String" (optional, default: "busy").

Specifies how this calendar object should be treated when calculating free-busy state. This **MUST** be one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value:

- o "free": The object should be ignored when calculating whether the user is busy.
- o "busy": The object should be included when calculating whether the user is busy.

[4.4.3.](#) **privacy**

Type: "String" (optional, default: "public").

Calendar objects are normally collected together and may be shared with other users. The privacy property allows the object owner to

indicate that it should not be shared, or should only have the time information shared but the details withheld. Enforcement of the restrictions indicated by this property are up to the API via which this object is accessed.

This property MUST NOT affect the information sent to scheduled participants; it is only interpreted when the object is shared as part of a shared calendar.

The value MUST be one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value. Any value the client or server doesn't understand should be preserved but treated as equivalent to "private".

- o "public": The full details of the object are visible to those whom the object's calendar is shared with.
- o "private": The details of the object are hidden; only the basic time and metadata is shared. The following properties MAY be shared, any other properties MUST NOT be shared:

- * @type
- * created
- * due
- * duration
- * estimatedDuration
- * freeBusyStatus
- * privacy
- * recurrenceOverrides. Only patches which apply to another permissible property are allowed to be shared.
- * sequence
- * showWithoutTime
- * start
- * timeZone
- * timeZones

- * uid
- * updated
- o "secret": The object is hidden completely (as though it did not exist) when the calendar this object is in is shared.

4.4.4. replyTo

Type: "String[String]" (optional).

Represents methods by which participants may submit their RSVP response to the organizer of the calendar object. The keys in the property value are the available methods and MUST only contain ASCII alphanumeric characters (A-Za-z0-9). The value is a URI for the method specified in the key. Future methods may be defined in future specifications and registered with IANA; a calendar client MUST ignore any method it does not understand, but MUST preserve the method key and URI. This property MUST be omitted if no method is defined (rather than being specified as an empty object). If this property is set, the "participants" property of this calendar object MUST contain at least one participant.

The following methods are defined:

- o "imip": The organizer accepts an iMIP [[RFC6047](#)] response at this email address. The value MUST be a "mailto:" URI.
- o "web": Opening this URI in a web browser will provide the user with a page where they can submit a reply to the organizer.
- o "other": The organizer is identified by this URI the method for submitting the response is undefined.

4.4.5. participants

Type: "Id[Participant]" (optional).

A map of participant ids to participants, describing their participation in the calendar object.

If this property is set, then the "replyTo" property of this calendar object MUST define at least one reply method.

A Participant object has the following properties:

- o @type: "String" (mandatory)

Specifies the type of this object. This MUST be "Participant".

- o name: "String" (optional)

The display name of the participant (e.g., "Joe Bloggs").

- o email: "String" (optional)

The email address for the participant.

- o sendTo: "String[String]" (optional)

Represents methods by which the participant may receive the invitation and updates to the calendar object.

The keys in the property value are the available methods and MUST only contain ASCII alphanumeric characters (A-Za-z0-9). The value is a URI for the method specified in the key. Future methods may be defined in future specifications and registered with IANA; a calendar client MUST ignore any method it does not understand, but MUST preserve the method key and URI. This property MUST be omitted if no method is defined (rather than being specified as an empty object).

The following methods are defined:

- * "imip": The participant accepts an iMIP [[RFC6047](#)] request at this email address. The value MUST be a "mailto:" URI. It MAY be different from the value of the participant's "email" property.
- * "other": The participant is identified by this URI but the method for submitting the invitation is undefined.

- o kind: "String" (optional)

What kind of entity this participant is, if known.

This MUST be one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value. Any value the client or server doesn't understand should be treated the same as if this property is omitted.

- * "individual": a single person
- * "group": a collection of people invited as a whole

- * "location": a physical location that needs to be scheduled, e.g., a conference room
- * "resource": a non-human resource other than a location, such as a projector

- o roles: "String[Boolean]" (mandatory)

A set of roles that this participant fulfills.

At least one role **MUST** be specified for the participant. The keys in the set **MUST** be one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value:

- * "owner": The participant is an owner of the object. This signifies they have permission to make changes to it that affect the other participants. Non-owner participants may only change properties that just affect themselves (for example setting their own alerts or changing their rsvp status).
- * "attendee": The participant is expected to attend.
- * "optional": The participant is invited but not required.
- * "informational": The participant is copied for informational reasons, and is not expected to attend.
- * "chair": The participant is in charge of the event/task when it occurs.

The value for each key in the set **MUST** be true. It is expected that no more than one of the roles "attendee", "optional", or "informational" be present; if more than one are given, "optional" takes precedence over "informational", and "attendee" takes precedence over both. Roles that are unknown to the implementation **MUST** be preserved.

- o locationId: "String" (optional)

The location at which this participant is expected to be attending.

If the value does not correspond to any location id in the "locations" property of the JSCalendar object, this **MUST** be treated the same as if the participant's locationId were omitted.

- o language: "String" (optional)

The language tag as defined in [[RFC5646](#)] that best describes the participant's preferred language, if known.

- o participationStatus: "String" (optional, default: "needs-action")

The participation status, if any, of this participant.

The value MUST be one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value:

- * "needs-action": No status yet set by the participant.
- * "accepted": The invited participant will participate.
- * "declined": The invited participant will not participate.
- * "tentative": The invited participant may participate.
- * "delegated": The invited participant has delegated their attendance to another participant, as specified in the delegatedTo property.

- o participationComment: "String" (optional)

A note from the participant to explain their participation status.

- o expectReply: "Boolean" (optional, default: false)

If true, the organizer is expecting the participant to notify them of their participation status.

- o scheduleAgent: "String" (optional, default: "server")

Who is responsible for sending scheduling messages with this calendar object to the participant.

The value MUST be one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value:

- * "server": The calendar server will send the scheduling messages.
- * "client": The calendar client will send the scheduling messages.
- * "none": No scheduling messages are to be sent to this participant.

- o `scheduleSequence`: "UnsignedInt" (optional, default: 0)

The sequence number of the last response from the participant. If defined, this MUST be a non-negative integer.

This can be used to determine whether the participant has sent a new RSVP following significant changes to the calendar object, and to determine if future responses are responding to a current or older view of the data.

- o `scheduleUpdated`: "UTCDateTime" (optional)

The "updated" property of the last iTIP response from the participant.

This can be compared to the "updated" property timestamp in future iTIP responses to determine if the response is older or newer than the current data.

- o `invitedBy`: "String" (optional)

The participant id of the participant who invited this one, if known.

- o `delegatedTo`: "String[Boolean]" (optional)

A set of participant ids that this participant has delegated their participation to. Each key in the set MUST be the id of a participant. The value for each key in the set MUST be true. If there are no delegates, this MUST be omitted (rather than specified as an empty set).

- o `delegatedFrom`: "String[Boolean]" (optional)

A set of participant ids that this participant is acting as a delegate for. Each key in the set MUST be the id of a participant. The value for each key in the set MUST be true. If there are no delegators, this MUST be omitted (rather than specified as an empty set).

- o `memberOf`: "String[Boolean]" (optional)

A set of group participants that were invited to this calendar object, which caused this participant to be invited due to their membership in the group(s). Each key in the set MUST be the id of a participant. The value for each key in the set MUST be true. If there are no groups, this MUST be omitted (rather than specified as an empty set).

- o linkIds: "String[Boolean]" (optional)

A set of links to more information about this participant, for example in vCard format. The keys in the set MUST be the id of a Link object in the calendar object's "links" property. The value for each key in the set MUST be true. If there are no links, this MUST be omitted (rather than specified as an empty set).

- o progress: "String" (optional). This is only allowed if the Participant is part of a JSTask. It represents the progress of the participant for this task, if known. This property MUST NOT be set if the "participationStatus" of this participant is any value other than "accepted". See [Section 5.2.4](#) for allowed values and semantics.
- o progressUpdated: "UTCDateTime" (optional). Specifies the date-time the progress property was last set on this participant. This is only allowed if the Participant is part of a JSTask.

[4.5.](#) Alerts Properties

[4.5.1.](#) useDefaultAlerts

Type: "Boolean" (optional, default: false).

If true, use the user's default alerts and ignore the value of the "alerts" property. Fetching user defaults is dependent on the API from which this JSCalendar object is being fetched, and is not defined in this specification. If an implementation cannot determine the user's default alerts, or none are set, it MUST process the alerts property as if "useDefaultAlerts" is set to false.

[4.5.2.](#) alerts

Type: "Id[Alert]" (optional).

A map of alert ids to Alert objects, representing alerts/reminders to display or send to the user for this calendar object.

An Alert Object has the following properties:

- o @type: "String" (mandatory)

Specifies the type of this object. This MUST be "Alert".

- o trigger: "OffsetTrigger|AbsoluteTrigger|UnknownTrigger" (mandatory)

Defines when to trigger the alert. New types may be defined in future documents.

An **OffsetTrigger** object has the following properties:

- * @type: "String" (mandatory)

Specifies the type of this object. This MUST be "OffsetTrigger".

- * offset: "SignedDuration" (mandatory).

Defines the offset at which to trigger the alert relative to the time property defined in the "relativeTo" property of the alert. Negative durations signify alerts before the time property, positive durations signify alerts after. If the calendar object does not define a time zone, the user's default time zone SHOULD be used when determining the offset, if known. Otherwise, the time zone to use is implementation specific.

- * relativeTo: "String" (optional, default: "start")

Specifies the time property that the alert offset is relative to. The value MUST be one of:

- + "start": triggers the alert relative to the start of the calendar object

- + "end": triggers the alert relative to the end/due time of the calendar object

An **AbsoluteTrigger** object has the following properties:

- * @type: "String" (mandatory)

Specifies the type of this object. This MUST be "AbsoluteTrigger".

- * when: "UTCDateTime" (mandatory).

Defines a specific UTC date-time when the alert is triggered.

An **UnknownTrigger** object is an object that contains a **@type** property whose value is not recognized (i.e., not "OffsetTrigger" or "AbsoluteTrigger"), plus zero or more other properties. This is for compatibility with client extensions and future specifications. Implementations SHOULD NOT trigger for trigger types they do not understand, but MUST preserve them.

- o acknowledged: "UTCDateTime" (optional)

This records when an alert was last acknowledged. This is set when the user has dismissed the alert; other clients that sync this property SHOULD automatically dismiss or suppress duplicate alerts (alerts with the same alert id that triggered on or before this date-time).

For a recurring calendar object, the "acknowledged" property of the parent object MUST be updated, unless the alert is already overridden in the "recurrenceOverrides" property.

Certain kinds of alert action may not provide feedback as to when the user sees them, for example email based alerts. For those kinds of alerts, this property SHOULD be set immediately when the alert is triggered and the action successfully carried out.

- o relatedTo: "String[Relation]" (optional)

Relates this alert to other alerts in the same JSCalendar object. If the user wishes to snooze an alert, the application SHOULD create an alert to trigger after snoozing. All snooze alerts SHOULD set a relation to the identifier of the original alert. The Relation object SHOULD set the "parent" relation type.

- o action: "String" (optional, default: "display")

Describes how to alert the user.

The value MUST be at most one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value:

- * "display": The alert should be displayed as appropriate for the current device and user context.
- * "email": The alert should trigger an email sent out to the user, notifying about the alert. This action is typically only appropriate for server implementations.

4.6. Multilingual Properties

4.6.1. localizations

Type: "String[PatchObject]" (optional).

A map of language tags [[RFC5646](#)] to patch objects, which localize the calendar object into the locale of the respective language tag.

See the description of PatchObject ([Section 1.4.8](#)) for the structure of the PatchObject. The patches are applied to the top-level calendar object. In addition, the "locale" property of the patched object is set to the language tag. All pointers for patches MUST end with one of the following suffixes; any patch that does not follow this MUST be ignored unless otherwise specified in a future RFC:

- o title
- o description
- o name

A patch MUST NOT have the prefix "recurrenceOverrides"; any localization of the override MUST be a patch to the localizations property inside the override instead. For example, a patch to "locations/abcd1234/title" is permissible, but a patch to "uid" or "recurrenceOverrides/2018-01-05T14:00:00/title" is not.

Note that this specification does not define how to maintain validity of localized content. For example, a client application changing a JSCalendar object's title property might also need to update any localizations of this property. Client implementations SHOULD provide the means to manage localizations, but how to achieve this is specific to the application's workflow and requirements.

[4.7.](#) Time Zone Properties

[4.7.1.](#) timeZone

Type: "String|null" (optional, default: null).

Identifies the time zone the object is scheduled in, or null for floating time. This is either a name from the IANA Time Zone Database [[TZDB](#)] or the id of a custom time zone from the "timeZones" property (see [Section 1.4.9](#)). If omitted, this MUST be presumed to be null (i.e., floating time).

[4.7.2.](#) timeZones

Type: "String[TimeZone]" (optional).

Maps identifiers of custom time zones to their time zone definitions. The following restrictions apply for each key in the map:

- o It MUST start with the "/" character (ASCII decimal 47; also see Sections [3.2.19](#) of [[RFC5545](#)] and 3.6. of [[RFC7808](#)] for discussion of the forward slash character in time zone identifiers).

- o It MUST be a valid "paramtext" value as specified in [Section 3.1. of \[RFC5545\]](#).
- o At least one other property in the same JSCalendar object MUST reference a time zone using this identifier (i.e., orphaned time zones are not allowed).

An identifier need only be unique to this JSCalendar object.

A TimeZone object maps a VTIMEZONE component from iCalendar [\[RFC5545\]](#) and the semantics are as defined there. A valid time zone MUST define at least one transition rule in the "standard" or "daylight" property. Its properties are:

- o @type: "String" (mandatory)
Specifies the type of this object. This MUST be "TimeZone".
- o tzId: "String" (mandatory).
The TZID property from iCalendar.
- o lastModified: "UTCDateTime" (optional)
The LAST-MODIFIED property from iCalendar.
- o url: "String" (optional)
The TZURL property from iCalendar.
- o validUntil: "UTCDateTime" (optional)
The TZUNTIL property from iCalendar specified in [\[RFC7808\]](#).
- o aliases: "String[Boolean]" (optional)
Maps the TZID-ALIAS-OF properties from iCalendar specified in [\[RFC7808\]](#) to a JSON set of aliases. The set is represented as an object, with the keys being the aliases. The value for each key in the set MUST be true.
- o standard: "TimeZoneRule[]" (optional)
The STANDARD sub-components from iCalendar. The order MUST be preserved during conversion.
- o daylight: "TimeZoneRule[]" (optional).

The DAYLIGHT sub-components from iCalendar. The order MUST be preserved during conversion.

A TimeZoneRule object maps a STANDARD or DAYLIGHT sub-component from iCalendar, with the restriction that at most one recurrence rule is allowed per rule. It has the following properties:

- o @type: "String" (mandatory)

Specifies the type of this object. This MUST be "TimeZoneRule".

- o start: "LocalDateTime" (mandatory)

The DTSTART property from iCalendar.

- o offsetTo: "String" (mandatory)

The TZOFFSETTO property from iCalendar.

- o offsetFrom: "String" (mandatory)

The TZOFFSETFROM property from iCalendar.

- o recurrenceRule: "RecurrenceRule" (optional)

The RRULE property mapped as specified in [Section 4.3.2](#). During recurrence rule evaluation, the "until" property value MUST be interpreted as a local time in the UTC time zone.

- o recurrenceDates: "LocalDateTime[Boolean]" (optional)

Maps the RDATE properties from iCalendar to a JSON set. The set is represented as an object, with the keys being the recurrence dates. The value for each key in the set MUST be true.

- o names: "String[Boolean]" (optional)

Maps the TZNAME properties from iCalendar to a JSON set. The set is represented as an object, with the keys being the names. The value for each key in the set MUST be true.

- o comments: "String[]" (optional). Maps the COMMENT properties from iCalendar. The order MUST be preserved during conversion.

5. Type-specific JSCalendar Properties

5.1. JSEvent Properties

In addition to the common JSCalendar object properties ([Section 4](#)) a JSEvent has the following properties:

5.1.1. start

Type: "LocalDateTime" (mandatory).

The date/time the event starts in the event's time zone (as specified in the "timeZone" property, see [Section 4.7.1](#)).

5.1.2. duration

Type: "Duration" (optional, default: "PT0S").

The zero or positive duration of the event in the event's start time zone.

Note that a duration specified using weeks or days does not always correspond to an exact multiple of 24 hours. The number of hours/minutes/seconds may vary if it overlaps a period of discontinuity in the event's time zone, for example a change from standard time to daylight-savings time. Leap seconds MUST NOT be considered when computing an exact duration. When computing an exact duration, the greatest order time components MUST be added first, that is, the number of days MUST be added first, followed by the number of hours, number of minutes, and number of seconds. Fractional seconds MUST be added last. These semantics match the iCalendar DURATION value type ([\[RFC5545\]](#), [Section 3.3.6](#)).

A JSEvent MAY involve start and end locations that are in different time zones (e.g., a trans-continental flight). This can be expressed using the "relativeTo" and "timeZone" properties of the JSEvent's Location objects (see [Section 4.2.5](#)).

5.1.3. status

Type: "String" (optional, default: "confirmed").

The scheduling status ([Section 4.4](#)) of a JSEvent. If set, it MUST be one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value:

- o "confirmed": Indicates the event is definitely happening.

- o "cancelled": Indicates the event has been cancelled.
- o "tentative": Indicates the event may happen.

5.2. JSTask Properties

In addition to the common JSCalendar object properties ([Section 4](#)) a JSTask has the following properties:

5.2.1. due

Type: "LocalDateTime" (optional).

The date/time the task is due in the task's time zone.

5.2.2. start

Type: "LocalDateTime" (optional).

The date/time the task should start in the task's time zone.

5.2.3. estimatedDuration

Type: "Duration" (optional).

Specifies the estimated positive duration of time the task takes to complete.

5.2.4. progress

Type: "String" (optional).

Defines the progress of this task. If omitted, the default progress ([Section 4.4](#)) of a JSTask is defined as follows (in order of evaluation):

- o "completed": if the "progress" property value of all participants is "completed".
- o "failed": if at least one "progress" property value of a participant is "failed".
- o "in-process": if at least one "progress" property value of a participant is "in-process".
- o "needs-action": If none of the other criteria match.

If set, it MUST be one of the following values, a value registered in the IANA JSCalendar Enum Registry, or a vendor-specific value:

- o "needs-action": Indicates the task needs action.
- o "in-process": Indicates the task is in process.
- o "completed": Indicates the task is completed.
- o "failed": Indicates the task failed.
- o "cancelled": Indicates the task was cancelled.

5.2.5. progressUpdated

Type: "UTCDateTime" (optional).

Specifies the date/time the "progress" property of either the task overall ([Section 5.2.4](#)) or a specific participant ([Section 4.4.5](#)) was last updated.

If the task is recurring and has future instances, a client may want to keep track of the last progress update timestamp of a specific task recurrence, but leave other instances unchanged. One way to achieve this is by overriding the progressUpdated property in the task "recurrenceOverrides" property. However, this could produce a long list of timestamps for regularly recurring tasks. An alternative approach is to split the JSTask into a current, single instance of JSTask with this instance progress update time and a future recurring instance. See also [Section 4.1.3](#) on splitting.

5.3. JSGroup Properties

JSGroup supports the following common JSCalendar properties ([Section 4](#)):

- o @type
- o categories
- o color
- o created
- o description
- o descriptionContentType

- o keywords
- o links
- o locale
- o prodId
- o title
- o updated
- o uid

In addition, the following JSGroup-specific properties are supported:

5.3.1. entries

Type: "String[JSTask|JSEvent]" (mandatory).

A collection of group members. This is represented as a map of the "uid" property value to the JSCalendar object member having that uid. Implementations MUST ignore entries of unknown type.

5.3.2. source

Type: "String" (optional).

The source from which updated versions of this group may be retrieved from. The value MUST be a URI.

6. Examples

The following examples illustrate several aspects of the JSCalendar data model and format. The examples may omit mandatory or additional properties, which is indicated by a placeholder property with key "...". While most of the examples use calendar event objects, they are also illustrative for tasks.

6.1. Simple event

This example illustrates a simple one-time event. It specifies a one-time event that begins on January 15, 2018 at 1pm New York local time and ends after 1 hour.


```
{
  "@type": "jsevent",
  "uid": "2a358cee-6489-4f14-a57f-c104db4dc2f1",
  "updated": "2018-01-15T18:00:00Z",
  "title": "Some event",
  "start": "2018-01-15T13:00:00",
  "timeZone": "America/New_York",
  "duration": "PT1H"
}
```

[6.2.](#) Simple task

This example illustrates a simple task for a plain to-do item.

```
{
  "@type": "jstask",
  "uid": "2a358cee-6489-4f14-a57f-c104db4dc2f2",
  "updated": "2018-01-15T18:00:00Z",
  "title": "Do something"
}
```

[6.3.](#) Simple group

This example illustrates a simple calendar object group that contains an event and a task.


```
{
  "@type": "jsgroup",
  "uid": "2a358cee-6489-4f14-a57f-c104db4dc343",
  "updated": "2018-01-15T18:00:00Z",
  "name": "A simple group",
  "entries": {
    "2a358cee-6489-4f14-a57f-c104db4dc2f1": {
      "@type": "jsevent",
      "uid": "2a358cee-6489-4f14-a57f-c104db4dc2f1",
      "updated": "2018-01-15T18:00:00Z",
      "title": "Some event",
      "start": "2018-01-15T13:00:00",
      "timeZone": "America/New_York",
      "duration": "PT1H"
    },
    "2a358cee-6489-4f14-a57f-c104db4dc2f2": {
      "@type": "jstask",
      "uid": "2a358cee-6489-4f14-a57f-c104db4dc2f2",
      "updated": "2018-01-15T18:00:00Z",
      "title": "Do something"
    }
  }
}
```

[6.4.](#) All-day event

This example illustrates an event for an international holiday. It specifies an all-day event on April 1 that occurs every year since the year 1900.

```
{
  "...": "",
  "title": "April Fool's Day",
  "showWithoutTime": true,
  "start": "1900-04-01T00:00:00",
  "duration": "P1D",
  "recurrenceRules": [{
    "@type": "RecurrenceRule",
    "frequency": "yearly"
  }]
}
```

[6.5.](#) Task with a due date

This example illustrates a task with a due date. It is a reminder to buy groceries before 6pm Vienna local time on January 19, 2018. The calendar user expects to need 1 hour for shopping.


```
{
  "...": "",
  "title": "Buy groceries",
  "due": "2018-01-19T18:00:00",
  "timeZone": "Europe/Vienna",
  "estimatedDuration": "PT1H"
}
```

6.6. Event with end time-zone

This example illustrates the use of end time-zones by use of an international flight. The flight starts on April 1, 2018 at 9am in Berlin local time. The duration of the flight is scheduled at 10 hours 30 minutes. The time at the flights destination is in the same time-zone as Tokyo. Calendar clients could use the end time-zone to display the arrival time in Tokyo local time and highlight the time-zone difference of the flight. The location names can serve as input for navigation systems.

```
{
  "...": "",
  "title": "Flight XY51 to Tokyo",
  "start": "2018-04-01T09:00:00",
  "timeZone": "Europe/Berlin",
  "duration": "PT10H30M",
  "locations": {
    "2a358cee-6489-4f14-a57f-c104db4dc2f1": {
      "@type": "Location",
      "rel": "start",
      "name": "Frankfurt Airport (FRA)"
    },
    "c2c7ac67-dc13-411e-a7d4-0780fb61fb08": {
      "@type": "Location",
      "rel": "end",
      "name": "Narita International Airport (NRT)",
      "timeZone": "Asia/Tokyo"
    }
  }
}
```

6.7. Floating-time event (with recurrence)

This example illustrates the use of floating-time. Since January 1, 2018, a calendar user blocks 30 minutes every day to practice Yoga at 7am local time, in whatever time-zone the user is located on that date.


```
{
  "...": "",
  "title": "Yoga",
  "start": "2018-01-01T07:00:00",
  "duration": "PT30M",
  "recurrenceRules": [{
    "@type": "RecurrenceRule",
    "frequency": "daily"
  }]
}
```

[6.8.](#) Event with multiple locations and localization

This example illustrates an event that happens at both a physical and a virtual location. Fans can see a live concert on premises or online. The event title and descriptions are localized.


```

{
  "...": "",
  "title": "Live from Music Bowl: The Band",
  "description": "Go see the biggest music event ever!",
  "locale": "en",
  "start": "2018-07-04T17:00:00",
  "timeZone": "America/New_York",
  "duration": "PT3H",
  "locations": {
    "c0503d30-8c50-4372-87b5-7657e8e0fedd": {
      "@type": "Location",
      "name": "The Music Bowl",
      "description": "Music Bowl, Central Park, New York",
      "coordinates": "geo:40.7829,-73.9654"
    }
  },
  "virtualLocations": {
    "6f3696c6-1e07-47d0-9ce1-f50014b0041a": {
      "@type": "VirtualLocation",
      "name": "Free live Stream from Music Bowl",
      "uri": "https://stream.example.com/the_band_2018"
    }
  },
  "localizations": {
    "de": {
      "title": "Live von der Music Bowl: The Band!",
      "description": "Schau dir das groesste Musikereignis an!",
      "virtualLocations/6f3696c6-1e07-47d0-9ce1-f50014b0041a/name":
        "Gratis Live-Stream aus der Music Bowl"
    }
  }
}

```

6.9. Recurring event with overrides

This example illustrates the use of recurrence overrides. A math course at a University is held for the first time on January 8, 2018 at 9am London time and occurs every week until June 25, 2018. Each lecture lasts for one hour and 30 minutes and is located at the Mathematics department. This event has exceptional occurrences: at the last occurrence of the course is an exam, which lasts for 2 hours and starts at 10am. Also, the location of the exam differs from the usual location. On April 2 no course is held. On January 5 at 2pm is an optional introduction course, that occurs before the first regular lecture.


```

{
  "...": "",
  "title": "Calculus I",
  "start": "2018-01-08T09:00:00",
  "timeZone": "Europe/London",
  "duration": "PT1H30M",
  "locations": {
    "2a358cee-6489-4f14-a57f-c104db4dc2f1": {
      "@type": "Location",
      "title": "Math lab room 1",
      "description": "Math Lab I, Department of Mathematics"
    }
  },
  "recurrenceRules": [{
    "@type": "RecurrenceRule",
    "frequency": "weekly",
    "until": "2018-06-25T09:00:00"
  }],
  "recurrenceOverrides": {
    "2018-01-05T14:00:00": {
      "title": "Introduction to Calculus I (optional)"
    },
    "2018-04-02T09:00:00": {
      "excluded": "true"
    },
    "2018-06-25T09:00:00": {
      "title": "Calculus I Exam",
      "start": "2018-06-25T10:00:00",
      "duration": "PT2H",
      "locations": {
        "2a358cee-6489-4f14-a57f-c104db4dc2f1": {
          "@type": "Location",
          "title": "Big Auditorium",
          "description": "Big Auditorium, Other Road"
        }
      }
    }
  }
}

```

6.10. Recurring event with participants

This example illustrates scheduled events. A team meeting occurs every week since January 8, 2018 at 9am Johannesburg time. The event owner also chairs the event. Participants meet in a virtual meeting room. An attendee has accepted the invitation, but on March 8, 2018 he is unavailable and declined participation for this occurrence.


```
{
  "...": "",
  "title": "FooBar team meeting",
  "start": "2018-01-08T09:00:00",
  "timeZone": "Africa/Johannesburg",
  "duration": "PT1H",
  "virtualLocations": {
    "2a358cee-6489-4f14-a57f-c104db4dc2f1": {
      "@type": "VirtualLocation",
      "name": "ChatMe meeting room",
      "uri": "https://chatme.example.com?id=1234567"
    }
  },
  "recurrenceRules": [{
    "@type": "RecurrenceRule",
    "frequency": "weekly"
  }],
  "replyTo": {
    "imip": "mailto:6489-4f14-a57f-c1@schedule.example.com"
  },
  "participants": {
    "dG9tQGZvb2Jhci5x1LmNvbQ": {
      "@type": "Participant",
      "name": "Tom Tool",
      "email": "tom@foobar.example.com",
      "sendTo": {
        "imip": "mailto:6489-4f14-a57f-c1@calendar.example.com"
      },
      "participationStatus": "accepted",
      "roles": {
        "attendee": true
      }
    },
    "em9lQGZvb2GFtcGx1LmNvbQ": {
      "@type": "Participant",
      "name": "Zoe Zelda",
      "email": "zoe@foobar.example.com",
      "sendTo": {
        "imip": "mailto:zoe@foobar.example.com"
      },
      "participationStatus": "accepted",
      "roles": {
        "owner": true,
        "attendee": true,
        "chair": true
      }
    }
  },
  "...": ""
}
```



```
    },
    "recurrenceOverrides": {
      "2018-03-08T09:00:00": {
        "participants/dG9tQGZvb2Jhci5x1LmNvbQ/participationStatus":
          "declined"
      }
    }
  }
}
```

7. Security Considerations

Calendaring and scheduling information is very privacy-sensitive. The transmission of such information must be done carefully to protect it from possible threats, such as eavesdropping, replay, message insertion, deletion, modification, and man-in-the-middle attacks. This document just defines the data format; such considerations are primarily the concern of the API or method of storage and transmission of such files.

7.1. Expanding Recurrences

A recurrence rule may produce infinite occurrences of an event. Implementations **MUST** handle expansions carefully to prevent accidental or deliberate resource exhaustion.

Conversely, a recurrence rule may be specified that does not expand to anything. It is not always possible to tell this through static analysis of the rule, so implementations **MUST** be careful to avoid getting stuck in infinite loops, or otherwise exhausting resources while searching for the next occurrence.

7.2. JSON Parsing

The Security Considerations of [[RFC8259](#)] apply to the use of JSON as the data interchange format.

As for any serialization format, parsers need to thoroughly check the syntax of the supplied data. JSON uses opening and closing tags for several types and structures, and it is possible that the end of the supplied data will be reached when scanning for a matching closing tag; this is an error condition, and implementations need to stop scanning at the end of the supplied data.

JSON also uses a string encoding with some escape sequences to encode special characters within a string. Care is needed when processing these escape sequences to ensure that they are fully formed before the special processing is triggered, with special care taken when the escape sequences appear adjacent to other (non-escaped) special

characters or adjacent to the end of data (as in the previous paragraph).

If parsing JSON into a non-textual structured data format, implementations may need to allocate storage to hold JSON string elements. Since JSON does not use explicit string lengths, the risk of denial of service due to resource exhaustion is small, but implementations may still wish to place limits on the size of allocations they are willing to make in any given context, to avoid untrusted data causing excessive memory allocation.

7.3. URI Values

Several JSCalendar properties contain URIs as values, and processing these properties requires extra care. [Section 7 of \[RFC3986\]](#) discusses security risk related to URIs.

8. IANA Considerations

8.1. Media Type Registration

This document defines a media type for use with JSCalendar data formatted in JSON.

Type name: application

Subtype name: jscalendar+json

Required parameters: type

The "type" parameter conveys the type of the JSCalendar data in the body part, with the value being one of "jsevent", "jstask", or "jsgroup". The parameter MUST NOT occur more than once. It MUST match the value of the "@type" property of the JSON-formatted JSCalendar object in the body.

Optional parameters: none

Encoding considerations: Same as encoding considerations of application/json as specified in [RFC8529, Section 11](#) [[RFC8259](#)].

Security considerations: See [Section 7](#) of this document.

Interoperability considerations: This media type provides an alternative to iCalendar, jCal and proprietary JSON-based calendaring data formats.

Published specification: This specification.

Applications that use this media type: Applications that currently make use of the text/calendar and application/calendar+json media types can use this as an alternative. Similarly, applications that use the application/json media type to transfer calendaring data can use this to further specify the content.

Fragment identifier considerations: N/A

Additional information:

Magic number(s): N/A

File extensions(s): N/A

Macintosh file type code(s): N/A

Person & email address to contact for further information:
calsify@ietf.org

Intended usage: COMMON

Restrictions on usage: N/A

Author: See the "Author's Address" section of this document.

Change controller: IETF

8.2. Creation of "JSCalendar Properties" Registry

The IANA will create the "JSCalendar Properties" registry to allow interoperability of extensions to JSCalendar objects.

This registry follows the Expert Review process ([\[RFC8126\]](#), [Section 4.5](#)) unless the "intended use" field is "common", in which case registration follows the Specification Required process ([\[RFC8126\]](#), [Section 4.6](#)). Preliminary community review for this registry is optional but strongly encouraged.

A registration can have an intended use of "common", "reserved", or "obsolete". The IANA will list common-use registrations prominently and separately from those with other intended use values.

A "reserved" registration reserves a property name without assigning semantics to avoid name collisions with future extensions or protocol use.

An "obsolete" registration denotes a property that is no longer expected to be added by up-to-date systems. A new property has probably been defined covering the obsolete property's semantics.

The JSCalendar property registration procedure is not a formal standards process but rather an administrative procedure intended to allow community comment and sanity checking without excessive time delay. It is designed to encourage vendors to document and register new properties they add for use cases not covered by the original standard, leading to increased interoperability.

8.2.1. Preliminary Community Review

Notice of a potential new registration SHOULD be sent to the Calext mailing list <calsify@ietf.org> for review. This mailing list is appropriate to solicit community feedback on a proposed new property.

Properties registrations must be marked with their intended use: "common", "reserved" or "obsolete".

The intent of the public posting to this list is to solicit comments and feedback on the choice of the property name, the unambiguity of the specification document, and a review of any interoperability or security considerations. The submitter may submit a revised registration proposal or abandon the registration completely at any time.

8.2.2. Submit Request to IANA

Registration requests can be sent to <iana@iana.org>.

8.2.3. Designated Expert Review

The primary concern of the designated expert (DE) is preventing name collisions and encouraging the submitter to document security and privacy considerations. For a common-use registration, the DE is expected to confirm that suitable documentation, as described in [Section 4.6 of \[RFC8126\]](#), is available to ensure interoperability. This preferably takes the form of an RFC, but for simple definitions a description in the registry may be sufficient. The DE should also verify that the property name does not conflict with work that is active or already published within the IETF. A published specification is not required for reserved or obsolete registrations.

The DE will either approve or deny the registration request and publish a notice of the decision to the Calext WG mailing list or its successor, as well as inform IANA. A denial notice must be justified by an explanation, and, in the cases where it is possible, concrete

suggestions on how the request can be modified so as to become acceptable should be provided.

8.2.4. Change Procedures

Once a JSCalendar property has been published by the IANA, the change controller may request a change to its definition. The same procedure that would be appropriate for the original registration request is used to process a change request.

JSCalendar property registrations may not be deleted; properties that are no longer believed appropriate for use can be declared obsolete by a change to their "intended use" field; such properties will be clearly marked in the lists published by the IANA.

Significant changes to a JSCalendar property's definition should be requested only when there are serious omissions or errors in the published specification, as such changes may cause interoperability issues. When review is required, a change request may be denied if it renders entities that were valid under the previous definition invalid under the new definition.

The owner of a JSCalendar property may pass responsibility to another person or agency by informing the IANA; this can be done without discussion or review.

8.2.5. JMAP Properties Registry Template

- o Property Name: The name of the property. The property name MUST NOT already be registered for any of the object types listed in the "Property Context" field of this registration. Other object types MAY already have registered a different property with the same name.
- o Property Type: The type of this property, using type signatures as specified in [Section 1.3](#). The property type MUST be registered in the Type Registry.
- o Property Context: A comma-separated list of JSCalendar object types this property is allowed on.
- o Reference or Description: A brief description or RFC number and section reference where the property is specified (omitted for "reserved" property names).
- o Intended Use: Common, reserved, or obsolete.
- o Change Controller: ("IETF" for IETF-stream RFCs).

8.2.6. Initial Contents for the JSCalendar Properties Registry

The following table lists the initial entries of the JSCalendar Properties registry. All properties are for common-use. All RFC section references are for this document. The change controller for all these properties is "IETF".

Property Name	Property Type	Property Context	Reference or Description
@type	String	JSEvent, JSTask, JSGroup, AbsoluteTrigger, Alert, Link, Location, OffsetTrigger, Participant, RecurrenceRule, Relation, TimeZone, VirtualLocation	Section 4.1.1, Section 4.5.2, Section 4.2.7, Section 4.2.5, Section 4.4.5, Section 4.3.2, Section 4.1.3, Section 4.7.2, Section 4.2.6
acknowledged	UTCDateTime	Alert	Section 4.5.2
action	String	Alert	Section 4.5.2
alerts	Id[Alert]	JSEvent, JSTask	Section 4.5.2
byDay	NDay[]	RecurrenceRule	Section 4.3.2
byHour	UnsignedInt[]	RecurrenceRule	Section 4.3.2
byMinute	UnsignedInt[]	RecurrenceRule	Section 4.3.2

		Rule	4.3.2
byMonth	String[]	Recurrence Rule	Section 4.3.2
byMonthDay	Int[]	Recurrence Rule	Section 4.3.2
bySecond	UnsignedInt[]	Recurrence Rule	Section 4.3.2
bySetPosition	Int[]	Recurrence Rule	Section 4.3.2
byWeekNo	Int[]	Recurrence Rule	Section 4.3.2
byYearDay	Int[]	Recurrence Rule	Section 4.3.2
categories	String[Boolean]	JSEvent, JSTask, JSGroup	Section 4.2.10
cid	String	Link	Section 4.2.7
color	String	JSEvent, JSTask, JSGroup	Section 4.2.11
contentType	String	Link	Section 4.2.7
coordinates	String	Location	Section 4.2.5
count	UnsignedInt	Recurrence Rule	Section 4.3.2
created	UTCDateTime	JSEvent, JSTask, JSGroup	Section 4.1.5
delegatedFrom	String[Boolean]	Participant	Section 4.4.5
delegatedTo	String[Boolean]	Participant	Section

		t	4.4.5
description	String	JSEvent, JSTask, Location, VirtualLoc ation	Section 4.2.2, Section 4.2.5, Section 4.2.6
descriptionCo ntentType	String	JSEvent, JSTask	Section 4.2.3
display	String	Link	Section 4.2.7
due	LocalDateTime	JSTask	Section 5.2.1
duration	Duration	JSEvent	Section 5.1.2
email	String	Participan t	Section 4.4.5
entries	String[JSTask JSEvent]	JSGroup	Section 5.3.1
estimatedDura tion	Duration	JSTask	Section 5.2.3
excluded	Boolean	JSEvent, JSTask	Section 4.3.4
expectReply	Boolean	Participan t	Section 4.4.5
firstDayOfWee k	String	Recurrence Rule	Section 4.3.2
freeBusyStatu s	String	JSEvent, JSTask	Section 4.4.2
frequency	String	Recurrence Rule	Section 4.3.2
href	String	Link	Section 4.2.7

interval	UnsignedInt	Recurrence Rule	Section 4.3.2
invitedBy	String	Participant	Section 4.4.5
keywords	String[Boolean]	JSEvent, JSTask, JSGroup	Section 4.2.9
kind	String	Participant	Section 4.4.5
language	String	Participant	Section 4.4.5
linkIds	Id[Boolean]	Location, Participant	Section 4.2.5, Section 4.4.5
links	Id[Link]	JSGroup, JSEvent, JSTask	Section 4.2.7
locale	String	JSGroup, JSEvent, JSTask	Section 4.2.7
localizations	String[PatchObject]	JSEvent, JSTask	Section 4.6.1
locationId	String	Participant	Section 4.4.5
locations	Id[Location]	JSEvent, JSTask	Section 4.2.5
locationTypes	String[Boolean]	Location	Section 4.2.5
memberOf	String[Boolean]	Participant	Section 4.4.5
method	String	JSEvent, JSTask	Section 4.1.8
name	String	Location,	Section

		VirtualLocation, Participant	4.2.5, Section 4.2.6, Section 4.4.5
offset	SignedDuration	OffsetTrigger	Section 4.5.2
participants	Id[Participant]	JSEvent, JSTask	Section 4.4.5
participationComment	String	Participant	Section 4.4.5
participationStatus	String	Participant	Section 4.4.5
priority	Int	JSEvent, JSTask	Section 4.4.1
privacy	String	JSEvent, JSTask	Section 4.4.3
prodId	String	JSEvent, JSTask, JSGroup	Section 4.1.4
progress	String	JSTask, Participant	Section 5.2.4
progressUpdated	UTCDateTime	JSTask, Participant	Section 5.2.5
recurrenceId	LocalDateTime	JSEvent, JSTask	Section 4.3.1
recurrenceOverrides	LocalDateTime[PatchObject]	JSEvent, JSTask	Section 4.3.3
recurrenceRules	RecurrenceRule[]	JSEvent, JSTask	Section 4.3.2
rel	String	Link	Section 4.2.7
relatedTo	String[Relation]	JSEvent, JSTask,	Section 4.1.3,

		Alert	Section
			4.5.2
relation	String[Boolean]	Relation	Section
			1.4.10
relativeTo	String	OffsetTrig ger, Location	Section
			4.5.2, Section
			4.2.5
replyTo	String[String]	JSEvent, JSTask	Section
			4.4.4
roles	String[Boolean]	Participan t	Section
			4.4.5
rscale	String	Recurrence Rule	Section
			4.3.2
scheduleAgent	String	Participan t	Section
			4.4.5
scheduleSeque nce	UnsignedInt	Participan t	Section
			4.4.5
scheduleUpdat ed	UTCDateTime	Participan t	Section
			4.4.5
sendTo	String[String]	Participan t	Section
			4.4.5
sequence	UnsignedInt	JSEvent, JSTask	Section
			4.1.7
showWithoutTi me	Boolean	JSEvent, JSTask	Section
			4.2.4
size	UnsignedInt	Link	Section
			4.2.7
skip	String	Recurrence Rule	Section
			4.3.2
source	String	JSGroup	Section
			5.3.2
start	LocalDateTime	JSEvent,	Section

		JSTask	5.1.1, Section 5.2.2
status	String	JSEvent	Section 5.1.3
timeZone	String null	JSEvent, JSTask, Location	Section 4.7.1, Section 4.2.5
timeZones	String[TimeZone]	JSEvent, JSTask	Section 4.7.2
title	String	JSEvent, JSTask, JSGroup, Link	Section 4.2.1
trigger	OffsetTrigger AbsoluteTrigger UnknownTrigger	Alert	Section 4.5.2
uid	String	JSEvent, JSTask, JSGroup	Section 4.1.2
until	LocalDateTime	Recurrence Rule	Section 4.3.2
updated	UTCDateTime	JSEvent, JSTask, JSGroup	Section 4.1.6
uri	String	VirtualLocation	Section 4.2.6
useDefaultAlerts	Boolean	JSEvent, JSTask	Section 4.5.1
virtualLocations	Id[VirtualLocation]	JSEvent, JSTask	Section 4.2.6
when	UTCDateTime	AbsoluteTrigger	Section 4.5.2

Table 1

8.3. Creation of "JSCalendar Types" Registry

The IANA will create the "JSCalendar Types" registry to avoid name collisions and provide a complete reference for all data types used for JSCalendar property values. The registration process is the same as for the JSCalendar Properties registry, as defined in [Section 8.2](#).

8.3.1. JMAP Types Registry Template

- o Type Name: The name of the type.
- o Reference or Description: A brief description or RFC number and section reference where the Type is specified (may be omitted for "reserved" type names).
- o Intended Use: Common, reserved, or obsolete.
- o Change Controller: ("IETF" for IETF-stream RFCs).

8.3.2. Initial Contents for the JSCalendar Types Registry

The following table lists the initial entries of the JSCalendar Types registry. All properties are for common-use. All RFC section references are for this document. The change controller for all these properties is "IETF".

Type Name	Reference or Description
Alert	Section 4.5.2
Boolean	Section 1.3
Duration	Section 1.4.5
Id	Section 1.4.7
Int	Section 1.4.1
LocalDateTime	Section 1.4.4
Link	Section 4.2.7
Location	Section 4.2.5
Number	Section 1.3
Participant	Section 4.4.5
PatchObject	Section 1.4.8
RecurrenceRule	Section 4.3.2
Relation	Section 1.4.10
SignedDuration	Section 1.4.6
String	Section 1.3
TimeZone	Section 4.7.2
TimeZoneRule	Section 4.7.2
UnsignedInt	Section 1.4.2
UTCDateTime	Section 1.4.3
VirtualLocation	Section 4.2.6

Table 2

8.4. Creation of "JSCalendar Enum Values" Registry

The IANA will create the "JSCalendar Enum Values" registry to allow interoperable extension of semantics for properties with enumerable values. Each such property will have a subregistry of allowed values. The registration process for creating a new subregistry is the same as for the JSCalendar Properties registry. The registration process for a new enum value is the same but is only subject to Expert Review; a specification is not required for a new allowed value in an existing enum property where a simple description will suffice.

8.4.1. JMAP Enum Subregistry Creation Template

This template is for adding a new subregistry to the JMAP Enum registry.

- o Registry Name: This MUST be of the form "Enum Values for {property-name} (Context: {context})" where:

 {property-name} is the name(s) of the property or properties where these values may be used. This MUST be registered in the JSCalendar Properties registry.

 {context} is the list of allowed object types where the property or properties may appear, as registered in the JSCalendar Properties registry. This disambiguates where there may be two distinct properties with the same name in different contexts.
- o Change Controller: ("IETF" for IETF-stream RFCs).
- o Experts: The initial list of experts for Expert Review of updates to the subregistry.
- o Initial Contents: The initial list of defined values for this enum, using the template defined in [Section 8.4.2](#).

8.4.2. JMAP Enum Subregistry Template

This template is for adding a new enum value to a subregistry in the JMAP Enum registry.

- o Enum Value: The verbatim value of the enum.
- o Reference or Description: A brief description or RFC number and section reference for the semantics of this value.

8.4.3. Initial Contents for the JSCalendar Enum Registry

For each subregistry created in this section, all RFC section references are for this document, the change controller is IETF and the experts are Neil Jenkins and Robert Stepanek.

Enum Values for action (Context: Alert)

Enum Value	Reference or Description
display	Section 4.5.2
email	Section 4.5.2

Table 3

Enum Values for display (Context: Link)

Enum Value	Reference or Description
badge	Section 4.2.7
graphic	Section 4.2.7
fullsize	Section 4.2.7
thumbnail	Section 4.2.7

Table 4

Enum Values for freeBusyStatus (Context: JSEvent, JSTask)

Enum Value	Reference or Description
free	Section 4.4.2
busy	Section 4.4.2

Table 5

Enum Values for kind (Context: Participant)

Enum Value	Reference or Description
individual	Section 4.4.5
group	Section 4.4.5
resource	Section 4.4.5
location	Section 4.4.5

Table 6

Enum Values for participationStatus (Context: Participant)

Enum Value	Reference or Description
needs-action	Section 4.4.5
accepted	Section 4.4.5
declined	Section 4.4.5
tentative	Section 4.4.5
delegated	Section 4.4.5

Table 7

Enum Values for privacy (Context: JSEvent, JSTask)

Enum Value	Reference or Description
public	Section 4.4.3
private	Section 4.4.3
secret	Section 4.4.3

Table 8

Enum Values for progress (Context: JSTask, Participant)

Enum Value	Reference or Description
needs-action	Section 5.2.4
in-process	Section 5.2.4
completed	Section 5.2.4
failed	Section 5.2.4
cancelled	Section 5.2.4

Table 9

Enum Values for relation (Context: Relation)

Enum Value	Reference or Description
first	Section 1.4.10
next	Section 1.4.10
child	Section 1.4.10
parent	Section 1.4.10

Table 10

Enum Values for `relativeTo` (Context: `OffsetTrigger`, `Location`)

Enum Value	Reference or Description
start	Section 4.5.2
end	Section 4.5.2

Table 11

Enum Values for `roles` (Context: `Participant`)

Enum Value	Reference or Description
owner	Section 4.4.5
attendee	Section 4.4.5
optional	Section 4.4.5
informational	Section 4.4.5
chair	Section 4.4.5

Table 12

Enum Values for scheduleAgent (Context: Participant)

Enum Value	Reference or Description
server	Section 4.4.5
client	Section 4.4.5
none	Section 4.4.5

Table 13

Enum Values for status (Context: JSEvent)

Enum Value	Reference or Description
confirmed	Section 5.1.3
cancelled	Section 5.1.3
tentative	Section 5.1.3

Table 14

9. Acknowledgments

The authors would like to thank the members of CalConnect for their valuable contributions. This specification originated from the work of the API technical committee of CalConnect, the Calendaring and Scheduling Consortium.

10. References

10.1. Normative References

- [CLDR] "Unicode Common Locale Data Repository",
<<http://cldr.unicode.org/>>.
- [COLORS] "CSS Color Module", <<https://www.w3.org/TR/css-color-3/>>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2392] Levinson, E., "Content-ID and Message-ID Uniform Resource Locators", [RFC 2392](#), DOI 10.17487/RFC2392, August 1998, <<https://www.rfc-editor.org/info/rfc2392>>.
- [RFC2397] Masinter, L., "The "data" URL scheme", [RFC 2397](#), DOI 10.17487/RFC2397, August 1998, <<https://www.rfc-editor.org/info/rfc2397>>.
- [RFC3339] Klyne, G. and C. Newman, "Date and Time on the Internet: Timestamps", [RFC 3339](#), DOI 10.17487/RFC3339, July 2002, <<https://www.rfc-editor.org/info/rfc3339>>.
- [RFC4589] Schulzrinne, H. and H. Tschofenig, "Location Types Registry", [RFC 4589](#), DOI 10.17487/RFC4589, July 2006, <<https://www.rfc-editor.org/info/rfc4589>>.
- [RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", [RFC 4648](#), DOI 10.17487/RFC4648, October 2006, <<https://www.rfc-editor.org/info/rfc4648>>.
- [RFC5545] Desruisseaux, B., Ed., "Internet Calendaring and Scheduling Core Object Specification (iCalendar)", [RFC 5545](#), DOI 10.17487/RFC5545, September 2009, <<https://www.rfc-editor.org/info/rfc5545>>.
- [RFC5646] Phillips, A., Ed. and M. Davis, Ed., "Tags for Identifying Languages", [BCP 47](#), [RFC 5646](#), DOI 10.17487/RFC5646, September 2009, <<https://www.rfc-editor.org/info/rfc5646>>.
- [RFC5870] Mayrhofer, A. and C. Spanring, "A Uniform Resource Identifier for Geographic Locations ('geo' URI)", [RFC 5870](#), DOI 10.17487/RFC5870, June 2010, <<https://www.rfc-editor.org/info/rfc5870>>.
- [RFC6838] Freed, N., Klensin, J., and T. Hansen, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 6838](#), DOI 10.17487/RFC6838, January 2013, <<https://www.rfc-editor.org/info/rfc6838>>.
- [RFC6901] Bryan, P., Ed., Zyp, K., and M. Nottingham, Ed., "JavaScript Object Notation (JSON) Pointer", [RFC 6901](#), DOI 10.17487/RFC6901, April 2013, <<https://www.rfc-editor.org/info/rfc6901>>.

- [RFC7493] Bray, T., Ed., "The I-JSON Message Format", [RFC 7493](#), DOI 10.17487/RFC7493, March 2015, <<https://www.rfc-editor.org/info/rfc7493>>.
- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 8126](#), DOI 10.17487/RFC8126, June 2017, <<https://www.rfc-editor.org/info/rfc8126>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8259] Bray, T., Ed., "The JavaScript Object Notation (JSON) Data Interchange Format", STD 90, [RFC 8259](#), DOI 10.17487/RFC8259, December 2017, <<https://www.rfc-editor.org/info/rfc8259>>.
- [RFC8288] Nottingham, M., "Web Linking", [RFC 8288](#), DOI 10.17487/RFC8288, October 2017, <<https://www.rfc-editor.org/info/rfc8288>>.
- [TZDB] "IANA Time Zone Database", <<https://www.iana.org/time-zones>>.

10.2. Informative References

- [LINKRELS] "IANA Link Relation Types", <<https://www.iana.org/assignments/link-relations/link-relations.xhtml>>.
- [MIME] "IANA Media Types", <<https://www.iana.org/assignments/media-types/media-types.xhtml>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC4122] Leach, P., Mealling, M., and R. Salz, "A Universally Unique IDentifier (UUID) URN Namespace", [RFC 4122](#), DOI 10.17487/RFC4122, July 2005, <<https://www.rfc-editor.org/info/rfc4122>>.

- [RFC4791] Daboo, C., Desruisseaux, B., and L. Dusseault, "Calendaring Extensions to WebDAV (CalDAV)", [RFC 4791](#), DOI 10.17487/RFC4791, March 2007, <<https://www.rfc-editor.org/info/rfc4791>>.
- [RFC5546] Daboo, C., Ed., "iCalendar Transport-Independent Interoperability Protocol (iTIP)", [RFC 5546](#), DOI 10.17487/RFC5546, December 2009, <<https://www.rfc-editor.org/info/rfc5546>>.
- [RFC6047] Melnikov, A., Ed., "iCalendar Message-Based Interoperability Protocol (iMIP)", [RFC 6047](#), DOI 10.17487/RFC6047, December 2010, <<https://www.rfc-editor.org/info/rfc6047>>.
- [RFC7265] Kewisch, P., Daboo, C., and M. Douglass, "jCal: The JSON Format for iCalendar", [RFC 7265](#), DOI 10.17487/RFC7265, May 2014, <<https://www.rfc-editor.org/info/rfc7265>>.
- [RFC7529] Daboo, C. and G. Yakushev, "Non-Gregorian Recurrence Rules in the Internet Calendaring and Scheduling Core Object Specification (iCalendar)", [RFC 7529](#), DOI 10.17487/RFC7529, May 2015, <<https://www.rfc-editor.org/info/rfc7529>>.
- [RFC7808] Douglass, M. and C. Daboo, "Time Zone Data Distribution Service", [RFC 7808](#), DOI 10.17487/RFC7808, March 2016, <<https://www.rfc-editor.org/info/rfc7808>>.
- [RFC7986] Daboo, C., "New Properties for iCalendar", [RFC 7986](#), DOI 10.17487/RFC7986, October 2016, <<https://www.rfc-editor.org/info/rfc7986>>.

Authors' Addresses

Neil Jenkins
Fastmail
PO Box 234
Collins St West
Melbourne VIC 8007
Australia

Email: neilj@fastmailteam.com
URI: <https://www.fastmail.com>

Robert Stepanek
Fastmail
PO Box 234
Collins St West
Melbourne VIC 8007
Australia

Email: rsto@fastmailteam.com

URI: <https://www.fastmail.com>