

INTERNET-DRAFT  
Document: [draft-ietf-calsify-rfc2447bis-11.txt](#)  
Intended status: Standard Track  
Expires: March 2011

A. Melnikov  
Editor  
September 10, 2010

## **iCalendar Message-Based Interoperability Protocol (iMIP)**

### Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#). This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/1id-abstracts.html>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

A revised version of this draft document will be submitted to the RFC editor as a Draft Standard for the Internet Community. Discussion and suggestions for improvement are requested, and should be sent to the CALSIFY Mailing list <[ietf-calsify@osafoundation.org](mailto:ietf-calsify@osafoundation.org)>. Distribution of this document is unlimited.

### Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the BSD License.

#### Abstract

This document, iCalendar Message-Based Interoperability Protocol (iMIP), specifies a binding from the iCalendar Transport-independent Interoperability Protocol (iTIP) to Internet email-based transports. Calendaring entries defined by the iCalendar Object Model (iCalendar) are wrapped using constructs from [RFC 5322](#) and MIME ([RFC 2045](#), [RFC 2046](#), [RFC 2047](#) and [RFC 2049](#)), and then transported over SMTP.



## Table of Contents

<a href="#">1</a>	<a href="#">INTRODUCTION.....</a>	<a href="#">2</a>
<a href="#">1.1</a>	<a href="#">RELATED MEMOS .....</a>	<a href="#">2</a>
<a href="#">1.2</a>	<a href="#">FORMATTING CONVENTIONS .....</a>	<a href="#">3</a>
<a href="#">1.3</a>	<a href="#">TERMINOLOGY .....</a>	<a href="#">4</a>
<a href="#">2</a>	<a href="#">MIME MESSAGE FORMAT BINDING.....</a>	<a href="#">4</a>
<a href="#">2.1</a>	<a href="#">MIME MEDIA TYPE .....</a>	<a href="#">4</a>
<a href="#">2.2</a>	<a href="#">SECURITY .....</a>	<a href="#">4</a>
<a href="#">2.2.1</a>	<a href="#">Authorization .....</a>	<a href="#">4</a>
<a href="#">2.2.2</a>	<a href="#">Authentication .....</a>	<a href="#">5</a>
<a href="#">2.2.3</a>	<a href="#">Confidentiality .....</a>	<a href="#">5</a>
<a href="#">2.3</a>	<a href="#">EMAIL ADDRESSES .....</a>	<a href="#">5</a>
<a href="#">2.4</a>	<a href="#">CONTENT TYPE .....</a>	<a href="#">5</a>
<a href="#">2.5</a>	<a href="#">CONTENT-TRANSFER-ENCODING .....</a>	<a href="#">6</a>
<a href="#">2.6</a>	<a href="#">CONTENT-DISPOSITION .....</a>	<a href="#">6</a>
<a href="#">3</a>	<a href="#">SECURITY CONSIDERATIONS.....</a>	<a href="#">7</a>
<a href="#">4</a>	<a href="#">EXAMPLES.....</a>	<a href="#">8</a>
<a href="#">4.1</a>	<a href="#">SINGLE COMPONENT WITH AN ATTACH PROPERTY .....</a>	<a href="#">8</a>
<a href="#">4.2</a>	<a href="#">USING MULTIPART ALTERNATIVE FOR LOW FIDELITY CLIENTS .....</a>	<a href="#">8</a>
<a href="#">4.3</a>	<a href="#">SINGLE COMPONENT WITH AN ATTACH PROPERTY AND INLINE ATTACHMENT ..</a>	<a href="#">9</a>
<a href="#">4.4</a>	<a href="#">MULTIPLE SIMILAR COMPONENTS .....</a>	<a href="#">10</a>
<a href="#">4.5</a>	<a href="#">MULTIPLE MIXED COMPONENTS .....</a>	<a href="#">11</a>
<a href="#">4.6</a>	<a href="#">DETAILED COMPONENTS WITH AN ATTACH PROPERTY .....</a>	<a href="#">13</a>
<a href="#">5</a>	<a href="#">RECOMMENDED PRACTICES.....</a>	<a href="#">14</a>
<a href="#">5.1</a>	<a href="#">USE OF CONTENT AND MESSAGE IDS .....</a>	<a href="#">14</a>
<a href="#">6</a>	<a href="#">REFERENCES.....</a>	<a href="#">15</a>
<a href="#">7</a>	<a href="#">EDITOR'S ADDRESSES.....</a>	<a href="#">16</a>
<a href="#">8</a>	<a href="#">FULL COPYRIGHT STATEMENT.....</a>	<a href="#">XX</a>
<a href="#">9</a>	<a href="#">INTELLECTUAL PROPERTY.....</a>	<a href="#">XX</a>

## [1](#) Introduction

This binding document provides the transport specific information necessary to convey iCalendar Transport-independent Interoperability Protocol (iTIP) [[iTIP](#)] over Internet email (using MIME) as defined in [[RFC-5322](#)] and [[RFC-2045](#)].

### [1.1](#) Related Memos

Implementers will need to be familiar with several other memos that, along with this memo, form a framework for Internet calendaring and scheduling standards.

This document, [iMIP], specifies an Internet email binding for iTIP.

[iCAL] - specifies a core specification of objects, data types, properties and property parameters;



[iTIP] - specifies an interoperability protocol for scheduling between different implementations;

This memo does not attempt to repeat the specification of concepts or definitions from these other memos. Where possible, references are made to the memo that provides for the specification of these concepts or definitions.

## **1.2 Formatting Conventions**

The mechanisms defined in this memo are defined in prose. In order to refer to elements of the calendaring and scheduling model, core object or interoperability protocol defined in [[iCAL](#)] and [[iTIP](#)] some formatting conventions have been used.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC-2119](#)].

Calendaring and scheduling roles are referred to in quoted-strings of text with the first character of each word in upper case. For example, "Organizer" refers to a role of a "Calendar User" within the scheduling protocol defined by [[iTIP](#)].

Calendar components defined by [[iCAL](#)] are referred to with capitalized, quoted-strings of text. All calendar components start with the letter "V". For example, "VEVENT" refers to the event calendar component, "VTODO" refers to the to-do calendar component and "VJOURNAL" refers to the daily journal calendar component.

Scheduling methods defined by [[iTIP](#)] are referred to with capitalized, quoted-strings of text. For example, "REQUEST" refers to the method for requesting a scheduling calendar component be created or modified, "REPLY" refers to the method a recipient of a request uses to update their status with the "Organizer" of the calendar component.

Properties defined by [[iCAL](#)] are referred to with capitalized, quoted-strings of text, followed by the word "property". For example, "ATTENDEE" property refers to the iCalendar property used to convey the calendar address of a calendar user.

Property parameters defined by [[iCAL](#)] are referred to with lower case, quoted-strings of text, followed by the word "parameter". For example, "value" parameter refers to the iCalendar property parameter used to override the default data type for a property value.



### **1.3 Terminology**

The email terms used in this memo are defined in [[RFC-5322](#)] and [[RFC-2045](#)]. The calendaring and scheduling terms used in this memo are defined in [[iCAL](#)] and [[iTIP](#)].

## **2 MIME Message Format Binding**

This section defines the message binding to the MIME electronic mail transport.

The sections below refer to the "originator" and the "recipient" of an iMIP message. In the case of a "request" method, the originator is the "Organizer" and the recipient is an "Attendee" of the event. In the case of a "response" method, the originator is an "Attendee" and the recipient is the "Organizer" of the event.

The [[RFC-5322](#)] "Reply-To" header field typically contains the email address of the originator of the scheduling message. However, this cannot be guaranteed because the sender of the iMIP message might not be the originator of the scheduling message and the sender's Mail User Agent (MUA) might not enforce iMIP semantics by translating the originator's address into the "Reply-To" email header field.

### **2.1 MIME Media Type**

A MIME entity containing content information formatted according to this document will be referenced as a "text/calendar" content type [[iCAL](#)]. It is assumed that this content type will be transported through a MIME electronic mail transport.

### **2.2 Security**

This section addresses several aspects of security including authentication, authorization and confidentiality. Authentication and confidentiality can be achieved using S/MIME [[RFC-5750](#)][[RFC-5751](#)], which uses Security Multiparts framework for MIME [[RFC-1847](#)].

#### **2.2.1 Authorization**

In [[iTIP](#)] messages, only the "Organizer" is authorized to modify or cancel calendar entries she organizes. That is, spoof@xyz.example.net is not allowed to modify or cancel a meeting that was organized by a@example.com. Furthermore, only the respondent has the authorization to indicate their status to the "Organizer". That is, the "Organizer" MUST ignore an [[iTIP](#)] message from spoof@xyz.example.net that declines a meeting invitation for b@example.com.





Implementations of iMIP SHOULD verify the authenticity of the creator of an iCalendar object before taking any action. Methods for doing this are presented later in this document.

[RFC-1847] Message flow in iTIP supports someone working on behalf of a "Calendar User" through use of the "sent-by" parameter that is associated with the "ATTENDEE" and "ORGANIZER" properties. However, there is no mechanism to verify whether or not a "Calendar User" has authorized someone to work on their behalf. It is left to implementations to provide mechanisms for the "Calendar Users" to make that decision.

### **2.2.2 Authentication**

Authentication MUST be performed using S/MIME [[RFC-5750](#)][RFC-5751]. Authentication is possible only on messages that have been signed. Unauthenticated messages (i.e., unsigned messages) may not be trusted.

### **2.2.3 Confidentiality**

To ensure confidentiality using iMIP implementations SHOULD utilize encryption specified in S/MIME [[RFC-5750](#)][RFC-5751]. iMIP does not restrict a "Calendar User Agent" (CUA) from forwarding iCalendar objects to other users or agents.

## **2.3 Email Addresses**

The calendar address specified within the "ORGANIZER" and "ATTENDEE" properties in an iCalendar object send using iMIP MUST be a proper "mailto:" [[MAILTO](#)] URI specification for the corresponding "Organizer" or "Attendee" of the "VEVENT" or "VTODO".

Because [[iTIP](#)] does not preclude "Attendees" from forwarding "VEVENTS" or "VTODOS" to others, the [[RFC-5322](#)] "Sender" value may not equal that of the "Organizer". Additionally, the "Organizer" or "Attendee" cannot be reliably inferred by the [[RFC-5322](#)] "Sender" or "Reply-to" header field values of an iMIP message. The relevant address MUST be ascertained by opening the "text/calendar" MIME body part and examining the "ATTENDEE" and "ORGANIZER" properties.

## **2.4 Content-Type Header Field**

A MIME body part containing content information that conforms to this document MUST have an [[RFC-2045](#)] "Content-Type" value of "text/calendar". The [[RFC-2045](#)] "Content-Type" header field MUST also include the type MIME parameter "method". The value MUST be the same (ignoring case) as the value of the "METHOD" property within the



iCalendar object.

Note 1: A MIME message containing multiple iCalendar objects with different method values MUST be further encapsulated with a "multipart/mixed" MIME entity [[RFC-2046](#)]. This will allow each of the iCalendar objects to be encapsulated within their own "text/calendar" MIME entity.

Note 2: A MIME body part of "text/calendar" "Content-Type" that lacks the "method" parameter is not considered to be an iMIP body part and thus is not subject to the requirements specified in this document.

Note that according to [[iCAL](#)] the default character set for iCalendar objects is UTF-8 [[UTF-8](#)]. However the default character set for a "text/\*" MIME entity according to [[RFC-2046](#)] is US-ASCII. Thus a "charset" MIME parameter MUST be present if the iCalendar object contains characters that can't be represented in US-ASCII character set and, as specified in [[iCAL](#)], it MUST have the value "UTF-8".

The optional "component" MIME parameter defines the iCalendar component type contained within the iCalendar object.

The following is an example of this header field with a value that indicates an event message.

```
Content-Type: text/calendar; method=request; charset=UTF-8;
             component=vevent
```

The "text/calendar" content type allows for the scheduling message type to be included in a MIME message with other content information (i.e., "multipart/mixed") or included in a MIME message with a clear-text, human-readable form of the scheduling message (i.e., "multipart/alternative" [[RFC-2046](#)]).

In order to permit the information in the scheduling message to be understood by MIME user agents (UA) that do not support the "text/calendar" content type, scheduling messages SHOULD be sent with an alternative, human-readable form of the information.

Note that "multipart/alternative" MUST NOT be used to represent two slightly different iCalendar objects, for example two VEVENT with alternative starting times.

CUAs can use other MIME parameters of the Content-Type header field, as well as a language specified in the Content-Language header field [[RFC-3282](#)], to pick a "text/calendar" part for processing if a "multipart/alternative" MIME message contains more than one "text/calendar" part.



Any receiving UA compliant with this specification MUST be able to process "text/calendar" body parts enclosed within "multipart/\*". Note that a "multipart/mixed" MIME message can include multiple "text/calendar" components. The receiving UA MUST be able to process all of them.

## **2.5 Content-Transfer-Encoding Header Field**

Unless iMIP message is transported over 8-bit clean transport (such as SMTP [[8BITMIME](#)]), a transfer encoding such as quoted-printable or base64 [[RFC-2045](#)] MUST be used for iCalendar objects containing any characters that can't be represented in the US-ASCII character set. For example:

```
From: user1@example.com
To: user2@example.com
Subject: Phone Conference
Mime-Version: 1.0
Date: Wed, 07 May 2008 21:30:25 +0400
Message-ID: <4821E731.5040506@laptop1.example.com>
Content-Type: text/calendar; method=REQUEST; charset=UTF-8
Content-Transfer-Encoding: quoted-printable

BEGIN:VCALENDAR
PRODID:-//Example/ExampleCalendarClient//EN
METHOD:REQUEST
VERSION:2.0
BEGIN:VEVENT
ORGANIZER:mailto:user1@example.com
ATTENDEE;ROLE=CHAIR;PARTSTAT=ACCEPTED:mailto:user1@example.com
ATTENDEE;RSVP=YES;CUTYPE=INDIVIDUAL:mailto:user2@example.com
DTSTAMP:20080507T170000Z
DTSTART:20080701T160000Z
DTEND:20080701T163000Z
SUMMARY:Phone call to discuss your last visit
DESCRIPTION:=D1=82=D1=8B =D0=BA=D0=B0=D0=BA - =D0=B4=D0=BE=D0=
=B2=D0=BE=D0=BB=D0=B5=D0=BD =D0=BF=D0=BE=D0=B5=D0=B7=D0=B4=D0=BA=D0
=BE=D0=B9?
UID:calsvr.example.com-8739701987387998
SEQUENCE:0
STATUS:TENTATIVE
END:VEVENT
END:VCALENDAR
```

## **2.6 Content-Disposition Header Field**

Implementations MAY include a "Content-Disposition" header field to define a file name for an iCalendar object. However, the handling of



a MIME part MUST be based on its [[RFC-2045](#)] "Content-Type" and not on the extension specified in the "Content-Disposition", as different email malware is known to trick User Agents into misinterpreting content of messages by specifying a file extension in the Content-Disposition header field that doesn't correspond to the value of Content-Type header field.



### 3 Security Considerations

The security threats that applications must address when implementing iMIP are detailed in [iMIP]. In particular two spoofing threats are identified in [iMIP]: Spoofing the "Organizer", and Spoofing an "Attendee". To address these threats, the originator of an iCalendar object must be authenticated by a recipient. Once authenticated, a determination can be made as to whether or not the originator is authorized to perform the requested operation. Compliant applications MUST support signing and encrypting text/calendar body parts using a mechanism based on S/MIME [RFC-5750][RFC-5751] in order to facilitate the authentication of the originator of the iCalendar object (see [Section 2.2.2](#) and 2.2.3). The steps for processing a signed iMIP message are described below:

1. Using S/MIME, determine who signed the text/calendar body part containing the iCalendar object. This is the "signer". (Note that the email address of the signer MUST be specified in the rfc822Name field of the subject alternative name extension of the signer certificate, as specified in [\[RFC-5280\]](#), [Section 4.1.2.6](#).) Note that the signer is not necessarily the person sending an e-mail message since an e-mail message can be forwarded.
2. Correlate the signer to either an "ATTENDEE" property or to the "ORGANIZER" property in the iCalendar object, based on the method and the calendar component specified in the iCalendar object, as defined in Section 1.4 of [iMIP]. If the signer cannot be correlated to an "ATTENDEE"/"ORGANIZER" property, then actively warn the user controlling the calendar user agent that the iCalendar object is untrusted and encourage the user to ignore the message, but give advanced users the option to (a) view the certificate of the signer and the entire certificate chain (if any) in order to help decide if the signer should be trusted to send the message, and then (b) allow CUA to accept and process the iCalendar object.
3. Determine whether or not the "ATTENDEE"/"ORGANIZER" is authorized to perform the operation as defined by [iMIP]. If the conditions are not met, ignore the message.
4. If all the above conditions are met, the message can be processed.

S/MIME signing also protects against malicious changes in transit.

If calendar confidentiality is required by the sender, signed iMIP messages SHOULD be encrypted by a mechanism based on S/MIME [RFC-5750][RFC-5751]. If iMIP is used within a single ADMD (Administrative Domain) [RFC5598], SMTP STARTTLS [SMTP-TLS] (together with STARTTLS in IMAP/POP [IMAP-POP-TLS]) MAY alternatively be used



to provide calendar confidentiality.

Once a signed and/or encrypted iMIP message is received and successfully verified (as detailed above) by a CUA, the CUA SHOULD remember whether the sender of the message is using signing and/or encrypting. If an unsigned iMIP message is received from the same sender later on, the receiving CUA SHOULD warn the receiving user about a possible man-in-the-middle attack and SHOULD ignore the message, unless explicitly overridden by the user.

Implementations MAY provide means for users to disable signing and encrypting.

It is possible to receive iMIP messages sent by someone working on behalf of another "Calendar User". This is determined by examining the "sent-by" parameter in the relevant "ORGANIZER" or "ATTENDEE" property. [[iCAL](#)] and [[iTIP](#)] provide no mechanism to verify that a "Calendar User" has authorized someone else to work on their behalf. To address this security issue, implementations MUST provide mechanisms for the "Calendar Users" to make that decision before applying changes from someone working on behalf of a "Calendar User". One way to achieve this is to reject iMIP messages sent by users other than the "ORGANIZER" or the "ATTENDEE"s. Alternatively, the receiver could have a list of trusted <sent-by, organizer> proxies in its local security policy. And yet another way is to prompt the user for confirmation.

iMIP based calendaring is frequently deployed within a single ADMD, with boundary filtering employed to restrict email calendaring flows to be inside the ADMD. This can help in minimizing malicious changes to calendaring messages in transit, as well as in making authorization decisions less risky.

A security consideration associated with use of Content-Disposition header field is described in [section 2.6](#).

Use of S/MIME makes Security Considerations discussed in [[RFC-5750](#)][RFC-5751] relevant to this document. For additional Security Considerations regarding certificate and CRL verification please see [[RFC-5280](#)].



## **4 Examples**

### **4.1 Single Component With An ATTACH Property**

This minimal message shows how an iCalendar object references an attachment. The attachment is accessible via its URL.

```
From: sman@netscape.example.com
To: stevesil@microsoft.example.com
Subject: Phone Conference
Mime-Version: 1.0
Content-Type: text/calendar; method=REQUEST; charset=US-ASCII
Content-Transfer-Encoding: 7bit

BEGIN:VCALENDAR
PRODID:-//Example/ExampleCalendarClient//EN
METHOD:REQUEST
VERSION:2.0
BEGIN:VEVENT
ORGANIZER:mailto:man@netscape.example.com
ATTENDEE;ROLE=CHAIR;PARTSTAT=ACCEPTED:mailto:man@netscape.example.com
ATTENDEE;RSVP=YES:mailto:stevesil@microsoft.example.com
DTSTAMP:19970611T190000Z
DTSTART:19970701T210000Z
DTEND:19970701T230000Z
SUMMARY:Phone Conference
DESCRIPTION:Please review the attached document.
UID:calsvr.example.com-873970198738777
ATTACH:ftp://ftp.bar.example.com/pub/docs/foo.doc
STATUS:CONFIRMED
END:VEVENT
END:VCALENDAR
```

### **4.2 Using Multipart Alternative for Low Fidelity Clients**

This example shows how a client can emit a multipart message that includes both a plain text version as well as the full iCalendar object. Clients that do not support text/calendar will still be capable of rendering the plain text representation.

```
From: foo1@example.com
To: foo2@example.com
Subject: Phone Conference
Mime-Version: 1.0
Content-Type: multipart/alternative;boundary="01BD3665.3AF0D360"

--01BD3665.3AF0D360
Content-Type: text/plain;charset=us-ascii
```



Content-Transfer-Encoding: 7bit

This is an alternative representation of a TEXT/CALENDAR MIME Object

When: 7/1/1997 10:00AM PDT - 7/1/97 10:30AM PDT

Where:

Organizer: foo1@example.com

Summary: Phone Conference

--01BD3665.3AF0D360

Content-Type: text/calendar; method=REQUEST; charset=US-ASCII

Content-Transfer-Encoding: 7bit

BEGIN:VCALENDAR

PRODID:-//Example/ExampleCalendarClient//EN

METHOD:REQUEST

VERSION:2.0

BEGIN:VEVENT

ORGANIZER:mailto:foo1@example.com

ATTENDEE;ROLE=CHAIR;PARTSTAT=ACCEPTED:mailto:foo1@example.com

ATTENDEE;RSVP=YES;CUTYPE=INDIVIDUAL:mailto:foo2@example.com

DTSTAMP:19970611T190000Z

DTSTART:19970701T170000Z

DTEND:19970701T173000Z

SUMMARY:Phone Conference

UID:calsvr.example.com-8739701987387771

SEQUENCE:0

STATUS:CONFIRMED

END:VEVENT

END:VCALENDAR

--01BD3665.3AF0D360

#### **4.3 Single Component With An ATTACH Property**

This example shows how a message containing an iCalendar object references an attached document. The reference is made using a Content-id (CID). Thus, the iCalendar object and the document are packaged in a multipart/related encapsulation.

From: foo1@example.com

To: foo2@example.com

Subject: Phone Conference

Mime-Version: 1.0

Content-Type: multipart/related; boundary="boundary-example-1"

--boundary-example-1

Content-Type: text/calendar; method=REQUEST; charset=US-ASCII





Content-Transfer-Encoding: 7bit  
Content-Disposition: attachment; filename="event.ics"

BEGIN:VCALENDAR  
PRODID:-//Example/ExampleCalendarClient//EN  
METHOD:REQUEST  
VERSION:2.0  
BEGIN:VEVENT  
ORGANIZER:mailto:foo1@example.com  
ATTENDEE;ROLE=CHAIR;PARTSTAT=ACCEPTED:mailto:foo1@example.com  
ATTENDEE;RSVP=YES;CUTYPE=INDIVIDUAL:mailto:foo2@example.com  
DTSTAMP:19970611T190000Z  
DTSTART:19970701T180000Z  
DTEND:19970701T183000Z  
SUMMARY:Phone Conference  
UID:calsvr.example.com-8739701987387771  
ATTACH:cid:123456789@example.com  
SEQUENCE:0  
STATUS:CONFIRMED  
END:VEVENT  
END:VCALENDAR

--boundary-example-1  
Content-Type: application/msword; name="FieldReport.doc"  
Content-Transfer-Encoding: base64  
Content-Disposition: inline; filename="FieldReport.doc"  
Content-ID: <123456789@example.com>

0M8R4KGxGuEAAAAAAAAAAAAAAAAAAGADAP7/CQAGAAAAAAAAAABAAAAA  
AAAAEAAAQAAAAEAAAD+////AAAAEUAAD////////////////////////////////  
...

--boundary-example-1--

#### **4.4 Multiple Similar Components**

Multiple iCalendar components of the same type can be included in the iCalendar object when the METHOD is the same for each component.

From: foo1@example.com  
To: foo2@example.com  
Subject: Summer Company Holidays  
Mime-Version: 1.0  
Content-Type: text/calendar; method=PUBLISH; charset=US-ASCII  
Content-Transfer-Encoding: 7bit  
Content-Disposition: attachment; filename="event.ics"



```
BEGIN:VCALENDAR
PRODID:-//Example/ExampleCalendarClient//EN
METHOD:PUBLISH
VERSION:2.0
BEGIN:VEVENT
ORGANIZER:MAILTO:FOO1@EXAMPLE.COM
DTSTAMP:19970611T150000Z
DTSTART:19970701T150000Z
DTEND:19970701T230000Z
SUMMARY:Company Picnic
DESCRIPTION:Food and drink will be provided
UID:CALSVR.EXAMPLE.COM-873970198738777-1
SEQUENCE:0
STATUS:CONFIRMED
END:VEVENT
BEGIN:VEVENT
ORGANIZER:MAILTO:FOO1@EXAMPLE.COM
DTSTAMP:19970611T190000Z
DTSTART:19970715T150000Z
DTEND:19970715T230000Z
SUMMARY:Company Bowling Tournament
DESCRIPTION:We have 10 lanes reserved
UID:CALSVR.EXAMPLE.COM-873970198738777-2
SEQUENCE:0
STATUS:CONFIRMED
END:VEVENT
END:VCALENDAR
```

#### [4.5](#) Multiple Mixed Components

Different component types must be encapsulated in separate iCalendar objects.

```
From: foo1@example.com
To: foo2@example.com
Subject: Phone Conference
Mime-Version: 1.0
Content-Type: multipart/mixed;boundary="--FEE3790DC7E35189CA67CE2C"
```

This is a multi-part message in MIME format.

```
-----FEE3790DC7E35189CA67CE2C
Content-Type: text/calendar; method=REQUEST; charset=US-ASCII
Content-Transfer-Encoding: 7bit
Content-Disposition: attachment; filename="event1.ics"
```



BEGIN:VCALENDAR  
PRODID:-//Example/ExampleCalendarClient//EN  
METHOD:REQUEST  
VERSION:2.0  
BEGIN:VEVENT  
ORGANIZER:mailto:foo1@example.com  
ATTENDEE;ROLE=CHAIR;PARTSTAT=ACCEPTED:mailto:foo1@example.com  
ATTENDEE;RSVP=YES;CUTYPE=INDIVIDUAL:mailto:foo2@example.com  
DTSTAMP:19970611T190000Z  
DTSTART:19970701T210000Z  
DTEND:19970701T230000Z  
SUMMARY:Phone Conference  
DESCRIPTION:Discuss what happened at the last meeting  
UID:calsvr.example.com-8739701987387772  
SEQUENCE:0  
STATUS:CONFIRMED  
END:VEVENT  
END:VCALENDAR

----FEE3790DC7E35189CA67CE2C  
Content-Type: text/calendar; method=REQUEST; charset=US-ASCII  
Content-Transfer-Encoding: 7bit  
Content-Disposition: attachment; filename="todo1.ics"

BEGIN:VCALENDAR  
PRODID:-//Example/ExampleCalendarClient//EN  
METHOD:REQUEST  
VERSION:2.0  
BEGIN:VTODO  
DUE:19970701T160000Z  
ORGANIZER:mailto:foo1@example.com  
ATTENDEE;ROLE=CHAIR;PARTSTAT=ACCEPTED:mailto:foo1@example.com  
ATTENDEE;RSVP=YES:mailto:foo2@example.com  
SUMMARY:Phone Conference  
DESCRIPTION:Discuss a new location for the company picnic  
UID:calsvr.example.com-td-8739701987387773  
SEQUENCE:0  
STATUS:NEEDS-ACTION  
END:VEVENT  
END:VCALENDAR

----FEE3790DC7E35189CA67CE2C



#### **4.6 Detailed Components With An ATTACH Property**

This example shows the format of a message containing a group meeting between three individuals. The multipart/related encapsulation is used because the iCalendar object contains an ATTACH property that uses a CID to reference the attachment.

```
From: foo1@example.com
MIME-Version: 1.0
To: foo2@example.com,foo3@example.com
Subject: REQUEST - Phone Conference
Content-Type: multipart/related;boundary="--FEE3790DC7E35189CA67CE2C"
```

```
----FEE3790DC7E35189CA67CE2C
Content-Type: multipart/alternative;
        boundary="--00FEE3790DC7E35189CA67CE2C00"
```

```
----00FEE3790DC7E35189CA67CE2C00
Content-Type: text/plain; charset=us-ascii
Content-Transfer-Encoding: 7bit
```

```
When: 7/1/1997 10:00PM PDT- 7/1/97 10:30 PM PDT
Where:
Organizer: foo1@example.com
Summary: Let's discuss the attached document
```

```
----00FEE3790DC7E35189CA67CE2C00

Content-Type: text/calendar; method=REQUEST; charset=US-ASCII;
        Component=vevent
Content-Transfer-Encoding: 7bit
Content-Disposition: attachment; filename="event.ics"
```

```
BEGIN:VCALENDAR
PRODID:-//Example/ExampleCalendarClient//EN
METHOD:REQUEST
VERSION:2.0
BEGIN:VEVENT
ORGANIZER:foo1@example.com
ATTENDEE;ROLE=CHAIR;PARTSTAT=ACCEPTED:foo1@example.com
ATTENDEE;RSVP=YES;CUTYPE=INDIVIDUAL:mailto:foo2@example.com
ATTENDEE;RSVP=YES;CUTYPE=INDIVIDUAL:mailto:foo3@example.com
DTSTAMP:19970611T190000Z
DTSTART:19970621T170000Z
DTEND:19970621T173000Z
SUMMARY:Let's discuss the attached document
UID:calsvr.example.com-873970198738777-8aa
ATTACH:cid:calsvr.example.com-12345aaa
```





SEQUENCE:0  
STATUS:CONFIRMED  
END:VEVENT  
END:VCALENDAR

----00FEE3790DC7E35189CA67CE2C00

----FEE3790DC7E35189CA67CE2C

Content-Type: application/msword; name="FieldReport.doc"  
Content-Transfer-Encoding: base64  
Content-Disposition: inline; filename="FieldReport.doc"  
Content-ID: <calsvr.example.com-12345aaa>

R0lGODdhTAQZAJEAAFVVvd3d3e4AAP///yAAAAATAQZAAAC/5yPOSld60ctNqLs94Xq  
AG4kiW5omm6sq27gvH8kzX9o1y+s73/g8MCoFEovGITCoxKMbyCR16cNSq9YrNarfcrvd  
riIH5LL5jE6rxc3G+v2cguf0uv20z+v38L7/DxgoOKjURnjIIbe3yNjo+AgZWYVIWWl5i  
ZnJY6J

...

----FEE3790DC7E35189CA67CE2C

## 5 Recommended Practices

This section outlines a series of recommended practices when using a messaging transport to exchange iCalendar objects.

### 5.1 Use of Content and Message IDs

The [[iCAL](#)] specification makes frequent use of the URI for data types in properties such as "DESCRIPTION", "ATTACH", "CONTACT" and others. Two forms of URIs are Message ID (MID) and Content ID (CID). These are defined in [[RFC-2392](#)]. Although [[RFC-2392](#)] allows referencing messages or MIME body parts in other MIME entities or stores, it is strongly RECOMMENDED that iMIP implementations include all referenced messages and body parts in a single MIME entity. Simply put, if an iCalendar object contains CID or MID references to other messages or body parts, implementations should ensure that these messages and/or body parts are transmitted with the iCalendar object. If they are not, there is no guarantee that the receiving CUA will have the access or the authorization to view those objects.



## **6 IANA Considerations**

Registration of text/calendar MIME Media Type is done in [iCal].

This document doesn't require any additional actions from IANA.

## **7 References**

### **7.1 Normative References**

[iCAL] Desruisseaux, B., (Ed.), "Internet Calendaring and Scheduling Core Object Specification (iCalendar)", [RFC 5545](#).

[iTIP] Daboo, C., "iCalendar Transport-Independent Interoperability Protocol (iTIP)", [RFC 5546](#).

[RFC-5322] Resnick, P., "Internet Message Format", [RFC 5322](#), October 2008.

[MAILTO] Hoffmann, P., Masinter, L., and J. Zawinski, "The mailto URL scheme", [RFC 2368](#), June 1998.

[RFC-1847] Galvin, J., Murphy, S., Crocker, S. and N. Freed, "Security Multiparts for MIME: Multipart/Signed and Multipart/Encrypted", [RFC 1847](#), October 1995.

[RFC-2045] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) - Part One: Format of Internet Message Bodies", [RFC 2045](#), November 1996.

[RFC-2046] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) - Part Two: Media Types", [RFC 2046](#), November 1996.

[RFC-2392] Levinson, E., "Content-ID and Message-ID Uniform Resource Locators", [RFC 2392](#), August 1998.

[RFC-2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[UTF-8] Yergeau, F., "UTF-8, a transformation format of ISO 10646", STD 63, [RFC 3629](#), November 2003.

[SMTP-TLS] Hoffman, P., "SMTP Service Extension for Secure SMTP over Transport Layer Security", [RFC 3207](#), February 2002.

[IMAP-POP-TLS] Newman, C., "Using TLS with IMAP, POP3 and ACAP", [RFC 2595](#), June 1999.



[RFC-5750] Ramsdell, B. and S. Turner, "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 3.2 Certificate Handling", [RFC 5750](#), January 2010.

[RFC-5751] Ramsdell, B. and S. Turner, "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 3.2 Message Specification", [RFC 5751](#), January 2010.

[RFC-5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R. and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", [RFC 5280](#), May 2008.

## **[7.2](#) Informative References**

[8BITMIME] Klensin, J., Freed, N., Rose, M., Stefferud, E., and D. Crocker, "SMTP Service Extension for 8bit-MIMEtransport", [RFC 1652](#), July 1994.

[RFC5598] Crocker, D., "Internet Mail Architecture", [RFC 5598](#), July 2009.

[RFC-3282] Alvestrand, H., "Content Language Headers", [RFC 3282](#), May 2002.



## **8 Authors' Addresses**

Alexey Melnikov (editor)  
Isode Ltd  
5 Castle Business Village  
36 Station Road  
Hampton, Middlesex TW12 2BX  
UK

Email: [Alexey.Melnikov@isode.com](mailto:Alexey.Melnikov@isode.com)

## **Appendix A. Changes since [RFC 2447](#).**

Updated references. Split them into Normative and Informative.

Updated examples to use example.com/example.net domains.

Corrected usage of [RFC 2119](#) language.

Clarified that charset=UTF-8 is required, unless the calendar can be entirely represented in US-ASCII.

Clarified that 7-bit content transfer encodings should be used unless the calendar object is known to be transferred over 8-bit clean transport.

Clarified that file extension specified in the Content-Disposition header field is not to be used to override the Content-Type MIME type.

Disallow use of "multipart/alternative" for slightly different representations of the same calendar.

Clarified handling of the "method" MIME parameter of the "Content-Type" header field.

Clarified that in an iMIP message an ORGANIZER/ATTENDEE property contains a mailto: URI.

Fixed examples with ATTENDEE property to use "CUTYPE=" instead of "TYPE=".

Clarified that message integrity/confidentiality should be achieved using S/MIME.

Additional examples.

Improved Security Considerations section.

Multiple editorial changes to different sections of the document.

## **Appendix B. Acknowledgements**

<<RFC Editor: feel free to move this section elsewhere.>>

The editor of this document wish to thank Frank Dawson, Steve Mansour and Steve Silverberg, the original authors of [RFC 2447](#), as well as the following individuals who have participated in the drafting, review and discussion of this memo:





Reinhold Kainhofer, Cyrus Daboo, Bernard Desruisseaux, Eliot Lear,  
Peter Saint-Andre.