

Internet-Draft
IETF CAT Working Group
Document: <[draft-ietf-cat-gssv2-javabind-03.txt](#)>

Jack Kabat
ValiCert, Inc.
Mayank Upadhyay
Sun Microsystems, Inc.

October 1999

Generic Security Service API Version 2 : Java bindings

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Abstract

The Generic Security Services Application Program Interface (GSS-API) offers application programmers uniform access to security services atop a variety of underlying cryptographic mechanisms. This document specifies the Java bindings for GSS-API which is described at a language independent conceptual level in [RFC 2078](#) [[GSSAPIv2](#)].

The GSS-API allows a caller application to authenticate a principal identity, to delegate rights to a peer, and to apply security services such as confidentiality and integrity on a per-message basis. Examples of security mechanisms defined for GSS-API are The Simple Public-Key GSS-API Mechanism [[SPKM](#)] and The Kerberos Version 5 GSS-API Mechanism [KERBV5].

Table of Contents

1.	Introduction	6
2.	GSS-API Operational Paradigm	7
3.	Additional Controls	8
3.1.	Delegation	9
3.2.	Mutual Authentication	10
3.3.	Replay and Out-of-Sequence Detection	11
3.4.	Anonymous Authentication	11
3.5.	Confidentiality	12
3.6.	Inter-process Context Transfer	13
3.7.	The Use of Incomplete Contexts	13
4.	Calling Conventions	14
4.1.	Package Name	14
4.2.	Provider Framework	14
4.3.	Integer types	15
4.4.	Opaque Data types	15
4.5.	Strings	15
4.6.	Object Identifiers	16
4.7.	Object Identifier Sets	16
4.8.	Credentials	16
4.9.	Contexts	18
4.10.	Authentication tokens	19
4.11.	Interprocess tokens	19
4.12.	Error Reporting	20
4.12.1.	GSS status codes	20
4.12.2.	Mechanism-specific status codes	22
4.12.3.	Supplementary status codes	22
4.13.	Names	23
4.14.	Channel Bindings	26
4.15.	Stream Objects	27
4.16.	Optional Parameters	27
5.	Introduction to GSS-API Classes and Interfaces	27
5.1.	GSSManager class	28
5.2.	GSSName interface	28
5.3.	GSSCredential interface	29
5.4.	GSSContext interface	30
5.5.	MessageProp class	31
5.6.	GSSException class	31
5.7.	Oid class	32
5.8.	ChannelBinding class	32
6.	Detailed GSS-API Class Description	32
6.1.	public class GSSManager	32
6.1.1.	Example Code	33
6.1.2.	Constructors	33
6.1.3.	setProvider	34
6.1.4.	setProvider	34
6.1.5.	getProvider	35

Expires: May 2000

[Page 2]

6.1.6.	getMechs	35
6.1.7.	getNamesForMech	35
6.1.8.	getMechsForName	36
6.1.9.	createName	36
6.1.10.	createName	36
6.1.11.	createName	37
6.1.12.	createName	38
6.1.13.	createCredential	38
6.1.14.	createCredential	38
6.1.15.	createCredential	39
6.1.16.	createContext	40
6.1.17.	createContext	40
6.1.18.	createContext	41
6.2.	public interface GSSName	41
6.2.1.	Example Code	41
6.2.2.	Static Constants	42
6.2.3.	equals	43
6.2.4.	equals	43
6.2.5.	canonicalize	44
6.2.6.	export	44
6.2.7.	toString	44
6.2.8.	getStringNameType	44
6.2.9.	isAnonymous	45
6.2.10.	isMN	45
6.3.	public interface GSSCredential implements Cloneable	45
6.3.1.	Example Code	46
6.3.2.	Static Constants	47
6.3.3.	dispose	47
6.3.4.	getName	47
6.3.5.	getName	47
6.3.6.	getRemainingLifetime	48
6.3.7.	getRemainingInitLifetime	48
6.3.8.	getRemainingAcceptLifetime	48
6.3.9.	getUsage	49
6.3.10.	getUsage	49
6.3.11.	getMechs	49
6.3.12.	add	49
6.3.13.	equals	50
6.4.	public interface GSSContext	51
6.4.1.	Example Code	52
6.4.2.	Static Constants	53
6.4.3.	initSecContext	54
6.4.3.1.	Example Code	54
6.4.4.	initSecContext	55
6.4.4.1.	Example Code	56
6.4.5.	acceptSecContext	57
6.4.5.1.	Example Code	57
6.4.6.	acceptSecContext	58

Expires: May 2000

[Page 3]

6.4.6.1.	Example Code	59
6.4.7.	isEstablished	59
6.4.8.	dispose	60
6.4.9.	getWrapSizeLimit	60
6.4.10.	wrap	61
6.4.11.	wrap	61
6.4.12.	unwrap	62
6.4.13.	unwrap	63
6.4.14.	getMIC	64
6.4.15.	getMIC	64
6.4.16.	verifyMIC	65
6.4.17.	verifyMIC	66
6.4.18.	export	67
6.4.19.	requestMutualAuth	67
6.4.20.	requestReplayDet	68
6.4.21.	requestSequenceDet	68
6.4.22.	requestCredDeleg	68
6.4.23.	requestAnonymity	69
6.4.24.	requestConf	69
6.4.25.	requestInteg	69
6.4.26.	requestLifetime	69
6.4.27.	setChannelBinding	70
6.4.28.	getCredDelegState	70
6.4.29.	getMutualAuthState	70
6.4.30.	getReplayDetState	70
6.4.31.	getSequenceDetState	71
6.4.32.	getAnonymityState	71
6.4.33.	isTransferable	71
6.4.34.	isProtReady	71
6.4.35.	getConfState	71
6.4.36.	getIntegState	72
6.4.37.	getLifetime	72
6.4.38.	getSrcName	72
6.4.39.	getTargName	72
6.4.40.	getMech	72
6.4.41.	getDelegCred	73
6.4.42.	isInitiator	73
6.5.	public class MessageProp	73
6.5.1.	Constructors	73
6.5.2.	getQOP	74
6.5.3.	getPrivacy	74
6.5.4.	getMinorStatus	74
6.5.5.	getMinorString	74
6.5.6.	setQOP	75
6.5.7.	setPrivacy	75
6.5.8.	isDuplicateToken	75
6.5.9.	isOldToken	75
6.5.10.	isUnseqToken	75

Expires: May 2000

[Page 4]

6.5.11.	isGapToken	75
6.5.12.	setSupplementaryStates	76
6.6.	public class ChannelBinding	76
6.6.1.	Constructors	77
6.6.2.	getInitiatorAddress	77
6.6.3.	getAcceptorAddress	78
6.6.4.	getApplicationData	78
6.6.5.	equals	78
6.7.	public class Oid	78
6.7.1.	Constructors	79
6.7.2.	toString	79
6.7.3.	equals	80
6.7.4.	getDER	80
6.7.5.	containedIn	80
6.8.	public class GSSException extends Exception	80
6.8.1.	Static Constants	81
6.8.2.	Constructors	83
6.8.3.	getMajor	84
6.8.4.	getMinor	84
6.8.5.	getMajorString	84
6.8.6.	getMinorString	84
6.8.7.	setMinor	85
6.8.8.	toString	85
6.8.9.	getMessage	85
7.	Sample Applications	85
7.1.	Simple GSS Context Initiator	86
7.2.	Simple GSS Context Acceptor	90
8.	Acknowledgments	94
9.	Bibliography	95
10.	Author's Address	96

Expires: May 2000

[Page 5]

1. Introduction

This document specifies Java language bindings for the Generic Security Services Application Programming Interface (GSS-API) Version 2. GSS-API Version 2 is described in a language independent format in [RFC 2078](#) [[GSSAPIv2](#)]. The GSS-API allows a caller application to authenticate a principal identity, to delegate rights to a peer, and to apply security services such as confidentiality and integrity on a per-message basis.

This document leverages the work performed by the WG in the area of [RFC 2078](#) [[GSSAPIv2](#)] the C-bindings draft [[GSSAPI-C](#)]. Whenever appropriate, text has been used from the C-bindings document to explain generic concepts and provide direction to the implementors.

The design goals of this API have been to satisfy all the functionality defined in [RFC 2078](#) and to provide these services in an object oriented method. The specification also aims to satisfy the needs of both types of Java application developers, those who would like access to a "system-wide" GSS-API implementation, as well as those who would want to provide their own "custom" implementation.

A "system-wide" implementation is one that is available to all applications in the form of a library package. It may be a standard package in the Java runtime environment (JRE) being used or it may be additionally installed and accessible to any application via the CLASSPATH.

A "custom" implementation of the GSS-API, on the other hand, is one that would, in most cases, be bundled with the application during distribution. It is expected that such an implementation would be meant to provide for some particular need of the application, such as support for some specific mechanism.

The design of this API also aims to provide a flexible framework to add and manage GSS-API mechanisms. GSS-API leverages the JCA provider concept to support the plugability of mechanisms. Mechanisms can be added on a "system-wide" basis, where all users of the framework will have them available. The specification also allows for the addition of mechanisms per-instance the GSS-API.

Lastly, this specification presents an API that will naturally fit within the operation environment of the Java platform. Readers are assumed to be familiar with both the GSS-API and the Java platform.

Expires: May 2000

[Page 6]

2. GSS-API Operational Paradigm

The Generic Security Service Application Programming Interface [[GSSAPIv2](#)] defines a generic security API to calling applications. It allows a communicating application to authenticate the user associated with another application, to delegate rights to another application, and to apply security services such as confidentiality and integrity on a per-message basis.

There are four stages to using GSS-API:

- 1) The application acquires a set of credentials with which it may prove its identity to other processes. The application's credentials vouch for its global identity, which may or may not be related to any local username under which it may be running.
- 2) A pair of communicating applications establish a joint security context using their credentials. The security context encapsulates shared state information, which is required in order that per-message security services may be provided. Examples of state information that might be shared between applications as part of a security context are cryptographic keys, and message sequence numbers. As part of the establishment of a security context, the context initiator is authenticated to the responder, and may require that the responder is authenticated back to the initiator. The initiator may optionally give the responder the right to initiate further security contexts, acting as an agent or delegate of the initiator. This transfer of rights is termed "delegation", and is achieved by creating a set of credentials, similar to those used by the initiating application, but which may be used by the responder.

A GSSContext object is used to establish and maintain the shared information that makes up the security context. Certain GSSContext methods will generate a token, which applications treat as cryptographically protected, opaque data. The caller of such GSSContext method is responsible for transferring the token to the peer application, encapsulated if necessary in an application-to-application protocol. On receipt of such a token, the peer application should pass it to a corresponding GSSContext method which will decode the token and extract the information, updating the security context state information accordingly.

Expires: May 2000

[Page 7]

- 3) Per-message services are invoked on a GSSContext object to apply either:

integrity and data origin authentication, or

confidentiality, integrity and data origin authentication

to application data, which are treated by GSS-API as arbitrary octet-strings. An application transmitting a message that it wishes to protect will call the appropriate GSSContext method (getMIC or wrap) to apply protection, and send the resulting token to the receiving application. The receiver will pass the received token (and, in the case of data protected by getMIC, the accompanying message-data) to the corresponding decoding method of the GSSContext interface (verifyMIC or unwrap) to remove the protection and validate the data.

- 4) At the completion of a communications session (which may extend across several transport connections), each application uses a GSSContext method to invalidate the security context and release any system or cryptographic resources held. Multiple contexts may also be used (either successively or simultaneously) within a single communications association, at the discretion of the applications.

3. Additional Controls

This section discusses the optional services that a context initiator may request of the GSS-API before the context establishment. Each of these services is requested by calling the appropriate mutator method in the GSSContext object before the first call to init is performed. Only the context initiator can request context flags.

The optional services defined are:

Delegation

The (usually temporary) transfer of rights from initiator to acceptor, enabling the acceptor to authenticate itself as an agent of the initiator.

Mutual Authentication

In addition to the initiator authenticating its identity to the

Expires: May 2000

[Page 8]

context acceptor, the context acceptor should also authenticate itself to the initiator.

Replay Detection

In addition to providing message integrity services, GSSContext per-message operations of getMIC and wrap should include message numbering information to enable verifyMIC and unwrap to detect if a message has been duplicated.

Out-of-Sequence Detection

In addition to providing message integrity services, GSSContext per-message operations (getMIC and wrap) should include message sequencing information to enable verifyMIC and unwrap to detect if a message has been received out of sequence.

Anonymous Authentication

The establishment of the security context should not reveal the initiator's identity to the context acceptor.

Some mechanisms may not support all optional services, and some mechanisms may only support some services in conjunction with others. The GSSContext interface offers query methods to allow the verification by the calling application of which services will be available from the context when the establishment phase is complete. In general, if the security mechanism is capable of providing a requested service, it should do so even if additional services must be enabled in order to provide the requested service. If the mechanism is incapable of providing a requested service, it should proceed without the service leaving the application to abort the context establishment process if it considers the requested service to be mandatory.

Some mechanisms may specify that support for some services is optional, and that implementors of the mechanism need not provide it. This is most commonly true of the confidentiality service, often because of legal restrictions on the use of data-encryption, but may apply to any of the services. Such mechanisms are required to send at least one token from acceptor to initiator during context establishment when the initiator indicates a desire to use such a service, so that the initiating GSS-API can correctly indicate whether the service is supported by the acceptor's GSS-API.

3.1. Delegation

The GSS-API allows delegation to be controlled by the initiating application via the requestCredDeleg method before the first call to init has been issued. Some mechanisms do not support delegation, and

Expires: May 2000

[Page 9]

for such mechanisms attempts by an application to enable delegation are ignored.

The acceptor of a security context, for which the initiator enabled delegation, can check if delegation was enabled by using the `getCredDelegState` method of the `GSSContext` interface. In cases when it is, the delegated credential object can be obtained by calling the `getDelegCred` method. The obtained `GSSCredential` object may then be used to initiate subsequent GSS-API security contexts as an agent or delegate of the initiator. If the original initiator's identity is "A" and the delegate's identity is "B", then, depending on the underlying mechanism, the identity embodied by the delegated credential may be either "A" or "B acting for A".

For many mechanisms that support delegation, a simple boolean does not provide enough control. Examples of additional aspects of delegation control that a mechanism might provide to an application are duration of delegation, network addresses from which delegation is valid, and constraints on the tasks that may be performed by a delegate. Such controls are presently outside the scope of the GSS-API. GSS-API implementations supporting mechanisms offering additional controls should provide extension routines that allow these controls to be exercised (perhaps by modifying the initiator's GSS-API credential object prior to its use in establishing a context). However, the simple delegation control provided by GSS-API should always be able to over-ride other mechanism-specific delegation controls. If the application instructs the `GSSContext` object that delegation is not desired, then the implementation must not permit delegation to occur. This is an exception to the general rule that a mechanism may enable services even if they are not requested - delegation may only be provided at the explicit request of the application.

3.2. Mutual Authentication

Usually, a context acceptor will require that a context initiator authenticate itself so that the acceptor may make an access-control decision prior to performing a service for the initiator. In some cases, the initiator may also request that the acceptor authenticate itself. GSS-API allows the initiating application to request this mutual authentication service by calling the `requestMutualAuth` method of the `GSSContext` interface with a "true" parameter before making the first call to `init`. The initiating application is informed as to whether or not the context acceptor has authenticated itself. Note that some mechanisms may not support mutual authentication, and other mechanisms may always perform mutual authentication, whether or not the initiating application requests it. In particular, mutual

Expires: May 2000

[Page 10]

authentication may be required by some mechanisms in order to support replay or out-of-sequence message detection, and for such mechanisms a request for either of these services will automatically enable mutual authentication.

3.3. Replay and Out-of-Sequence Detection

The GSS-API may provide detection of mis-ordered messages once a security context has been established. Protection may be applied to messages by either application, by calling either `getMIC` or `wrap` methods of the `GSSContext` interface, and verified by the peer application by calling `verifyMIC` or `unwrap` for the peer's `GSSContext` object.

The `getMIC` method calculates a cryptographic checksum of an application message, and returns that checksum in a token. The application should pass both the token and the message to the peer application, which presents them to the `verifyMIC` method of the peer's `GSSContext` object.

The `wrap` method calculates a cryptographic checksum of an application message, and places both the checksum and the message inside a single token. The application should pass the token to the peer application, which presents it to the `unwrap` method of the peer's `GSSContext` object to extract the message and verify the checksum.

Either pair of routines may be capable of detecting out-of-sequence message delivery, or duplication of messages. Details of such mis-ordered messages are indicated through supplementary query methods of the `MessageProp` object that is filled in by each of these routines.

A mechanism need not maintain a list of all tokens that have been processed in order to support these status codes. A typical mechanism might retain information about only the most recent "N" tokens processed, allowing it to distinguish duplicates and missing tokens within the most recent "N" messages; the receipt of a token older than the most recent "N" would result in the `isOldToken` method of the instance of `MessageProp` to return "true".

3.4. Anonymous Authentication

In certain situations, an application may wish to initiate the authentication process to authenticate a peer, without revealing its own identity. As an example, consider an application providing access to a database containing medical information, and offering unrestricted access to the service. A client of such a service might

Expires: May 2000

[Page 11]

wish to authenticate the service (in order to establish trust in any information retrieved from it), but might not wish the service to be able to obtain the client's identity (perhaps due to privacy concerns about the specific inquiries, or perhaps simply to avoid being placed on mailing-lists).

In normal use of the GSS-API, the initiator's identity is made available to the acceptor as a result of the context establishment process. However, context initiators may request that their identity not be revealed to the context acceptor. Many mechanisms do not support anonymous authentication, and for such mechanisms the request will not be honored. An authentication token will still be generated, but the application is always informed if a requested service is unavailable, and has the option to abort context establishment if anonymity is valued above the other security services that would require a context to be established.

In addition to informing the application that a context is established anonymously (via the `isAnonymous` method of the `GSSContext` class), the `getSrcName` method of the acceptor's `GSSContext` object will, for such contexts, return a reserved internal-form name, defined by the implementation.

The `toString` method for a `GSSName` object representing an anonymous entity will return a printable name. The returned value will be syntactically distinguishable from any valid principal name supported by the implementation. The associated name-type object identifier will be an oid representing the value of `NT_ANONYMOUS`. This name-type oid will be defined as a public, static `Oid` object of the `GSSName` class. The printable form of an anonymous name should be chosen such that it implies anonymity, since this name may appear in, for example, audit logs. For example, the string "<anonymous>" might be a good choice, if no valid printable names supported by the implementation can begin with "<" and end with ">".

When using the `equal` method of the `GSSName` interface, and one of the operands is a `GSSName` instance representing an anonymous entity, the method must return "false".

3.5. Confidentiality

If a `GSSContext` supports the confidentiality service, `wrap` method may be used to encrypt application messages. Messages are selectively encrypted, under the control of the `setPrivacy` method of the `MessageProp` object used in the `wrap` method.

Expires: May 2000

[Page 12]

3.6. Inter-process Context Transfer

GSS-API V2 provides functionality which allows a security context to be transferred between processes on a single machine. These are implemented using the export method of GSSContext and a byte array constructor of the same class. The most common use for such a feature is a client-server design where the server is implemented as a single process that accepts incoming security contexts, which then launches child processes to deal with the data on these contexts. In such a design, the child processes must have access to the security context object created within the parent so that they can use per-message protection services and delete the security context when the communication session ends.

Since the security context data structure is expected to contain sequencing information, it is impractical in general to share a context between processes. Thus GSSContext interface provides an export method that the process, which currently owns the context, can call to declare that it has no intention to use the context subsequently, and to create an inter-process token containing information needed by the adopting process to successfully re-create the context. After successful completion of export, the original security context is made inaccessible to the calling process by GSS-API and any further usage of this object will result in failures. The originating process transfers the inter-process token to the adopting process, which creates a new GSSContext object using the byte array constructor. The properties of the context are equivalent to that of the original context.

The inter-process token may contain sensitive data from the original security context (including cryptographic keys). Applications using inter-process tokens to transfer security contexts must take appropriate steps to protect these tokens in transit.

Implementations are not required to support the inter-process transfer of security contexts. Calling the `isTransferable` method of the GSSContext interface will indicate if the context object is transferable.

3.7. The Use of Incomplete Contexts

Some mechanisms may allow the per-message services to be used before the context establishment process is complete. For example, a mechanism may include sufficient information in its initial context-level tokens for the context acceptor to immediately decode messages protected with wrap or getMIC. For such a mechanism, the initiating application need not wait until subsequent context-level tokens have

Expires: May 2000

[Page 13]

been sent and received before invoking the per-message protection services.

An application can invoke the `isProtReady` method of the `GSSContext` class to determine if the per-message services are available in advance of complete context establishment. Applications wishing to use per-message protection services on partially-established contexts should query this method before attempting to invoke `wrap` or `getMIC`.

4. Calling Conventions

Java provides the implementors with not just a syntax for the language, but also an operational environment. For example, memory is automatically managed and does not require application intervention. These language features have allowed for a simpler API and have led to the elimination of certain GSS-API functions.

Moreover, the Java Cryptographic Architecture (JCA) defines a provider model which allows an implementation independent access to its security services. Using this model, applications can seamlessly switch between different implementations and dynamically add new services. The GSS-API specification leverages these concepts by the usage of providers for the mechanism implementations.

4.1. Package Name

The classes and interfaces defined in this document reside in the package called "org.ietf.jgss". Applications that wish to make use of this API should import this package name as shows in [section 7](#).

4.2. Provider Framework

The Java security API's use a provider architecture that allows applications to be implementation independent and security API implementations to be modular and extensible. The `java.security.Provider` class is an abstract class that a vendor extends. This class maps various properties that represent different security services that are available to the names of the actual vendor classes that implement those services. When requesting a service, an application simply specifies the desired provider and the API delegates the request to service classes available from that provider.

Expires: May 2000

[Page 14]

Using the Java security provider model insulates applications from implementation details of the services they wish to use. Applications can switch between providers easily and new providers can be added as needed, even at runtime.

The GSS-API may use providers to find components for specific underlying security mechanisms. For instance, a particular provider might contain components that will allow the GSS-API to support the Kerberos v5 mechanism and another might contain components to support the SPKM mechanism. By delegating mechanism specific functionality to the components obtained from providers the GSS-API can be extended to support an arbitrary list of mechanism.

How the GSS-API locates and queries these providers is beyond the scope of this document and is being deferred to a Service Provider Interface (SPI) specification. The availability of such a SPI specification is not mandatory for the adoption of this API specification nor is it mandatory to use providers in the implementation of a GSS-API framework. However, by using the provider framework together with an SPI specification one can create an extensible and implementation independent GSS-API framework.

4.3. Integer types

All numeric values are declared as "int" primitive Java type. The Java specification guarantees that this will be a 32 bit two's complement signed number.

Throughout this API, the "boolean" primitive Java type is used wherever a boolean value is required or returned.

4.4. Opaque Data types

Java byte arrays are used to represent opaque data types which are consumed and produced by the GSS-API in the forms of tokens. Java arrays contain a length field which enables the users to easily determine their size. The language has automatic garbage collection which alleviates the need by developers to release memory and simplifies buffer ownership issues.

4.5. Strings

The String object will be used to represent all textual data. The Java String object, transparently treats all characters as two-byte Unicode characters which allows support for many locals. All

Expires: May 2000

[Page 15]

routines returning or accepting textual data will use the String object.

4.6. Object Identifiers

An Oid object will be used to represent Universal Object Identifiers (Oids). Oids are ISO-defined, hierarchically globally-interpretable identifiers used within the GSS-API framework to identify security mechanisms and name formats. The Oid object can be created from a string representation of its dot notation (e.g. "1.3.6.1.5.6.2") as well as from its ASN.1 DER encoding. Methods are also provided to test equality and provide the DER representation for the object.

An important feature of the Oid class is that its instances are immutable - i.e. there are no methods defined that allow one to change the contents of an Oid. This property allows one to treat these objects as "statics" without the need to perform copies.

Certain routines allow the usage of a default oid. A "null" value can be used in those cases.

4.7. Object Identifier Sets

The Java bindings represents object identifiers sets as arrays of Oid objects. All Java arrays contain a length field which allows for easy manipulation and reference.

In order to support the full functionality of [RFC 2078](#), the Oid class includes a method which checks for existence of an Oid object within a specified array. This is equivalent in functionality to `gss_test_oid_set_member`. The use of Java arrays and Java's automatic garbage collection has eliminated the need for the following routines: `gss_create_empty_oid_set`, `gss_release_oid_set`, and `gss_add_oid_set_member`. Java GSS-API implementations will not contain them. Java's automatic garbage collection and the immutable property of the Oid object eliminates the complicated memory management issues of the C counterpart.

When ever a default value for an Object Identifier Set is required, a "null" value can be used. Please consult the detailed method description for details.

4.8. Credentials

GSS-API credentials are represented by the `GSSCredential` interface.

Expires: May 2000

[Page 16]

The interface contains several constructs to allow for the creation of most common credential objects for the initiator and the acceptor. Comparisons are performed using the interface's "equals" method. The following general description of GSS-API credentials is included from the C-bindings specification:

GSS-API credentials can contain mechanism-specific principal authentication data for multiple mechanisms. A GSS-API credential is composed of a set of credential-elements, each of which is applicable to a single mechanism. A credential may contain at most one credential-element for each supported mechanism. A credential-element identifies the data needed by a single mechanism to authenticate a single principal, and conceptually contains two credential-references that describe the actual mechanism-specific authentication data, one to be used by GSS-API for initiating contexts, and one to be used for accepting contexts. For mechanisms that do not distinguish between acceptor and initiator credentials, both references would point to the same underlying mechanism-specific authentication data.

Credentials describe a set of mechanism-specific principals, and give their holder the ability to act as any of those principals. All principal identities asserted by a single GSS-API credential should belong to the same entity, although enforcement of this property is an implementation-specific matter. A single GSSCredential object represents all the credential elements that have been acquired.

The creation's of an GSSContext object allows the value of "null" to be specified as the GSSCredential input parameter. This will indicate a desire by the application to act as a default principal. While individual GSS-API implementations are free to determine such default behavior as appropriate to the mechanism, the following default behavior by these routines is recommended for portability:

For the initiator side of the context:

- 1) If there is only a single principal capable of initiating security contexts for the chosen mechanism that the application is authorized to act on behalf of, then that principal shall be used, otherwise
- 2) If the platform maintains a concept of a default network-identity for the chosen mechanism, and if the application is authorized to act on behalf of that identity for the purpose of initiating security contexts, then the principal corresponding to that identity shall be used, otherwise
- 3) If the platform maintains a concept of a default local

Expires: May 2000

[Page 17]

identity, and provides a means to map local identities into network-identities for the chosen mechanism, and if the application is authorized to act on behalf of the network-identity image of the default local identity for the purpose of initiating security contexts using the chosen mechanism, then the principal corresponding to that identity shall be used, otherwise

- 4) A user-configurable default identity should be used.

and for the acceptor side of the context

- 1) If there is only a single authorized principal identity capable of accepting security contexts for the chosen mechanism, then that principal shall be used, otherwise
- 2) If the mechanism can determine the identity of the target principal by examining the context-establishment token processed during the accept method, and if the accepting application is authorized to act as that principal for the purpose of accepting security contexts using the chosen mechanism, then that principal identity shall be used, otherwise
- 3) If the mechanism supports context acceptance by any principal, and if mutual authentication was not requested, any principal that the application is authorized to accept security contexts under using the chosen mechanism may be used, otherwise
- 4) A user-configurable default identity shall be used.

The purpose of the above rules is to allow security contexts to be established by both initiator and acceptor using the default behavior whenever possible. Applications requesting default behavior are likely to be more portable across mechanisms and implementations than ones that instantiate an `GSSCredential` object representing a specific identity.

4.9. Contexts

The `GSSContext` interface is used to represent one end of a GSS-API security context, storing state information appropriate to that end of the peer communication, including cryptographic state information.

Expires: May 2000

[Page 18]

The instantiation of the context object is done differently by the initiator and the acceptor. After the context has been instantiated, the initiator may choose to set various context options which will determine the characteristics of the desired security context. When all the application desired characteristics have been set, the initiator will call the `initSecContext` method which will produce a token for consumption by the peer's `acceptSecContext` method. It is the responsibility of the application to deliver the authentication token(s) between the peer applications for processing. Upon completion of the context establishment phase, context attributes can be retrieved, by both the initiator and acceptor, using the accessor methods. These will reflect the actual attributes of the established context. At this point the context can be used by the application to apply cryptographic services to its data.

4.10. Authentication tokens

A token is a caller-opaque type that GSS-API uses to maintain synchronization between each end of the GSS-API security context. The token is a cryptographically protected octet-string, generated by the underlying mechanism at one end of a GSS-API security context for use by the peer mechanism at the other end. Encapsulation (if required) within the application protocol and transfer of the token are the responsibility of the peer applications.

Java GSS-API uses byte arrays to represent authentication tokens. Overloaded methods exist which allow the caller to supply input and output streams which will be used for the reading and writing of the token data.

4.11. Interprocess tokens

Certain GSS-API routines are intended to transfer data between processes in multi-process programs. These routines use a caller-opaque octet-string, generated by the GSS-API in one process for use by the GSS-API in another process. The calling application is responsible for transferring such tokens between processes. Note that, while GSS-API implementors are encouraged to avoid placing sensitive information within interprocess tokens, or to cryptographically protect them, many implementations will be unable to avoid placing key material or other sensitive data within them. It is the application's responsibility to ensure that interprocess tokens are protected in transit, and transferred only to processes that are trustworthy. An interprocess token is represented using a byte array emitted from the `export` method of the `GSSContext` interface. The receiver of the interprocess token would initialize

Expires: May 2000

[Page 19]

an GSSContext object with this token to create a new context. Once a context has been exported, the GSSContext object is invalidated and is no longer available.

4.12. Error Reporting

[RFC 2078](#) defined the usage of major and minor status values for signaling of GSS-API errors. The major code, also called GSS status code, is used to signal errors at the GSS-API level independent of the underlying mechanism(s). The minor status value or Mechanism status code, is a mechanism defined error value indicating a mechanism specific error code.

Java GSS-API uses exceptions implemented by the GSSException class to signal both minor and major error values. Both, mechanism specific errors and GSS-API level errors are signaled through instances of this class. The usage of exceptions replaces the need for major and minor codes to be used within the API calls. GSSException class also contains methods to obtain textual representations for both the major and minor values, which is equivalent to the functionality of `gss_display_status`.

4.12.1. GSS status codes

GSS status codes indicate errors that are independent of the underlying mechanism(s) used to provide the security service. The errors that can be indicated via a GSS status code are generic API routine errors (errors that are defined in the GSS-API specification). These bindings take advantage of the Java exceptions mechanism, thus eliminating the need for calling errors.

A GSS status code indicates a single fatal generic API error from the routine that has thrown the GSSException. Using exceptions announces that a fatal error has occurred during the execution of the method. The GSS-API operational model also allows for the signaling of supplementary status information from the per-message calls. These need to be handled as return values since using exceptions is not appropriate for informatory or warning-like information. The methods that are capable of producing supplementary information are the two per-message methods `GSSContext.verifyMIC()` and `GSSContext.unwrap()`. These methods fill the supplementary status codes in the `MessageProp` object that was passed in.

GSSException object, along with providing the functionality for setting of the various error codes and translating them into textual representation, also contains the definitions of all the numeric

Expires: May 2000

[Page 20]

error values. The following table lists the definitions of error codes:

Table: GSS Status Codes

Name	Value	Meaning
BAD_MECH	1	An unsupported mechanism was requested.
BAD_NAME	2	An invalid name was supplied.
BAD_NAMETYPE	3	A supplied name was of an unsupported type.
BAD_BINDINGS	4	Incorrect channel bindings were supplied.
BAD_STATUS	5	An invalid status code was supplied.
BAD_MIC	6	A token had an invalid MIC.
NO_CRED	7	No credentials were supplied, or the credentials were unavailable or inaccessible.
NO_CONTEXT	8	Invalid context has been supplied.
DEFECTIVE_TOKEN	9	A supplied token was invalid.
DEFECTIVE_CREDENTIAL	10	A supplied credential was invalid.
CREDENTIALS_EXPIRED	11	The referenced credentials have expired.
CONTEXT_EXPIRED	12	The context has expired.
FAILURE	13	Miscellaneous failure, unspecified at the GSS-API level.
BAD_QOP	14	The quality-of-protection requested could not be provided.
UNAUTHORIZED	15	The operation is forbidden by

Expires: May 2000

[Page 21]

		local security policy.
UNAVAILABLE	16	The operation or option is unavailable.
DUPLICATE_ELEMENT	17	The requested credential element already exists.
NAME_NOT_MN	18	The provided name was not a mechanism name.
OLD_TOKEN	19	The token's validity period has expired.
DUPLICATE_TOKEN	20	The token was a duplicate of an earlier version.

The GSS major status code of FAILURE is used to indicate that the underlying mechanism detected an error for which no specific GSS status code is defined. The mechanism-specific status code can provide more details about the error.

4.12.2. Mechanism-specific status codes

Mechanism-specific status codes are communicated in two ways, they are part of any GSSException thrown from the mechanism specific layer to signal a fatal error, or they are part of the MessageProp object that the per-message calls use to signal non-fatal errors.

A default value of 0 in either the GSSException object or the MessageProp object will be used to represent the absence of any mechanism specific status code.

4.12.3. Supplementary status codes

Supplementary status codes are confined to the per-message methods of the GSSContext interface. Because of the informative nature of these errors it is not appropriate to use exceptions to signal them. Instead, the per-message operations of the GSSContext interface return these values in a MessageProp object.

The MessageProp class defines query methods which return boolean values indicating the following supplementary states:

Expires: May 2000

[Page 22]

Table: Supplementary Status Methods

Method Name	Meaning when "true" is returned
isDuplicateToken	The token was a duplicate of an earlier token.
isOldToken	The token's validity period has expired.
isUnseqToken	A later token has already been processed.
isGapToken	An expected per-message token was not received.

"true" return value for any of the above methods indicates that the token exhibited the specified property. The application must determine the appropriate course of action for these supplementary values. They are not treated as errors by the GSS-API.

[4.13.](#) Names

A name is used to identify a person or entity. GSS-API authenticates the relationship between a name and the entity claiming the name.

Since different authentication mechanisms may employ different namespaces for identifying their principals, GSS-API's naming support is necessarily complex in multi-mechanism environments (or even in some single-mechanism environments where the underlying mechanism supports multiple namespaces).

Two distinct conceptual representations are defined for names:

- 1) A GSS-API form represented by implementations of the GSSName interface: A single GSSName object may contain multiple names from different namespaces, but all names should refer to the same entity. An example of such an internal name would be the name returned from a call to the getName method of the GSSCredential interface, when applied to a credential containing credential elements for multiple authentication mechanisms employing different namespaces. This GSSName object will contain a distinct name for the entity for each authentication mechanism.

Expires: May 2000

[Page 23]

For GSS-API implementations supporting multiple namespaces, GSSName implementations must contain sufficient information to determine the namespace to which each primitive name belongs.

- 2) Mechanism-specific contiguous byte array and string forms:
Different GSSName initialization methods are provided to handle both byte array and string formats and to accommodate various calling applications and name types. These formats are capable of containing only a single name (from a single namespace). Contiguous string names are always accompanied by an object identifier specifying the namespace to which the name belongs, and their format is dependent on the authentication mechanism that employs that name. The string name forms are assumed to be printable, and may therefore be used by GSS-API applications for communication with their users. The byte array name formats are assumed to be in non-printable formats (e.g. the byte array returned from the export method of the GSSName interface).

An GSSName object can be converted to a contiguous representation by using the toString method. This will guarantee that the name will be converted to a printable format. Different initialization methods in the GSSName interface are defined allowing support for multiple syntaxes for each supported namespace, and allowing users the freedom to choose a preferred name representation. The toString method should use an implementation-chosen printable syntax for each supported name-type. To obtain the printable name type, getStringNameType method can be used.

There is no guarantee that calling the toString method on the GSSName interface will produce the same string form as the original imported string name. Furthermore, it is possible that the name was not even constructed from a string representation. The same applies to namespace identifiers which may not necessarily survive unchanged after a journey through the internal name-form. An example of this might be a mechanism that authenticates X.500 names, but provides an algorithmic mapping of Internet DNS names into X.500. That mechanism's implementation of GSSName might, when presented with a DNS name, generate an internal name that contained both the original DNS name and the equivalent X.500 name. Alternatively, it might only store the X.500 name. In the latter case, the toString method of GSSName would most likely generate a printable X.500 name, rather than the original DNS name.

The context acceptor can obtain an GSSName object representing the entity performing the context initiation (through the usage of getSrcName method). Since this name has been authenticated by a single mechanism, it contains only a single name (even if the internal name presented by the context initiator to the GSSContext

Expires: May 2000

[Page 24]

object had multiple components). Such names are termed internal mechanism names, or "MN"s and the names emitted by GSSContext interface in the `getSrcName` and `getTargName` are always of this type. Since some applications may require MNs without wanting to incur the overhead of an authentication operation, creation methods are provided that take not only the name buffer and name type, but also the mechanism oid for which this name should be created. When dealing with an existing GSSName object, the `canonicalize` method may be invoked to convert a general internal name into an MN.

GSSName objects can be compared using their `equal` method, which returns "true" if the two names being compared refer to the same entity. This is the preferred way to perform name comparisons instead of using the printable names that a given GSS-API implementation may support. Since GSS-API assumes that all primitive names contained within a given internal name refer to the same entity, `equal` can return "true" if the two names have at least one primitive name in common. If the implementation embodies knowledge of equivalence relationships between names taken from different namespaces, this knowledge may also allow successful comparisons of internal names containing no overlapping primitive elements.

When used in large access control lists, the overhead of creating an GSSName object on each name and invoking the `equal` method on each name from the ACL may be prohibitive. As an alternative way of supporting this case, GSS-API defines a special form of the contiguous byte array name which may be compared directly (byte by byte). Contiguous names suitable for comparison are generated by the `export` method. Exported names may be re-imported by using the byte array constructor and specifying the `NT_EXPORT_NAME` as the name type object identifier. The resulting GSSName name will also be a MN. The GSSName interface defines public static `Oid` objects representing the standard name types. Structurally, an exported name object consists of a header containing an OID identifying the mechanism that authenticated the name, and a trailer containing the name itself, where the syntax of the trailer is defined by the individual mechanism specification. Detailed description of the format is specified in the language-independent GSS-API specification [\[GSSAPIV2\]](#).

Note that the results obtained by using the `equals` method will in general be different from those obtained by invoking `canonicalize` and `export`, and then comparing the byte array output. The first series of operation determines whether two (unauthenticated) names identify the same principal; the second whether a particular mechanism would authenticate them as the same principal. These two operations will in general give the same results only for MNs.

Expires: May 2000

[Page 25]

It is important to note that the above are guidelines as how GSSName implementations should behave, and are not intended to be specific requirements of how names objects must be implemented. The mechanism designers are free to decide on the details of their implementations of the GSSName interface as long as the behavior satisfies the above guidelines.

4.14. Channel Bindings

GSS-API supports the use of user-specified tags to identify a given context to the peer application. These tags are intended to be used to identify the particular communications channel that carries the context. Channel bindings are communicated to the GSS-API using the ChannelBinding object. The application may use byte arrays to specify the application data to be used in the channel binding as well as using instances of the InetAddress. The InetAddress for the initiator and/or acceptor can be used within an instance of a ChannelBinding. ChannelBinding can be set for the GSSContext object using the setChannelBinding method before the first call to init or accept has been performed. Unless the setChannelBinding method has been used to set the ChannelBinding for an GSSContext object, "null" ChannelBinding will be assumed. InetAddress is currently the only address type defined within the Java platform and as such, it is the only one supported within the ChannelBinding class. Applications that use other types of addresses can include them as part of the application specific data.

Conceptually, the GSS-API concatenates the initiator and acceptor address information, and the application supplied byte array to form an octet string. The mechanism calculates a MIC over this octet string and binds the MIC to the context establishment token emitted by init method of the GSSContext interface. The same bindings are set by the context acceptor for its GSSContext object and during processing of the accept method a MIC is calculated in the same way. The calculated MIC is compared with that found in the token, and if the MICs differ, accept will throw a GSSEException with the major code set to BAD_BINDINGS, and the context will not be established. Some mechanisms may include the actual channel binding data in the token (rather than just a MIC); applications should therefore not use confidential data as channel-binding components.

Individual mechanisms may impose additional constraints on addresses that may appear in channel bindings. For example, a mechanism may verify that the initiator address field of the channel binding contains the correct network address of the host system. Portable applications should therefore ensure that they either provide correct information for the address fields, or omit setting of the addressing

Expires: May 2000

[Page 26]

information.

[4.15.](#) Stream Objects

The context object provides overloaded methods which use input and output streams as the means to convey authentication and per-message GSS-API tokens. It is important to note that the streams are expected to contain the usual GSS-API tokens which would otherwise be handled through the usage of byte arrays. The tokens are expected to have a definite start and an end. The callers are responsible for ensuring that the supplied streams will not block, or expect to block until a full token is processed by the GSS-API method. Only a single GSS-API token will be processed per invocation of the stream based method.

The usage of streams allows the callers to have control and management of the supplied buffers. Because streams are non-primitive objects, the callers can make the streams as complicated or as simple as desired simply by using the streams defined in the `java.io` package or creating their own through the use of inheritance. This will allow for the application's greatest flexibility.

[4.16.](#) Optional Parameters

Whenever the application wishes to omit an optional parameter the "null" value shall be used. The detailed method descriptions indicate which parameters are optional. Methods overloading has also been used as a technique to indicate default parameters.

[5.](#) Introduction to GSS-API Classes and Interfaces

This section presents a brief description of the classes and interfaces that constitute the GSS-API. The implementations of these are obtained from the CLASSPATH defined by the application. If Java GSS becomes part of the standard Java API's then these classes will be available by default on all systems as part of the JRE's system classes.

This section also shows the corresponding [RFC 2078](#) functionality implemented by each of the classes. Detailed description of these classes and their methods is presented in [section 6](#).

Expires: May 2000

[Page 27]

5.1. GSSManager class

This class serves as a factory to instantiate implementations of the GSS-API interfaces and also provides methods to make queries about underlying security mechanisms. How this class locates and communicates with components from the underlying security mechanisms is outside the scope of this document, but may be specified in whatever SPI the GSSManager implementation follows.

Applications that desire to provide their own implementation of the GSSManager class can simply extend the standard GSSManager class and instantiate the new subclass. However, it is recommended that rather than replacing the implementation, they enable the existing implementation to support their needs by providing the necessary components via the SPI that it follows.

This class contains equivalents of the following [RFC 2078](#) routines:

RFC 2078 Routine	Function	Section
<code>gss_import_name</code>	Create an internal name from the supplied information.	6.1.9-6.1.12
<code>gss_acquire_cred</code>	Acquire credential for use.	6.1.13-6.1.15
<code>gss_import_sec_context</code>	Create a previously exported context.	6.1.18
<code>gss_indicate_mechs</code>	List the mechanisms supported by this GSS-API implementation.	6.1.6
<code>gss_inquire_mechs_for_name</code>	List the mechanisms supporting the specified name type.	6.1.8
<code>gss_inquire_names_for_mech</code>	List the name types supported by the specified mechanism.	6.1.7

5.2. GSSName interface

GSS-API names are represented in the Java bindings through the

Expires: May 2000

[Page 28]

GSSName interface. Different name formats and their definitions are identified with universal Object Identifiers (oids). The format of the names can be derived based on the unique oid of each name type. The following GSS-API routines are provided by the GSSName interface:

RFC 2078 Routine	Function	Section(s)
<code>gss_display_name</code>	Covert internal name representation to text format.	6.2.7
<code>gss_compare_name</code>	Compare two internal names.	6.2.3, 6.2.4
<code>gss_release_name</code>	Release resources associated with the internal name.	N/A
<code>gss_canonicalize_name</code>	Convert an internal name to a mechanism name.	6.1.11,
<code>gss_export_name</code>	Convert a mechanism name to export format.	6.2.6
<code>gss_duplicate_name</code>	Create a copy of the internal name.	N/A

The `gss_release_name` call is not provided as Java does its own garbage collection. The `gss_duplicate_name` call is also redundant; the GSSName interface has no mutator methods that can change the state of the object so it is safe for sharing.

[5.3.](#) GSSCredential interface

The GSSCredential interface is responsible for the encapsulation of GSS-API credentials. Credentials identify a single entity and provide the necessary cryptographic information to enable the creation of a context on behalf of that entity. A single credential may contain multiple mechanism specific credentials, each referred to as a credential element. The GSSCredential interface provides the functionality of the following GSS-API routines:

RFC 2078 Routine	Function	Section(s)
<code>gss_add_cred</code>	Constructs credentials incrementally.	6.3.12

Expires: May 2000

[Page 29]

<code>gss_inquire_cred</code>	Obtain information about credential.	6.3.4, 6.3.5
<code>gss_inquire_cred_by_mech</code>	Obtain per-mechanism information about a credential.	6.3.5-6.3.10
<code>gss_release_cred</code>	Disposes of credentials after use.	6.3.3

5.4. GSSContext interface

This interface encapsulates the functionality of context-level calls required for security context establishment and management between peers as well as the per-message services offered to applications. A context is established between a pair of peers and allows the usage of security services on a per-message basis on application data. It is created over a single security mechanism. The GSSContext interface provides the functionality of the following GSS-API routines:

RFC 2078 Routine	Function	Section(s)
<code>gss_init_sec_context</code>	Initiate the creation of a security context with a peer.	6.4.3, 6.4.4
<code>gss_accept_sec_context</code>	Accept a security context initiated by a peer.	6.4.5, 6.4.6
<code>gss_delete_sec_context</code>	Destroy a security context.	6.4.8
<code>gss_context_time</code>	Obtain remaining context time.	6.4.37
<code>gss_inquire_context</code>	Obtain context characteristics.	6.4.29 to 6.3.42
<code>gss_wrap_size_limit</code>	Determine token-size limit for <code>gss_wrap</code> .	6.4.9
<code>gss_export_sec_context</code>	Transfer security context to another process.	6.4.18

Expires: May 2000

[Page 30]

<code>gss_get_mic</code>	Calculate a cryptographic Message Integrity Code (MIC) for a message.	6.4.14, 6.4.15
<code>gss_verify_mic</code>	Verify integrity on a received message.	6.4.16, 6.4.17
<code>gss_wrap</code>	Attach a MIC to a message and optionally encrypt the message content.	6.4.10, 6.4.11
<code>gss_unwrap</code>	Obtain a previously wrapped application message verifying its integrity and optionally decrypting it.	6.4.12, 6.4.13

The functionality offered by the `gss_process_context_token` routine has not been included in the Java bindings specification. The corresponding functionality of `gss_delete_sec_context` has also been modified to not return any peer tokens. This has been proposed in accordance to the recommendations stated in the [RFC 2078](#) update draft. `GSSContext` does offer the functionality of destroying the locally-stored context information.

[5.5.](#) MessageProp class

This helper class is used in the per-message operations on the context. An instance of this class is created by the application and then passed into the per-message calls. In some cases, the application conveys information to the GSS-API implementation through this object and in other cases the GSS-API returns information to the application by setting it in this object. See the description of the per-message operations `wrap`, `unwrap`, `getMIC`, and `verifyMIC` in the `GSSContext` interfaces for details.

[5.6.](#) GSSException class

Exceptions are used in the Java bindings to signal fatal errors to the calling applications. This replaces the major and minor codes used in the C-bindings specification as a method of signaling failures. The `GSSException` class handles both minor and major codes, as well as their translation into textual representation. All GSS-API methods are declared as throwing this exception.

Expires: May 2000

[Page 31]

RFC 2078 Routine	Function	Section
<code>gss_display_status</code>	Retrieve textual representation of error codes.	6.8.5, 6.8.6, 6.8.8, 6.8.9

[5.7.](#) **Oid class**

This utility class is used to represent Universal Object Identifiers and their associated operations. GSS-API uses object identifiers to distinguish between security mechanisms and name types. This class, aside from being used whenever an object identifier is needed, implements the following GSS-API functionality:

RFC 2078 Routine	Function	Section
<code>gss_test_oid_set_member</code>	Determine if the specified oid is part of a set of oids.	6.7.5

[5.8.](#) **ChannelBinding class**

An instance of this class is used to specify channel binding information to the GSSContext object before the start of a security context establishment. The application may use a byte array to specify application data to be used in the channel binding as well as use instances of the `InetAddress`. `InetAddress` is currently the only address type defined within the Java platform and as such, it is the only one supported within the `ChannelBinding` class. Applications that use other types of addresses can include them as part of the application data.

[6.](#) **Detailed GSS-API Class Description**

This section lists a detailed description of all the public methods that each of the GSS-API classes and interfaces must provide.

[6.1.](#) **public class GSSManager**

The `GSSManager` is a concrete class that serves as a factory for three GSS interfaces: `GSSName`, `GSSCredential`, and `GSSContext`. It also

Expires: May 2000

[Page 32]

provides methods for applications to determine what mechanisms are available on the system and what nametypes these mechanisms support.

The GSSManager class may be internally implemented as a modular provider based layer that follows some service provider specification to lookup underlying mechanism components. It provides the application with a method to set a preferred provider for any given mechanism.

6.1.1. Example Code

```
GSSManager mgr = new GSSManager();

// What mechs are available to us?
Oid[] supportedMechs = mgr.getMechs();

// Set a preference for the provider to be used when support is need
// for the mechanisms "1.2.840.113554.1.2.2" and "1.3.6.1.5.5.2".
// Assume this provider (called "Sun") has already been installed on
// the system.

Oid krb = new Oid("1.2.840.113554.1.2.2");
Oid spnego = new Oid("1.3.6.1.5.5.2");

mgr.setProvider(krb, "Sun");
mgr.setProvider(spnego, "Sun");

// Add support for a new mechanism "1.3.6.1.5.5.1.1" that is
// available from a specific provider being bundled with the
// application.

Oid spkm1 = new Oid("1.3.6.1.5.5.1.1");

Provider prov = (Provider) (new com.foo.security.Provider());

mgr.setProvider(spkm1, prov);

// What name types does this spkm implementation support?
Oid[] nameTypes = mgr.getNamesForMech(spkm1);
```

6.1.2. Constructors

```
public GSSManager()
```


Expires: May 2000

[Page 33]

Constructor which instantiates a GSSManager for the application.

6.1.3. setProvider

```
public void setProvider(Ord mech, String provName)
    throws GSSEException, java.security.NoSuchProviderException
```

Sets the provider for the GSS-API to use internally when it needs components to support the indicated mechanism.

If the GSSManager implementation does not support an SPI with a pluggable provider architecture it should throw a GSSEException with the status code GSSEException.UNAVAILABLE to indicate that the operation is unavailable. If the requested provider does not support the indicated mech then it should throw a GSSEException with the status code GSSEException.BAD_MECH.

This call assumes that the provider defined by the string provName is already installed on the system either statically or dynamically using the Java Cryptography Architecture (JCA) specification. If it does not find the provider it should throw a NoSuchProviderException.

Parameters:

mech	The mechanism for which the provider is being set
provName	The name of the provider that should be used whenever support is needed for mech. A value of null will remove any previous preference set by the application.

6.1.4. setProvider

```
public void setProvider(Ord mech, java.security.Provider p)
    throws GSSEException
```

Sets the provider for the GSS-API to use internally when it needs components to support the indicated mechanism.

If the GSSManager implementation does not support an SPI with a pluggable provider architecture it should throw a GSSEException with the status code GSSEException.UNAVAILABLE to indicate that the operation is unavailable. If the requested provider does not support the indicated mech then it should throw a GSSEException with the status code GSSEException.BAD_MECH.

Expires: May 2000

[Page 34]

This provider need not be installed globally on the system at all. The application instantiates the provider and passes it to the instance of GSSManager through this method.

Parameters:

mech	The mechanism for which the provider is being set
p	The provider instance to be used to implement the services for the specified mechanism. A value of null will remove any previous preference set by the application.

[6.1.5.](#) **getProvider**

```
public Provider getProvider(Oid mech)
```

Returns the preferred Provider instance that the GSS-API would use when trying to instantiate elements for the indicated mechanism.

[6.1.6.](#) **getMechs**

```
public Oid[] getMechs()
```

Returns an array of Oid objects indicating mechanisms available to GSS-API callers. A "null" value is returned when no mechanism are available (an example of this would be when mechanism are dynamically configured, and currently no mechanisms are installed).

[6.1.7.](#) **getNamesForMech**

```
public Oid[] getNamesForMech(Oid mech)
                        throws GSSException
```

Returns name type Oid's supported by the specified mechanism.

Parameters:

mech	The Oid object for the mechanism to query.
------	--

Expires: May 2000

[Page 35]

6.1.8. getMechsForName

```
public Oid[] getMechsForName(Oid nameType)
```

Returns an array of Oid objects corresponding to the mechanisms that support the specific name type. "null" is returned when no mechanisms are found to support the specified name type.

Parameters:

nameType The Oid object for the name type.

6.1.9. createName

```
public GSSName createName(String nameStr, Oid nameSpace)
    throws GSSEException
```

Factory method to convert a contiguous string name from the specified namespace to an GSSName object. In general, the GSSName object created will not be an MN; two examples that are exceptions to this are when the namespace type parameter indicates NT_EXPORT_NAME or when the GSS-API implementation is not multi-mechanism.

Parameters:

nameStr The string representing a printable form of the name to create.

nameType The Oid specifying the namespace of the printable name supplied. Note that nameType serves to describe and qualify the interpretation of the input nameStr, it does not necessarily imply a type for the output GSSName implementation. "null" value can be used to specify that a mechanism specific default printable syntax should be assumed by each mechanism that examines nameStr.

6.1.10. createName

```
public GSSName createName(byte name[], Oid nameType)
    throws GSSEException
```

Factory method to convert a contiguous byte array containing a name

Expires: May 2000

[Page 36]

from the specified namespace to an GSSName object. In general, the GSSName object created will not be an MN; two examples that are exceptions to this are when the namespace type parameter indicates NT_EXPORT_NAME or when the GSS-API implementation is not multi-mechanism.

Parameters:

- | | |
|----------|--|
| name | The byte array containing the name to create. |
| nameType | The Oid specifying the namespace of the name supplied in the byte array. Note that nameType serves to describe and qualify the interpretation of the input name byte array, it does not necessarily imply a type for the output GSSName implementation. "null" value can be used to specify that a mechanism specific default syntax should be assumed by each mechanism that examines the byte array. |

6.1.11. createName

```
public GSSName createName(String nameStr, Oid nameType,  
                          Oid mechType) throws GSSException
```

Factory method to convert a contiguous string name from the specified namespace to an GSSName object that is a mechanism name (MN). In other words, this method is a utility that does the equivalent of two steps: the createName described in 6.1.7 and then also the GSSName.canonicalize() described in 6.2.5.

Parameters:

- | | |
|----------|---|
| nameStr | The string representing a printable form of the name to create. |
| nameType | The Oid specifying the namespace of the printable name supplied. Note that nameType serves to describe and qualify the interpretation of the input nameStr, it does not necessarily imply a type for the output GSSName implementation. "null" value can be used to specify that a mechanism specific default printable syntax should be assumed when the mechanism examines nameStr. |
| mechType | Oid specifying the mechanism for which this name should be created. |

Expires: May 2000

[Page 37]

[6.1.12.](#) **createName**

```
public createName(byte name[], Oid nameType, Oid mechType)
    throws GSSException
```

Factory method to convert a contiguous byte array containing a name from the specified namespace to an GSSName object that is an MN. In other words, this method is a utility that does the equivalent of two steps: the createName described in 6.1.8 and then also the GSSName.canonicalize() described in 6.2.5.

Parameters:

- | | |
|----------|--|
| name | The byte array representing the name to create. |
| nameType | The Oid specifying the namespace of the name supplied in the byte array. Note that nameType serves to describe and qualify the interpretation of the input name byte array, it does not necessarily imply a type for the output GSSName implementation. "null" value can be used to specify that a mechanism specific default syntax should be assumed by each mechanism that examines the byte array. |
| mechType | Oid specifying the mechanism for which this name should be created. |

[6.1.13.](#) **createCredential**

```
public GSSCredential createCredential (int usage)
    throws GSSException
```

Factory method for acquiring default credentials. This will cause the GSS-API to use system specific defaults for the set of mechanisms, name, and an INDEFINITE lifetime.

Parameters:

- | | |
|-------|--|
| usage | The intended usage for this credential object. The value of this parameter must be one of:
GSSCredential.ACCEPT_AND_INITIATE,
GSSCredential.ACCEPT_ONLY, GSSCredential.INITIATE_ONLY |
|-------|--|

[6.1.14.](#) **createCredential**

```
public GSSCredential createCredential (GSSName aName,
```

Expires: May 2000

[Page 38]

```
int lifetime, Oid mechOid, int usage)
throws GSSEException
```

Factory method for acquiring a single mechanism credential.

Parameters:

aName	Name of the principal for whom this credential is to be acquired. Use "null" to specify the default principal.
lifetime	The number of seconds that credentials should remain valid. Use GSSCredential.INDEFINITE to request that the credentials have the maximum permitted lifetime.
mechOid	The oid of the desired mechanism. Use "(Oid) null" to request the default mechanism(s).
usage	The intended usage for this credential object. The value of this parameter must be one of: GSSCredential.ACCEPT_AND_INITIATE, GSSCredential.ACCEPT_ONLY, GSSCredential.INITIATE_ONLY

[6.1.15.](#) createCredential

```
public GSSCredential createCredential(GSSName aName,
int lifetime, Oid mechs[], int usage)
throws GSSEException
```

Factory method for acquiring credentials over a set of mechanisms. Acquires credentials for each of the mechanisms specified in the array called mechs. To determine the list of mechanisms' for which the acquisition of credentials succeeded, the caller should use the GSSCredential.getMechs() method.

Parameters:

aName	Name of the principal for whom this credential is to be acquired. Use "null" to specify the default principal.
lifetime	The number of seconds that credentials should remain valid. Use GSSCredential.INDEFINITE to request that the credentials have the maximum permitted lifetime.
mechOid	The array of mechanisms over which the credential is to be acquired. Use "(Oid[]) null" for requesting a

Expires: May 2000

[Page 39]

system specific default set of mechanisms.

usage The intended usage for this credential object. The value of this parameter must be one of:
 GSSCredential.ACCEPT_AND_INITIATE,
 GSSCredential.ACCEPT_ONLY, GSSCredential.INITIATE_ONLY

6.1.16. createContext

```
public GSSContext createContext(GSSName peer, Oid mechOid,  
                               GSSCredential myCred, int lifetime)  
    throws GSSEException
```

Factory method for creating a context on the initiator's side. Context flags may be modified through the mutator methods prior to calling GSSContext.initSecContext().

Parameters:

peer	Name of the target peer.
mechOid	Oid of the desired mechanism. Use "(Oid) null" to request default mechanism.
myCred	Credentials of the initiator. Use "null" to act as a default initiator principal.
lifetime	The request lifetime, in seconds, for the credential.

6.1.17. createContext

```
public GSSContext createContext(GSSCredential myCred)  
    throws GSSEException
```

Factory method for creating a context on the acceptor' side. The context's properties will be determined from the input token supplied to the accept method.

Parameters:

myCred	Credentials for the acceptor. Use "null" to act as a default acceptor principal.
--------	--

Expires: May 2000

[Page 40]

6.1.18. createContext

```
public GSSContext createContext(byte [] interProcessToken)
    throws GSSException
```

Factory method for creating a previously exported context. The context properties will be determined from the input token and can't be modified through the set methods.

Parameters:

```
    interProcessToken
        The token previously emitted from the export method.
```

6.2. public interface GSSName

This interface encapsulates a single GSS-API principal entity. Different name formats and their definitions are identified with universal Object Identifiers (Oids). The format of the names can be derived based on the unique oid of its namespace type.

6.2.1. Example Code

Included below are code examples utilizing the GSSName interface. The code below creates a GSSName, converts it to a mechanism name (MN), performs a comparison, obtains a printable representation of the name, exports it and then re-imports to obtain a new GSSName.

```
GSSManager mgr = new GSSManager();

// create a host based service name
GSSName name = mgr.createName("service@host",
    GSSName.NT_HOSTBASED_SERVICE);

Oid krb5 = new Oid("1.2.840.113554.1.2.2");

GSSName mechName = name.canonicalize(krb5);

// the above two steps are equivalent to the following
GSSName mechName = mgr.createName("service@host",
    GSSName.NT_HOSTBASED_SERVICE, krb5);

// perform name comparison
if (name.equals(mechName))
```


Expires: May 2000

[Page 41]

```
        print("Names are equals.");

// obtain textual representation of name and its printable
// name type
print(mechName.toString() +
      mechName.getStringNameType().toString());

// export and re-import the name
byte [] exportName = mechName.export();

// create a new name object from the exported buffer
GSSName newName = mgr.createName(exportName,
      GSSName.NT_EXPORT_NAME);
```

6.2.2. Static Constants

```
public static final Oid NT_HOSTBASED_SERVICE
```

Oid indicating a host-based service name form. It is used to represent services associated with host computers. This name form is constructed using two elements, "service" and "hostname", as follows:

service@hostname

Values for the "service" element are registered with the IANA. It represents the following value: { 1(iso), 3(org), 6(dod), 1(internet), 5(security), 6(nametypes), 2(gss-host-based-services) }

```
public static final Oid NT_USER_NAME
```

Name type to indicate a named user on a local system. It represents the following value: { iso(1) member-body(2) United States(840) mit(113554) infosys(1) gssapi(2) generic(1) user_name(1) }

```
public static final Oid NT_MACHINE_UID_NAME
```

Name type to indicate a numeric user identifier corresponding to a user on a local system. (e.g. Uid). It represents the following value: { iso(1) member-body(2) United States(840) mit(113554) infosys(1) gssapi(2) generic(1) machine_uid_name(2) }

```
public static final Oid NT_STRING_UID_NAME
```

Expires: May 2000

[Page 42]

Name type to indicate a string of digits representing the numeric user identifier of a user on a local system. It represents the following value: { iso(1) member-body(2) United States(840) mit(113554) infosys(1) gssapi(2) generic(1) string_uid_name(3) }

```
public static final Oid NT_ANONYMOUS
```

Name type for representing an anonymous entity. It represents the following value: { 1(iso), 3(org), 6(dod), 1(internet), 5(security), 6(nametypes), 3(gss-anonymous-name) }

```
public static final Oid NT_EXPORT_NAME
```

Name type used to indicate an exported name produced by the export method. It represents the following value: { 1(iso), 3(org), 6(dod), 1(internet), 5(security), 6(nametypes), 4(gss-api-exported-name) }

[6.2.3.](#) equals

```
public boolean equals(GSSName another) throws GSSEException
```

Compares two GSSName objects to determine whether they refer to the same entity. This method may throw a GSSEException when the names cannot be compared. If either of the names represents an anonymous entity, the method will return "false".

Parameters:

another GSSName object to compare with.

[6.2.4.](#) equals

```
public boolean equals(Object another)
```

A variation of the equals method described in 6.2.3 that is provided to override the Object.equals() method that the implementing class will inherit. The behaviour is exactly the same as that in 6.2.3 except that no GSSEException is thrown; instead, false will be returned in the situation where an error occurs.

Parameters:

another GSSName object to compare with.

Expires: May 2000

[Page 43]

6.2.5. canonicalize

`public GSSName canonicalize(Oid mechOid) throws GSSEException`

Creates a mechanism name (MN) from an arbitrary internal name. This is equivalent to using the factory methods described in 6.1.9 or 6.1.10 that take the mechanism name as one of their parameters.

Parameters:

`mechOid` The oid for the mechanism for which the canonical form of the name is requested.

6.2.6. export

`public byte[] export() throws GSSEException`

Returns a canonical contiguous byte representation of a mechanism name (MN), suitable for direct, byte by byte comparison by authorization functions. If the name is not an MN, implementations may throw a GSSEException with the NAME_NOT_MN status code. If an implementation chooses not to throw an exception, it should use some system specific default mechanism to canonicalize the name and then export it. The format of the header of the output buffer is specified in [RFC 2078](#).

6.2.7. toString

`public String toString()`

Returns a textual representation of the GSSName object. To retrieve the printed name format, which determines the syntax of the returned string, the `getStringNameType` method can be used.

6.2.8. getStringNameType

`public Oid getStringNameType() throws GSSEException`

Returns the oid representing the type of name returned through the `toString` method. Using this oid, the syntax of the printable name can be determined.

Expires: May 2000

[Page 44]

6.2.9. isAnonymous

```
public boolean isAnonymous()
```

Tests if this name object represents an anonymous entity. Returns "true" if this is an anonymous name.

6.2.10. isMN

```
public boolean isMN()
```

Tests if this name object contains only one mechanism element and is thus a mechanism name as defined by [RFC 2078](#).

6.3. public interface GSSCredential implements Cloneable

This interface encapsulates the GSS-API credentials for an entity. A credential contains all the necessary cryptographic information to enable the creation of a context on behalf of the entity that it represents. It may contain multiple, distinct, mechanism specific credential elements, each containing information for a specific security mechanism, but all referring to the same entity.

A credential may be used to perform context initiation, acceptance, or both.

GSS-API implementations must impose a local access-control policy on callers to prevent unauthorized callers from acquiring credentials to which they are not entitled. GSS-API credential creation is not intended to provide a "login to the network" function, as such a function would involve the creation of new credentials rather than merely acquiring a handle to existing credentials. Such functions, if required, should be defined in implementation-specific extensions to the API.

If credential acquisition is time-consuming for a mechanism, the mechanism may choose to delay the actual acquisition until the credential is required (e.g. by GSSContext). Such mechanism-specific implementation decisions should be invisible to the calling application; thus the query methods immediately following the creation of a credential object must return valid credential data, and may therefore incur the overhead of a deferred credential acquisition.

Applications will create a credential object passing the desired

Expires: May 2000

[Page 45]

parameters. The application can then use the query methods to obtain specific information about the instantiated credential object (equivalent to the `gss_inquire` routines). When the credential is no longer needed, the application should call the `dispose` (equivalent to `gss_release_cred`) method to release any resources held by the credential object and to destroy any cryptographically sensitive information.

Classes implementing this interface also implement the `Cloneable` interface. This indicates the the class will support the `clone()` method that will allow the creation of duplicate credentials. This is useful when called just before the `add()` call to retain a copy of the original credential.

6.3.1. Example Code

This example code demonstrates the creation of a `GSSCredential` implementation for a specific entity, querying of its fields, and its release when it is no longer needed.

```
GSSManager mgr = new GSSManager();

// start by creating a name object for the entity
GSSName name = mgr.createName("userName", GSSName.NT_USER_NAME);

// now acquire credentials for the entity
GSSCredential cred = mgr.createCredential(name,
                                           GSSCredential.ACCEPT_ONLY);

// display credential information - name, remaining lifetime,
// and the mechanisms it has been acquired over
print(cred.getName().toString());
print(cred.getRemainingLifetime());

Oid [] mechs = cred.getMechs();
if (mechs != null) {
    for (int i = 0; i < mechs.length; i++)
        print(mechs[i].toString());
}

// release system resources held by the credential
cred.dispose();
```

Expires: May 2000

[Page 46]

6.3.2. Static Constants

```
public static final int INITIATE_AND_ACCEPT
```

Credential usage flag requesting that it be able to be used for both context initiation and acceptance.

```
public static final int INITIATE_ONLY
```

Credential usage flag requesting that it be able to be used for context initiation only.

```
public static final int ACCEPT_ONLY
```

Credential usage flag requesting that it be able to be used for context acceptance only.

```
public static final int INDEFINITE
```

A lifetime constant representing indefinite credential lifetime. This value must be set to the maximum integer value in Java - Integer.MAX_VALUE.

6.3.3. dispose

```
public void dispose() throws GSSEException
```

Releases any sensitive information that the GSSCredential object may be containing. Applications should call this method as soon as the credential is no longer needed to minimize the time any sensitive information is maintained.

6.3.4. getName

```
public GSSName getName() throws GSSEException
```

Retrieves the name of the entity that the credential asserts.

6.3.5. getName

```
public GSSName getName(oid mechOID) throws GSSEException
```

Expires: May 2000

[Page 47]

Retrieves a mechanism name of the entity that the credential asserts. Equivalent to calling `canonicalize()` on the name returned by 7.3.3.

Parameters:

 mechOID The mechanism for which information should be returned.

6.3.6. getRemainingLifetime

`public int getRemainingLifetime() throws GSSEException`

Returns the remaining lifetime in seconds for a credential. The remaining lifetime is the minimum lifetime for any of the underlying credential mechanisms. A return value of `GSSCredential.INDEFINITE` indicates that the credential does not expire. A return value of 0 indicates that the credential is already expired.

6.3.7. getRemainingInitLifetime

`public int getRemainingInitLifetime(Oid mech) throws GSSEException`

Returns the remaining lifetime in seconds for the credential to remain capable of initiating security contexts under the specified mechanism. A return value of `GSSCredential.INDEFINITE` indicates that the credential does not expire for context initiation. A return value of 0 indicates that the credential is already expired.

Parameters:

 mechOID The mechanism for which information should be returned.

6.3.8. getRemainingAcceptLifetime

`public int getRemainingAcceptLifetime(Oid mech) throws GSSEException`

Returns the remaining lifetime in seconds for the credential to remain capable of accepting security contexts under the specified mechanism. A return value of `GSSCredential.INDEFINITE` indicates that the credential does not expire for context acceptance. A return value of 0 indicates that the credential is already expired.

Parameters:

Expires: May 2000

[Page 48]

mechOID The mechanism for which information should be returned.

[6.3.9.](#) **getUsage**

public int getUsage() throws GSSEException

Returns the credential usage flag. The return value will be one of GSSCredential.INITIATE_ONLY, GSSCredential.ACCEPT_ONLY, or GSSCredential.INITIATE_AND_ACCEPT.

[6.3.10.](#) **getUsage**

public int getUsage(Oid mechOID) throws GSSEException

Returns the credential usage flag for the specified credential mechanism. The return value will be one of GSSCredential.INITIATE_ONLY, GSSCredential.ACCEPT_ONLY, or GSSCredential.INITIATE_AND_ACCEPT.

Parameters:

mechOID The mechanism for which information should be returned.

[6.3.11.](#) **getMechs**

public Oid[] getMechs() throws GSSEException

Returns an array of mechanisms supported by this credential.

[6.3.12.](#) **add**

public void add(GSSName aName, int initLifetime, int acceptLifetime, Oid mech, int usage) throws GSSEException

Adds a mechanism specific credential-element to an existing credential. This method allows the construction of credentials one mechanism at a time.

This routine is envisioned to be used mainly by context acceptors during the creation of acceptance credentials which are to be used with a variety of clients using different security mechanisms.

Expires: May 2000

[Page 49]

This routine adds the new credential element "in-place". To add the element in a new credential, first call `clone()` to obtain a copy of this credential, then call its `add()` method.

Parameters:

<code>aName</code>	Name of the principal for whom this credential is to be acquired. Use "null" to specify the default principal.
<code>initLifetime</code>	The number of seconds that credentials should remain valid for initiating of security contexts. Use <code>GSSCredential.INDEFINITE</code> to request that the credentials have the maximum permitted lifetime.
<code>acceptLifetime</code>	The number of seconds that credentials should remain valid for accepting of security contexts. Use <code>GSSCredential.INDEFINITE</code> to request that the credentials have the maximum permitted lifetime.
<code>mechOid</code>	The mechanisms over which the credential is to be acquired.
<code>usage</code>	The intended usage for this credential object. The value of this parameter must be one of: <code>GSSCredential.ACCEPT_AND_INITIATE</code> , <code>GSSCredential.ACCEPT_ONLY</code> , <code>GSSCredential.INITIATE_ONLY</code>

6.3.13. equals

```
public boolean equals(Object another)
```

Tests if this `GSSCredential` refers to the same entity as the supplied object. The two credentials must be acquired over the same mechanisms and must refer to the same principal. Returns "true" if the two `GSSCredentials` refer to the same entity; "false" otherwise.

Parameters:

<code>another</code>	Another <code>GSSCredential</code> object for comparison.
----------------------	---

Expires: May 2000

[Page 50]

6.4. public interface GSSContext

This interface encapsulates the GSS-API security context and provides the security services (wrap, unwrap, getMIC, verifyMIC) that are available over the context. Security contexts are established between peers using locally acquired credentials. Multiple contexts may exist simultaneously between a pair of peers, using the same or different set of credentials. GSS-API functions in a manner independent of the underlying transport protocol and depends on its calling application to transport its tokens between peers.

Before the context establishment phase is initiated, the context initiator may request specific characteristics desired of the established context. These can be set using the set methods. After the context is established, the caller can check the actual characteristic and services offered by the context using the query methods.

The context establishment phase begins with the first call to the `init` method by the context initiator. During this phase the `initSecContext` and `acceptSecContext` methods will produce GSS-API authentication tokens which the calling application needs to send to its peer. If an error occurs at any point, an exception will get thrown and the code will start executing in a catch block. If not, the normal flow of code continues and the application can make a call to the `isEstablished()` method. If this method returns false it indicates that a token is needed from its peer in order to continue the context establishment phase. A return value of true signals that the local end of the context is established. This may still require that a token be sent to the peer, if one is produced by GSS-API. During the context establishment phase, the `isProtReady()` method may be called to determine if the context can be used for the per-message operations. This allows applications to use per-message operations on contexts which aren't fully established.

After the context has been established or the `isProtReady()` method returns "true", the query routines can be invoked to determine the actual characteristics and services of the established context. The application can also start using the per-message methods of `wrap` and `getMIC` to obtain cryptographic operations on application supplied data.

When the context is no longer needed, the application should call `dispose` to release any system resources the context may be using.

Expires: May 2000

[Page 51]

6.4.1. Example Code

The example code presented below demonstrates the usage of the GSSContext interface for the initiating peer. Different operations on the GSSContext object are presented, including: object instantiation, setting of desired flags, context establishment, query of actual context flags, per-message operations on application data, and finally context deletion.

```
GSSManager mgr = new GSSManager();

// start by creating the name for a service entity
GSSName targetName = mgr.createName("service@host",
                                     GSSName.NT_HOSTBASED_SERVICE);

// create a context using default credentials for the above entity
// and the implementation specific default mechanism
GSSContext context = mgr.createContext(targetName,
                                       null, /* default mechanism */
                                       null, /* default credentials */
                                       GSSContext.INDEFINITE);

// set desired context options - all others are false by default
context.requestConf(true);
context.requestMutualAuth(true);
context.requestReplayDet(true);
context.requestSequenceDet(true);

// establish a context between peers - using byte arrays
byte []inTok = new byte[0];

try {
    do {
        byte[] outTok = context.initSecContext(inTok, 0,
                                                inTok.length);

        // send the token if present
        if (outTok != null)
            sendToken(outTok);

        // check if we should expect more tokens
        if (context.isEstablished())
            break;

        // another token expected from peer
        inTok = readToken();
    }
}
```

Expires: May 2000

[Page 52]

```
        } while (true);

    } catch (GSSEException e) {
        print("GSSAPI error: " + e.getMessage());
    }

    // display context information
    print("Remaining lifetime in seconds = " + context.getLifetime());
    print("Context mechanism = " + context.getMech().toString());
    print("Initiator = " + context.getSrcName().toString());
    print("Acceptor = " + context.getTargName().toString());

    if (context.getConfState())
        print("Confidentiality security service available");

    if (context.getIntegState())
        print("Integrity security service available");

    // perform wrap on an application supplied message, appMsg,
    // using QOP = 0, and requesting privacy service
    byte [] appMsg ...

    MessageProp mProp = new MessageProp(0, true);

    byte [] tok = context.wrap(appMsg, 0, appMsg.length, mProp);

    if (mProp.getPrivacy())
        print("Message protected with privacy.");

    sendToken(tok);

    // release the local-end of the context
    context.dispose();
```

6.4.2. Static Constants

```
public static final int INDEFINITE
```

A lifetime constant representing indefinite context lifetime. This value must be set to the maximum integer value in Java - `Integer.MAX_VALUE`.

Expires: May 2000

[Page 53]

6.4.3. initSecContext

```
public byte[] initSecContext(byte inputBuf[], int offset, int len)
    throws GSSException
```

Called by the context initiator to start the context creation process. This is equivalent to the stream based method except that the token buffers are handled as byte arrays instead of using stream objects. This method may return an output token which the application will need to send to the peer for processing by the accept call. "null" return value indicates that no token needs to be sent to the peer. The application can call `isEstablished()` to determine if the context establishment phase is complete for this peer. A return value of "false" from `isEstablished()` indicates that more tokens are expected to be supplied to the `initSecContext()` method. Note that it is possible that the `initSecContext()` method return a token for the peer, and `isEstablished()` return "true" also. This indicates that the token needs to be sent to the peer, but the local end of the context is now fully established.

Upon completion of the context establishment, the available context options may be queried through the get methods.

Parameters:

<code>inputBuf</code>	Token generated by the peer. This parameter is ignored on the first call.
<code>offset</code>	The offset within the <code>inputBuf</code> where the token begins.
<code>len</code>	The length of the token within the <code>inputBuf</code> (starting at the offset).

6.4.3.1. Example Code

```
// Create a new GSSContext implementation object.
// GSSContext wrapper implements interface GSSContext.
GSSContext context = mgr.createContext(...);
```

```
byte []inTok = new byte[0];
```

```
try {
```

```
    do {
```

```
        byte[] outTok = context.initSecContext(inTok, 0,
```

Expires: May 2000

[Page 54]

```
                inTok.length);

        // send the token if present
        if (outTok != null)
            sendToken(outTok);

        // check if we should expect more tokens
        if (context.isEstablished())
            break;

        // another token expected from peer
        inTok = readToken();
    } while (true);

} catch (GSSEException e) {
    print("GSSAPI error: " + e.getMessage());
}
```

6.4.4. initSecContext

```
public int initSecContext(InputStream inStream,
                        OutputStream outStream) throws GSSEException
```

Called by the context initiator to start the context creation process. This is equivalent to the byte array based method. This method may write an output token to the outStream, which the application will need to send to the peer for processing by the accept call. 0 bytes written to the output stream indicate that no token needs to be sent to the peer. The application can call `isEstablished()` to determine if the context establishment phase is complete for this peer. A return value of "false" from `isEstablished` indicates that more tokens are expected to be supplied to the `initSecContext` method. Note that it is possible that the `initSecContext()` method return a token for the peer, and `isEstablished()` return "true" also. This indicates that the token needs to be sent to the peer, but the local end of the context is now fully established.

The GSS-API authentication tokens contain a definitive start and end. This method will attempt to read one of these tokens per invocation, and may block on the stream if only part of the token is available.

Upon completion of the context establishment, the available context options may be queried through the get methods.

Expires: May 2000

[Page 55]

Parameters:

`inStream` Contains the token generated by the peer. This parameter is ignored on the first call.

`outStream` Output stream where the output token will be written. During the final stage of context establishment, there may be no bytes written.

6.4.4.1. Example Code

```
// Create a new GSSContext implementation object.
// GSSContext wrapper implements interface GSSContext.
GSSContext context = mgr.createContext(...);

// use standard java.io stream objects
ByteArrayOutputStream os = new ByteArrayOutputStream();
ByteArrayInputStream is = null;

try {
    do {
        context.initSecContext(is, os);

        // send token if present
        if (os.size() > 0)
            sendToken(os);

        // check if we should expect more tokens
        if (context.isEstablished())
            break;

        // another token expected from peer
        is = recvToken();
    } while (true);
} catch (GSSEException e) {
    print("GSSAPI error: " + e.getMessage());
}
```

Expires: May 2000

[Page 56]

6.4.5. acceptSecContext

```
public byte[] acceptSecContext(byte inTok[], int offset, int len)
    throws GSSException
```

Called by the context acceptor upon receiving a token from the peer. This call is equivalent to the stream based method except that the token buffers are handled as byte arrays instead of using stream objects.

This method may return an output token which the application will need to send to the peer for further processing by the `init` call. "null" return value indicates that no token needs to be sent to the peer. The application can call `isEstablished()` to determine if the context establishment phase is complete for this peer. A return value of "false" from `isEstablished()` indicates that more tokens are expected to be supplied to this method.

Note that it is possible that `acceptSecContext()` return a token for the peer, and `isEstablished()` return "true" also. This indicates that the token needs to be sent to the peer, but the local end of the context is now fully established.

Upon completion of the context establishment, the available context options may be queried through the `get` methods.

Parameters:

<code>inTok</code>	Token generated by the peer.
<code>offset</code>	The offset within the <code>inTok</code> where the token begins.
<code>len</code>	The length of the token within the <code>inTok</code> (starting at the offset).

6.4.5.1. Example Code

```
// acquire server credentials
GSSCredential server = mgr.createCredential(...);

// create acceptor GSS-API context from the default provider
GSSContext context = mgr.createContext(server, null);

try {
    do {
        byte [] inTok = readToken();
```


Expires: May 2000

[Page 57]

```
byte []outTok = context.acceptSecContext(inTok, 0,
                                         inTok.length);

// possibly send token to peer
if (outTok != null)
    sendToken(outTok);

// check if local context establishment is complete
if (context.isEstablished())
    break;
} while (true);

} catch (GSSEException e) {
    print("GSS-API error: " + e.getMessage());
}
```

6.4.6. acceptSecContext

```
public void acceptSecContext(InputStream inStream,
                             OutputStream outStream) throws GSSEException
```

Called by the context acceptor upon receiving a token from the peer. This call is equivalent to the byte array method. It may write an output token to the outStream, which the application will need to send to the peer for processing by its `initSecContext` method. 0 bytes written to the output stream indicate that no token needs to be sent to the peer. The application can call `isEstablished()` to determine if the context establishment phase is complete for this peer. A return value of "false" from `isEstablished()` indicates that more tokens are expected to be supplied to this method.

Note that it is possible that `acceptSecContext()` return a token for the peer, and `isEstablished()` return "true" also. This indicates that the token needs to be sent to the peer, but the local end of the context is now fully established.

The GSS-API authentication tokens contain a definitive start and end. This method will attempt to read one of these tokens per invocation, and may block on the stream if only part of the token is available.

Upon completion of the context establishment, the available context options may be queried through the `get` methods.

Parameters:

`inStream` Contains the token generated by the peer.

Expires: May 2000

[Page 58]

outStream Output stream where the output token will be written.
During the final stage of context establishment, there
may be no bytes written.

6.4.6.1. Example Code

```
// acquire server credentials
GSSCredential server = mgr.createCredential(...);

// create acceptor GSS-API context from the default provider
GSSContext context = mgr.createContext(server, null);

// use standard java.io stream objects
ByteArrayOutputStream os = new ByteArrayOutputStream();
ByteArrayInputStream is = null;

try {
    do {

        is = recvToken();

        context.acceptSecContext(is, os);

        // possibly send token to peer
        if (os.size() > 0)
            sendToken(os);

        // check if local context establishment is complete
        if (context.isEstablished())
            break;
    } while (true);

} catch (GSSException e) {
    print("GSS-API error: " + e.getMessage());
}
```

6.4.7. isEstablished

```
public boolean isEstablished()
```

Used during context establishment to determine the state of the context. Returns "true" if this is a fully established context on the caller's side and no more tokens are needed from the peer.

Expires: May 2000

[Page 59]

Should be called after a call to `initSecContext()` or `acceptSecContext()` when no `GSSEException` is thrown.

6.4.8. dispose

`public void dispose()` throws `GSSEException`

Releases any system resources and cryptographic information stored in the context object. This will invalidate the context.

6.4.9. getWrapSizeLimit

`public int getWrapSizeLimit(int qop, boolean confReq,
int maxTokenSize)` throws `GSSEException`

Returns the maximum message size that, if presented to the `wrap` method with the same `confReq` and `qop` parameters, will result in an output token containing no more than the `maxTokenSize` bytes.

This call is intended for use by applications that communicate over protocols that impose a maximum message size. It enables the application to fragment messages prior to applying protection.

GSS-API implementations are recommended but not required to detect invalid QOP values when `getWrapSizeLimit` is called. This routine guarantees only a maximum message size, not the availability of specific QOP values for message protection.

Successful completion of this call does not guarantee that `wrap` will be able to protect a message of the computed length, since this ability may depend on the availability of system resources at the time that `wrap` is called. However, if the implementation itself imposes an upper limit on the length of messages that may be processed by `wrap`, the implementation should not return a value that is greater than this length.

Parameters:

- | | |
|---------------------------|---|
| <code>qop</code> | Indicates the level of protection <code>wrap</code> will be asked to provide. |
| <code>confReq</code> | Indicates if <code>wrap</code> will be asked to provide privacy service. |
| <code>maxTokenSize</code> | The desired maximum size of the token emitted by <code>wrap</code> . |

Expires: May 2000

[Page 60]

[6.4.10.](#) wrap

```
public byte[] wrap(byte inBuf[], int offset, int len,  
    MessageProp msgProp) throws GSSEException
```

Applies per-message security services over the established security context. The method will return a token with a cryptographic MIC and may optionally encrypt the specified inBuf. This method is equivalent in functionality to its stream counterpart. The returned byte array will contain both the MIC and the message.

The MessageProp object is instantiated by the application and used to specify a QOP value which selects cryptographic algorithms, and a privacy service to optionally encrypt the message. The underlying mechanism that is used in the call may not be able to provide the privacy service. It sets the actual privacy service that it does provide in this MessageProp object which the caller should then query upon return. If the mechanism is not able to provide the requested QOP, it throws a GSSEException with the BAD_QOP code.

Since some application-level protocols may wish to use tokens emitted by wrap to provide "secure framing", implementations should support the wrapping of zero-length messages.

The application will be responsible for sending the token to the peer.

Parameters:

inBuf	Application data to be protected.
offset	The offset within the inBuf where the data begins.
len	The length of the data within the inBuf (starting at the offset).
msgProp	Instance of MessageProp that is used by the application to set the desired QOP and privacy state. Set the desired QOP to 0 to request the default QOP. Upon return from this method, this object will contain the the actual privacy state that was applied to the message by the underlying mechanism.

[6.4.11.](#) wrap

```
public void wrap(InputStream inStream, OutputStream outStream,  
    MessageProp msgProp) throws GSSEException
```


Expires: May 2000

[Page 61]

Allows to apply per-message security services over the established security context. The method will produce a token with a cryptographic MIC and may optionally encrypt the message in `inStream`. The `outStream` will contain both the MIC and the message.

The `MessageProp` object is instantiated by the application and used to specify a QOP value which selects cryptographic algorithms, and a privacy service to optionally encrypt the message. The underlying mechanism that is used in the call may not be able to provide the privacy service. It sets the actual privacy service that it does provide in this `MessageProp` object which the caller should then query upon return. If the mechanism is not able to provide the requested QOP, it throws a `GSSEException` with the `BAD_QOP` code.

Since some application-level protocols may wish to use tokens emitted by `wrap` to provide "secure framing", implementations should support the wrapping of zero-length messages.

The application will be responsible for sending the token to the peer.

Parameters:

- `inStream` Input stream containing the application data to be protected.
- `outStream` The output stream to write the protected message to. The application is responsible for sending this to the other peer for processing in its `unwrap` method.
- `msgProp` Instance of `MessageProp` that is used by the application to set the desired QOP and privacy state. Set the desired QOP to 0 to request the default QOP. Upon return from this method, this object will contain the the actual privacy state that was applied to the message by the underlying mechanism.

[6.4.12.](#) `unwrap`

```
public byte [] unwrap(byte[] inBuf, int offset, int len,  
                      MessageProp msgProp) throws GSSEException
```

Used by the peer application to process tokens generated with the `wrap` call. This call is equal in functionality to its stream counterpart. The method will return the message supplied in the peer application to the `wrap` call, verifying the embedded MIC.

Expires: May 2000

[Page 62]

The MessageProp object is instantiated by the application and is used by the underlying mechanism to return information to the caller such as the QOP, whether confidentiality was applied to the message, and other supplementary message state information.

Since some application-level protocols may wish to use tokens emitted by wrap to provide "secure framing", implementations should support the wrapping and unwrapping of zero-length messages.

Parameters:

inBuf	GSS-API wrap token received from peer.
offset	The offset within the inBuf where the token begins.
len	The length of the token within the inBuf (starting at the offset).
msgProp	Upon return from the method, this object will contain the applied QOP, the privacy state of the message, and supplementary information described in 4.12.3 stating whether the token was a duplicate, old, out of sequence or arriving after a gap.

6.4.13. unwrap

```
public void unwrap(InputStream inStream, OutputStream outStream,  
                  MessageProp msgProp) throws GSSEException
```

Used by the peer application to process tokens generated with the wrap call. This call is equal in functionality to its byte array counterpart. It will produce the message supplied in the peer application to the wrap call, verifying the embedded MIC.

The MessageProp object is instantiated by the application and is used by the underlying mechanism to return information to the caller such as the QOP, whether confidentiality was applied to the message, and other supplementary message state information.

Since some application-level protocols may wish to use tokens emitted by wrap to provide "secure framing", implementations should support the wrapping and unwrapping of zero-length messages.

Parameters:

inStream	Input stream containing the GSS-API wrap token received from the peer.
----------	--

Expires: May 2000

[Page 63]

`outStream` The output stream to write the application message to.

`msgProp` Upon return from the method, this object will contain the applied QOP, the privacy state of the message, and supplementary information described in 4.12.3 stating whether the token was a duplicate, old, out of sequence or arriving after a gap.

[6.4.14.](#) **getMIC**

```
public byte[] getMIC(byte []inMsg, int offset, int len,  
                    MessageProp msgProp) throws GSSEException
```

Returns a token containing a cryptographic MIC for the supplied message, for transfer to the peer application. Unlike `wrap`, which encapsulates the user message in the returned token, only the message MIC is returned in the output token. This method is identical in functionality to its stream counterpart.

Note that privacy can only be applied through the `wrap` call.

Since some application-level protocols may wish to use tokens emitted by `getMIC` to provide "secure framing", implementations should support derivation of MICs from zero-length messages.

Parameters:

<code>inMsg</code>	Message to generate MIC over.
<code>offset</code>	The offset within the <code>inMsg</code> where the token begins.
<code>len</code>	The length of the token within the <code>inMsg</code> (starting at the <code>offset</code>).
<code>msgProp</code>	Instance of <code>MessageProp</code> that is used by the application to set the desired QOP. Set the desired QOP to 0 in <code>msgProp</code> to request the default QOP. Alternatively pass in "null" for <code>msgProp</code> to request default QOP.

[6.4.15.](#) **getMIC**

```
public void getMIC(InputStream inStream, OutputStream outStream,  
                  MessageProp msgProp) throws GSSEException
```

Produces a token containing a cryptographic MIC for the supplied

Expires: May 2000

[Page 64]

message, for transfer to the peer application. Unlike wrap, which encapsulates the user message in the returned token, only the message MIC is produced in the output token. This method is identical in functionality to its byte array counterpart.

Note that privacy can only be applied through the wrap call.

Since some application-level protocols may wish to use tokens emitted by getMIC to provide "secure framing", implementations should support derivation of MICs from zero-length messages.

Parameters:

inStream	inStream	Input stream containing the message to generate MIC over.
outStream	outStream	Output stream to write the GSS-API output token to.
msgProp	Instance of MessageProp	that is used by the application to set the desired QOP. Set the desired QOP to 0 in msgProp to request the default QOP. Alternatively pass in "null" for msgProp to request default QOP.

6.4.16. verifyMIC

```
public void verifyMIC(byte []inTok, int tokOffset, int tokLen,  
                     byte[] inMsg, int msgOffset, int msgLen,  
                     MessageProp msgProp) throws GSSEException
```

Verifies the cryptographic MIC, contained in the token parameter, over the supplied message. This method is equivalent in functionality to its stream counterpart.

The MessageProp object is instantiated by the application and is used by the underlying mechanism to return information to the caller such as the QOP indicating the strength of protection that was applied to the message and other supplementary message state information.

Since some application-level protocols may wish to use tokens emitted by getMIC to provide "secure framing", implementations should support the calculation and verification of MICs over zero-length messages.

Parameters:

inTok	Token generated by peer's getMIC method.
-------	--

Expires: May 2000

[Page 65]

`tokOffset` The offset within the `inTok` where the token begins.

`tokLen` The length of the token within the `inTok` (starting at the offset).

`inMsg` Application message to verify the cryptographic MIC over.

`msgOffset` The offset within the `inMsg` where the message begins.

`msgLen` The length of the message within the `inMsg` (starting at the offset).

`msgProp` Upon return from the method, this object will contain the applied QOP and supplementary information described in 4.12.3 stating whether the token was a duplicate, old, out of sequence or arriving after a gap. The confidentiality state will be set to "false".

[6.4.17.](#) **verifyMIC**

```
public void verifyMIC(InputStream tokStream, InputStream msgStream,  
                      MessageProp msgProp) throws GSSEException
```

Verifies the cryptographic MIC, contained in the token parameter, over the supplied message. This method is equivalent in functionality to its byte array counterpart.

The `MessageProp` object is instantiated by the application and is used by the underlying mechanism to return information to the caller such as the QOP indicating the strength of protection that was applied to the message and other supplementary message state information.

Since some application-level protocols may wish to use tokens emitted by `getMIC` to provide "secure framing", implementations should support the calculation and verification of MICs over zero-length messages.

Parameters:

`tokStream` Input stream containing the token generated by peer's `getMIC` method.

`msgStream` Input stream containing the application message to verify the cryptographic MIC over.

`msgProp` Upon return from the method, this object will contain

Expires: May 2000

[Page 66]

the applied QOP and supplementary information described in 4.12.3 stating whether the token was a duplicate, old, out of sequence or arriving after a gap. The confidentiality state will be set to "false".

6.4.18. export

```
public byte [] export() throws GSSEException
```

Provided to support the sharing of work between multiple processes. This routine will typically be used by the context-acceptor, in an application where a single process receives incoming connection requests and accepts security contexts over them, then passes the established context to one or more other processes for message exchange.

This method deactivates the security context and creates an interprocess token which, when passed to the byte array constructor of the GSSContext interface in another process, will re-activate the context in the second process. Only a single instantiation of a given context may be active at any one time; a subsequent attempt by a context exporter to access the exported security context will fail.

The implementation may constrain the set of processes by which the interprocess token may be imported, either as a function of local security policy, or as a result of implementation decisions. For example, some implementations may constrain contexts to be passed only between processes that run under the same account, or which are part of the same process group.

The interprocess token may contain security-sensitive information (for example cryptographic keys). While mechanisms are encouraged to either avoid placing such sensitive information within interprocess tokens, or to encrypt the token before returning it to the application, in a typical GSS-API implementation this may not be possible. Thus the application must take care to protect the interprocess token, and ensure that any process to which the token is transferred is trustworthy.

6.4.19. requestMutualAuth

```
public void requestMutualAuth(boolean state) throws GSSEException
```

Sets the request state of the mutual authentication flag for the context. This method is only valid before the context creation

Expires: May 2000

[Page 67]

process begins and only for the initiator.

Parameters:

state	Boolean representing if mutual authentication should be requested during context establishment.
-------	---

6.4.20. requestReplayDet

public void requestReplayDet(boolean state) throws GSSEException

Sets the request state of the replay detection service for the context. This method is only valid before the context creation process begins and only for the initiator.

Parameters:

state	Boolean representing if replay detection is desired over the established context.
-------	---

6.4.21. requestSequenceDet

public void requestSequenceDet(boolean state) throws GSSEException

Sets the request state for the sequence checking service of the context. This method is only valid before the context creation process begins and only for the initiator.

Parameters:

state	Boolean representing if sequence detection is desired over the established context.
-------	---

6.4.22. requestCredDeleg

public void requestCredDeleg(boolean state) throws GSSEException

Sets the request state for the credential delegation flag for the context. This method is only valid before the context creation process begins and only for the initiator.

Parameters:

state	Boolean representing if credential delegation is desired.
-------	---

Expires: May 2000

[Page 68]

6.4.23. requestAnonymity

public void requestAnonymity(boolean state) throws GSSEException

Requests anonymous support over the context. This method is only valid before the context creation process begins and only for the initiator.

Parameters:

state Boolean representing if anonymity support is requested.

6.4.24. requestConf

public void requestConf(boolean state) throws GSSEException

Requests that confidentiality service be available over the context. This method is only valid before the context creation process begins and only for the initiator.

Parameters:

state Boolean indicating if confidentiality services are to be requested for the context.

6.4.25. requestInteg

public void requestInteg(boolean state) throws GSSEException

Requests that integrity services be available over the context. This method is only valid before the context creation process begins and only for the initiator.

Parameters:

state Boolean indicating if integrity services are to be requested for the context.

6.4.26. requestLifetime

public void requestLifetime(int lifetime) throws GSSEException

Sets the desired lifetime for the context in seconds. This method is only valid before the context creation process begins and only for

Expires: May 2000

[Page 69]

the initiator.

Parameters:

lifetime The desired context lifetime in seconds.

6.4.27. setChannelBinding

```
public void setChannelBinding(ChannelBinding cb) throws GSSException
```

Sets the channel bindings to be used during context establishment. This method is only valid before the context creation process begins.

Parameters:

cb Channel bindings to be used.

6.4.28. getCredDelegState

```
public boolean getCredDelegState()
```

Returns the state of the delegated credentials for the context. When issued before context establishment is completed or when the `isProtReady` method returns "false", it returns the desired state, otherwise it will indicate the actual state over the established context.

6.4.29. getMutualAuthState

```
public boolean getMutualAuthState()
```

Returns the state of the mutual authentication option for the context. When issued before context establishment completes or when the `isProtReady` method returns "false", it returns the desired state, otherwise it will indicate the actual state over the established context.

6.4.30. getReplayDetState

```
public boolean getReplayDetState()
```

Returns the state of the replay detection option for the context. When issued before context establishment completes or when the `isProtReady` method returns "false", it returns the desired state,

Expires: May 2000

[Page 70]

otherwise it will indicate the actual state over the established context.

6.4.31. getSequenceDetState

```
public boolean getSequenceDetState()
```

Returns the state of the sequence detection option for the context. When issued before context establishment completes or when the `isProtReady` method returns "false", it returns the desired state, otherwise it will indicate the actual state over the established context.

6.4.32. getAnonymityState

```
public boolean getAnonymityState()
```

Returns "true" if this is an anonymous context. When issued before context establishment completes or when the `isProtReady` method returns "false", it returns the desired state, otherwise it will indicate the actual state over the established context.

6.4.33. isTransferable

```
public boolean isTransferable() throws GSSEException
```

Returns "true" if the context is transferable to other processes through the use of the `export` method. This call is only valid on fully established contexts.

6.4.34. isProtReady

```
public boolean isProtReady()
```

Returns "true" if the per message operations can be applied over the context. Some mechanisms may allow the usage of per-message operations before the context is fully established. This will also indicate that the `get` methods will return actual context state characteristics instead of the desired ones.

6.4.35. getConfState

```
public boolean getConfState()
```

Expires: May 2000

[Page 71]

Returns the confidentiality service state over the context. When issued before context establishment completes or when the `isProtReady` method returns "false", it returns the desired state, otherwise it will indicate the actual state over the established context.

[6.4.36.](#) **getIntegState**

```
public boolean getIntegState()
```

Returns the integrity service state over the context. When issued before context establishment completes or when the `isProtReady` method returns "false", it returns the desired state, otherwise it will indicate the actual state over the established context.

[6.4.37.](#) **getLifetime**

```
public int getLifetime()
```

Returns the context lifetime in seconds. When issued before context establishment completes or when the `isProtReady` method returns "false", it returns the desired lifetime, otherwise it will indicate the remaining lifetime for the context.

[6.4.38.](#) **getSrcName**

```
public GSSName getSrcName() throws GSSException
```

Returns the name of the context initiator. This call is valid only after the context is fully established or the `isProtReady` method returns "true". It is guaranteed to return an MN.

[6.4.39.](#) **getTargName**

```
public GSSName getTargName() throws GSSException
```

Returns the name of the context target (acceptor). This call is valid only after the context is fully established or the `isProtReady` method returns "true". It is guaranteed to return an MN.

[6.4.40.](#) **getMech**

```
public Oid getMech() throws GSSException
```

Expires: May 2000

[Page 72]

Returns the mechanism oid for this context.

6.4.41. getDelegCred

`public GSSCredential getDelegCred()` throws `GSSEException`

Returns the delegated credential object on the acceptor's side. To check for availability of delegated credentials call `getDelegCredState`. This call is only valid on fully established contexts.

6.4.42. isInitiator

`public boolean isInitiator()` throws `GSSEException`

Returns "true" if this is the initiator of the context. This call is only valid after the context creation process has started.

6.5. public class MessageProp

This is a utility class used within the per-message `GSSContext` methods to convey per-message properties.

When used with the `GSSContext` interface's `wrap` and `getMIC` methods, an instance of this class is used to indicate the desired QOP and to request if confidentiality services are to be applied to caller supplied data (`wrap` only). To request default QOP, the value of 0 should be used for QOP.

When used with the `unwrap` and `verifyMIC` methods of the `GSSContext` interface, an instance of this class will be used to indicate the applied QOP and confidentiality services over the supplied message. In the case of `verifyMIC`, the confidentiality state will always be "false". Upon return from these methods, this object will also contain any supplementary status values applicable to the processed token. The supplementary status values can indicate old tokens, out of sequence tokens, gap tokens or duplicate tokens.

6.5.1. Constructors

`public MessageProp(boolean privState)`

Constructor which sets QOP to 0 indicating that the default QOP is

Expires: May 2000

[Page 73]

requested.

Parameters:

privState The desired privacy state. "true" for privacy and "false" for integrity only.

```
public MessageProp(int qop, boolean privState)
```

Constructor which sets the values for the qop and privacy state.

Parameters:

qop The desired QOP. Use 0 to request a default QOP.

privState The desired privacy state. "true" for privacy and "false" for integrity only.

[6.5.2.](#) **getQOP**

```
public int getQOP()
```

Retrieves the QOP value.

[6.5.3.](#) **getPrivacy**

```
public boolean getPrivacy()
```

Retrieves the privacy state.

[6.5.4.](#) **getMinorStatus**

```
public int getMinorStatus()
```

Retrieves the minor status that the underlying mechanism might have set.

[6.5.5.](#) **getMinorString**

```
public String getMinorString()
```

Returns a string explaining the mechanism specific error code. null will be returned when no mechanism error code has been set.

Expires: May 2000

[Page 74]

6.5.6. setQOP

```
public void setQOP(int qopVal)
```

Sets the QOP value.

Parameters:

qopVal	The QOP value to be set. Use 0 to request a default QOP value.
--------	--

6.5.7. setPrivacy

```
public void setPrivacy(boolean privState)
```

Sets the privacy state.

Parameters:

privState	The privacy state to set.
-----------	---------------------------

6.5.8. isDuplicateToken

```
public boolean isDuplicateToken()
```

Returns "true" if this is a duplicate of an earlier token.

6.5.9. isOldToken

```
public boolean isOldToken()
```

Returns "true" if the token's validity period has expired.

6.5.10. isUnseqToken

```
public boolean isUnseqToken()
```

Returns "true" if a later token has already been processed.

6.5.11. isGapToken

```
public boolean isGapToken()
```

Expires: May 2000

[Page 75]

Returns "true" if an expected per-message token was not received.

6.5.12. setSupplementaryStates

```
public void setSupplementaryStates(boolean duplicate,
                                   boolean old, boolean unseq, boolean gap,
                                   int minorStatus, String minorString)
```

This method sets the state for the supplementary information flags and the minor status in MessageProp. It is not used by the application but by the GSS implementation to return this information to the caller of a per-message context method.

Parameters:

duplicate	true if the token was a duplicate of an earlier token, false otherwise
old	true if the token's validity period has expired, false otherwise
unseq	true if a later token has already been processed, false otherwise
gap	true if one or more predecessor tokens have not yet been successfully processed, false otherwise
minorStatus	the integer minor status code that the underlying mechanism wants to set
minorString	the textual representation of the minorStatus value

6.6. public class ChannelBinding

The GSS-API accommodates the concept of caller-provided channel binding information. Channel bindings are used to strengthen the quality with which peer entity authentication is provided during context establishment. They enable the GSS-API callers to bind the establishment of the security context to relevant characteristics like addresses or to application specific data.

The caller initiating the security context must determine the appropriate channel binding values to set in the GSSContext object.

Expires: May 2000

[Page 76]

The acceptor must provide an identical binding in order to validate that received tokens possess correct channel-related characteristics.

Use of channel bindings is optional in GSS-API. Since channel-binding information may be transmitted in context establishment tokens, applications should therefore not use confidential data as channel-binding components.

6.6.1. Constructors

```
public ChannelBinding(InetAddress initAddr, InetAddress acceptAddr,  
                     byte[] appData)
```

Create a ChannelBinding object with user supplied address information and data. "null" values can be used for any fields which the application does not want to specify.

Parameters:

initAddr The address of the context initiator. "null" value can be supplied to indicate that the application does not want to set this value.

acceptAddr The address of the context acceptor. "null" value can be supplied to indicate that the application does not want to set this value.

appData Application supplied data to be used as part of the channel bindings. "null" value can be supplied to indicate that the application does not want to set this value.

```
public ChannelBinding(byte[] appData)
```

Creates a ChannelBinding object without any addressing information.

Parameters:

appData Application supplied data to be used as part of the channel bindings.

6.6.2. getInitiatorAddress

```
public InetAddress getInitiatorAddress()
```


Expires: May 2000

[Page 77]

Returns the initiator's address for this channel binding. "null" is returned if the address has not been set.

6.6.3. getAcceptorAddress

```
public InetAddress getAcceptorAddress()
```

Returns the acceptor's address for this channel binding. "null" is returned if the address has not been set.

6.6.4. getApplicationData

```
public byte[] getApplicationData()
```

Returns application data being used as part of the ChannelBinding. "null" is returned if no application data has been specified for the channel binding.

6.6.5. equals

```
public boolean equals(Object obj)
```

Returns "true" if two channel bindings match.

Parameters:

obj Another channel binding to compare with.

6.7. public class Oid

This class represents Universal Object Identifiers (Oids) and their associated operations.

Oids are hierarchically globally-interpretable identifiers used within the GSS-API framework to identify mechanisms and name formats.

The structure and encoding of Oids is defined in ISOIEC-8824 and ISOIEC-8825. For example the Oid representation of Kerberos V5 mechanism is "1.2.840.113554.1.2.2"

The GSSName name class contains public static Oid objects

Expires: May 2000

[Page 78]

representing the standard name types defined in GSS-API.

6.7.1. Constructors

`public Oid(String strOid) throws GSSEException`

Creates an Oid object from a string representation of its integer components (e.g. "1.2.840.113554.1.2.2").

Parameters:

`strOid` The string representation for the oid.

`public Oid(InputStream derOid) throws GSSEException`

Creates an Oid object from its DER encoding. This refers to the full encoding including tag and length. The structure and encoding of Oids is defined in ISOIEC-8824 and ISOIEC-8825. This method is identical in functionality to its byte array counterpart.

Parameters:

`derOid` Stream containing the DER encoded oid.

`public Oid(byte[] DERoid) throws GSSEException`

Creates an Oid object from its DER encoding. This refers to the full encoding including tag and length. The structure and encoding of Oids is defined in ISOIEC-8824 and ISOIEC-8825. This method is identical in functionality to its byte array counterpart.

Parameters:

`derOid` Byte array storing a DER encoded oid.

6.7.2. toString

`public String toString()`

Returns a string representation of the oid's integer components in dot separated notation (e.g. "1.2.840.113554.1.2.2").

Expires: May 2000

[Page 79]

6.7.3. equals

```
public boolean equals(Object Obj)
```

Returns "true" if the two Oid objects represent the same oid value.

Parameters:

 obj Another Oid object to compare with.

6.7.4. getDER

```
public byte[] getDER()
```

Returns the full ASN.1 DER encoding for this oid object, which includes the tag and length.

6.7.5. containedIn

```
public boolean containedIn(Oid[] oids)
```

A utility method to test if an Oid object is contained within the supplied Oid object array.

Parameters:

 oids An array of oids to search.

6.8. public class GSSException extends Exception

This exception is thrown whenever a fatal GSS-API error occurs including mechanism specific errors. It may contain both, the major and minor, GSS-API status codes. The mechanism implementers are responsible for setting appropriate minor status codes when throwing this exception. Aside from delivering the numeric error code(s) to the caller, this class performs the mapping from their numeric values to textual representations. All Java GSS-API methods are declared throwing this exception.

All implementations are encouraged to use the Java internationalization techniques to provide local translations of the message strings.

Expires: May 2000

[Page 80]

6.8.1. Static Constants

All valid major GSS-API error code values are declared as constants in this class.

```
public static final int BAD_BINDINGS
```

Channel bindings mismatch error.

```
public static final int BAD_MECH
```

Unsupported mechanism requested error.

```
public static final int BAD_NAME
```

Invalid name provided error.

```
public static final int BAD_NAME_TYPE
```

Name of unsupported type provided error.

```
public static final int BAD_STATUS
```

Invalid status code error - this is the default status value.

```
public static final int BAD_MIC
```

Token had invalid integrity check error.

```
public static final int CONTEXT_EXPIRED
```

Specified security context expired error.

```
public static final int CREDENTIALS_EXPIRED
```

Expired credentials detected error.

```
public static final int DEFECTIVE_CREDENTIAL
```


Expires: May 2000

[Page 81]

Defective credential error.

```
public static final int DEFECTIVE_TOKEN
```

Defective token error.

```
public static final int FAILURE
```

General failure, unspecified at GSS-API level.

```
public static final int NO_CONTEXT
```

Invalid security context error.

```
public static final int NO_CRED
```

Invalid credentials error.

```
public static final int BAD_QOP
```

Unsupported QOP value error.

```
public static final int UNAUTHORIZED
```

Operation unauthorized error.

```
public static final int UNAVAILABLE
```

Operation unavailable error.

```
public static final int DUPLICATE_ELEMENT
```

Duplicate credential element requested error.

```
public static final int NAME_NOT_MN
```

Name contains multi-mechanism elements error.

Expires: May 2000

[Page 82]

```
public static final int DUPLICATE_TOKEN
```

The token was a duplicate of an earlier token. This is a fatal error code that may occur during context establishment. It is not used to indicate supplementary status values. The MessageProp object is used for that purpose.

```
public static final int OLD_TOKEN
```

The token's validity period has expired. This is a fatal error code that may occur during context establishment. It is not used to indicate supplementary status values. The MessageProp object is used for that purpose.

```
public static final int UNSEQ_TOKEN
```

A later token has already been processed. This is a fatal error code that may occur during context establishment. It is not used to indicate supplementary status values. The MessageProp object is used for that purpose.

```
public static final int GAP_TOKEN
```

An expected per-message token was not received. This is a fatal error code that may occur during context establishment. It is not used to indicate supplementary status values. The MessageProp object is used for that purpose.

6.8.2. Constructors

```
public GSSEException(int majorCode)
```

Creates a GSSEException object with a specified major code.

Parameters:

majorCode The GSS error code causing this exception to be thrown.

```
public GSSEException(int majorCode, int minorCode, String minorString)
```

Creates a GSSEException object with the specified major code, minor code, and minor code textual explanation. This constructor is to be

Expires: May 2000

[Page 83]

used when the exception is originating from the security mechanism. It allows to specify the GSS code and the mechanism code.

Parameters:

majorCode	The GSS error code causing this exception to be thrown.
minorCode	The mechanism error code causing this exception to be thrown.
minorString	The textual explanation of the mechanism error code.

6.8.3. getMajor

```
public int getMajor()
```

Returns the major code representing the GSS error code that caused this exception to be thrown.

6.8.4. getMinor

```
public int getMinor()
```

Returns the mechanism error code that caused this exception. The minor code is set by the underlying mechanism. Value of 0 indicates that mechanism error code is not set.

6.8.5. getMajorString

```
public String getMajorString()
```

Returns a string explaining the GSS major error code causing this exception to be thrown.

6.8.6. getMinorString

```
public String getMinorString()
```

Returns a string explaining the mechanism specific error code. null will be returned when no mechanism error code has been set.

Expires: May 2000

[Page 84]

6.8.7. setMinor

```
public void setMinor(int minorCode, String message)
```

Used internally by the GSS-API implementation and the underlying mechanisms to set the minor code and its textual representation.

Parameters:

minorCode The mechanism specific error code.

message A textual explanation of the mechanism error code.

6.8.8. toString

```
public String toString()
```

Returns a textual representation of both the major and minor status codes.

6.8.9. getMessage

```
public String getMessage()
```

Returns a detailed message of this exception. Overrides `Throwable.getMessage`. It is customary in Java to use this method to obtain exception information.

7. Sample Applications

Full Copyright Statement

Copyright (C) The Internet Society (1999). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for

Expires: May 2000

[Page 85]

copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

7.1. Simple GSS Context Initiator

```
import org.ietf.jgss.*;

/**
 * This is a partial sketch for a simple client program that acts
 * as a GSS context initiator. It illustrates how to use the Java
 * bindings for the GSS-API specified in
 * draft-ietf-cat-gssv2-javabind-03.txt.
 *
 * This code sketch assumes the existence of a GSS-API
 * implementation that supports the mechanism that it will need and
 * is present as a library package (org.ietf.jgss) either as part of
 * the standard JRE or in the CLASSPATH the application specifies.
 */

public class SimpleClient {

    private String serviceName; // name of peer (ie. server)
    private GSSCredential clientCred = null;
    private GSSContext context = null;
    private Oid mech; // underlying mechanism to use

    private GSSManager mgr = new GSSManager();

    ...
    ...

    private void clientActions() {

        initializeGSS();
    }
}
```

Expires: May 2000

[Page 86]

```
        establishContext();
        doCommunication();
    }

    /**
     * Acquire credentials for the client.
     */
    private void initializeGSS() {

        try {

            clientCred = mgr.createCredential(null /*default princ*/,
                GSSCredential.INDEFINITE /* max lifetime */,
                mech /* mechanism to use */,
                GSSCredential.INITIATE_ONLY /* init context */);

            print("GSSCredential created for " +
                cred.getName().toString());
            print("Credential lifetime (sec)=" +
                cred.getRemainingLifetime());
        } catch (GSSEException e) {
            print("GSS-API error in credential acquisition: "
                + e.getMessage());
            ...
        }

        ...
    }

    /**
     * Does the security context establishment with the
     * server.
     */
    private void establishContext() {

        byte[] inToken = new byte[0];
        byte[] outToken = null;

        try {

            GSSName peer = mgr.createName(serviceName,
                GSSName.NT_HOSTBASED_SERVICE);

            context = mgr.createContext(peer, mech, gssCred,
                GSSContext.INDEFINITE/*lifetime*/);
        }
    }
}
```

Expires: May 2000

[Page 87]

```
// Will need to support confidentiality
context.requestConf(true);

while (!context.isEstablished()) {

    outToken = context.initSecContext(inToken, 0,
                                      inToken.length);

    if (outToken != null)
        writeGSSToken(outToken);

    if (!context.isEstablished())
        inToken = readGSSToken();
}

GSSName peer = context.getSrcName();
print("Security context established with " + peer +
      " using underlying mechanism " + mech.toString());
} catch (GSSEException e) {
    print("GSS-API error during context establishment: "
          + e.getMessage());
    ...
    ...
}

...
...
}

/**
 * Sends some data to the server and reads back the
 * response.
 */
private void doCommunication() {
    byte[] inToken = null;
    byte[] outToken = null;
    byte[] buffer;

    // Container for multiple input-output arguments to and
    // from the per-message routines (e.g., wrap/unwrap).
    MessageProp messgInfo = new MessageProp();

    try {

        /*
         * Now send some bytes to the server to be
         * processed. They will be integrity protected but
         * not encrypted for privacy.
         */
    }
}
```

Expires: May 2000

[Page 88]

```
    */

    buffer = readFromFile();

    // Set privacy to false and use the default QOP
    messgInfo.setPrivacy(false);

    outToken = context.wrap(buffer, 0, buffer.length,
                             messgInfo);

    writeGSSToken(outToken);

    /*
     * Now read the response from the server.
     */

    inToken = readGSSToken();
    buffer = context.unwrap(inToken, 0, inToken.length,
                             messgInfo);
    // All ok if no exception was thrown!

    GSSName peer = context.getSrcName();

    print("Message from "      + peer.toString()
          + " arrived.");
    print("Was it encrypted? " +
          messgInfo.getPrivacy());
    print("Duplicate Token? "  +
          messgInfo.isDuplicateToken());
    print("Old Token? "        +
          messgInfo.isOldToken());
    print("Unsequenced Token? " +
          messgInfo.isUnseqToken());
    print("Gap Token? "        +
          messgInfo.isGapToken());

    ...
    ...

} catch (GSSEException e) {
    print("GSS-API error in per-message calls: "
          + e.getMessage());

    ...
    ...
}

...
...
```


Expires: May 2000

[Page 89]

```
    } // end of doCommunication method

    ...
    ...

} // end of class SimpleClient
```

7.2. Simple GSS Context Acceptor

```
import org.ietf.jgss.*;

/**
 * This is a partial sketch for a simple server program that acts
 * as a GSS context acceptor. It illustrates how to use the Java
 * bindings for the GSS-API specified in
 * draft-ietf-cat-gssv2-javabind-03.txt.
 *
 * This code sketch assumes the existence of a GSS-API
 * implementation that supports the mechanisms that it will need and
 * is present as a library package (org.ietf.jgss) either as part of
 * the standard JRE or in the CLASSPATH the application specifies.
 */

import org.ietf.jgss.*;

public class SimpleServer {

    private String serviceName;
    private GSSName name;
    private GSSCredential cred;

    private GSSManager mgr;

    ...
    ...

    /**
     * Wait for client connections, establish security contexts and
     * provide service.
     */
    private void loop() {

        ...
    }
}
```

Expires: May 2000

[Page 90]

```
...

mgr = new GSSManager();

name = mgr.createName(serviceName,
    GSSName.NT_HOSTBASED_SERVICE);

cred = mgr.createCredential(name,
    GSSCredential.INDEFINITE,
    null,
    GSSCredential.ACCEPT_ONLY);

// Loop infinitely
while (true) {

    Socket s = serverSock.acceptSecContext();

    // Start a new thread to serve this connection
    Thread serverThread = new ServerThread(s);
    serverThread.start();

}
}

/**
 * Inner class ServerThread whose run() method provides the
 * secure service to a connection.
 */

private class ServerThread extends Thread {

...
...

/**
 * Deals with the connection from one client. It also
 * handles all GSSException's thrown while talking to
 * this client.
 */
public void run() {

    byte[] inToken = null;
    byte[] outToken = null;
    byte[] buffer;

    GSSName peer;
```

Expires: May 2000

[Page 91]

```
// Container for multiple input-output arguments to and
// from the per-message routines (ie. wrap/unwrap).
MessageProp supplInfo = new MessageProp();

GSSContext secContext = null;

try {

    // Now do the context establishment loop

    GSSContext context = mgr.createContext(cred);

    while (!context.isEstablished()) {

        inToken = readGSSToken();

        outToken = context.acceptSecContext(inToken, 0,
                                           inToken.length);

        if (outToken != null)
            writeGSSToken(outToken);

    }

    // SimpleServer wants confidentiality to be
    // available. Check for it.
    if (!context.getConfState()){
        ...
    }

    GSSName peer = context.getSrcName();
    Oid mech = context.getMech();
    print("Security context established with " +
          peer.toString() +
          " using underlying mechanism " +
          mech.toString() +
          " from Provider " +
          context.getProvider().getName());

    // Now read the bytes sent by the client to be
    // processed.
    inToken = readGSSToken();

    // Unwrap the message
```

Expires: May 2000

[Page 92]

```
buffer = context.unwrap(inToken, 0, inToken.length,
                        supplInfo);
// All ok if no exception was thrown!

// Print other supplementary per-message status
// information

print("Message from " +
      peer.toString() + " arrived.");
print("Was it encrypted? " +
      supplInfo.getPrivacy());
print("Duplicate Token? " +
      supplInfo.isDuplicateToken());
print("Old Token? " + supplInfo.isOldToken());
print("Unsequenced Token? " +
      supplInfo.isUnseqToken());
print("Gap Token? " + supplInfo.isGapToken());

/*
 * Now process the bytes and send back an encrypted
 * response.
 */

buffer = serverProcess(buffer);

// Encipher it and send it across

supplInfo.setPrivacy(true); // privacy requested
supplInfo.setQOP(0); // default QOP
outToken = context.wrap(buffer, 0, buffer.length,
                        supplInfo);
writeGSSToken(outToken);

} catch (GSSEException e) {
    print("GSS-API Error: " + e.getMessage());
    // Alternatively, could call e.getMajorMessage()
    // and e.getMinorMessage()
    print("Abandoning security context.");

    ...
    ...
}

...
...

} // end of run method in ServerThread
```


Expires: May 2000

[Page 93]

```
    } // end of inner class ServerThread  
  
    ...  
    ...  
  
} // end of class SimpleServer
```

8. Acknowledgments

This proposed API leverages earlier work performed by the IETF's CAT WG as outlined in both [RFC 2078](#) and J. Wray's C-bindings draft for the GSS-API. Many conceptual definitions, implementation directions, and explanations have been included from the C-bindings draft.

We would like to thank Mike Eisler, Lin Ling, Ram Marti, Michael Saltz and other members of Sun's development team for their helpful input, comments and suggestions.

We would also like to thank Joe Salowey, and Michael Smith for many insightful ideas and suggestions that have contributed to this draft.

Expires: May 2000

[Page 94]

9. Bibliography

[GSSAPIV2]

J. Linn, "Generic Security Service Application Program Interface, Version 2", [RFC 2078](#), January 1997.

[GSSAPIV2-UPDATE]

J. Linn, "Generic Security Service Application Program Interface, Version 2, Update 1", IETF work in progress, Internet Draft, July 1998.

[GSSAPI-Cbind]

J. Wray, "Generic Security Service API Version 2 : C-bindings", IETF work in progress, Internet Draft, July 1998.

[KERBEROS_V5]

J. Linn, "The Kerberos Version 5 GSS-API Mechanism", [RFC 1964](#), June 1996.

[SPKM]

C. Adams, "The Simple Public-Key GSS-API Mechanism", [RFC 2025](#), October 1996.

Expires: May 2000

[Page 95]

10. Author's Address

Address comments related to this memorandum to:

<cat-ietf@mit.edu>

Jack Kabat
ValiCert, Inc.
1215 Terra Bella Avenue
Mountain View, CA
94043, USA

Phone: +1-650-567-5496
E-mail: jackk@valicert.com

Mayank Upadhyay
Sun Microsystems, Inc.
901 San Antonio Road, MS CUP02-102
Palo Alto, CA 94303

Phone: +1-408-517-5956
E-mail: mdu@eng.sun.com

Expires: May 2000

[Page 96]