

Network Working Group
Internet-Draft
Intended status: Informational
Expires: September 1, 2019

J. Roatch

C. Bormann
Universitaet Bremen TZI
February 28, 2019

Concise Binary Object Representation (CBOR) Tags for Typed Arrays
draft-ietf-cbor-array-tags-02

Abstract

The Concise Binary Object Representation (CBOR, [RFC 7049](#)) is a data format whose design goals include the possibility of extremely small code size, fairly small message size, and extensibility without the need for version negotiation.

The present document makes use of this extensibility to define a number of CBOR tags for typed arrays of numeric data, as well as two additional tags for multi-dimensional and homogeneous arrays. It is intended as the reference document for the IANA registration of the CBOR tags defined.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 1, 2019.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of

publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Terminology	3
2.	Typed Arrays	3
2.1.	Types of numbers	3
3.	Additional Array Tags	4
3.1.	Multi-dimensional Array	5
3.2.	Homogeneous Array	7
4.	Discussion	8
5.	CDDL typenames	9
6.	IANA Considerations	10
7.	Security Considerations	12
8.	References	13
8.1.	Normative References	13
8.2.	Informative References	13
	Contributors	14
	Acknowledgements	14
	Authors' Addresses	14

[1.](#) Introduction

The Concise Binary Object Representation (CBOR, [[RFC7049](#)]) provides for the interchange of structured data without a requirement for a pre-agreed schema. [RFC 7049](#) defines a basic set of data types, as well as a tagging mechanism that enables extending the set of data types supported via an IANA registry.

Recently, a simple form of typed arrays of numeric data have received interest both in the Web graphics community [[TypedArray](#)] and in the JavaScript specification [[TypedArrayES6](#)], as well as in corresponding implementations [[ArrayBuffer](#)].

Since these typed arrays may carry significant amounts of data, there is interest in interchanging them in CBOR without the need of lengthy conversion of each number in the array.

This document defines a number of interrelated CBOR tags that cover these typed arrays, as well as two additional tags for multi-dimensional and homogeneous arrays. It is intended as the reference document for the IANA registration of the tags defined.

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

The term "byte" is used in its now customary sense as a synonym for "octet". Where bit arithmetic is explained, this document uses the notation familiar from the programming language C (including C++14's `0bnnn` binary literals), except that the operator `***` stands for exponentiation.

2. Typed Arrays

Typed arrays are homogeneous arrays of numbers, all of which are encoded in a single form of binary representation. The concatenation of these representations is encoded as a single CBOR byte string (major type 2), enclosed by a single tag indicating the type and encoding of all the numbers represented in the byte string.

2.1. Types of numbers

Three classes of numbers are of interest: unsigned integers (uint), signed integers (two's complement, sint), and IEEE 754 binary floating point numbers (which are always signed). For each of these classes, there are multiple representation lengths in active use:

Length	uint	sint	float
0	uint8	sint8	binary16
1	uint16	sint16	binary32
2	uint32	sint32	binary64
3	uint64	sint64	binary128

Table 1: Length values

Here, `sintN` stands for a signed integer of exactly `N` bits (for instance, `sint16`), and `uintN` stands for an unsigned integer of exactly `N` bits (for instance, `uint32`). The name `binaryN` stands for the number form of the same name defined in IEEE 754.

Since one objective of these tags is to be able to directly ship the `ArrayBuffers` underlying the Typed Arrays without re-encoding them,

and these may be either in big endian (network byte order) or in little endian form, we need to define tags for both variants.

In total, this leads to 24 variants. In the tag, we need to express the choice between integer and floating point, the signedness (for integers), the endianness, and one of the four length values.

In order to simplify implementation, a range of tags is being allocated that allows retrieving all this information from the bits of the tag: Tag values from TBD64 to TBD87.

The value is split up into 5 bit fields: TBD0b010_f_s_e_ll, as detailed in Table 2.

Field	Use
TBD0b010	a constant such as '010', to be defined
f	0 for integer, 1 for float
s	0 for unsigned integer or float, 1 for signed integer
e	0 for big endian, 1 for little endian
ll	A number for the length (Table 1).

Table 2: Bit fields in the low 8 bits of the tag

The number of bytes in each array element can then be calculated by 2^{f+ll} (or $1 \ll (f + ll)$ in a typical programming language). (Notice that f and ll are the lsb of each nibble (4bit) in the byte.)

In the CBOR representation, the total number of elements in the array is not expressed explicitly, but implied from the length of the byte string and the length of each representation. It can be computed inversely to the previous formula: $\text{bytelen} \gg (f + ll)$.

For the uint8/sint8 values, the endianness is redundant. Only the big endian variant is used. The little endian variant of sint8 MUST NOT be used, its tag is marked as reserved. As a special case, the tag number that would have been the little endian variant of uint8 is used to signify that the numbers in the array are using clamped conversion from integers, as described in more detail in Section 7.1 of [\[TypedArrayUpdate\]](#).

3. Additional Array Tags

This specification defines three additional array tags. The Multi-dimensional Array tags can be combined with classical CBOR arrays as well as with Typed Arrays in order to build multi-dimensional arrays

with constant numbers of elements in the sub-arrays. The Homogeneous Array tag can be used to facilitate the ingestion of homogeneous classical CBOR arrays, providing performance advantages even when a Typed Array does not apply.

3.1. Multi-dimensional Array

Tag: TBD40

Data Item: array (major type 4) of two arrays, one array (major type 4) of dimensions, and one array (major type 4, a Typed Array, or a Homogeneous Array) of elements

A multi-dimensional array is represented as a tagged array that contains two (one-dimensional) arrays. The first array defines the dimensions of the multi-dimensional array (in the sequence of outer dimensions towards inner dimensions) while the second array represents the contents of the multi-dimensional array. If the second array is itself tagged as a Typed Array then the element type of the multi-dimensional array is known to be the same type as that of the Typed Array. Data in the Typed Array byte string consists of consecutive values where the last dimension is considered contiguous (row-major order).

Figure 1 shows a declaration of a two-dimensional array in the C language, a representation of that in CBOR using both a multidimensional array tag and a typed array tag.

```
uint16_t a[2][3] = {
    {2, 4, 8}, /* row 0 */
    {4, 16, 256},
};

<Tag TBD40> # multi-dimensional array tag
  82      # array(2)
    82      # array(2)
      02      # unsigned(2) 1st Dimension
      03      # unsigned(3) 2nd Dimension
    <Tag TBD65> # uint16 array
      4c      # byte string(12)
        0002 # unsigned(2)
        0004 # unsigned(4)
        0008 # unsigned(8)
        0004 # unsigned(4)
        0010 # unsigned(16)
        0100 # unsigned(256)
```

Figure 1: Multi-dimensional array in C and CBOR

Figure 2 shows the same two-dimensional array using the multidimensional array tag in conjunction with a basic CBOR array (which, with the small numbers chosen for the example, happens to be shorter).

```
<Tag TBD40> # multi-dimensional array tag
  82      # array(2)
    82      # array(2)
      02      # unsigned(2) 1st Dimension
      03      # unsigned(3) 2nd Dimension
    86      # array(6)
      02      # unsigned(2)
      04      # unsigned(4)
      08      # unsigned(8)
      04      # unsigned(4)
      10      # unsigned(16)
      19 0100 # unsigned(256)
```

Figure 2: Multi-dimensional array using basic CBOR array

Tag: TBD1040

Data Item: as with tag TBD40

Note that above arrays are in "row major" order, which is the preferred order for the purposes of this specification. An analogous representation that uses "column major" order arrays is provided under the tag TBD1040, as illustrated in Figure 3.

```
<Tag TBD1040> # multi-dimensional array tag, column major order
  82      # array(2)
    82      # array(2)
      02      # unsigned(2) 1st Dimension
      03      # unsigned(3) 2nd Dimension
    86      # array(6)
      02      # unsigned(2)
      04      # unsigned(4)
      04      # unsigned(4)
      10      # unsigned(16)
      08      # unsigned(8)
      19 0100 # unsigned(256)
```

Figure 3: Multi-dimensional array using basic CBOR array, column major order

3.2. Homogeneous Array

Tag: TBD41

Data Item: array (major type 4)

This tag provides a hint to decoders that the array tagged by it has elements that are all of the same application type. The element type of the array is thus determined by the application type of the first array element. This can be used by implementations in strongly typed languages while decoding to create native homogeneous arrays of specific types instead of ordered lists.

Which CBOR data items constitute elements of the same application type is specific to the application. However, type systems of programming languages have enough commonality that an application should be able to create portable homogeneous arrays.

Figure 4 shows an example for a homogeneous array of booleans in C++ and CBOR.

```
bool boolArray[2] = { true, false };
```

```
<Tag TBD41>  # Homogeneous Array Tag
      82      #array(2)
      F5      # true
      F4      # false
```

Figure 4: Homogeneous array in C++ and CBOR

Figure 5 extends the example with a more complex structure.

```
typedef struct {
    bool active;
    int value;
} foo;
foo myArray[2] = { {true, 3}, {true, -4} };
```

```
<Tag TBD41>
      82  # array(2)
          82  # array(2)
              F5  # true
              03  # 3
          82  # array(2)
              F5  # true
              23  # -4
```

Figure 5: Homogeneous array in C++ and CBOR

4. Discussion

Support for both little- and big-endian representation may seem out of character with CBOR, which is otherwise fully big endian. This support is in line with the intended use of the typed arrays and the objective not to require conversion of each array element.

This specification allocates a sizable chunk out of the single-byte tag space. This use of code point space is justified by the wide use of typed arrays in data interchange.

Providing a column-major order variant of the multi-dimensional array may seem superfluous to some, and useful to others. It is cheap to define the additional tag so it is available when actually needed. Allocating it out of a different number space makes the preference for row-major evident.

Applying a Homogeneous Array tag to a Typed Array would be redundant and is therefore not provided by the present specification.

5. CDDL typenames

For the use with CDDL [[I-D.ietf-cbor-cddl](#)], the typenames defined in Figure 6 are recommended:

```
ta-uint8 = #6.TBD64(bstr)
ta-uint16be = #6.TBD65(bstr)
ta-uint32be = #6.TBD66(bstr)
ta-uint64be = #6.TBD67(bstr)
ta-uint8-clamped = #6.TBD68(bstr)
ta-uint16le = #6.TBD69(bstr)
ta-uint32le = #6.TBD70(bstr)
ta-uint64le = #6.TBD71(bstr)
ta-sint8 = #6.TBD72(bstr)
ta-sint16be = #6.TBD73(bstr)
ta-sint32be = #6.TBD74(bstr)
ta-sint64be = #6.TBD75(bstr)
; reserved: #6.TBD76(bstr)
ta-sint16le = #6.TBD77(bstr)
ta-sint32le = #6.TBD78(bstr)
ta-sint64le = #6.TBD79(bstr)
ta-float16be = #6.TBD80(bstr)
ta-float32be = #6.TBD81(bstr)
ta-float64be = #6.TBD82(bstr)
ta-float128be = #6.TBD83(bstr)
ta-float16le = #6.TBD84(bstr)
ta-float32le = #6.TBD85(bstr)
ta-float64le = #6.TBD86(bstr)
ta-float128le = #6.TBD87(bstr)
homogeneous<array> = #6.TBD41(array)
multi-dim<dim, array> = #6.TBD40([dim, array])
multi-dim-column-major<dim, array> = #6.TBD1040([dim, array])
```

Figure 6: Recommended typenames for CDDL

6. IANA Considerations

IANA is requested to allocate the tags in Table 3, with the present document as the specification reference. (The reserved value is reserved for a future revision of typed array tags.)

The allocations come out of the "specification required" space (24..255), with the exception of TBD1040, which comes out of the "first come first served" space (256..).

Tag	Data Item	Semantics
TBD64	byte string	uint8 Typed Array
TBD65	byte string	uint16, big endian, Typed Array
TBD66	byte string	uint32, big endian, Typed Array
TBD67	byte string	uint64, big endian, Typed Array
TBD68	byte string	uint8 Typed Array, clamped arithmetic
TBD69	byte string	uint16, little endian, Typed Array
TBD70	byte string	uint32, little endian, Typed Array
TBD71	byte string	uint64, little endian, Typed Array
TBD72	byte string	sint8 Typed Array
TBD73	byte string	sint16, big endian, Typed Array
TBD74	byte string	sint32, big endian, Typed Array
TBD75	byte string	sint64, big endian, Typed Array
TBD76	byte string	(reserved)
TBD77	byte string	sint16, little endian, Typed Array
TBD78	byte string	sint32, little endian, Typed Array
TBD79	byte string	sint64, little endian, Typed Array
TBD80	byte string	IEEE 754 binary16, big endian, Typed Array
TBD81	byte string	IEEE 754 binary32, big endian, Typed Array
TBD82	byte string	IEEE 754 binary64, big endian, Typed Array
TBD83	byte string	IEEE 754 binary128, big endian, Typed Array
TBD84	byte string	IEEE 754 binary16, little endian, Typed Array
TBD85	byte string	IEEE 754 binary32, little endian, Typed Array
TBD86	byte string	IEEE 754 binary64, little endian, Typed Array
TBD87	byte string	IEEE 754 binary128, little endian, Typed Array
TBD40	array of two arrays*	Multi-dimensional Array, row-major order
TBD1040	array of two arrays*	Multi-dimensional Array, column-major order
TBD41	array	Homogeneous Array

Table 3: Values for Tags

*) TBD40 or TBD1040 data item: second element of outer array in data item is native CBOR array (major type 4) or Typed Array (one of Tag TBD64..TBD87)

RFC editor note: Please replace TBDnn by the tag numbers allocated by IANA throughout the document and delete this note; this also applies to the binary representation TBD0b010 in [Section 2.1](#), which becomes 0b010 if the numbers are allocated as proposed. IANA note: To make the calculations work, TDB64 to TBD87 need to come from a contiguous range the start of which is divisible by 32, which they do if the "TBD" is simply removed.

[7.](#) Security Considerations

The security considerations of [RFC 7049](#) apply; special attention is drawn to the second paragraph of [Section 8 of RFC 7049](#). The tags introduced here are not expected to raise security considerations beyond those.

8. References

8.1. Normative References

- [I-D.ietf-cbor-cddl]
Birkholz, H., Vigano, C., and C. Bormann, "Concise data definition language (CDDL): a notational convention to express CBOR and JSON data structures", [draft-ietf-cbor-cddl-07](#) (work in progress), February 2019.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC7049] Bormann, C. and P. Hoffman, "Concise Binary Object Representation (CBOR)", [RFC 7049](#), DOI 10.17487/RFC7049, October 2013, <<https://www.rfc-editor.org/info/rfc7049>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

8.2. Informative References

- [ArrayBuffer]
Mozilla Developer Network, "JavaScript typed arrays", 2013, <https://developer.mozilla.org/en-US/docs/Web/JavaScript/Typed_arrays>.
- [TypedArray]
Vukicevic, V. and K. Russell, "Typed Array Specification", February 2011, <<https://www.khronos.org/registry/typedarray/specs/1.0/>>.
- [TypedArrayES6]
"22.2 TypedArray Objects", in: ECMA-262 6th Edition, The ECMAScript 2015 Language Specification, June 2015, <<http://www.ecma-international.org/ecma-262/6.0/#sec-typedarray-objects>>.
- [TypedArrayUpdate]
Herman, D. and K. Russell, "Typed Array Specification", July 2013, <<https://www.khronos.org/registry/typedarray/specs/latest/>>.

Contributors

Glenn Engel suggested the tags for multi-dimensional arrays and homogeneous arrays, Jim Schaad reminded us that column-major order still is in use. IANA helped correct an error in a previous version.

Acknowledgements

TBD

Authors' Addresses

Johnathan Roatch

Email: jroatch@gmail.com

Carsten Bormann

Universitaet Bremen TZI

Postfach 330440

Bremen D-28359

Germany

Phone: +49-421-218-63921

Email: cabo@tzi.org

