

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: 22 October 2022

C. Bormann  
Universität Bremen TZI  
20 April 2022

Packed CBOR  
draft-ietf-cbor-packed-05

## Abstract

The Concise Binary Object Representation (CBOR, [RFC 8949](#) == STD 94) is a data format whose design goals include the possibility of extremely small code size, fairly small message size, and extensibility without the need for version negotiation.

CBOR does not provide any forms of data compression. CBOR data items, in particular when generated from legacy data models, often allow considerable gains in compactness when applying data compression. While traditional data compression techniques such as DEFLATE ([RFC 1951](#)) can work well for CBOR encoded data items, their disadvantage is that the receiver needs to uncompress the compressed form to make use of the data.

This specification describes Packed CBOR, a simple transformation of a CBOR data item into another CBOR data item that is almost as easy to consume as the original CBOR data item. A separate decompression step is therefore often not required at the receiver.

## Note to Readers

This is a working-group draft of the CBOR working group of the IETF, <https://datatracker.ietf.org/wg/cbor/about/> (<https://datatracker.ietf.org/wg/cbor/about/>). Discussion takes places on the GitHub repository <https://github.com/cbor-wg/cbor-packed> (<https://github.com/cbor-wg/cbor-packed>) and on the CBOR WG mailing list, <https://www.ietf.org/mailman/listinfo/cbor> (<https://www.ietf.org/mailman/listinfo/cbor>).

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Draft

Packed CBOR

April 2022

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 22 October 2022.

## Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">1.1.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Packed CBOR . . . . .	<a href="#">4</a>
<a href="#">2.1.</a>	Packing Tables . . . . .	<a href="#">4</a>
<a href="#">2.2.</a>	Referencing Shared Items . . . . .	<a href="#">5</a>
<a href="#">2.3.</a>	Referencing Affix Items . . . . .	<a href="#">6</a>
<a href="#">2.4.</a>	Discussion . . . . .	<a href="#">7</a>
<a href="#">3.</a>	Table Setup . . . . .	<a href="#">8</a>
<a href="#">3.1.</a>	Basic Packed CBOR . . . . .	<a href="#">9</a>
<a href="#">4.</a>	IANA Considerations . . . . .	<a href="#">10</a>
<a href="#">5.</a>	Security Considerations . . . . .	<a href="#">11</a>
<a href="#">6.</a>	References . . . . .	<a href="#">12</a>
<a href="#">6.1.</a>	Normative References . . . . .	<a href="#">12</a>
<a href="#">6.2.</a>	Informative References . . . . .	<a href="#">12</a>
<a href="#">Appendix A.</a>	Examples . . . . .	<a href="#">13</a>
	Acknowledgements . . . . .	<a href="#">17</a>
	Author's Address . . . . .	<a href="#">18</a>

## [1.](#) Introduction

The Concise Binary Object Representation (CBOR, [[STD94](#)]) is a data format whose design goals include the possibility of extremely small code size, fairly small message size, and extensibility without the need for version negotiation.

CBOR does not provide any forms of data compression. CBOR data items, in particular when generated from legacy data models, often allow considerable gains in compactness when applying data compression. While traditional data compression techniques such as DEFLATE [[RFC1951](#)] can work well for CBOR encoded data items, their disadvantage is that the receiver needs to uncompress the compressed form to make use of the data.

This specification describes Packed CBOR, a simple transformation of a CBOR data item into another CBOR data item that is almost as easy to consume as the original CBOR data item. A separate decompression step is therefore often not required at the receiver.

This document defines the Packed CBOR format by specifying the transformation from a Packed CBOR data item to the original CBOR data item; it does not define an algorithm for a packer. Different packers can differ in the amount of effort they invest in arriving at a minimal packed form; often, they simply employ the sharing that is natural for a specific application.

Packed CBOR can make use of two kinds of optimization:

- \* item sharing: substructures (data items) that occur repeatedly in the original CBOR data item can be collapsed to a simple reference to a common representation of that data item. The processing required during consumption is limited to following that reference.
- \* affix sharing: data items (strings, containers) that share a prefix or suffix (affix) can be replaced by a reference to a common affix plus the rest of the data item. For strings, the processing required during consumption is similar to following the affix reference plus that for an indefinite-length string.

A specific application protocol that employs Packed CBOR might allow both kinds of optimization or limit the representation to item

sharing only.

Packed CBOR is defined in two parts: Referencing packing tables ([Section 2](#)) and setting up packing tables ([Section 3](#)).

### [1.1](#). Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

Bormann

Expires 22 October 2022

[Page 3]

---

Internet-Draft

Packed CBOR

April 2022

Packed reference: A shared item reference or an affix reference.

Shared item reference: A reference to a shared item as defined in [Section 2.2](#).

Affix reference: A reference that combines an affix item as defined in [Section 2.3](#).

Affix: Prefix or suffix.

Packing tables: The triple of a shared item table, a prefix table, and a suffix table.

Current set: The packing tables in effect at the data item under consideration.

Expansion: The result of applying a packed reference in the context of given Packing tables.

The definitions of [[STD94](#)] apply. Specifically: The term "byte" is used in its now customary sense as a synonym for "octet"; "byte strings" are CBOR data items carrying a sequence of zero or more (binary) bytes, while "text strings" are CBOR data items carrying a sequence of zero or more Unicode code points, encoded in UTF-8 [[STD63](#)].

Where bit arithmetic is explained, this document uses the notation familiar from the programming language C (including C++14's `0bnnn` binary literals), except that, in the plain text form of this

document, the operator "^" stands for exponentiation, and, in the HTML and PDF versions, subtraction and negation are rendered as a hyphen ("-", as are various dashes).

## [2.](#) Packed CBOR

This section describes the packing tables, their structure, and how they are referenced.

### [2.1.](#) Packing Tables

At any point within a data item making use of Packed CBOR, there is a Current Set of packing tables that applies.

There are three packing tables in a Current Set:

- \* Shared item table
- \* Prefix table

- \* Suffix table

Without any table setup, all these tables are empty arrays. Table setup can cause these arrays to be non-empty, where the elements are (potentially themselves packed) data items. Each of the tables is indexed by an unsigned integer (starting from 0). Such an index may be derived from information in tags and their content as well as from CBOR simple values.

### [2.2.](#) Referencing Shared Items

Shared items are stored in the shared item table of the Current Set.

The shared data items are referenced by using the reference data items in Table 1. When reconstructing the original data item, such a reference is replaced by the referenced data item, which is then recursively unpacked.

+=====+=====+	
reference	table index
+=====+=====+	
Simple value 0-15	0-15

+-----+-----+
Tag 6(unsigned integer N)   16 + 2*N
+-----+-----+
Tag 6(negative integer N)   16 - 2*N - 1
+-----+-----+

Table 1: Referencing Shared Values

As examples in CBOR diagnostic notation ([Section 8 of \[STD94\]](#)), the first 22 elements of the shared item table are referenced by `simple(0)`, `simple(1)`, ... `simple(15)`, `6(0)`, `6(-1)`, `6(1)`, `6(-2)`, `6(2)`, `6(-3)`. (The alternation between unsigned and negative integers for even/odd table index values -- "zigzag encoding" -- makes systematic use of shorter integer encodings first.)

Taking into account the encoding of these referring data items, there are 16 one-byte references, 48 two-byte references, 512 three-byte references, 131072 four-byte references, etc. As CBOR integers can grow to very large (or very negative) values, there is no practical limit to how many shared items might be used in a Packed CBOR item.

Note that the semantics of Tag 6 depend on its tag content: An integer turns the tag into a shared item reference, whereas a string or container (map or array) turns it into a prefix reference (see Table 2). Note also that the tag content of Tag 6 may itself be packed, so it may need to be unpacked to make this determination.

### [2.3.](#) Referencing Affix Items

Prefix items are stored in the prefix table of the Current Set; suffix items are stored in the suffix table of the Current Set. We collectively call these items affix items; when referencing, which of the tables is actually used depends on whether a prefix or a suffix reference was used.

+=====+
prefix reference   table index
+=====+
Tag 6(suffix)   0
+-----+
Tag 225-255(suffix)   1-31
+-----+

Tag 28704-32767(suffix)	32-4095
+-----+	+-----+
Tag 1879052288-2147483647(suffix)	4096-268435455
+-----+	+-----+

Table 2: Referencing Prefix Values

+=====+	+=====+
suffix reference	table index
+=====+	+=====+
Tag 216-223(prefix)	0-7
+-----+	+-----+
Tag 27647-28671(prefix)	8-1023
+-----+	+-----+
Tag 1811940352-1879048191(prefix)	1024-67108863
+-----+	+-----+

Table 3: Referencing Suffix Values

Affix data items are referenced by using the data items in Table 2 and Table 3. The tag number indicates the table used (prefix or suffix) and a table index (an unsigned integer); the tag content contains a "rump item". When reconstructing the original data item, such a reference is replaced by a data item constructed from the referenced affix data item (affix, which might need to be recursively unpacked first) "concatenated" with the tag content (rump, again possibly recursively unpacked).

- \* For a rump of type array and map, the affix also needs to be an array or a map. For an array, the elements from the prefix are prepended to the rump array, while the elements from a suffix are appended. For a map, the entries in the affix are added to those of the rump; prefix and suffix references differ in how entries

with identical keys are combined: for prefix references, an entry in the rump with the same key as an entry in the affix overrides the one in the affix, while for suffix references, an entry in the affix overrides an entry in the rump that has the same key.

| NOTE: One application of the rule for prefix references is to  
 | supply default values out of a dictionary, which can then be  
 | overridden by the entries in the map supplied as the rump

| value. Note that this pattern provides no way to remove a map  
| entry from the prefix table entry.

- \* For a rump of one of the string types, the affix also needs to be one of the string types; the bytes of the strings are concatenated as specified (prefix + rump, rump + suffix). The result of the concatenation gets the type of the rump; this way a single affix can be used to build both byte and text strings, depending on what type of rump is being used.

As a contrived (but short) example, if the prefix table is ["foobar", "foob", "fo"], the following prefix references will all unpack to "foobart": 6("t"), 224("art"), 225("obart") (the last example is not an optimization).

Taking into account the encoding, there is one single-byte prefix reference, 31 ( $2^5-2^0$ ) two-byte references, 4064 ( $2^{12}-2^5$ ) three-byte references, and 26843160 ( $2^{28}-2^{12}$ ) five-byte references for prefixes. 268435455 ( $2^{28}$ ) is an artificial limit, but should be high enough that there, again, is no practical limit to how many prefix items might be used in a Packed CBOR item. The numbers for suffix references are one quarter of those, except that there is no single-byte reference and 8 two-byte references.

| Rationale: Experience suggests that prefix packing might be  
| more likely than suffix packing. Also for this reason, there  
| is no intent to spend a 1+0 tag value for suffix packing.

## [2.4.](#) Discussion

This specification uses up a large number of Simple Values and Tags, in particular one of the rare one-byte tags and two thirds of the one-byte simple values. Since the objective is compression, this is warranted only based on a consensus that this specific format could be useful for a wide area of applications, while maintaining reasonable simplicity in particular at the side of the consumer.

A maliciously crafted Packed CBOR data item might contain a reference loop. A consumer/decompressor MUST protect against that.

| Different strategies for decoding/consuming Packed CBOR are



available.  
For example:

- \* the decoder can decode and unpack the packed item, presenting an unpacked data item to the application. In this case, the onus of dealing with loops is on the decoder. (This strategy generally has the highest memory consumption, but also the simplest interface to the application.) Besides avoiding getting stuck in a reference loop, the decoder will need to control its resource allocation, as data items can "blow up" during unpacking.
- \* the decoder can be oblivious of Packed CBOR. In this case, the onus of dealing with loops is on the application, as is the entire onus of dealing with Packed CBOR.
- \* hybrid models are possible, for instance: The decoder builds a data item tree directly from the Packed CBOR as if it were oblivious, but also provides accessors that hide (resolve) the packing. In this specific case, the onus of dealing with loops is on the accessors.

In general, loop detection can be handled in a similar way in which loops of symbolic links are handled in a file system: A system-wide limit (often 31 or 40 indirections for symbolic links) is applied to any reference chase.

NOTE: The present specification does nothing to help with the packing of CBOR sequences [[RFC8742](#)]; maybe such a specification should be added.

### [3.](#) Table Setup

The packing references described in [Section 2](#) assume that packing tables have been set up.

By default, all three tables are empty (zero-length arrays).

Table setup can happen in one of two ways:

- \* By the application environment, e.g., a media type. These can define tables that amount to a static dictionary that can be used in a CBOR data item for this application environment. Note that, without this information, a data item that uses such a static dictionary can be decoded at the CBOR level, but not fully

unpacked. The table setup mechanisms provided by this document are defined in such a way that an unpacker can at least recognize if this is the case.

- \* By one or more tags enclosing the packed content. These can be defined to add to the packing tables that already apply to the tag. Usually, the semantics of the tag will be to prepend items to one of the tables. Note that it may be useful to leave a particular efficiency tier alone and only prepend to a higher tier; e.g., a tag could insert shared items at table index 16 and shift anything that was already there further down in the array while leaving index 0 to 15 alone. Explicit additions by tag can combine with application-environment supplied tables that apply to the entire CBOR data item.

For table setup, the present specification only defines a single tag, which operates by prepending to the (by default empty) tables.

```
| We could also define a tag for dictionary referencing (or
| include that in the basic packed CBOR), but the desirable
| details are likely to vary considerably between applications.
| A URI-based reference would be easy to add, but might be too
| inefficient when used in the likely combination with an ni: URI
| [RFC6920].
```

### [3.1.](#) Basic Packed CBOR

A predefined tag for packing table setup is defined in CDDL [[RFC8610](#)] as in Figure 1:

```
Basic-Packed-CBOR = #6.51([[*shared-item], [*prefix-item],
                           [*suffix-item], rump])
rump = any
prefix-item = any
suffix-item = any
shared-item = any
```

Figure 1: Packed CBOR in CDDL

(This assumes the allocation of tag number 51 for this tag.)

The arrays given as the first, second, and third element of the content of the tag 51 are prepended to the tables for shared items, prefixes, and suffixes that apply to the entire tag (by default empty tables).

The original CBOR data item can be reconstructed by recursively replacing shared, prefix, and suffix references encountered in the rump by their expansions.

Packed item references in the newly constructed (low-numbered) parts of the table need to be interpreted in the number space of that table (which includes the, now higher-numbered, inherited parts), while references in any existing, inherited (higher-numbered) part continue to use the (more limited) number space of the inherited table.

#### 4. IANA Considerations

In the registry "CBOR Tags" [[IANA.cbor-tags](#)], IANA is requested to allocate the tags defined in Table 4.

Tag	Data Item	Semantics	Reference
6	integer (for shared); text string, byte string, array, map (for prefix)	Packed CBOR: shared/ prefix	<a href="#">draft-ietf-cbor-packed</a>
225-255	text string, byte string, array, map	Packed CBOR: prefix	<a href="#">draft-ietf-cbor-packed</a>
28704-32767	text string,	Packed CBOR:	<a href="#">draft-ietf-cbor-packed</a>

	byte string, array, map	prefix	
1879052288-2147483647	text string, byte string,	Packed CBOR: prefix	<a href="#">draft-ietf-cbor-packed</a>

Bormann

Expires 22 October 2022

[Page 10]

Internet-Draft

Packed CBOR

April 2022

	array, map		
216-223	text string, byte string, array, map	Packed CBOR: suffix	<a href="#">draft-ietf-cbor-packed</a>
27647-28671	text string, byte string, array, map	Packed CBOR: suffix	<a href="#">draft-ietf-cbor-packed</a>
1811940352-1879048191	text string, byte string, array, map	Packed CBOR: suffix	<a href="#">draft-ietf-cbor-packed</a>

Table 4: Values for Tag Numbers

In the registry "CBOR Simple Values" [[IANA.cbor-simple-values](#)], IANA is requested to allocate the simple values defined in Table 5.

```

=====+=====+=====+
| Value | Semantics           | Reference           |

```

0-15	Packed CBOR: shared	<a href="#">draft-ietf-cbor-packed</a>
------	---------------------	--

Table 5: Simple Values

## 5. Security Considerations

The security considerations of [STD94] apply.

Loops in the Packed CBOR can be used as a denial of service attack, see [Section 2.4](#).

As the unpacking is deterministic, packed forms can be used as signing inputs. (Note that if external dictionaries are added to cbor-packed, this requires additional consideration.)

Bormann Expires 22 October 2022 [Page 11]

---

Internet-Draft Packed CBOR April 2022

## 6. References

### 6.1. Normative References

- [IANA.cbor-simple-values]  
IANA, "Concise Binary Object Representation (CBOR) Simple Values",  
<<https://www.iana.org/assignments/cbor-simple-values>>.
- [IANA.cbor-tags]  
IANA, "Concise Binary Object Representation (CBOR) Tags",  
<<https://www.iana.org/assignments/cbor-tags>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997,  
<<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8610] Birkholz, H., Vigano, C., and C. Bormann, "Concise Data Definition Language (CDDL): A Notational Convention to Express Concise Binary Object Representation (CBOR) and

JSON Data Structures", [RFC 8610](#), DOI 10.17487/RFC8610, June 2019, <<https://www.rfc-editor.org/info/rfc8610>>.

- [STD94] Bormann, C. and P. Hoffman, "Concise Binary Object Representation (CBOR)", STD 94, [RFC 8949](#), DOI 10.17487/RFC8949, December 2020, <<https://www.rfc-editor.org/info/rfc8949>>.

## 6.2. Informative References

- [RFC1951] Deutsch, P., "DEFLATE Compressed Data Format Specification version 1.3", [RFC 1951](#), DOI 10.17487/RFC1951, May 1996, <<https://www.rfc-editor.org/info/rfc1951>>.
- [RFC6920] Farrell, S., Kutscher, D., Dannewitz, C., Ohlman, B., Keranen, A., and P. Hallam-Baker, "Naming Things with Hashes", [RFC 6920](#), DOI 10.17487/RFC6920, April 2013, <<https://www.rfc-editor.org/info/rfc6920>>.
- [RFC7049] Bormann, C. and P. Hoffman, "Concise Binary Object Representation (CBOR)", [RFC 7049](#), DOI 10.17487/RFC7049, October 2013, <<https://www.rfc-editor.org/info/rfc7049>>.

Bormann

Expires 22 October 2022

[Page 12]

---

Internet-Draft

Packed CBOR

April 2022

- [RFC8742] Bormann, C., "Concise Binary Object Representation (CBOR) Sequences", [RFC 8742](#), DOI 10.17487/RFC8742, February 2020, <<https://www.rfc-editor.org/info/rfc8742>>.
- [STD63] Yergeau, F., "UTF-8, a transformation format of ISO 10646", STD 63, [RFC 3629](#), DOI 10.17487/RFC3629, November 2003, <<https://www.rfc-editor.org/info/rfc3629>>.

## Appendix A. Examples

The (JSON-compatible) CBOR data structure depicted in Figure 2, 400 bytes of binary CBOR, could lead to a packed CBOR data item depicted in Figure 3, ~309 bytes. Note that this particular example does not lend itself to prefix compression.

```
{ "store": {  
  "book": [  
    { "category": "reference",
```

```

    "author": "Nigel Rees",
    "title": "Sayings of the Century",
    "price": 8.95
  },
  { "category": "fiction",
    "author": "Evelyn Waugh",
    "title": "Sword of Honour",
    "price": 12.99
  },
  { "category": "fiction",
    "author": "Herman Melville",
    "title": "Moby Dick",
    "isbn": "0-553-21311-3",
    "price": 8.99
  },
  { "category": "fiction",
    "author": "J. R. R. Tolkien",
    "title": "The Lord of the Rings",
    "isbn": "0-395-19395-8",
    "price": 22.99
  }
],
"bicycle": {
  "color": "red",
  "price": 19.95
}
}

```

Figure 2: Example original CBOR data item

```

51(["price", "category", "author", "title", "fiction", 8.95, "isbn"],
  / 0      1      2      3      4      5      6 /
[], []],
[{"store": {
  "book": [
    {simple(1): "reference", simple(2): "Nigel Rees",
      simple(3): "Sayings of the Century", simple(0): simple(5)},
    {simple(1): simple(4), simple(2): "Evelyn Waugh",
      simple(3): "Sword of Honour", simple(0): 12.99},
    {simple(1): simple(4), simple(2): "Herman Melville",
      simple(3): "Moby Dick", simple(6): "0-553-21311-3",

```

```

    simple(0): simple(5)},
    {simple(1): simple(4), simple(2): "J. R. R. Tolkien",
      simple(3): "The Lord of the Rings",
      simple(6): "0-395-19395-8", simple(0): 22.99}],
    "bicycle": {"color": "red", simple(0): 19.95}}]])

```

Figure 3: Example packed CBOR data item

The (JSON-compatible) CBOR data structure below has been packed with shared item and (partial) prefix compression only.

```

{
  "name": "MyLED",
  "interactions": [
    {
      "links": [
        {
          "href":
            "http://192.168.1.103:8445/wot/thing/MyLED/rgbValueRed",
          "mediaType": "application/json"
        }
      ],
      "outputData": {
        "valueType": {
          "type": "number"
        }
      },
      "name": "rgbValueRed",
      "writable": true,
      "@type": [
        "Property"
      ]
    },
    {
      "links": [
        {
          "href":

```

```

      "http://192.168.1.103:8445/wot/thing/MyLED/rgbValueGreen",
      "mediaType": "application/json"
    }
  ],

```



```

    "outputData": {
      "valueType": {
        "type": "number"
      }
    },
    "name": "rgbValueGreen",
    "writable": true,
    "@type": [
      "Property"
    ]
  },
  {
    "links": [
      {
        "href":
          "http://192.168.1.103:8445/wot/thing/MyLED/rgbValueBlue",
        "mediaType": "application/json"
      }
    ],
    "outputData": {
      "valueType": {
        "type": "number"
      }
    },
    "name": "rgbValueBlue",
    "writable": true,
    "@type": [
      "Property"
    ]
  },
  {
    "links": [
      {
        "href":
          "http://192.168.1.103:8445/wot/thing/MyLED/rgbValueWhite",
        "mediaType": "application/json"
      }
    ],
    "outputData": {
      "valueType": {
        "type": "number"
      }
    },
    "name": "rgbValueWhite",

```

```
    "writable": true,
    "@type": [
      "Property"
    ]
  },
  {
    "links": [
      {
        "href":
          "http://192.168.1.103:8445/wot/thing/MyLED/ledOnOff",
        "mediaType": "application/json"
      }
    ],
    "outputData": {
      "valueType": {
        "type": "boolean"
      }
    },
    "name": "ledOnOff",
    "writable": true,
    "@type": [
      "Property"
    ]
  },
  {
    "links": [
      {
        "href":
"http://192.168.1.103:8445/wot/thing/MyLED/colorTemperatureChanged",
        "mediaType": "application/json"
      }
    ],
    "outputData": {
      "valueType": {
        "type": "number"
      }
    },
    "name": "colorTemperatureChanged",
    "@type": [
      "Event"
    ]
  }
],
"@type": "Lamp",
"id": "0",
"base": "http://192.168.1.103:8445/wot/thing",
"@context":
```

"http://192.168.1.102:8444/wot/w3c-wot-td-context.jsonld"

}

Figure 4: Example original CBOR data item

```
51([/shared/["name", "@type", "links", "href", "mediaType",
/ 0 1 2 3 4 /
"application/json", "outputData", {"valueType": {"type":
/ 5 6 7 /
"number"}}], ["Property"], "writable", "valueType", "type"],
/ 8 9 10 11 /
/prefix/ ["http://192.168.1.10", 6("3:8445/wot/thing"),
/ 6 225 /
225("/MyLED/"), 226("rgbValue"), "rgbValue",
/ 226 227 228 /
{simple(6): simple(7), simple(9): true, simple(1): simple(8)}],
/ 229 /
/suffix/ [],
/rump/ {simple(0): "MyLED",
"interactions": [
229({simple(2): [{simple(3): 227("Red"), simple(4): simple(5)}],
simple(0): 228("Red")}),
229({simple(2): [{simple(3): 227("Green"), simple(4): simple(5)}],
simple(0): 228("Green")}),
229({simple(2): [{simple(3): 227("Blue"), simple(4): simple(5)}],
simple(0): 228("Blue")}),
229({simple(2): [{simple(3): 227("White"), simple(4): simple(5)}],
simple(0): "rgbValueWhite"}),
{simple(2): [{simple(3): 226("ledOnOff"), simple(4): simple(5)}],
simple(6): {simple(10): {simple(11): "boolean"}}, simple(0):
"ledOnOff", simple(9): true, simple(1): simple(8)},
{simple(2): [{simple(3): 226("colorTemperatureChanged"),
simple(4): simple(5)}], simple(6): simple(7), simple(0):
"colorTemperatureChanged", simple(1): ["Event"]}],
simple(1): "Lamp", "id": "0", "base": 225(""),
"@context": 6("2:8444/wot/w3c-wot-td-context.jsonld")}]])
```

Figure 5: Example packed CBOR data item

CBOR packing was originally invented with the rest of CBOR, but did not make it into [[RFC7049](#)], the predecessor of [[STD94](#)]. Various attempts to come up with a specification over the years didn't proceed. In 2017, Sebastian Käbisch proposed investigating compact representations of W3C Thing Descriptions, which prompted the author to come up with essentially the present design.

Bormann

Expires 22 October 2022

[Page 17]

---

Internet-Draft

Packed CBOR

April 2022

#### Author's Address

Carsten Bormann  
Universität Bremen TZI  
Postfach 330440  
D-28359 Bremen  
Germany  
Phone: +49-421-218-63921  
Email: [cabo@tzi.org](mailto:cabo@tzi.org)

Bormann

Expires 22 October 2022

[Page 18]