Workgroup: Network Working Group Internet-Draft: draft-ietf-cbor-tags-oid-03 Published: 17 November 2020 Intended Status: Standards Track Expires: 21 May 2021 Authors: C. Bormann S. Leonard Universität Bremen TZI Penango, Inc. Concise Binary Object Representation (CBOR) Tags for Object Identifiers

Abstract

The Concise Binary Object Representation (CBOR, draft-ietfcbor-7049bis) is a data format whose design goals include the possibility of extremely small code size, fairly small message size, and extensibility without the need for version negotiation.

The present document defines CBOR tags for object identifiers (OIDs). It is intended as the reference document for the IANA registration of the CBOR tags so defined.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>https://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 21 May 2021.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents

(<u>https://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- <u>1</u>. <u>Introduction</u>
- 2. Object Identifiers
- <u>3. Examples</u>
- <u>4</u>. <u>Discussion</u>
- 5. Tag Factoring with OID Arrays and Maps
- 6. <u>Applications and Examples of OIDs</u>
- 7. <u>CDDL Control Operators</u>
- 8. CDDL typenames
- 9. IANA Considerations
- <u>10</u>. <u>Security Considerations</u>
- <u>11</u>. <u>References</u>
 - <u>11.1</u>. <u>Normative References</u>

<u>11.2</u>. <u>Informative References</u>

<u>Appendix A.</u> <u>Change Log</u> <u>Acknowledgments</u> <u>Authors' Addresses</u>

1. Introduction

The Concise Binary Object Representation (CBOR, [<u>I-D.ietf-</u> <u>cbor-7049bis</u>]) provides for the interchange of structured data without a requirement for a pre-agreed schema. [<u>I-D.ietf-</u> <u>cbor-7049bis</u>] defines a basic set of data types, as well as a tagging mechanism that enables extending the set of data types supported via an IANA registry.

The present document defines CBOR tags for object identifiers (OIDs, [X.660]), which many IETF protocols carry. The ASN.1 Basic Encoding Rules (BER, [X.690]) specify binary encodings of both (absolute) object identifiers and relative object identifiers. The contents of these encodings (the "value" part of BER's type-length-value structure) can be carried in a CBOR byte string. This document defines two CBOR tags that cover the two kinds of ASN.1 object identifiers encoded in this way. The tags can also be applied to arrays and maps to efficiently tag all elements of an array or all keys of a map. It is intended as the reference document for the IANA registration of the tags so defined.

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [<u>RFC2119</u>] [<u>RFC8174</u>] when, and only when, they appear in all capitals, as shown here.

The terminology of draft-ietf-cbor-7049bis applies; in particular the term "byte" is used in its now customary sense as a synonym for "octet".

2. Object Identifiers

The International Object Identifier tree [X.660] is a hierarchically managed space of identifiers, each of which is uniquely represented as a sequence of unsigned integer values [X.680]. (These integer values are called "primary integer values" in X.660 because they can be accompanied by (not necessarily unambiguous) secondary identifiers. We ignore the latter and simply use the term "integer values" here, occasionally calling out their unsignedness.)

While these sequences can easily be represented in CBOR arrays of unsigned integers, a more compact representation can often be achieved by adopting the widely used representation of object identifiers defined in BER; this representation may also be more amenable to processing by other software that makes use of object identifiers.

BER represents the sequence of unsigned integers by concatenating self-delimiting [RFC6256] representations of each of the integer values in sequence.

ASN.1 distinguishes absolute object identifiers (ASN.1 Type OBJECT IDENTIFIER), which begin at a root arc ([X.660] Clause 3.5.21), from relative object identifiers (ASN.1 Type RELATIVE-OID), which begin relative to some object identifier known from context ([X.680] Clause 3.8.63). As a special optimization, BER combines the first two integers in an absolute object identifier into one numeric identifier by making use of the property of the hierarchy that the first arc has only three integer values (0, 1, and 2), and the second arcs under 0 and 1 are limited to the integer values between 0 and 39. (The root arc joint-iso-itu-t(2) has no such limitations on its second arc.) If X and Y are the first two integer values, the single integer value actually encoded is computed as:

X * 40 + Y

The inverse transformation (again making use of the known ranges of X and Y) is applied when decoding the object identifier.

Since the semantics of absolute and relative object identifiers differ, this specification defines two tags, collectively called the "OID tags" here:

Tag TBD111: tags a byte string as the [X.690] encoding of an absolute object identifier (simply "object identifier" or "OID").

Tag TBD110: tags a byte string as the [X.690] encoding of a relative object identifier (also "relative OID"). Since the encoding of each number is the same as for [RFC6256] Self-Delimiting Numeric Values (SDNVs), this tag can also be used for tagging a byte string that contains a sequence of zero or more SDNVs.

Tag TBD112: structurally like TBD110, but understood to be relative to 1.3.6.1.4.1 (IANA Private Enterprise Number OID). Hence, the semantics of the result are that of an absolute object identifier.

2.1. Requirements on the byte string being tagged

To form a valid tag, a byte string tagged by TBD111, TBD110, or TBD112 MUST be a syntactically valid BER representation of an object identifier: A concatenation of zero or more SDNV values, where each SDNV value is a sequence of one or more bytes that all have their most significant bit set, except for the last byte, where it must be unset; the first byte of each SDNV cannot be 0x80 (which would be a leading zero in SDNV's base-128 arithmetic).

In other words:

*its first byte, and any byte that follows a byte that has the most significant bit unset, MUST NOT be 0x80 (this requirement requires expressing the integer values in their shortest form, with no leading zeroes)

*its last byte MUST NOT have the most significant bit set (this requirement excludes an incomplete final integer value)

If either of these invalid conditions are encountered, the tag is invalid.

[X.680] restricts RELATIVE-OID values to have at least one arc, i.e., their encoding would have at least one SDNV. This specification permits empty relative object identifiers; they may still be excluded by application semantics.

To facilitate the search for specific object ID values, it is RECOMMENDED that definite length encoding (see Section 3.2.3 of [<u>I-D.ietf-cbor-7049bis</u>]) is used for the byte strings used as tag content for these tags.

The valid set of byte strings can also be expressed using regular expressions on bytes, using no specific notation but resembling [PCRE]. Unlike typical regular expressions that operate on character

sequences, the following regular expressions take bytes as their domain, so they can be applied directly to CBOR byte strings.

For byte strings with tag TBD111:

/^(([\x81-\xFF][\x80-\xFF]*)?[\x00-\x7F])+\$/

For byte strings with tag TBD110 or TBD112:

/^(([\x81-\xFF][\x80-\xFF]*)?[\x00-\x7F])*\$/

A tag with tagged content that does not conform to the applicable regexp is invalid.

3. Examples

3.1. Encoding of the SHA-256 OID

ASN.1 Value Notation: { joint-iso-itu-t(2) country(16) us(840)
 organization(1) gov(101) csor(3) nistalgorithm(4) hashalgs(2)
 sha256(1) }

Dotted Decimal Notation: 2.16.840.1.101.3.4.2.1

06											#	UNIVERSAL TAG 6
	09										#	9 bytes, primitive
		60	86	48	01	65	03	04	02	01	#	X.690 Clause 8.19
#			:	840	1		3	4	2	1		show component encoding
#	2	16			1	L01						

Figure 1: SHA-256 OID in BER

D8 6F # tag(111) 49 # 0b010_01001: mt 2, 9 bytes 60 86 48 01 65 03 04 02 01 # X.690 Clause 8.19

Figure 2: SHA-256 OID in CBOR

3.2. Encoding of a MIB Relative OID

Given some OID (e.g., lowpanMib, assumed to be 1.3.6.1.2.1.226 [RFC7388]), to which the following is added:

ASN.1 Value Notation: { lowpanObjects(1) lowpanStats(1)
 lowpanOutTransmits(29) }

Dotted Decimal Notation: .1.1.29

0D				# UNIVERSAL TAG 13
	03			# 3 bytes, primitive
	01	01	1D	# X.690 Clause 8.20
#	1	1	29	show component encoding

Figure 3: MIB relative object identifier, in BER

D8 6E # tag(110) 43 # 0b010_01001: mt 2 (bstr), 3 bytes 01 01 1D # X.690 Clause 8.20

Figure 4: MIB relative object identifier, in CBOR

This relative OID saves seven bytes compared to the full OID encoding.

4. Discussion

Staying close to the way object identifiers are encoded in ASN.1 BER makes back-and-forth translation easy; otherwise we would choose a more efficient encoding. Object identifiers in IETF protocols are serialized in dotted decimal form or BER form, so there is an advantage in not inventing a third form. Also, expectations of the cost of encoding object identifiers are based on BER; using a different encoding might not be aligned with these expectations. If additional information about an OID is desired, lookup services such as the OID Resolution Service (ORS) [X.672] and the OID Repository [OID-INF0] are available.

5. Tag Factoring with OID Arrays and Maps

OID tags can tag byte strings (as discussed above), but also CBOR arrays and maps. The idea in the latter case is that the tag is factored out from each individual item in the container; the tag is placed on the array or map instead.

When an OID tag is applied to an array, it means that the respective tag is imputed to all elements of the array that are byte strings, arrays, or maps. (There is no effect on other elements, including text strings or tags.) For example, when an array is tagged with TBD111, every array element that is a byte string is an OID, and every element that is an array or map is in turn treated as discussed here.

When an OID tag is applied to a map, it means that the respective tag is imputed to all keys in the map that are byte strings, arrays, or maps; again, there is no effect on keys of other major types. Note that there is also no effect on the values in the map. As a result of these rules, tag factoring in nested arrays and maps is supported. For example, a 3-dimensional array of OIDs can be composed by using a single TBD111 tag containing an array of arrays of arrays of byte strings. All such byte strings are then considered OIDs.

6. Applications and Examples of OIDs

6.1. X.500 Distinguished Name

Consider the X.500 distinguished name:

Attribute Types	Attribute Values
c (2.5.4.6)	US
1 (2.5.4.7)	Los Angeles
s (2.5.4.8)	CA
<pre>postalCode (2.5.4.17)</pre>	90013
street (2.5.4.9)	532 S Olive St
<pre>businessCategory (2.5.4.15)</pre>	Public Park
buildingName (0.9.2342.19200300.100.1.48)	Pershing Square
Table 1: Example X.500 Distinguis	hed Name

<u>Table 1</u> has four "relative distinguished names" (RDNs). The country and street RDNs are single-valued. The second and fourth RDNs are multi-valued.

The equivalent representations in CBOR diagnostic notation and CBOR are:

Figure 5: Distinguished Name, in CBOR Diagnostic Notation

d8	6f				#	tag(111)
	84				#	array(4)
		a1			#	map(1)
			43	550406	#	2.5.4.6 (4)
			62		#	text(2)
				5553	#	"US"
		a3			#	map(3)
			43	550407		2.5.4.7 (4)
			6b			text(11)
				4c6f7320416e67656c6573		"Los Angeles"
			43	550408		2.5.4.8 (4)
			62			text(2)
				4341	#	"CA"
			43	550411	#	2.5.4.17 (4)
			65		#	text(5)
				3930303133	#	"90013"
		a1			#	map(1)
			43	550409	#	2.5.4.9 (4)
			6e		#	text(14)
				3533322053204f6c697665205374	#	"532 S Olive St"
		a2			#	map(2)
			43	55040f	#	2.5.4.15 (4)
			6b		#	text(11)
				5075626c6963205061726b	#	"Public Park"
			4a	0992268993f22c640130 # 0.9.2	234	42.19200300.100.1.48 (11)
			6f			text(15)
				5065727368696e6720537175617265	#	"Pershing Square"

Figure 6: Distinguished Name, in CBOR (109 bytes)

(This example encoding assumes that all attribute values are UTF-8 strings, or can be represented as UTF-8 strings with no loss of information.)

7. CDDL Control Operators

CDDL specifications may want to specify the use of SDNVs or SDNV sequences (as defined for the tag content for TBD110). This document introduces two new control operators that can be applied to a target value that is a byte string:

*.sdnv, with a control type that contains unsigned integers. The byte string is specified to be encoded as an [<u>RFC6256</u>] SDNV (BER encoding) for the matching values of the control type.

*.sdnvseq, with a control type that contains arrays of unsigned integers. The byte string is specified to be encoded as a sequence of [<u>RFC6256</u>] SDNVs (BER encoding) that decodes to an array of unsigned integers matching the control type.

```
*.oid, like .sdnvseq, except that the X*40+Y translation for
      absolute OIDs is included (see Figure 8).
   Figure 7 shows an example for the use of .sdnvseq for a part of a
   structure using OIDs that could be used in Figure 6; Figure 8 shows
   the same with the .oid operator.
country-rdn = {country-oid => country-value}
country-oid = bytes .sdnvseq [85, 4, 6]
country-value = text .size 2
                        Figure 7: Using .sdnvseq
country-rdn = {country-oid => country-value}
country-oid = bytes .oid [2, 5, 4, 6]
country-value = text .size 2
                          Figure 8: Using .oid
   Note that the control type need not be a literal; e.g., bytes .oid
   [2, 5, 4, *uint] matches all OIDs inside OID arc 2.5.4,
   attributeType.
8. CDDL typenames
   For the use with CDDL [<u>RFC8610</u>], the typenames defined in Figure 9
   are recommended:
oid = #6.111(bstr)
```

roid = #6.110(bstr)
pen = #6.112(bstr)

Figure 9: Recommended typenames for CDDL

9. IANA Considerations

9.1. CBOR Tags

IANA is requested to assign the CBOR tags in <u>Table 2</u>, with the present document as the specification reference.

Тад	Data Item	Semantics
TBD111	byte string or array or map	object identifier (BER encoding)
TBD110	byte string or array or map	relative object identifier (BER encoding); SDNV [<u>RFC6256</u>] sequence

Тад	Data Item	Semantics
TBD112	byte string or	object identifier (BER encoding),
	array or map	relative to 1.3.6.1.4.1

Table 2: Values for New Tags

9.2. CDDL Control Operators

IANA is requested to assign the CDDL Control Operators in Table 3, with the present document as the specification reference.

Name	Reference						
.sdnv	[this document, <u>Section 7</u>]						
.sdnvseq	[this document, <u>Section 7</u>]						
.oid	[this document, <u>Section 7</u>]						
Table 3: New CDDL Operators							

10. Security Considerations

The security considerations of [<u>I-D.ietf-cbor-7049bis</u>] apply.

The encodings in Clauses 8.19 and 8.20 of [X.690] are quite compact and unambiguous, but MUST be followed precisely to avoid security pitfalls. In particular, the requirements set out in <u>Section 2.1</u> of this document need to be followed; otherwise, an attacker may be able to subvert a checking process by submitting alternative representations that are later taken as the original (or even something else entirely) by another decoder supposed to be protected by the checking process.

OIDs and relative OIDs can always be treated as opaque byte strings. Actually understanding the structure that was used for generating them is not necessary, and, except for checking the structure requirements, it is strongly NOT RECOMMENDED to perform any processing of this kind (e.g., converting into dotted notation and back) unless absolutely necessary. If the OIDs are translated into other representations, the usual security considerations for nontrivial representation conversions apply; the integer values are unlimited in range.

11. References

11.1. Normative References

[I-D.ietf-cbor-7049bis]

Bormann, C. and P. Hoffman, "Concise Binary Object Representation (CBOR)", Work in Progress, Internet-Draft, draft-ietf-cbor-7049bis-16, 30 September 2020, <<u>http://</u> www.ietf.org/internet-drafts/draft-ietfcbor-7049bis-16.txt>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/ RFC2119, March 1997, <<u>https://www.rfc-editor.org/info/</u> rfc2119>.
- [RFC6256] Eddy, W. and E. Davies, "Using Self-Delimiting Numeric Values in Protocols", RFC 6256, DOI 10.17487/RFC6256, May 2011, <<u>https://www.rfc-editor.org/info/rfc6256</u>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<u>https://www.rfc-editor.org/info/rfc8174</u>>.
- [RFC8610] Birkholz, H., Vigano, C., and C. Bormann, "Concise Data Definition Language (CDDL): A Notational Convention to Express Concise Binary Object Representation (CBOR) and JSON Data Structures", RFC 8610, DOI 10.17487/RFC8610, June 2019, <<u>https://www.rfc-editor.org/info/rfc8610</u>>.
- [X.660] International Telecommunications Union, "Information technology – Procedures for the operation of object identifier registration authorities: General procedures and top arcs of the international object identifier tree", ITU-T Recommendation X.660, July 2011.
- [X.680] International Telecommunications Union, "Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation", ITU-T Recommendation X. 680, August 2015.
- [X.690] International Telecommunications Union, "Information technology – ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)", ITU-T Recommendation X.690, August 2015.

11.2. Informative References

- [OID-INFO] Orange SA, "OID Repository", 2016, <<u>http://www.oidinfo.com/</u>>.
- [PCRE] Ho, A., "PCRE Perl Compatible Regular Expressions", 2018, <<u>http://www.pcre.org/</u>>.
- [RFC7388] Schoenwaelder, J., Sehgal, A., Tsou, T., and C. Zhou, "Definition of Managed Objects for IPv6 over Low-Power Wireless Personal Area Networks (6LoWPANs)", RFC 7388,

DOI 10.17487/RFC7388, October 2014, <<u>https://www.rfc-</u>editor.org/info/rfc7388>.

[X.672] International Telecommunications Union, "Information technology – Open systems interconnection – Object identifier resolution system", ITU-T Recommendation X. 672, August 2010.

Appendix A. Change Log

This section is to be removed before publishing as an RFC.

A.1. Changes from -01 to -02

Minor editorial changes, remove some remnants, ready for WGLC.

A.2. Changes from -00 to -01

Clean up OID tag factoring.

A.3. Changes from -07 (bormann) to -00 (ietf)

Resubmitted as WG draft after adoption.

A.4. Changes from -06 to -07

Reduce the draft back to its basic mandate: Describe CBOR tags for what is colloquially know as ASN.1 Object IDs.

A.5. Changes from -05 to -06

Refreshed the draft to the current date ("keep-alive").

A.6. Changes from -04 to -05

Discussed UUID usage in CBOR, and incorporated fixes proposed by Olivier Dubuisson, including fixes regarding OID nomenclature.

A.7. Changes from -03 to -04

Changes occurred based on limited feedback, mainly centered around the abstract and introduction, rather than substantive technical changes. These changes include:

*Changed the title so that it is about tags and techniques.

*Rewrote the abstract to describe the content more accurately, and to point out that no changes to the wire protocol are being proposed. *Removed "ASN.1" from "object identifiers", as OIDs are independent of ASN.1.

*Rewrote the introduction to be more about the present text.

*Proposed a concise OID arc.

*Provided binary regular expression forms for OID validation.

*Updated IANA registration tables.

A.8. Changes from -02 to -03

Many significant changes occurred in this version. These changes include:

*Expanded the draft scope to be a comprehensive CBOR update.

*Added OID-related sections: OID Enumerations, OID Maps and Arrays, and Applications and Examples of OIDs.

*Added Tag 36 update (binary MIME, better definitions).

*Added stub/experimental sections for X.690 Series Tags (tag <<X>>) and Regular Expressions (tag 35).

*Added technique for representing sets and multisets.

*Added references and fixed typos.

Acknowledgments

Jim Schaad provided a review of this document.

Authors' Addresses

Carsten Bormann Universität Bremen TZI Postfach 330440 D-28359 Bremen Germany

Phone: <u>+49-421-218-63921</u> Email: <u>cabo@tzi.org</u>

Sean Leonard Penango, Inc. 5900 Wilshire Boulevard 21st Floor Los Angeles, CA, 90036 United States of America

Email: dev+ietf@seantek.com
URI: http://www.penango.com/