

Workgroup: Network Working Group

Internet-Draft: draft-ietf-cbor-time-tag-00

Published: 19 May 2021

Intended Status: Informational

Expires: 20 November 2021

Authors: C. Bormann

B. Gamari

H. Birkholz

Universität Bremen TZI

Well-Typed

Fraunhofer SIT

Concise Binary Object Representation (CBOR) Tags for Time, Duration, and Period

Abstract

The Concise Binary Object Representation (CBOR, RFC 8949) is a data format whose design goals include the possibility of extremely small code size, fairly small message size, and extensibility without the need for version negotiation.

In CBOR, one point of extensibility is the definition of CBOR tags. RFC 8949 defines two tags for time: CBOR tag 0 (RFC3339 time as a string) and tag 1 (Posix time as int or float). Since then, additional requirements have become known. The present document defines a CBOR tag for time that allows a more elaborate representation of time, as well as related CBOR tags for duration and time period. It is intended as the reference document for the IANA registration of the CBOR tags defined.

Note to Readers

Version -00 of the individual submission that led to the present draft opened up the possibilities provided by extended representations of time in CBOR. Version -01 consolidated this draft to non-speculative content, the normative parts of which were believed will stay unchanged during further development of the draft. This version was provided to aid the registration of the CBOR tag immediately needed. Further versions of the individual submission made use of the IANA allocations registered and made other editorial updates. Now a WG document, future versions could re-introduce some of the material from the initial submission, but in a more concrete form.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 20 November 2021.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction
1.1.	Terminology
2.	Objectives
3.	Time Format
3.1.	Key 1
3.2.	Keys 4 and 5
3.3.	Keys -3, -6, -9, -12, -15, -18
3.4.	Key -1: Time Scale
3.5.	Clock Quality
3.5.1.	ClockClass (Key -2)
3.5.2.	ClockAccuracy (Key -4)
3.5.3.	OffsetScaledLogVariance (Key -5)
3.5.4.	Uncertainty (Key -7)
3.5.5.	Guarantee (Key -8)
4.	Duration Format
5.	Period Format
6.	CDDL typenames
7.	IANA Considerations
8.	Security Considerations
9.	References
9.1.	Normative References
9.2.	Informative References
	Acknowledgements
	Authors' Addresses

1. Introduction

The Concise Binary Object Representation (CBOR, [[RFC8949](#)]) provides for the interchange of structured data without a requirement for a pre-agreed schema. RFC 8949 defines a basic set of data types, as well as a tagging mechanism that enables extending the set of data types supported via an IANA registry.

(TBD: Expand on text from abstract here.)

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

The term "byte" is used in its now customary sense as a synonym for "octet". Where bit arithmetic is explained, this document uses the notation familiar from the programming language C (including C++14's `0bnnn` binary literals), except that the operator `***` stands for exponentiation.

2. Objectives

For the time tag, the present specification addresses the following objectives that go beyond the original tags 0 and 1:

- *Additional resolution for epoch-based time (as in tag 1). CBOR tag 1 only provides for integer and up to binary64 floating point representation of times, limiting resolution to approximately microseconds at the time of writing (and progressively becoming worse over time).

- *Indication of time scale. Tags 0 and 1 are for UTC; however, some interchanges are better performed on TAI. Other time scales may be registered once they become relevant (e.g., one of the proposed successors to UTC that might no longer use leap seconds, or a scale based on smeared leap seconds).

Not currently addressed, but possibly covered by the definition of additional map keys for the map inside the tag:

- *Direct representation of natural platform time formats. Some platforms use epoch-based time formats that require some computation to convert them into the representations allowed by tag 1; these computations can also lose precision and cause ambiguities. (TBD: The present specification does not take a position on whether tag 1 can be "fixed" to include, e.g.,

Decimal or BigFloat representations. It does define how to use these with the extended time format.)

*Additional indication of intents about the interpretation of the time given, in particular for future times. Intents might include information about time zones, daylight savings times, etc.

Additional tags are defined for durations and periods.

3. Time Format

An extended time is indicated by CBOR tag 1001, which tags a map data item (CBOR major type 5). The map may contain integer (major types 0 and 1) or text string (major type 3) keys, with the value type determined by each specific key. Implementations **MUST** ignore key/value types they do not understand for negative integer and text string values of the key. Not understanding key/value for unsigned keys is an error.

The map must contain exactly one unsigned integer key, which specifies the "base time", and may also contain one or more negative integer or text-string keys, which may encode supplementary information such as:

- *a higher precision time offset to be added to the base time,

- *a reference time scale and epoch different from the default UTC and 1970-01-01

- *information about clock quality parameters, such as source, accuracy, and uncertainty

Future keys may add:

- *intent information such as timezone and daylight savings time, and/or possibly positioning coordinates, to express information that would indicate a local time.

While this document does not define supplementary text keys, a number of unsigned and negative-integer keys are defined below.

3.1. Key 1

Key 1 indicates a value that is exactly like the data item that would be tagged by CBOR tag 1 (Posix time [[TIME_T](#)] as int or float). The time value indicated by the value under this key can be further modified by other keys.

3.2. Keys 4 and 5

Keys 4 and 5 are like key 1, except that the data item is an array as defined for CBOR tag 4 or 5, respectively. This can be used to include a Decimal or Bigfloat epoch-based float [TIME T] in an extended time.

3.3. Keys -3, -6, -9, -12, -15, -18

The keys -3, -6, -9, -12, -15 and -18 indicate additional decimal fractions by giving an unsigned integer (major type 0) and scaling this with the scale factor 1e-3, 1e-6, 1e-9, 1e-12, 1e-15, and 1e-18, respectively (see Table 1). More than one of these keys **MUST NOT** be present in one extended time data item. These additional fractions are added to a base time in seconds [SI-SECOND] indicated by a Key 1, which then **MUST** also be present and **MUST** have an integer value.

Key	meaning	example usage
-3	milliseconds	Java time
-6	microseconds	(old) UNIX time
-9	nanoseconds	(new) UNIX time
-12	picoseconds	Haskell time
-15	femtoseconds	(future)
-18	attoseconds	(future)

Table 1: Key for decimally scaled Fractions

3.4. Key -1: Time Scale

Key -1 is used to indicate a time scale. The value 0 indicates UTC, with the POSIX epoch [TIME T]; the value 1 indicates TAI, with the PTP (Precision Time Protocol) epoch [IEEE1588-2008].

If key -1 is not present, time scale value 0 is implied. Additional values can be registered in the (TBD define name for time scale registry); values **MUST** be integers or text strings.

(Note that there should be no time scales "GPS" or "NTP" -- instead, the time should be converted to TAI or UTC using a single addition or subtraction.)

$$\begin{aligned}t_{utc} &= t_{ntp} - 2208988800 \\t_{tai} &= t_{gps} + 315964819\end{aligned}$$

Figure 1: Converting Common Offset Time Scales

3.5. Clock Quality

A number of keys are defined to indicate the quality of clock that was used to determine the point in time.

The first three are analogous to clock-quality-grouping in [RFC8575], which is in turn based on the definitions in [IEEE1588-2008]; two more are specific to this document.

```
ClockQuality-group = (  
  ? ClockClass => uint .size 1 ; PTP/RFC8575  
  ? ClockAccuracy => uint .size 1 ; PTP/RFC8575  
  ? OffsetScaledLogVariance => uint .size 2 ; PTP/RFC8575  
  ? Uncertainty => ~time/~duration  
  ? Guarantee => ~time/~duration  
)  
ClockClass = -2  
ClockAccuracy = -4  
OffsetScaledLogVariance = -5  
Uncertainty = -7  
Guarantee = -8
```

3.5.1. ClockClass (Key -2)

Key -2 (ClockClass) can be used to indicate the clock class as per Table 5 of [IEEE1588-2008]. It is defined as a one-byte unsigned integer as that is the range defined there.

3.5.2. ClockAccuracy (Key -4)

Key -4 (ClockAccuracy) can be used to indicate the clock accuracy as per Table 6 of [IEEE1588-2008]. It is defined as a one-byte unsigned integer as that is the range defined there. The range between 32 and 47 is a slightly distorted logarithmic scale from 25 ns to 1 s (see Figure 2); the number 254 is the value to be used if an unknown accuracy needs to be expressed.

$$enum_{acc} \approx 48 + \left\lceil 2 \cdot \log_{10} \frac{acc}{s} - \epsilon \right\rceil$$

Figure 2: Approximate conversion from accuracy to accuracy enumeration value

3.5.3. OffsetScaledLogVariance (Key -5)

Key -5 (OffsetScaledLogVariance) can be used to represent the variance exhibited by the clock when it has lost its synchronization

with an external reference clock. The details for the computation of this characteristic are defined in Section 7.6.3 of [[IEEE1588-2008](#)].

3.5.4. Uncertainty (Key -7)

Key -7 (Uncertainty) can be used to represent a known measurement uncertainty for the clock, as a numeric value in seconds or as a duration ([Section 4](#)).

For this document, uncertainty is defined as in Section 2.2.3 of [[GUM](#)]: "parameter, associated with the result of a measurement, that characterizes the dispersion of the values that could reasonably be attributed to the measurand". More specifically, the value for this key represents the extended uncertainty for $k = 2$, in seconds.

3.5.5. Guarantee (Key -8)

Key -8 (Guarantee) can be used to represent a stated guarantee for the accuracy of the point in time, as a numeric value in seconds or as a duration ([Section 4](#)) representing the maximum allowed deviation from the true value.

While such a guarantee is unattainable in theory, existing standards such as [[RFC3161](#)] stipulate the representation of such guarantees, and therefore this format provides a way to represent them as well; the time value given is nominally guaranteed to not deviate from the actual time by more than the value of the guarantee, in seconds.

4. Duration Format

A duration is the length of an interval of time. Durations in this format are given in SI seconds, possibly adjusted for conventional corrections of the time scale given (e.g., leap seconds).

Except for using Tag 1002 instead of 1001, durations are structurally identical to time values. Semantically, they do not measure the time elapsed from a given epoch, but from the start to the end of (an otherwise unspecified) interval of time.

In combination with an epoch identified in the context, a duration can also be used to express an absolute time.

(TBD: Clearly, ISO8601 durations are rather different; we do not want to use these.)

5. Period Format

A period is a specific interval of time, specified as either two times giving the start and the end of that interval, or as one of these two plus a duration.

They are given as an array of unwrapped time and duration elements, tagged with Tag 1003:

```
Period = #6.1003([
  start: ~Time / null
  end: ~Time / null
  ? duration: ~Duration / null
])
```

If the third array element is not given, the duration element is null. Exactly two out of the three elements must be non-null, this can be clumsily expressed in CDDL as:

```
Period = #6.1003([
  (start: ~Time,
    ((end: ~Time,
      ? duration: null) //
    (end: null,
      duration: ~Duration))) //
  (start: null,
    end: ~Time,
    duration: ~Duration)
])
```

(Issue: should start/end be given the two-element treatment, or start/duration?)

6. CDDL typenames

For the use with the CBOR Data Definition Language, CDDL [[RFC8610](#)], the type names defined in [Figure 3](#) are recommended:

```
etime = #6.1001({* (int/tstr) => any})
duration = #6.1002({* (int/tstr) => any})
period = #6.1003([~etime/null, ~etime/null, ~duration/null])
```

Figure 3: Recommended type names for CDDL

7. IANA Considerations

In the registry [[IANA.cbor-tags](#)], IANA has allocated the tags in [Table 2](#) from the FCFS space, with the present document as the specification reference.

Tag	Data Item	Semantics
1001	map	[RFCthis] extended time
1002	map	[RFCthis] duration
1003	array	[RFCthis] period

Table 2: Values for Tags

IANA is requested to change the "Data Item" column for Tag 1003 from "map" to "array".

(TBD: Add registry for time scales. Add registry for map keys and allocation policies for additional keys.)

8. Security Considerations

The security considerations of RFC 8949 apply; the tags introduced here are not expected to raise security considerations beyond those.

Time, of course, has significant security considerations; these include the exploitation of ambiguities where time is security relevant (e.g., for freshness or in a validity span) or the disclosure of characteristics of the emitting system (e.g., time zone, or clock resolution and wall clock offset).

9. References

9.1. Normative References

- [GUM] Joint Committee for Guides in Metrology, "Evaluation of measurement data – Guide to the expression of uncertainty in measurement", JCGM 100:2008, September 2008, <<https://www.bipm.org/en/publications/guides/gum.html>>.
- [IANA.cbor-tags] IANA, "Concise Binary Object Representation (CBOR) Tags", <<http://www.iana.org/assignments/cbor-tags>>.
- [IEEE1588-2008] IEEE, "1588-2008 - IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems", July 2008, <<http://standards.ieee.org/findstds/standard/1588-2008.html>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/

RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

[RFC8610] Birkholz, H., Vigano, C., and C. Bormann, "Concise Data Definition Language (CDDL): A Notational Convention to Express Concise Binary Object Representation (CBOR) and JSON Data Structures", RFC 8610, DOI 10.17487/RFC8610, June 2019, <<https://www.rfc-editor.org/info/rfc8610>>.

[RFC8949] Bormann, C. and P. Hoffman, "Concise Binary Object Representation (CBOR)", STD 94, RFC 8949, DOI 10.17487/RFC8949, December 2020, <<https://www.rfc-editor.org/info/rfc8949>>.

[SI-SECOND] International Organization for Standardization (ISO), "Quantities and units – Part 3: Space and time", ISO 80000-3, 1 March 2006.

[TIME_T] The Open Group Base Specifications, "Vol. 1: Base Definitions, Issue 7", Section 4.15 'Seconds Since the Epoch', IEEE Std 1003.1-2008, 2016 Edition, 2016, <http://pubs.opengroup.org/onlinepubs/9699919799/basedefs/V1_chap04.html#tag_04_16>.

9.2. Informative References

[RFC3161] Adams, C., Cain, P., Pinkas, D., and R. Zuccherato, "Internet X.509 Public Key Infrastructure Time-Stamp Protocol (TSP)", RFC 3161, DOI 10.17487/RFC3161, August 2001, <<https://www.rfc-editor.org/info/rfc3161>>.

[RFC8575] Jiang, Y., Ed., Liu, X., Xu, J., and R. Cummings, Ed., "YANG Data Model for the Precision Time Protocol (PTP)", RFC 8575, DOI 10.17487/RFC8575, May 2019, <<https://www.rfc-editor.org/info/rfc8575>>.

Acknowledgements

Authors' Addresses

Carsten Bormann
Universität Bremen TZI
Postfach 330440
D-28359 Bremen
Germany

Phone: [+49-421-218-63921](tel:+49-421-218-63921)

Email: cabo@tzi.org

Ben Gamari

Well-Typed

117 Middle Rd.

Portsmouth, NH 03801

United States

Email: ben@well-typed.com

Henk Birkholz

Fraunhofer Institute for Secure Information Technology

Rheinstrasse 75

64295 Darmstadt

Germany

Email: henk.birkholz@sit.fraunhofer.de