

Network Working Group  
Internet Draft  
Intended status: Standards Track  
Expires: December 2010

G. Bernstein  
Grotto Networking  
Y. Lee  
D. Li  
Huawei  
W. Imajuku  
NTT

June 9, 2010

## General Network Element Constraint Encoding for GMPLS Controlled Networks

[draft-ietf-ccamp-general-constraint-encode-02.txt](#)

### Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on December 9, 2010.

### Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

---

Internet-Draft   General Network Element Constraint Encoding   June 2010

This document is subject to [BCP 78](http://trustee.ietf.org/license-info) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Abstract

Generalized Multiprotocol Label Switching can be used to control a wide variety of technologies. In some of these technologies network elements and links may impose additional routing constraints such as asymmetric switch connectivity, non-local label assignment, and label range limitations on links.

This document provides efficient, protocol-agnostic encodings for general information elements representing connectivity and label constraints as well as label availability. It is intended that protocol-specific documents will reference this memo to describe how information is carried for specific uses.

## Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC-2119](http://tools.ietf.org/html/rfc2119) [[RFC2119](http://tools.ietf.org/html/rfc2119)].

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction.....</a>	<a href="#">3</a>
<a href="#">1.1.</a>	<a href="#">Node Switching Asymmetry Constraints.....</a>	<a href="#">4</a>
<a href="#">1.2.</a>	<a href="#">Non-Local Label Assignment Constraints.....</a>	<a href="#">4</a>
<a href="#">2.</a>	<a href="#">Extension Encoding Usage Recommendations.....</a>	<a href="#">5</a>
<a href="#">2.1.</a>	<a href="#">Extension Node TLV.....</a>	<a href="#">6</a>
<a href="#">2.2.</a>	<a href="#">Extension Link TLV.....</a>	<a href="#">6</a>
<a href="#">2.3.</a>	<a href="#">Extension Dynamic Link TLV.....</a>	<a href="#">6</a>
<a href="#">3.</a>	<a href="#">Encoding.....</a>	<a href="#">6</a>

<a href="#">3.1. Link Set Field.....</a>	<a href="#">6</a>
<a href="#">3.2. Label Set Field.....</a>	<a href="#">8</a>
<a href="#">3.2.1. Inclusive/Exclusive Label Lists.....</a>	<a href="#">9</a>

---

Internet-Draft    General Network Element Constraint Encoding    June 2010

<a href="#">3.2.2. Inclusive/Exclusive Label Ranges.....</a>	<a href="#">10</a>
<a href="#">3.2.3. Bitmap Label Set.....</a>	<a href="#">10</a>
<a href="#">3.3. Available Labels Sub-TLV.....</a>	<a href="#">11</a>
<a href="#">3.4. Shared Backup Labels Sub-TLV.....</a>	<a href="#">12</a>
<a href="#">3.5. Connectivity Matrix Sub-TLV.....</a>	<a href="#">12</a>
<a href="#">3.6. Port Label Restriction sub-TLV.....</a>	<a href="#">13</a>
<a href="#">3.6.1. SIMPLE_LABEL.....</a>	<a href="#">14</a>
<a href="#">3.6.2. CHANNEL_COUNT.....</a>	<a href="#">15</a>
<a href="#">3.6.3. LABEL_RANGE1.....</a>	<a href="#">15</a>
<a href="#">3.6.4. SIMPLE_LABEL &amp; CHANNEL_COUNT.....</a>	<a href="#">15</a>
<a href="#">4. Security Considerations.....</a>	<a href="#">16</a>
<a href="#">5. IANA Considerations.....</a>	<a href="#">16</a>
<a href="#">6. Acknowledgments.....</a>	<a href="#">16</a>
<a href="#">APPENDIX A: Encoding Examples.....</a>	<a href="#">17</a>
<a href="#">A.1. Link Set Field.....</a>	<a href="#">17</a>
<a href="#">A.2. Label Set Field.....</a>	<a href="#">17</a>
<a href="#">A.3. Connectivity Matrix Sub-TLV.....</a>	<a href="#">18</a>
<a href="#">A.4. Connectivity Matrix with Bi-directional Symmetry.....</a>	<a href="#">21</a>
<a href="#">7. References.....</a>	<a href="#">24</a>
<a href="#">7.1. Normative References.....</a>	<a href="#">24</a>
<a href="#">7.2. Informative References.....</a>	<a href="#">24</a>
<a href="#">8. Contributors.....</a>	<a href="#">26</a>
<a href="#">Authors' Addresses.....</a>	<a href="#">26</a>
<a href="#">Intellectual Property Statement.....</a>	<a href="#">27</a>
<a href="#">Disclaimer of Validity.....</a>	<a href="#">28</a>

## 1. Introduction

Some data plane technologies that wish to make use of a GMPLS control plane contain additional constraints on switching capability and label assignment. In addition, some of these technologies must perform non-local label assignment based on the nature of the technology, e.g., wavelength continuity constraint in WSON [WSON-Frame]. Such constraints can lead to the requirement for link by link label availability in path computation and label assignment.

This document provides efficient encodings of information needed by the routing and label assignment process in technologies such as WSON

and are potentially applicable to a wider range of technologies. Such encodings can be used to extend GMPLS signaling and routing protocols. In addition these encodings could be used by other mechanisms to convey this same information to a path computation element (PCE).

### 1.1. Node Switching Asymmetry Constraints

For some network elements the ability of a signal or packet on a particular ingress port to reach a particular egress port may be limited. In addition, in some network elements the connectivity between some ingress ports and egress ports may be fixed, e.g., a simple multiplexer. To take into account such constraints during path computation we model this aspect of a network element via a connectivity matrix.

The connectivity matrix (ConnectivityMatrix) represents either the potential connectivity matrix for asymmetric switches or fixed connectivity for an asymmetric device such as a multiplexer. Note that this matrix does not represent any particular internal blocking behavior but indicates which ingress ports and labels (e.g., wavelengths) could possibly be connected to a particular output port. Representing internal state dependent blocking for a node is beyond the scope of this document and due to its highly implementation dependent nature would most likely not be subject to standardization in the future. The connectivity matrix is a conceptual M by N matrix representing the potential switched or fixed connectivity, where M represents the number of ingress ports and N the number of egress ports.

ConnectivityMatrix(i, j) ::= <MatrixID> <ConnType> <Matrix>

Where

<MatrixID> is a unique identifier for the matrix.

<ConnType> can be either 0 or 1 depending upon whether the connectivity is either fixed or potentially switched.

<Matrix> represents the fixed or switched connectivity in that  $\text{Matrix}(i, j) = 0$  or  $1$  depending on whether ingress port  $i$  can connect to egress port  $j$  for one or more labels.

## [1.2](#). Non-Local Label Assignment Constraints

If the nature of the equipment involved in a network results in a requirement for non-local label assignment we can have constraints based on limits imposed by the ports themselves and those that are implied by the current label usage. Note that constraints such as these only become important when label assignment has a non-local

character. For example in MPLS an LSR may have a limited range of labels available for use on an egress port and a set of labels already in use on that port and hence unavailable for use. This information, however, does not need to be shared unless there is some limitation on the LSR's label swapping ability. For example if a TDM node lacks the ability to perform time-slot interchange or a WSON lacks the ability to perform wavelength conversion then the label assignment process is not local to a single node and it may be advantageous to share the label assignment constraint information for use in path computation.

Port label restrictions (PortLabelRestriction) model the label restrictions that the network element (node) and link may impose on a port. These restrictions tell us what labels may or may not be used on a link and are intended to be relatively static. More dynamic information is contained in the information on available labels. Port label restrictions are specified relative to the port in general or to a specific connectivity matrix for increased modeling flexibility. Reference [[Switch](#)] gives an example where both switch and fixed connectivity matrices are used and both types of constraints occur on the same port.

```
<PortLabelRestriction> ::= [<GeneralPortRestrictions>...]  
[<MatrixSpecificRestrictions>...]
```

```
<GeneralPortRestrictions> ::= <RestrictionType>  
[<RestrictionParameters>]
```

`<MatrixSpecificRestriction> ::= <MatrixID> <RestrictionType>  
[<RestrictionParameters>]`

Where

MatrixID is the ID of the corresponding connectivity matrix

The RestrictionType parameter is used to specify general port restrictions and matrix specific restrictions.

## 2. Extension Encoding Usage Recommendations

In this section we give recommendations of typical usage of the sub-TLVs and composite TLVs.

### [2.1.](#) Extension Node TLV

The Extension Node TLV could consist of the following list of sub-TLVs:

`<Node_Info> ::= <Node_ID> [Other GMPLS sub-TLVs]  
[<ConnectivityMatrix>...]`

### [2.2.](#) Extension Link TLV

The new link related sub-TLVs could be incorporated into a composite link TLV as follows:

`<LinkInfo> ::= <LinkID> [Other GMPLS sub-TLVs]  
[<PortLabelRestriction>...][<AvailableLabels>] [<SharedBackupLabels>]`

### [2.3.](#) Extension Dynamic Link TLV

If the protocol supports the separation of dynamic information from relatively static information then the available wavelength and shared backup status can be separated from the general link TLV into a TLV for dynamic link information.

```
<DynamicLinkInfo> ::= <LinkID> <AvailableLabels>
[<SharedBackupLabels>]
```

### 3. Encoding

A type-length-value (TLV) encoding of the general connectivity and label restrictions and availability extensions is given in this section. This encoding is designed to be suitable for use in the GMPLS routing protocols OSPF [[RFC4203](#)] and IS-IS [[RFC5307](#)] and in the PCE protocol PCEP [[PCEP](#)]. Note that the information distributed in [[RFC4203](#)] and [[RFC5307](#)] is arranged via the nesting of sub-TLVs within TLVs and this document makes use of such constructs. First, however we define two general purpose fields that will be used repeatedly in the subsequent TLVs.

#### [3.1.](#) Link Set Field

We will frequently need to describe properties of groups of links. To do so efficiently we can make use of a link set concept similar to the label set concept of [[RFC3471](#)]. This Link Set Field is used in

the <ConnectivityMatrix> sub-TLV, which is defined in [Section 6.3](#). The information carried in a Link Set is defined by:

0								1								2								3								
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	
Action								Dir	Format								Length															
Link Identifier 1																																
:																:																:
:																:																:
Link Identifier N																																

Action: 8 bits

## 0 - Inclusive List

Indicates that one or more link identifiers are included in the Link Set. Each identifies a separate link that is part of the set.

## 1 - Inclusive Range

Indicates that the Link Set defines a range of links. It contains two link identifiers. The first identifier indicates the start of the range (inclusive). The second identifier indicates the end of the range (inclusive). All links with numeric values between the bounds are considered to be part of the set. A value of zero in either position indicates that there is no bound on the corresponding portion of the range. Note that the Action field can be set to 0x02(Inclusive Range) only when unnumbered link identifier is used.

Dir: Directionality of the Link Set (2 bits)

0 -- bidirectional

1 -- ingress

2 -- egress

For example in optical networks we think in terms of unidirectional as well as bidirectional links. For example, label restrictions or connectivity may be different for an ingress port, than for its

"companion" egress port if one exists. Note that "interfaces" such as those discussed in the Interfaces MIB [[RFC2863](#)] are assumed to be bidirectional. This also applies to the links advertised in various link state routing protocols.

Format: The format of the link identifier (6 bits)

0 -- Link Local Identifier

Indicates that the links in the Link Set are identified by link local identifiers. All link local identifiers are supplied in the context of the advertising node.

1 -- Local Interface IPv4 Address



Indicates that the links in the Link Set are identified by Local Interface IP Address. All Local Interface IP Address are supplied in the context of the advertising node.

Others TBD.

Note that all link identifiers in the same list must be of the same type.

Length: 16 bits

This field indicates the total length in bytes of the Link Set field.


Link Identifier: length is dependent on the link format


The link identifier represents the port which is being described either for connectivity or label restrictions. This can be the link local identifier of [RFC4202], GMPLS routing, [RFC4203] GMPLS OSPF routing, and [RFC5307] IS-IS GMPLS routing. The use of the link local identifier format can result in more compact encodings when the assignments are done in a reasonable fashion.

### 3.2. Label Set Field

Label Set Field is used within the <AvailableLabels> sub-TLV or the <SharedBackupLabels> sub-TLV, which is defined in [Section 6.1](#) and 6.2, respectively.

The general format for a label set is given below. This format uses the Action concept from [\[RFC3471\]](#) with an additional Action to define a "bit map" type of label set. The second 32 bit field is a base label used as a starting point in many of the specific formats.





Action:


- 0 - Inclusive List
- 1 - Exclusive List
- 2 - Inclusive Range
- 3 - Exclusive Range
- 4 - Bitmap Set

Num Labels is only meaningful for Action value of 4 (Bitmap Set). It indicates the number of labels represented by the bit map. See more detail in [section 3.2.3](#).

Length is the length in bytes of the entire field.

### 3.2.1. Inclusive/Exclusive Label Lists

In the case of the inclusive/exclusive lists the wavelength set format is given by:



```

+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Base Label                                     |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
:                                                                                       :
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Last Label                                    |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Where:

Num Labels is not used in this particular format since the Length parameter is sufficient to determine the number of labels in the list.

### 3.2.2. Inclusive/Exclusive Label Ranges

In the case of inclusive/exclusive ranges the label set format is given by:

```

      0               1               2               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|2 or 3 | Num Labels(not used) |                               Length          |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Start Label                                    |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     End Label                                     |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Note that the start and end label must in some sense "compatible" in the technology being used.

### 3.2.3. Bitmap Label Set

In the case of Action = 4, the bitmap the label set format is given by:



### 3.4. Shared Backup Labels Sub-TLV

To indicate the labels available for shared backup use on a link the Shared Backup Labels sub-TLV consists of a single variable length label set field as follows:

[illegible]

### 3.5. Connectivity Matrix Sub-TLV

Connectivity Matrix represents how ingress ports are connected to egress ports for network elements.

The switch and fixed connectivity matrices of [WSON-Info] can be compactly represented in terms of a minimal list of ingress and egress port set pairs that have mutual connectivity. As described in [Switch] such a minimal list representation leads naturally to a graph representation for path computation purposes that involves the fewest additional nodes and links.

A TLV encoding of this list of link set pairs is:

[illegible]

---

Internet-Draft   General Network Element Constraint Encoding   June 2010

Where

Connectivity is the device type.

0 -- the device is fixed

1 -- the device is switched(e.g., ROADM/OXC)

MatrixID represents the ID of the connectivity matrix and is an 8 bit integer. The value of 0xFF is reserved for use with port wavelength constraints and should not be used to identify a connectivity matrix.

Link Set A #1 and Link Set B #1 together represent a pair of link sets. There are two permitted combinations for the link set field parameter "dir" for Link Set A and B pairs:

- o Link Set A dir=ingress, Link Set B dir=egress

The meaning of the pair of link sets A and B in this case is that any signal that ingresses a link in set A can be potentially switched out of an egress link in set B.

- o Link Set A dir=bidirectional, Link Set B dir=bidirectional

The meaning of the pair of link sets A and B in this case is that any signal that ingresses on the links in set A can potentially egress on a link in set B, and any ingress signal on the links in set B can potentially egress on a link in set A.

See [Appendix A](#) for both types of encodings as applied to a ROADM example.

### [3.6](#). Port Label Restriction sub-TLV

Port Label Restriction tells us what labels may or may not be used on a link.

The port label restriction of [\[WSO-Info\]](#) can be encoded as a sub-TLV as follows. More than one of these sub-TLVs may be needed to fully specify a complex port constraint. When more than one of these sub-

TLVs are present the resulting restriction is the intersection of the restrictions expressed in each sub-TLV. To indicate that a restriction applies to the port in general and not to a specific connectivity matrix use the reserved value of 0xFF for the MatrixID.

```

      0                               1                               2                               3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|  MatrixID    | RestrictionType |      Reserved/Parameter      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Additional Restriction Parameters per RestrictionType |
:                                                         :
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Where:


MatrixID: either is the value in the corresponding Connectivity Matrix sub-TLV or takes the value 0xFF to indicate the restriction applies to the port regardless of any Connectivity Matrix.

RestrictionType can take the following values and meanings:

- 0: SIMPLE\_LABEL (Simple label selective restriction)
- 1: CHANNEL\_COUNT (Channel count restriction)
- 2: LABEL\_RANGE1 (Label range device with a movable center label and width)
- 3: SIMPLE\_LABEL & CHANNEL\_COUNT (Combination of SIMPLE\_LABEL and CHANNEL\_COUNT restriction. The accompanying label set and channel count indicate labels permitted on the port and the maximum number of channels that can be simultaneously used on the port)

### 3.6.1. SIMPLE\_LABEL


In the case of the SIMPLE\_LABEL the GeneralPortRestrictions (or MatrixSpecificRestrictions) format is given by:



In this case the accompanying label set indicates the labels permitted on the port.

### 3.6.2. CHANNEL\_COUNT


In the case of the CHANNEL\_COUNT the format is given by:



In this case the accompanying MaxNumChannels indicates the maximum number of channels (labels) that can be simultaneously used on the port/matrix.

### 3.6.3. LABEL\_RANGE1

In the case of the LABEL\_RANGE1 the GeneralPortRestrictions (or MatrixSpecificRestrictions) format is given by:







TBD. Once our approach is finalized we may need identifiers for the various TLVs and sub-TLVs.

## 6. Acknowledgments

This document was prepared using 2-Word-v2.0.template.dot.

## APPENDIX A: Encoding Examples

Here we give examples of the general encoding extensions applied to some simple ROADM network elements and links.

### [A.1.](#) Link Set Field

Suppose that we wish to describe a set of ingress ports that are have link local identifiers number 3 through 42. In the link set field we set the Action = 1 to denote an inclusive range; the Dir = 1 to denote ingress links; and, the Format = 0 to denote link local identifiers. In particular we have:

```
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|  Action=1      |0 1|0 0 0 0 0 0|                                Length = 12      |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|                                Link Local Identifier = #3          |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|                                Link Local Identifier = #42         |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
```

## A.2. Label Set Field

Example:

A 40 channel C-Band DWDM system with 100GHz spacing with lowest frequency 192.0THz (1561.4nm) and highest frequency 195.9THz (1530.3nm). These frequencies correspond to  $n = -11$ , and  $n = 28$  respectively. Now suppose the following channels are available:

Frequency (THz)	n Value	bit map position
192.0	-11	0
192.5	-6	5
193.1	0	11
193.9	8	19
194.0	9	20
195.2	21	32
195.8	27	38

With the Grid value set to indicate an ITU-T G.694.1 DWDM grid, C.S. set to indicate 100GHz this lambda bit map set would then be encoded as follows:

```

0                               1                               2                               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| 4 | Num Wavelengths = 40 | Length = 16 bytes |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|Grid| C.S. | Reserved | n for lowest frequency = -11 |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|1 0 0 0 0 1 0 0 0 0 0 1 0 0 0 0 0 0 0 1 1 0 0 0 0 0 0 0 0 0 0|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|1 0 0 0 0 0 1 0| Not used in 40 Channel system (all zeros) |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
```

To encode this same set as an inclusive list we would have:

```

0                               1                               2                               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
```

```


+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| 0      | Num Wavelengths = 40 |      Length = 20 bytes      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|Grid |  C.S. |      Reserved  | n  for lowest frequency = -11 |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|Grid |  C.S. |      Reserved  | n  for lowest frequency = -6  |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|Grid |  C.S. |      Reserved  | n  for lowest frequency = -0  |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|Grid |  C.S. |      Reserved  | n  for lowest frequency = 8   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|Grid |  C.S. |      Reserved  | n  for lowest frequency = 9   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|Grid |  C.S. |      Reserved  | n  for lowest frequency = 21  |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|Grid |  C.S. |      Reserved  | n  for lowest frequency = 27  |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+


```

[A.3.](#) Connectivity Matrix Sub-TLV

Example:

Suppose we have a typical 2-degree 40 channel ROADM. In addition to its two line side ports it has 80 add and 80 drop ports. The picture below illustrates how a typical 2-degree ROADM system that works with bi-directional fiber pairs is a highly asymmetrical system composed of two unidirectional ROADM subsystems.





Referring to the figure we see that the ingress direction of ports #3-#42 (add ports) can only connect to the egress on port #1. While the ingress side of port #2 (line side) can only connect to the egress on ports #3-#42 (drop) and to the egress on port #1 (pass through). Similarly, the ingress direction of ports #43-#82 can only connect to the egress on port #2 (line). While the ingress direction of port #1 can only connect to the egress on ports #43-#82 (drop) or port #2 (pass through). We can now represent this potential connectivity matrix as follows. This representation uses only 30 32-bit words.

0	1	2	3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1			
+	+	+	+
	Conn = 1		MatrixID
+	+	+	+
	Reserved		1
+	+	+	+

```

Note: adds to line
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=1      |0 1|0 0 0 0 0 0|          Length = 12          |2
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|               Link Local Identifier = #3              |3
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|               Link Local Identifier = #42             |4
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=0      |1 0|0 0 0 0 0 0|          Length = 8          |5
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|               Link Local Identifier = #1              |6
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
Note: line to drops
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=0      |0 1|0 0 0 0 0 0|          Length = 8          |7
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|               Link Local Identifier = #2              |8
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=1      |1 0|0 0 0 0 0 0|          Length = 12          |9
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|               Link Local Identifier = #3              |10
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|               Link Local Identifier = #42             |11
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
Note: line to line
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=0      |0 1|0 0 0 0 0 0|          Length = 8          |12
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|               Link Local Identifier = #2              |13
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=0      |1 0|0 0 0 0 0 0|          Length = 8          |14
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|               Link Local Identifier = #1              |15
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
Note: adds to line
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=1      |0 1|0 0 0 0 0 0|          Length = 12          |16
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|               Link Local Identifier = #43             |17
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```


```

+-----+
| Action=0      |1 0|0 0 0 0 0 0|          Length = 8          |19
+-----+
|                               Link Local Identifier = #2          |20
+-----+
                        Note: line to drops
+-----+
| Action=0      |0 1|0 0 0 0 0 0||          Length = 8          |21
+-----+
|                               Link Local Identifier = #1          |22
+-----+
| Action=1      |1 0|0 0 0 0 0 0|          Length = 12         |23
+-----+
|                               Link Local Identifier = #43         |24
+-----+
|                               Link Local Identifier = #82         |25
+-----+
                        Note: line to line
+-----+
| Action=0      |0 1|0 0 0 0 0 0|          Length = 8          |26
+-----+
|                               Link Local Identifier = #1          |27
+-----+
| Action=0      |1 0|0 0 0 0 0 0|          Length = 8          |28
+-----+
|                               Link Local Identifier = #2          |30
+-----+

```

#### [A.4.](#) Connectivity Matrix with Bi-directional Symmetry

If one has the ability to renumber the ports of the previous example as shown in the next figure then we can take advantage of the bi-directional symmetry and use bi-directional encoding of the connectivity matrix. Note that we set dir=bidirectional in the link set fields.





## Internet-Draft General Network Element Constraint Encoding June 2010

```

      0          1          2          3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Conn = 1   |   MatrixID   |   Reserved   |1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
                        Add/Drops #3-42 to Line side #1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=1      |0 0|0 0 0 0 0 0|           Length = 12      |2
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Link Local Identifier = #3   |3
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Link Local Identifier = #42  |4
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=0      |0 0|0 0 0 0 0 0|           Length = 8       |5
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Link Local Identifier = #1   |6
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
                        Note: line #2 to add/drops #43-82
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=0      |0 0|0 0 0 0 0 0|           Length = 8       |7
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Link Local Identifier = #2   |8
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=1      |0 0|0 0 0 0 0 0|           Length = 12      |9
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Link Local Identifier = #43   |10
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Link Local Identifier = #82   |11
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
                        Note: line to line
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=0      |0 0|0 0 0 0 0 0|           Length = 8       |12
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Link Local Identifier = #1   |13
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Action=0      |0 0|0 0 0 0 0 0|           Length = 8       |14
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Link Local Identifier = #2   |15
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

---

Internet-Draft   General Network Element Constraint Encoding   June 2010

## 7. References

### 7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), June 2000.
- [RFC3471] Berger, L., "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description", [RFC 3471](#), January 2003.
- [G.694.1] ITU-T Recommendation G.694.1, "Spectral grids for WDM applications: DWDM frequency grid", June, 2002.
- [RFC4202] Kompella, K., Ed., and Y. Rekhter, Ed., "Routing Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", [RFC 4202](#), October 2005
- [RFC4203] Kompella, K., Ed., and Y. Rekhter, Ed., "OSPF Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", [RFC 4203](#), October 2005.

### 7.2. Informative References

- [G.694.1] ITU-T Recommendation G.694.1, Spectral grids for WDM applications: DWDM frequency grid, June 2002.
- [G.694.2] ITU-T Recommendation G.694.2, Spectral grids for WDM applications: CWDM wavelength grid, December 2003.

[Otani] T. Otani, H. Guo, K. Miyazaki, D. Caviglia, "Generalized Labels for G.694 Lambda-Switching Capable Label Switching Routers", work in progress: [draft-ietf-ccamp-gmpls-g-694-lambda-labels](#).

[RFC5307] Kompella, K., Ed., and Y. Rekhter, Ed., "IS-IS Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", [RFC 5307](#), October 2008.

[Switch] G. Bernstein, Y. Lee, A. Gavler, J. Martensson, " Modeling WDM Wavelength Switching Systems for Use in GMPLS and Automated Path Computation", Journal of Optical Communications and Networking, vol. 1, June, 2009, pp. 187-195.

[WSO-Frame] Y. Lee, G. Bernstein, W. Imajuku, "Framework for GMPLS and PCE Control of Wavelength Switched Optical Networks", work in progress: [draft-ietf-ccamp-wavelength-switched-framework](#), February, 2010.

[WSO-Info] Y. Lee, G. Bernstein, D. Li, W. Imajuku, "Routing and Wavelength Assignment Information Model for Wavelength Switched Optical Networks", work in progress: [draft-ietf-ccamp-rwa-info](#), February, 2010.

[WSO-Encode] G. Bernstein, Y. Lee, D. Li, W. Imajuku, "Routing and Wavelength Assignment Information Encoding for Wavelength Switched Optical Networks", work in progress: [draft-ietf-ccamp-rwa-wson-encode](#), February, 2010.

[PCEP] Vasseur, JP., Ed. and JL. Le Roux, Ed., "Path Computation Element (PCE) communication Protocol (PCEP) - Version 1", [RFC5440](#).

Internet-Draft   General Network Element Constraint Encoding   June 2010

## 8. Contributors

Diego Caviglia  
Ericsson  
Via A. Negrone 1/A 16153  
Genoa Italy

Phone: +39 010 600 3736  
Email: [diego.caviglia@marconi.com](mailto:diego.caviglia@marconi.com), [ericsson.com](mailto:ericsson.com))

Anders Gavler  
Acreo AB  
Electrum 236  
SE - 164 40 Kista Sweden

Email: [Anders.Gavler@acreo.se](mailto:Anders.Gavler@acreo.se)

Jonas Martensson  
Acreo AB  
Electrum 236  
SE - 164 40 Kista, Sweden

Email: [Jonas.Martensson@acreo.se](mailto:Jonas.Martensson@acreo.se)

Itaru Nishioka  
NEC Corp.  
1753 Simonumabe, Nakahara-ku, Kawasaki, Kanagawa 211-8666

Japan

Phone: +81 44 396 3287

Email: i-nishioka@cb.jp.nec.com

#### Authors' Addresses

Greg M. Bernstein (ed.)

Grotto Networking

Fremont California, USA

Phone: (510) 573-2237

Email: gregb@grotto-networking.com

Bernstein and Lee

Expires December 9, 2010

[Page 26]

---

Internet-Draft   General Network Element Constraint Encoding   June 2010

Young Lee (ed.)

Huawei Technologies

1700 Alma Drive, Suite 100

Plano, TX 75075

USA

Phone: (972) 509-5599 (x2240)

Email: ylee@huawei.com

Dan Li

Huawei Technologies Co., Ltd.

F3-5-B R&D Center, Huawei Base,

Bantian, Longgang District

Shenzhen 518129 P.R.China

Phone: +86-755-28973237

Email: danli@huawei.com

Wataru Imajuku

NTT Network Innovation Labs

1-1 Hikari-no-oka, Yokosuka, Kanagawa

Japan

Phone: +81-(46) 859-4315

Email: imajuku.wataru@lab.ntt.co.jp

Jianrui Han

Huawei Technologies Co., Ltd.

F3-5-B R&D Center, Huawei Base,

Bantian, Longgang District

Shenzhen 518129 P.R.China

Phone: +86-755-28972916

Email: hanjianrui@huawei.com

## Intellectual Property Statement

The IETF Trust takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in any IETF Document or the extent to which any license under such rights might or might not be available; nor does it

Bernstein and Lee

Expires December 9, 2010

[Page 27]

---

Internet-Draft   General Network Element Constraint Encoding   June 2010

represent that it has made any independent effort to identify any such rights.

Copies of Intellectual Property disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement any standard or specification contained in an IETF Document. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

Disclaimer of Validity

All IETF Documents and the information contained therein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION THEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

#### Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.