

CCAMP Working Group  
Internet Draft  
Category: Informational

Expiration Date: May 2004

Wesam Alanqar (Sprint)  
Deborah Brungard (ATT)  
Dave Meyer (1-4-5 Net)  
Lyndon Ong (Ciena)  
Dimitri Papadimitriou (Alcatel)  
Jonathan Sadler (Tellabs)  
Stephen Shew (Nortel)

December 2003

**Requirements for Generalized MPLS (GMPLS) Routing  
for Automatically Switched Optical Network (ASON)**

[draft-ietf-ccamp-gmpls-ason-routing-reqts-00.txt](#)

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC-2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts. Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Abstract

The Generalized MPLS (GMPLS) suite of protocols has been defined to control different switching technologies as well as different applications. These include support for requesting TDM connections including SONET/SDH and Optical Transport Networks (OTNs).

This document concentrates on the routing requirements on the GMPLS suite of protocols to support the capabilities and functionalities of an Automatically Switched Optical Network (ASON).

\*\*\* This draft is in an early stage and propose only a template to

be further developed \*\*\*

## **1. Contributors**

This document is the result of the CCAMP Working Group ASON Routing Requirements design team joint effort.

## **2. Conventions used in this document**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC-2119](#).

The reader is also assumed to be familiar with the terminology used in [\[G.8080\]](#) and [\[G.7715\]](#).

## **3. Introduction**

The GMPLS suite of protocol provides support for controlling different switching technologies as well as different applications. These include support for requesting TDM connections including SONET/SDH (see ANSI T1.105 and ITU-T G.707, respectively) as well as Optical Transport Networks (see ITU-T G.709). However, there are certain capabilities that are needed to support Automatically Switched Optical Networks (ASON) control planes. Therefore, it is desirable to understand the corresponding requirements for the GMPLS protocol suite. ASON control plane architecture is defined in [\[G.8080\]](#) and ASON routing requirements are identified in [\[G.7715\]](#). Also, the SG15/Q.14 is working on refining these requirements.

This document focuses on the routing requirements for the GMPLS suite of protocols to support the capabilities and functionalities of ASON control planes. It discusses the requirements for GMPLS routing that MAY subsequently lead to additional backward compatible extensions to support the capabilities specified in the above referenced document. A description of backward compatibility considerations is provided in [Section 5](#). Nonetheless, any protocol (in particular, routing) design or suggested protocol extensions is strictly outside the scope of this document. A terminology section (that may be further completed) is provided in the Appendix.

The ASON model distinguishes reference points (representing points of protocol information exchange) defined (1) between an administrative domain and a user a.k.a. user-network interface (UNI), (2) between (and when needed within) administrative domains a.k.a. external network-network interface (E-NNI) and, (3) between

areas of the same administrative domain and when needed between control components (or simply controllers) within areas a.k.a. internal network-network interface (I-NNI).

The ASON routing architectural model is based on the following assumptions:

- The information exchanged between routing controllers is subject

W.Alanqar et al. - Expires May 2004

2

[draft-ietf-ccamp-gmpls-ason-routing-reqts-00.txt](#)

December 2003

to policy constraints imposed at reference points (E-NNI and I-NNI)

- The routing information exchanged between routing domains (i.e. inter-domain) is independent of intra-domain routing protocol
- The routing information exchanged between routing domains is independent of intra-domain control distribution choices, e.g. centralized, fully distributed
- The routing adjacency topology and transport network topology shall not be assumed to be congruent
- Each routing area shall be uniquely identifiable within a carrier's network (constituted by several routing domains)

The following functionality is to be supported by GMPLS routing to instantiate ASON routing realization:

- support multiple hierarchical levels
- support hierarchical routing information dissemination including summarized routing information
- support for multiple links between nodes (and allow for link and node diversity)
- support architectural evolution in terms of the number of levels of hierarchies, aggregation and segmentation of (control ?) domains
- support routing information divided between attributes pertaining to links and nodes (representing either a routing area or sub-network)

In addition the behaviour of GMPLS routing is expected to be such that:

- it is scalable with respect to the number of links, nodes and routing area hierarchical levels. - what does this means ? is it routing areas and hierarchical levels ? or hierarchical levels of routing areas -
- in response to a routing event (e.g. topology update, reachability

- update), it delivers convergence and damping against flapping
- it fulfils the operational security objectives where required

#### **4. ASON Requirements for GMPLS Routing**

The next sections detail the requirements for GMPLS routing to support the following ASON routing functions:

- supporting multiple hierarchical levels
- support hierarchical routing information dissemination including summarized routing information
- support for multiple links between nodes (and allow for link and node diversity)
- support architectural evolution in terms of the number of levels of hierarchies, aggregation and segmentation of (control ?) domains

W.Alanqar et al. - Expires May 2004

3

[draft-ietf-ccamp-gmpls-ason-routing-reqts-00.txt](#)

December 2003

- support of routing attributes for links and nodes

##### **4.1 Multiple Hierarchical Levels**

TBD.

##### **4.2 Hierarchical Routing Information Dissemination**

TBD.

##### **4.3 Multiple Links between Nodes**

TBD.

##### **4.4 Evolution**

TBD.

##### **4.5 Routing Attributes**

TBD.

###### **4.5.1 Link Attributes**

TBD.

###### **4.5.2 Node Attributes**

TBD.

#### **5. Backward Compatibility**

TBD.

## **6. Security Considerations**

TBD.

## **7. Acknowledgements**

The authors would like to thank Kireeti Kompella for having initiated the proposal of an ASON Routing Requirement Design Team.

## **8. References**

- [RFC 2026] S.Bradner, "The Internet Standards Process -- Revision 3", [BCP 9](#), [RFC 2026](#), October 1996.
- [RFC 2119] S.Bradner, "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [G.7715] ITU-T Rec. G.7715/Y.1306, "Architecture and

W.Alanqar et al. - Expires May 2004

4

[draft-ietf-ccamp-gmpls-ason-routing-reqts-00.txt](#)

December 2003

Requirements for the Automatically Switched Optical Network (ASON)," June 2002.

- [G.8080] ITU-T Rec. G.8080/Y.1304, "Architecture for the Automatically Switched Optical Network (ASON)," November 2001 (and Revision, January 2003).

## **9. Author's Addresses**

Wesam Alanqar  
Sprint - Technology Research and Development  
EMail: wesam.alanqar@mail.sprint.com

Deborah Brungard (AT&T)  
Rm. D1-3C22 - 200 S. Laurel Ave.  
Middletown, NJ 07748, USA  
Phone: +1 732 4201573  
EMail: dbrungard@att.com

David Meyer  
EMail: dmm@1-4-5.net

Lyndon Ong (Ciena Corporation)  
5965 Silver Creek Valley Rd

San Jose, CA 95128, USA  
Tel: +1 408 8347894  
EMail: lyong@ciena.com

Dimitri Papadimitriou (Alcatel)  
Francis Wellensplein 1,  
B-2018 Antwerpen, Belgium  
Phone : +32 3 2408491  
EMail: dimitri.papadimitriou@alcatel.be

Jonathan Sadler  
1415 W. Diehl Rd  
Naperville, IL 60563  
EMail: jonathan.sadler@tellabs.com

Stephen Shew (Nortel Networks)  
PO Box 3511 Station C  
Ottawa, Ontario, CANADA K1Y 4H7  
Tel: +1 613 7632462  
EMail: sdsheew@nortelnetworks.com

W.Alanqar et al. - Expires May 2004

5

[draft-ietf-ccamp-gmpls-ason-routing-reqts-00.txt](#)

December 2003

## Appendix - Terminology

This document makes use of the following terms:

Administrative domain: See Recommendation G.805.

Control plane: performs the call control and connection control functions. Through signaling, the control plane sets up and releases connections, and may restore a connection in case of a failure.

(Control) Domain: represents a collection of entities that are grouped for a particular purpose. G.8080 applies this G.805 recommendation concept (that defines two particular forms, the administrative domain and the management domain) to the control plane in the form of a control domain. The entities that are grouped in a control domain are components of the control plane.

External NNI (E-NNI): interfaces are located between protocol

controllers between control domains.

Internal NNI (I-NNI): interfaces are located between protocol controllers within control domains.

Link: See Recommendation G.805.

Management plane: performs management functions for the Transport Plane, the control plane and the system as a whole. It also provides coordination between all the planes. The following management functional areas are performed in the management plane: performance, fault, configuration, accounting and security management

Management domain: See Recommendation G.805.

Transport plane: provides bi-directional or unidirectional transfer of user information, from one location to another. It can also provide transfer of some control and network management information. The Transport Plane is layered; it is equivalent to the Transport Network defined in G.805.

User Network Interface (UNI): interfaces are located between protocol controllers between a user and a control domain.

#### Full Copyright Statement

"Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other

Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.